



PUBLIC

SQL Anywhere

Document Version: 17.01.0 – 2021-10-15

SQL Anywhere Errors

Content

- 1 SQL Anywhere - Error Messages. 3**
- 1.1 SQL Anywhere Error Messages. 4
 - SQL Anywhere Error Messages Sorted by SQLCODE. 4
 - SQL Anywhere Error Messages Sorted by SQLSTATE. 59
 - SQL Anywhere Error Messages Sorted by Sybase Error Code. 114
 - SQL Anywhere Error Messages Listed by Message Text. 163
- 1.2 SQL Preprocessor Error Messages. 936
 - SQL Preprocessor Error Messages Sorted by Error Code. 936
 - SQL Preprocessor Error Messages Listed by Message Text. 938
- 1.3 MobiLink Server Error Messages. 967
 - MobiLink Server Error Messages Sorted by Error Code. 968
 - MobiLink Server Error Messages Listed by Message Text. 982
- 1.4 MobiLink Server Warning Messages. 1137
 - MobiLink Server Warning Messages Sorted by Error Code. 1137
 - MobiLink Server Warning Messages Listed by Message Text. 1142
- 1.5 MobiLink Communication Error Messages. 1184
 - MobiLink Communication Error Messages Sorted by Error Code. 1185
 - MobiLink Communication Error Messages Listed by Message Text. 1191
- 1.6 MobiLink Replay Utility Error Messages. 1278
 - MobiLink Replay Utility Error Messages Sorted by Error Code. 1279
 - MobiLink Replay Utility Error Messages Listed by Message Text. 1282
- 1.7 MobiLink Replay Utility Warning Messages. 1307
 - MobiLink Replay Utility Warning Messages Sorted by Error Code. 1307
 - MobiLink Replay Utility Warning Messages Listed by Message Text. 1308
- 1.8 Relay Server Error Messages. 1315
 - Relay Server Error Messages Sorted by Error Code. 1316
 - Relay Server Error Messages Listed by Message Text. 1323
- 1.9 Relay Server Warning Messages. 1387
 - Relay Server Warning Messages Sorted by Error Code. 1388
 - Relay Server warning messages listed by message text. 1388
- 1.10 Outbound Enabler Error Messages. 1392
 - Outbound Enabler Error Messages Sorted by Error Code. 1393
 - Outbound Enabler Error Messages Listed by Message Text. 1398
- 1.11 Outbound Enabler Warning Messages. 1438
 - Outbound Enabler Warning Messages Sorted by Error Code. 1438
 - Outbound Enabler Warning Messages Listed by Message Text. 1439

1 SQL Anywhere - Error Messages

This book describes a complete listing of SQL Anywhere error messages together with any relevant diagnostic information.

In this section:

[SQL Anywhere Error Messages \[page 4\]](#)

Each error has a numeric error code, called the SQLCODE. Negative codes are errors, and positive codes are warnings. SQLCODE 0 indicates successful completion.

[SQL Preprocessor Error Messages \[page 936\]](#)

The SQL preprocessor generates messages depending on which command-line options are set. Each message may be an error, a warning, or a non-conformance flag, which itself can be an error or a warning.

[MobiLink Server Error Messages \[page 967\]](#)

Each MobiLink server error has a numeric error code: error codes are always negative, warning codes are always positive, and zero means no error or warning.

[MobiLink Server Warning Messages \[page 1137\]](#)

The MobiLink server warning messages are written to the MobiLink server message log. Each error has a numeric error code: both error and warning codes are positive, while warning codes are greater than 10000.

[MobiLink Communication Error Messages \[page 1184\]](#)

The error messages are written to the MobiLink server message log and the MobiLink SQL Anywhere client message log. The error codes are returned to UltraLite clients in the `ss_error_code` member of the `stream_error` parameter.

[MobiLink Replay Utility Error Messages \[page 1278\]](#)

The MobiLink Replay utility error messages are written to the MobiLink Replay utility message log.

[MobiLink Replay Utility Warning Messages \[page 1307\]](#)

The MobiLink Replay utility warning messages are written to the MobiLink Replay utility message log.

[Relay Server Error Messages \[page 1315\]](#)

Each Relay Server error has a numeric error code.

[Relay Server Warning Messages \[page 1387\]](#)

The Relay Server warning messages are written to the Relay Server message log.

[Outbound Enabler Error Messages \[page 1392\]](#)

The Outbound Enabler messages are written to the Outbound Enabler message log.

[Outbound Enabler Warning Messages \[page 1438\]](#)

The Outbound Enabler messages are written to the Outbound Enabler message log.

1.1 SQL Anywhere Error Messages

Each error has a numeric error code, called the SQLCODE. Negative codes are errors, and positive codes are warnings. SQLCODE 0 indicates successful completion.

Many of the error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.

In this section:

[SQL Anywhere Error Messages Sorted by SQLCODE \[page 4\]](#)

[SQL Anywhere Error Messages Sorted by SQLSTATE \[page 59\]](#)

[SQL Anywhere Error Messages Sorted by Sybase Error Code \[page 114\]](#)

[SQL Anywhere Error Messages Listed by Message Text \[page 163\]](#)

1.1.1 SQL Anywhere Error Messages Sorted by SQLCODE

SQL Anywhere SQLCODE	Message text
201	The ICU collation '%1' has defaulted to another collation [page 767]
200	Warning: %1 [page 925]
151	UltraLite performed database recovery on startup [page 859]
150	Database contains no tables to synchronize [page 365]
149	Automatic database upgrade applied [page 247]
148	Event notification queue '%1' not found warning [page 424]
147	Event notifications lost on queue '%1' [page 424]
146	Event notification queue '%1' is full, notification discarded [page 423]
145	Two rows with the same primary key have been downloaded for table '%1' [page 855]
144	Mirror file requires higher checksum_level [page 572]
143	Retrying read of corrupt page (page '%1') [page 652]
142	UltraLite database state was restored [page 859]
140	Encryption has not been enabled [page 402]
139	Option '%1' specified more than once [page 611]
138	Publication predicates were not evaluated [page 637]
137	Row was dropped from table %1 to maintain referential integrity [page 658]

SQL Anywhere SQLCODE	Message text
136	The database was created [page 758]
134	UltraLite cursor (or result set or table) was restored [page 858]
133	UltraLite connection was restored [page 858]
132	Cannot output the histogram for string column '%1' [page 291]
130	A row was dropped because it could not be converted to the new schema format [page 223]
129	Plan may contain virtual indexes [page 625]
127	Character substitution occurred when converting from %1 to %2 [page 314]
125	An invalid multi-byte input character was encountered when converting from %1 to %2 [page 236]
124	Invalid data conversion: NULL was inserted for column '%1' on row %2 [page 498]
122	The result returned is non-deterministic [page 792]
121	Cursor option values changed [page 358]
120	'%1' is an unknown option [page 209]
119	Unable to open backup log '%1' [page 870]
118	Illegal user selectivity estimate specified [page 475]
117	Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead [page 899]
116	Language '%1' is not supported, '%2' will be used [page 552]
115	Database server cannot convert data from/to character set '%1', conversion may not be correct [page 373]
114	Character set conversion to '%1' cannot be performed; '%2' is used instead [page 314]
113	Database option '%1' for user '%2' has an invalid setting [page 370]
112	More information required [page 579]
111	Statement cannot be executed [page 694]
110	Transaction log backup page only partially full [page 848]
109	Null value eliminated in aggregate function [page 599]
107	Language extension detected in syntax near '%1' on line %2 [page 553]
106	Value for column '%1' in table '%2' has changed [page 919]
105	Procedure has completed [page 634]
104	Row has been updated since last time read [page 656]

SQL Anywhere SQLCODE	Message text
103	Invalid data conversion [page 497]
102	Using temporary table [page 916]
101	Value truncated [page 919]
100	Row not found [page 658]
0	(no message text) [page 217]
-72	No database file specified [page 588]
-74	The selected database is currently inactive [page 797]
-75	Request to start/stop database denied [page 646]
-76	Request denied -- no active databases [page 645]
-77	Database name not unique [page 368]
-78	Dynamic memory exhausted during %1 [page 398]
-79	Invalid local database option [page 510]
-80	Unable to start database server [page 875]
-81	Invalid database server command line [page 500]
-82	Unable to start specified database: %1 [page 877]
-83	Specified database not found [page 683]
-84	Specified database is invalid [page 683]
-85	Communication error [page 331]
-86	Not enough memory to start [page 598]
-87	Database name required to start server [page 369]
-88	Client/server communications protocol version mismatch [page 322]
-89	Database server not running in multi-user mode [page 376]
-90	Argument %1 of procedure '%2' cannot be NULL [page 240]
-91	Procedure '%1' terminated with unhandled exception '%2' [page 634]
-92	'%1' is not a valid class file [page 212]
-93	Class '%1' has no public field '%2' [page 317]
-94	Invalid type for field reference [page 538]
-95	Parse error: %1 [page 616]
-96	Database server already running [page 372]
-97	Database page size too big: %1 [page 370]
-98	Authentication violation [page 246]
-99	Connections to database have been disabled [page 338]
-100	Database server not found [page 375]

SQL Anywhere SQLCODE	Message text
-101	Not connected to a database [page 597]
-102	Database server connection limit exceeded [page 374]
-103	Invalid user ID or password [page 542]
-104	Invalid user ID or password on preprocessed module [page 543]
-105	Database cannot be started -- %1 [page 364]
-106	Cannot open transaction log file -- %1 [page 291]
-107	Error writing to transaction log file [page 420]
-108	Connection not found [page 336]
-109	There are still active database connections [page 818]
-110	Item '%1' already exists [page 546]
-111	Index name '%1' not unique [page 481]
-112	Table already has a primary key [page 728]
-113	Column '%1' in foreign key has a different definition than primary key [page 325]
-114	Number of columns defined for the view does not match SELECT statement [page 601]
-116	Table must be empty [page 730]
-118	Table '%1' has no primary key [page 722]
-119	Primary key column '%1' already defined [page 630]
-120	User '%1' already has GRANT OPTION [page 907]
-121	Permission denied: %1 [page 622]
-122	Operation would cause a group cycle [page 609]
-123	User '%1' is not a user group [page 910]
-124	Dropping all columns from table '%1' is not allowed [page 394]
-125	ALTER clause conflict [page 230]
-126	Table cannot have two primary keys [page 728]
-127	Cannot alter a column in an index [page 258]
-128	Cannot drop a user that owns tables in runtime system [page 282]
-130	Invalid statement [page 533]
-131	Syntax error near '%1' %2 %3 [page 717]
-132	SQL statement error [page 687]
-133	Invalid prepared statement type [page 521]
-134	Feature '%1' not implemented [page 451]

SQL Anywhere SQLCODE	Message text
-135	Language extension [page 552]
-136	Table '%1' is in an outer join cycle [page 724]
-137	Table '%1' requires a unique correlation name [page 727]
-138	DbSPACE '%1' not found [page 384]
-139	More than one table is identified as '%1' [page 580]
-140	User ID '%1' does not exist [page 911]
-141	Table '%1' not found [page 726]
-142	Correlation name '%1' not found [page 343]
-143	Column '%1' not found [page 326]
-144	Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name [page 324]
-145	Foreign key name '%1' not found [page 458]
-146	There is no way to join '%1' to '%2' [page 820]
-147	There is more than one way to join '%1' to '%2' [page 819]
-148	Unknown function '%1' [page 895]
-149	Function or column reference to '%1' must also appear in a GROUP BY [page 464]
-150	Invalid use of an aggregate function [page 539]
-151	Subquery allowed only one SELECT list item [page 703]
-152	Invalid ORDER BY specification [page 514]
-153	Select lists in UNION, INTERSECT, or EXCEPT do not match in length [page 664]
-154	Wrong number of parameters to function '%1' [page 929]
-155	Invalid host variable [page 508]
-156	Invalid expression near '%1' [page 505]
-157	Cannot convert %1 to %2 [page 266]
-158	Value %1 out of range for destination [page 918]
-159	Invalid column number [page 495]
-160	Can only describe a SELECT statement [page 255]
-161	Invalid type on DESCRIBE statement [page 539]
-162	Cannot convert %1 to %2. The bad value was supplied for column '%3' on row %4 of the data file [page 266]
-163	Derived table '%1' has no name for column %2 [page 389]
-164	Namespace heap exhausted at internal function: %1 [page 586]
-165	Java VM heap exhausted at internal function: %1 [page 547]

SQL Anywhere SQLCODE	Message text
-170	Cursor has not been declared [page 356]
-171	Error opening cursor [page 412]
-172	Cursor already open [page 356]
-180	Cursor not open [page 358]
-181	No indicator variable provided for NULL result [page 590]
-182	Not enough fields allocated in SQLDA [page 597]
-183	Cannot find index named '%1' [page 285]
-184	Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3 [page 326]
-185	SELECT returns more than one row [page 665]
-186	Subquery cannot return more than one row [page 703]
-187	Illegal cursor operation attempt [page 472]
-188	Not enough values for host variables [page 598]
-189	Unable to find in index '%1' for table '%2' [page 867]
-190	Cannot update an expression [page 304]
-191	Cannot modify column '%1' in table '%2' [page 289]
-192	Update operation attempted on non-updatable query [page 902]
-193	Primary key for table '%1' is not unique: Primary key value ('%2') [page 631]
-194	No primary key value for foreign key '%1' in table '%2' [page 593]
-195	Column '%1' in table '%2' cannot be NULL [page 325]
-196	Index '%1' for table '%2' would not be unique [page 479]
-197	No current row of cursor [page 587]
-198	Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3' [page 630]
-199	INSERT/DELETE on cursor can modify only one table [page 486]
-200	Invalid option '%1' -- no PUBLIC setting exists [page 513]
-201	Invalid setting for option '%1' [page 529]
-202	Only PUBLIC settings are allowed for option '%1' [page 605]
-203	Cannot set a temporary option for user '%1' [page 299]
-204	You do not have '%1' system privilege or authority to set the option '%2' [page 935]
-205	Integrated logins are not permitted [page 488]

SQL Anywhere SQLCODE	Message text
-206	Integrated logins are required, standard logins are not permitted [page 489]
-207	Wrong number of values for INSERT [page 929]
-208	Row has changed since last read -- operation canceled [page 656]
-209	Constraint '%1' violated: Invalid value for column '%2' in table '%3' [page 339]
-210	User '%1' has the row in '%2' locked [page 908]
-211	Not allowed while '%1' is using the database [page 596]
-212	CHECKPOINT statement requires a rollback log [page 316]
-213	Savepoints require a rollback log [page 661]
-214	Table in use [page 729]
-215	Procedure in use by '%1' [page 635]
-216	The option '%1' can only be set as a temporary option [page 784]
-217	The option '%1' cannot be set from within a procedure [page 785]
-218	Authentication failed [page 246]
-220	Savepoint '%1' not found [page 660]
-221	ROLLBACK TO SAVEPOINT not allowed [page 655]
-222	Result set not allowed from within an atomic compound statement [page 651]
-230	sqlpp/dblib version mismatch [page 689]
-231	Client/database server version mismatch [page 322]
-240	Unknown backup operation [page 893]
-241	Database backup not started [page 364]
-242	Incomplete transactions prevent transaction log renaming [page 476]
-243	Unable to delete database file [page 866]
-244	Transaction log was truncated [page 849]
-245	Integrated login failed [page 488]
-246	Integrated logins are not supported for this database [page 489]
-247	The integrated login ID guest can only be mapped to the guest database user ID [page 768]
-248	Cannot map a login ID to the sys or public user ID [page 289]
-249	The login ID '%1' is already mapped to user ID '%2' [page 774]

SQL Anywhere SQLCODE	Message text
-250	Identifier '%1' too long [page 470]
-251	Foreign key '%1' for table '%2' duplicates an existing foreign key [page 457]
-260	Variable '%1' not found [page 920]
-261	There is already a variable named '%1' [page 819]
-262	Label '%1' not found [page 551]
-263	Invalid absolute or relative offset in FETCH [page 491]
-264	Wrong number of variables in FETCH [page 930]
-265	Procedure '%1' not found [page 633]
-267	COMMIT/ROLLBACK not allowed within atomic operation [page 330]
-268	Trigger '%1' not found [page 851]
-269	Cannot delete or rename a column referenced in a trigger definition [page 276]
-270	Cannot drop a user that owns procedures in runtime server [page 281]
-271	Trigger definition conflicts with existing triggers [page 852]
-272	Invalid REFERENCES clause in trigger definition [page 523]
-273	COMMIT/ROLLBACK not allowed within trigger actions [page 331]
-274	Procedure or trigger calls have nested too deeply [page 635]
-280	Publication '%1' not found [page 636]
-281	Table '%1' has publications [page 723]
-282	Subscription to '%1' for '%2' already exists [page 704]
-283	Subscription to '%1' for '%2' not found [page 705]
-284	User '%1' is already the publisher for this database [page 909]
-285	User '%1' is not a remote user for this database [page 910]
-286	Remote message type '%1' not found [page 641]
-287	Passthrough statement inconsistent with current pass-through [page 618]
-288	Remote statement failed [page 644]
-289	Multiple consolidated users cannot be defined [page 580]
-294	Format string argument number %1 is invalid [page 459]
-295	Cannot uniquely identify rows in cursor [page 304]
-296	Error number %1 for RAISERROR must not be less than 17000 [page 412]

SQL Anywhere SQLCODE	Message text
-297	User-defined exception signaled [page 915]
-298	Attempted two active database requests [page 245]
-299	Statement interrupted by user [page 696]
-300	Run time SQL error -- %1 [page 659]
-301	Internal database error %1 -- transaction rolled back [page 490]
-302	Terminated by user -- transaction rolled back [page 738]
-303	Disk write failure '%1' -- transaction rolled back [page 392]
-304	Disk full '%1' -- transaction rolled back [page 391]
-305	I/O error %1 -- transaction rolled back [page 469]
-306	Deadlock detected [page 385]
-307	All threads are blocked [page 230]
-308	Connection was terminated [page 337]
-309	Memory error -- transaction rolled back [page 568]
-311	Internal rollback log corrupted [page 490]
-312	User '%1' already has membership in group '%2' [page 908]
-313	The login ID '%1' has not been mapped to any database user ID [page 773]
-601	'%1' is not a known file format for loading or unloading tables [page 211]
-602	Cannot access file '%1' -- %2 [page 256]
-604	A dbspace has reached its maximum file size [page 219]
-605	The server attempted to access a page beyond the end of the maximum allowable dbspace file size [page 797]
-606	The pattern is too long [page 788]
-607	Cannot stop the database server [page 301]
-608	Invalid TEXTPTR value used with WRITETEXT or READTEXT [page 535]
-609	Invalid data type for column in WRITETEXT or READTEXT [page 499]
-610	User message %1 already exists [page 912]
-611	Transact-SQL feature not supported [page 847]
-612	User message %1 not found [page 912]
-613	User-defined type '%1' not found [page 915]
-614	Cannot drop a user that owns messages or data types [page 280]
-615	Parameter '%1' not found in procedure '%2' [page 615]

SQL Anywhere SQLCODE	Message text
-616	Too many columns in table [page 831]
-617	Calling functions outside the database server is not supported [page 254]
-618	No entry point specified for the current system configuration [page 589]
-619	Need a dynamic library name [page 586]
-620	Could not load dynamic library '%1' [page 349]
-621	Could not find '%1' in dynamic library '%2' [page 347]
-622	Could not allocate resources to call external function [page 344]
-623	Data definition statements not allowed in procedures or triggers [page 361]
-624	Expression has unsupported data type [page 427]
-625	Too many parameters to this external procedure call [page 835]
-626	A thread used internally could not be started [page 225]
-627	Disallowed language extension detected in syntax near '%1' on line %2 [page 391]
-628	Division by zero [page 392]
-629	Invalid escape character '%1' [page 503]
-630	Invalid escape sequence '%1' [page 503]
-631	RAISERROR executed: %1 [page 637]
-632	WITH CHECK OPTION violated for insert/update on base table '%1' [page 927]
-633	Update operation attempted on a read-only cursor [page 902]
-634	Unterminated C string [page 901]
-635	GRANT of column permission on view not allowed [page 466]
-636	Duplicate referencing column [page 398]
-637	Duplicate insert column [page 396]
-638	Right truncation of string data [page 653]
-639	Parameter name missing in call to procedure '%1' [page 615]
-640	Invalid descriptor index [page 501]
-641	Error in assignment [page 409]
-642	Invalid SQL descriptor name [page 531]
-643	UNLOAD TABLE cannot be used to unload a view [page 897]
-644	Invalid database page size [page 499]

SQL Anywhere SQLCODE	Message text
-645	Database creation failed: %1 [page 366]
-646	Could not load the store DLL "%1" [page 350]
-647	Could not execute store DLL (%1) entry point [page 347]
-648	Cannot create item (%1) in the specified dbspace [page 272]
-649	Field '%1' of class '%2' cannot be NULL [page 453]
-650	Index type specification of '%1' is invalid [page 481]
-651	An attempt to delete database '%1' failed [page 232]
-652	Could not decompress class '%1' from JAR [page 346]
-653	Cannot remove class '%1': member of JAR [page 296]
-654	The connection parameters file could not be found [page 752]
-655	Error parsing connection parameter string [page 413]
-656	Unable to connect to server '%1': %2 [page 862]
-657	Unable to connect, server definition is circular [page 863]
-658	Remote server '%1' is currently configured as read-only [page 642]
-659	Remote server '%1' could not be found [page 642]
-660	Server '%1': %2 [page 669]
-661	Backward scrolling cursors are not supported for remote objects [page 250]
-662	Cannot serialize Java object with class '%1' [page 298]
-663	Cannot deserialize Java object [page 278]
-664	Database is active [page 367]
-665	Database "%1" needs recovery [page 362]
-666	The remote table '%1' could not be found [page 792]
-667	Could not access column information for the table '%1' [page 343]
-668	Cursor is restricted to FETCH NEXT operations [page 357]
-669	Method '%1' cannot be called at this time [page 570]
-670	Invalid class byte code [page 494]
-672	Database upgrade failed [page 376]
-673	Database upgrade not possible [page 377]
-674	Statement's size limit is invalid [page 700]
-675	External environment could not be started, '%1' could not be found [page 431]
-676	The specified transaction isolation is invalid [page 804]

SQL Anywhere SQLCODE	Message text
-677	Table '%1' has a foreign key with a referential action [page 721]
-678	Index name '%1' is ambiguous [page 480]
-680	Invalid expression in WHERE clause of Transact-SQL outer join [page 504]
-681	Invalid join type used with Transact-SQL outer join [page 510]
-682	%1 [page 205]
-683	The cursor name '%1' already exists [page 753]
-684	Rollback occurred due to deadlock during prefetch [page 655]
-685	Resource governor for '%1' exceeded [page 648]
-686	Insufficient cache to start Java VM [page 487]
-689	Input parameter index out of range [page 485]
-691	Could not load the backup/restore DLL "%1" [page 349]
-692	Could not execute backup/restore DLL (%1) entry point [page 346]
-697	Error during backup/restore: %1 [page 408]
-698	The remote server does not support an auto-incrementing data type [page 791]
-700	SQLDA fields inconsistent for a multi-row SQLDA [page 689]
-702	TRUNCATE TABLE statement cannot be used on a view [page 854]
-703	Cannot insert or update computed column '%1' [page 288]
-704	Cannot create an index on Java class '%1' [page 270]
-705	Return type of void from procedure '%1' cannot be used in any expression [page 653]
-706	Remote server does not have the ability to support this statement [page 643]
-707	Statement is not allowed in passthrough mode [page 696]
-708	READTEXT or WRITETEXT statement cannot refer to a view [page 638]
-709	Computed columns are not supported in this database [page 333]
-710	Invalid comparison [page 496]
-711	Incorrect database store DLL (%1) version [page 477]
-712	External login for server '%1' could not be found [page 434]
-715	Contents of backup files are inconsistent [page 341]

SQL Anywhere SQLCODE	Message text
-716	Backup file format is invalid [page 249]
-717	RESTORE unable to open file '%1' [page 649]
-718	RESTORE unable to write to file '%1' [page 650]
-719	RESTORE unable to start database '%1' [page 650]
-720	VALIDATE statement must refer to a base table [page 917]
-721	The data type specified for column '%1' is not compatible with the actual data type [page 755]
-722	The column '%1' does not exist in the remote table [page 751]
-723	The length specified for column '%1' is different than the actual length [page 772]
-724	NULL attribute mismatch for column '%1' [page 599]
-725	Identity attribute mismatch for column '%1' [page 471]
-726	The table specification '%1' identifies more than one remote table [page 811]
-727	The optimizer was unable to construct a valid access plan [page 784]
-728	Update operation attempted on non-updatable remote query [page 903]
-729	The specified foreign key (%1) cannot be enforced [page 801]
-730	Invalid JAR file [page 510]
-731	Cannot drop a user that owns objects involved in replication [page 281]
-732	Creating remote tables with computed columns is not supported [page 354]
-733	Number of columns allowing NULLs exceeds limit [page 600]
-734	Cannot update or delete an all-NULL row from table '%1' [page 307]
-735	Invalid parameter [page 515]
-736	The data type of column or variable '%1' is not supported [page 754]
-737	Signature '%1' does not match procedure parameters [page 676]
-738	Password must be at least %1 characters [page 621]
-739	db_init has not been called or the call to db_init failed [page 379]
-740	The communications environment could not be created [page 751]
-749	Feature not available with UltraLite [page 452]

SQL Anywhere SQLCODE	Message text
-750	User owns procedures in use [page 913]
-751	User owns tables in use [page 914]
-754	Parse error: %1 [page 617]
-755	You cannot synchronize or upgrade with uncommitted transactions [page 933]
-757	Modifications not permitted for read-only database [page 578]
-759	SQLDA data type invalid [page 688]
-760	Invalid SQL identifier [page 531]
-761	Server capability name '%1' could not be found in the database [page 669]
-764	Server not found and unable to automatically start [page 670]
-765	Synchronization message type '%1' not found [page 711]
-766	View references '%1', which is a temporary object. Views can only refer to permanent objects [page 923]
-767	Cannot find synchronization subscription with the name '%1' [page 286]
-768	Cannot subscribe to '%1' [page 302]
-769	Cannot modify synchronization entry using ALTER PUBLICATION [page 290]
-770	Cannot modify publication entry using ALTER SYNCHRONIZATION [page 290]
-771	Event '%1' not found [page 422]
-772	Event '%1' already exists [page 421]
-773	Schedule '%1' for event '%2' not found [page 662]
-774	Schedule '%1' for event '%2' already exists [page 662]
-777	Cannot synchronize table '%1' since it does not have a primary key [page 302]
-778	Must include primary key for table '%1' in the synchronization [page 582]
-779	Cannot create synchronization entry for table '%1' with BLOB primary key [page 274]
-780	Cannot update primary key for table '%1' involved in a publication [page 307]
-782	Cannot register '%1' since another exclusive instance is running [page 294]
-783	Cannot register another '%1' as an exclusive application [page 295]

SQL Anywhere SQLCODE	Message text
-784	Cannot register connection because of invalid application cookie [page 295]
-785	Cannot deregister application because of invalid cookie [page 277]
-786	Cannot deregister '%1' since active registered connection exists [page 277]
-787	Current connection is already registered to '%1' as '%2' [page 355]
-788	Another connection has already registered as '%1' [page 238]
-789	Cannot register '%1' since registration cookie exhausted [page 294]
-790	Cannot register connection to '%1' since automatic label exhausted [page 296]
-791	Invalid day of week or month '%1' for event '%2' [page 500]
-792	Invalid time '%1' for event '%2' [page 535]
-793	Invalid start date/time for event '%1' [page 532]
-794	Synchronization server failed to commit the upload [page 716]
-797	Synchronization option '%1' contains semicolon, equal sign, curly brace, or is null [page 712]
-799	DTC transactions are not supported on this platform [page 395]
-800	Cannot commit or rollback while enlisted in a transaction [page 265]
-801	Cannot enlist in a transaction while already enlisted in a transaction [page 284]
-802	Cannot enlist in a transaction with uncommitted data pending [page 285]
-803	Unable to enlist transaction; DTC may be down [page 867]
-804	Unable to re-enlist transaction; DTC may be down [page 872]
-805	Synchronization option '%1' not found [page 712]
-806	System event type '%1' not found [page 719]
-807	Host variables must not be used within a batch [page 468]
-809	Synchronization option is too long [page 713]
-810	External object '%1' not found [page 435]
-811	JAR '%1' not found [page 546]
-812	The SELECT list for the derived table '%1' has no expression to match '%2' [page 796]

SQL Anywhere SQLCODE	Message text
-813	FOR UPDATE has been incorrectly specified for a READ ONLY cursor [page 456]
-814	Cannot update column '%1' since it appears in the ORDER BY clause [page 305]
-815	Cannot update column '%1' since it does not appear in the SELECT clause [page 305]
-816	Specified database file already in use [page 682]
-817	Too many temporary tables in connection [page 838]
-818	Version 'V%1' interface used by external function call '%2' is not supported for execution in the current context [page 922]
-819	Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change [page 725]
-820	Invalid scroll position '%1' [page 526]
-821	Dbospace for table '%1' not found [page 384]
-822	Table '%1' is already included [page 724]
-823	Cannot handle expressions involving remote tables inside stored procedures [page 287]
-824	Illegal reference to correlation name '%1' [page 474]
-825	Previous error lost before RESIGNAL [page 629]
-826	Database upgrade not possible; RowGenerator table not owned by user dbo [page 378]
-827	Database upgrade not possible; user tables have table IDs in system table range [page 378]
-828	A conflict with the dbmsync download phase was detected [page 218]
-829	TLS handshake failure [page 826]
-830	Alias '%1' is not unique [page 229]
-831	Definition for alias '%1' must appear before its first reference [page 388]
-832	Connection error: %1 [page 335]
-833	Row in table '%1' was modified or deleted in BEFORE trigger [page 657]
-834	Column '%1' not found in table '%2' [page 327]
-835	Event '%1' in use [page 422]
-836	Procedure '%1' is no longer valid [page 632]
-837	Trigger or foreign key for table '%1' is no longer valid [page 853]
-838	TLS initialization on server failed [page 826]

SQL Anywhere SQLCODE	Message text
-839	Download failed because of conflicts with existing rows on table '%1' (row: %2) [page 393]
-840	Incorrect or missing encryption key [page 477]
-843	Cannot find synchronization user with the name '%1' [page 286]
-845	Owner '%1' used in a qualified column reference does not match correlation name '%2' [page 613]
-846	SET clause for column '%1' used incorrectly [page 675]
-849	Referential integrity actions other than RESTRICT not allowed for temporary tables [page 640]
-850	Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared [page 733]
-851	Decryption error: %1 [page 387]
-852	Table name '%1' is ambiguous [page 730]
-853	Cursor not in a valid state [page 357]
-854	Function or column reference to '%1' in the ORDER BY clause is invalid [page 463]
-855	Trigger name '%1' is ambiguous [page 852]
-856	Invalid sqlen field in SQLDA [page 532]
-857	Synchronization failed due to an error on the MobiLink server: %1 [page 709]
-858	CREATE/DROP STATISTICS statement cannot refer to virtual tables [page 354]
-860	At least one of the specified dbspaces was not calibrated [page 242]
-861	Aggregated expression '%1' contains multiple columns of which one or more are outer references [page 228]
-862	The aggregate expression '%1' must appear in either the SELECT list or a HAVING clause subquery [page 748]
-863	Grouped query contains more than one distinct aggregate function [page 466]
-864	Statement contains an illegal usage of the NUMBER(*) function [page 695]
-865	Key constraint between temporary tables requires a primary key (not unique constraint) [page 551]
-866	%1 returned a result set with a different schema than expected [page 215]
-867	Cannot change synchronization user_name when status of the last upload is unknown [page 261]

SQL Anywhere SQLCODE	Message text
-868	'%1' is an unknown character set encoding label [page 208]
-869	Database server cannot convert data from/to character set '%1' [page 373]
-870	Cannot convert between requested character set '%1' and database character set '%2' [page 267]
-872	%1 does not return a result set [page 207]
-873	%1 returned multiple result sets [page 215]
-874	Column must be named: %1 [page 328]
-875	There is no way to join to '%1' [page 821]
-876	Client out of memory [page 321]
-877	SETUSER not allowed in procedures, triggers, events, or batches [page 675]
-878	Index '%1' cannot be clustered [page 478]
-879	An invalid multi-byte input character was encountered when converting from %1 to %2 [page 236]
-881	Character substitution was required when converting from %1 to %2 [page 315]
-883	Character conversion error or warning report is not available when the single-byte converter is used [page 313]
-887	Virtual index creation with more than %1 columns [page 924]
-888	XML parser error: %1 [page 931]
-889	Statement contains an illegal usage of the non-deterministic function '%1' [page 695]
-890	Statement size or complexity exceeds server limits [page 699]
-891	Cannot convert between requested character sets '%1' and '%2' [page 268]
-892	XPath parser error: %1 [page 931]
-893	Illegal flags value passed to OPENXML [page 473]
-894	Plan cannot be generated for this type of statement [page 625]
-895	Encryption error: %1 [page 401]
-896	Cannot delete PUBLIC option '%1' since user settings exist [page 276]
-897	Illegal tag value: '%1' [page 474]
-898	Unknown FOR XML EXPLICIT directive: '%1' [page 894]
-899	Illegal column name: '%1' [page 472]
-900	Parent not open: '%1' [page 616]

SQL Anywhere SQLCODE	Message text
-901	Undeclared tag ID: '%1' [page 890]
-902	Too few columns [page 827]
-903	CDATA has a name [page 311]
-904	Illegal ORDER BY in aggregate function [page 473]
-905	Invalid XQuery constructor [page 545]
-906	XMLGEN evaluation failure [page 931]
-907	No name for argument [page 592]
-908	Invalid operation on a closed object [page 512]
-909	Too many columns [page 829]
-910	System command failed with return code %1 [page 718]
-911	Control character in XML output [page 341]
-912	Insufficient memory for OPENXML query [page 487]
-913	Cannot turn on auditing: The audit settings currently require a transaction log file [page 303]
-914	Cycle in common table expression references [page 360]
-915	Service type required for CREATE SERVICE [page 674]
-916	'%1' is an unrecognized service type [page 210]
-918	A user name must be specified if AUTHORIZATION is Off [page 226]
-919	Service '%1' already exists [page 671]
-920	Service '%1' not found [page 672]
-921	Invalid recursive query [page 522]
-922	No column list for recursive query [page 587]
-923	Too many recursive iterations [page 836]
-924	Service '%1' in use [page 671]
-925	Invalid service name '%1' [page 527]
-926	Host variable reference in service definition must be named [page 468]
-927	Service statement definition is inconsistent with service type [page 673]
-928	Constant expressions must not appear in GROUP BY clause [page 338]
-929	Constraint '%1' not found [page 339]
-930	Attempt to alter unnamed column constraint when named constraints exist [page 244]
-931	Service definition requires a statement when authorization is off [page 672]

SQL Anywhere SQLCODE	Message text
-934	Unable to start specified database: Server must be up-graded to start database %1 [page 885]
-935	Unable to start specified database: Log file error [page 884]
-936	Too many constraints in database [page 832]
-937	Invalid reference to or operation on constraint '%1' [page 523]
-938	Recursion is not allowed without the RECURSIVE keyword [page 639]
-939	Invalid setting for HTTP option '%1' [page 528]
-940	Invalid setting for HTTP header '%1' [page 528]
-941	jConnect does not support encryption [page 547]
-942	A workload capture (%1) is already in progress [page 227]
-943	No workload capture currently exists [page 595]
-944	Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation [page 833]
-945	Recursive column %1: conversion from '%2' to '%3' loses precision [page 640]
-946	Result set not permitted in '%1' [page 652]
-947	Window '%1' not found [page 926]
-948	PARTITION BY not allowed in reference to window '%1' [page 618]
-949	ORDER BY not allowed in window '%1' [page 611]
-950	Frame not allowed for window '%1' [page 461]
-951	Cannot access schema file '%1' [page 257]
-952	The status of the last synchronization upload is unknown [page 807]
-953	A schema upgrade is not currently allowed [page 224]
-954	The database '%1' was not found [page 756]
-955	This connection already exists [page 822]
-956	Information for synchronization is incomplete or invalid, check '%1' [page 484]
-957	Invalid preceding or following size in OLAP function [page 520]
-958	Password cannot be longer than %1 characters [page 619]
-959	Compression error: %1 [page 332]
-960	Decompression error: %1 [page 386]
-961	Input string is not base64-encoded [page 485]

SQL Anywhere SQLCODE	Message text
-962	Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause [page 240]
-963	Password contains an illegal character [page 619]
-964	Window function used in predicate [page 927]
-965	Window function requires ORDER BY [page 926]
-966	Composite ORDER BY not allowed with RANGE [page 332]
-967	Backup file '%1' already exists [page 248]
-968	User '%1' already has EXECUTE permission [page 907]
-969	Required operators excluded [page 647]
-970	Invalid hint specified for table '%1' [page 507]
-971	Checksums are not enabled in this database [page 316]
-972	Database page size too small: %1 [page 371]
-973	The string is too long (%1) [page 809]
-974	File I/O failed for '%1' [page 454]
-975	Incorrect volume ID for '%1' [page 478]
-976	Could not load the encryption DLL "%1" [page 350]
-978	Directory for output file does not exist [page 390]
-979	Output file cannot be written [page 613]
-980	The URI '%1' is invalid [page 813]
-981	Unable to connect to the remote host specified by '%1' [page 862]
-982	Connection timed out [page 337]
-983	HTTP request failed. Status code '%1' [page 469]
-984	Could not initialize the encryption DLL: '%1' [page 348]
-985	The database name 'utility_db' is reserved for the utility database [page 757]
-986	Invalid procedure type '%1' [page 522]
-987	Invalid procedure subtype '%1' for type '%2' [page 521]
-988	Invalid response from the HTTP server [page 525]
-989	NAMESPACE attribute is not valid with procedure type '%1' [page 585]
-990	The secure connection to the remote host failed: %1 [page 795]
-991	Clause '%1' has invalid attribute '%2' [page 318]
-992	The specified listener could not be registered [page 802]
-993	LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS [page 560]

SQL Anywhere SQLCODE	Message text
-994	Too many arguments for function or procedure '%1' [page 828]
-995	Warning detected when optimizing SELECT INTO is treated as an error [page 924]
-996	Specified local connection ID not found [page 685]
-997	Local connection ID does not refer to the current database [page 562]
-998	Cannot close a remote JDBC connection that is not the current connection [page 264]
-999	Invalid request log format on line %1 [page 525]
-1000	Temporary space limit exceeded [page 737]
-1001	Parameter '%1' in procedure or function '%2' does not have a default value [page 614]
-1002	The option '%1' is not recognized [page 785]
-1003	Too many distinct group mappings for integrated user [page 832]
-1004	Unable to start specified database: '%1' is not a database [page 879]
-1005	Unable to start specified database: '%1' was created by a different version of the software [page 881]
-1006	Unable to start specified database: '%1' is not a valid database file [page 879]
-1007	Unable to start specified database: '%1' is an invalid transaction log [page 878]
-1008	Unable to start specified database: '%1' is an invalid transaction log mirror [page 878]
-1009	Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid [page 885]
-1010	Unable to start specified database: '%1' not expecting any operations in transaction log [page 880]
-1011	Unable to start specified database: Unknown encryption algorithm [page 886]
-1012	Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing) [page 880]
-1016	Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file [page 882]
-1017	Unable to start specified database: '%1': transaction log file not found [page 881]
-1018	Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file [page 883]

SQL Anywhere SQLCODE	Message text
-1019	Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently [page 883]
-1020	Unable to start specified database: Cannot use log file '%1' since it is shorter than expected [page 882]
-1021	Invalid backup operation [page 492]
-1022	Invalid value for attribute '%1' in service [page 544]
-1023	Missing value for attribute '%1' in service [page 576]
-1024	Unsupported property '%1' in service USING attribute [page 900]
-1025	Duplicate attribute '%1' in service [page 396]
-1026	USING attribute cannot coexist with FORMAT or GROUP attributes [page 916]
-1027	Service type does not allow '%1' attribute [page 674]
-1028	Connection attempting BACKUP has uncommitted transactions [page 334]
-1029	Support for materialized views is not available for this database [page 706]
-1030	Secure HTTP connections are not supported on this platform [page 663]
-1031	Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2' [page 717]
-1032	Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2' [page 718]
-1033	Unable to start database server: Server fatal error [page 877]
-1034	The '%1' attribute is not valid with procedure type '%2' [page 745]
-1035	LOAD TABLE ... WITH FILE NAME LOGGING not permitted on mirrored database [page 557]
-1036	The DBN/DBF parameters do not match the database for this alternate server name [page 761]
-1037	Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it [page 283]
-1038	Cannot use view '%1' because it has been disabled [page 310]
-1039	Cannot connect to mirror server. Use server name '%1' to find the primary server [page 265]
-1040	Cannot use view '%1' because it is invalid [page 310]
-1041	Materialized View '%1' not found [page 566]

SQL Anywhere SQLCODE	Message text
-1042	Cannot add a comment to a table declared as LOCAL TEMPORARY [page 257]
-1043	Request interrupted due to timeout [page 646]
-1044	Invalid password: %1 [page 516]
-1045	Invalid backup parameter value [page 493]
-1046	Illegal column definition: %1 [page 471]
-1047	This database does not support encrypted tables [page 822]
-1050	Cannot return NULL result as requested data type [page 297]
-1051	Cannot create a materialized view because option '%1' has an inappropriate setting [page 269]
-1052	Cannot update materialized view because option '%1' has an inappropriate setting [page 306]
-1053	'%1' is an invalid value for '%2' [page 208]
-1054	Snapshot isolation disabled or pending [page 677]
-1057	BACKUP clause '%1' conflicts with '%2' [page 248]
-1060	Operation conflict with publication type [page 606]
-1061	Table created or altered after start of snapshot [page 729]
-1062	Statement not allowed during snapshot [page 697]
-1063	Unable to start database %1: Cannot use read-only mode since auditing is currently logging to the transaction log [page 875]
-1064	Update conflict on snapshot transaction [page 901]
-1065	Attempt to use snapshot isolation in a non-snapshot transaction [page 245]
-1066	File system error: %1 [page 455]
-1068	Default dbspace '%1' not found [page 387]
-1069	Kerberos login failed [page 550]
-1070	Kerberos logins are not supported [page 550]
-1071	The %1 algorithm is not available in FIPS mode [page 743]
-1072	'%1' is not a valid character set encoding for use with collation '%2' [page 211]
-1073	'%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used [page 206]
-1074	Login mode '%1' not permitted by login_mode setting [page 563]
-1075	Failed to convert from character set '%1' to '%2' [page 438]
-1076	dbicu libraries are required but not installed [page 384]

SQL Anywhere SQLCODE	Message text
-1077	Cannot use materialized view '%1' because it has not yet been initialized [page 309]
-1078	Cycle in computed column dependencies [page 360]
-1079	Backup is unable to open database file '%1' [page 249]
-1080	Cannot revoke these permissions while user '%1' is actively replicating transactions [page 297]
-1081	Could not refresh tracing: at least one enabled tracing level must be specified [page 351]
-1082	Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1 [page 352]
-1083	Could not refresh tracing: failed to find object %1 on row %2 [page 351]
-1084	Use of feature '%1' is not allowed [page 904]
-1085	Duplicate key column (%1) [page 397]
-1087	Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected [page 352]
-1088	ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database [page 243]
-1089	Invalid commit action for shared temporary table [page 496]
-1090	Function '%1' has invalid parameter '%2' ('%3') [page 462]
-1091	Constraint '%1' violated: Invalid value in table '%2' [page 340]
-1092	The method you attempted to invoke was not enabled for your application [page 780]
-1093	The size of the character column, variable, or value data type exceeds 32767 [page 799]
-1094	The HTTP header '%1' is reserved and cannot be modified [page 767]
-1095	The specified HTTP header contains illegal or non-ASCII characters [page 802]
-1096	The specified HTTP header is malformed [page 802]
-1097	ATTACH TRACING could not connect to the tracing database [page 242]
-1098	A tracing connection is already active [page 226]
-1099	Transact-SQL outer joins are currently disabled [page 847]
-1100	The operation failed because column '%1's type does not support streaming [page 783]
-1101	Column '%1' not part of any indexes in its containing table [page 328]

SQL Anywhere SQLCODE	Message text
-1102	Unable to retry download because upload is not finished [page 873]
-1103	No partial download was found [page 593]
-1104	Too many users in database [page 839]
-1106	Too many publications specified for operation [page 836]
-1107	Too many references to a BLOB [page 836]
-1108	Unable to access the file system on the device [page 860]
-1109	Unable to perform requested operation since this database uses keyless encryption [page 871]
-1110	UltraLite cannot synchronize because a synchronization is already running [page 857]
-1111	Information for synchronization was not provided [page 484]
-1112	Specified file system volume not found for database '%1' [page 684]
-1113	Correlation name '%1' is not valid for use with the ROWID function [page 342]
-1114	Invalid setting for SOAP header '%1' [page 529]
-1115	Table '%1' contains an invalid reference to the ROWID function [page 720]
-1116	Collation '%1' not supported on this platform [page 323]
-1117	A row cannot be stored because it exceeds the database page size [page 223]
-1118	Cannot change the MobiLink remote ID when the status of the last upload is unknown [page 262]
-1119	The '%1' property is no longer supported [page 746]
-1120	The dbspace '%1' cannot be dropped because it contains tables or indexes [page 761]
-1121	Not enough free space on device to grow dbspace '%1' by requested amount [page 597]
-1122	Exceeded maximum of '%1' allowable parameters [page 427]
-1123	Invalid mime type '%1' [page 511]
-1124	The dbicu library and server versions do not match [page 759]
-1125	Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1' [page 334]
-1126	Operation failed because table or view '%1' has an INSTEAD OF trigger [page 607]

SQL Anywhere SQLCODE	Message text
-1127	Positioned update operation attempted on a view with an INSTEAD OF trigger [page 627]
-1128	Start date/time for non-recurring event '%1' is in the past [page 693]
-1129	The '%1' attribute contains mismatched parentheses within '%2' [page 744]
-1130	The '%1' attribute is missing a comma within '%2' [page 745]
-1131	The attribute '%1' sets an option '%2' that is incompatible with '%3' [page 750]
-1132	Maximum row size for table '%1' would be exceeded [page 567]
-1133	Invalid trigger type for view '%1' [page 538]
-1134	Triggers cannot be created on materialized view '%1' [page 853]
-1135	Invalid regular expression: %1 in '%2' [page 524]
-1136	Invalid use of escape character '%1' [page 541]
-1137	Escape character conflict '%1' [page 421]
-1138	The mirror '%1' does not match database '%2' [page 781]
-1139	The remote data access feature is not supported on this platform [page 791]
-1140	Unable to start database "%1": CHAR collation or tailoring not supported on this platform [page 874]
-1141	Unable to start database "%1": NCHAR collation or tailoring not supported on this platform [page 874]
-1142	Use of statement '%1', which requires feature '%2', is not allowed [page 904]
-1143	Encryption has not been enabled [page 402]
-1144	'%1' cannot be used as the encoding specification for '%2' data [page 206]
-1145	Unable to connect: The server did not accept the requested encryption type [page 863]
-1146	LOAD TABLE not allowed on temporary table which has foreign key references from another table [page 560]
-1147	Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html [page 363]
-1148	Feature not supported by the client version or the client interface [page 453]

SQL Anywhere SQLCODE	Message text
-1149	Database '%1' cannot be started on this platform. See http://iAnywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html [page 362]
-1150	The SQL scripts DLL cannot be loaded [page 806]
-1151	The logging type ('%1') specified is invalid, not supported or incompatible [page 773]
-1152	Password has expired [page 620]
-1153	Password has expired but cannot be changed because the database is read-only [page 620]
-1154	Traced query (%1, %2) does not exist [page 846]
-1155	Unable to close the cursor on table "%1". LOAD TABLE cannot be executed [page 861]
-1156	Argument "%1" must be a column reference [page 239]
-1157	All column reference arguments must refer to the same table [page 229]
-1158	No matching text index [page 590]
-1159	Non-constant or unknown text query string [page 595]
-1160	Text configuration "%1"."%2" not found [page 738]
-1161	Text configuration "%1" already exists [page 738]
-1162	Term length outside allowed range [page 737]
-1163	Invalid collation: "%1" [page 495]
-1164	Text query parser error: %1 [page 743]
-1165	Error creating text index "%1" on table "%2" [page 407]
-1166	Text indexes are not supported for this database [page 741]
-1167	Cannot drop a user that owns text configurations [page 282]
-1168	Cannot alter or drop a text configuration referenced by a text index [page 259]
-1169	Cannot access a table that is part of a text index [page 255]
-1170	The materialized view %1 cannot be changed to immediate because it has already been initialized [page 775]
-1171	Client application does not allow transfer of data ('%1') [page 319]
-1172	Client application disallowed the transfer of data ('%1') [page 318]
-1173	Client library reported an error accessing data during transfer ('%1') [page 320]
-1174	Cannot create text configuration '%1' because option '%2' has an inappropriate setting [page 275]

SQL Anywhere SQLCODE	Message text
-1175	Unable to acquire table locks in specified time [page 860]
-1178	Transaction log mirroring cannot be used with database mirroring [page 848]
-1179	Unable to start database server: missing license file [page 876]
-1180	Cannot set database option "%1" because it is on the options watch list [page 300]
-1181	The materialized view cannot be changed to immediate because its definition must not contain more than one query block [page 777]
-1182	Statement not allowed on IMMEDIATE REFRESH text index [page 697]
-1183	Support for permissions on dbspaces is not available for this database [page 707]
-1184	Cannot drop last unique index of an immediate materialized view [page 283]
-1185	Index validation failed for table %1, index %2 with code: %3 [page 482]
-1186	Database page validation failed with code: %1 [page 371]
-1187	Cannot append when using compression or encryption [page 259]
-1188	LOAD TABLE error: %1 [page 558]
-1189	The UTF-16 endian specified does not match the Byte Order Mark found in the data [page 814]
-1190	LOAD TABLE is not allowed on a materialized view %1 [page 559]
-1191	LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 561]
-1192	Cannot update multiple tables immediate materialized view %1 depends on [page 306]
-1193	TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 854]
-1194	Login policy "%1" already exists [page 564]
-1195	Login policy "%1" not found [page 565]
-1196	Login policies are not supported for this database [page 563]
-1197	Login policy "%1" in use [page 564]
-1198	User "%1" already exists [page 906]
-1199	The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list [page 776]

SQL Anywhere SQLCODE	Message text
-1200	Client library reported a permissions error accessing object ('%1') during transfer [page 319]
-1201	Client library reported an error opening object ('%1') during transfer [page 320]
-1202	Operation not allowed on a table with dependent immediate materialized views [page 608]
-1203	WRITETEXT not allowed: immediate materialized view %1 depends on %2 [page 928]
-1204	INSERT...ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2 [page 486]
-1205	External environment '%1' could not be found [page 429]
-1206	External environments are not supported for this database [page 433]
-1207	Invalid use of NEAR operator in text query [page 541]
-1211	MERGE statement ANSI cardinality violation on table '%1' [page 569]
-1212	Connection disallowed by login policy for this user [page 335]
-1213	External environment does not support result sets [page 431]
-1214	External library '%1' is in use [page 433]
-1215	External library '%1' not loaded [page 434]
-1216	The arguments to this procedure must be literal strings [page 749]
-1217	Synchronization profile '%1' not found [page 714]
-1218	The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate, non-nullable columns [page 776]
-1219	Maintenance of dependent immediate materialized view(s) failed [page 566]
-1220	User cannot be dropped because external logins exist for this user [page 911]
-1221	Duplicate options not allowed in the CREATE DATABASE statement [page 398]
-1223	Synchronization profile '%1' already exists [page 713]
-1224	Synchronization profile '%1' has invalid parameter '%2' [page 714]
-1225	Synchronization profiles are not supported for this database [page 715]
-1226	Foreign key columns do not match the primary key or a uniqueness constraint in "%1" [page 457]

SQL Anywhere SQLCODE	Message text
-1229	Reorganize table is already being run on table "%1" [page 645]
-1230	Too many open cursors [page 835]
-1231	Statement timed out: '%1' [page 699]
-1232	Attempt to start a second snapshot in a transaction [page 244]
-1233	The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns [page 774]
-1235	Too many columns in SELECT list [page 831]
-1236	Too many expressions in GROUP BY list [page 833]
-1237	Too many columns in procedure result set [page 829]
-1240	The provided stoplist is too long [page 790]
-1241	Value-sensitive cursor used after a TRUNCATE [page 920]
-1243	An attempt to encrypt database '%1' failed [page 232]
-1244	An attempt to decrypt database '%1' failed [page 231]
-1253	The text index %1 needs to be refreshed [page 811]
-1254	MERGE statement for table '%1' failed because of a RAISEROR specification in the statement [page 569]
-1259	Hash error: %1 [page 467]
-1260	This server is not licensed to support the '%1' feature [page 824]
-1261	This server is not licensed to support '%1' connections [page 824]
-1262	This edition of SQL Anywhere is not available on this platform [page 823]
-1263	Event notification queue '%1' not found [page 423]
-1264	Event object name '%1' is not valid [page 425]
-1265	Event object named '%1' already exists [page 426]
-1266	No notification within timeout on queue '%1' [page 592]
-1267	Event parameter '%1' not found [page 426]
-1268	The materialized view cannot be changed to immediate because its definition contains an illegal construct [page 777]
-1269	Service statement definition is invalid or unsupported [page 673]
-1270	Must own table '%1' to make an immediate view reference it [page 582]
-1271	Synchronization download failed to complete [page 708]

SQL Anywhere SQLCODE	Message text
-1272	Synchronization is already in progress [page 711]
-1273	Table '%1' has no columns [page 722]
-1274	Index '%1' has no columns [page 480]
-1275	Invalid domain '%1' [page 502]
-1276	Configuration cannot not be modified while in use [page 333]
-1277	Parameter '%1' cannot be null [page 614]
-1278	Operation is not allowed [page 608]
-1279	Operation '%1' failed for reason: '%2' [page 605]
-1280	Underflow when converting '%1' [page 890]
-1281	Another connection has the row in '%1' locked [page 239]
-1283	A CONTAINS query is not allowed on the view or derived table '%1' [page 218]
-1286	Immediate materialized view definition cannot contain a SUM function over a nullable expression [page 475]
-1288	'%1' statement is not allowed on a mirrored database [page 216]
-1289	LOAD TABLE option '%1' not allowed with FORMAT %2 [page 561]
-1290	FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR) [page 456]
-1303	Too many MESSAGE...FOR CONNECTION messages [page 834]
-1304	Could not create a new text index for this table with the same settings as "%1" [page 344]
-1305	MobiLink communication error -- code: %1, parameter: %2, system code: %3 [page 578]
-1307	Database mirroring options are not supported for this database [page 367]
-1308	Mirror server "%1" not found [page 574]
-1309	Mirror server "%1" already exists [page 572]
-1310	Mirror server "%1" is referenced by another server [page 574]
-1311	Principal mirror servers are already defined [page 632]
-1312	Mirror server "%1" is not a valid parent server [page 573]
-1313	Maximum string length exceeded [page 568]
-1314	Cannot force failover when current server is marked as preferred [page 287]

SQL Anywhere SQLCODE	Message text
-1315	Script file missing statement "go" delimiter on a separate line [page 663]
-1318	More articles are being dropped from publication '%1' than are defined [page 579]
-1319	Synchronization schema changes and script versions are not supported for this database [page 716]
-1321	Table or view '%1' is not valid for use with this statement [page 731]
-1322	A synchronization schema change is already in progress [page 225]
-1323	Subscription to publication '%1' for '%2' omitted from statement [page 705]
-1324	Connection is not allowed to have table locks when executing this statement [page 336]
-1325	Column subset for table '%1' in publication '%2' does not match that specified in publication '%3' [page 329]
-1326	Subscription '%1' not found [page 704]
-1327	The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression [page 778]
-1328	Table '%1' must synchronize to be in publication '%2' [page 725]
-1329	This operation is only allowed within a synchronization schema change [page 823]
-1330	The function '%1' does not allow use of the '%2' clause [page 766]
-1331	The function '%1' requires the use of the '%2' clause [page 766]
-1332	Feature '%1' is unknown or invalid [page 450]
-1333	Feature '%1' was not locked by this connection [page 452]
-1334	Feature '%1' is locked by another connection [page 449]
-1335	Type '%1' does not support method calls (near '%2') [page 856]
-1336	Type '%1' has no method named '%2' (near '%3') [page 856]
-1337	Method invocation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 571]
-1338	Type '%1' is not instantiable (near '%2') [page 857]
-1339	Method '%1' cannot be called with %2 arguments (near '%3') [page 570]

SQL Anywhere SQLCODE	Message text
-1340	Type '%1' cannot be instantiated with %2 arguments (near '%3') [page 855]
-1341	The instantiation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 768]
-1342	Data modifications are not allowed in a synchronization schema change [page 361]
-1343	Feature '%1' is locked because synchronization is in progress [page 449]
-1344	Rollback occurred due to blocking_others_timeout [page 654]
-1348	Mirror server name '%1' does not match current server name [page 575]
-1349	The parent of this mirror server is not currently connected [page 787]
-1350	The parent of this mirror server is not the primary server [page 788]
-1351	Mirror child server creation failed [page 571]
-1352	Mirror server with type '%1' is already defined [page 576]
-1353	Invalid operation '%2' on sequence '%1' [page 512]
-1354	Sequence '%1' already exists [page 666]
-1355	No more values available in sequence %1 [page 591]
-1356	Definition for sequence '%1' is invalid [page 389]
-1357	Multiple settings of same option specified for sequence '%1' [page 581]
-1358	Sequence name '%1' is ambiguous [page 668]
-1359	Sequence '%1' not found [page 667]
-1360	Cannot assign automatic mirror server parent [page 260]
-1361	TREAT AS can only be used with extended types. Cannot treat %1 as a %2 [page 851]
-1362	Cannot treat value '%1' as type %2. The dynamic type is %3 [page 303]
-1363	The 'currval' operator is not defined yet for sequence '%1' for this connection [page 746]
-1366	Sequence '%1' in use by another connection [page 667]
-1367	User owns sequences in use [page 914]
-1369	Sequence generators are not supported for this database [page 668]
-1370	Text queries cannot contain more than 300 terms [page 742]

SQL Anywhere SQLCODE	Message text
-1371	The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN [page 778]
-1372	The server is not able to establish TCP/IP connections [page 798]
-1373	Synchronization failed with internal error: %1 [page 709]
-1374	Synchronization failed. Check the results of the call to sp_get_last_synchronize_result(%1) for more information [page 710]
-1375	Failed to start the dbmlsync server [page 446]
-1376	Failed to connect to the dbmlsync server [page 437]
-1377	The SYNCHRONIZE statement timed out [page 810]
-1378	The database server failed to shut down the dbmlsync server [page 758]
-1379	The dbmlsync server failed to shut down in a timely manner [page 760]
-1380	Client redirected more than once [page 321]
-1381	Database server name '%1' cannot be the same as either the primary or mirror server [page 375]
-1382	Download failed due to an invalid or unsupported row value [page 393]
-1383	The licensed maximum number of mirror servers with type COPY has been exceeded [page 772]
-1384	Unable to stop specified database: %1 [page 888]
-1385	Synchronization failed. Check the dbmlsync log file for more details [page 710]
-1386	Failed to connect to the dbmlsync server. Check the dbmlsync log file for more details [page 438]
-1387	Failed to shut down the dbmlsync server. Check the dbmlsync log file for more details [page 445]
-1388	Failed to start the dbmlsync server. Check the dbmlsync log file for more details [page 446]
-1389	The value for the stoplist cannot be NULL [page 815]
-1390	An incremental refresh is not possible when handles are exhausted [page 233]
-1391	Invalid stoplist value [page 534]
-1392	Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database [page 891]
-1393	Error initializing external term breaker [page 411]
-1394	Invalid external prefilter name specified [page 505]

SQL Anywhere SQLCODE	Message text
-1395	Invalid external term breaker name specified [page 506]
-1396	Error initializing external prefilter [page 410]
-1397	The definition of temporary table '%1' has changed since last used [page 762]
-1398	VERIFY and RENAME cannot be used together [page 921]
-1399	Invalid intersection matrix '%1' [page 509]
-1400	Point is duplicated %1 [page 626]
-1401	Element is an empty set (near '%1') [page 399]
-1402	Mixed spatial reference systems %1 and %2 (near %3) [page 577]
-1403	Non-contiguous curves near '%1' [page 596]
-1404	Unknown unit of measure '%1' [page 897]
-1405	Failed to transform geometry (error %1) [page 447]
-1406	Error parsing well-known-text (WKT) scanning '%1' at offset %2 [page 418]
-1407	Error parsing well-known-binary (WKB) at offset %1 [page 415]
-1408	Mixed coordinate dimensions [page 577]
-1409	Unknown spatial reference system (%1) [page 896]
-1410	An ST_CircularString cannot be constructed from %1 points (near '%2') [page 238]
-1411	Cannot convert from %1 to %2 (near %3) [page 268]
-1412	Support for spatial is not available for this database [page 708]
-1413	Spatial feature %1 is not supported [page 678]
-1414	Error parsing well-known-text (WKT): inconsistent dimensions at offset %1 [page 419]
-1415	Error parsing geometry internal serialization at offset %1 [page 414]
-1417	Error parsing well-known-binary (WKB): type code %1 at offset %2 is invalid [page 417]
-1418	Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent [page 417]
-1419	Error parsing well-known-binary (WKB): unexpected end of input [page 418]
-1420	Error parsing well-known-binary (WKB): inconsistent dimensions at offset %1 [page 416]
-1421	Error parsing well-known-binary (WKB): invalid byte order mark %1 at offset %2 [page 416]

SQL Anywhere SQLCODE	Message text
-1422	Error parsing shapefile record [page 415]
-1423	Error parsing shapefile attributes [page 414]
-1424	Invalid shapefile filename [page 530]
-1425	The multi patch shapefile shape is not supported [page 782]
-1426	The embedded SRID (%1) conflicts with the provided SRID (%2) [page 762]
-1427	The embedded SRID are inconsistent (%1 and %2) [page 763]
-1428	The format type '%1' is not recognized [page 765]
-1429	The format type '%1' cannot be used here [page 765]
-1430	An input string in '%1' format cannot be used here [page 234]
-1431	The format specification syntax is invalid [page 764]
-1432	The format specification option '%1' is not recognized [page 764]
-1433	The value '%2' is not a valid setting for the '%1' format specification option [page 815]
-1434	The data is not in a recognized format [page 754]
-1435	A geometry with SRID=%1 is not supported for method %2 [page 221]
-1436	A geometry with SRID=%1 is not supported when computing distance between non-point geometries [page 222]
-1438	Error reading configuration file [page 420]
-1439	Invalid configuration name %1 [page 497]
-1440	The comparison '%1' cannot be used with geometries [page 752]
-1441	Invalid spatial reference system well-known-text (WKT) [page 530]
-1442	Invalid transform definition '%1' [page 537]
-1443	Transform definition is too long [page 849]
-1444	Transform from SRID %1 to %2 not supported [page 850]
-1445	Transform from SRID %1 not supported [page 849]
-1446	Unit of measure "%1" is not a linear unit [page 891]
-1447	Unit of measure "%1" is not an angular unit [page 892]
-1448	Invalid polygon format '%1' [page 516]
-1449	Invalid polygon: no exterior ring [page 518]
-1450	Invalid polygon nesting [page 517]
-1451	Invalid polygon: multiple exterior rings [page 518]

SQL Anywhere SQLCODE	Message text
-1452	Table '%1' contains a spatial column '%2' and no primary key [page 720]
-1453	Spatial column '%1' cannot be included in a primary key or unique index [page 677]
-1454	Spatial column '%1' cannot be included in an index because it is not constrained to a single SRID [page 678]
-1455	The CONVERT USING clause must be specified when creating a unit of measure [page 753]
-1456	The string '%1' is not a valid axis order [page 808]
-1457	The string '%1' is not a valid coordinate name [page 808]
-1458	Unit of measure '%1' not found [page 893]
-1459	Spatial reference system '%1' not found [page 681]
-1460	Unit of measure '%1' already exists [page 892]
-1461	Spatial reference system '%1' already exists [page 680]
-1462	Spatial reference system must specify the SRID to use [page 681]
-1463	Error parsing definition string '%1' [page 413]
-1464	The spatial reference system type is not supported ('%1') [page 799]
-1465	Ellipsoid parameters missing for geographic spatial reference system [page 400]
-1466	Ellipsoid parameters specified for non-geographic spatial reference system [page 400]
-1467	Coordinate bounds missing for coordinate %1 [page 342]
-1468	The specified axis order is not supported for this type of spatial reference system [page 800]
-1469	The specified polygon format '%1' is not supported for this type of spatial reference system [page 803]
-1470	Invalid storage format '%1' [page 534]
-1471	Spatial reference system %1 cannot be modified because it is in use [page 680]
-1472	Spatial reference system "%1" is reserved [page 679]
-1473	Spatial unit of measure "%1" is reserved [page 682]
-1474	SRID %1 is referenced by column '%2' of table '%3' [page 690]
-1475	SRID %1 is referenced by parameter '%2' of procedure '%3' [page 691]
-1476	SRID %1 is referenced by domain "%3"."%2" [page 690]
-1477	The SRID %1 does not identify a geographic spatial reference system [page 807]

SQL Anywhere SQLCODE	Message text
-1478	ST_Geometry arguments not supported by SQL function %1 [page 691]
-1479	An expression of type %1 is not union-compatible with type %2 [page 233]
-1480	An internal error has occurred in the spatial library [page 235]
-1482	Curve contains nearly antipodal points %1 and %2 (near '%3') [page 359]
-1483	LineString must contain at least 2 points (near '%1') [page 556]
-1484	Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%) [page 917]
-1485	Invalid polygon: ring is not closed (near '%1') [page 520]
-1486	Invalid polygon: ring has zero area (near '%1') [page 519]
-1487	Invalid polygon: curve is not a ring [page 517]
-1488	Invalid polygon: ring is larger than allowed for SRID=%1 (near '%2') [page 519]
-1489	Position %1 is invalid (should be between %2 and %3) [page 627]
-1490	Polygon ring order has been reoriented [page 626]
-1491	CircularString with 3 points has been converted to use 5 points [page 317]
-1492	Could not create a text index without external prefilter library on column "%1" [page 345]
-1493	Could not create a text index with external prefilter library on column "%1" [page 345]
-1494	Geometries with CircularString not supported (near "%1") [page 465]
-1495	Geometries with CircularString are not supported in spatial reference system %1 [page 464]
-1496	LOAD TABLE error: Invalid content encountered on row %1 of the data file [page 559]
-1497	The synchronization failed because MobiLink returned authentication status '%1' with value '%2' [page 809]
-1498	'%1' is an unknown property [page 209]
-1499	Invalid grid size %1 [page 507]
-1500	Invalid tolerance %1 [page 536]
-1501	Invalid bounds for coordinate %1 (near "BETWEEN %2 AND %3") [page 494]
-1502	ST_MultiSurface contains elements with an invalid intersection (near "%1") [page 692]

SQL Anywhere SQLCODE	Message text
-1503	Operation not supported for ST_GeomCollection with intersecting elements (near "%1") [page 609]
-1504	Error from external library: -%1: %2 [page 409]
-1505	Mirror server "%1" defined with type COPY does not include a parent definition [page 573]
-1506	Unknown collation '%1' [page 894]
-1507	The materialized view cannot be changed to immediate because the ON conditions refer to tables which are not in the null-supplying and preserved sides of the OUTER JOINS [page 779]
-1508	The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list [page 775]
-1509	The materialized view cannot be changed to immediate because the primary key columns of any table in the preserved side of an OUTER JOIN must exist in the SELECT list [page 780]
-1510	Cannot specify range that excludes next value for sequence %1 [page 300]
-1511	Text indexes are not allowed across server types [page 741]
-1512	Text index with external prefilter cannot contain both binary and string columns [page 740]
-1515	Support for spatial is not available for this CPU [page 707]
-1516	The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points [page 769]
-1522	Database needs to be upgraded to support the use of external libraries with text indexes [page 369]
-1525	Cannot perform specified operation, number of administrators for role '%1' falls below min_role_admins option value [page 292]
-1526	Text index %1 cannot be used with text procedure %2 [page 740]
-1527	Task '%1' is not allowed [page 734]
-1528	No more role grant permitted [page 591]
-1529	Outer reference not permitted in DML derived table [page 612]
-1530	Format '%1' is not supported in the UNLOAD statement [page 459]
-1531	Geometry expressions cannot be used in the ORDER BY specification (near '%1') [page 465]
-1532	Failed to transform point %1 (error %2) [page 447]

SQL Anywhere SQLCODE	Message text
-1535	System Privileges and Roles feature is not supported in this database [page 719]
-1536	Invalid user ID or role name '%1' specified [page 543]
-1537	Role "%1" already exists [page 654]
-1538	User or Role ID '%1' does not exist [page 913]
-1539	Use of WITH NO SYSTEM PRIVILEGE INHERITANCE option is not allowed with %1 [page 906]
-1540	Operation would cause a role cycle [page 610]
-1541	Specified System Privilege '%1' is Invalid [page 686]
-1551	Login redirection is required to complete the connection, but it is not supported by the client [page 565]
-1552	Invalid text index type for the materialized view [page 535]
-1553	Cannot perform specified operation, set user condition violated [page 292]
-1554	Specified LDAP server '%1' is not found [page 684]
-1555	Statement not allowed on text index for a materialized view [page 698]
-1556	External environment failed to start and establish a connection within the %1 second timeout [page 432]
-1557	External environment cannot be started during database startup [page 430]
-1558	Specified user '%1' is a role [page 686]
-1559	Specified role '%1' is not a user extended as role [page 685]
-1560	Specified role '%1' is a user extended as role [page 685]
-1561	Use of WITH DROP OBJECTS is not allowed with '%1' [page 905]
-1562	The role '%1' was not dropped because it is granted to other users or roles. Use the 'WITH REVOKE' option to drop it [page 793]
-1563	Cannot drop a role that owns sequences in runtime server [page 279]
-1564	Cannot drop a role that owns events in runtime server [page 278]
-1565	Cannot drop a role that owns web services in runtime server [page 280]
-1566	Cannot drop a role that owns external environment objects in runtime server [page 279]
-1567	External environment cannot be started, external process terminated on start up [page 430]
-1569	LDAP Server "%1" already exists [page 553]

SQL Anywhere SQLCODE	Message text
-1570	Attempt to allocate memory for LDAP server "%1" failed [page 243]
-1571	The attempt to drop LDAP server "%1" failed, suspend the server to drop it [page 749]
-1572	LDAP User Authentication feature is not supported in this database [page 555]
-1573	MIRROR server class is not supported for SAP IQ databases [page 575]
-1574	You must upgrade your database in order to use the MIRROR server class [page 935]
-1576	LDAP server "%1" is in use by login policy "%2" [page 554]
-1578	Table parameterized functions are not allowed across server types [page 732]
-1579	External procedures or functions are not allowed across server types [page 435]
-1580	Failed to load the MobiLink client support libraries [page 442]
-1581	Database name must be specified when connecting to a cloud database server [page 368]
-1582	Server name can only be specified when connecting to a cloud database server with NODETYPE=DIRECT [page 670]
-1584	Unable to load the dbrsakp shared object [page 869]
-1585	Invalid tool name or admin user for generating security token [page 537]
-1586	Error modifying refresh type for text index "%1" on materialized view "%2" [page 411]
-1587	Storing certificates is not supported for this database [page 701]
-1588	The specified certificate is not valid [page 800]
-1589	Certificate '%1' not found [page 312]
-1590	You cannot use a security token when making remote connections [page 934]
-1591	Invalid use of BEFORE operator in text query [page 540]
-1592	Text indexes on materialized views are not supported for this database [page 742]
-1593	Unable to copy file %1 to destination %2 [page 864]
-1594	LDAP server definition of "%1" is incomplete. A search URL, access distinguished name, password, and authentication URL are required [page 555]
-1595	Column '%1' not found in variable '%2' [page 327]

SQL Anywhere SQLCODE	Message text
-1596	Database contains users with 'SYS_' prefix and '_ROLE' suffix [page 366]
-1597	The transaction may not be committed because the primary server lost quorum [page 812]
-1598	Array element error: array index '%1' is out of range [page 241]
-1599	Invalid use of collection type [page 540]
-1600	The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2' [page 750]
-1601	Password encryption failed. Error message '%1' [page 619]
-1602	The specified distinguished name '%1' does not match the search result '%2' [page 801]
-1603	The search using '%1' failed due to one or more invalid values set [page 795]
-1605	Table Parameterized Functions and V4 TableUDFs are not supported for this database [page 731]
-1606	Multiple table parameters are not supported [page 581]
-1607	Outer references are not allowed for TPF input tables [page 612]
-1608	Unable to delete file %1 [page 867]
-1609	File %1 already exists [page 454]
-1610	Unable to create directory %1 [page 865]
-1611	Unable to copy file %1 [page 864]
-1612	Cannot ALTER LDAP SERVER '%1' while LDAP server is in active state [page 258]
-1613	Tag ID: '%1' specifies a value not bounded by an array [page 734]
-1617	The %1 remote data access class is no longer supported, please use %2 instead [page 744]
-1620	The value specified is not within the required range %1 to %2 [page 816]
-1621	LDAP server %1 may not accept anonymous binds [page 554]
-1622	Bind to LDAP server %1 without a password is not allowed [page 250]
-1623	The search on LDAP server %1 completed with no matching results [page 794]
-1624	The length of the value specified is too long, it exceeds the limit of %1 bytes [page 771]
-1625	The UltraLite database deploy file is invalid (code: %1, file: %2) [page 812]

SQL Anywhere SQLCODE	Message text
-1627	TLS ON cannot be used with URL %1 [page 826]
-1629	Only one IDENTIFIED BY value may be specified [page 604]
-1631	Use of table privilege '%1' is not supported on the current database [page 905]
-1632	Dropping or altering arbiter "%1" requires a connection to the partner [page 395]
-1633	Trace event '%1' is not valid [page 839]
-1634	The specified session name '%1' is not valid [page 803]
-1635	Trace event '%1' already exists [page 839]
-1636	Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first [page 840]
-1637	Trace event session '%1' is active. Stop active session before dropping the session [page 844]
-1638	Too many arguments for trace event '%1' [page 829]
-1639	Database alter failed: %1 [page 363]
-1640	Too many active trace event sessions [page 828]
-1641	Trace event session '%1' already active [page 840]
-1642	One or more targets in the trace event session '%1' failed to start [page 604]
-1643	Trace event session '%1' failed to start [page 844]
-1644	Trace event session '%1' is already stopped [page 845]
-1645	Trace event session '%1' already has trace event '%2' [page 842]
-1646	The specified target type '%1' is not valid [page 804]
-1647	Unknown option '%1' specified for target type '%2' [page 896]
-1648	The option '%1' was not specified for target type '%2' [page 786]
-1649	Trace event session '%1' already has target type '%2' [page 841]
-1650	Trace event session '%1' does not have trace event '%2' [page 843]
-1651	Trace event session '%1' does not have target type '%2' [page 842]
-1652	Trace event session '%1' already exists [page 841]
-1655	Invalid value for login policy option "%1" [page 545]
-1659	File or directory %1 not found [page 455]
-1660	Fail to compare %1 and %2 [page 436]

SQL Anywhere SQLCODE	Message text
-1661	%1 is not a directory [page 210]
-1662	%1 and %2 must not be the same [page 205]
-1663	Prevented removal of LDAP server because it is referenced by login policy "%1" which is the only login policy with an LDAP server and the value of login_mode is "LDAPUA" [page 629]
-1664	Prevented removal of LDAP server "%1" because it is the only LDAP server and the value of login_mode is "LDAPUA" [page 628]
-1665	Cannot change password because change_password_dual_control process is in progress [page 260]
-1666	Expression is not an array [page 428]
-1671	The file '%1' is invalid when the disk sandbox feature is enabled for database '%2' [page 763]
-1672	A disk sandbox error occurred for database '%1' when determining the disk sandbox status for file '%2' [page 219]
-1673	A disk sandbox error occurred for database '%1' when finding the full path for file '%1' [page 220]
-1674	Error at offset '%1': unexpected token '%2' [page 405]
-1675	Error at offset '%1': unexpected trailing text [page 406]
-1676	Error at offset '%1': invalid data [page 404]
-1677	Error at offset '%1': expected token '%2' [page 403]
-1678	Error at offset '%1': expected JSON name/value pair [page 403]
-1679	Error at offset '%1': mismatched object or array terminator [page 405]
-1680	Invalid variable or type [page 545]
-1681	Procedure is currently being altered or dropped [page 635]
-1683	Cannot change the mirror server type from %1 to %2 [page 262]
-1684	Trace target option '%1' conflicts with option '%2' [page 845]
-1685	There was insufficient memory to complete the %1 operation [page 821]
-1686	Invalid parameter was used in the call to %1 [page 515]
-1687	The secure feature key name '%2' is not valid in the call to %1 [page 796]
-1688	An invalid authorization code was specified in the call to %1 [page 235]
-1689	An invalid secure feature list '%2' was specified in the call to %1 [page 237]

SQL Anywhere SQLCODE	Message text
-1690	You are not authorized to assign the feature list '%2' to a secure feature key using %1 [page 932]
-1691	You are not authorized to change the secure feature key named '%2' using %1 [page 933]
-1692	Call to %1 failed - the maximum number of secure feature keys has already been created [page 252]
-1693	Call to %1 failed - the secure feature key named '%2' already exists [page 253]
-1694	Call to %1 failed - the secure feature key named '%2' does not exist [page 254]
-1695	Call to %1 failed - the authorization code specified for the secure feature key named '%2' is incorrect [page 251]
-1696	Call to %1 failed - the key named '%2' is the last key with the MANAGE_FEATURES and MANAGE_KEYS features [page 252]
-1698	change_password_dual_control is enabled for this user. Use ALTER USER to change password [page 312]
-1700	TDS login requests with unencrypted passwords are not permitted [page 736]
-1701	TDS login requests with RSA encrypted passwords must also use a nonce [page 735]
-1702	Collection types not supported [page 323]
-1703	The user name specified must be the user name of the current connection [page 813]
-1704	Remote column %1 has been specified with the wrong case [page 641]
-1709	Invalid DEFAULT value near '%1' on line %2 [page 501]
-1710	Invalid value for INSERT near '%1' on line %2 [page 544]
-1714	The dbmsync server did not have sufficient database permissions [page 759]
-1715	Invalid options for UPGRADE: SCRIPT FILE can only be specified with RESTART [page 513]
-1716	Statement %1 disallowed during upgrade from script [page 694]
-1722	The variable '%1' must not be NULL in this context [page 817]
-1723	The length of the variable '%1' is too long in this context; it exceeds the limit of %2 bytes [page 771]
-1724	The variable '%1' must be %2 in this context [page 816]
-1725	Failed to set up audit log session for database '%1' [page 445]

SQL Anywhere SQLCODE	Message text
-1727	Use of %TYPE or %ROWTYPE is not allowed for variable or temporary objects [page 903]
-1728	Function '%1' has invalid parameter '%2' ('%3') [page 462]
-1729	Cannot create base table '%1': A global temporary table with the same name exists [page 271]
-1730	Cannot create global temporary table '%1': A base table with the same name exists [page 271]
-1731	Cannot set audit_log to the transaction log: The transaction log is not enabled for the database [page 299]
-1732	Cannot update the audit_log option: one or more of the specified targets is invalid [page 308]
-1733	Unable to declare a row variable from the cursor using %ROWTYPE; invalid name for field %1 [page 865]
-1734	Unable to declare a row variable from the cursor using %ROWTYPE; no fields were found in the cursor [page 866]
-1735	Cursor %1 cannot be used to declare a row variable using %ROWTYPE [page 355]
-1736	Debugger error: %1 [page 386]
-1737	Number of columns defined for the table does not match SELECT statement [page 600]
-1738	Cannot create table '%1': Name is used by a non-table object [page 275]
-1739	Need a function entry point [page 587]
-1740	Cannot load encryption DLL %1: version mismatch [page 288]
-1741	DBA user ID must be specified in the CREATE DATABASE statement [page 380]
-1742	DBA password must be specified in the CREATE DATABASE statement [page 380]
-1749	The PAM User Authentication (PAMUA) feature is not supported on this computer [page 787]
-1753	Transact-SQL expression in a non-Transact-SQL statement near '%1' %2 [page 846]
-1761	Host variables must not be used in this context [page 468]
-1764	REORGANIZE TABLE ran out of space [page 645]
-1765	The address parameter "%1" conflicts with an existing %2 listener [page 747]
-1766	%1 listener binding failure for the address parameter "%2" [page 213]
-1767	%1 listener for the address parameter "%2" is not found [page 213]

SQL Anywhere SQLCODE	Message text
-1768	The last shared memory or TCPIP listener cannot be stopped without using the force parameter [page 770]
-1769	Cannot convert value to a timestamp [page 269]
-1770	The USING LOG PATH clause must be used in conjunction with the RECOVER UNTIL clause [page 814]
-1772	Storing OData Producers is not supported for this database [page 701]
-1773	OData Producer '%1' not found [page 601]
-1774	OData Producer option error: %1 [page 602]
-1775	%1 listener start option parse error: %2 [page 214]
-1776	%1 listener start option includes an unsupported option: %2 [page 214]
-1777	Database connection limit exceeded [page 365]
-1778	Database upgrade not possible; user-defined database option "%1" conflicts with the system-defined database option with the same name [page 379]
-1779	Shared memory listener already started [page 676]
-1780	No running shared memory listener was found [page 594]
-1781	The last HTTP or HTTPS listener cannot be stopped without using the force parameter [page 770]
-1782	Listener type "%1" failed to initialize when starting a listener [page 556]
-1783	Invalid address parameter "%1" provided to start a listener [page 491]
-1785	Invalid address parameter "%1" provided to stop a listener [page 492]
-1787	CATALOG ONLY and MULTIPLEX cannot be used together [page 311]
-1788	Time zone '%1' not found [page 825]
-1789	Storing time zone information is not supported for this database [page 702]
-1790	Time zone option error: %1 [page 825]
-1792	Invalid use of table reference type [page 542]
-1793	Table reference types not supported [page 733]
-1794	Table reference '%1' has been invalidated [page 732]
-1795	Expression of type %1 is not allowed in this context (near: %2) [page 429]
-1796	The OData server returned an error: %1 [page 782]
-1797	Cannot drop the database's current time zone [page 284]

SQL Anywhere SQLCODE	Message text
-1798	PIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 623]
-1799	Cannot create mutex "%1": %2 with this name already exists [page 273]
-1800	Cannot create semaphore "%1": %2 with this name already exists [page 274]
-1801	Cannot create semaphore "%1" as a temporary semaphore with this name already exists [page 273]
-1802	Cannot create mutex "%1" as a temporary mutex with this name already exists [page 272]
-1803	Invalid start value for semaphore "%1": %2 [page 533]
-1804	Mutex was dropped [page 585]
-1805	Semaphore was dropped [page 665]
-1806	Deadlock involving a mutex detected [page 385]
-1807	Mutex "%1" not found [page 583]
-1808	Semaphore "%1" not found [page 665]
-1809	Temporary mutex or semaphore can only be dropped by the connection that created it [page 736]
-1810	Invalid increment value for semaphore "%1": %2 [page 509]
-1811	Invalid timeout value %1 [page 536]
-1812	Mutex "%1" with transaction scope cannot be released [page 584]
-1813	Mutex "%1" was not locked by this connection [page 584]
-1814	The variable in the INTO clause is not a row type [page 817]
-1815	Unsupported use of ROW type in an INTO clause [page 900]
-1816	Invalid generated identifier '%1' [page 506]
-1817	UNPIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 898]
-1818	Indirect identifiers not supported [page 483]
-1819	Indirect identifier `[%1]` yielded an invalid identifier name '%2' [page 483]
-1820	Invalid ROW or ARRAY domain [page 526]
-1821	Start listener error: %1 [page 693]
-1825	Cannot change the setting of the UseSingleJVMInstance server option after Java has already been started [page 264]
-1826	PIVOT error: only one aggregate function can be specified without an alias [page 623]
-1830	User owns locked mutexes [page 913]

SQL Anywhere SQLCODE	Message text
-1831	Mutex "%1" is locked by another connection [page 583]
-1832	Cannot specify read only in both the READ ONLY clause and the USING clause [page 301]
-1834	Unable to start specified database: Cannot use log file '%1' since the timeline does do not match the timeline of the database file [page 884]
-1835	%2 error occurred while trying to read file %1 during backup [page 217]
-1836	Invalid cockpit parameter [page 495]
-1840	The database '%1' cannot be used for the SQL Anywhere Cockpit [page 755]
-1841	The SQL Anywhere Cockpit '%1' cannot be used for the current operation [page 805]
-1842	Cannot change the setting of the SingleCLRInstanceVersion server option after the CLR external environment has already been started [page 263]
-1843	The database name is reserved for SQL Anywhere Cockpit [page 757]
-1845	PIVOT error: Too many aggregate functions and IN clause items [page 624]
-1846	PIVOT error: PIVOT XML does not contain a valid subquery, ANY, or ALL in the IN clause [page 624]
-1847	UNPIVOT error: Cannot create valid identifiers for IN clause items [page 898]
-1849	Too many temporary mutexes and semaphores created [page 837]
-1850	Too many mutexes and semaphores created [page 834]
-1851	Unable to start the SQL Anywhere Cockpit: %1 [page 887]
-1852	Invalid repeat interval for event '%1' [page 524]
-1853	Invalid event parameter for event '%1' [page 504]
-1855	Remote server is currently in use and cannot be dropped [page 643]
-1857	RESTORE unable to find a log backup on the latest timeline [page 649]
-1858	Unable to open the SQL Anywhere Cockpit template -- '%1' [page 870]
-1859	Failed to copy the SQL Anywhere Cockpit template file '%1' to destination '%2' [page 439]
-1860	The SQL Anywhere Cockpit template file '%1' not found [page 806]

SQL Anywhere SQLCODE	Message text
-1861	Failed to delete the SQL Anywhere Cockpit file '%1': %2 [page 440]
-1863	Failed to access the SQL Anywhere Cockpit file '%1': %2 [page 436]
-1864	Failed to read the SQL Anywhere Cockpit setting file '%1' [page 444]
-1865	Failed to write the SQL Anywhere Cockpit setting file '%1' [page 448]
-1866	Unable to start the SQL Anywhere Cockpit when it is stopping [page 886]
-1867	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is being started [page 382]
-1868	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is starting [page 383]
-1869	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is active [page 381]
-1870	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is stopping [page 383]
-1871	Unable to stop the SQL Anywhere Cockpit when it is being started [page 888]
-1872	Unable to upgrade the SQL Anywhere Cockpit when it is not active [page 889]
-1873	Unable to finish upgrade the SQL Anywhere Cockpit when it is not active [page 869]
-1874	Invalid empty string specified as 'ESCAPE CHARACTER' option of LOAD or UNLOAD TABLE [page 502]
-1875	Unable to find the cockpit parameters used to start or stop [page 868]
-1876	Failed to rename the SQL Anywhere Cockpit file '%1' to '%2': %3 [page 444]
-1877	Encryption failed for the SQL Anywhere Cockpit setting file. Error message '%1' [page 401]
-1878	The SQL Anywhere Cockpit template '%1' cannot be used for the current operation [page 805]
-1879	Failed to get status information on the path '%1': %2 [page 441]
-1880	Failed to get file system statistics for the path '%1' [page 441]

SQL Anywhere SQLCODE	Message text
-1881	Procedure '%1' needs a RESULT clause for returned ROW or ARRAY [page 633]
-1882	There is already a database variable named '%1' [page 818]
-1883	Address parameter "%1" is not supported to start a listener for the personal database server [page 227]
-1884	The address parameter "%1" provided to stop a listener has an invalid IP address or no port [page 748]
-1885	Stop listener error: %1 [page 700]
-1886	Scalar variable '%1' not found [page 661]
-1887	Feature '%1' is not supported for this database [page 450]
-1888	Reading %1 database pages exceeds available cache of %2 pages [page 638]
-1889	No stored cache pages [page 594]
-1892	JSON object contains too many properties [page 549]
-1893	JSON array contains too many elements [page 548]
-1894	Too many tables in query [page 837]
-1895	Too many columns in schema [page 830]
-1896	Too many columns in row type [page 830]
-1897	Array contains too many elements [page 241]
-1898	IN-list is too long [page 476]
-1899	Statement requires too much memory during %1 [page 698]
-1900	JSON nesting too deep [page 548]
-1902	Invalid setting '%1' specified for option '%2' for target type '%3' [page 527]
-1907	Error processing SAP HANA strategy [page 419]
-1908	RESTORE statement missing a FROM clause [page 648]
-1909	Cannot use CLEAR LOG clause with offline log backups [page 309]
-1910	Unsupported extended storage syntax [page 899]
-1911	Failed to create pipe %1 during BACKUP using BACKINT %2 [page 439]
-1912	Failed to open pipe %1 during BACKUP using BACKINT %2 [page 443]
-1913	Failed to close pipe %1 during BACKUP using BACKINT %2 [page 437]
-1914	Failed to write pipe %1 during BACKUP using BACKINT %2 [page 448]

SQL Anywhere SQLCODE	Message text
-1915	Failed to read pipe %1 during BACKUP using BACKINT %2 [page 443]
-1916	SAP HANA environment error, unable to execute command on name server [page 660]
-1917	Invalid BACKUP operation or type specified: %1 [page 493]
-1918	Verify fails, bytes written to pipe %1 and bytes written to file %2 [page 922]
-1919	BACKINT configuration file error, %1 [page 247]
-1920	SAP HANA environment error, unable to ping name server [page 659]
-1921	Failed to get BACKUP id for file name %1 [page 440]
-1922	Error in parsing BACKINT configuration file [page 410]
-1925	Possible database corruption found: %1 [page 628]
-1926	Unable to start the SQL Anywhere Cockpit: Please restart the server with a minimum page size of 4096 [page 887]
-1927	No external backup identity found for archive file '%1' in HANA strategy document [page 589]
-1928	Error backing up existing log area. Found '%1' logs in '%2' directory [page 407]
-1929	Found a file '%1' with relative path in delta dbspace during backup existing log area. [page 461]
-1931	PBKDF2 error: %1!s! [page 622]
-1933	Duplicate options not allowed in %1!s! [page 397]
-1934	Cannot use both the OR REPLACE and IF NOT EXISTS clauses [page 308]
-1935	SQL statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 688]
-1936	SQL statements in BEGIN PARALLEL WORK...END PARALLEL WORK statement are not of the same type [page 687]
-1937	Table '%1' specified more than once in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 727]
-1938	When wait_for_commit database option is enabled, LOAD TABLE statement is not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 925]
-1939	Load-source for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 557]
-1940	Logging type ('%1') for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 562]

SQL Anywhere SQLCODE	Message text
-1941	WITH CHECKPOINT ON clause for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 928]
-1942	Function-name clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 463]
-1943	'%1' for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 207]
-1944	Error executing BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 408]
-1945	VIRTUAL clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 923]
-1946	Table '%1' for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 721]
-1947	Text index \"%1\" on table \"%2\" exists. Table with text index is not supported for LOAD TABLE statement in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 739]
-1949	Dialect '%1' is not supported by this database [page 390]
-1950	Option '%1' cannot be used with HSQL COMPATIBLE [page 610]
-1954	Unable to prepare to save the SQL Anywhere Cockpit when it is not active. [page 871]
-1955	Cannot save SQL Anywhere Cockpit to existing file '%1' [page 298]
-1957	Unable to stop the SQL Anywhere Cockpit when it is being prepared to save. [page 889]
-1958	DBF parameter cannot be used when the SQL Anywhere Cockpit is being prepared to save. [page 381]
-1959	Unable to prepare to save the SQL Anywhere Cockpit when it is already being prepared. [page 872]
-1960	Unable to save and restart the SQL Anywhere Cockpit when it is not prepared. [page 873]
-1961	VERIFY and FOR REPLICATION cannot be used together [page 921]
-1962	RECOVER UNTIL and FOR REPLICATION cannot be used together [page 639]
-1965	Feature '%1' not supported [page 451]
-1967	Command '%1' received BACKINT_ERROR from HANA [page 330]

SQL Anywhere SQLCODE	Message text
-1968	Unable to clean directory %1 [page 861]
-1969	Operation failed - could not complete checkpoint [page 606]
-1970	Format string contains invalid format specifiers: '%1' [page 460]
-1971	Format string contains more than %2 format specifiers: '%1' [page 460]
-1975	Restoring database from an upgrade image [page 651]
-1978	'%1' statement is not allowed as a consumer [page 216]
-1979	Cannot create a proxy table LIKE another table [page 270]
-1984	Cannot proceed with online backup, SQLA log guid is ahead [page 293]
-1986	The database must be upgraded to use the KEY option on the SYNCHRONIZE command [page 756]
-1987	Database upgrade not possible; database has auditing enabled [page 377]
-1990	Failed to load %1 HANA library [page 442]
-1991	CHAR configuration provided for NCHAR column for text index \"%1\" on table \"%2\" [page 313]
-1992	Offline reset password failed: %1 [page 602]
-1993	Offline reset password is not allowed for user ID '%1' that has no password [page 603]
-1994	Offline reset password not supported [page 603]
-2000	JWT Provider '%1' does not exist [page 549]
-2056	An internal error has occurred in the profiler library [page 234]
-2057	A fatal error has occurred in the profiler library [page 221]
-2058	The profiler is not supported [page 790]
-2059	A memory error occurred causing the profiler operation to fail [page 222]
2060	There is no profiler data available [page 820]
-2061	The operation cannot be executed while the profiler is running [page 783]
-2062	The profiler is not running [page 789]
-2063	The profiler is already running [page 789]
-2064	The profiler has not been initialized. Contact SAP support. [page 789]
-2065	The output path '%1' is invalid [page 786]
-2068	The minimum percentage '%1' is invalid. The minimum percentage must be between 0 and 100. [page 781]

SQL Anywhere SQLCODE	Message text
-2069	The sample wait time cannot be changed once samples have been collected. Clear the sample data and then set the option. [page 794]
-2071	Could not start a new profiling session because the previous session is still being processed. [page 353]
-2072	Could not write the profiler data because the previous session is still being processed. [page 353]

1.1.2 SQL Anywhere Error Messages Sorted by SQLSTATE

SQLSTATE	Message text
00000	(no message text) [page 217]
01000	Warning: %1 [page 925]
01003	Null value eliminated in aggregate function [page 599]
01004	Value truncated [page 919]
01005	Encryption has not been enabled [page 402]
01F01	Position %1 is invalid (should be between %2 and %3) [page 627]
01FW1	Polygon ring order has been reoriented [page 626]
01FW2	CircularString with 3 points has been converted to use 5 points [page 317]
01S02	Cursor option values changed [page 358]
01W01	Invalid data conversion: NULL was inserted for column '%1' on row %2 [page 498]
01W02	Using temporary table [page 916]
01W03	Invalid data conversion [page 497]
01W04	Row has been updated since last time read [page 656]
01W05	Procedure has completed [page 634]
01W06	Value for column '%1' in table '%2' has changed [page 919]
01W07	Language extension detected in syntax near '%1' on line %2 [page 553]
01W08	Statement cannot be executed [page 694]
01W09	More information required [page 579]
01W10	Transaction log backup page only partially full [page 848]
01W11	Database option '%1' for user '%2' has an invalid setting [page 370]

SQLSTATE	Message text
01W12	Character set conversion to '%1' cannot be performed; '%2' is used instead [page 314]
01W13	Database server cannot convert data from/to character set '%1', conversion may not be correct [page 373]
01W14	Language '%1' is not supported, '%2' will be used [page 552]
01W15	Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead [page 899]
01W16	Illegal user selectivity estimate specified [page 475]
01W17	'%1' is an unknown option [page 209]
01W18	The result returned is non-deterministic [page 792]
01W20	Plan may contain virtual indexes [page 625]
01W21	A row was dropped because it could not be converted to the new schema format [page 223]
01W23	Cannot output the histogram for string column '%1' [page 291]
01W24	Row was dropped from table %1 to maintain referential integrity [page 658]
01W25	Publication predicates were not evaluated [page 637]
01W26	Option '%1' specified more than once [page 611]
01W27	Two rows with the same primary key have been downloaded for table '%1' [page 855]
01W28	Database contains no tables to synchronize [page 365]
01WC1	An invalid multi-byte input character was encountered when converting from %1 to %2 [page 236]
01WC3	Character substitution occurred when converting from %1 to %2 [page 314]
01WC4	The ICU collation '%1' has defaulted to another collation [page 767]
02000	Row not found [page 658]
04W07	A dbspace has reached its maximum file size [page 219]
04W08	The server attempted to access a page beyond the end of the maximum allowable dbspace file size [page 797]
07001	Not enough values for host variables [page 598]
07002	Not enough fields allocated in SQLDA [page 597]
07003	Error opening cursor [page 412]
07005	Can only describe a SELECT statement [page 255]
07009	Invalid descriptor index [page 501]
07W01	Invalid type on DESCRIBE statement [page 539]

SQLSTATE	Message text
07W02	Invalid statement [page 533]
07W03	Invalid prepared statement type [page 521]
07W04	SQLDA fields inconsistent for a multi-row SQLDA [page 689]
07W05	SQLDA data type invalid [page 688]
07W06	Invalid SQL identifier [page 531]
07W07	Host variables must not be used within a batch [page 468]
07W08	Invalid sqllen field in SQLDA [page 532]
08001	Database cannot be started -- %1 [page 364]
08003	Not connected to a database [page 597]
08004	User ID '%1' does not exist [page 911]
08005	Password contains an illegal character [page 619]
08S01	There was insufficient memory to complete the %1 operation [page 821]
08S02	Invalid parameter was used in the call to %1 [page 515]
08S03	The secure feature key name '%2' is not valid in the call to %1 [page 796]
08S04	An invalid authorization code was specified in the call to %1 [page 235]
08S05	An invalid secure feature list '%2' was specified in the call to %1 [page 237]
08S06	You are not authorized to assign the feature list '%2' to a secure feature key using %1 [page 932]
08S07	You are not authorized to change the secure feature key named '%2' using %1 [page 933]
08S08	Call to %1 failed - the maximum number of secure feature keys has already been created [page 252]
08S09	Call to %1 failed - the secure feature key named '%2' already exists [page 253]
08S10	Call to %1 failed - the secure feature key named '%2' does not exist [page 254]
08S11	Call to %1 failed - the authorization code specified for the secure feature key named '%2' is incorrect [page 251]
08S12	Call to %1 failed - the key named '%2' is the last key with the MANAGE_FEATURES and MANAGE_KEYS features [page 252]
08W01	Database server not found [page 375]
08W02	Connection not found [page 336]
08W03	Database server connection limit exceeded [page 374]
08W04	Connections to database have been disabled [page 338]

SQLSTATE	Message text
08W05	Cannot open transaction log file -- %1 [page 291]
08W06	There are still active database connections [page 818]
08W07	Unable to start database server [page 875]
08W08	Invalid database server command line [page 500]
08W09	Unable to start specified database: %1 [page 877]
08W10	Specified database not found [page 683]
08W11	Specified database is invalid [page 683]
08W12	Communication error [page 331]
08W13	Not enough memory to start [page 598]
08W14	Database name required to start server [page 369]
08W15	Client/server communications protocol version mismatch [page 322]
08W16	Database server not running in multi-user mode [page 376]
08W17	Error writing to transaction log file [page 420]
08W18	sqlpp/dblib version mismatch [page 689]
08W19	Client/database server version mismatch [page 322]
08W20	The database name 'utility_db' is reserved for the utility database [page 757]
08W21	Authentication violation [page 246]
08W22	Database page size too big: %1 [page 370]
08W23	Database server already running [page 372]
08W24	Invalid parameter [page 515]
08W25	Invalid local database option [page 510]
08W26	Dynamic memory exhausted during %1 [page 398]
08W27	Database name not unique [page 368]
08W28	Request denied -- no active databases [page 645]
08W29	Request to start/stop database denied [page 646]
08W30	The selected database is currently inactive [page 797]
08W32	Invalid database page size [page 499]
08W33	Database creation failed: %1 [page 366]
08W34	Could not load the store DLL "%1" [page 350]
08W35	Could not execute store DLL (%1) entry point [page 347]
08W36	Cannot create item (%1) in the specified dbspace [page 272]
08W37	The connection parameters file could not be found [page 752]

SQLSTATE	Message text
08W38	Error parsing connection parameter string [page 413]
08W39	No database file specified [page 588]
08W40	Database is active [page 367]
08W41	Database "%1" needs recovery [page 362]
08W42	Database upgrade failed [page 376]
08W43	Database upgrade not possible [page 377]
08W44	Could not load the backup/restore DLL "%1" [page 349]
08W45	Could not execute backup/restore DLL (%1) entry point [page 346]
08W46	Error during backup/restore: %1 [page 408]
08W47	Incorrect database store DLL (%1) version [page 477]
08W48	Authentication failed [page 246]
08W49	Parse error: %1 [page 616]
08W54	Parse error: %1 [page 617]
08W55	Server not found and unable to automatically start [page 670]
08W56	Specified database file already in use [page 682]
08W57	Database upgrade not possible; RowGenerator table not owned by user dbo [page 378]
08W58	Database upgrade not possible; user tables have table IDs in system table range [page 378]
08W59	TLS handshake failure [page 826]
08W60	Connection error: %1 [page 335]
08W61	TLS initialization on server failed [page 826]
08W62	Incorrect or missing encryption key [page 477]
08W63	Decryption error: %1 [page 387]
08W64	Database server cannot convert data from/to character set '%1' [page 373]
08W65	Client out of memory [page 321]
08W66	Encryption error: %1 [page 401]
08W67	Unable to start specified database: Server must be upgraded to start database %1 [page 885]
08W68	Unable to start specified database: Log file error [page 884]
08W69	jConnect does not support encryption [page 547]
08W70	Could not load the encryption DLL "%1" [page 350]
08W71	Parameter '%1' in procedure or function '%2' does not have a default value [page 614]

SQLSTATE	Message text
08W72	Unable to start specified database: '%1' is an invalid transaction log mirror [page 878]
08W73	Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid [page 885]
08W74	Unable to start specified database: '%1' not expecting any operations in transaction log [page 880]
08W75	Unable to start specified database: Unknown encryption algorithm [page 886]
08W76	Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing) [page 880]
08W77	Database connection limit exceeded [page 365]
08W78	Database upgrade not possible; user-defined database option "%1" conflicts with the system-defined database option with the same name [page 379]
08W79	A memory error occurred causing the profiler operation to fail [page 222]
08W80	Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file [page 882]
08W81	Unable to start specified database: '%1': transaction log file not found [page 881]
08W82	Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file [page 883]
08W83	Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently [page 883]
08W84	Unable to start specified database: Cannot use log file '%1' since it is shorter than expected [page 882]
08W85	Unable to start specified database: '%1' is not a database [page 879]
08W86	Unable to start specified database: '%1' was created by a different version of the software [page 881]
08W87	Unable to start specified database: '%1' is not a valid database file [page 879]
08W88	Unable to start specified database: '%1' is an invalid transaction log [page 878]
08W89	Unable to start database server: Server fatal error [page 877]
08W90	The DBN/DBF parameters do not match the database for this alternate server name [page 761]
08W91	Cannot connect to mirror server. Use server name '%1' to find the primary server [page 265]

SQLSTATE	Message text
08W92	Hash error: %1 [page 467]
08W93	Unable to start database %1: Cannot use read-only mode since auditing is currently logging to the transaction log [page 875]
08W94	Function '%1' has invalid parameter '%2' ('%3') [page 462]
08W95	ATTACH TRACING could not connect to the tracing database [page 242]
08W96	A tracing connection is already active [page 226]
08W97	Unable to connect: The server did not accept the requested encryption type [page 863]
08W98	Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html [page 363]
08W99	Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html [page 362]
08WA0	Password has expired [page 620]
08WA1	Password has expired but cannot be changed because the database is read-only [page 620]
08WA2	Unable to start database server: missing license file [page 876]
08WA3	The server is not able to establish TCP/IP connections [page 798]
08WA4	Client redirected more than once [page 321]
08WA5	Unable to stop specified database: %1 [page 888]
08WA6	Login redirection is required to complete the connection, but it is not supported by the client [page 565]
08WA7	Database name must be specified when connecting to a cloud database server [page 368]
08WA8	Server name can only be specified when connecting to a cloud database server with NODETYPE=DIRECT [page 670]
08WA9	Unable to load the dbrsakp shared object [page 869]
08WB1	Invalid tool name or admin user for generating security token [page 537]
08WB2	Unable to copy file %1 to destination %2 [page 864]
08WB3	Database contains users with 'SYS_' prefix and '_ROLE' suffix [page 366]
08WB4	Unable to delete file %1 [page 867]
08WB5	File %1 already exists [page 454]

SQLSTATE	Message text
08WB6	Unable to create directory %1 [page 865]
08WB7	Unable to copy file %1 [page 864]
08WB8	Database alter failed: %1 [page 363]
08WB9	File or directory %1 not found [page 455]
08WBA	Unable to clean directory %1 [page 861]
08WC1	Fail to compare %1 and %2 [page 436]
08WC2	%1 is not a directory [page 210]
08WC3	%1 and %2 must not be the same [page 205]
08WC4	Database upgrade not possible; database has auditing enabled [page 377]
08WDO	Cannot load encryption DLL %1: version mismatch [page 288]
08WD1	The address parameter "%1" conflicts with an existing %2 listener [page 747]
08WD2	%1 listener binding failure for the address parameter "%2" [page 213]
08WD3	%1 listener for the address parameter "%2" is not found [page 213]
08WD4	The last shared memory or TCPIP listener cannot be stopped without using the force parameter [page 770]
08WD5	%1 listener start option parse error: %2 [page 214]
08WD6	%1 listener start option includes an unsupported option: %2 [page 214]
08WD7	Shared memory listener already started [page 676]
08WD8	No running shared memory listener was found [page 594]
08WD9	The last HTTP or HTTPS listener cannot be stopped without using the force parameter [page 770]
08WE1	Listener type "%1" failed to initialize when starting a listener [page 556]
08WE2	Invalid address parameter "%1" provided to start a listener [page 491]
08WE3	Invalid address parameter "%1" provided to stop a listener [page 492]
08WE4	Start listener error: %1 [page 693]
08WEC	Unable to start specified database: Cannot use log file %1 since the timeline does not match the timeline of the database file [page 884]
08WEG	Address parameter "%1" is not supported to start a listener for the personal database server [page 227]

SQLSTATE	Message text
08WEH	The address parameter "%1" provided to stop a listener has an invalid IP address or no port [page 748]
08WEI	Stop listener error: %1 [page 700]
08WF1	Invalid cockpit parameter [page 495]
08WF2	Unable to find the cockpit parameters used to start or stop [page 868]
08WF4	The database '%1' cannot be used for the SQL Anywhere Cockpit [page 755]
08WF5	The SQL Anywhere Cockpit '%1' cannot be used for the current operation [page 805]
08WF6	Dialect '%1' is not supported by this database [page 390]
08WF7	The database name is reserved for SQL Anywhere Cockpit [page 757]
08WF8	Unable to start the SQL Anywhere Cockpit: %1 [page 887]
08WF9	The SQL Anywhere Cockpit template '%1' cannot be used for the current operation [page 805]
08WFA	Option '%1' cannot be used with HSQL COMPATIBLE [page 610]
08WG0	Unable to open the SQL Anywhere Cockpit template -- '%1' [page 870]
08WG1	Failed to copy the SQL Anywhere Cockpit template file '%1' to destination '%2' [page 439]
08WG2	The SQL Anywhere Cockpit template file '%1' not found [page 806]
08WG3	Unable to start the SQL Anywhere Cockpit: Please restart the server with a minimum page size of 4096 [page 887]
08WH1	Unable to start the SQL Anywhere Cockpit when it is stopping [page 886]
08WH2	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is being started [page 382]
08WH3	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is starting [page 383]
08WH4	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is active [page 381]
08WH5	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is stopping [page 383]
08WH6	Unable to stop the SQL Anywhere Cockpit when it is being started [page 888]

SQLSTATE	Message text
08WH7	Unable to upgrade the SQL Anywhere Cockpit when it is not active [page 889]
08WH8	Unable to finish upgrade the SQL Anywhere Cockpit when it is not active [page 869]
08WH9	Unable to prepare to save the SQL Anywhere Cockpit when it is not active. [page 871]
08WIO	Possible database corruption found: %1 [page 628]
08WJO	Unable to stop the SQL Anywhere Cockpit when it is being prepared to save. [page 889]
08WJ1	DBF parameter cannot be used when the SQL Anywhere Cockpit is being prepared to save. [page 381]
08WJ3	Unable to prepare to save the SQL Anywhere Cockpit when it is already being prepared. [page 872]
08WJ4	Unable to save and restart the SQL Anywhere Cockpit when it is not prepared. [page 873]
08X01	Invalid options for UPGRADE: SCRIPT FILE can only be specified with RESTART [page 513]
08X02	Statement %1 disallowed during upgrade from script [page 694]
09W02	Illegal cursor operation attempt [page 472]
09W03	Result set not permitted in '%1' [page 652]
09W04	INSERT/DELETE on cursor can modify only one table [page 486]
09W05	Cannot uniquely identify rows in cursor [page 304]
09W06	Cursor is restricted to FETCH NEXT operations [page 357]
09W07	Statement's size limit is invalid [page 700]
09W08	Cannot update or delete an all-NULL row from table '%1' [page 307]
0A000	Feature '%1' not implemented [page 451]
0A001	The method you attempted to invoke was not enabled for your application [page 780]
0A002	This server is not licensed to support the '%1' feature [page 824]
0A003	This server is not licensed to support '%1' connections [page 824]
0A004	This edition of SQL Anywhere is not available on this platform [page 823]
0A007	Use of table privilege '%1' is not supported on the current database [page 905]
0AW01	Language extension [page 552]

SQLSTATE	Message text
OAW02	Transact-SQL feature not supported [page 847]
OAW03	Disallowed language extension detected in syntax near '%1' on line %2 [page 391]
)AW04	Feature '%1' not supported [page 451]
OAW05	Statement is not allowed in passthrough mode [page 696]
OAW06	Computed columns are not supported in this database [page 333]
OAW07	Feature not available with UltraLite [page 452]
OAW08	You cannot synchronize or upgrade with uncommitted transactions [page 933]
OAW09	Synchronization server failed to commit the upload [page 716]
OAW0A	Feature '%1' is not supported for this database [page 450]
OAW10	DTC transactions are not supported on this platform [page 395]
OAW11	Download failed because of conflicts with existing rows on table '%1' (row: %2) [page 393]
OAW12	Synchronization failed due to an error on the MobiLink server: %1 [page 709]
OAW13	Cannot change synchronization user_name when status of the last upload is unknown [page 261]
OAW14	Plan cannot be generated for this type of statement [page 625]
OAW15	Support for materialized views is not available for this database [page 706]
OAW16	The %1 algorithm is not available in FIPS mode [page 743]
OAW17	Cannot change the MobiLink remote ID when the status of the last upload is unknown [page 262]
OAW18	The remote data access feature is not supported on this platform [page 791]
OAW19	Feature not supported by the client version or the client interface [page 453]
OAW22	Support for permissions on dbspaces is not available for this database [page 707]
OAW23	Synchronization download failed to complete [page 708]
OAW24	Synchronization is already in progress [page 711]
OAW26	Download failed due to an invalid or unsupported row value [page 393]
OAW27	System Privileges and Roles feature is not supported in this database [page 719]

SQLSTATE	Message text
OAW28	Collection types not supported [page 323]
OAW29	The PAM User Authentication (PAMUA) feature is not supported on this computer [page 787]
OAW30	Table reference types not supported [page 733]
OAW31	Indirect identifiers not supported [page 483]
OAW32	Cannot specify read only in both the READ ONLY clause and the USING clause [page 301]
OAW33	SQL statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 688]
OAW34	SQL statements in BEGIN PARALLEL WORK...END PARALLEL WORK statement are not of the same type [page 687]
OAW35	When wait_for_commit database option is enabled, LOAD TABLE statement is not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 925]
OAW36	Load-source for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 557]
OAW37	Logging type ('%1') for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 562]
OAW38	WITH CHECKPOINT ON clause for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 928]
OAW39	Function-name clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 463]
OAW40	'%1' for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 207]
OAW41	VIRTUAL clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 923]
OAW42	Table '%1' for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 721]
OAW43	Text index \"%1\" on table \"%2\" exists. Table with text index is not supported for LOAD TABLE statement in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 739]
OAW44	Cannot create a proxy table LIKE another table [page 270]
OAW48	Offline reset password not supported [page 603]
OAW49	The profiler is not supported [page 790]

SQLSTATE	Message text
OAWD5	MobiLink communication error -- code: %1, parameter: %2, system code: %3 [page 578]
OEW00	Table '%1' has no columns [page 722]
OEW01	Index '%1' has no columns [page 480]
21000	SELECT returns more than one row [page 665]
21W01	Subquery cannot return more than one row [page 703]
21W02	Number of columns defined for the table does not match SELECT statement [page 600]
22001	Right truncation of string data [page 653]
22002	No indicator variable provided for NULL result [page 590]
22003	Value %1 out of range for destination [page 918]
22005	Error in assignment [page 409]
2200B	Escape character conflict '%1' [page 421]
2200C	Invalid use of escape character '%1' [page 541]
22012	Division by zero [page 392]
22019	Invalid escape character '%1' [page 503]
2201B	Invalid regular expression: %1 in '%2' [page 524]
22024	Unterminated C string [page 901]
22025	Invalid escape sequence '%1' [page 503]
2202E	Array element error: array index '%1' is out of range [page 241]
22030	Cannot return NULL result as requested data type [page 297]
22031	Invalid start value for semaphore "%1": %2 [page 533]
22032	Invalid increment value for semaphore "%1": %2 [page 509]
22033	Invalid timeout value %1 [page 536]
22W02	Row has changed since last read -- operation canceled [page 656]
22W03	Invalid TEXTPTR value used with WRITETEXT or READTEXT [page 535]
22X13	Invalid preceding or following size in OLAP function [page 520]
23501	Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3 [page 326]
23502	Column '%1' in table '%2' cannot be NULL [page 325]
23503	No primary key value for foreign key '%1' in table '%2' [page 593]

SQLSTATE	Message text
23504	Number of columns allowing NULLs exceeds limit [page 600]
23505	Index '%1' for table '%2' would not be unique [page 479]
23506	Constraint '%1' violated: Invalid value for column '%2' in table '%3' [page 339]
23507	The specified foreign key (%1) cannot be enforced [page 801]
23508	Constraint '%1' violated: Invalid value in table '%2' [page 340]
23509	MERGE statement ANSI cardinality violation on table '%1' [page 569]
23510	MERGE statement for table '%1' failed because of a RAISEROR specification in the statement [page 569]
23W01	Primary key for table '%1' is not unique: Primary key value ('%2') [page 631]
23W05	Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3' [page 630]
24000	Cursor not in a valid state [page 357]
24001	Value-sensitive cursor used after a TRUNCATE [page 920]
24501	Cursor not open [page 358]
24502	Cursor already open [page 356]
24503	No current row of cursor [page 587]
24504	Invalid scroll position '%1' [page 526]
24W01	Cursor has not been declared [page 356]
26501	SQL statement error [page 687]
28000	Invalid user ID or password [page 542]
28W25	Invalid user ID or role name '%1' specified [page 543]
28W26	Role "%1" already exists [page 654]
28W27	User or Role ID '%1' does not exist [page 913]
28W28	Use of WITH NO SYSTEM PRIVILEGE INHERITANCE option is not allowed with %1 [page 906]
28W29	Operation would cause a role cycle [page 610]
28W30	Specified System Privilege '%1' is Invalid [page 686]
28W31	Specified LDAP server '%1' is not found [page 684]
28W32	Specified user '%1' is a role [page 686]
28W33	Specified role '%1' is not a user extended as role [page 685]
28W34	Specified role '%1' is a user extended as role [page 685]
28W35	Use of WITH DROP OBJECTS is not allowed with '%1' [page 905]

SQLSTATE	Message text
28W36	The role '%1' was not dropped because it is granted to other users or roles. Use the 'WITH REVOKE' option to drop it [page 793]
28W37	JWT Provider '%1' does not exist [page 549]
28W40	Offline reset password failed: %1 [page 602]
28W41	Offline reset password is not allowed for user ID '%1' that has no password [page 603]
28W01	Invalid user ID or password on preprocessed module [page 543]
28W02	Integrated logins are not permitted [page 488]
28W03	Integrated logins are required, standard logins are not permitted [page 489]
28W04	Integrated login failed [page 488]
28W05	Integrated logins are not supported for this database [page 489]
28W06	The integrated login ID guest can only be mapped to the guest database user ID [page 768]
28W07	Cannot map a login ID to the sys or public user ID [page 289]
28W08	The login ID '%1' is already mapped to user ID '%2' [page 774]
28W09	The login ID '%1' has not been mapped to any database user ID [page 773]
28W10	Too many distinct group mappings for integrated user [page 832]
28W11	Invalid password: %1 [page 516]
28W12	Kerberos login failed [page 550]
28W13	Kerberos logins are not supported [page 550]
28W14	Login mode '%1' not permitted by login_mode setting [page 563]
28W15	Connection disallowed by login policy for this user [page 335]
28W17	The synchronization failed because MobiLink returned authentication status '%1' with value '%2' [page 809]
28W18	Task '%1' is not allowed [page 734]
28W19	No more role grant permitted [page 591]
28W20	Cannot change password because change_password_dual_control process is in progress [page 260]
28W21	change_password_dual_control is enabled for this user. Use ALTER USER to change password [page 312]

SQLSTATE	Message text
28W22	TDS login requests with unencrypted passwords are not permitted [page 736]
28W23	TDS login requests with RSA encrypted passwords must also use a nonce [page 735]
28W24	Temporary mutex or semaphore can only be dropped by the connection that created it [page 736]
2D501	COMMIT/ROLLBACK not allowed within trigger actions [page 331]
2FF04	Invalid intersection matrix '%1' [page 509]
2FF05	Point is duplicated %1 [page 626]
2FF06	Element is an empty set (near '%1') [page 399]
2FF10	Mixed spatial reference systems %1 and %2 (near %3) [page 577]
2FF11	Non-contiguous curves near '%1' [page 596]
2FF14	Unknown unit of measure '%1' [page 897]
2FF15	Failed to transform geometry (error %1) [page 447]
2FF16	Cannot convert from %1 to %2 (near %3) [page 268]
2FF17	Failed to transform point %1 (error %2) [page 447]
2FF22	Error parsing well-known-text (WKT) scanning '%1' at offset %2 [page 418]
2FF23	Error parsing well-known-binary (WKB) at offset %1 [page 415]
2FF25	Mixed coordinate dimensions [page 577]
2FF59	Unknown spatial reference system (%1) [page 896]
2FF71	An ST_CircularString cannot be constructed from %1 points (near '%2') [page 238]
2FF72	The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points [page 769]
2FW02	Support for spatial is not available for this database [page 708]
2FW03	Spatial feature %1 is not supported [page 678]
2FW05	Error parsing well-known-text (WKT): inconsistent dimensions at offset %1 [page 419]
2FW06	Error parsing geometry internal serialization at offset %1 [page 414]
2FW08	Error parsing well-known-binary (WKB): type code %1 at offset %2 is invalid [page 417]
2FW09	Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent [page 417]

SQLSTATE	Message text
2FW10	Error parsing well-known-binary (WKB): unexpected end of input [page 418]
2FW11	Error parsing well-known-binary (WKB): inconsistent dimensions at offset %1 [page 416]
2FW12	Error parsing well-known-binary (WKB): invalid byte order mark %1 at offset %2 [page 416]
2FW13	Error parsing shapefile record [page 415]
2FW14	Error parsing shapefile attributes [page 414]
2FW15	Invalid shapefile filename [page 530]
2FW16	The multi patch shapefile shape is not supported [page 782]
2FW19	The embedded SRID (%1) conflicts with the provided SRID (%2) [page 762]
2FW20	The embedded SRID are inconsistent (%1 and %2) [page 763]
2FW21	The format type '%1' is not recognized [page 765]
2FW22	The format type '%1' cannot be used here [page 765]
2FW23	An input string in '%1' format cannot be used here [page 234]
2FW24	The format specification syntax is invalid [page 764]
2FW25	The format specification option '%1' is not recognized [page 764]
2FW26	The value '%2' is not a valid setting for the '%1' format specification option [page 815]
2FW27	The data is not in a recognized format [page 754]
2FW28	A geometry with SRID=%1 is not supported for method %2 [page 221]
2FW29	A geometry with SRID=%1 is not supported when computing distance between non-point geometries [page 222]
2FW31	Error reading configuration file [page 420]
2FW32	Invalid configuration name %1 [page 497]
2FW33	The comparison '%1' cannot be used with geometries [page 752]
2FW34	Invalid spatial reference system well-known-text (WKT) [page 530]
2FW35	Invalid transform definition '%1' [page 537]
2FW36	Transform definition is too long [page 849]
2FW37	Transform from SRID %1 to %2 not supported [page 850]
2FW38	Transform from SRID %1 not supported [page 849]
2FW39	Unit of measure "%1" is not a linear unit [page 891]

SQLSTATE	Message text
2FW40	Unit of measure "%1" is not an angular unit [page 892]
2FW41	Invalid polygon format '%1' [page 516]
2FW42	Invalid polygon: no exterior ring [page 518]
2FW43	Invalid polygon nesting [page 517]
2FW44	Invalid polygon: multiple exterior rings [page 518]
2FW45	Table '%1' contains a spatial column '%2' and no primary key [page 720]
2FW46	Spatial column '%1' cannot be included in a primary key or unique index [page 677]
2FW47	Spatial column '%1' cannot be included in an index because it is not constrained to a single SRID [page 678]
2FW48	The CONVERT USING clause must be specified when creating a unit of measure [page 753]
2FW49	The string '%1' is not a valid axis order [page 808]
2FW50	The string '%1' is not a valid coordinate name [page 808]
2FW51	Unit of measure '%1' not found [page 893]
2FW52	Spatial reference system '%1' not found [page 681]
2FW53	Unit of measure '%1' already exists [page 892]
2FW54	Spatial reference system '%1' already exists [page 680]
2FW55	Spatial reference system must specify the SRID to use [page 681]
2FW56	Error parsing definition string '%1' [page 413]
2FW57	The spatial reference system type is not supported ('%1') [page 799]
2FW58	Ellipsoid parameters missing for geographic spatial reference system [page 400]
2FW59	Ellipsoid parameters specified for non-geographic spatial reference system [page 400]
2FW60	Coordinate bounds missing for coordinate %1 [page 342]
2FW61	The specified axis order is not supported for this type of spatial reference system [page 800]
2FW62	The specified polygon format '%1' is not supported for this type of spatial reference system [page 803]
2FW63	Invalid storage format '%1' [page 534]
2FW64	Spatial reference system %1 cannot be modified because it is in use [page 680]
2FW65	Spatial reference system "%1" is reserved [page 679]
2FW66	Spatial unit of measure "%1" is reserved [page 682]

SQLSTATE	Message text
2FW67	SRID %1 is referenced by column '%2' of table '%3' [page 690]
2FW68	SRID %1 is referenced by parameter '%2' of procedure '%3' [page 691]
2FW69	SRID %1 is referenced by domain "%3"."%2" [page 690]
2FW70	The SRID %1 does not identify a geographic spatial reference system [page 807]
2FW71	ST_Geometry arguments not supported by SQL function %1 [page 691]
2FW72	An expression of type %1 is not union-compatible with type %2 [page 233]
2FW73	An internal error has occurred in the spatial library [page 235]
2FW77	Curve contains nearly antipodal points %1 and %2 (near '%3') [page 359]
2FW78	LineString must contain at least 2 points (near '%1') [page 556]
2FW79	Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%) [page 917]
2FW80	Invalid polygon: ring is not closed (near '%1') [page 520]
2FW81	Invalid polygon: ring has zero area (near '%1') [page 519]
2FW82	Invalid polygon: curve is not a ring [page 517]
2FW83	Invalid polygon: ring is larger than allowed for SRID=%1 (near '%2') [page 519]
2FW84	Geometries with CircularString not supported (near "%1") [page 465]
2FW85	Geometries with CircularString are not supported in spatial reference system %1 [page 464]
2FW86	Invalid grid size %1 [page 507]
2FW87	Invalid tolerance %1 [page 536]
2FW88	Invalid bounds for coordinate %1 (near "BETWEEN %2 AND %3") [page 494]
2FW89	ST_MultiSurface contains elements with an invalid intersection (near "%1") [page 692]
2FW90	Operation not supported for ST_GeomCollection with intersecting elements (near "%1") [page 609]
2FW91	Support for spatial is not available for this CPU [page 707]
2FW92	Geometry expressions cannot be used in the ORDER BY specification (near '%1') [page 465]
2FW93	Function '%1' has invalid parameter '%2' ('%3') [page 462]

SQLSTATE	Message text
33000	Invalid SQL descriptor name [page 531]
37505	Wrong number of parameters to function '%1' [page 929]
38W01	System command failed with return code %1 [page 718]
3B001	Savepoint '%1' not found [page 660]
3B002	ROLLBACK TO SAVEPOINT not allowed [page 655]
3BW01	Savepoints require a rollback log [page 661]
3BW02	Result set not allowed from within an atomic compound statement [page 651]
40000	Run time SQL error -- %1 [page 659]
40001	Deadlock detected [page 385]
40002	Deadlock involving a mutex detected [page 385]
40W01	Internal database error %1 -- transaction rolled back [page 490]
40W02	Terminated by user -- transaction rolled back [page 738]
40W03	Disk full '%1' -- transaction rolled back [page 391]
40W04	I/O error %1 -- transaction rolled back [page 469]
40W05	Disk write failure '%1' -- transaction rolled back [page 392]
40W06	All threads are blocked [page 230]
40W07	Connection was terminated [page 337]
40W08	Memory error -- transaction rolled back [page 568]
40W10	Operation failed - could not complete checkpoint [page 606]
42501	Permission denied: %1 [page 622]
42R01	Referential integrity actions other than RESTRICT not allowed for temporary tables [page 640]
42R02	Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared [page 733]
42R03	Key constraint between temporary tables requires a primary key (not unique constraint) [page 551]
42R04	Foreign key columns do not match the primary key or a uniqueness constraint in "%1" [page 457]
42U00	View references '%1', which is a temporary object. Views can only refer to permanent objects [page 923]
42U01	Illegal reference to correlation name '%1' [page 474]
42U02	Owner '%1' used in a qualified column reference does not match correlation name '%2' [page 613]
42U03	SET clause for column '%1' used incorrectly [page 675]

SQLSTATE	Message text
42U04	Constraint '%1' not found [page 339]
42U05	Attempt to alter unnamed column constraint when named constraints exist [page 244]
42U06	Invalid reference to or operation on constraint '%1' [page 523]
42U07	Invalid hint specified for table '%1' [page 507]
42U08	Duplicate options not allowed in the CREATE DATABASE statement [page 398]
42U09	Outer reference not permitted in DML derived table [page 612]
42U10	Cannot create global temporary table '%1': A base table with the same name exists [page 271]
42U11	Cannot create base table '%1': A global temporary table with the same name exists [page 271]
42U12	Cannot create table '%1': Name is used by a non-table object [page 275]
42U20	DBA user ID must be specified in the CREATE DATABASE statement [page 380]
42U21	DBA password must be specified in the CREATE DATABASE statement [page 380]
42U35	Cannot create mutex "%1": %2 with this name already exists [page 273]
42U36	Cannot create semaphore "%1": %2 with this name already exists [page 274]
42U37	Cannot create semaphore "%1" as a temporary semaphore with this name already exists [page 273]
42U38	Cannot create mutex "%1" as a temporary mutex with this name already exists [page 272]
42U47	Duplicate options not allowed in %1!s! [page 397]
42U48	Cannot use both the OR REPLACE and IF NOT EXISTS clauses [page 308]
42W01	User '%1' already has GRANT OPTION [page 907]
42W02	Operation would cause a group cycle [page 609]
42W03	User '%1' is not a user group [page 910]
42W04	Syntax error near '%1' %2 %3 [page 717]
42W05	Unknown function '%1' [page 895]
42W06	Invalid use of an aggregate function [page 539]
42W07	Invalid host variable [page 508]
42W08	Invalid expression near '%1' [page 505]

SQLSTATE	Message text
42W09	SETUSER not allowed in procedures, triggers, events, or batches [page 675]
42W10	Invalid DEFAULT value near '%1' on line %2 [page 501]
42W11	Invalid value for INSERT near '%1' on line %2 [page 544]
42W13	Invalid column number [page 495]
42W14	Variable '%1' not found [page 920]
42W15	There is already a variable named '%1' [page 819]
42W16	Invalid option '%1' -- no PUBLIC setting exists [page 513]
42W17	Invalid setting for option '%1' [page 529]
42W18	User '%1' has the row in '%2' locked [page 908]
42W19	Not allowed while '%1' is using the database [page 596]
42W20	CHECKPOINT statement requires a rollback log [page 316]
42W21	Table in use [page 729]
42W22	Attempted two active database requests [page 245]
42W23	Procedure in use by '%1' [page 635]
42W24	Label '%1' not found [page 551]
42W25	Invalid absolute or relative offset in FETCH [page 491]
42W26	Wrong number of variables in FETCH [page 930]
42W28	COMMIT/ROLLBACK not allowed within atomic operation [page 330]
42W29	Procedure or trigger calls have nested too deeply [page 635]
42W30	Update operation attempted on a read-only cursor [page 902]
42W31	Update operation attempted on non-updatable query [page 902]
42W32	Cannot modify column '%1' in table '%2' [page 289]
42W33	Table '%1' not found [page 726]
42W34	User '%1' already has membership in group '%2' [page 908]
42W35	Update operation attempted on non-updatable remote query [page 903]
42W36	FOR UPDATE has been incorrectly specified for a READ ONLY cursor [page 456]
42W37	Cannot update column '%1' since it appears in the ORDER BY clause [page 305]
42W38	Cannot update column '%1' since it does not appear in the SELECT clause [page 305]
42W39	Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1' [page 334]

SQLSTATE	Message text
42W3A	Operation failed because table or view '%1' has an INSTEAD OF trigger [page 607]
42W3B	Positioned update operation attempted on a view with an INSTEAD OF trigger [page 627]
42W3C	Invalid trigger type for view '%1' [page 538]
42W3D	Triggers cannot be created on materialized view '%1' [page 853]
42W40	Duplicate referencing column [page 398]
42W41	Duplicate insert column [page 396]
42W42	Parameter name missing in call to procedure '%1' [page 615]
42W43	Only PUBLIC settings are allowed for option '%1' [page 605]
42W44	Dropping all columns from table '%1' is not allowed [page 394]
42W45	Cannot set a temporary option for user '%1' [page 299]
42W46	You do not have '%1' system privilege or authority to set the option '%2' [page 935]
42W47	Parameter '%1' not found in procedure '%2' [page 615]
42W49	TRUNCATE TABLE statement cannot be used on a view [page 854]
42W50	READTEXT or WRITETEXT statement cannot refer to a view [page 638]
42W51	VALIDATE statement must refer to a base table [page 917]
42W52	The option '%1' can only be set as a temporary option [page 784]
42W53	The option '%1' cannot be set from within a procedure [page 785]
42W54	Signature '%1' does not match procedure parameters [page 676]
42W55	User owns procedures in use [page 913]
42W56	User owns tables in use [page 914]
42W57	External object '%1' not found [page 435]
42W58	JAR '%1' not found [page 546]
42W59	The SELECT list for the derived table '%1' has no expression to match '%2' [page 796]
42W60	Alias '%1' is not unique [page 229]
42W61	Definition for alias '%1' must appear before its first reference [page 388]
42W62	Row in table '%1' was modified or deleted in BEFORE trigger [page 657]

SQLSTATE	Message text
42W63	Procedure '%1' is no longer valid [page 632]
42W64	Trigger or foreign key for table '%1' is no longer valid [page 853]
42W65	Function or column reference to '%1' in the ORDER BY clause is invalid [page 463]
42W66	Trigger name '%1' is ambiguous [page 852]
42W67	CREATE/DROP STATISTICS statement cannot refer to virtual tables [page 354]
42W68	Aggregated expression '%1' contains multiple columns of which one or more are outer references [page 228]
42W69	The aggregate expression '%1' must appear in either the SELECT list or a HAVING clause subquery [page 748]
42W70	Grouped query contains more than one distinct aggregate function [page 466]
42W71	Statement contains an illegal usage of the NUMBER(*) function [page 695]
42W73	There is no way to join to '%1' [page 821]
42W74	Index '%1' cannot be clustered [page 478]
42W75	Synchronization profile '%1' not found [page 714]
42W76	Synchronization profile '%1' already exists [page 713]
42W77	Synchronization profile '%1' has invalid parameter '%2' [page 714]
42W78	Synchronization profiles are not supported for this database [page 715]
42W79	Statement contains an illegal usage of the non-deterministic function '%1' [page 695]
42W7B	The database must be upgraded to use the KEY option on the SYNCHRONIZE command [page 756]
42W80	Another connection has the row in '%1' locked [page 239]
42W82	Cannot delete PUBLIC option '%1' since user settings exist [page 276]
42W83	Invalid setting for HTTP option '%1' [page 528]
42W84	Invalid setting for HTTP header '%1' [page 528]
42W85	'%1' is an invalid value for '%2' [page 208]
42W86	Invalid setting for SOAP header '%1' [page 529]
42W89	More articles are being dropped from publication '%1' than are defined [page 579]
42W90	Illegal ORDER BY in aggregate function [page 473]
42W91	Cannot turn on auditing: The audit settings currently require a transaction log file [page 303]

SQLSTATE	Message text
42W92	Service type required for CREATE SERVICE [page 674]
42W93	Cycle in common table expression references [page 360]
42W94	'%1' is an unrecognized service type [page 210]
42W95	Invalid service name '%1' [page 527]
42W96	A user name must be specified if AUTHORIZATION is Off [page 226]
42W97	Service '%1' already exists [page 671]
42W98	Service '%1' not found [page 672]
42W99	Invalid recursive query [page 522]
42W9A	No column list for recursive query [page 587]
42W9B	Host variable reference in service definition must be named [page 468]
42W9C	Service statement definition is inconsistent with service type [page 673]
42W9D	Constant expressions must not appear in GROUP BY clause [page 338]
42W9E	Service definition requires a statement when authorization is off [page 672]
42WA0	Recursion is not allowed without the RECURSIVE keyword [page 639]
42WA1	Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation [page 833]
42WA2	Recursive column %1: conversion from '%2' to '%3' loses precision [page 640]
42WA3	Window '%1' not found [page 926]
42WA4	PARTITION BY not allowed in reference to window '%1' [page 618]
42WA5	ORDER BY not allowed in window '%1' [page 611]
42WA6	Frame not allowed for window '%1' [page 461]
42WA7	Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause [page 240]
42WA8	Window function used in predicate [page 927]
42WA9	Window function requires ORDER BY [page 926]
42WAA	Composite ORDER BY not allowed with RANGE [page 332]
42WAB	User '%1' already has EXECUTE permission [page 907]
42WAC	Too many arguments for function or procedure '%1' [page 828]
42WAD	Invalid value for attribute '%1' in service [page 544]

SQLSTATE	Message text
42WAE	Missing value for attribute '%1' in service [page 576]
42WAF	Unsupported property '%1' in service USING attribute [page 900]
42WB0	Duplicate attribute '%1' in service [page 396]
42WB1	USING attribute cannot coexist with FORMAT or GROUP attributes [page 916]
42WB2	Service type does not allow '%1' attribute [page 674]
42WB3	Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2' [page 717]
42WB4	Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2' [page 718]
42WB5	Materialized View '%1' not found [page 566]
42WB6	Cannot create a materialized view because option '%1' has an inappropriate setting [page 269]
42WB7	Cannot update materialized view because option '%1' has an inappropriate setting [page 306]
42WB8	Table created or altered after start of snapshot [page 729]
42WB9	Statement not allowed during snapshot [page 697]
42WBA	Update conflict on snapshot transaction [page 901]
42WBB	Attempt to use snapshot isolation in a non-snapshot transaction [page 245]
42WBC	Cannot use materialized view '%1' because it has not yet been initialized [page 309]
42WBD	Cycle in computed column dependencies [page 360]
42WBE	Cannot revoke these permissions while user '%1' is actively replicating transactions [page 297]
42WBF	Correlation name '%1' is not valid for use with the ROWID function [page 342]
42WC0	Duplicate key column (%1) [page 397]
42WC1	Table '%1' contains an invalid reference to the ROWID function [page 720]
42WC2	The '%1' property is no longer supported [page 746]
42WC3	The materialized view %1 cannot be changed to immediate because it has already been initialized [page 775]
42WC4	Unable to acquire table locks in specified time [page 860]
42WC5	The materialized view cannot be changed to immediate because its definition must not contain more than one query block [page 777]

SQLSTATE	Message text
42WC6	The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list [page 776]
42WC7	The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate, non-nullable columns [page 776]
42WC8	Maintenance of dependent immediate materialized view(s) failed [page 566]
42WC9	Attempt to start a second snapshot in a transaction [page 244]
42WCA	The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns [page 774]
42WCB	The materialized view cannot be changed to immediate because its definition contains an illegal construct [page 777]
42WCC	Service statement definition is invalid or unsupported [page 673]
42WCD	Immediate materialized view definition cannot contain a SUM function over a nullable expression [page 475]
42WCE	The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression [page 778]
42WD3	Must own table '%1' to make an immediate view reference it [page 582]
42WD4	FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR) [page 456]
42WD5	The user name specified must be the user name of the current connection [page 813]
42WD6	Transact-SQL expression in a non-Transact-SQL statement near '%1' %2 [page 846]
42WE0	The function '%1' does not allow use of the '%2' clause [page 766]
42WE1	The function '%1' requires the use of the '%2' clause [page 766]
42WE2	User owns sequences in use [page 914]
42WE3	Sequence '%1' in use by another connection [page 667]
42WE4	The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN [page 778]
42WE5	VERIFY and RENAME cannot be used together [page 921]
42WE6	Mirror server "%1" defined with type COPY does not include a parent definition [page 573]

SQLSTATE	Message text
42WE7	The materialized view cannot be changed to immediate because the ON conditions refer to tables which are not in the null-supplying and preserved sides of the OUTER JOINS [page 779]
42WE8	The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list [page 775]
42WE9	The materialized view cannot be changed to immediate because the primary key columns of any table in the preserved side of an OUTER JOIN must exist in the SELECT list [page 780]
42WE10	VERIFY and FOR REPLICATION cannot be used together [page 921]
42WE11	RECOVER UNTIL and FOR REPLICATION cannot be used together [page 639]
42WF0	Procedure is currently being altered or dropped [page 635]
42WF1	CATALOG ONLY and MULTIPLEX cannot be used together [page 311]
42WF2	Cannot change the mirror server type from %1 to %2 [page 262]
42WF3	Cannot convert value to a timestamp [page 269]
42WF4	The USING LOG PATH clause must be used in conjunction with the RECOVER UNTIL clause [page 814]
42WF5	User owns locked mutexes [page 913]
42WF6	Procedure '%1' needs a RESULT clause for returned ROW or ARRAY [page 633]
42WF7	PBKDF2 error: %1!s! [page 622]
42WF8	Table '%1' specified more than once in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 727]
42X00	Type '%1' does not support method calls (near '%2') [page 856]
42X01	Type '%1' has no method named '%2' (near '%3') [page 856]
42X02	Method invocation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 571]
42X03	Type '%1' is not instantiable (near '%2') [page 857]
42X04	Method '%1' cannot be called with %2 arguments (near '%3') [page 570]
42X05	Type '%1' cannot be instantiated with %2 arguments (near '%3') [page 855]
42X06	The instantiation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 768]

SQLSTATE	Message text
42X07	Expression is not an array [page 428]
42X08	The variable '%1' must not be NULL in this context [page 817]
42X09	The variable '%1' must be %2 in this context [page 816]
42X10	Host variables must not be used in this context [page 468]
42X11	Table reference '%1' has been invalidated [page 732]
42X12	Expression of type %1 is not allowed in this context (near: %2) [page 429]
42X13	Indirect identifier `[%1]` yielded an invalid identifier name '%2' [page 483]
42X14	Scalar variable '%1' not found [page 661]
42X15	RESTORE statement missing a FROM clause [page 648]
42X16	Cannot use CLEAR LOG clause with offline log backups [page 309]
42X17	Unsupported extended storage syntax [page 899]
44000	WITH CHECK OPTION violated for insert/update on base table '%1' [page 927]
52002	Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name [page 324]
52003	Column '%1' not found [page 326]
52004	Derived table '%1' has no name for column %2 [page 389]
52005	Column '%1' not found in table '%2' [page 327]
52006	Column '%1' not found in variable '%2' [page 327]
52009	Primary key column '%1' already defined [page 630]
52010	Item '%1' already exists [page 546]
52012	More than one table is identified as '%1' [page 580]
52W02	Correlation name '%1' not found [page 343]
52W03	Cannot find index named '%1' [page 285]
52W04	Index name '%1' not unique [page 481]
52W05	Table cannot have two primary keys [page 728]
52W06	Foreign key '%1' for table '%2' duplicates an existing foreign key [page 457]
52W07	Foreign key name '%1' not found [page 458]
52W08	There is more than one way to join '%1' to '%2' [page 819]
52W09	Procedure '%1' not found [page 633]
52W10	Trigger '%1' not found [page 851]

SQLSTATE	Message text
52W11	Trigger definition conflicts with existing triggers [page 852]
52W12	Invalid REFERENCES clause in trigger definition [page 523]
52W13	DbSPACE '%1' not found [page 384]
52W14	Table '%1' is in an outer join cycle [page 724]
52W15	Table '%1' requires a unique correlation name [page 727]
52W16	User message %1 already exists [page 912]
52W17	User message %1 not found [page 912]
52W18	User-defined type '%1' not found [page 915]
52W19	DbSPACE for table '%1' not found [page 384]
52W20	Too many columns in table [page 831]
52W21	Data definition statements not allowed in procedures or triggers [page 361]
52W22	GRANT of column permission on view not allowed [page 466]
52W23	Invalid expression in WHERE clause of Transact-SQL outer join [page 504]
52W24	Invalid join type used with Transact-SQL outer join [page 510]
52W25	Invalid comparison [page 496]
52W26	Invalid commit action for shared temporary table [page 496]
52W40	Index name '%1' is ambiguous [page 480]
52W41	Too many temporary tables in connection [page 838]
52W42	Table name '%1' is ambiguous [page 730]
52W43	Default dbSPACE '%1' not found [page 387]
52W44	Sequence '%1' not found [page 667]
52W45	Sequence name '%1' is ambiguous [page 668]
52W46	Invalid operation '%2' on sequence '%1' [page 512]
52W47	Sequence '%1' already exists [page 666]
52W48	No more values available in sequence %1 [page 591]
52W49	Definition for sequence '%1' is invalid [page 389]
52W50	Multiple settings of same option specified for sequence '%1' [page 581]
52W51	The 'CURVAL' operator is not defined yet for sequence '%1' for this connection [page 746]
52W52	Sequence generators are not supported for this database [page 668]

SQLSTATE	Message text
52W53	Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database [page 891]
52W54	Cannot specify range that excludes next value for sequence %1 [page 300]
53002	Wrong number of values for INSERT [page 929]
53003	Function or column reference to '%1' must also appear in a GROUP BY [page 464]
53005	Invalid ORDER BY specification [page 514]
53011	Number of columns defined for the view does not match SELECT statement [page 601]
53017	Cannot convert %1 to %2. The bad value was supplied for column '%3' on row %4 of the data file [page 266]
53018	Cannot convert %1 to %2 [page 266]
53019	Return type of void from procedure '%1' cannot be used in any expression [page 653]
53020	TREAT AS can only be used with extended types. Cannot treat %1 as a %2 [page 851]
53021	Cannot treat value '%1' as type %2. The dynamic type is %3 [page 303]
53023	Subquery allowed only one SELECT list item [page 703]
53026	Select lists in UNION, INTERSECT, or EXCEPT do not match in length [page 664]
53030	Column '%1' in foreign key has a different definition than primary key [page 325]
53031	PIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 623]
53032	Invalid generated identifier '%1' [page 506]
53033	UNPIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 898]
53034	PIVOT error: only one aggregate function can be specified without an alias [page 623]
53036	PIVOT error: Too many aggregate functions and IN clause items [page 624]
53037	PIVOT error: PIVOT XML does not contain a valid subquery, ANY, or ALL in the IN clause [page 624]
53038	UNPIVOT error: Cannot create valid identifiers for IN clause items [page 898]
53W01	ALTER clause conflict [page 230]
53W02	Cannot update an expression [page 304]
53W04	There is no way to join '%1' to '%2' [page 820]

SQLSTATE	Message text
53W05	Cannot alter a column in an index [page 258]
53W06	Cannot delete or rename a column referenced in a trigger definition [page 276]
53W07	Error number %1 for RAISERROR must not be less than 17000 [page 412]
53W08	Format string argument number %1 is invalid [page 459]
53W09	Invalid data type for column in WRITETEXT or READTEXT [page 499]
53W10	Format string contains invalid format specifiers: '%1' [page 460]
53W11	Format string contains more than %2 format specifiers: '%1' [page 460]
54003	Identifier '%1' too long [page 470]
54W01	Statement size or complexity exceeds server limits [page 699]
54W02	Too many constraints in database [page 832]
54W03	Database page size too small: %1 [page 371]
54W04	The specified listener could not be registered [page 802]
54W05	Temporary space limit exceeded [page 737]
54W06	The string is too long (%1) [page 809]
54W07	Password must be at least %1 characters [page 621]
54W08	Password cannot be longer than %1 characters [page 619]
54W09	The size of the character column, variable, or value data type exceeds 32767 [page 799]
54W10	Too many users in database [page 839]
54W11	Too many references to a BLOB [page 836]
54W12	Too many open cursors [page 835]
54W13	Too many columns in SELECT list [page 831]
54W14	Too many expressions in GROUP BY list [page 833]
54W15	Too many columns in procedure result set [page 829]
54W16	Too many MESSAGE...FOR CONNECTION messages [page 834]
54W17	Maximum string length exceeded [page 568]
54W18	The length of the variable '%1' is too long in this context; it exceeds the limit of %2 bytes [page 771]
54W19	Statement requires too much memory during %1 [page 698]
54W20	Too many tables in query [page 837]
54W21	Too many columns in schema [page 830]

SQLSTATE	Message text
54W22	Too many columns in row type [page 830]
54W23	Array contains too many elements [page 241]
54W24	IN-list is too long [page 476]
54W50	Virtual index creation with more than %1 columns [page 924]
54W51	Reorganize table is already being run on table "%1" [page 645]
54W52	Invalid domain '%1' [page 502]
54W53	REORGANIZE TABLE ran out of space [page 645]
54W54	Reading %1 database pages exceeds available cache of %2 pages [page 638]
55008	Table '%1' has no primary key [page 722]
55013	Table already has a primary key [page 728]
55W02	Table must be empty [page 730]
55W03	Cannot drop a user that owns tables in runtime system [page 282]
55W04	Cannot drop a user that owns procedures in runtime server [page 281]
55W05	Cannot drop a user that owns messages or data types [page 280]
55W06	Cannot drop a user that owns objects involved in replication [page 281]
55W07	db_init has not been called or the call to db_init failed [page 379]
55W08	Modifications not permitted for read-only database [page 578]
55W09	Cannot commit or rollback while enlisted in a transaction [page 265]
55W10	Cannot enlist in a transaction while already enlisted in a transaction [page 284]
55W11	Cannot enlist in a transaction with uncommitted data pending [page 285]
55W12	Cannot drop a user that owns text configurations [page 282]
55W14	Invalid operation on a closed object [page 512]
55W15	Service '%1' in use [page 671]
55W16	Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it [page 283]
55W17	Cannot use view '%1' because it has been disabled [page 310]
55W18	Cannot use view '%1' because it is invalid [page 310]

SQLSTATE	Message text
55W19	Illegal column definition: %1 [page 471]
55W20	This database does not support encrypted tables [page 822]
55W21	Cannot drop last unique index of an immediate materialized view [page 283]
55W23	Snapshot isolation disabled or pending [page 677]
55W24	Could not refresh tracing: at least one enabled tracing level must be specified [page 351]
55W25	Transact-SQL outer joins are currently disabled [page 847]
55W26	The dbspace '%1' cannot be dropped because it contains tables or indexes [page 761]
55W27	Encryption has not been enabled [page 402]
55W28	Traced query (%1, %2) does not exist [page 846]
55W29	Cannot update multiple tables immediate materialized view %1 depends on [page 306]
55W30	TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 854]
55W31	Operation not allowed on a table with dependent immediate materialized views [page 608]
55W32	WRITETEXT not allowed: immediate materialized view %1 depends on %2 [page 928]
55W33	INSERT...ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2 [page 486]
55W34	Configuration cannot not be modified while in use [page 333]
55W36	Cannot perform specified operation, number of administrators for role '%1' falls below min_role_admins option value [page 292]
55W37	Cannot perform specified operation, set user condition violated [page 292]
55W38	Cannot drop a role that owns sequences in runtime server [page 279]
55W39	Cannot drop a role that owns events in runtime server [page 278]
55W40	Cannot drop a role that owns web services in runtime server [page 280]
55W41	Cannot drop a role that owns external environment objects in runtime server [page 279]
55W42	Storing certificates is not supported for this database [page 701]
55W43	The specified certificate is not valid [page 800]
55W44	Certificate '%1' not found [page 312]

SQLSTATE	Message text
55W45	Storing OData Producers is not supported for this database [page 701]
55W46	OData Producer '%1' not found [page 601]
55W47	OData Producer option error: %1 [page 602]
55W48	Time zone '%1' not found [page 825]
55W49	Storing time zone information is not supported for this database [page 702]
55W50	Time zone option error: %1 [page 825]
55W51	The OData server returned an error: %1 [page 782]
55W52	Cannot drop the database's current time zone [page 284]
55W53	Mutex "%1" not found [page 583]
55W54	Semaphore "%1" not found [page 665]
55W55	Mutex "%1" with transaction scope cannot be released [page 584]
55W56	No stored cache pages [page 594]
55W60	There is no profiler data available [page 820]
55W61	The operation cannot be executed while the profiler is running [page 783]
55W62	The profiler is not running [page 789]
55W63	The profiler is already running [page 789]
56001	Table '%1' has a foreign key with a referential action [page 721]
57014	Statement interrupted by user [page 696]
57015	Too many recursive iterations [page 836]
57W01	Request interrupted due to timeout [page 646]
57W02	Use of feature '%1' is not allowed [page 904]
57W03	Not enough free space on device to grow dbspace '%1' by requested amount [page 597]
57W04	Use of statement '%1', which requires feature '%2', is not allowed [page 904]
57W05	Statement timed out: '%1' [page 699]
57W06	The file '%1' is invalid when the disk sandbox feature is enabled for database '%2' [page 763]
57W07	A disk sandbox error occurred for database '%1' when determining the disk sandbox status for file '%2' [page 219]
57W08	A disk sandbox error occurred for database '%1' when finding the full path for file '%1' [page 220]
5RW01	Publication '%1' not found [page 636]

SQLSTATE	Message text
5RW02	Table '%1' has publications [page 723]
5RW03	Subscription to '%1' for '%2' already exists [page 704]
5RW04	Subscription to '%1' for '%2' not found [page 705]
5RW05	User '%1' is already the publisher for this database [page 909]
5RW06	User '%1' is not a remote user for this database [page 910]
5RW07	Remote message type '%1' not found [page 641]
5RW08	Passthrough statement inconsistent with current pass-through [page 618]
5RW09	Remote statement failed [page 644]
5RW10	Multiple consolidated users cannot be defined [page 580]
5RW11	Synchronization message type '%1' not found [page 711]
5RW12	Cannot find synchronization subscription with the name '%1' [page 286]
5RW13	Cannot subscribe to '%1' [page 302]
5RW14	Cannot modify synchronization entry using ALTER PUBLICATION [page 290]
5RW15	Cannot modify publication entry using ALTER SYNCHRONIZATION [page 290]
5RW16	Cannot synchronize table '%1' since it does not have a primary key [page 302]
5RW17	Must include primary key for table '%1' in the synchronization [page 582]
5RW18	Cannot create synchronization entry for table '%1' with BLOB primary key [page 274]
5RW19	Cannot update primary key for table '%1' involved in a publication [page 307]
5RW21	Cannot register '%1' since another exclusive instance is running [page 294]
5RW22	Cannot register another '%1' as an exclusive application [page 295]
5RW23	Cannot register connection because of invalid application cookie [page 295]
5RW24	Cannot deregister application because of invalid cookie [page 277]
5RW25	Cannot deregister '%1' since active registered connection exists [page 277]
5RW26	Current connection is already registered to '%1' as '%2' [page 355]

SQLSTATE	Message text
5RW27	Another connection has already registered as '%1' [page 238]
5RW28	Cannot register '%1' since registration cookie exhausted [page 294]
5RW29	Cannot register connection to '%1' since automatic label exhausted [page 296]
5RW32	Synchronization option '%1' contains semicolon, equal sign, curly brace, or is null [page 712]
5RW33	Synchronization option '%1' not found [page 712]
5RW34	Synchronization option is too long [page 713]
5RW35	Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change [page 725]
5RW36	Table '%1' is already included [page 724]
5RW37	Cannot find synchronization user with the name '%1' [page 286]
5RW38	Operation conflict with publication type [page 606]
5RW40	Subscription '%1' not found [page 704]
5RW41	This operation is only allowed within a synchronization schema change [page 823]
5RW42	Data modifications are not allowed in a synchronization schema change [page 361]
5RW43	Synchronization failed with internal error: %1 [page 709]
5RW44	Synchronization failed. Check the results of the call to sp_get_last_synchronize_result(%1) for more information [page 710]
5RW45	Failed to start the dbmsync server [page 446]
5RW46	Failed to connect to the dbmsync server [page 437]
5RW47	The SYNCHRONIZE statement timed out [page 810]
5RW48	The database server failed to shut down the dbmsync server [page 758]
5RW49	The dbmsync server failed to shut down in a timely manner [page 760]
5RW50	The dbmsync server did not have sufficient database permissions [page 759]
99999	User-defined exception signaled [page 915]
HY000	'%1' statement is not allowed as a consumer [page 216]
WB001	Unknown backup operation [page 893]
WB002	Database backup not started [page 364]

SQLSTATE	Message text
WB003	Incomplete transactions prevent transaction log renaming [page 476]
WB004	Unable to delete database file [page 866]
WB005	Transaction log was truncated [page 849]
WB006	Contents of backup files are inconsistent [page 341]
WB007	Backup file format is invalid [page 249]
WB008	RESTORE unable to open file '%1' [page 649]
WB009	RESTORE unable to write to file '%1' [page 650]
WB010	RESTORE unable to start database '%1' [page 650]
WB011	Unable to open backup log '%1' [page 870]
WB012	Backup file '%1' already exists [page 248]
WB013	Invalid backup operation [page 492]
WB014	Connection attempting BACKUP has uncommitted transactions [page 334]
WB015	Invalid backup parameter value [page 493]
WB016	BACKUP clause '%1' conflicts with '%2' [page 248]
WB017	Backup is unable to open database file '%1' [page 249]
WB018	%2 error occurred while trying to read file %1 during backup [page 217]
WB019	RESTORE unable to find a log backup on the latest timeline [page 649]
WB020	Error processing SAP HANA strategy [page 419]
WB021	Failed to create pipe %1 during BACKUP using BACKINT %2 [page 439]
WB022	Failed to open pipe %1 during BACKUP using BACKINT %2 [page 443]
WB023	Failed to close pipe %1 during BACKUP using BACKINT %2 [page 437]
WB024	Failed to write pipe %1 during BACKUP using BACKINT %2 [page 448]
WB025	Failed to read pipe %1 during BACKUP using BACKINT %2 [page 443]
WB026	SAP HANA environment error, unable to execute command on name server [page 660]
WB027	Invalid BACKUP operation or type specified: %1 [page 493]
WB028	Verify fails, bytes written to pipe %1 and bytes written to file %2 [page 922]
WB029	BACKINT configuration file error, %1 [page 247]

SQLSTATE	Message text
WB030	SAP HANA environment error, unable to ping name server [page 659]
WB031	Failed to get BACKUP id for file name %1 [page 440]
WB032	Error in parsing BACKINT configuration file [page 410]
WB033	No external backup identity found for archive file '%1' in HANA strategy document [page 589]
WB034	Error backing up existing log area. Found '%1' logs in '%2' directory [page 407]
WB035	Found a file '%1' with relative path in delta dbspace during backup existing log area. [page 461]
WB036	Command '%1' received BACKINT_ERROR from HANA [page 330]
WB038	Cannot proceed with online backup, SQLA log guid is ahead [page 293]
WB039	Failed to load %1 HANA library [page 442]
WC001	'%1' is an unknown character set encoding label [page 208]
WC002	Cannot convert between requested character set '%1' and database character set '%2' [page 267]
WC003	An invalid multi-byte input character was encountered when converting from %1 to %2 [page 236]
WC004	The UTF-16 endian specified does not match the Byte Order Mark found in the data [page 814]
WC005	Character substitution was required when converting from %1 to %2 [page 315]
WC007	Character conversion error or warning report is not available when the single-byte converter is used [page 313]
WC008	Cannot convert between requested character sets '%1' and '%2' [page 268]
WC009	'%1' is not a valid character set encoding for use with collation '%2' [page 211]
WC010	'%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used [page 206]
WC011	Failed to convert from character set '%1' to '%2' [page 438]
WC012	dbicu libraries are required but not installed [page 384]
WC013	Collation '%1' not supported on this platform [page 323]
WC014	The dbicu library and server versions do not match [page 759]
WC015	Unable to start database "%1": CHAR collation or tailoring not supported on this platform [page 874]
WC016	Unable to start database "%1": NCHAR collation or tailoring not supported on this platform [page 874]

SQLSTATE	Message text
WC017	'%1' cannot be used as the encoding specification for '%2' data [page 206]
WC018	Unknown collation '%1' [page 894]
WE001	Event '%1' not found [page 422]
WE002	Event '%1' already exists [page 421]
WE003	Schedule '%1' for event '%2' not found [page 662]
WE004	Schedule '%1' for event '%2' already exists [page 662]
WE005	Invalid day of week or month '%1' for event '%2' [page 500]
WE006	Invalid time '%1' for event '%2' [page 535]
WE007	Invalid start date/time for event '%1' [page 532]
WE008	System event type '%1' not found [page 719]
WE009	Event '%1' in use [page 422]
WE010	Start date/time for non-recurring event '%1' is in the past [page 693]
WE011	Event notification queue '%1' is full, notification discarded [page 423]
WE012	Event notifications lost on queue '%1' [page 424]
WE013	Event notification queue '%1' not found warning [page 424]
WE014	Event notification queue '%1' not found [page 423]
WE015	Event object name '%1' is not valid [page 425]
WE016	Event object named '%1' already exists [page 426]
WE017	No notification within timeout on queue '%1' [page 592]
WE018	Event parameter '%1' not found [page 426]
WE019	Trace event '%1' is not valid [page 839]
WE020	The specified session name '%1' is not valid [page 803]
WE021	Trace event '%1' already exists [page 839]
WE022	Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first [page 840]
WE023	Trace event session '%1' is active. Stop active session before dropping the session [page 844]
WE024	Too many arguments for trace event '%1' [page 829]
WE025	Too many active trace event sessions [page 828]
WE026	Trace event session '%1' already active [page 840]
WE027	One or more targets in the trace event session '%1' failed to start [page 604]
WE028	Trace event session '%1' failed to start [page 844]
WE029	Trace event session '%1' is already stopped [page 845]

SQLSTATE	Message text
WE030	Trace event session '%1' already has trace event '%2' [page 842]
WE031	The specified target type '%1' is not valid [page 804]
WE032	Unknown option '%1' specified for target type '%2' [page 896]
WE033	The option '%1' was not specified for target type '%2' [page 786]
WE034	Trace event session '%1' already has target type '%2' [page 841]
WE035	Trace event session '%1' does not have trace event '%2' [page 843]
WE036	Trace event session '%1' does not have target type '%2' [page 842]
WE037	Trace event session '%1' already exists [page 841]
WE038	Trace target option '%1' conflicts with option '%2' [page 845]
WE039	Failed to set up audit log session for database '%1' [page 445]
WE040	Cannot set audit_log to the transaction log: The transaction log is not enabled for the database [page 299]
WE041	Cannot update the audit_log option: one or more of the specified targets is invalid [page 308]
WE042	Invalid repeat interval for event '%1' [page 524]
WE043	Invalid event parameter for event '%1' [page 504]
WE044	Invalid setting '%1' specified for option '%2' for target type '%3' [page 527]
WI002	Index validation failed for table %1, index %2 with code: %3 [page 482]
WI003	Database page validation failed with code: %1 [page 371]
WI004	Internal rollback log corrupted [page 490]
WI005	Unable to find in index '%1' for table '%2' [page 867]
WI009	Cannot serialize Java object with class '%1' [page 298]
WI010	The optimizer was unable to construct a valid access plan [page 784]
WI011	Required operators excluded [page 647]
WI012	Error executing BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 408]
WI112	An internal error has occurred in the profiler library [page 234]
WI113	A fatal error has occurred in the profiler library [page 221]

SQLSTATE	Message text
WI114	The profiler has not been initialized. Contact SAP support. [page 789]
WJ001	Method '%1' cannot be called at this time [page 570]
WJ003	The specified transaction isolation is invalid [page 804]
WJ004	The cursor name '%1' already exists [page 753]
WJ005	Input parameter index out of range [page 485]
WJ030	External environment '%1' could not be found [page 429]
WJ031	External environment does not support result sets [page 431]
WJ032	Cannot change the setting of the UseSingleJVMInstance server option after Java has already been started [page 264]
WJ033	Cannot change the setting of the SingleCLRInstanceVersion server option after the CLR external environment has already been started [page 263]
WL001	'%1' is not a known file format for loading or unloading tables [page 211]
WL002	Cannot access file '%1' -- %2 [page 256]
WL004	UNLOAD TABLE cannot be used to unload a view [page 897]
WL005	Unable to enlist transaction; DTC may be down [page 867]
WL006	Unable to re-enlist transaction; DTC may be down [page 872]
WL007	LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS [page 560]
WL008	LOAD TABLE ... WITH FILE NAME LOGGING not permitted on mirrored database [page 557]
WL009	LOAD TABLE not allowed on temporary table which has foreign key references from another table [page 560]
WL010	The logging type ('%1') specified is invalid, not supported or incompatible [page 773]
WL011	Unable to close the cursor on table "%1". LOAD TABLE cannot be executed [page 861]
WL012	Cannot append when using compression or encryption [page 259]
WL013	LOAD TABLE error: %1 [page 558]
WL014	LOAD TABLE is not allowed on a materialized view %1 [page 559]
WL015	LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 561]
WL016	LOAD TABLE option '%1' not allowed with FORMAT %2 [page 561]

SQLSTATE	Message text
WL017	LOAD TABLE error: Invalid content encountered on row %1 of the data file [page 559]
WL018	Format '%1' is not supported in the UNLOAD statement [page 459]
WL019	Invalid empty string specified as 'ESCAPE CHARACTER' option of LOAD or UNLOAD TABLE [page 502]
WO001	Unable to connect to server '%1': %2 [page 862]
WO002	Unable to connect, server definition is circular [page 863]
WO003	Remote server '%1' is currently configured as read-only [page 642]
WO004	Remote server '%1' could not be found [page 642]
WO005	Server '%1': %2 [page 669]
WO006	Backward scrolling cursors are not supported for remote objects [page 250]
WO007	The remote table '%1' could not be found [page 792]
WO008	Could not access column information for the table '%1' [page 343]
WO009	Table parameterized functions are not allowed across server types [page 732]
WO010	%1 [page 205]
WO011	The remote server does not support an auto-incrementing data type [page 791]
WO012	Remote server does not have the ability to support this statement [page 643]
WO013	External login for server '%1' could not be found [page 434]
WO014	Server capability name '%1' could not be found in the database [page 669]
WO015	The data type specified for column '%1' is not compatible with the actual data type [page 755]
WO016	The column '%1' does not exist in the remote table [page 751]
WO017	The length specified for column '%1' is different than the actual length [page 772]
WO018	NULL attribute mismatch for column '%1' [page 599]
WO019	Identity attribute mismatch for column '%1' [page 471]
WO020	The table specification '%1' identifies more than one remote table [page 811]
WO021	Creating remote tables with computed columns is not supported [page 354]

SQLSTATE	Message text
WO022	The data type of column or variable '%1' is not supported [page 754]
WO023	Cannot handle expressions involving remote tables inside stored procedures [page 287]
WO024	Specified local connection ID not found [page 685]
WO025	Local connection ID does not refer to the current database [page 562]
WO026	Cannot close a remote JDBC connection that is not the current connection [page 264]
WO027	File system error: %1 [page 455]
WO028	User cannot be dropped because external logins exist for this user [page 911]
WO029	MIRROR server class is not supported for SAP IQ databases [page 575]
WO030	You must upgrade your database in order to use the MIRROR server class [page 935]
WO031	External procedures or functions are not allowed across server types [page 435]
WO032	You cannot use a security token when making remote connections [page 934]
WO033	The %1 remote data access class is no longer supported, please use %2 instead [page 744]
WO035	Remote column %1 has been specified with the wrong case [page 641]
WO036	Remote server is currently in use and cannot be dropped [page 643]
WP000	Argument %1 of procedure '%2' cannot be NULL [page 240]
WP001	Procedure '%1' terminated with unhandled exception '%2' [page 634]
WP002	'%1' is not a valid class file [page 212]
WP003	Could not decompress class '%1' from JAR [page 346]
WP004	Cannot remove class '%1': member of JAR [page 296]
WP005	Invalid class byte code [page 494]
WP006	External environment could not be started, '%1' could not be found [page 431]
WP007	Namespace heap exhausted at internal function: %1 [page 586]
WP008	Java VM heap exhausted at internal function: %1 [page 547]
WP009	Resource governor for '%1' exceeded [page 648]
WP010	Invalid JAR file [page 510]

SQLSTATE	Message text
WP011	Previous error lost before RESIGNAL [page 629]
WP012	%1 returned a result set with a different schema than expected [page 215]
WP013	%1 returned multiple result sets [page 215]
WP014	%1 does not return a result set [page 207]
WP015	Insufficient cache to start Java VM [page 487]
WP016	Warning detected when optimizing SELECT INTO is treated as an error [page 924]
WP017	External environment failed to start and establish a connection within the %1 second timeout [page 432]
WP018	External environment cannot be started during database startup [page 430]
WP019	External environment cannot be started, external process terminated on start up [page 430]
WP020	Table Parameterized Functions and V4 TableUDFs are not supported for this database [page 731]
WP021	Multiple table parameters are not supported [page 581]
WP022	Outer references are not allowed for TPF input tables [page 612]
WP023	Use of %TYPE or %ROWTYPE is not allowed for variable or temporary objects [page 903]
WP024	Unable to declare a row variable from the cursor using %ROWTYPE; invalid name for field %1 [page 865]
WP025	Unable to declare a row variable from the cursor using %ROWTYPE; no fields were found in the cursor [page 866]
WP026	Cursor %1 cannot be used to declare a row variable using %ROWTYPE [page 355]
WP027	Mutex was dropped [page 585]
WP028	Semaphore was dropped [page 665]
WP029	The variable in the INTO clause is not a row type [page 817]
WP030	Unsupported use of ROW type in an INTO clause [page 900]
WP031	There is already a database variable named '%1' [page 818]
WT001	Argument "%1" must be a column reference [page 239]
WT002	All column reference arguments must refer to the same table [page 229]
WT003	No matching text index [page 590]
WT004	Non-constant or unknown text query string [page 595]
WT005	Text configuration "%1"."%2" not found [page 738]
WT006	Text configuration "%1" already exists [page 738]

SQLSTATE	Message text
WT007	Term length outside allowed range [page 737]
WT008	Invalid collation: "%1" [page 495]
WT009	Text query parser error: %1 [page 743]
WT010	Error creating text index "%1" on table "%2" [page 407]
WT011	Text indexes are not supported for this database [page 741]
WT012	Cannot alter or drop a text configuration referenced by a text index [page 259]
WT013	Cannot access a table that is part of a text index [page 255]
WT014	Cannot create text configuration '%1' because option '%2' has an inappropriate setting [page 275]
WT015	Statement not allowed on IMMEDIATE REFRESH text index [page 697]
WT016	Invalid use of NEAR operator in text query [page 541]
WT017	The arguments to this procedure must be literal strings [page 749]
WT018	The provided stoplist is too long [page 790]
WT019	The text index %1 needs to be refreshed [page 811]
WT020	A CONTAINS query is not allowed on the view or derived table '%1' [page 218]
WT021	Could not create a new text index for this table with the same settings as "%1" [page 344]
WT022	Text queries cannot contain more than 300 terms [page 742]
WT023	The value for the stoplist cannot be NULL [page 815]
WT024	An incremental refresh is not possible when handles are exhausted [page 233]
WT025	Invalid stoplist value [page 534]
WT026	Invalid external term breaker name specified [page 506]
WT027	Error initializing external prefilter [page 410]
WT028	Error initializing external term breaker [page 411]
WT029	Invalid external prefilter name specified [page 505]
WT030	Could not create a text index without external prefilter library on column "%1" [page 345]
WT031	Could not create a text index with external prefilter library on column "%1" [page 345]
WT032	Error from external library: -%1: %2 [page 409]
WT033	Text indexes are not allowed across server types [page 741]

SQLSTATE	Message text
WT034	Text index with external prefilter cannot contain both binary and string columns [page 740]
WT035	Database needs to be upgraded to support the use of external libraries with text indexes [page 369]
WT036	Text index %1 cannot be used with text procedure %2 [page 740]
WT037	Invalid text index type for the materialized view [page 535]
WT038	Statement not allowed on text index for a materialized view [page 698]
WT039	Error modifying refresh type for text index "%1" on materialized view "%2" [page 411]
WT040	Invalid use of BEFORE operator in text query [page 540]
WT041	Text indexes on materialized views are not supported for this database [page 742]
WT042	CHAR configuration provided for NCHAR column for text index \"%1\" on table \"%2\" [page 313]
WU001	'%1' is an unknown property [page 209]
WU002	The UltraLite database deploy file is invalid (code: %1, file: %2) [page 812]
WW001	The pattern is too long [page 788]
WW002	Cannot stop the database server [page 301]
WW003	Calling functions outside the database server is not supported [page 254]
WW004	No entry point specified for the current system configuration [page 589]
WW005	Need a dynamic library name [page 586]
WW006	Could not load dynamic library '%1' [page 349]
WW007	Could not find '%1' in dynamic library '%2' [page 347]
WW008	Could not allocate resources to call external function [page 344]
WW009	Expression has unsupported data type [page 427]
WW010	Too many parameters to this external procedure call [page 835]
WW011	A thread used internally could not be started [page 225]
WW012	RAISERROR executed: %1 [page 637]
WW013	Class '%1' has no public field '%2' [page 317]
WW014	Invalid type for field reference [page 538]
WW015	Field '%1' of class '%2' cannot be NULL [page 453]
WW016	Index type specification of '%1' is invalid [page 481]

SQLSTATE	Message text
WW017	An attempt to delete database '%1' failed [page 232]
WW018	Cannot deserialize Java object [page 278]
WW019	Rollback occurred due to deadlock during prefetch [page 655]
WW020	Invalid request log format on line %1 [page 525]
WW021	Need a function entry point [page 587]
WW022	Cannot create an index on Java class '%1' [page 270]
WW023	Cannot insert or update computed column '%1' [page 288]
WW024	The communications environment could not be created [page 751]
WW026	Version 'V%1' interface used by external function call '%2' is not supported for execution in the current context [page 922]
WW027	A conflict with the dbmsync download phase was detected [page 218]
WW028	At least one of the specified dbspaces was not calibrated [page 242]
WW029	A workload capture (%1) is already in progress [page 227]
WW030	No workload capture currently exists [page 595]
WW031	Cannot access schema file '%1' [page 257]
WW032	The status of the last synchronization upload is unknown [page 807]
WW033	A schema upgrade is not currently allowed [page 224]
WW034	The database '%1' was not found [page 756]
WW035	This connection already exists [page 822]
WW036	Information for synchronization is incomplete or invalid, check '%1' [page 484]
WW037	Compression error: %1 [page 332]
WW038	Decompression error: %1 [page 386]
WW039	Input string is not base64-encoded [page 485]
WW040	UltraLite connection was restored [page 858]
WW041	UltraLite cursor (or result set or table) was restored [page 858]
WW042	Checksums are not enabled in this database [page 316]
WW043	File I/O failed for '%1' [page 454]
WW044	Incorrect volume ID for '%1' [page 478]
WW045	The operation failed because column '%1's type does not support streaming [page 783]

SQLSTATE	Message text
WW046	Script file missing statement "go" delimiter on a separate line [page 663]
WW047	Directory for output file does not exist [page 390]
WW048	Output file cannot be written [page 613]
WW049	The URI '%1' is invalid [page 813]
WW050	Unable to connect to the remote host specified by '%1' [page 862]
WW051	Connection timed out [page 337]
WW052	HTTP request failed. Status code '%1' [page 469]
WW053	Could not initialize the encryption DLL: '%1' [page 348]
WW055	Invalid procedure type '%1' [page 522]
WW056	Invalid procedure subtype '%1' for type '%2' [page 521]
WW057	Invalid response from the HTTP server [page 525]
WW058	NAMESPACE attribute is not valid with procedure type '%1' [page 585]
WW059	The secure connection to the remote host failed: %1 [page 795]
WW060	Clause '%1' has invalid attribute '%2' [page 318]
WW061	The database was created [page 758]
WW062	The option '%1' is not recognized [page 785]
WW063	Secure HTTP connections are not supported on this platform [page 663]
WW064	The '%1' attribute is not valid with procedure type '%2' [page 745]
WW065	Cannot add a comment to a table declared as LOCAL TEMPORARY [page 257]
WW066	Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1 [page 352]
WW067	Could not refresh tracing: failed to find object %1 on row %2 [page 351]
WW068	Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected [page 352]
WW069	ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database [page 243]
WW070	The HTTP header '%1' is reserved and cannot be modified [page 767]
WW071	The specified HTTP header contains illegal or non-ASCII characters [page 802]
WW072	The specified HTTP header is malformed [page 802]

SQLSTATE	Message text
WW073	Column '%1' not part of any indexes in its containing table [page 328]
WW074	Unable to retry download because upload is not finished [page 873]
WW075	No partial download was found [page 593]
WW077	Too many publications specified for operation [page 836]
WW078	Unable to access the file system on the device [page 860]
WW079	Unable to perform requested operation since this database uses keyless encryption [page 871]
WW080	UltraLite cannot synchronize because a synchronization is already running [page 857]
WW081	Information for synchronization was not provided [page 484]
WW082	Specified file system volume not found for database '%1' [page 684]
WW083	A row cannot be stored because it exceeds the database page size [page 223]
WW084	Exceeded maximum of '%1' allowable parameters [page 427]
WW085	Invalid mime type '%1' [page 511]
WW086	The '%1' attribute contains mismatched parentheses within '%2' [page 744]
WW087	The '%1' attribute is missing a comma within '%2' [page 745]
WW088	The attribute '%1' sets an option '%2' that is incompatible with '%3' [page 750]
WW089	Maximum row size for table '%1' would be exceeded [page 567]
WW090	The mirror '%1' does not match database '%2' [page 781]
WW091	The SQL scripts DLL cannot be loaded [page 806]
WW092	Client application does not allow transfer of data ('%1') [page 319]
WW093	Client application disallowed the transfer of data ('%1') [page 318]
WW094	Client library reported an error accessing data during transfer ('%1') [page 320]
WW095	Transaction log mirroring cannot be used with database mirroring [page 848]
WW096	Cannot set database option "%1" because it is on the options watch list [page 300]
WW097	Login policy "%1" already exists [page 564]

SQLSTATE	Message text
WW098	Login policy "%1" not found [page 565]
WW099	Login policies are not supported for this database [page 563]
WW100	Login policy "%1" in use [page 564]
WW101	User "%1" already exists [page 906]
WW102	Client library reported an error opening object ('%1') during transfer [page 320]
WW103	Client library reported a permissions error accessing object ('%1') during transfer [page 319]
WW104	External environments are not supported for this database [page 433]
WW108	External library '%1' is in use [page 433]
WW109	External library '%1' not loaded [page 434]
WW114	UltraLite database state was restored [page 859]
WW115	Retrying read of corrupt page (page '%1') [page 652]
WW116	Mirror file requires higher checksum_level [page 572]
WW118	An attempt to encrypt database '%1' failed [page 232]
WW119	An attempt to decrypt database '%1' failed [page 231]
WW120	'%1' statement is not allowed on a mirrored database [page 216]
WW130	Database mirroring options are not supported for this database [page 367]
WW131	Mirror server "%1" not found [page 574]
WW132	Mirror server "%1" already exists [page 572]
WW133	Mirror server "%1" is referenced by another server [page 574]
WW134	Principal mirror servers are already defined [page 632]
WW135	Mirror server "%1" is not a valid parent server [page 573]
WW136	Cannot force failover when current server is marked as preferred [page 287]
WW137	Synchronization schema changes and script versions are not supported for this database [page 716]
WW138	Column subset for table '%1' in publication '%2' does not match that specified in publication '%3' [page 329]
WW139	Table or view '%1' is not valid for use with this statement [page 731]
WW140	A synchronization schema change is already in progress [page 225]

SQLSTATE	Message text
WW141	Subscription to publication '%1' for '%2' omitted from statement [page 705]
WW142	Connection is not allowed to have table locks when executing this statement [page 336]
WW143	Table '%1' must synchronize to be in publication '%2' [page 725]
WW144	Feature '%1' is unknown or invalid [page 450]
WW145	Feature '%1' was not locked by this connection [page 452]
WW146	Feature '%1' is locked by another connection [page 449]
WW147	Feature '%1' is locked because synchronization is in progress [page 449]
WW148	Rollback occurred due to blocking_others_timeout [page 654]
WW149	Mutex "%1" was not locked by this connection [page 584]
WW150	Mutex "%1" is locked by another connection [page 583]
WW151	Mirror server name '%1' does not match current server name [page 575]
WW152	The parent of this mirror server is not currently connected [page 787]
WW153	The parent of this mirror server is not the primary server [page 788]
WW154	Mirror child server creation failed [page 571]
WW155	Mirror server with type '%1' is already defined [page 576]
WW156	Cannot assign automatic mirror server parent [page 260]
WW159	Database server name '%1' cannot be the same as either the primary or mirror server [page 375]
WW160	The licensed maximum number of mirror servers with type COPY has been exceeded [page 772]
WW161	Synchronization failed. Check the dbmsync log file for more details [page 710]
WW162	Failed to connect to the dbmsync server. Check the dbmsync log file for more details [page 438]
WW163	Failed to shut down the dbmsync server. Check the dbmsync log file for more details [page 445]
WW164	Failed to start the dbmsync server. Check the dbmsync log file for more details [page 446]
WW165	The definition of temporary table '%1' has changed since last used [page 762]
WW166	The transaction may not be committed because the primary server lost quorum [page 812]

SQLSTATE	Message text
WW167	Too many temporary mutexes and semaphores created [page 837]
WW168	Too many mutexes and semaphores created [page 834]
WW202	LDAP Server "%1" already exists [page 553]
WW203	Attempt to allocate memory for LDAP server "%1" failed [page 243]
WW204	The attempt to drop LDAP server "%1" failed, suspend the server to drop it [page 749]
WW205	LDAP User Authentication feature is not supported in this database [page 555]
WW206	LDAP server "%1" is in use by login policy "%2" [page 554]
WW207	Failed to load the MobiLink client support libraries [page 442]
WW208	LDAP server definition of "%1" is incomplete. A search URL, access distinguished name, password, and authentication URL are required [page 555]
WW210	Invalid use of collection type [page 540]
WW211	The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2' [page 750]
WW212	Password encryption failed. Error message '%1' [page 619]
WW213	The specified distinguished name '%1' does not match the search result '%2' [page 801]
WW214	The search using '%1' failed due to one or more invalid values set [page 795]
WW215	Cannot ALTER LDAP SERVER '%1' while LDAP server is in active state [page 258]
WW216	The length of the value specified is too long, it exceeds the limit of %1 bytes [page 771]
WW217	The value specified is not within the required range %1 to %2 [page 816]
WW218	LDAP server %1 may not accept anonymous binds [page 554]
WW219	Bind to LDAP server %1 without a password is not allowed [page 250]
WW220	The search on LDAP server %1 completed with no matching results [page 794]
WW223	Invalid use of table reference type [page 542]
WW229	Parameter '%1' cannot be null [page 614]
WW230	Operation is not allowed [page 608]
WW231	Operation '%1' failed for reason: '%2' [page 605]
WW232	Underflow when converting '%1' [page 890]

SQLSTATE	Message text
WW234	Automatic database upgrade applied [page 247]
WW240	TLS ON cannot be used with URL %1 [page 826]
WW241	Only one IDENTIFIED BY value may be specified [page 604]
WW242	Dropping or altering arbiter "%1" requires a connection to the partner [page 395]
WW243	Invalid value for login policy option "%1" [page 545]
WW245	Prevented removal of LDAP server because it is referenced by login policy "%1" which is the only login policy with an LDAP server and the value of login_mode is "LDAPUA" [page 629]
WW246	Prevented removal of LDAP server "%1" because it is the only LDAP server and the value of login_mode is "LDAPUA" [page 628]
WW247	UltraLite performed database recovery on startup [page 859]
WW248	Debugger error: %1 [page 386]
WW249	Invalid ROW or ARRAY domain [page 526]
WW250	Failed to delete the SQL Anywhere Cockpit file '%1': %2 [page 440]
WW251	Failed to access the SQL Anywhere Cockpit file '%1': %2 [page 436]
WW252	Failed to rename the SQL Anywhere Cockpit file '%1' to '%2': %3 [page 444]
WW253	Failed to read the SQL Anywhere Cockpit setting file '%1' [page 444]
WW254	Failed to write the SQL Anywhere Cockpit setting file '%1' [page 448]
WW255	Encryption failed for the SQL Anywhere Cockpit setting file. Error message '%1' [page 401]
WW256	Failed to get status information on the path '%1': %2 [page 441]
WW257	Failed to get file system statistics for the path '%1' [page 441]
WW258	Cannot save SQL Anywhere Cockpit to existing file '%1' [page 298]
WW259	Restoring database from an upgrade image [page 651]
WW265	The output path '%1' is invalid [page 786]
WW267	The minimum percentage '%1' is invalid. The minimum percentage must be between 0 and 100. [page 781]

SQLSTATE	Message text
WW268	The sample wait time cannot be changed once samples have been collected. Clear the sample data and then set the option. [page 794]
WW270	Could not start a new profiling session because the previous session is still being processed. [page 353]
WW271	Could not write the profiler data because the previous session is still being processed. [page 353]
WX001	Column must be named: %1 [page 328]
WX002	XML parser error: %1 [page 931]
WX003	XPath parser error: %1 [page 931]
WX004	Illegal flags value passed to OPENXML [page 473]
WX005	Illegal tag value: '%1' [page 474]
WX006	Unknown FOR XML EXPLICIT directive: '%1' [page 894]
WX007	Illegal column name: '%1' [page 472]
WX008	Parent not open: '%1' [page 616]
WX009	Undeclared tag ID: '%1' [page 890]
WX010	Too few columns [page 827]
WX011	CDATA has a name [page 311]
WX012	Invalid XQuery constructor [page 545]
WX013	XMLGEN evaluation failure [page 931]
WX014	No name for argument [page 592]
WX015	Control character in XML output [page 341]
WX016	Insufficient memory for OPENXML query [page 487]
WX017	Tag ID: '%1' specifies a value not bounded by an array [page 734]
WX018	Error at offset '%1': unexpected token '%2' [page 405]
WX019	Error at offset '%1': unexpected trailing text [page 406]
WX020	Error at offset '%1': invalid data [page 404]
WX021	Error at offset '%1': expected token '%2' [page 403]
WX022	Error at offset '%1': expected JSON name/value pair [page 403]
WX023	Error at offset '%1': mismatched object or array terminator [page 405]
WX024	Invalid variable or type [page 545]
WX025	Too many columns [page 829]
WX026	JSON nesting too deep [page 548]
WX027	JSON object contains too many properties [page 549]

SQLSTATE	Message text
WX028	JSON array contains too many elements [page 548]

1.1.3 SQL Anywhere Error Messages Sorted by Sybase Error Code

Sybase error code	SQL Anywhere SQLCODE	Message text
0	-631	RAISERROR executed: %1 [page 637]
102	-171	Error opening cursor [page 412]
102	-199	INSERT/DELETE on cursor can modify only one table [page 486]
102	-273	COMMIT/ROLLBACK not allowed within trigger actions [page 331]
102	-131	Syntax error near '%1' %2 %3 [page 717]
102	-875	There is no way to join to '%1' [page 821]
102	-145	Foreign key name '%1' not found [page 458]
102	-271	Trigger definition conflicts with existing triggers [page 852]
102	-272	Invalid REFERENCES clause in trigger definition [page 523]
102	-635	GRANT of column permission on view not allowed [page 466]
102	-151	Subquery allowed only one SELECT list item [page 703]
102	-269	Cannot delete or rename a column referenced in a trigger definition [page 276]
103	-250	Identifier '%1' too long [page 470]
104	-854	Function or column reference to '%1' in the ORDER BY clause is invalid [page 463]
108	-152	Invalid ORDER BY specification [page 514]
133	-262	Label '%1' not found [page 551]
134	-261	There is already a variable named '%1' [page 819]
137	-260	Variable '%1' not found [page 920]

Sybase error code	SQL Anywhere SQLCODE	Message text
154	-623	Data definition statements not allowed in procedures or triggers [page 361]
155	-200	Invalid option '%1' -- no PUBLIC setting exists [page 513]
174	-154	Wrong number of parameters to function '%1' [page 929]
176	-611	Transact-SQL feature not supported [page 847]
176	-1702	Collection types not supported [page 323]
176	-148	Unknown function '%1' [page 895]
176	-1965	Feature '%1' not supported [page 451]
182	-159	Invalid column number [page 495]
201	-639	Parameter name missing in call to procedure '%1' [page 615]
201	-615	Parameter '%1' not found in procedure '%2' [page 615]
201	-737	Signature '%1' does not match procedure parameters [page 676]
205	-153	Select lists in UNION, INTERSECT, or EXCEPT do not match in length [page 664]
207	-124	Dropping all columns from table '%1' is not allowed [page 394]
207	-143	Column '%1' not found [page 326]
208	-142	Correlation name '%1' not found [page 343]
209	-144	Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name [page 324]
209	-163	Derived table '%1' has no name for column %2 [page 389]
213	-207	Wrong number of values for INSERT [page 929]
217	-274	Procedure or trigger calls have nested too deeply [page 635]
220	-158	Value %1 out of range for destination [page 918]
230	-191	Cannot modify column '%1' in table '%2' [page 289]

Sybase error code	SQL Anywhere SQLCODE	Message text
230	-190	Cannot update an expression [page 304]
233	-195	Column '%1' in table '%2' cannot be NULL [page 325]
233	-733	Number of columns allowing NULLs exceeds limit [page 600]
257	-157	Cannot convert %1 to %2 [page 266]
257	-705	Return type of void from procedure '%1' cannot be used in any expression [page 653]
262	-121	Permission denied: %1 [page 622]
264	-637	Duplicate insert column [page 396]
285	-708	READTEXT or WRITETEXT statement cannot refer to a view [page 638]
301	-147	There is more than one way to join '%1' to '%2' [page 819]
301	-680	Invalid expression in WHERE clause of Transact-SQL outer join [page 504]
301	-146	There is no way to join '%1' to '%2' [page 820]
305	-681	Invalid join type used with Transact-SQL outer join [page 510]
311	-295	Cannot uniquely identify rows in cursor [page 304]
314	-122	Operation would cause a group cycle [page 609]
315	-136	Table '%1' is in an outer join cycle [page 724]
315	-137	Table '%1' requires a unique correlation name [page 727]
401	-134	Feature '%1' not implemented [page 451]
401	-135	Language extension [page 552]
401	-156	Invalid expression near '%1' [page 505]
401	-994	Too many arguments for function or procedure '%1' [page 828]
404	-890	Statement size or complexity exceeds server limits [page 699]
409	109	Null value eliminated in aggregate function [page 599]

Sybase error code	SQL Anywhere SQLCODE	Message text
409	-90	Argument %1 of procedure '%2' cannot be NULL [page 240]
504	-265	Procedure '%1' not found [page 633]
509	-140	User ID '%1' does not exist [page 911]
512	-186	Subquery cannot return more than one row [page 703]
518	103	Invalid data conversion [page 497]
532	104	Row has been updated since last time read [page 656]
532	106	Value for column '%1' in table '%2' has changed [page 919]
538	-627	Disallowed language extension detected in syntax near '%1' on line %2 [page 391]
546	-194	No primary key value for foreign key '%1' in table '%2' [page 593]
547	-198	Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3' [page 630]
547	-677	Table '%1' has a foreign key with a referential action [page 721]
548	-196	Index '%1' for table '%2' would not be unique [page 479]
548	-209	Constraint '%1' violated: Invalid value for column '%2' in table '%3' [page 339]
548	-1091	Constraint '%1' violated: Invalid value in table '%2' [page 340]
549	-729	The specified foreign key (%1) cannot be enforced [page 801]
550	-632	WITH CHECK OPTION violated for insert/update on base table '%1' [page 927]
553	-264	Wrong number of variables in FETCH [page 930]
554	-208	Row has changed since last read -- operation canceled [page 656]
557	-853	Cursor not in a valid state [page 357]
557	-170	Cursor has not been declared [page 356]
558	-172	Cursor already open [page 356]
559	-180	Cursor not open [page 358]

Sybase error code	SQL Anywhere SQLCODE	Message text
560	100	Row not found [page 658]
560	-197	No current row of cursor [page 587]
573	-738	Password must be at least %1 characters [page 621]
590	111	Statement cannot be executed [page 694]
601	-642	Invalid SQL descriptor name [page 531]
708	-80	Unable to start database server [page 875]
708	-86	Not enough memory to start [page 598]
708	-1179	Unable to start database server: missing license file [page 876]
709	-996	Specified local connection ID not found [page 685]
710	-997	Local connection ID does not refer to the current database [page 562]
711	-998	Cannot close a remote JDBC connection that is not the current connection [page 264]
840	-82	Unable to start specified database: %1 [page 877]
840	-87	Database name required to start server [page 369]
840	-1008	Unable to start specified database: '%1' is an invalid transaction log mirror [page 878]
840	-1009	Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid [page 885]
840	-1010	Unable to start specified database: '%1' not expecting any operations in transaction log [page 880]
840	-1011	Unable to start specified database: Unknown encryption algorithm [page 886]
840	-1012	Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing) [page 880]
840	-1016	Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file [page 882]

Sybase error code	SQL Anywhere SQLCODE	Message text
840	-1017	Unable to start specified database: '%1': transaction log file not found [page 881]
840	-1018	Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file [page 883]
840	-1019	Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently [page 883]
840	-1020	Unable to start specified database: Cannot use log file '%1' since it is shorter than expected [page 882]
840	-1004	Unable to start specified database: '%1' is not a database [page 879]
840	-1005	Unable to start specified database: '%1' was created by a different version of the software [page 881]
840	-1006	Unable to start specified database: '%1' is not a valid database file [page 879]
840	-1007	Unable to start specified database: '%1' is an invalid transaction log [page 878]
840	-1063	Unable to start database %1: Cannot use read-only mode since auditing is currently logging to the transaction log [page 875]
840	-1147	Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html [page 363]
840	-1149	Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html [page 362]
911	-83	Specified database not found [page 683]
924	-816	Specified database file already in use [page 682]
927	-97	Database page size too big: %1 [page 370]
927	-644	Invalid database page size [page 499]

Sybase error code	SQL Anywhere SQLCODE	Message text
928	-645	Database creation failed: %1 [page 366]
932	-311	Internal rollback log corrupted [page 490]
950	-76	Request denied -- no active databases [page 645]
950	-74	The selected database is currently inactive [page 797]
1205	-306	Deadlock detected [page 385]
1205	-307	All threads are blocked [page 230]
1205	-684	Rollback occurred due to deadlock during prefetch [page 655]
1601	-102	Database server connection limit exceeded [page 374]
1602	-85	Communication error [page 331]
1602	-88	Client/server communications protocol version mismatch [page 322]
1702	-616	Too many columns in table [page 831]
1709	-849	Referential integrity actions other than RESTRICT not allowed for temporary tables [page 640]
1709	-850	Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared [page 733]
1709	-865	Key constraint between temporary tables requires a primary key (not unique constraint) [page 551]
1719	-118	Table '%1' has no primary key [page 722]
1721	-113	Column '%1' in foreign key has a different definition than primary key [page 325]
1801	-77	Database name not unique [page 368]
1802	-138	Dbospace '%1' not found [page 384]
1909	-636	Duplicate referencing column [page 398]
1909	-119	Primary key column '%1' already defined [page 630]
1909	-251	Foreign key '%1' for table '%2' duplicates an existing foreign key [page 457]

Sybase error code	SQL Anywhere SQLCODE	Message text
1921	-111	Index name '%1' not unique [page 481]
1921	-678	Index name '%1' is ambiguous [page 480]
1923	-126	Table cannot have two primary keys [page 728]
1923	-112	Table already has a primary key [page 728]
2561	-106	Cannot open transaction log file -- %1 [page 291]
2601	-193	Primary key for table '%1' is not unique: Primary key value ('%2') [page 631]
2706	-141	Table '%1' not found [page 726]
2715	-613	User-defined type '%1' not found [page 915]
2727	-189	Unable to find in index '%1' for table '%2' [page 867]
2732	-296	Error number %1 for RAISERROR must not be less than 17000 [page 412]
2748	-612	User message %1 not found [page 912]
2749	-294	Format string argument number %1 is invalid [page 459]
3013	-305	I/O error %1 -- transaction rolled back [page 469]
3013	-309	Memory error -- transaction rolled back [page 568]
3206	-240	Unknown backup operation [page 893]
3206	-241	Database backup not started [page 364]
3206	-242	Incomplete transactions prevent transaction log renaming [page 476]
3206	-1021	Invalid backup operation [page 492]
3451	-672	Database upgrade failed [page 376]
3451	-673	Database upgrade not possible [page 377]
3618	-302	Terminated by user -- transaction rolled back [page 738]
3618	-304	Disk full '%1' -- transaction rolled back [page 391]
3619	-107	Error writing to transaction log file [page 420]

Sybase error code	SQL Anywhere SQLCODE	Message text
3621	-299	Statement interrupted by user [page 696]
3702	-214	Table in use [page 729]
3702	-215	Procedure in use by '%1' [page 635]
3702	-750	User owns procedures in use [page 913]
3702	-751	User owns tables in use [page 914]
3819	-160	Can only describe a SELECT statement [page 255]
4001	-105	Database cannot be started -- %1 [page 364]
4001	-84	Specified database is invalid [page 683]
4001	-72	No database file specified [page 588]
4002	-103	Invalid user ID or password [page 542]
4002	-104	Invalid user ID or password on preprocessed module [page 543]
4002	-1497	The synchronization failed because MobiLink returned authentication status '%1' with value '%2' [page 809]
4224	-108	Connection not found [page 336]
4224	-99	Connections to database have been disabled [page 338]
4224	-308	Connection was terminated [page 337]
4406	-703	Cannot insert or update computed column '%1' [page 288]
4409	-114	Number of columns defined for the view does not match SELECT statement [page 601]
4412	-766	View references '%1', which is a temporary object. Views can only refer to permanent objects [page 923]
4708	-702	TRUNCATE TABLE statement cannot be used on a view [page 854]
4901	-116	Table must be empty [page 730]
4939	-127	Cannot alter a column in an index [page 258]
5006	-604	A dbspace has reached its maximum file size [page 219]
5006	-605	The server attempted to access a page beyond the end of the maximum allowable dbspace file size [page 797]

Sybase error code	SQL Anywhere SQLCODE	Message text
5703	107	Language extension detected in syntax near '%1' on line %2 [page 553]
5849	-201	Invalid setting for option '%1' [page 529]
5849	-1053	'%1' is an invalid value for '%2' [page 208]
5864	-81	Invalid database server command line [page 500]
5864	-735	Invalid parameter [page 515]
5864	-79	Invalid local database option [page 510]
5864	-95	Parse error: %1 [page 616]
5864	-754	Parse error: %1 [page 617]
5878	-204	You do not have '%1' system privilege or authority to set the option '%2' [page 935]
5878	-216	The option '%1' can only be set as a temporary option [page 784]
5878	-217	The option '%1' cannot be set from within a procedure [page 785]
6001	-109	There are still active database connections [page 818]
6004	-75	Request to start/stop database denied [page 646]
6226	-183	Cannot find index named '%1' [page 285]
6259	-263	Invalid absolute or relative offset in FETCH [page 491]
6267	-814	Cannot update column '%1' since it appears in the ORDER BY clause [page 305]
6401	-220	Savepoint '%1' not found [page 660]
7123	-608	Invalid TEXTPTR value used with WRITETEXT or READTEXT [page 535]
7139	-609	Invalid data type for column in WRITETEXT or READTEXT [page 499]
7201	-155	Invalid host variable [page 508]
7203	-89	Database server not running in multi-user mode [page 376]
7301	-192	Update operation attempted on non-updatable query [page 902]

Sybase error code	SQL Anywhere SQLCODE	Message text
7301	-813	FOR UPDATE has been incorrectly specified for a READ ONLY cursor [page 456]
7321	-149	Function or column reference to '%1' must also appear in a GROUP BY [page 464]
7337	101	Value truncated [page 919]
7338	-728	Update operation attempted on non-updatable remote query [page 903]
7364	-139	More than one table is identified as '%1' [page 580]
7374	-676	The specified transaction isolation is invalid [page 804]
7705	-630	Invalid escape sequence '%1' [page 503]
7706	-606	The pattern is too long [page 788]
7707	-629	Invalid escape character '%1' [page 503]
7732	-633	Update operation attempted on a read-only cursor [page 902]
7740	-815	Cannot update column '%1' since it does not appear in the SELECT clause [page 305]
7950	-100	Database server not found [page 375]
7950	-96	Database server already running [page 372]
8201	-640	Invalid descriptor index [page 501]
8205	-641	Error in assignment [page 409]
8405	-210	User '%1' has the row in '%2' locked [page 908]
9119	-78	Dynamic memory exhausted during %1 [page 398]
9502	-638	Right truncation of string data [page 653]
9526	-187	Illegal cursor operation attempt [page 472]
9819	-268	Trigger '%1' not found [page 851]
10356	-624	Expression has unsupported data type [page 427]
11205	-698	The remote server does not support an auto-incrementing data type [page 791]

Sybase error code	SQL Anywhere SQLCODE	Message text
11205	-732	Creating remote tables with computed columns is not supported [page 354]
11205	-736	The data type of column or variable '%1' is not supported [page 754]
11206	-656	Unable to connect to server '%1': %2 [page 862]
11207	-667	Could not access column information for the table '%1' [page 343]
11208	-722	The column '%1' does not exist in the remote table [page 751]
11209	-721	The data type specified for column '%1' is not compatible with the actual data type [page 755]
11210	-723	The length specified for column '%1' is different than the actual length [page 772]
11211	-724	NULL attribute mismatch for column '%1' [page 599]
11212	-725	Identity attribute mismatch for column '%1' [page 471]
11214	-659	Remote server '%1' could not be found [page 642]
11214	-666	The remote table '%1' could not be found [page 792]
11215	-726	The table specification '%1' identifies more than one remote table [page 811]
11221	-712	External login for server '%1' could not be found [page 434]
11227	-706	Remote server does not have the ability to support this statement [page 643]
11248	-658	Remote server '%1' is currently configured as read-only [page 642]
12006	-110	Item '%1' already exists [page 546]
12115	-2072	Could not write the profiler data because the previous session is still being processed. [page 353]
12116	-2071	Could not start a new profiling session because the previous session is still being processed. [page 353]
12118	-2069	The sample wait time cannot be changed once samples have been collected. Clear the sample data and then set the option. [page 794]

Sybase error code	SQL Anywhere SQLCODE	Message text
12119	-2068	The minimum percentage '%1' is invalid. The minimum percentage must be between 0 and 100. [page 781]
12125	-2065	The output path '%1' is invalid [page 786]
12126	-2064	The profiler has not been initialized. Contact SAP support. [page 789]
12127	-2063	The profiler is already running [page 789]
12128	-2062	The profiler is not running [page 789]
12129	-2061	The operation cannot be executed while the profiler is running [page 783]
12130	-2060	There is no profiler data available [page 820]
12131	-2059	A memory error occurred causing the profiler operation to fail [page 222]
12132	-2058	The profiler is not supported [page 790]
12133	-2057	A fatal error has occurred in the profiler library [page 221]
12134	-2056	An internal error has occurred in the profiler library [page 234]
12185	-2000	JWT Provider '%1' does not exist [page 549]
12190	-1994	Offline reset password not supported [page 603]
12191	-1993	Offline reset password is not allowed for user ID '%1' that has no password [page 603]
12192	-1992	Offline reset password failed: %1 [page 602]
12193	-1991	CHAR configuration provided for NCHAR column for text index \"%1\" on table \"%2\" [page 313]
12194	-1990	Failed to load %1 HANA library [page 442]
12196	-1987	Database upgrade not possible; database has auditing enabled [page 377]
12197	-1986	The database must be upgraded to use the KEY option on the SYNCHRONIZE command [page 756]
12200	-1984	Cannot proceed with online backup, SQLA log guid is ahead [page 293]

Sybase error code	SQL Anywhere SQLCODE	Message text
12203	-1979	Cannot create a proxy table LIKE another table [page 270]
12204	-1978	'%1' statement is not allowed as a consumer [page 216]
12207	-1975	Restoring database from an upgrade image [page 651]
12211	-1971	Format string contains more than %2 format specifiers: '%1' [page 460]
12212	-1970	Format string contains invalid format specifiers: '%1' [page 460]
12213	-1969	Operation failed - could not complete checkpoint [page 606]
12214	-1968	Unable to clean directory %1 [page 861]
12215	-1967	Command '%1' received BACKINT_ERROR from HANA [page 330]
12218	-1963	RENAME and FOR REPLICATION cannot be used together [page 644]
12219	-1962	RECOVER UNTIL and FOR REPLICATION cannot be used together [page 639]
12220	-1961	VERIFY and FOR REPLICATION cannot be used together [page 921]
12221	-1960	Unable to save and restart the SQL Anywhere Cockpit when it is not prepared. [page 873]
12222	-1958	DBF parameter cannot be used when the SQL Anywhere Cockpit is being prepared to save. [page 381]
12223	-1959	Unable to prepare to save the SQL Anywhere Cockpit when it is already being prepared. [page 872]
12224	-1955	Cannot save SQL Anywhere Cockpit to existing file '%1' [page 298]
12225	-1954	Unable to prepare to save the SQL Anywhere Cockpit when it is not active. [page 871]
12227	-1950	Option '%1' cannot be used with HSQL COMPATIBLE [page 610]
12228	-1949	Dialect '%1' is not supported by this database [page 390]

Sybase error code	SQL Anywhere SQLCODE	Message text
12230	-1947	Text index \"%1\" on table \"%2\" exists. Table with text index is not supported for LOAD TABLE statement in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 739]
12231	-1946	Table '%1' for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 721]
12232	-1945	VIRTUAL clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 923]
12233	-1944	Error executing BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 408]
12234	-1943	'%1' for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 207]
12235	-1942	Function-name clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 463]
12236	-1941	Unable to start the SQL Anywhere Cockpit: Please restart the server with a minimum page size of 4096 [page 887]
12237	-1940	Logging type ('%1') for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 562]
12238	-1939	Load-source for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 557]
12239	-1938	When wait_for_commit database option is enabled, LOAD TABLE statement is not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 925]
12240	-1937	Table '%1' specified more than once in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 727]
12241	-1936	SQL statements in BEGIN PARALLEL WORK...END PARALLEL WORK statement are not of the same type [page 687]

Sybase error code	SQL Anywhere SQLCODE	Message text
12242	-1935	SQL statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 688]
12243	-1934	Cannot use both the OR REPLACE and IF NOT EXISTS clauses [page 308]
12244	-1933	Duplicate options not allowed in %!s! [page 397]
12245	-1931	PBKDF2 error: %!s! [page 622]
12247	-1928	Error backing up existing log area. Found '%1' logs in '%2' directory [page 407]
12248	-1929	Found a file '%1' with relative path in delta dbspace during backup existing log area. [page 461]
12248	-1927	No external backup identity found for archive file '%1' in HANA strategy document [page 589]
12249	-1926	Unable to start the SQL Anywhere Cockpit: Please restart the server with a minimum page size of 4096 [page 887]
12251	-1925	Possible database corruption found: %1 [page 628]
12252	-1907	Error processing SAP HANA strategy [page 419]
12253	-1908	RESTORE statement missing a FROM clause [page 648]
12253	-1902	Invalid setting '%1' specified for option '%2' for target type '%3' [page 527]
12254	-1909	Cannot use CLEAR LOG clause with off-line log backups [page 309]
12255	-1898	IN-list is too long [page 476]
12256	-1910	Unsupported extended storage syntax [page 899]
12256	-1894	Too many tables in query [page 837]
12257	-1895	Too many columns in schema [page 830]
12257	-1911	Failed to create pipe %1 during BACKUP using BACKINT %2 [page 439]
12258	-1896	Too many columns in row type [page 830]
12258	-1912	Failed to open pipe %1 during BACKUP using BACKINT %2 [page 443]

Sybase error code	SQL Anywhere SQLCODE	Message text
12259	-1899	Statement requires too much memory during %1 [page 698]
12259	-1897	Array contains too many elements [page 241]
12259	-1913	Failed to close pipe %1 during BACKUP using BACKINT %2 [page 437]
12260	-1914	Failed to write pipe %1 during BACKUP using BACKINT %2 [page 448]
12260	-1900	JSON nesting too deep [page 548]
12261	-1889	No stored cache pages [page 594]
12261	-1915	Failed to read pipe %1 during BACKUP using BACKINT %2 [page 443]
12261	-1892	JSON object contains too many properties [page 549]
12262	-1888	Reading %1 database pages exceeds available cache of %2 pages [page 638]
12262	-1916	SAP HANA environment error, unable to execute command on name server [page 660]
12262	-1893	JSON array contains too many elements [page 548]
12263	-1887	Feature '%1' is not supported for this database [page 450]
12263	-1917	Invalid BACKUP operation or type specified: %1 [page 493]
12264	-1886	Scalar variable '%1' not found [page 661]
12264	-1918	Verify fails, bytes written to pipe %1 and bytes written to file %2 [page 922]
12265	-1885	Stop listener error: %1 [page 700]
12265	-1919	BACKINT configuration file error. %1 [page 247]
12266	-1884	The address parameter "%1" provided to stop a listener has an invalid IP address or no port [page 748]
12266	-1920	SAP HANA environment error, unable to ping name server [page 659]
12267	-1883	Address parameter "%1" is not supported to start a listener for the personal database server [page 227]
12267	-1921	Failed to get BACKUP id for file name %1 [page 440]

Sybase error code	SQL Anywhere SQLCODE	Message text
12268	-1922	Error in parsing BACKINT configuration file [page 410]
12268	-1882	There is already a database variable named '%1' [page 818]
12269	-1881	Procedure '%1' needs a RESULT clause for returned ROW or ARRAY [page 633]
12270	-1880	Failed to get file system statistics for the path '%1' [page 441]
12271	-1879	Failed to get status information on the path '%1': %2 [page 441]
12272	-1878	The SQL Anywhere Cockpit template '%1' cannot be used for the current operation [page 805]
12273	-1877	Encryption failed for the SQL Anywhere Cockpit setting file. Error message '%1' [page 401]
12274	-1876	Failed to rename the SQL Anywhere Cockpit file '%1' to '%2': %3 [page 444]
12275	-1872	Unable to upgrade the SQL Anywhere Cockpit when it is not active [page 889]
12275	-1957	Unable to stop the SQL Anywhere Cockpit when it is being prepared to save. [page 889]
12276	-1871	Unable to stop the SQL Anywhere Cockpit when it is being started [page 888]
12277	-1870	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is stopping [page 383]
12278	-1869	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is active [page 381]
12279	-1868	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is starting [page 383]
12280	-1867	DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is being started [page 382]
12281	-1866	Unable to start the SQL Anywhere Cockpit when it is stopping [page 886]

Sybase error code	SQL Anywhere SQLCODE	Message text
12281	-1874	Invalid empty string specified as 'ESCAPE CHARACTER' option of LOAD or UNLOAD TABLE [page 502]
12282	-1865	Failed to write the SQL Anywhere Cockpit setting file '%1' [page 448]
12283	-1864	Failed to read the SQL Anywhere Cockpit setting file '%1' [page 444]
12284	-1863	Failed to access the SQL Anywhere Cockpit file '%1': %2 [page 436]
12285	-1875	Unable to find the cockpit parameters used to start or stop [page 868]
12286	-1861	Failed to delete the SQL Anywhere Cockpit file '%1': %2 [page 440]
12287	-1860	The SQL Anywhere Cockpit template file '%1' not found [page 806]
12288	-1859	Failed to copy the SQL Anywhere Cockpit template file '%1' to destination '%2' [page 439]
12289	-1858	Unable to open the SQL Anywhere Cockpit template -- '%1' [page 870]
12290	-1855	Remote server is currently in use and cannot be dropped [page 643]
12292	-1853	Invalid event parameter for event '%1' [page 504]
12293	-1852	Invalid repeat interval for event '%1' [page 524]
12294	-1851	Unable to start the SQL Anywhere Cockpit: %1 [page 887]
12295	-1850	Too many mutexes and semaphores created [page 834]
12296	-1849	Too many temporary mutexes and semaphores created [page 837]
12297	-1847	UNPIVOT error: Cannot create valid identifiers for IN clause items [page 898]
12298	-1846	PIVOT error: PIVOT XML does not contain a valid subquery, ANY, or ALL in the IN clause [page 624]
12300	-1845	PIVOT error: Too many aggregate functions and IN clause items [page 624]
12301	-1843	The database name is reserved for SQL Anywhere Cockpit [page 757]

Sybase error code	SQL Anywhere SQLCODE	Message text
12302	-1842	Cannot change the setting of the SingleCLRInstanceVersion server option after the CLR external environment has already been started [page 263]
12303	-1841	The SQL Anywhere Cockpit '%1' cannot be used for the current operation [page 805]
12304	-1840	The database '%1' cannot be used for the SQL Anywhere Cockpit [page 755]
12305	-1873	Unable to finish upgrade the SQL Anywhere Cockpit when it is not active [page 869]
12306	-1857	RESTORE unable to find a log backup on the latest timeline [page 649]
12308	-1836	Invalid cockpit parameter [page 495]
12309	-1835	%2 error occurred while trying to read file %1 during backup [page 217]
12310	-1834	Unable to start specified database: Cannot use log file '%1' since the timeline does not match the timeline of the database file [page 884]
12312	-1832	Cannot specify read only in both the READ ONLY clause and the USING clause [page 301]
12313	-1831	Mutex "%1" is locked by another connection [page 583]
12314	-1830	User owns locked mutexes [page 913]
12318	-1826	PIVOT error: only one aggregate function can be specified without an alias [page 623]
12319	-1825	Cannot change the setting of the UseSingleJVMInstance server option after Java has already been started [page 264]
12323	-1821	Start listener error: %1 [page 693]
12324	-1820	Invalid ROW or ARRAY domain [page 526]
12325	-1819	Indirect identifier '['%1']' yielded an invalid identifier name '%2' [page 483]
12326	-1818	Indirect identifiers not supported [page 483]
12327	-1817	UNPIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 898]

Sybase error code	SQL Anywhere SQLCODE	Message text
12328	-1816	Invalid generated identifier '%1' [page 506]
12329	-1815	Unsupported use of ROW type in an INTO clause [page 900]
12330	-1814	The variable in the INTO clause is not a row type [page 817]
12331	-1813	Mutex "%1" was not locked by this connection [page 584]
12332	-1812	Mutex "%1" with transaction scope cannot be released [page 584]
12333	-1811	Invalid timeout value %1 [page 536]
12334	-1810	Invalid increment value for semaphore "%1": %2 [page 509]
12335	-1809	Temporary mutex or semaphore can only be dropped by the connection that created it [page 736]
12336	-1808	Semaphore "%1" not found [page 665]
12337	-1807	Mutex "%1" not found [page 583]
12338	-1806	Deadlock involving a mutex detected [page 385]
12339	-1805	Semaphore was dropped [page 665]
12340	-1804	Mutex was dropped [page 585]
12341	-1803	Invalid start value for semaphore "%1": %2 [page 533]
12342	-1802	Cannot create mutex "%1" as a temporary mutex with this name already exists [page 272]
12343	-1801	Cannot create semaphore "%1" as a temporary semaphore with this name already exists [page 273]
12344	-1800	Cannot create semaphore "%1": %2 with this name already exists [page 274]
12345	-1799	Cannot create mutex "%1": %2 with this name already exists [page 273]
12346	-1798	PIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 623]
12347	-1796	The OData server returned an error: %1 [page 782]
12348	-1795	Expression of type %1 is not allowed in this context (near: %2) [page 429]

Sybase error code	SQL Anywhere SQLCODE	Message text
12349	-1794	Table reference '%1' has been invalidated [page 732]
12350	-1793	Table reference types not supported [page 733]
12351	-1792	Invalid use of table reference type [page 542]
12353	-1790	Time zone option error: %1 [page 825]
12354	-1789	Storing time zone information is not supported for this database [page 702]
12355	-1788	Time zone '%1' not found [page 825]
12356	-1785	Invalid address parameter "%1" provided to stop a listener [page 492]
12357	-1783	Invalid address parameter "%1" provided to start a listener [page 491]
12358	-1782	Listener type "%1" failed to initialize when starting a listener [page 556]
12359	-1781	The last HTTP or HTTPS listener cannot be stopped without using the force parameter [page 770]
12360	-1780	No running shared memory listener was found [page 594]
12361	-1779	Shared memory listener already started [page 676]
12362	-1778	Database upgrade not possible; user-defined database option "%1" conflicts with the system-defined database option with the same name [page 379]
12363	-1777	Database connection limit exceeded [page 365]
12364	-1776	%1 listener start option includes an unsupported option: %2 [page 214]
12365	-1775	%1 listener start option parse error: %2 [page 214]
12366	-1774	OData Producer option error: %1 [page 602]
12367	-1773	OData Producer '%1' not found [page 601]
12368	-1772	Storing OData Producers is not supported for this database [page 701]
12370	-1770	The USING LOG PATH clause must be used in conjunction with the RECOVER UNTIL clause [page 814]

Sybase error code	SQL Anywhere SQLCODE	Message text
12371	-1769	Cannot convert value to a timestamp [page 269]
12372	-1768	The last shared memory or TCPIP listener cannot be stopped without using the force parameter [page 770]
12373	-1767	%1 listener for the address parameter "%2" is not found [page 213]
12374	-1766	%1 listener binding failure for the address parameter "%2" [page 213]
12375	-1765	The address parameter "%1" conflicts with an existing %2 listener [page 747]
12376	-1764	REORGANIZE TABLE ran out of space [page 645]
12379	-1761	Host variables must not be used in this context [page 468]
12381	-1797	Cannot drop the database's current time zone [page 284]
12389	-1753	Transact-SQL expression in a non-Transact-SQL statement near '%1' %2 [page 846]
12394	-1749	The PAM User Authentication (PAMUA) feature is not supported on this computer [page 787]
12395	-1742	DBA password must be specified in the CREATE DATABASE statement [page 380]
12396	-1741	DBA user ID must be specified in the CREATE DATABASE statement [page 380]
12397	-1740	Cannot load encryption DLL %1: version mismatch [page 288]
12398	-1739	Need a function entry point [page 587]
12399	-1738	Cannot create table '%1': Name is used by a non-table object [page 275]
12400	-1737	Number of columns defined for the table does not match SELECT statement [page 600]
12401	-1736	Debugger error: %1 [page 386]
12402	-1735	Cursor %1 cannot be used to declare a row variable using %ROWTYPE [page 355]
12403	-1734	Unable to declare a row variable from the cursor using %ROWTYPE; no fields were found in the cursor [page 866]

Sybase error code	SQL Anywhere SQLCODE	Message text
12404	-1733	Unable to declare a row variable from the cursor using %ROWTYPE; invalid name for field %1 [page 865]
12405	-1729	Cannot create base table '%1': A global temporary table with the same name exists [page 271]
12406	-1730	Cannot create global temporary table '%1': A base table with the same name exists [page 271]
12407	-1731	Cannot set audit_log to the transaction log: The transaction log is not enabled for the database [page 299]
12408	-1732	Cannot update the audit_log option: one or more of the specified targets is invalid [page 308]
12409	-1728	Function '%1' has invalid parameter '%2' ('%3') [page 462]
12410	-1727	Use of %TYPE or %ROWTYPE is not allowed for variable or temporary objects [page 903]
12412	-1725	Failed to set up audit log session for database '%1' [page 445]
12413	-1724	The variable '%1' must be %2 in this context [page 816]
12414	-1723	The length of the variable '%1' is too long in this context; it exceeds the limit of %2 bytes [page 771]
12415	-1722	The variable '%1' must not be NULL in this context [page 817]
12421	-1715	Invalid options for UPGRADE: SCRIPT FILE can only be specified with RESTART [page 513]
12422	-1716	Statement %1 disallowed during upgrade from script [page 694]
12423	151	UltraLite performed database recovery on startup [page 859]
12424	-1714	The dbmsync server did not have sufficient database permissions [page 759]
12431	-1709	Invalid DEFAULT value near '%1' on line %2 [page 501]
12432	-1710	Invalid value for INSERT near '%1' on line %2 [page 544]
12432	-1704	Remote column %1 has been specified with the wrong case [page 641]

Sybase error code	SQL Anywhere SQLCODE	Message text
12433	-1703	The user name specified must be the user name of the current connection [page 813]
12434	-1701	TDS login requests with RSA encrypted passwords must also use a nonce [page 735]
12435	-1700	TDS login requests with unencrypted passwords are not permitted [page 736]
12437	-1698	change_password_dual_control is enabled for this user. Use ALTER USER to change password [page 312]
12439	-1685	There was insufficient memory to complete the %1 operation [page 821]
12440	-1686	Invalid parameter was used in the call to %1 [page 515]
12440	-1684	Trace target option '%1' conflicts with option '%2' [page 845]
12441	-1687	The secure feature key name '%2' is not valid in the call to %1 [page 796]
12442	-1688	An invalid authorization code was specified in the call to %1 [page 235]
12442	-1683	Cannot change the mirror server type from %1 to %2 [page 262]
12443	-1689	An invalid secure feature list '%2' was specified in the call to %1 [page 237]
12443	-1680	Invalid variable or type [page 545]
12444	-1690	You are not authorized to assign the feature list '%2' to a secure feature key using %1 [page 932]
12444	-1679	Error at offset '%1': mismatched object or array terminator [page 405]
12445	-1691	You are not authorized to change the secure feature key named '%2' using %1 [page 933]
12445	-1678	Error at offset '%1': expected JSON name/value pair [page 403]
12446	-1692	Call to %1 failed - the maximum number of secure feature keys has already been created [page 252]
12446	-1677	Error at offset '%1': expected token '%2' [page 403]
12447	-1693	Call to %1 failed - the secure feature key named '%2' already exists [page 253]

Sybase error code	SQL Anywhere SQLCODE	Message text
12447	-1676	Error at offset '%1': invalid data [page 404]
12448	-1694	Call to %1 failed - the secure feature key named '%2' does not exist [page 254]
12448	-1675	Error at offset '%1': unexpected trailing text [page 406]
12449	-1695	Call to %1 failed - the authorization code specified for the secure feature key named '%2' is incorrect [page 251]
12449	-1674	Error at offset '%1': unexpected token '%2' [page 405]
12450	-1696	Call to %1 failed - the key named '%2' is the last key with the MANAGE_FEATURES and MANAGE_KEYS features [page 252]
12450	-1673	A disk sandbox error occurred for database '%1' when finding the full path for file '%1' [page 220]
12451	-1672	A disk sandbox error occurred for database '%1' when determining the disk sandbox status for file '%2' [page 219]
12452	-1681	Procedure is currently being altered or dropped [page 635]
12452	-1671	The file '%1' is invalid when the disk sandbox feature is enabled for database '%2' [page 763]
12457	-1666	Expression is not an array [page 428]
12458	-1665	Cannot change password because change_password_dual_control process is in progress [page 260]
12459	-1664	Prevented removal of LDAP server "%1" because it is the only LDAP server and the value of login_mode is "LDAPUA" [page 628]
12460	-1663	Prevented removal of LDAP server because it is referenced by login policy "%1" which is the only login policy with an LDAP server and the value of login_mode is "LDAPUA" [page 629]
12461	-1659	File or directory %1 not found [page 455]
12462	-1660	Fail to compare %1 and %2 [page 436]
12463	-1661	%1 is not a directory [page 210]

Sybase error code	SQL Anywhere SQLCODE	Message text
12464	-1662	%1 and %2 must not be the same [page 205]
12464	-1655	Invalid value for login policy option "%1" [page 545]
12467	-1640	Too many active trace event sessions [page 828]
12468	-1639	Database alter failed: %1 [page 363]
12468	-1641	Trace event session '%1' already active [page 840]
12469	-1634	The specified session name '%1' is not valid [page 803]
12469	-1642	One or more targets in the trace event session '%1' failed to start [page 604]
12470	-1635	Trace event '%1' already exists [page 839]
12470	-1643	Trace event session '%1' failed to start [page 844]
12471	-1638	Too many arguments for trace event '%1' [page 829]
12471	-1644	Trace event session '%1' is already stopped [page 845]
12472	-1637	Trace event session '%1' is active. Stop active session before dropping the session [page 844]
12472	-1645	Trace event session '%1' already has trace event '%2' [page 842]
12473	-1633	Trace event '%1' is not valid [page 839]
12473	-1646	The specified target type '%1' is not valid [page 804]
12474	-1647	Unknown option '%1' specified for target type '%2' [page 896]
12474	-1632	Dropping or altering arbiter "%1" requires a connection to the partner [page 395]
12475	-1631	Use of table privilege '%1' is not supported on the current database [page 905]
12475	-1648	The option '%1' was not specified for target type '%2' [page 786]
12476	-1636	Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first [page 840]

Sybase error code	SQL Anywhere SQLCODE	Message text
12476	-1649	Trace event session '%1' already has target type '%2' [page 841]
12477	-1650	Trace event session '%1' does not have trace event '%2' [page 843]
12477	-1629	Only one IDENTIFIED BY value may be specified [page 604]
12478	-1651	Trace event session '%1' does not have target type '%2' [page 842]
12479	-1652	Trace event session '%1' already exists [page 841]
12479	-1627	TLS ON cannot be used with URL %1 [page 826]
12481	-1625	The UltraLite database deploy file is invalid (code: %1, file: %2) [page 812]
12482	-1624	The length of the value specified is too long, it exceeds the limit of %1 bytes [page 771]
12483	-1623	The search on LDAP server %1 completed with no matching results [page 794]
12484	-1622	Bind to LDAP server %1 without a password is not allowed [page 250]
12485	-1621	LDAP server %1 may not accept anonymous binds [page 554]
12486	-1620	The value specified is not within the required range %1 to %2 [page 816]
12489	-1617	The %1 remote data access class is no longer supported, please use %2 instead [page 744]
12493	-1613	Tag ID: '%1' specifies a value not bounded by an array [page 734]
12494	-1612	Cannot ALTER LDAP SERVER '%1' while LDAP server is in active state [page 258]
12495	-1611	Unable to copy file %1 [page 864]
12496	-1610	Unable to create directory %1 [page 865]
12497	-1609	File %1 already exists [page 454]
12498	-1608	Unable to delete file %1 [page 867]
12499	-1607	Outer references are not allowed for TPF input tables [page 612]

Sybase error code	SQL Anywhere SQLCODE	Message text
12500	-1605	Table Parameterized Functions and V4 TableUDFs are not supported for this database [page 731]
12501	-1606	Multiple table parameters are not supported [page 581]
12503	-1603	The search using '%1' failed due to one or more invalid values set [page 795]
12504	-1602	The specified distinguished name '%1' does not match the search result '%2' [page 801]
12505	-1601	Password encryption failed. Error message '%1' [page 619]
12506	-1600	The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2' [page 750]
12507	-1599	Invalid use of collection type [page 540]
12508	-1598	Array element error: array index '%1' is out of range [page 241]
12509	-1597	The transaction may not be committed because the primary server lost quorum [page 812]
12510	-1596	Database contains users with 'SYS_' prefix and '_ROLE' suffix [page 366]
12511	-1594	LDAP server definition of "%1" is incomplete. A search URL, access distinguished name, password, and authentication URL are required [page 555]
12512	-1593	Unable to copy file %1 to destination %2 [page 864]
12513	-1592	Text indexes on materialized views are not supported for this database [page 742]
12514	-1591	Invalid use of BEFORE operator in text query [page 540]
12515	-1590	You cannot use a security token when making remote connections [page 934]
12516	-1589	Certificate '%1' not found [page 312]
12517	-1588	The specified certificate is not valid [page 800]
12518	-1587	Storing certificates is not supported for this database [page 701]
12519	-1586	Error modifying refresh type for text index "%1" on materialized view "%2" [page 411]

Sybase error code	SQL Anywhere SQLCODE	Message text
12520	-1585	Invalid tool name or admin user for generating security token [page 537]
12521	-1584	Unable to load the dbrsakup shared object [page 869]
12523	-1582	Server name can only be specified when connecting to a cloud database server with NODETYPE=DIRECT [page 670]
12524	-1581	Database name must be specified when connecting to a cloud database server [page 368]
12525	-1580	Failed to load the MobiLink client support libraries [page 442]
12526	-1579	External procedures or functions are not allowed across server types [page 435]
12527	-1578	Table parameterized functions are not allowed across server types [page 732]
12529	-1576	LDAP server "%1" is in use by login policy "%2" [page 554]
12531	-1574	You must upgrade your database in order to use the MIRROR server class [page 935]
12532	-1573	MIRROR server class is not supported for SAP IQ databases [page 575]
12533	-1572	LDAP User Authentication feature is not supported in this database [page 555]
12534	-1571	The attempt to drop LDAP server "%1" failed, suspend the server to drop it [page 749]
12535	-1570	Attempt to allocate memory for LDAP server "%1" failed [page 243]
12536	-1569	LDAP Server "%1" already exists [page 553]
12538	-1567	External environment cannot be started, external process terminated on start up [page 430]
12539	-1566	Cannot drop a role that owns external environment objects in runtime server [page 279]
12540	-1565	Cannot drop a role that owns web services in runtime server [page 280]
12541	-1564	Cannot drop a role that owns events in runtime server [page 278]

Sybase error code	SQL Anywhere SQLCODE	Message text
12542	-1563	Cannot drop a role that owns sequences in runtime server [page 279]
12543	-1562	The role '%1' was not dropped because it is granted to other users or roles. Use the 'WITH REVOKE' option to drop it [page 793]
12544	-1561	Use of WITH DROP OBJECTS is not allowed with '%1' [page 905]
12545	-1560	Specified role '%1' is a user extended as role [page 685]
12546	-1559	Specified role '%1' is not a user extended as role [page 685]
12547	-1558	Specified user '%1' is a role [page 686]
12548	-1557	External environment cannot be started during database startup [page 430]
12549	-1556	External environment failed to start and establish a connection within the %1 second timeout [page 432]
12550	-1555	Statement not allowed on text index for a materialized view [page 698]
12551	-1554	Specified LDAP server '%1' is not found [page 684]
12552	-1553	Cannot perform specified operation, set user condition violated [page 292]
12553	-1552	Invalid text index type for the materialized view [page 535]
12554	-1551	Login redirection is required to complete the connection, but it is not supported by the client [page 565]
12564	-1541	Specified System Privilege '%1' is Invalid [page 686]
12565	-1540	Operation would cause a role cycle [page 610]
12566	-1539	Use of WITH NO SYSTEM PRIVILEGE INHERITANCE option is not allowed with %1 [page 906]
12567	-1538	User or Role ID '%1' does not exist [page 913]
12568	-1537	Role "%1" already exists [page 654]
12569	-1536	Invalid user ID or role name '%1' specified [page 543]

Sybase error code	SQL Anywhere SQLCODE	Message text
12570	-1535	System Privileges and Roles feature is not supported in this database [page 719]
12573	-1532	Failed to transform point %1 (error %2) [page 447]
12574	-1531	Geometry expressions cannot be used in the ORDER BY specification (near '%1') [page 465]
12575	-1530	Format '%1' is not supported in the UNLOAD statement [page 459]
12576	-1529	Outer reference not permitted in DML derived table [page 612]
12577	-1528	No more role grant permitted [page 591]
12578	-1527	Task '%1' is not allowed [page 734]
12579	-1525	Cannot perform specified operation, number of administrators for role '%1' falls below min_role_admins option value [page 292]
12579	-1526	Text index %1 cannot be used with text procedure %2 [page 740]
12582	-1522	Database needs to be upgraded to support the use of external libraries with text indexes [page 369]
12588	-1516	The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points [page 769]
12589	-1515	Support for spatial is not available for this CPU [page 707]
12592	-1512	Text index with external prefilter cannot contain both binary and string columns [page 740]
12593	-1511	Text indexes are not allowed across server types [page 741]
12594	-1509	The materialized view cannot be changed to immediate because the primary key columns of any table in the preserved side of an OUTER JOIN must exist in the SELECT list [page 780]

Sybase error code	SQL Anywhere SQLCODE	Message text
12595	-1508	The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list [page 775]
12596	-1507	The materialized view cannot be changed to immediate because the ON conditions refer to tables which are not in the null-supplying and preserved sides of the OUTER JOINS [page 779]
12597	-1506	Unknown collation '%1' [page 894]
12598	150	Database contains no tables to synchronize [page 365]
12599	-1398	VERIFY and RENAME cannot be used together [page 921]
12600	-1787	CATALOG ONLY and MULTIPLEX cannot be used together [page 311]
13075	102	Using temporary table [page 916]
13080	-1510	Cannot specify range that excludes next value for sequence %1 [page 300]
13081	-1491	CircularString with 3 points has been converted to use 5 points [page 317]
13082	-1490	Polygon ring order has been reoriented [page 626]
13083	-1489	Position %1 is invalid (should be between %2 and %3) [page 627]
13084	-1488	Invalid polygon: ring is larger than allowed for SRID=%1 (near '%2') [page 519]
13085	-1487	Invalid polygon: curve is not a ring [page 517]
13086	-1486	Invalid polygon: ring has zero area (near '%1') [page 519]
13087	-1485	Invalid polygon: ring is not closed (near '%1') [page 520]
13088	-1484	Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%) [page 917]
13089	-1483	LineString must contain at least 2 points (near '%1') [page 556]
13090	-1482	Curve contains nearly antipodal points %1 and %2 (near '%3') [page 359]
13092	-1480	An internal error has occurred in the spatial library [page 235]

Sybase error code	SQL Anywhere SQLCODE	Message text
13093	-1479	An expression of type %1 is not union-compatible with type %2 [page 233]
13094	-1478	ST_Geometry arguments not supported by SQL function %1 [page 691]
13095	-1477	The SRID %1 does not identify a geographic spatial reference system [page 807]
13096	-1476	SRID %1 is referenced by domain "%3"."%2" [page 690]
13097	-1475	SRID %1 is referenced by parameter '%2' of procedure '%3' [page 691]
13098	-1474	SRID %1 is referenced by column '%2' of table '%3' [page 690]
13099	-1473	Spatial unit of measure "%1" is reserved [page 682]
13100	-1472	Spatial reference system "%1" is reserved [page 679]
13101	-1471	Spatial reference system %1 cannot be modified because it is in use [page 680]
13102	-1470	Invalid storage format '%1' [page 534]
13103	-1469	The specified polygon format '%1' is not supported for this type of spatial reference system [page 803]
13104	-1468	The specified axis order is not supported for this type of spatial reference system [page 800]
13105	-1467	Coordinate bounds missing for coordinate %1 [page 342]
13106	-1466	Ellipsoid parameters specified for non-geographic spatial reference system [page 400]
13107	-1465	Ellipsoid parameters missing for geographic spatial reference system [page 400]
13108	-1464	The spatial reference system type is not supported ('%1') [page 799]
13109	-1463	Error parsing definition string '%1' [page 413]
13110	-1462	Spatial reference system must specify the SRID to use [page 681]
13111	-1461	Spatial reference system '%1' already exists [page 680]

Sybase error code	SQL Anywhere SQLCODE	Message text
13112	-1460	Unit of measure '%1' already exists [page 892]
13113	-1459	Spatial reference system '%1' not found [page 681]
13114	-1458	Unit of measure '%1' not found [page 893]
13115	-1457	The string '%1' is not a valid coordinate name [page 808]
13116	-1456	The string '%1' is not a valid axis order [page 808]
13117	-1455	The CONVERT USING clause must be specified when creating a unit of measure [page 753]
13118	-1454	Spatial column '%1' cannot be included in an index because it is not constrained to a single SRID [page 678]
13119	-1453	Spatial column '%1' cannot be included in a primary key or unique index [page 677]
13120	-1452	Table '%1' contains a spatial column '%2' and no primary key [page 720]
13121	-1451	Invalid polygon: multiple exterior rings [page 518]
13122	-1450	Invalid polygon nesting [page 517]
13123	-1449	Invalid polygon: no exterior ring [page 518]
13124	-1448	Invalid polygon format '%1' [page 516]
13125	-1447	Unit of measure "%1" is not an angular unit [page 892]
13126	-1446	Unit of measure "%1" is not a linear unit [page 891]
13127	-1445	Transform from SRID %1 not supported [page 849]
13128	-1444	Transform from SRID %1 to %2 not supported [page 850]
13129	-1443	Transform definition is too long [page 849]
13130	-1442	Invalid transform definition '%1' [page 537]
13131	-1441	Invalid spatial reference system well-known-text (WKT) [page 530]
13132	-1440	The comparison '%1' cannot be used with geometries [page 752]

Sybase error code	SQL Anywhere SQLCODE	Message text
13133	-1439	Invalid configuration name %1 [page 497]
13134	-1438	Error reading configuration file [page 420]
13135	-1505	Mirror server "%1" defined with type COPY does not include a parent definition [page 573]
13136	-1436	A geometry with SRID=%1 is not supported when computing distance between non-point geometries [page 222]
13137	-1435	A geometry with SRID=%1 is not supported for method %2 [page 221]
13138	-1434	The data is not in a recognized format [page 754]
13139	-1433	The value '%2' is not a valid setting for the '%1' format specification option [page 815]
13140	-1432	The format specification option '%1' is not recognized [page 764]
13141	-1431	The format specification syntax is invalid [page 764]
13142	-1430	An input string in '%1' format cannot be used here [page 234]
13143	-1429	The format type '%1' cannot be used here [page 765]
13144	-1428	The format type '%1' is not recognized [page 765]
13145	-1427	The embedded SRID are inconsistent (%1 and %2) [page 763]
13146	-1426	The embedded SRID (%1) conflicts with the provided SRID (%2) [page 762]
13147	-1425	The multi patch shapefile shape is not supported [page 782]
13148	-1424	Invalid shapefile filename [page 530]
13149	-1423	Error parsing shapefile attributes [page 414]
13150	-1422	Error parsing shapefile record [page 415]
13151	-1421	Error parsing well-known-binary (WKB): invalid byte order mark %1 at offset %2 [page 416]

Sybase error code	SQL Anywhere SQLCODE	Message text
13152	-1420	Error parsing well-known-binary (WKB): inconsistent dimensions at offset %1 [page 416]
13153	-1419	Error parsing well-known-binary (WKB): unexpected end of input [page 418]
13154	-1418	Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent [page 417]
13155	-1417	Error parsing well-known-binary (WKB): type code %1 at offset %2 is invalid [page 417]
13156	-1504	Error from external library: -%1: %2 [page 409]
13157	-1415	Error parsing geometry internal serialization at offset %1 [page 414]
13158	-1414	Error parsing well-known-text (WKT): inconsistent dimensions at offset %1 [page 419]
13159	-1413	Spatial feature %1 is not supported [page 678]
13160	-1412	Support for spatial is not available for this database [page 708]
13161	-1411	Cannot convert from %1 to %2 (near %3) [page 268]
13162	-1410	An ST_CircularString cannot be constructed from %1 points (near '%2') [page 238]
13163	-1409	Unknown spatial reference system (%1) [page 896]
13164	-1408	Mixed coordinate dimensions [page 577]
13165	-1407	Error parsing well-known-binary (WKB) at offset %1 [page 415]
13166	-1406	Error parsing well-known-text (WKT) scanning '%1' at offset %2 [page 418]
13167	-1405	Failed to transform geometry (error %1) [page 447]
13168	-1404	Unknown unit of measure '%1' [page 897]
13169	-1403	Non-contiguous curves near '%1' [page 596]
13170	-1402	Mixed spatial reference systems %1 and %2 (near %3) [page 577]

Sybase error code	SQL Anywhere SQLCODE	Message text
13171	-1401	Element is an empty set (near '%1') [page 399]
13172	-1400	Point is duplicated %1 [page 626]
13173	-1399	Invalid intersection matrix '%1' [page 509]
13174	-1397	The definition of temporary table '%1' has changed since last used [page 762]
13175	-1395	Invalid external term breaker name specified [page 506]
13176	-1394	Invalid external prefilter name specified [page 505]
13177	-1393	Error initializing external term breaker [page 411]
13178	-1392	Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database [page 891]
13178	-1396	Error initializing external prefilter [page 410]
13179	-1389	The value for the stoplist cannot be NULL [page 815]
13180	-1390	An incremental refresh is not possible when handles are exhausted [page 233]
13180	-1388	Failed to start the dbmlsync server. Check the dbmlsync log file for more details [page 446]
13181	-1391	Invalid stoplist value [page 534]
13181	-1387	Failed to shut down the dbmlsync server. Check the dbmlsync log file for more details [page 445]
13182	-1386	Failed to connect to the dbmlsync server. Check the dbmlsync log file for more details [page 438]
13183	-1385	Synchronization failed. Check the dbmlsync log file for more details [page 710]
13184	-1384	Unable to stop specified database: %1 [page 888]
13185	-1383	The licensed maximum number of mirror servers with type COPY has been exceeded [page 772]
13186	-1382	Download failed due to an invalid or unsupported row value [page 393]

Sybase error code	SQL Anywhere SQLCODE	Message text
13187	-1381	Database server name '%1' cannot be the same as either the primary or mirror server [page 375]
13188	-1380	Client redirected more than once [page 321]
13189	-1373	Synchronization failed with internal error: %1 [page 709]
13190	-1372	The server is not able to establish TCP/IP connections [page 798]
13190	-1374	Synchronization failed. Check the results of the call to sp_get_last_synchronize_result(%1) for more information [page 710]
13191	-1371	The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN [page 778]
13191	-1375	Failed to start the dbmsync server [page 446]
13192	-1376	Failed to connect to the dbmsync server [page 437]
13192	-1370	Text queries cannot contain more than 300 terms [page 742]
13193	-1369	Sequence generators are not supported for this database [page 668]
13193	-1377	The SYNCHRONIZE statement timed out [page 810]
13194	-1378	The database server failed to shut down the dbmsync server [page 758]
13195	-1367	User owns sequences in use [page 914]
13195	-1379	The dbmsync server failed to shut down in a timely manner [page 760]
13196	-1366	Sequence '%1' in use by another connection [page 667]
13197	-1503	Operation not supported for ST_GeomCollection with intersecting elements (near "%1") [page 609]
13198	-1492	Could not create a text index without external prefilter library on column "%1" [page 345]
13199	-1363	The 'currval' operator is not defined yet for sequence '%1' for this connection [page 746]

Sybase error code	SQL Anywhere SQLCODE	Message text
13200	-1362	Cannot treat value '%1' as type %2. The dynamic type is %3 [page 303]
13201	-1361	TREAT AS can only be used with extended types. Cannot treat %1 as a %2 [page 851]
13202	-1360	Cannot assign automatic mirror server parent [page 260]
13203	-1357	Multiple settings of same option specified for sequence '%1' [page 581]
13204	-150	Invalid use of an aggregate function [page 539]
13204	-1356	Definition for sequence '%1' is invalid [page 389]
13205	-1355	No more values available in sequence %1 [page 591]
13205	-1352	Mirror server with type '%1' is already defined [page 576]
13206	-1354	Sequence '%1' already exists [page 666]
13206	-1351	Mirror child server creation failed [page 571]
13207	-1353	Invalid operation '%2' on sequence '%1' [page 512]
13207	-1350	The parent of this mirror server is not the primary server [page 788]
13208	-1358	Sequence name '%1' is ambiguous [page 668]
13208	-1349	The parent of this mirror server is not currently connected [page 787]
13209	-1359	Sequence '%1' not found [page 667]
13209	-1348	Mirror server name '%1' does not match current server name [page 575]
13210	-1493	Could not create a text index with external prefilter library on column "%1" [page 345]
13212	-1344	Rollback occurred due to blocking_others_timeout [page 654]
13213	-1343	Feature '%1' is locked because synchronization is in progress [page 449]
13214	-1342	Data modifications are not allowed in a synchronization schema change [page 361]

Sybase error code	SQL Anywhere SQLCODE	Message text
13215	-1341	The instantiation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 768]
13216	-1340	Type '%1' cannot be instantiated with %2 arguments (near '%3') [page 855]
13217	-1339	Method '%1' cannot be called with %2 arguments (near '%3') [page 570]
13218	-1338	Type '%1' is not instantiable (near '%2') [page 857]
13219	-1337	Method invocation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 571]
13220	-1336	Type '%1' has no method named '%2' (near '%3') [page 856]
13221	-1335	Type '%1' does not support method calls (near '%2') [page 856]
13222	-1334	Feature '%1' is locked by another connection [page 449]
13223	-1333	Feature '%1' was not locked by this connection [page 452]
13224	-1332	Feature '%1' is unknown or invalid [page 450]
13225	-1331	The function '%1' requires the use of the '%2' clause [page 766]
13226	-1330	The function '%1' does not allow use of the '%2' clause [page 766]
13227	-1329	This operation is only allowed within a synchronization schema change [page 823]
13228	-1328	Table '%1' must synchronize to be in publication '%2' [page 725]
13229	-1327	The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression [page 778]
13230	-1326	Subscription '%1' not found [page 704]
13231	-1325	Column subset for table '%1' in publication '%2' does not match that specified in publication '%3' [page 329]
13232	-1324	Connection is not allowed to have table locks when executing this statement [page 336]

Sybase error code	SQL Anywhere SQLCODE	Message text
13233	-1323	Subscription to publication '%1' for '%2' omitted from statement [page 705]
13234	-1322	A synchronization schema change is already in progress [page 225]
13235	-1321	Table or view '%1' is not valid for use with this statement [page 731]
13237	-1319	Synchronization schema changes and script versions are not supported for this database [page 716]
13238	-1318	More articles are being dropped from publication '%1' than are defined [page 579]
13241	-1315	Script file missing statement "go" delimiter on a separate line [page 663]
13242	-1314	Cannot force failover when current server is marked as preferred [page 287]
13243	-1267	Event parameter '%1' not found [page 426]
13244	-1266	No notification within timeout on queue '%1' [page 592]
13245	-1265	Event object named '%1' already exists [page 426]
13246	-1264	Event object name '%1' is not valid [page 425]
13247	-1263	Event notification queue '%1' not found [page 423]
13248	148	Event notification queue '%1' not found warning [page 424]
13249	147	Event notifications lost on queue '%1' [page 424]
13250	-1269	Service statement definition is invalid or unsupported [page 673]
13251	-1262	This edition of SQL Anywhere is not available on this platform [page 823]
13252	-1261	This server is not licensed to support '%1' connections [page 824]
13253	-1260	This server is not licensed to support the '%1' feature [page 824]
13254	145	Two rows with the same primary key have been downloaded for table '%1' [page 855]
13255	-1259	Hash error: %1 [page 467]

Sybase error code	SQL Anywhere SQLCODE	Message text
13259	-1254	MERGE statement for table '%1' failed because of a RAISERROR specification in the statement [page 569]
13260	-1253	The text index %1 needs to be refreshed [page 811]
13261	-1151	The logging type ('%1') specified is invalid, not supported or incompatible [page 773]
13266	-1313	Maximum string length exceeded [page 568]
13267	-1312	Mirror server "%1" is not a valid parent server [page 573]
13270	-1244	An attempt to decrypt database '%1' failed [page 231]
13271	-1243	An attempt to encrypt database '%1' failed [page 232]
13273	-1241	Value-sensitive cursor used after a TRUNCATE [page 920]
13274	144	Mirror file requires higher checksum_level [page 572]
13275	143	Retrying read of corrupt page (page '%1') [page 652]
13276	142	UltraLite database state was restored [page 859]
13277	-1240	The provided stoplist is too long [page 790]
13278	-1311	Principal mirror servers are already defined [page 632]
13281	-1237	Too many columns in procedure result set [page 829]
13282	-1236	Too many expressions in GROUP BY list [page 833]
13283	-1235	Too many columns in SELECT list [page 831]
13284	-1233	The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns [page 774]
13285	-1232	Attempt to start a second snapshot in a transaction [page 244]
13286	-1231	Statement timed out: '%1' [page 699]
13287	-1230	Too many open cursors [page 835]

Sybase error code	SQL Anywhere SQLCODE	Message text
13288	-1229	Reorganize table is already being run on table "%1" [page 645]
13291	-1226	Foreign key columns do not match the primary key or a uniqueness constraint in "%1" [page 457]
13292	-1225	Synchronization profiles are not supported for this database [page 715]
13293	-1224	Synchronization profile '%1' has invalid parameter '%2' [page 714]
13294	-1223	Synchronization profile '%1' already exists [page 713]
13296	-1221	Duplicate options not allowed in the CREATE DATABASE statement [page 398]
13297	-1216	The arguments to this procedure must be literal strings [page 749]
13298	-1219	Maintenance of dependent immediate materialized view(s) failed [page 566]
13299	-1218	The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate, non-nullable columns [page 776]
13300	-1220	User cannot be dropped because external logins exist for this user [page 911]
13301	-1213	External environment does not support result sets [page 431]
13302	-1217	Synchronization profile '%1' not found [page 714]
13303	-1212	Connection disallowed by login policy for this user [page 335]
13304	-1211	MERGE statement ANSI cardinality violation on table '%1' [page 569]
13308	-1207	Invalid use of NEAR operator in text query [page 541]
13309	-1206	External environments are not supported for this database [page 433]
13310	-1205	External environment '%1' could not be found [page 429]
13311	-1204	INSERT...ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2 [page 486]
13312	-1203	WRITETEXT not allowed: immediate materialized view %1 depends on %2 [page 928]

Sybase error code	SQL Anywhere SQLCODE	Message text
13313	-1202	Operation not allowed on a table with dependent immediate materialized views [page 608]
13314	-1201	Client library reported an error opening object ('%1') during transfer [page 320]
13315	-1200	Client library reported a permissions error accessing object ('%1') during transfer [page 319]
13316	-1199	The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list [page 776]
13317	-1198	User "%1" already exists [page 906]
13318	-1197	Login policy "%1" in use [page 564]
13319	-1196	Login policies are not supported for this database [page 563]
13320	-1195	Login policy "%1" not found [page 565]
13321	-1194	Login policy "%1" already exists [page 564]
13322	-1193	TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 854]
13323	-1192	Cannot update multiple tables immediate materialized view %1 depends on [page 306]
13324	-1191	LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 561]
13325	-1190	LOAD TABLE is not allowed on a materialized view %1 [page 559]
13326	-1189	The UTF-16 endian specified does not match the Byte Order Mark found in the data [page 814]
13327	-1188	LOAD TABLE error: %1 [page 558]
13328	-1187	Cannot append when using compression or encryption [page 259]
13329	-1186	Database page validation failed with code: %1 [page 371]
13330	-1185	Index validation failed for table %1, index %2 with code: %3 [page 482]
13331	-1184	Cannot drop last unique index of an immediate materialized view [page 283]

Sybase error code	SQL Anywhere SQLCODE	Message text
13332	-1183	Support for permissions on dbspaces is not available for this database [page 707]
13333	-1182	Statement not allowed on IMMEDIATE REFRESH text index [page 697]
13334	-1181	The materialized view cannot be changed to immediate because its definition must not contain more than one query block [page 777]
13335	-1180	Cannot set database option "%1" because it is on the options watch list [page 300]
13336	-1178	Transaction log mirroring cannot be used with database mirroring [page 848]
13338	-1175	Unable to acquire table locks in specified time [page 860]
13339	-1174	Cannot create text configuration '%1' because option '%2' has an inappropriate setting [page 275]
13340	-1173	Client library reported an error accessing data during transfer ('%1') [page 320]
13341	-1172	Client application disallowed the transfer of data ('%1') [page 318]
13342	-1171	Client application does not allow transfer of data ('%1') [page 319]
13343	-1170	The materialized view %1 cannot be changed to immediate because it has already been initialized [page 775]
13344	-1169	Cannot access a table that is part of a text index [page 255]
13345	-1168	Cannot alter or drop a text configuration referenced by a text index [page 259]
13346	-1167	Cannot drop a user that owns text configurations [page 282]
13347	-1166	Text indexes are not supported for this database [page 741]
13348	-1165	Error creating text index "%1" on table "%2" [page 407]
13349	-1164	Text query parser error: %1 [page 743]
13350	-1163	Invalid collation: "%1" [page 495]

Sybase error code	SQL Anywhere SQLCODE	Message text
13351	-1162	Term length outside allowed range [page 737]
13352	-1161	Text configuration "%1" already exists [page 738]
13353	-1160	Text configuration "%1"."%2" not found [page 738]
13354	-1159	Non-constant or unknown text query string [page 595]
13355	-1158	No matching text index [page 590]
13356	-1157	All column reference arguments must refer to the same table [page 229]
13357	-1156	Argument "%1" must be a column reference [page 239]
13358	-1155	Unable to close the cursor on table "%1". LOAD TABLE cannot be executed [page 861]
13359	-1154	Traced query (%1, %2) does not exist [page 846]
13360	-1153	Password has expired but cannot be changed because the database is read-only [page 620]
13361	-1152	Password has expired [page 620]
13362	-1150	The SQL scripts DLL cannot be loaded [page 806]
13363	-1148	Feature not supported by the client version or the client interface [page 453]
13364	-1310	Mirror server "%1" is referenced by another server [page 574]
13365	-1309	Mirror server "%1" already exists [page 572]
13366	-1146	LOAD TABLE not allowed on temporary table which has foreign key references from another table [page 560]
13367	-1145	Unable to connect: The server did not accept the requested encryption type [page 863]
13368	-1144	'%1' cannot be used as the encoding specification for '%2' data [page 206]
13369	140	Encryption has not been enabled [page 402]
13370	-1143	Encryption has not been enabled [page 402]

Sybase error code	SQL Anywhere SQLCODE	Message text
13371	-1142	Use of statement '%1', which requires feature '%2', is not allowed [page 904]
13372	-1141	Unable to start database "%1": NCHAR collation or tailoring not supported on this platform [page 874]
13373	-1140	Unable to start database "%1": CHAR collation or tailoring not supported on this platform [page 874]
13374	-1139	The remote data access feature is not supported on this platform [page 791]
13375	-1138	The mirror '%1' does not match database '%2' [page 781]
13376	-1137	Escape character conflict '%1' [page 421]
13377	-1136	Invalid use of escape character '%1' [page 541]
13378	-1135	Invalid regular expression: %1 in '%2' [page 524]
13379	-1134	Triggers cannot be created on materialized view '%1' [page 853]
13380	-1133	Invalid trigger type for view '%1' [page 538]
13381	-1132	Maximum row size for table '%1' would be exceeded [page 567]
13382	-1131	The attribute '%1' sets an option '%2' that is incompatible with '%3' [page 750]
13383	-1130	The '%1' attribute is missing a comma within '%2' [page 745]
13384	-1129	The '%1' attribute contains mismatched parentheses within '%2' [page 744]
13385	-1128	Start date/time for non-recurring event '%1' is in the past [page 693]
13386	-1127	Positioned update operation attempted on a view with an INSTEAD OF trigger [page 627]
13387	-1126	Operation failed because table or view '%1' has an INSTEAD OF trigger [page 607]
13388	-1125	Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1' [page 334]
13389	-1124	The dbicu library and server versions do not match [page 759]

Sybase error code	SQL Anywhere SQLCODE	Message text
13390	-1123	Invalid mime type '%1' [page 511]
13391	-1122	Exceeded maximum of '%1' allowable parameters [page 427]
13392	-1121	Not enough free space on device to grow dbspace '%1' by requested amount [page 597]
13393	-1120	The dbspace '%1' cannot be dropped because it contains tables or indexes [page 761]
13394	-1119	The '%1' property is no longer supported [page 746]
13395	-1118	Cannot change the MobiLink remote ID when the status of the last upload is unknown [page 262]
13396	-1117	A row cannot be stored because it exceeds the database page size [page 223]
13397	201	The ICU collation '%1' has defaulted to another collation [page 767]
13398	-1116	Collation '%1' not supported on this platform [page 323]
13399	-1115	Table '%1' contains an invalid reference to the ROWID function [page 720]
13400	-1114	Invalid setting for SOAP header '%1' [page 529]
13401	-1113	Correlation name '%1' is not valid for use with the ROWID function [page 342]
13402	-1112	Specified file system volume not found for database '%1' [page 684]
13403	-1111	Information for synchronization was not provided [page 484]
13404	-1110	UltraLite cannot synchronize because a synchronization is already running [page 857]
13405	-1109	Unable to perform requested operation since this database uses keyless encryption [page 871]
13406	-1108	Unable to access the file system on the device [page 860]
13407	-1107	Too many references to a BLOB [page 836]
13408	-1106	Too many publications specified for operation [page 836]

Sybase error code	SQL Anywhere SQLCODE	Message text
13409	-1308	Mirror server "%1" not found [page 574]
13410	-1104	Too many users in database [page 839]
13411	-1103	No partial download was found [page 593]
13412	-1102	Unable to retry download because upload is not finished [page 873]
13413	-1101	Column '%1' not part of any indexes in its containing table [page 328]
13414	-1100	The operation failed because column '%1's type does not support streaming [page 783]
13415	139	Option '%1' specified more than once [page 611]
13416	-1099	Transact-SQL outer joins are currently disabled [page 847]
13417	-1098	A tracing connection is already active [page 226]

1.1.4 SQL Anywhere Error Messages Listed by Message Text

In this section:

- [%1 \[page 205\]](#)
- [%1 and %2 must not be the same \[page 205\]](#)
- ['%1' cannot be used as the encoding specification for '%2' data \[page 206\]](#)
- ['%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used \[page 206\]](#)
- [%1 does not return a result set \[page 207\]](#)
- ['%1' for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement \[page 207\]](#)
- ['%1' is an invalid value for '%2' \[page 208\]](#)
- ['%1' is an unknown character set encoding label \[page 208\]](#)
- ['%1' is an unknown option \[page 209\]](#)
- ['%1' is an unknown property \[page 209\]](#)
- ['%1' is an unrecognized service type \[page 210\]](#)
- [%1 is not a directory \[page 210\]](#)
- ['%1' is not a known file format for loading or unloading tables \[page 211\]](#)
- ['%1' is not a valid character set encoding for use with collation '%2' \[page 211\]](#)

'%1' is not a valid class file [page 212]

%1 listener binding failure for the address parameter "%2" [page 213]

%1 listener for the address parameter "%2" is not found [page 213]

%1 listener start option includes an unsupported option: %2 [page 214]

%1 listener start option parse error: %2 [page 214]

%1 returned a result set with a different schema than expected [page 215]

%1 returned multiple result sets [page 215]

'%1' statement is not allowed as a consumer [page 216]

'%1' statement is not allowed on a mirrored database [page 216]

%2 error occurred while trying to read file %1 during backup [page 217]

(no message text) [page 217]

A conflict with the dbmsync download phase was detected [page 218]

A CONTAINS query is not allowed on the view or derived table '%1' [page 218]

A dbspace has reached its maximum file size [page 219]

A disk sandbox error occurred for database '%1' when determining the disk sandbox status for file '%2' [page 219]

A disk sandbox error occurred for database '%1' when finding the full path for file '%1' [page 220]

A fatal error has occurred in the profiler library [page 221]

A geometry with SRID=%1 is not supported for method %2 [page 221]

A geometry with SRID=%1 is not supported when computing distance between non-point geometries [page 222]

A memory error occurred causing the profiler operation to fail [page 222]

A row cannot be stored because it exceeds the database page size [page 223]

A row was dropped because it could not be converted to the new schema format [page 223]

A schema upgrade is not currently allowed [page 224]

A synchronization schema change is already in progress [page 225]

A thread used internally could not be started [page 225]

A tracing connection is already active [page 226]

A user name must be specified if AUTHORIZATION is Off [page 226]

A workload capture (%1) is already in progress [page 227]

Address parameter "%1" is not supported to start a listener for the personal database server [page 227]

Aggregated expression '%1' contains multiple columns of which one or more are outer references [page 228]

Alias '%1' is not unique [page 229]

All column reference arguments must refer to the same table [page 229]

All threads are blocked [page 230]

[ALTER clause conflict \[page 230\]](#)

[An attempt to decrypt database '%1' failed \[page 231\]](#)

[An attempt to delete database '%1' failed \[page 232\]](#)

[An attempt to encrypt database '%1' failed \[page 232\]](#)

[An expression of type %1 is not union-compatible with type %2 \[page 233\]](#)

[An incremental refresh is not possible when handles are exhausted \[page 233\]](#)

[An input string in '%1' format cannot be used here \[page 234\]](#)

[An internal error has occurred in the profiler library \[page 234\]](#)

[An internal error has occurred in the spatial library \[page 235\]](#)

[An invalid authorization code was specified in the call to %1 \[page 235\]](#)

[An invalid multi-byte input character was encountered when converting from %1 to %2 \[page 236\]](#)

[An invalid multi-byte input character was encountered when converting from %1 to %2 \[page 236\]](#)

[An invalid secure feature list '%2' was specified in the call to %1 \[page 237\]](#)

[An ST_CircularString cannot be constructed from %1 points \(near '%2'\) \[page 238\]](#)

[Another connection has already registered as '%1' \[page 238\]](#)

[Another connection has the row in '%1' locked \[page 239\]](#)

[Argument "%1" must be a column reference \[page 239\]](#)

[Argument %1 of procedure '%2' cannot be NULL \[page 240\]](#)

[Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause \[page 240\]](#)

[Array contains too many elements \[page 241\]](#)

[Array element error: array index '%1' is out of range \[page 241\]](#)

[At least one of the specified dbspaces was not calibrated \[page 242\]](#)

[ATTACH TRACING could not connect to the tracing database \[page 242\]](#)

[ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database \[page 243\]](#)

[Attempt to allocate memory for LDAP server "%1" failed \[page 243\]](#)

[Attempt to alter unnamed column constraint when named constraints exist \[page 244\]](#)

[Attempt to start a second snapshot in a transaction \[page 244\]](#)

[Attempt to use snapshot isolation in a non-snapshot transaction \[page 245\]](#)

[Attempted two active database requests \[page 245\]](#)

[Authentication failed \[page 246\]](#)

[Authentication violation \[page 246\]](#)

[Automatic database upgrade applied \[page 247\]](#)

[BACKINT configuration file error, %1 \[page 247\]](#)

[BACKUP clause '%1' conflicts with '%2' \[page 248\]](#)

[Backup file '%1' already exists \[page 248\]](#)

Backup file format is invalid [page 249]

Backup is unable to open database file '%1' [page 249]

Backward scrolling cursors are not supported for remote objects [page 250]

Bind to LDAP server %1 without a password is not allowed [page 250]

Call to %1 failed - the authorization code specified for the secure feature key named '%2' is incorrect [page 251]

Call to %1 failed - the key named '%2' is the last key with the MANAGE_FEATURES and MANAGE_KEYS features [page 252]

Call to %1 failed - the maximum number of secure feature keys has already been created [page 252]

Call to %1 failed - the secure feature key named '%2' already exists [page 253]

Call to %1 failed - the secure feature key named '%2' does not exist [page 254]

Calling functions outside the database server is not supported [page 254]

Can only describe a SELECT statement [page 255]

Cannot access a table that is part of a text index [page 255]

Cannot access file '%1' -- %2 [page 256]

Cannot access schema file '%1' [page 257]

Cannot add a comment to a table declared as LOCAL TEMPORARY [page 257]

Cannot alter a column in an index [page 258]

Cannot ALTER LDAP SERVER '%1' while LDAP server is in active state [page 258]

Cannot alter or drop a text configuration referenced by a text index [page 259]

Cannot append when using compression or encryption [page 259]

Cannot assign automatic mirror server parent [page 260]

Cannot change password because change_password_dual_control process is in progress [page 260]

Cannot change synchronization user_name when status of the last upload is unknown [page 261]

Cannot change the mirror server type from %1 to %2 [page 262]

Cannot change the MobiLink remote ID when the status of the last upload is unknown [page 262]

Cannot change the setting of the SingleCLRInstanceVersion server option after the CLR external environment has already been started [page 263]

Cannot change the setting of the UseSingleJVMInstance server option after Java has already been started [page 264]

Cannot close a remote JDBC connection that is not the current connection [page 264]

Cannot commit or rollback while enlisted in a transaction [page 265]

Cannot connect to mirror server. Use server name '%1' to find the primary server [page 265]

Cannot convert %1 to %2 [page 266]

Cannot convert %1 to %2. The bad value was supplied for column '%3' on row %4 of the data file [page 266]

Cannot convert between requested character set '%1' and database character set '%2' [page 267]

Cannot convert between requested character sets '%1' and '%2' [page 268]

Cannot convert from %1 to %2 (near %3) [page 268]

Cannot convert value to a timestamp [page 269]

Cannot create a materialized view because option '%1' has an inappropriate setting [page 269]

Cannot create a proxy table LIKE another table [page 270]

Cannot create an index on Java class '%1' [page 270]

Cannot create base table '%1': A global temporary table with the same name exists [page 271]

Cannot create global temporary table '%1': A base table with the same name exists [page 271]

Cannot create item (%1) in the specified dbspace [page 272]

Cannot create mutex "%1" as a temporary mutex with this name already exists [page 272]

Cannot create mutex "%1": %2 with this name already exists [page 273]

Cannot create semaphore "%1" as a temporary semaphore with this name already exists [page 273]

Cannot create semaphore "%1": %2 with this name already exists [page 274]

Cannot create synchronization entry for table '%1' with BLOB primary key [page 274]

Cannot create table '%1': Name is used by a non-table object [page 275]

Cannot create text configuration '%1' because option '%2' has an inappropriate setting [page 275]

Cannot delete or rename a column referenced in a trigger definition [page 276]

Cannot delete PUBLIC option '%1' since user settings exist [page 276]

Cannot deregister '%1' since active registered connection exists [page 277]

Cannot deregister application because of invalid cookie [page 277]

Cannot deserialize Java object [page 278]

Cannot drop a role that owns events in runtime server [page 278]

Cannot drop a role that owns external environment objects in runtime server [page 279]

Cannot drop a role that owns sequences in runtime server [page 279]

Cannot drop a role that owns web services in runtime server [page 280]

Cannot drop a user that owns messages or data types [page 280]

Cannot drop a user that owns objects involved in replication [page 281]

Cannot drop a user that owns procedures in runtime server [page 281]

Cannot drop a user that owns tables in runtime system [page 282]

Cannot drop a user that owns text configurations [page 282]

Cannot drop last unique index of an immediate materialized view [page 283]

Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it [page 283]

Cannot drop the database's current time zone [page 284]

Cannot enlist in a transaction while already enlisted in a transaction [page 284]

Cannot enlist in a transaction with uncommitted data pending [page 285]

Cannot find index named '%1' [page 285]

Cannot find synchronization subscription with the name '%1' [page 286]

Cannot find synchronization user with the name '%1' [page 286]

Cannot force failover when current server is marked as preferred [page 287]

Cannot handle expressions involving remote tables inside stored procedures [page 287]

Cannot insert or update computed column '%1' [page 288]

Cannot load encryption DLL %1: version mismatch [page 288]

Cannot map a login ID to the sys or public user ID [page 289]

Cannot modify column '%1' in table '%2' [page 289]

Cannot modify publication entry using ALTER SYNCHRONIZATION [page 290]

Cannot modify synchronization entry using ALTER PUBLICATION [page 290]

Cannot open transaction log file -- %1 [page 291]

Cannot output the histogram for string column '%1' [page 291]

Cannot perform specified operation, number of administrators for role '%1' falls below min_role_admins option value [page 292]

Cannot perform specified operation, set user condition violated [page 292]

Cannot proceed with online backup, SQLA log guid is ahead [page 293]

Cannot register '%1' since another exclusive instance is running [page 294]

Cannot register '%1' since registration cookie exhausted [page 294]

Cannot register another '%1' as an exclusive application [page 295]

Cannot register connection because of invalid application cookie [page 295]

Cannot register connection to '%1' since automatic label exhausted [page 296]

Cannot remove class '%1': member of JAR [page 296]

Cannot return NULL result as requested data type [page 297]

Cannot revoke these permissions while user '%1' is actively replicating transactions [page 297]

Cannot save SQL Anywhere Cockpit to existing file '%1' [page 298]

Cannot serialize Java object with class '%1' [page 298]

Cannot set a temporary option for user '%1' [page 299]

Cannot set audit_log to the transaction log: The transaction log is not enabled for the database [page 299]

Cannot set database option "%1" because it is on the options watch list [page 300]

Cannot specify range that excludes next value for sequence %1 [page 300]

Cannot specify read only in both the READ ONLY clause and the USING clause [page 301]

Cannot stop the database server [page 301]

Cannot subscribe to '%1' [page 302]

Cannot synchronize table '%1' since it does not have a primary key [page 302]

Cannot treat value '%1' as type %2. The dynamic type is %3 [page 303]

Cannot turn on auditing: The audit settings currently require a transaction log file [page 303]

Cannot uniquely identify rows in cursor [page 304]

Cannot update an expression [page 304]

Cannot update column '%1' since it appears in the ORDER BY clause [page 305]

Cannot update column '%1' since it does not appear in the SELECT clause [page 305]

Cannot update materialized view because option '%1' has an inappropriate setting [page 306]

Cannot update multiple tables immediate materialized view %1 depends on [page 306]

Cannot update or delete an all-NULL row from table '%1' [page 307]

Cannot update primary key for table '%1' involved in a publication [page 307]

Cannot update the audit_log option: one or more of the specified targets is invalid [page 308]

Cannot use both the OR REPLACE and IF NOT EXISTS clauses [page 308]

Cannot use CLEAR LOG clause with offline log backups [page 309]

Cannot use materialized view '%1' because it has not yet been initialized [page 309]

Cannot use view '%1' because it has been disabled [page 310]

Cannot use view '%1' because it is invalid [page 310]

CATALOG ONLY and MULTIPLEX cannot be used together [page 311]

CDATA has a name [page 311]

Certificate '%1' not found [page 312]

change_password_dual_control is enabled for this user. Use ALTER USER to change password [page 312]

CHAR configuration provided for NCHAR column for text index \"%1\" on table \"%2\" [page 313]

Character conversion error or warning report is not available when the single-byte converter is used [page 313]

Character set conversion to '%1' cannot be performed; '%2' is used instead [page 314]

Character substitution occurred when converting from %1 to %2 [page 314]

Character substitution was required when converting from %1 to %2 [page 315]

CHECKPOINT statement requires a rollback log [page 316]

Checksums are not enabled in this database [page 316]

CircularString with 3 points has been converted to use 5 points [page 317]

Class '%1' has no public field '%2' [page 317]

Clause '%1' has invalid attribute '%2' [page 318]

Client application disallowed the transfer of data ('%1') [page 318]

Client application does not allow transfer of data ('%1') [page 319]

Client library reported a permissions error accessing object ('%1') during transfer [page 319]

Client library reported an error accessing data during transfer ('%1') [page 320]

Client library reported an error opening object ('%1') during transfer [page 320]

Client out of memory [page 321]

Client redirected more than once [page 321]

Client/database server version mismatch [page 322]

Client/server communications protocol version mismatch [page 322]

Collation '%1' not supported on this platform [page 323]

Collection types not supported [page 323]

Column '%1' found in more than one table or it is used more than once in the SELECT list -- it needs a correlation name [page 324]

Column '%1' in foreign key has a different definition than primary key [page 325]

Column '%1' in table '%2' cannot be NULL [page 325]

Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3 [page 326]

Column '%1' not found [page 326]

Column '%1' not found in table '%2' [page 327]

Column '%1' not found in variable '%2' [page 327]

Column '%1' not part of any indexes in its containing table [page 328]

Column must be named: %1 [page 328]

Column subset for table '%1' in publication '%2' does not match that specified in publication '%3' [page 329]

Command '%1' received BACKINT_ERROR from HANA [page 330]

COMMIT/ROLLBACK not allowed within atomic operation [page 330]

COMMIT/ROLLBACK not allowed within trigger actions [page 331]

Communication error [page 331]

Composite ORDER BY not allowed with RANGE [page 332]

Compression error: %1 [page 332]

Computed columns are not supported in this database [page 333]

Configuration cannot not be modified while in use [page 333]

Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1' [page 334]

Connection attempting BACKUP has uncommitted transactions [page 334]

Connection disallowed by login policy for this user [page 335]

Connection error: %1 [page 335]

Connection is not allowed to have table locks when executing this statement [page 336]

Connection not found [page 336]

Connection timed out [page 337]

Connection was terminated [page 337]

Connections to database have been disabled [page 338]

Constant expressions must not appear in GROUP BY clause [page 338]

Constraint '%1' not found [page 339]

Constraint '%1' violated: Invalid value for column '%2' in table '%3' [page 339]

Constraint '%1' violated: Invalid value in table '%2' [page 340]

Contents of backup files are inconsistent [page 341]

Control character in XML output [page 341]

Coordinate bounds missing for coordinate %1 [page 342]

Correlation name '%1' is not valid for use with the ROWID function [page 342]

Correlation name '%1' not found [page 343]

Could not access column information for the table '%1' [page 343]

Could not allocate resources to call external function [page 344]

Could not create a new text index for this table with the same settings as "%1" [page 344]

Could not create a text index with external prefilter library on column "%1" [page 345]

Could not create a text index without external prefilter library on column "%1" [page 345]

Could not decompress class '%1' from JAR [page 346]

Could not execute backup/restore DLL (%1) entry point [page 346]

Could not execute store DLL (%1) entry point [page 347]

Could not find '%1' in dynamic library '%2' [page 347]

Could not initialize the encryption DLL: '%1' [page 348]

Could not load dynamic library '%1' [page 349]

Could not load the backup/restore DLL "%1" [page 349]

Could not load the encryption DLL "%1" [page 350]

Could not load the store DLL "%1" [page 350]

Could not refresh tracing: at least one enabled tracing level must be specified [page 351]

Could not refresh tracing: failed to find object %1 on row %2 [page 351]

Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1 [page 352]

Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected [page 352]

Could not start a new profiling session because the previous session is still being processed. [page 353]

Could not write the profiler data because the previous session is still being processed. [page 353]

CREATE/DROP STATISTICS statement cannot refer to virtual tables [page 354]

Creating remote tables with computed columns is not supported [page 354]

Current connection is already registered to '%1' as '%2' [page 355]

Cursor %1 cannot be used to declare a row variable using %ROWTYPE [page 355]

Cursor already open [page 356]

Cursor has not been declared [page 356]

Cursor is restricted to FETCH NEXT operations [page 357]

Cursor not in a valid state [page 357]

Cursor not open [page 358]

Cursor option values changed [page 358]

Curve contains nearly antipodal points %1 and %2 (near '%3') [page 359]

Cycle in common table expression references [page 360]

Cycle in computed column dependencies [page 360]

Data definition statements not allowed in procedures or triggers [page 361]

Data modifications are not allowed in a synchronization schema change [page 361]

Database "%1" needs recovery [page 362]

Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_cant_change_platform.html [page 362]

Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/endian_corruption_warning.html [page 363]

Database alter failed: %1 [page 363]

Database backup not started [page 364]

Database cannot be started -- %1 [page 364]

Database connection limit exceeded [page 365]

Database contains no tables to synchronize [page 365]

Database contains users with 'SYS_' prefix and '_ROLE' suffix [page 366]

Database creation failed: %1 [page 366]

Database is active [page 367]

Database mirroring options are not supported for this database [page 367]

Database name must be specified when connecting to a cloud database server [page 368]

Database name not unique [page 368]

Database name required to start server [page 369]

Database needs to be upgraded to support the use of external libraries with text indexes [page 369]

Database option '%1' for user '%2' has an invalid setting [page 370]

Database page size too big: %1 [page 370]

Database page size too small: %1 [page 371]

Database page validation failed with code: %1 [page 371]

Database server already running [page 372]

Database server cannot convert data from/to character set '%1' [page 373]

Database server cannot convert data from/to character set '%1', conversion may not be correct [page 373]

Database server connection limit exceeded [page 374]

Database server name '%1' cannot be the same as either the primary or mirror server [page 375]

Database server not found [page 375]

Database server not running in multi-user mode [page 376]

Database upgrade failed [page 376]

Database upgrade not possible [page 377]

Database upgrade not possible; database has auditing enabled [page 377]

Database upgrade not possible; RowGenerator table not owned by user dbo [page 378]

Database upgrade not possible; user tables have table IDs in system table range [page 378]

Database upgrade not possible; user-defined database option "%1" conflicts with the system-defined database option with the same name [page 379]

db_init has not been called or the call to db_init failed [page 379]

DBA password must be specified in the CREATE DATABASE statement [page 380]

DBA user ID must be specified in the CREATE DATABASE statement [page 380]

DBF parameter cannot be used when the SQL Anywhere Cockpit is being prepared to save. [page 381]

DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is active [page 381]

DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is being started [page 382]

DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is starting [page 383]

DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is stopping [page 383]

dbicu libraries are required but not installed [page 384]

DbSPACE '%1' not found [page 384]

DbSPACE for table '%1' not found [page 384]

Deadlock detected [page 385]

Deadlock involving a mutex detected [page 385]

Debugger error: %1 [page 386]

Decompression error: %1 [page 386]

Decryption error: %1 [page 387]

Default dbSPACE '%1' not found [page 387]

Definition for alias '%1' must appear before its first reference [page 388]

Definition for sequence '%1' is invalid [page 389]

Derived table '%1' has no name for column %2 [page 389]

Dialect '%1' is not supported by this database [page 390]

Directory for output file does not exist [page 390]

Disallowed language extension detected in syntax near '%1' on line %2 [page 391]

Disk full '%1' -- transaction rolled back [page 391]

Disk write failure '%1' -- transaction rolled back [page 392]

[Division by zero \[page 392\]](#)

[Download failed because of conflicts with existing rows on table '%1' \(row: %2\) \[page 393\]](#)

[Download failed due to an invalid or unsupported row value \[page 393\]](#)

[Dropping all columns from table '%1' is not allowed \[page 394\]](#)

[Dropping or altering arbiter "%1" requires a connection to the partner \[page 395\]](#)

[DTC transactions are not supported on this platform \[page 395\]](#)

[Duplicate attribute '%1' in service \[page 396\]](#)

[Duplicate insert column \[page 396\]](#)

[Duplicate key column \(%1\) \[page 397\]](#)

[Duplicate options not allowed in %1!s! \[page 397\]](#)

[Duplicate options not allowed in the CREATE DATABASE statement \[page 398\]](#)

[Duplicate referencing column \[page 398\]](#)

[Dynamic memory exhausted during %1 \[page 398\]](#)

[Element is an empty set \(near '%1'\) \[page 399\]](#)

[Ellipsoid parameters missing for geographic spatial reference system \[page 400\]](#)

[Ellipsoid parameters specified for non-geographic spatial reference system \[page 400\]](#)

[Encryption error: %1 \[page 401\]](#)

[Encryption failed for the SQL Anywhere Cockpit setting file. Error message '%1' \[page 401\]](#)

[Encryption has not been enabled \[page 402\]](#)

[Encryption has not been enabled \[page 402\]](#)

[Error at offset '%1': expected JSON name/value pair \[page 403\]](#)

[Error at offset '%1': expected token '%2' \[page 403\]](#)

[Error at offset '%1': invalid data \[page 404\]](#)

[Error at offset '%1': mismatched object or array terminator \[page 405\]](#)

[Error at offset '%1': unexpected token '%2' \[page 405\]](#)

[Error at offset '%1': unexpected trailing text \[page 406\]](#)

[Error backing up existing log area. Found '%1' logs in '%2' directory \[page 407\]](#)

[Error creating text index "%1" on table "%2" \[page 407\]](#)

[Error during backup/restore: %1 \[page 408\]](#)

[Error executing BEGIN PARALLEL WORK...END PARALLEL WORK statement \[page 408\]](#)

[Error from external library: -%1: %2 \[page 409\]](#)

[Error in assignment \[page 409\]](#)

[Error in parsing BACKINT configuration file \[page 410\]](#)

[Error initializing external prefilter \[page 410\]](#)

[Error initializing external term breaker \[page 411\]](#)

Error modifying refresh type for text index "%1" on materialized view "%2" [page 411]

Error number %1 for RAISERROR must not be less than 17000 [page 412]

Error opening cursor [page 412]

Error parsing connection parameter string [page 413]

Error parsing definition string '%1' [page 413]

Error parsing geometry internal serialization at offset %1 [page 414]

Error parsing shapefile attributes [page 414]

Error parsing shapefile record [page 415]

Error parsing well-known-binary (WKB) at offset %1 [page 415]

Error parsing well-known-binary (WKB): inconsistent dimensions at offset %1 [page 416]

Error parsing well-known-binary (WKB): invalid byte order mark %1 at offset %2 [page 416]

Error parsing well-known-binary (WKB): type code %1 at offset %2 is invalid [page 417]

Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent [page 417]

Error parsing well-known-binary (WKB): unexpected end of input [page 418]

Error parsing well-known-text (WKT) scanning '%1' at offset %2 [page 418]

Error parsing well-known-text (WKT): inconsistent dimensions at offset %1 [page 419]

Error processing SAP HANA strategy [page 419]

Error reading configuration file [page 420]

Error writing to transaction log file [page 420]

Escape character conflict '%1' [page 421]

Event '%1' already exists [page 421]

Event '%1' in use [page 422]

Event '%1' not found [page 422]

Event notification queue '%1' is full, notification discarded [page 423]

Event notification queue '%1' not found [page 423]

Event notification queue '%1' not found warning [page 424]

Event notifications lost on queue '%1' [page 424]

Event object name '%1' is not valid [page 425]

Event object named '%1' already exists [page 426]

Event parameter '%1' not found [page 426]

Exceeded maximum of '%1' allowable parameters [page 427]

Expression has unsupported data type [page 427]

Expression is not an array [page 428]

Expression of type %1 is not allowed in this context (near: %2) [page 429]

External environment '%1' could not be found [page 429]

External environment cannot be started during database startup [page 430]

External environment cannot be started, external process terminated on start up [page 430]

External environment could not be started, '%1' could not be found [page 431]

External environment does not support result sets [page 431]

External environment failed to start and establish a connection within the %1 second timeout [page 432]

External environments are not supported for this database [page 433]

External library '%1' is in use [page 433]

External library '%1' not loaded [page 434]

External login for server '%1' could not be found [page 434]

External object '%1' not found [page 435]

External procedures or functions are not allowed across server types [page 435]

Fail to compare %1 and %2 [page 436]

Failed to access the SQL Anywhere Cockpit file '%1': %2 [page 436]

Failed to close pipe %1 during BACKUP using BACKINT %2 [page 437]

Failed to connect to the dbmlsync server [page 437]

Failed to connect to the dbmlsync server. Check the dbmlsync log file for more details [page 438]

Failed to convert from character set '%1' to '%2' [page 438]

Failed to copy the SQL Anywhere Cockpit template file '%1' to destination '%2' [page 439]

Failed to create pipe %1 during BACKUP using BACKINT %2 [page 439]

Failed to delete the SQL Anywhere Cockpit file '%1': %2 [page 440]

Failed to get BACKUP id for file name %1 [page 440]

Failed to get file system statistics for the path '%1' [page 441]

Failed to get status information on the path '%1': %2 [page 441]

Failed to load %1 HANA library [page 442]

Failed to load the MobiLink client support libraries [page 442]

Failed to open pipe %1 during BACKUP using BACKINT %2 [page 443]

Failed to read pipe %1 during BACKUP using BACKINT %2 [page 443]

Failed to read the SQL Anywhere Cockpit setting file '%1' [page 444]

Failed to rename the SQL Anywhere Cockpit file '%1' to '%2': %3 [page 444]

Failed to set up audit log session for database '%1' [page 445]

Failed to shut down the dbmlsync server. Check the dbmlsync log file for more details [page 445]

Failed to start the dbmlsync server [page 446]

Failed to start the dbmlsync server. Check the dbmlsync log file for more details [page 446]

Failed to transform geometry (error %1) [page 447]

Failed to transform point %1 (error %2) [page 447]

Failed to write pipe %1 during BACKUP using BACKINT %2 [page 448]

Failed to write the SQL Anywhere Cockpit setting file '%1' [page 448]

Feature '%1' is locked because synchronization is in progress [page 449]

Feature '%1' is locked by another connection [page 449]

Feature '%1' is not supported for this database [page 450]

Feature '%1' is unknown or invalid [page 450]

Feature '%1' not implemented [page 451]

Feature '%1' not supported [page 451]

Feature '%1' was not locked by this connection [page 452]

Feature not available with UltraLite [page 452]

Feature not supported by the client version or the client interface [page 453]

Field '%1' of class '%2' cannot be NULL [page 453]

File %1 already exists [page 454]

File I/O failed for '%1' [page 454]

File or directory %1 not found [page 455]

File system error: %1 [page 455]

FOR UPDATE has been incorrectly specified for a READ ONLY cursor [page 456]

FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR) [page 456]

Foreign key '%1' for table '%2' duplicates an existing foreign key [page 457]

Foreign key columns do not match the primary key or a uniqueness constraint in "%1" [page 457]

Foreign key name '%1' not found [page 458]

Format '%1' is not supported in the UNLOAD statement [page 459]

Format string argument number %1 is invalid [page 459]

Format string contains invalid format specifiers: '%1' [page 460]

Format string contains more than %2 format specifiers: '%1' [page 460]

Found a file '%1' with relative path in delta dbspace during backup existing log area. [page 461]

Frame not allowed for window '%1' [page 461]

Function '%1' has invalid parameter '%2' ('%3') [page 462]

Function '%1' has invalid parameter '%2' ('%3') [page 462]

Function-name clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 463]

Function or column reference to '%1' in the ORDER BY clause is invalid [page 463]

Function or column reference to '%1' must also appear in a GROUP BY [page 464]

Geometries with CircularString are not supported in spatial reference system %1 [page 464]

Geometries with CircularString not supported (near "%1") [page 465]

Geometry expressions cannot be used in the ORDER BY specification (near '%1') [page 465]

GRANT of column permission on view not allowed [page 466]

Grouped query contains more than one distinct aggregate function [page 466]

Hash error: %1 [page 467]

Host variable reference in service definition must be named [page 468]

Host variables must not be used in this context [page 468]

Host variables must not be used within a batch [page 468]

HTTP request failed. Status code '%1' [page 469]

I/O error %1 -- transaction rolled back [page 469]

Identifier '%1' too long [page 470]

Identity attribute mismatch for column '%1' [page 471]

Illegal column definition: %1 [page 471]

Illegal column name: '%1' [page 472]

Illegal cursor operation attempt [page 472]

Illegal flags value passed to OPENXML [page 473]

Illegal ORDER BY in aggregate function [page 473]

Illegal reference to correlation name '%1' [page 474]

Illegal tag value: '%1' [page 474]

Illegal user selectivity estimate specified [page 475]

Immediate materialized view definition cannot contain a SUM function over a nullable expression [page 475]

IN-list is too long [page 476]

Incomplete transactions prevent transaction log renaming [page 476]

Incorrect database store DLL (%1) version [page 477]

Incorrect or missing encryption key [page 477]

Incorrect volume ID for '%1' [page 478]

Index '%1' cannot be clustered [page 478]

Index '%1' for table '%2' would not be unique [page 479]

Index '%1' has no columns [page 480]

Index name '%1' is ambiguous [page 480]

Index name '%1' not unique [page 481]

Index type specification of '%1' is invalid [page 481]

Index validation failed for table %1, index %2 with code: %3 [page 482]

Indirect identifier `[%1]` yielded an invalid identifier name '%2' [page 483]

Indirect identifiers not supported [page 483]

Information for synchronization is incomplete or invalid, check '%1' [page 484]

Information for synchronization was not provided [page 484]

Input parameter index out of range [page 485]

Input string is not base64-encoded [page 485]

INSERT...ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2 [page 486]

INSERT/DELETE on cursor can modify only one table [page 486]

Insufficient cache to start Java VM [page 487]

Insufficient memory for OPENXML query [page 487]

Integrated login failed [page 488]

Integrated logins are not permitted [page 488]

Integrated logins are not supported for this database [page 489]

Integrated logins are required, standard logins are not permitted [page 489]

Internal database error %1 -- transaction rolled back [page 490]

Internal rollback log corrupted [page 490]

Invalid absolute or relative offset in FETCH [page 491]

Invalid address parameter "%1" provided to start a listener [page 491]

Invalid address parameter "%1" provided to stop a listener [page 492]

Invalid backup operation [page 492]

Invalid BACKUP operation or type specified: %1 [page 493]

Invalid backup parameter value [page 493]

Invalid bounds for coordinate %1 (near "BETWEEN %2 AND %3") [page 494]

Invalid class byte code [page 494]

Invalid cockpit parameter [page 495]

Invalid collation: "%1" [page 495]

Invalid column number [page 495]

Invalid commit action for shared temporary table [page 496]

Invalid comparison [page 496]

Invalid configuration name %1 [page 497]

Invalid data conversion [page 497]

Invalid data conversion: NULL was inserted for column '%1' on row %2 [page 498]

Invalid data type for column in WRITETEXT or READTEXT [page 499]

Invalid database page size [page 499]

Invalid database server command line [page 500]

Invalid day of week or month '%1' for event '%2' [page 500]

Invalid DEFAULT value near '%1' on line %2 [page 501]

Invalid descriptor index [page 501]

[Invalid domain '%1' \[page 502\]](#)

[Invalid empty string specified as 'ESCAPE CHARACTER' option of LOAD or UNLOAD TABLE \[page 502\]](#)

[Invalid escape character '%1' \[page 503\]](#)

[Invalid escape sequence '%1' \[page 503\]](#)

[Invalid event parameter for event '%1' \[page 504\]](#)

[Invalid expression in WHERE clause of Transact-SQL outer join \[page 504\]](#)

[Invalid expression near '%1' \[page 505\]](#)

[Invalid external prefilter name specified \[page 505\]](#)

[Invalid external term breaker name specified \[page 506\]](#)

[Invalid generated identifier '%1' \[page 506\]](#)

[Invalid grid size %1 \[page 507\]](#)

[Invalid hint specified for table '%1' \[page 507\]](#)

[Invalid host variable \[page 508\]](#)

[Invalid increment value for semaphore "%1": %2 \[page 509\]](#)

[Invalid intersection matrix '%1' \[page 509\]](#)

[Invalid JAR file \[page 510\]](#)

[Invalid join type used with Transact-SQL outer join \[page 510\]](#)

[Invalid local database option \[page 510\]](#)

[Invalid mime type '%1' \[page 511\]](#)

[Invalid operation '%2' on sequence '%1' \[page 512\]](#)

[Invalid operation on a closed object \[page 512\]](#)

[Invalid option '%1' -- no PUBLIC setting exists \[page 513\]](#)

[Invalid options for UPGRADE: SCRIPT FILE can only be specified with RESTART \[page 513\]](#)

[Invalid ORDER BY specification \[page 514\]](#)

[Invalid parameter \[page 515\]](#)

[Invalid parameter was used in the call to %1 \[page 515\]](#)

[Invalid password: %1 \[page 516\]](#)

[Invalid polygon format '%1' \[page 516\]](#)

[Invalid polygon nesting \[page 517\]](#)

[Invalid polygon: curve is not a ring \[page 517\]](#)

[Invalid polygon: multiple exterior rings \[page 518\]](#)

[Invalid polygon: no exterior ring \[page 518\]](#)

[Invalid polygon: ring has zero area \(near '%1'\) \[page 519\]](#)

[Invalid polygon: ring is larger than allowed for SRID=%1 \(near '%2'\) \[page 519\]](#)

[Invalid polygon: ring is not closed \(near '%1'\) \[page 520\]](#)

[Invalid preceding or following size in OLAP function \[page 520\]](#)

[Invalid prepared statement type \[page 521\]](#)

[Invalid procedure subtype '%1' for type '%2' \[page 521\]](#)

[Invalid procedure type '%1' \[page 522\]](#)

[Invalid recursive query \[page 522\]](#)

[Invalid reference to or operation on constraint '%1' \[page 523\]](#)

[Invalid REFERENCES clause in trigger definition \[page 523\]](#)

[Invalid regular expression: %1 in '%2' \[page 524\]](#)

[Invalid repeat interval for event '%1' \[page 524\]](#)

[Invalid request log format on line %1 \[page 525\]](#)

[Invalid response from the HTTP server \[page 525\]](#)

[Invalid ROW or ARRAY domain \[page 526\]](#)

[Invalid scroll position '%1' \[page 526\]](#)

[Invalid service name '%1' \[page 527\]](#)

[Invalid setting '%1' specified for option '%2' for target type '%3' \[page 527\]](#)

[Invalid setting for HTTP header '%1' \[page 528\]](#)

[Invalid setting for HTTP option '%1' \[page 528\]](#)

[Invalid setting for option '%1' \[page 529\]](#)

[Invalid setting for SOAP header '%1' \[page 529\]](#)

[Invalid shapefile filename \[page 530\]](#)

[Invalid spatial reference system well-known-text \(WKT\) \[page 530\]](#)

[Invalid SQL descriptor name \[page 531\]](#)

[Invalid SQL identifier \[page 531\]](#)

[Invalid sqlllen field in SQLDA \[page 532\]](#)

[Invalid start date/time for event '%1' \[page 532\]](#)

[Invalid start value for semaphore "%1": %2 \[page 533\]](#)

[Invalid statement \[page 533\]](#)

[Invalid stoplist value \[page 534\]](#)

[Invalid storage format '%1' \[page 534\]](#)

[Invalid text index type for the materialized view \[page 535\]](#)

[Invalid TEXTPTR value used with WRITETEXT or READTEXT \[page 535\]](#)

[Invalid time '%1' for event '%2' \[page 535\]](#)

[Invalid timeout value %1 \[page 536\]](#)

[Invalid tolerance %1 \[page 536\]](#)

[Invalid tool name or admin user for generating security token \[page 537\]](#)

[Invalid transform definition '%1' \[page 537\]](#)

[Invalid trigger type for view '%1' \[page 538\]](#)

[Invalid type for field reference \[page 538\]](#)

[Invalid type on DESCRIBE statement \[page 539\]](#)

[Invalid use of an aggregate function \[page 539\]](#)

[Invalid use of BEFORE operator in text query \[page 540\]](#)

[Invalid use of collection type \[page 540\]](#)

[Invalid use of escape character '%1' \[page 541\]](#)

[Invalid use of NEAR operator in text query \[page 541\]](#)

[Invalid use of table reference type \[page 542\]](#)

[Invalid user ID or password \[page 542\]](#)

[Invalid user ID or password on preprocessed module \[page 543\]](#)

[Invalid user ID or role name '%1' specified \[page 543\]](#)

[Invalid value for attribute '%1' in service \[page 544\]](#)

[Invalid value for INSERT near '%1' on line %2 \[page 544\]](#)

[Invalid value for login policy option "%1" \[page 545\]](#)

[Invalid variable or type \[page 545\]](#)

[Invalid XQuery constructor \[page 545\]](#)

[Item '%1' already exists \[page 546\]](#)

[JAR '%1' not found \[page 546\]](#)

[Java VM heap exhausted at internal function: %1 \[page 547\]](#)

[jConnect does not support encryption \[page 547\]](#)

[JSON array contains too many elements \[page 548\]](#)

[JSON nesting too deep \[page 548\]](#)

[JSON object contains too many properties \[page 549\]](#)

[JWT Provider '%1' does not exist \[page 549\]](#)

[Kerberos login failed \[page 550\]](#)

[Kerberos logins are not supported \[page 550\]](#)

[Key constraint between temporary tables requires a primary key \(not unique constraint\) \[page 551\]](#)

[Label '%1' not found \[page 551\]](#)

[Language '%1' is not supported, '%2' will be used \[page 552\]](#)

[Language extension \[page 552\]](#)

[Language extension detected in syntax near '%1' on line %2 \[page 553\]](#)

[LDAP Server "%1" already exists \[page 553\]](#)

[LDAP server "%1" is in use by login policy "%2" \[page 554\]](#)

LDAP server %1 may not accept anonymous binds [page 554]

LDAP server definition of "%1" is incomplete. A search URL, access distinguished name, password, and authentication URL are required [page 555]

LDAP User Authentication feature is not supported in this database [page 555]

LineString must contain at least 2 points (near '%1') [page 556]

Listener type "%1" failed to initialize when starting a listener [page 556]

Load-source for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 557]

LOAD TABLE ... WITH FILE NAME LOGGING not permitted on mirrored database [page 557]

LOAD TABLE error: %1 [page 558]

LOAD TABLE error: Invalid content encountered on row %1 of the data file [page 559]

LOAD TABLE is not allowed on a materialized view %1 [page 559]

LOAD TABLE not allowed on temporary table which has foreign key references from another table [page 560]

LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS [page 560]

LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 561]

LOAD TABLE option '%1' not allowed with FORMAT %2 [page 561]

Local connection ID does not refer to the current database [page 562]

Logging type ('%1') for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 562]

Login mode '%1' not permitted by login_mode setting [page 563]

Login policies are not supported for this database [page 563]

Login policy "%1" already exists [page 564]

Login policy "%1" in use [page 564]

Login policy "%1" not found [page 565]

Login redirection is required to complete the connection, but it is not supported by the client [page 565]

Maintenance of dependent immediate materialized view(s) failed [page 566]

Materialized View '%1' not found [page 566]

Maximum row size for table '%1' would be exceeded [page 567]

Maximum string length exceeded [page 568]

Memory error -- transaction rolled back [page 568]

MERGE statement ANSI cardinality violation on table '%1' [page 569]

MERGE statement for table '%1' failed because of a RAISERROR specification in the statement [page 569]

Method '%1' cannot be called at this time [page 570]

Method '%1' cannot be called with %2 arguments (near '%3') [page 570]

Method invocation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 571]

Mirror child server creation failed [page 571]

Mirror file requires higher checksum_level [page 572]

Mirror server "%1" already exists [page 572]

Mirror server "%1" defined with type COPY does not include a parent definition [page 573]

Mirror server "%1" is not a valid parent server [page 573]

Mirror server "%1" is referenced by another server [page 574]

Mirror server "%1" not found [page 574]

MIRROR server class is not supported for SAP IQ databases [page 575]

Mirror server name '%1' does not match current server name [page 575]

Mirror server with type '%1' is already defined [page 576]

Missing value for attribute '%1' in service [page 576]

Mixed coordinate dimensions [page 577]

Mixed spatial reference systems %1 and %2 (near %3) [page 577]

MobiLink communication error -- code: %1, parameter: %2, system code: %3 [page 578]

Modifications not permitted for read-only database [page 578]

More articles are being dropped from publication '%1' than are defined [page 579]

More information required [page 579]

More than one table is identified as '%1' [page 580]

Multiple consolidated users cannot be defined [page 580]

Multiple settings of same option specified for sequence '%1' [page 581]

Multiple table parameters are not supported [page 581]

Must include primary key for table '%1' in the synchronization [page 582]

Must own table '%1' to make an immediate view reference it [page 582]

Mutex "%1" is locked by another connection [page 583]

Mutex "%1" not found [page 583]

Mutex "%1" was not locked by this connection [page 584]

Mutex "%1" with transaction scope cannot be released [page 584]

Mutex was dropped [page 585]

NAMESPACE attribute is not valid with procedure type '%1' [page 585]

Namespace heap exhausted at internal function: %1 [page 586]

Need a dynamic library name [page 586]

Need a function entry point [page 587]

No column list for recursive query [page 587]

No current row of cursor [page 587]

No database file specified [page 588]

No entry point specified for the current system configuration [page 589]

No external backup identity found for archive file '%1' in HANA strategy document [page 589]

No indicator variable provided for NULL result [page 590]

No matching text index [page 590]

No more role grant permitted [page 591]

No more values available in sequence %1 [page 591]

No name for argument [page 592]

No notification within timeout on queue '%1' [page 592]

No partial download was found [page 593]

No primary key value for foreign key '%1' in table '%2' [page 593]

No running shared memory listener was found [page 594]

No stored cache pages [page 594]

No workload capture currently exists [page 595]

Non-constant or unknown text query string [page 595]

Non-contiguous curves near '%1' [page 596]

Not allowed while '%1' is using the database [page 596]

Not connected to a database [page 597]

Not enough fields allocated in SQLDA [page 597]

Not enough free space on device to grow dbspace '%1' by requested amount [page 597]

Not enough memory to start [page 598]

Not enough values for host variables [page 598]

NULL attribute mismatch for column '%1' [page 599]

Null value eliminated in aggregate function [page 599]

Number of columns allowing NULLs exceeds limit [page 600]

Number of columns defined for the table does not match SELECT statement [page 600]

Number of columns defined for the view does not match SELECT statement [page 601]

OData Producer '%1' not found [page 601]

OData Producer option error: %1 [page 602]

Offline reset password failed: %1 [page 602]

Offline reset password is not allowed for user ID '%1' that has no password [page 603]

Offline reset password not supported [page 603]

One or more targets in the trace event session '%1' failed to start [page 604]

Only one IDENTIFIED BY value may be specified [page 604]

Only PUBLIC settings are allowed for option '%1' [page 605]

Operation '%1' failed for reason: '%2' [page 605]

Operation cannot be performed while AUTOCOMMIT_DDL is 'OFF' [page 606]

Operation conflict with publication type [page 606]

Operation failed - could not complete checkpoint [page 606]

Operation failed because table or view '%1' has an INSTEAD OF trigger [page 607]

Operation is not allowed [page 608]

Operation not allowed on a table with dependent immediate materialized views [page 608]

Operation not supported for ST_GeomCollection with intersecting elements (near "%1") [page 609]

Operation would cause a group cycle [page 609]

Operation would cause a role cycle [page 610]

Option '%1' cannot be used with HSQL COMPATIBLE [page 610]

Option '%1' specified more than once [page 611]

ORDER BY not allowed in window '%1' [page 611]

Outer reference not permitted in DML derived table [page 612]

Outer references are not allowed for TPF input tables [page 612]

Output file cannot be written [page 613]

Owner '%1' used in a qualified column reference does not match correlation name '%2' [page 613]

Parameter '%1' cannot be null [page 614]

Parameter '%1' in procedure or function '%2' does not have a default value [page 614]

Parameter '%1' not found in procedure '%2' [page 615]

Parameter name missing in call to procedure '%1' [page 615]

Parent not open: '%1' [page 616]

Parse error: %1 [page 616]

Parse error: %1 [page 617]

PARTITION BY not allowed in reference to window '%1' [page 618]

Passthrough statement inconsistent with current passthrough [page 618]

Password cannot be longer than %1 characters [page 619]

Password contains an illegal character [page 619]

Password encryption failed. Error message '%1' [page 619]

Password has expired [page 620]

Password has expired but cannot be changed because the database is read-only [page 620]

Password must be at least %1 characters [page 621]

PBKDF2 error: %1!s! [page 622]

Permission denied: %1 [page 622]

PIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 623]

PIVOT error: only one aggregate function can be specified without an alias [page 623]

PIVOT error: PIVOT XML does not contain a valid subquery, ANY, or ALL in the IN clause [page 624]

PIVOT error: Too many aggregate functions and IN clause items [page 624]

Plan cannot be generated for this type of statement [page 625]

Plan may contain virtual indexes [page 625]

Point is duplicated %1 [page 626]

Polygon ring order has been reoriented [page 626]

Position %1 is invalid (should be between %2 and %3) [page 627]

Positioned update operation attempted on a view with an INSTEAD OF trigger [page 627]

Possible database corruption found: %1 [page 628]

Prevented removal of LDAP server "%1" because it is the only LDAP server and the value of login_mode is "LDAPUA" [page 628]

Prevented removal of LDAP server because it is referenced by login policy "%1" which is the only login policy with an LDAP server and the value of login_mode is "LDAPUA" [page 629]

Previous error lost before RESIGNAL [page 629]

Primary key column '%1' already defined [page 630]

Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3' [page 630]

Primary key for table '%1' is not unique: Primary key value ('%2') [page 631]

Principal mirror servers are already defined [page 632]

Procedure '%1' is no longer valid [page 632]

Procedure '%1' needs a RESULT clause for returned ROW or ARRAY [page 633]

Procedure '%1' not found [page 633]

Procedure '%1' terminated with unhandled exception '%2' [page 634]

Procedure has completed [page 634]

Procedure in use by '%1' [page 635]

Procedure is currently being altered or dropped [page 635]

Procedure or trigger calls have nested too deeply [page 635]

Publication '%1' not found [page 636]

Publication predicates were not evaluated [page 637]

RAISERROR executed: %1 [page 637]

Reading %1 database pages exceeds available cache of %2 pages [page 638]

READTEXT or WRITETEXT statement cannot refer to a view [page 638]

RECOVER UNTIL and FOR REPLICATION cannot be used together [page 639]

Recursion is not allowed without the RECURSIVE keyword [page 639]

Recursive column %1: conversion from '%2' to '%3' loses precision [page 640]

Referential integrity actions other than RESTRICT not allowed for temporary tables [page 640]

Remote column %1 has been specified with the wrong case [page 641]

Remote message type '%1' not found [page 641]

Remote server '%1' could not be found [page 642]

Remote server '%1' is currently configured as read-only [page 642]

Remote server does not have the ability to support this statement [page 643]

Remote server is currently in use and cannot be dropped [page 643]

Remote statement failed [page 644]

RENAME and FOR REPLICATION cannot be used together [page 644]

Reorganize table is already being run on table "%1" [page 645]

REORGANIZE TABLE ran out of space [page 645]

Request denied -- no active databases [page 645]

Request interrupted due to timeout [page 646]

Request to start/stop database denied [page 646]

Required operators excluded [page 647]

Resource governor for '%1' exceeded [page 648]

RESTORE statement missing a FROM clause [page 648]

RESTORE unable to find a log backup on the latest timeline [page 649]

RESTORE unable to open file '%1' [page 649]

RESTORE unable to start database '%1' [page 650]

RESTORE unable to write to file '%1' [page 650]

Restoring database from an upgrade image [page 651]

Result set not allowed from within an atomic compound statement [page 651]

Result set not permitted in '%1' [page 652]

Retrying read of corrupt page (page '%1') [page 652]

Return type of void from procedure '%1' cannot be used in any expression [page 653]

Right truncation of string data [page 653]

Role "%1" already exists [page 654]

Rollback occurred due to blocking_others_timeout [page 654]

Rollback occurred due to deadlock during prefetch [page 655]

ROLLBACK TO SAVEPOINT not allowed [page 655]

Row has been updated since last time read [page 656]

Row has changed since last read -- operation canceled [page 656]

Row in table '%1' was modified or deleted in BEFORE trigger [page 657]

Row not found [page 658]

Row was dropped from table %1 to maintain referential integrity [page 658]

Run time SQL error -- %1 [page 659]

SAP HANA environment error, unable to ping name server [page 659]

SAP HANA environment error, unable to execute command on name server [page 660]

Savepoint '%1' not found [page 660]

Savepoints require a rollback log [page 661]

Scalar variable '%1' not found [page 661]

Schedule '%1' for event '%2' already exists [page 662]

Schedule '%1' for event '%2' not found [page 662]

Script file missing statement "go" delimiter on a separate line [page 663]

Secure HTTP connections are not supported on this platform [page 663]

Select lists in UNION, INTERSECT, or EXCEPT do not match in length [page 664]

SELECT returns more than one row [page 665]

Semaphore "%1" not found [page 665]

Semaphore was dropped [page 665]

Sequence '%1' already exists [page 666]

Sequence '%1' in use by another connection [page 667]

Sequence '%1' not found [page 667]

Sequence generators are not supported for this database [page 668]

Sequence name '%1' is ambiguous [page 668]

Server '%1': %2 [page 669]

Server capability name '%1' could not be found in the database [page 669]

Server name can only be specified when connecting to a cloud database server with NODETYPE=DIRECT [page 670]

Server not found and unable to automatically start [page 670]

Service '%1' already exists [page 671]

Service '%1' in use [page 671]

Service '%1' not found [page 672]

Service definition requires a statement when authorization is off [page 672]

Service statement definition is inconsistent with service type [page 673]

Service statement definition is invalid or unsupported [page 673]

Service type does not allow '%1' attribute [page 674]

Service type required for CREATE SERVICE [page 674]

SET clause for column '%1' used incorrectly [page 675]

SETUSER not allowed in procedures, triggers, events, or batches [page 675]

Shared memory listener already started [page 676]

Signature '%1' does not match procedure parameters [page 676]

Snapshot isolation disabled or pending [page 677]

Spatial column '%1' cannot be included in a primary key or unique index [page 677]

Spatial column '%1' cannot be included in an index because it is not constrained to a single SRID [page 678]

Spatial feature %1 is not supported [page 678]

Spatial reference system "%1" is reserved [page 679]

Spatial reference system %1 cannot be modified because it is in use [page 680]

Spatial reference system '%1' already exists [page 680]

Spatial reference system '%1' not found [page 681]

Spatial reference system must specify the SRID to use [page 681]

Spatial unit of measure "%1" is reserved [page 682]

Specified database file already in use [page 682]

Specified database is invalid [page 683]

Specified database not found [page 683]

Specified file system volume not found for database '%1' [page 684]

Specified LDAP server '%1' is not found [page 684]

Specified local connection ID not found [page 685]

Specified role '%1' is a user extended as role [page 685]

Specified role '%1' is not a user extended as role [page 685]

Specified System Privilege '%1' is Invalid [page 686]

Specified user '%1' is a role [page 686]

SQL statement error [page 687]

SQL statements in BEGIN PARALLEL WORK...END PARALLEL WORK statement are not of the same type [page 687]

SQL statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 688]

SQLDA data type invalid [page 688]

SQLDA fields inconsistent for a multi-row SQLDA [page 689]

sqlpp/dblib version mismatch [page 689]

SRID %1 is referenced by column '%2' of table '%3' [page 690]

SRID %1 is referenced by domain "%3"."%2" [page 690]

SRID %1 is referenced by parameter '%2' of procedure '%3' [page 691]

ST_Geometry arguments not supported by SQL function %1 [page 691]

ST_MultiSurface contains elements with an invalid intersection (near "%1") [page 692]

Start date/time for non-recurring event '%1' is in the past [page 693]

Start listener error: %1 [page 693]

Statement %1 disallowed during upgrade from script [page 694]

Statement cannot be executed [page 694]

Statement contains an illegal usage of the non-deterministic function '%1' [page 695]

Statement contains an illegal usage of the NUMBER(*) function [page 695]

Statement interrupted by user [page 696]

Statement is not allowed in passthrough mode [page 696]

Statement not allowed during snapshot [page 697]

Statement not allowed on IMMEDIATE REFRESH text index [page 697]

Statement not allowed on text index for a materialized view [page 698]

Statement requires too much memory during %1 [page 698]

Statement size or complexity exceeds server limits [page 699]

Statement timed out: '%1' [page 699]

Statement's size limit is invalid [page 700]

Stop listener error: %1 [page 700]

Storing certificates is not supported for this database [page 701]

Storing OData Producers is not supported for this database [page 701]

Storing time zone information is not supported for this database [page 702]

String '%1' cannot be used as quote when QUOTE ALL is specified [page 702]

Subquery allowed only one SELECT list item [page 703]

Subquery cannot return more than one row [page 703]

Subscription '%1' not found [page 704]

Subscription to '%1' for '%2' already exists [page 704]

Subscription to '%1' for '%2' not found [page 705]

Subscription to publication '%1' for '%2' omitted from statement [page 705]

Support for materialized views is not available for this database [page 706]

Support for permissions on dbspaces is not available for this database [page 707]

Support for spatial is not available for this CPU [page 707]

Support for spatial is not available for this database [page 708]

Synchronization download failed to complete [page 708]

Synchronization failed due to an error on the MobiLink server: %1 [page 709]

Synchronization failed with internal error: %1 [page 709]

Synchronization failed. Check the dbmlsync log file for more details [page 710]

Synchronization failed. Check the results of the call to sp_get_last_synchronize_result(%1) for more information [page 710]

Synchronization is already in progress [page 711]

Synchronization message type '%1' not found [page 711]

Synchronization option '%1' contains semicolon, equal sign, curly brace, or is null [page 712]

Synchronization option '%1' not found [page 712]

Synchronization option is too long [page 713]

Synchronization profile '%1' already exists [page 713]

Synchronization profile '%1' has invalid parameter '%2' [page 714]

Synchronization profile '%1' not found [page 714]

Synchronization profiles are not supported for this database [page 715]

Synchronization schema changes and script versions are not supported for this database [page 716]

Synchronization server failed to commit the upload [page 716]

Syntax error near '%1' %2 %3 [page 717]

Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2' [page 717]

Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2' [page 718]

System command failed with return code %1 [page 718]

System event type '%1' not found [page 719]

System Privileges and Roles feature is not supported in this database [page 719]

Table '%1' contains a spatial column '%2' and no primary key [page 720]

Table '%1' contains an invalid reference to the ROWID function [page 720]

Table '%1' for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 721]

Table '%1' has a foreign key with a referential action [page 721]

Table '%1' has no columns [page 722]

Table '%1' has no primary key [page 722]

Table '%1' has publications [page 723]

Table '%1' is already included [page 724]

Table '%1' is in an outer join cycle [page 724]

Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change [page 725]

Table '%1' must synchronize to be in publication '%2' [page 725]

Table '%1' not found [page 726]

Table '%1' requires a unique correlation name [page 727]

Table '%1' specified more than once in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 727]

Table already has a primary key [page 728]

Table cannot have two primary keys [page 728]

Table created or altered after start of snapshot [page 729]

Table in use [page 729]

Table must be empty [page 730]

Table name '%1' is ambiguous [page 730]

Table or view '%1' is not valid for use with this statement [page 731]

Table Parameterized Functions and V4 TableUDFs are not supported for this database [page 731]

Table parameterized functions are not allowed across server types [page 732]

Table reference '%1' has been invalidated [page 732]

Table reference types not supported [page 733]

Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared [page 733]

Tag ID: '%1' specifies a value not bounded by an array [page 734]

Task '%1' is not allowed [page 734]

TDS login requests with RSA encrypted passwords must also use a nonce [page 735]

TDS login requests with unencrypted passwords are not permitted [page 736]

Temporary mutex or semaphore can only be dropped by the connection that created it [page 736]

Temporary space limit exceeded [page 737]

Term length outside allowed range [page 737]

Terminated by user -- transaction rolled back [page 738]

Text configuration "%1" already exists [page 738]

Text configuration "%1"."%2" not found [page 738]

Text index \"%1\" on table \"%2\" exists. Table with text index is not supported for LOAD TABLE statement in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 739]

Text index %1 cannot be used with text procedure %2 [page 740]

Text index with external prefilter cannot contain both binary and string columns [page 740]

Text indexes are not allowed across server types [page 741]

Text indexes are not supported for this database [page 741]

Text indexes on materialized views are not supported for this database [page 742]

Text queries cannot contain more than 300 terms [page 742]

Text query parser error: %1 [page 743]

The %1 algorithm is not available in FIPS mode [page 743]

The %1 remote data access class is no longer supported, please use %2 instead [page 744]

The '%1' attribute contains mismatched parentheses within '%2' [page 744]

The '%1' attribute is missing a comma within '%2' [page 745]

The '%1' attribute is not valid with procedure type '%2' [page 745]

The '%1' property is no longer supported [page 746]

The 'currvall' operator is not defined yet for sequence '%1' for this connection [page 746]

The address parameter "%1" conflicts with an existing %2 listener [page 747]

The address parameter "%1" provided to stop a listener has an invalid IP address or no port [page 748]

The aggregate expression '%1' must appear in either the SELECT list or a HAVING clause subquery [page 748]

The arguments to this procedure must be literal strings [page 749]

The attempt to drop LDAP server "%1" failed, suspend the server to drop it [page 749]

The attribute '%1' sets an option '%2' that is incompatible with '%3' [page 750]

The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2' [page 750]

The column '%1' does not exist in the remote table [page 751]

The communications environment could not be created [page 751]

The comparison '%1' cannot be used with geometries [page 752]

The connection parameters file could not be found [page 752]

The CONVERT USING clause must be specified when creating a unit of measure [page 753]

The cursor name '%1' already exists [page 753]

The data is not in a recognized format [page 754]

The data type of column or variable '%1' is not supported [page 754]

The data type specified for column '%1' is not compatible with the actual data type [page 755]

The database '%1' cannot be used for the SQL Anywhere Cockpit [page 755]

The database '%1' was not found [page 756]

The database must be upgraded to use the KEY option on the SYNCHRONIZE command [page 756]

The database name 'utility_db' is reserved for the utility database [page 757]

The database name is reserved for SQL Anywhere Cockpit [page 757]

The database server failed to shut down the dbmlsync server [page 758]

The database was created [page 758]

The dbicu library and server versions do not match [page 759]

The dbmlsync server did not have sufficient database permissions [page 759]

The dbmlsync server failed to shut down in a timely manner [page 760]

The DBN/DBF parameters do not match the database for this alternate server name [page 761]

The dbspace '%1' cannot be dropped because it contains tables or indexes [page 761]

The definition of temporary table '%1' has changed since last used [page 762]

The embedded SRID (%1) conflicts with the provided SRID (%2) [page 762]

The embedded SRID are inconsistent (%1 and %2) [page 763]

The file '%1' is invalid when the disk sandbox feature is enabled for database '%2' [page 763]

The format specification option '%1' is not recognized [page 764]

The format specification syntax is invalid [page 764]

The format type '%1' cannot be used here [page 765]

The format type '%1' is not recognized [page 765]

The function '%1' does not allow use of the '%2' clause [page 766]

The function '%1' requires the use of the '%2' clause [page 766]

The HTTP header '%1' is reserved and cannot be modified [page 767]

The ICU collation '%1' has defaulted to another collation [page 767]

The instantiation '%1' does not match an overload (near '%2'). Available overloads are '%3' [page 768]

The integrated login ID guest can only be mapped to the guest database user ID [page 768]

The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points [page 769]

The last HTTP or HTTPS listener cannot be stopped without using the force parameter [page 770]

The last shared memory or TCPIP listener cannot be stopped without using the force parameter [page 770]

The length of the value specified is too long, it exceeds the limit of %1 bytes [page 771]

The length of the variable '%1' is too long in this context; it exceeds the limit of %2 bytes [page 771]

The length specified for column '%1' is different than the actual length [page 772]

The licensed maximum number of mirror servers with type COPY has been exceeded [page 772]

The logging type ('%1') specified is invalid, not supported or incompatible [page 773]

The login ID '%1' has not been mapped to any database user ID [page 773]

The login ID '%1' is already mapped to user ID '%2' [page 774]

The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns [page 774]

The materialized view %1 cannot be changed to immediate because it has already been initialized [page 775]

The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list [page 775]

The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list [page 776]

The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate, non-nullable columns [page 776]

The materialized view cannot be changed to immediate because its definition contains an illegal construct [page 777]

The materialized view cannot be changed to immediate because its definition must not contain more than one query block [page 777]

The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression [page 778]

The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN [page 778]

The materialized view cannot be changed to immediate because the ON conditions refer to tables which are not in the null-supplying and preserved sides of the OUTER JOINS [page 779]

The materialized view cannot be changed to immediate because the primary key columns of any table in the preserved side of an OUTER JOIN must exist in the SELECT list [page 780]

The method you attempted to invoke was not enabled for your application [page 780]

The minimum percentage '%1' is invalid. The minimum percentage must be between 0 and 100. [page 781]

The mirror '%1' does not match database '%2' [page 781]

The multi patch shapefile shape is not supported [page 782]

The OData server returned an error: %1 [page 782]

The operation cannot be executed while the profiler is running [page 783]

The operation failed because column '%1's type does not support streaming [page 783]

The optimizer was unable to construct a valid access plan [page 784]

The option '%1' can only be set as a temporary option [page 784]

The option '%1' cannot be set from within a procedure [page 785]

The option '%1' is not recognized [page 785]

The option '%1' was not specified for target type '%2' [page 786]

The output path '%1' is invalid [page 786]

The PAM User Authentication (PAMUA) feature is not supported on this computer [page 787]

The parent of this mirror server is not currently connected [page 787]

The parent of this mirror server is not the primary server [page 788]

The pattern is too long [page 788]

The profiler has not been initialized. Contact SAP support. [page 789]

The profiler is already running [page 789]

The profiler is not running [page 789]

The profiler is not supported [page 790]

The provided stoplist is too long [page 790]

The remote data access feature is not supported on this platform [page 791]

The remote server does not support an auto-incrementing data type [page 791]

The remote table '%1' could not be found [page 792]

The result returned is non-deterministic [page 792]

The role '%1' was not dropped because it is granted to other users or roles. Use the 'WITH REVOKE' option to drop it [page 793]

The sample wait time cannot be changed once samples have been collected. Clear the sample data and then set the option. [page 794]

The search on LDAP server %1 completed with no matching results [page 794]

The search using '%1' failed due to one or more invalid values set [page 795]

The secure connection to the remote host failed: %1 [page 795]

The secure feature key name '%2' is not valid in the call to %1 [page 796]

The SELECT list for the derived table '%1' has no expression to match '%2' [page 796]

The selected database is currently inactive [page 797]

The server attempted to access a page beyond the end of the maximum allowable dbspace file size [page 797]

The server is not able to establish TCP/IP connections [page 798]

The size of the character column, variable, or value data type exceeds 32767 [page 799]

The spatial reference system type is not supported ('%1') [page 799]

The specified axis order is not supported for this type of spatial reference system [page 800]

The specified certificate is not valid [page 800]

The specified distinguished name '%1' does not match the search result '%2' [page 801]

The specified foreign key (%1) cannot be enforced [page 801]

The specified HTTP header contains illegal or non-ASCII characters [page 802]

The specified HTTP header is malformed [page 802]

The specified listener could not be registered [page 802]

The specified polygon format '%1' is not supported for this type of spatial reference system [page 803]

The specified session name '%1' is not valid [page 803]

The specified target type '%1' is not valid [page 804]

The specified transaction isolation is invalid [page 804]

The SQL Anywhere Cockpit '%1' cannot be used for the current operation [page 805]

The SQL Anywhere Cockpit template '%1' cannot be used for the current operation [page 805]

The SQL Anywhere Cockpit template file '%1' not found [page 806]

The SQL scripts DLL cannot be loaded [page 806]

The SRID %1 does not identify a geographic spatial reference system [page 807]

The status of the last synchronization upload is unknown [page 807]

The string '%1' is not a valid axis order [page 808]

The string '%1' is not a valid coordinate name [page 808]

The string is too long (%1) [page 809]

The synchronization failed because MobiLink returned authentication status '%1' with value '%2' [page 809]

The SYNCHRONIZE statement timed out [page 810]

The table specification '%1' identifies more than one remote table [page 811]

The text index %1 needs to be refreshed [page 811]

The transaction may not be committed because the primary server lost quorum [page 812]

The UltraLite database deploy file is invalid (code: %1, file: %2) [page 812]

The URI '%1' is invalid [page 813]

The user name specified must be the user name of the current connection [page 813]

The USING LOG PATH clause must be used in conjunction with the RECOVER UNTIL clause [page 814]

The UTF-16 endian specified does not match the Byte Order Mark found in the data [page 814]

The value '%2' is not a valid setting for the '%1' format specification option [page 815]

The value for the stoplist cannot be NULL [page 815]

The value specified is not within the required range %1 to %2 [page 816]

The variable '%1' must be %2 in this context [page 816]

The variable '%1' must not be NULL in this context [page 817]

The variable in the INTO clause is not a row type [page 817]

There is already a database variable named '%1' [page 818]

There are still active database connections [page 818]

There is already a variable named '%1' [page 819]

There is more than one way to join '%1' to '%2' [page 819]

There is no profiler data available [page 820]

There is no way to join '%1' to '%2' [page 820]

There is no way to join to '%1' [page 821]

There was insufficient memory to complete the %1 operation [page 821]

This connection already exists [page 822]

This database does not support encrypted tables [page 822]

This edition of SQL Anywhere is not available on this platform [page 823]

This operation is only allowed within a synchronization schema change [page 823]

This server is not licensed to support '%1' connections [page 824]

This server is not licensed to support the '%1' feature [page 824]

Time zone '%1' not found [page 825]

Time zone option error: %1 [page 825]

TLS handshake failure [page 826]

TLS initialization on server failed [page 826]

TLS ON cannot be used with URL %1 [page 826]

Too few columns [page 827]

Too many active trace event sessions [page 828]

Too many arguments for function or procedure '%1' [page 828]

Too many arguments for trace event '%1' [page 829]

Too many columns [page 829]

Too many columns in procedure result set [page 829]

Too many columns in row type [page 830]

Too many columns in schema [page 830]

Too many columns in SELECT list [page 831]

Too many columns in table [page 831]

Too many constraints in database [page 832]

Too many distinct group mappings for integrated user [page 832]

Too many expressions in GROUP BY list [page 833]

Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation [page 833]

Too many MESSAGE...FOR CONNECTION messages [page 834]

Too many mutexes and semaphores created [page 834]

Too many open cursors [page 835]

Too many parameters to this external procedure call [page 835]

Too many publications specified for operation [page 836]

Too many recursive iterations [page 836]

Too many references to a BLOB [page 836]

Too many tables in query [page 837]

Too many temporary mutexes and semaphores created [page 837]

Too many temporary tables in connection [page 838]

Too many users in database [page 839]

Trace event '%1' already exists [page 839]

Trace event '%1' is not valid [page 839]

Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first [page 840]

Trace event session '%1' already active [page 840]

Trace event session '%1' already exists [page 841]

Trace event session '%1' already has target type '%2' [page 841]

Trace event session '%1' already has trace event '%2' [page 842]

Trace event session '%1' does not have target type '%2' [page 842]

Trace event session '%1' does not have trace event '%2' [page 843]

Trace event session '%1' failed to start [page 844]

Trace event session '%1' is active. Stop active session before dropping the session [page 844]

Trace event session '%1' is already stopped [page 845]

Trace target option '%1' conflicts with option '%2' [page 845]

Traced query (%1, %2) does not exist [page 846]

Transact-SQL expression in a non-Transact-SQL statement near '%1' %2 [page 846]

Transact-SQL feature not supported [page 847]

Transact-SQL outer joins are currently disabled [page 847]

Transaction log backup page only partially full [page 848]

Transaction log mirroring cannot be used with database mirroring [page 848]

Transaction log was truncated [page 849]

Transform definition is too long [page 849]

Transform from SRID %1 not supported [page 849]

Transform from SRID %1 to %2 not supported [page 850]

TREAT AS can only be used with extended types. Cannot treat %1 as a %2 [page 851]

Trigger '%1' not found [page 851]

Trigger definition conflicts with existing triggers [page 852]

Trigger name '%1' is ambiguous [page 852]

Trigger or foreign key for table '%1' is no longer valid [page 853]

Triggers cannot be created on materialized view '%1' [page 853]

TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2 [page 854]

TRUNCATE TABLE statement cannot be used on a view [page 854]

Two rows with the same primary key have been downloaded for table '%1' [page 855]

Type '%1' cannot be instantiated with %2 arguments (near '%3') [page 855]

Type '%1' does not support method calls (near '%2') [page 856]

Type '%1' has no method named '%2' (near '%3') [page 856]

Type '%1' is not instantiable (near '%2') [page 857]

UltraLite cannot synchronize because a synchronization is already running [page 857]

UltraLite connection was restored [page 858]

UltraLite cursor (or result set or table) was restored [page 858]

UltraLite database state was restored [page 859]

UltraLite performed database recovery on startup [page 859]

Unable to access the file system on the device [page 860]

Unable to acquire table locks in specified time [page 860]

Unable to clean directory %1 [page 861]

Unable to close the cursor on table "%1". LOAD TABLE cannot be executed [page 861]

Unable to connect to server '%1': %2 [page 862]

Unable to connect to the remote host specified by '%1' [page 862]

Unable to connect, server definition is circular [page 863]

Unable to connect: The server did not accept the requested encryption type [page 863]

Unable to copy file %1 [page 864]

Unable to copy file %1 to destination %2 [page 864]

Unable to create directory %1 [page 865]

Unable to declare a row variable from the cursor using %ROWTYPE; invalid name for field %1 [page 865]

Unable to declare a row variable from the cursor using %ROWTYPE; no fields were found in the cursor [page 866]

Unable to delete database file [page 866]

Unable to delete file %1 [page 867]

Unable to enlist transaction; DTC may be down [page 867]

Unable to find in index '%1' for table '%2' [page 867]

Unable to find the cockpit parameters used to start or stop [page 868]

Unable to finish upgrade the SQL Anywhere Cockpit when it is not active [page 869]

Unable to load the dbrsakp shared object [page 869]

Unable to open backup log '%1' [page 870]

Unable to open the SQL Anywhere Cockpit template -- '%1' [page 870]

Unable to perform requested operation since this database uses keyless encryption [page 871]

Unable to prepare to save the SQL Anywhere Cockpit when it is not active. [page 871]

Unable to prepare to save the SQL Anywhere Cockpit when it is already being prepared. [page 872]

Unable to re-enlist transaction; DTC may be down [page 872]

Unable to retry download because upload is not finished [page 873]

Unable to save and restart the SQL Anywhere Cockpit when it is not prepared. [page 873]

Unable to start database "%1": CHAR collation or tailoring not supported on this platform [page 874]

Unable to start database "%1": NCHAR collation or tailoring not supported on this platform [page 874]

Unable to start database %1: Cannot use read-only mode since auditing is currently logging to the transaction log [page 875]

Unable to start database server [page 875]

Unable to start database server: missing license file [page 876]

Unable to start database server: Server fatal error [page 877]

Unable to start specified database: %1 [page 877]

Unable to start specified database: '%1' is an invalid transaction log [page 878]

Unable to start specified database: '%1' is an invalid transaction log mirror [page 878]

Unable to start specified database: '%1' is not a database [page 879]

Unable to start specified database: '%1' is not a valid database file [page 879]

Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing) [page 880]

Unable to start specified database: '%1' not expecting any operations in transaction log [page 880]

Unable to start specified database: '%1' was created by a different version of the software [page 881]

Unable to start specified database: '%1': transaction log file not found [page 881]

Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file [page 882]

Unable to start specified database: Cannot use log file '%1' since it is shorter than expected [page 882]

Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently [page 883]

Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file [page 883]

Unable to start specified database: Cannot use log file '%1' since the timeline does do not match the timeline of the database file [page 884]

Unable to start specified database: Log file error [page 884]

Unable to start specified database: Server must be upgraded to start database %1 [page 885]

Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid [page 885]

Unable to start specified database: Unknown encryption algorithm [page 886]

Unable to start the SQL Anywhere Cockpit when it is stopping [page 886]

Unable to start the SQL Anywhere Cockpit: %1 [page 887]

Unable to start the SQL Anywhere Cockpit: Please restart the server with a minimum page size of 4096 [page 887]

Unable to stop specified database: %1 [page 888]

Unable to stop the SQL Anywhere Cockpit when it is being started [page 888]

Unable to stop the SQL Anywhere Cockpit when it is being prepared to save. [page 889]

Unable to upgrade the SQL Anywhere Cockpit when it is not active [page 889]

Undeclared tag ID: '%1' [page 890]

Underflow when converting '%1' [page 890]

Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database [page 891]

Unit of measure "%1" is not a linear unit [page 891]

Unit of measure "%1" is not an angular unit [page 892]

Unit of measure '%1' already exists [page 892]

Unit of measure '%1' not found [page 893]

Unknown backup operation [page 893]

Unknown collation '%1' [page 894]

Unknown FOR XML EXPLICIT directive: '%1' [page 894]

Unknown function '%1' [page 895]

Unknown option '%1' specified for target type '%2' [page 896]

Unknown spatial reference system (%1) [page 896]

Unknown unit of measure '%1' [page 897]

UNLOAD TABLE cannot be used to unload a view [page 897]

UNPIVOT error: An IN clause item does not contain the same number of items as the FOR clause [page 898]

UNPIVOT error: Cannot create valid identifiers for IN clause items [page 898]

Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead [page 899]

Unsupported extended storage syntax [page 899]

Unsupported property '%1' in service USING attribute [page 900]

Unsupported use of ROW type in an INTO clause [page 900]

Unterminated C string [page 901]

Update conflict on snapshot transaction [page 901]

Update operation attempted on a read-only cursor [page 902]

Update operation attempted on non-updatable query [page 902]

Update operation attempted on non-updatable remote query [page 903]

Use of %TYPE or %ROWTYPE is not allowed for variable or temporary objects [page 903]

Use of feature '%1' is not allowed [page 904]

Use of statement '%1', which requires feature '%2', is not allowed [page 904]

Use of table privilege '%1' is not supported on the current database [page 905]

Use of WITH DROP OBJECTS is not allowed with '%1' [page 905]

Use of WITH NO SYSTEM PRIVILEGE INHERITANCE option is not allowed with %1 [page 906]

User "%1" already exists [page 906]

User '%1' already has EXECUTE permission [page 907]

User '%1' already has GRANT OPTION [page 907]

User '%1' already has membership in group '%2' [page 908]

User '%1' has the row in '%2' locked [page 908]

User '%1' is already the publisher for this database [page 909]

User '%1' is not a remote user for this database [page 910]

User '%1' is not a user group [page 910]

User cannot be dropped because external logins exist for this user [page 911]

User ID '%1' does not exist [page 911]

User message %1 already exists [page 912]

User message %1 not found [page 912]

User or Role ID '%1' does not exist [page 913]

User owns locked mutexes [page 913]

User owns procedures in use [page 913]

User owns sequences in use [page 914]

User owns tables in use [page 914]

User-defined exception signaled [page 915]

User-defined type '%1' not found [page 915]

USING attribute cannot coexist with FORMAT or GROUP attributes [page 916]

Using temporary table [page 916]

VALIDATE statement must refer to a base table [page 917]

Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%) [page 917]

Value %1 out of range for destination [page 918]

Value for column '%1' in table '%2' has changed [page 919]

Value truncated [page 919]

Value-sensitive cursor used after a TRUNCATE [page 920]

Variable '%1' not found [page 920]

VERIFY and FOR REPLICATION cannot be used together [page 921]

VERIFY and RENAME cannot be used together [page 921]

Verify fails, bytes written to pipe %1 and bytes written to file %2 [page 922]

Version 'V%1' interface used by external function call '%2' is not supported for execution in the current context [page 922]

View references '%1', which is a temporary object. Views can only refer to permanent objects [page 923]

VIRTUAL clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 923]

Virtual index creation with more than %1 columns [page 924]

Warning detected when optimizing SELECT INTO is treated as an error [page 924]

Warning: %1 [page 925]

When wait_for_commit database option is enabled, LOAD TABLE statement is not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 925]

Window '%1' not found [page 926]

Window function requires ORDER BY [page 926]

Window function used in predicate [page 927]

WITH CHECK OPTION violated for insert/update on base table '%1' [page 927]

WITH CHECKPOINT ON clause for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement [page 928]

WRITETEXT not allowed: immediate materialized view %1 depends on %2 [page 928]

Wrong number of parameters to function '%1' [page 929]

Wrong number of values for INSERT [page 929]

Wrong number of variables in FETCH [page 930]

XML parser error: %1 [page 931]

XMLGEN evaluation failure [page 931]

XPath parser error: %1 [page 931]

You are not authorized to assign the feature list '%2' to a secure feature key using %1 [page 932]

You are not authorized to change the secure feature key named '%2' using %1 [page 933]

You cannot synchronize or upgrade with uncommitted transactions [page 933]

You cannot use a security token when making remote connections [page 934]

You do not have '%1' system privilege or authority to set the option '%2' [page 935]

You must upgrade your database in order to use the MIRROR server class [page 935]

1.1.4.1 %1

Error constant	SQLE_OMNI_DEBUG
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The debug message for the console.
Severity	16
SQLCODE	-682
SQLSTATE	W0010
Sybase error code	13734

Probable cause

This message is used for displaying component integration services debug messages in the messages window.

1.1.4.2 %1 and %2 must not be the same

Error constant	SQLE_SAME_SOURCE_TARGET
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The source file or directory name
Parameter 2	The target file or directory name
Severity	16
SQLCODE	-1662
SQLSTATE	08WC3
Sybase error code	12464

Probable cause

You attempted to perform an operation using the same source and target file or directory.

1.1.4.3 '%1' cannot be used as the encoding specification for '%2' data

Error constant	SQL_E_INVALID_OPENSTRING_ENCODING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The encoding that has been specified
Parameter 2	The data type for which the encoding has been specified
Severity	16
SQLCODE	-1144
SQLSTATE	WC017
Sybase error code	13368

Probable cause

The specified encoding cannot be used for interpreting the given data. For CHAR data, the encoding must be the database's CHAR character encoding and for NCHAR data, it must be the database's NCHAR character encoding.

1.1.4.4 '%1' cannot be used as the NCHAR collation: only UCA and UTF8BIN may be used

Error constant	SQL_E_INVALID_NCHAR_COLLATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The collation that cannot be used as the NCHAR collation.
Severity	16
SQLCODE	-1073
SQLSTATE	WC010
Sybase error code	13442

Probable cause

The specified collation cannot be used as the NCHAR collation. NCHAR always uses UTF-8, so the collation must be either UCA or UTF8BIN.

1.1.4.5 %1 does not return a result set

Error constant	SQL_NO_RESULT_SET
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the procedure.
Severity	16
SQLCODE	-872
SQLSTATE	WP014
Sybase error code	13876

Probable cause

A procedure called in the FROM clause of a SELECT statement must return a result set.

1.1.4.6 '%1' for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_CREATEINDEX_TABLE_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified table or materialized view name.
Severity	16
SQLCODE	-1943
SQLSTATE	OAW40
Sybase error code	12234

Probable cause

The specified table or materialized view name for the CREATE INDEX statement is not supported when the statement is in the BEGIN PARALLEL WORK..END PARALLEL WORK statement.

1.1.4.7 '%1' is an invalid value for '%2'

Error constant	SQLE_INVALID_OPTION_VALUE
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The invalid value.
Parameter 2	Name of the option.
Severity	16
SQLCODE	-1053
SQLSTATE	42W85
Sybase error code	5849

Probable cause

You supplied an invalid value for an option. Some options only allow numeric values and some options only allow true or false. Also, many options do not permit the empty string as a value.

Related Information

[UltraLite Connection Strings and Parameters](#)
[UltraLite Connection Parameters](#)

1.1.4.8 '%1' is an unknown character set encoding label

Error constant	SQLE_UNKNOWN_CHARSET
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The character set encoding label that is not recognized.
Severity	16
SQLCODE	-868
SQLSTATE	WC001
Sybase error code	13872

Probable cause

The specified character set label is not recognized, so conversion from/to that character set is not possible.

1.1.4.9 '%1' is an unknown option

Error constant	SQLE_UNKNOWN_OPTION
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	The option that is unknown to the server.
Severity	10
SQLCODE	120
SQLSTATE	01W17
Sybase error code	13751

Probable cause

You attempted to set the value of an option that is not known to the server.

Related Information

[Database Options](#)

[UltraLite Database Options](#)

1.1.4.10 '%1' is an unknown property

Error constant	SQLE_UNKNOWN_PROPERTY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The property name (or ID).
Severity	16
SQLCODE	-1498
SQLSTATE	WU001

Probable cause

The specified property is unknown.

Related Information

[DB_PROPERTY Function \[System\]](#)

1.1.4.11 '%1' is an unrecognized service type

Error constant	SQLE_UNKNOWN_SERVICE_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The service type that is unrecognized.
Severity	16
SQLCODE	-916
SQLSTATE	42W94
Sybase error code	13568

Probable cause

An unrecognized service type was specified.

1.1.4.12 %1 is not a directory

Error constant	SQLE_NOT_A_DIRECTORY
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The path name that is not a directory

Severity	16
SQLCODE	-1661
SQLSTATE	08WC2
Sybase error code	12463

Probable cause

Failed to perform an operation using directory name.

1.1.4.13 '%1' is not a known file format for loading or unloading tables

Error constant	SQL_E_UNSUPPORTED_LOAD_FORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified format.
Severity	19
SQLCODE	-601
SQLSTATE	WL001
Sybase error code	13669

Probable cause

An unsupported file format was specified for LOAD TABLE or UNLOAD TABLE.

1.1.4.14 '%1' is not a valid character set encoding for use with collation '%2'

Error constant	SQL_E_INVALID_ENCODING_FOR_COLLATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The character set encoding that is invalid.

Parameter 2	The collation for which the character set encoding is invalid.
Severity	16
SQLCODE	-1072
SQLSTATE	WC009
Sybase error code	13441

Probable cause

The specified character set cannot be used with the specified collation.

1.1.4.15 '%1' is not a valid class file

Error constant	SQL_E_BAD_CLASS_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the invalid file.
Severity	16
SQLCODE	-92
SQLSTATE	WP002
Sybase error code	13736

Probable cause

A file passed to the INSTALL JAVA statement was not a valid Java class file.

Related Information

[INSTALL JAVA Statement](#)

1.1.4.16 %1 listener binding failure for the address parameter "%2"

Error constant	SQLE_START_LISTENER_BIND_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener type
Parameter 2	The listener address parameter
Severity	16
SQLCODE	-1766
SQLSTATE	08WD2
Sybase error code	12374

Probable cause

A binding error occurred on the listener provided.

1.1.4.17 %1 listener for the address parameter "%2" is not found

Error constant	SQLE_STOP_LISTENER_NOT_FOUND_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener type
Parameter 2	The listener address parameter
Severity	16
SQLCODE	-1767
SQLSTATE	08WD3
Sybase error code	12373

Probable cause

You attempted to stop a listener that is not running.

1.1.4.18 %1 listener start option includes an unsupported option: %2

Error constant	SQLC_START_LISTENER_OPTION_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener type
Parameter 2	Error message
Severity	16
SQLCODE	-1776
SQLSTATE	08WD6
Sybase error code	12364

Probable cause

You attempted to start a listener with an unsupported option. For example, the "PORT" option should not be included in the options parameter to start a HTTP or HTTPS listener.

1.1.4.19 %1 listener start option parse error: %2

Error constant	SQLC_START_LISTENER_OPTION_PARSE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener type
Parameter 2	Error message
Severity	16
SQLCODE	-1775
SQLSTATE	08WD5
Sybase error code	12365

Probable cause

A parsing error occurred in the options for starting a listener.

1.1.4.20 %1 returned a result set with a different schema than expected

Error constant	SQLE_BAD_RESULT_SET
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the procedure that returned the incorrect result set.
Severity	12
SQLCODE	-866
SQLSTATE	WP012
Sybase error code	13870

Probable cause

When calling a procedure in the FROM clause of a SELECT statement, the expected schema of the result is taken from the WITH clause. If no WITH clause is given, the expected schema is taken from the system catalog. The result set returned from the call must match the expected schema or it must be possible to convert every column so that it matches.

1.1.4.21 %1 returned multiple result sets

Error constant	SQLE_TOO_MANY_RESULT_SETS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the procedure.
Severity	16
SQLCODE	-873
SQLSTATE	WP013
Sybase error code	13877

Probable cause

A procedure called in the FROM clause of a SELECT statement cannot return multiple result sets.

1.1.4.22 '%1' statement is not allowed as a consumer

Error constant	STMT_NOT_ALLOWED_AS_CONSUMER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Statement that generates the error.
Severity	16
SQLCODE	-1978
SQLSTATE	HY000
Sybase error code	12204

Probable cause

You attempted to execute a statement that is not allowed when being a consumer.

1.1.4.23 '%1' statement is not allowed on a mirrored database

Error constant	SQL_E_STMT_NOT_ALLOWED_WITH_MIRRORING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Statement that generates the error.
Severity	16
SQLCODE	-1288
SQLSTATE	WW120
Sybase error code	13666

Probable cause

You attempted to execute a statement that is not allowed when using a mirrored database.

1.1.4.24 %2 error occurred while trying to read file %1 during backup

Error constant	SQLE_BACKUP_ERROR_READING_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the file on which read failed
Parameter 2	OS error thrown during the read operation
Severity	16
SQLCODE	-1835
SQLSTATE	WB018
Sybase error code	12309

Probable cause

Read occurred error on transaction log file for a log backup cannot be opened

1.1.4.25 (no message text)

Error constant	SQLE_NOERROR
ODBC 2 state	00000
ODBC 3 state	00000
Severity	10
SQLCODE	0
SQLSTATE	00000
Sybase error code	13600

Probable cause

This code indicates that there was no error or warning.

1.1.4.26 A conflict with the dbmsync download phase was detected

Error constant	SQLE_RECORDING_CONFLICT_DETECTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-828
SQLSTATE	WW027
Sybase error code	13834

Probable cause

Dbmsync uses this error to detect download phase conflicts with rows modified by other connections.

1.1.4.27 A CONTAINS query is not allowed on the view or derived table '%1'

Error constant	SQLE_TEXT_INVALID_VIEW_FOR_CONTAINS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the view or derived table that cannot be queried with CONTAINS.
Severity	16
SQLCODE	-1283
SQLSTATE	WT020
Sybase error code	13791

Probable cause

A query expression (a view or a derived table) can only be queried using CONTAINS predicates if it does not use TOP, FIRST, LIMIT, or window aggregates in its nested query blocks. A query expression can only be queried using CONTAINS in the FROM clause if it has one nested query block, and it does not use DISTINCT, GROUP BY, TOP, FIRST, LIMIT, or window aggregates. In addition, the list of columns to search must all come from a single query expression or base table in the FROM clause of each nested query block. If more than one text index is used in the nested query blocks, they must have the same text configuration.

Related Information

[Regular Views](#)
[FROM Clause](#)

1.1.4.28 A dbspace has reached its maximum file size

Error constant	SQLE_DBSPACE_FULL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-604
SQLSTATE	04W07
Sybase error code	5006

Probable cause

A dbspace has grown to its maximum number of disk pages, which is usually limited by the maximum operating system file size. This is a fatal error.

Related Information

[Additional Dbspaces Considerations](#)
[Physical Limitations on Size and Number of Databases](#)
[UltraLite Database Limitations](#)

1.1.4.29 A disk sandbox error occurred for database '%1' when determining the disk sandbox status for file '%2'

Error constant	SQLE_DISKSANDBOX_UNABLE_TO_DETERMINE
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	The name of the database that could not determine the disk sandbox status of the file.
Parameter 2	The name of the invalid file.
Severity	15
SQLCODE	-1672
SQLSTATE	57W07
Sybase error code	12451

Probable cause

The file passed to the operation caused an error when determining the disk sandbox status.

Related Information

[-sbx Database Option](#)

[-sbx Database Server Option](#)

[disk_sandbox Option](#)

1.1.4.30 A disk sandbox error occurred for database '%1' when finding the full path for file '%1'

Error constant	SQLE_DISKSANDBOX_FULLPATH_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database that could not find the full path of the file.
Parameter 2	The name of the invalid file.
Severity	15
SQLCODE	-1673
SQLSTATE	57W08
Sybase error code	12450

Probable cause

There was an error in finding the full path of the file that was passed to the operation.

Related Information

[-sbx Database Option](#)
[-sbx Database Server Option](#)
[disk_sandbox Option](#)

1.1.4.31 A fatal error has occurred in the profiler library

Error constant	PROFILER_FATAL_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-2057
SQLSTATE	W1113
Sybase error code	12133

Probable cause

A fatal error occurred in the profiler library.

1.1.4.32 A geometry with SRID=%1 is not supported for method %2

Error constant	SQLE_SLERR_ROUND_EARTH_UNSUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The SRID of the geometry.
Parameter 2	The name of the method that does not support this SRID.
Severity	16
SQLCODE	-1435
SQLSTATE	2FW28
Sybase error code	13137

Probable cause

The named method does not support geometries in the specified spatial reference system. For example, the method might not support round-Earth data.

1.1.4.33 A geometry with SRID=%1 is not supported when computing distance between non-point geometries

Error constant	SQLE_SLERR_ROUND_EARTH_UNSUPPORTED_DIS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The SRID of the geometry.
Severity	16
SQLCODE	-1436
SQLSTATE	2FW29
Sybase error code	13136

Probable cause

When operating with round-Earth data, distance between non-point geometries is not supported.

1.1.4.34 A memory error occurred causing the profiler operation to fail

Error constant	PROFILER_MEMORY_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	17
SQLCODE	-2059
SQLSTATE	08W79
Sybase error code	12131

Probable cause

A memory error occurred which caused the profiler operation to fail.

1.1.4.35 A row cannot be stored because it exceeds the database page size

Error constant	SQL_ROW_EXCEEDS_PAGE_SIZE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1117
SQLSTATE	WW083
Sybase error code	13396

Probable cause

You attempted to insert or update a row which is too large to be stored on a database page. For UltraLite, with the exception of BLOB columns, a row must fit entirely on a single database page. Larger page sizes may be used to accommodate larger rows.

Related Information

[Maximum Page Size Considerations](#)
[UltraLite Initialize Database Utility \(ulinit\)](#)
[UltraLite page_size Creation Option](#)

1.1.4.36 A row was dropped because it could not be converted to the new schema format

Error constant	SQL_ROW_DROPPED_DURING_SCHEMA_UPGRADE
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10

SQLCODE	130
SQLSTATE	01W21
Sybase error code	13588

Probable cause

A row that was valid in the old schema is no longer valid. This could be because a column domain changed and the old value cannot be cast to the new domain. Rows are also dropped if a uniqueness or foreign key constraint cannot be satisfied.

Related Information

[Table Alteration](#)

[Adding a UNIQUE Constraint](#)

[ALTER TABLE Statement](#)

[ALTER TABLE Statement \[UltraLite\]](#)

1.1.4.37 A schema upgrade is not currently allowed

Error constant	SQLE_SCHEMA_UPGRADE_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-953
SQLSTATE	WW033
Sybase error code	13535

Probable cause

A schema upgrade cannot proceed because of concurrent use of the database. For example, all cursors must be closed before a schema upgrade can occur.

Related Information

[SQL Anywhere Server Upgrades](#)

[UltraLite Upgrades](#)

[Unload Utility \(dbunload\)](#)

[Upgrade Utility \(dbupgrad\)](#)

1.1.4.38 A synchronization schema change is already in progress

Error constant	SQLE_SYNC_SCHEMA_IN_PROGRESS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1322
SQLSTATE	WW140
Sybase error code	13234

Probable cause

A START SYNCHRONIZATION SCHEMA CHANGE statement is already in progress.

1.1.4.39 A thread used internally could not be started

Error constant	SQLE_THREAD_START_FAILURE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-626
SQLSTATE	WW011
Sybase error code	13681

Probable cause

This is a Windows 95 specific error. An operating system thread could not be started that is required to execute external functions.

1.1.4.40 A tracing connection is already active

Error constant	SQLE_TRACING_ALREADY_ATTACHED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1098
SQLSTATE	08W96
Sybase error code	13417

Probable cause

This database is already participating in a tracing connection, either as the sender (the database being traced) or as the receiver (the tracing database). A database can only send or receive one stream of tracing data at a time.

1.1.4.41 A user name must be specified if AUTHORIZATION is Off

Error constant	SQLE_SERVICE_REQUIRES_USER_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-918
SQLSTATE	42W96
Sybase error code	13566

Probable cause

A valid user name must be specified if AUTHORIZATION is Off.

Related Information

[CREATE SERVICE Statement \[HTTP Web Service\]](#)

[CREATE SERVICE Statement \[SOAP Web Service\]](#)

[ALTER SERVICE Statement \[HTTP Web Service\]](#)

[ALTER SERVICE Statement \[SOAP Web Service\]](#)

1.1.4.42 A workload capture (%1) is already in progress

Error constant	SQL_E_WORKLOAD_CAPTURE_ALREADY_EXISTS
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	The name of the workload capture that is already in progress.
Severity	16
SQLCODE	-942
SQLSTATE	WW029
Sybase error code	13546

Probable cause

You have tried to initiate a workload capture when one is already in progress. You need to wait for the other capture to complete.

1.1.4.43 Address parameter "%1" is not supported to start a listener for the personal database server

Error constant	SQL_E_START_LISTENER_UNSUPPORTED_ADDRESS
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	The listener address parameter
Severity	16
SQLCODE	-1883
SQLSTATE	08WEG
Sybase error code	12267

Probable cause

You attempted to start a listener with an unsupported IP address or port for the personal database server. The personal database server only allows the loopback address 127.0.0.1 or (:::1) when starting a listener.

1.1.4.44 Aggregated expression '%1' contains multiple columns of which one or more are outer references

Error constant	SQLE_MULTIPLE_AGGREGATE_COLUMNS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The aggregated expression in error.
Severity	15
SQLCODE	-861
SQLSTATE	42W68
Sybase error code	13865

Probable cause

A subselect within the nested query contains an aggregate function whose parameters include an outer reference. In such cases, the outer reference must be the only column referenced in the expression.

Related Information

[Correlated and Uncorrelated Subqueries](#)
[Where You Can Use Aggregate Functions](#)
[FROM Clause](#)
[Subqueries in Expressions - UltraLite](#)
[FROM Clause \[UltraLite\]](#)

1.1.4.45 Alias '%1' is not unique

Error constant	SQLE_ALIAS_NOT_UNIQUE
ODBC 2 state	37000
ODBC 3 state	ERROR
Parameter 1	Name of the alias.
Severity	15
SQLCODE	-830
SQLSTATE	42W60
Sybase error code	13836

Probable cause

The same alias is used more than once in a SELECT list.

Related Information

[Renamed Columns in Query Results](#)

[SELECT Statement](#)

[SELECT Statement \[UltraLite\]](#)

1.1.4.46 All column reference arguments must refer to the same table

Error constant	SQLE_TEXT_TOO_MANY_TABLE_REFERENCES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1157
SQLSTATE	WT002
Sybase error code	13356

Probable cause

All column references in a CONTAINS query must refer to the same table.

Related Information

[CONTAINS Search Condition](#)

1.1.4.47 All threads are blocked

Error constant	SQL_E_THREAD_DEADLOCK
ODBC 2 state	40001
ODBC 3 state	40001
Severity	13
SQLCODE	-307
SQLSTATE	40W06
Sybase error code	1205

Probable cause

You attempted to read or write a row and it is locked by another user. Also, all other threads (see the -gn server option) are blocked waiting for a lock to be released. This is a deadlock situation and your transaction has been chosen as the one to rollback.

Related Information

[Transaction Blocking and Deadlock](#)
[-gn Database Server Option](#)

1.1.4.48 ALTER clause conflict

Error constant	SQL_E.Alter_clause_conflict
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Severity	15
SQLCODE	-125
SQLSTATE	53W01
Sybase error code	13623

Probable cause

A primary key clause, foreign key clause, or a uniqueness clause must be the only clause of an ALTER TABLE statement.

Related Information

[ALTER TABLE Statement](#)

1.1.4.49 An attempt to decrypt database '%1' failed

Error constant	SQL_E_DECRYPT_DATABASE_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database that could not be decrypted.
Severity	16
SQLCODE	-1244
SQLSTATE	WW119
Sybase error code	13270

Probable cause

Your attempt to decrypt a database file failed.

1.1.4.50 An attempt to delete database '%1' failed

Error constant	SQLE_DROP_DATABASE_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database that could not be deleted.
Severity	16
SQLCODE	-651
SQLSTATE	WW017
Sybase error code	13705

Probable cause

Your attempt to delete a database file failed. You may have attempted to delete a running database. Some parts of the database may have been deleted before failure.

Related Information

[Dropping a Database \(SQL Central\)](#)

[DROP DATABASE Statement](#)

[Erase Utility \(dberase\)](#)

[UltraLite Erase Utility \(ulerase\)](#)

1.1.4.51 An attempt to encrypt database '%1' failed

Error constant	SQLE_ENCRYPT_DATABASE_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database that could not be encrypted.
Severity	16
SQLCODE	-1243
SQLSTATE	WW118
Sybase error code	13271

Probable cause

Your attempt to encrypt a database file failed.

1.1.4.52 An expression of type %1 is not union-compatible with type %2

Error constant	SQLE_SLERR_NOT_UNION_COMPAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The type of expression 1.
Parameter 2	The type of expression 2.
Severity	16
SQLCODE	-1479
SQLSTATE	2FW72
Sybase error code	13093

Probable cause

The two types cannot be combined, for example in a set operation such as UNION or in a SQL function such as COALESCE.

1.1.4.53 An incremental refresh is not possible when handles are exhausted

Error constant	SQLE_TEXT_HANDLES_EXHAUSTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1390
SQLSTATE	WT024
Sybase error code	13180

Probable cause

Incremental refresh of a MANUAL or AUTO REFRESH text index is not possible when handles are exhausted. You need to rebuild the text index before you can use incremental refresh.

Related Information

[Text Index Refresh Types](#)
[REFRESH TEXT INDEX Statement](#)

1.1.4.54 An input string in '%1' format cannot be used here

Error constant	SQLE_SLERR_WRONG_FORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid format.
Severity	16
SQLCODE	-1430
SQLSTATE	2FW23
Sybase error code	13142

Probable cause

A string with the specified format cannot be used in this context.

1.1.4.55 An internal error has occurred in the profiler library

Error constant	PROFILER_INTERNAL_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	18
SQLCODE	-2056
SQLSTATE	W1112

Probable cause

You used a JWT provider name that does not exist.

1.1.4.56 An internal error has occurred in the spatial library

Error constant	SQLE_SLERR_INTERNAL_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1480
SQLSTATE	2FW73
Sybase error code	13092

Probable cause

An unexpected error occurred.

1.1.4.57 An invalid authorization code was specified in the call to %1

Error constant	SQLE_SFC_INVALID_KEY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Severity	15
SQLCODE	-1688
SQLSTATE	08S04
Sybase error code	12442

Probable cause

An invalid secure feature key value was passed to the specified procedure.

Related Information

[Secured Features](#)

[-sf Database Server Option](#)

[sa_server_option System Procedure](#)

1.1.4.58 An invalid multi-byte input character was encountered when converting from %1 to %2

Error constant	SQLE_ILLEGAL_MULTIBYTE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	16
SQLCODE	-879
SQLSTATE	WC003
Sybase error code	13890

Probable cause

While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The operation was aborted.

1.1.4.59 An invalid multi-byte input character was encountered when converting from %1 to %2

Error constant	SQLE_ILLEGAL_MULTIBYTE_WARNING
ODBC 2 state	01000

ODBC 3 state	01000
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	10
SQLCODE	125
SQLSTATE	01WC1
Sybase error code	13892

Probable cause

While the server was performing character set conversion on an input string, an invalid multi-byte character was encountered. The illegal character was directly copied without conversion. Data following the illegal character may be misinterpreted. See `on_charset_conversion_failure` option.

Related Information

[Character Set Conversion](#)

1.1.4.60 An invalid secure feature list '%2' was specified in the call to %1

Error constant	SQLE_SFC_INVALID_FEAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature list.
Severity	15
SQLCODE	-1689
SQLSTATE	08S05
Sybase error code	12443

Probable cause

An invalid list of secure features was passed to the specified procedure.

Related Information

[Secured Features](#)

[-sf Database Server Option](#)

[sa_server_option System Procedure](#)

1.1.4.61 An ST_CircularString cannot be constructed from %1 points (near '%2')

Error constant	SQLE_SLERR_CIRC_NUM_POINTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The incorrect number of points given.
Parameter 2	The value or method where the error was detected.
Severity	16
SQLCODE	-1410
SQLSTATE	2FF71
Sybase error code	13162

Probable cause

A circularstring geometry should consist of three points followed optionally by an arbitrary number of pairs of points.

1.1.4.62 Another connection has already registered as '%1'

Error constant	SQLE_NOT_UNIQUE_CONN_REG_LABEL
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Registered connection label.
Severity	16
SQLCODE	-788
SQLSTATE	5RW27
Sybase error code	13798

Probable cause

You attempted to register a connection with a label already in use for the same application.

1.1.4.63 Another connection has the row in '%1' locked

Error constant	SQLE_ROW_LOCKED
ODBC 2 state	40001
ODBC 3 state	40001
Parameter 1	Table that generates the error.
Severity	21
SQLCODE	-1281
SQLSTATE	42W80
Sybase error code	13805

Probable cause

You attempted modify or delete a row that is locked by another connection. The row will be unlocked once that connection commits or rolls back.

1.1.4.64 Argument "%1" must be a column reference

Error constant	SQLE_TEXT_BAD_COLUMN_REFERENCE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The argument number.
Severity	16
SQLCODE	-1156
SQLSTATE	WT001
Sybase error code	13357

Probable cause

The CONTAINS argument must be a column reference.

1.1.4.65 Argument %1 of procedure '%2' cannot be NULL

Error constant	SQLE_ARGUMENT_CANNOT_BE_NULL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The argument number that cannot be NULL.
Parameter 2	The name of the procedure that cannot receive the NULL parameter.
Severity	16
SQLCODE	-90
SQLSTATE	WP000
Sybase error code	409

Probable cause

You passed a NULL value to a procedure expecting a scalar argument. For example, a Java procedure that has an 'int' argument cannot receive a NULL value.

1.1.4.66 Argument to GROUPING aggregate must be a grouping column in the GROUP BY clause

Error constant	SQLE_INVALID_GROUPING_AGGREGATE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-962
SQLSTATE	42WA7
Sybase error code	13527

Probable cause

Only a grouping column is permitted as an argument to the GROUPING aggregate function. An argument that contains anything other than a single grouping column expression will not be accepted.

1.1.4.67 Array contains too many elements

Error constant	SQLE_TOO_MANY_ARRAY_ELEMENTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1897
SQLSTATE	54W23
Sybase error code	12259

Probable cause

The array contains too many elements. The number of elements in an array is limited to 65535.

1.1.4.68 Array element error: array index '%1' is out of range

Error constant	SQLE_INVALID_ARRAY_INDEX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Value of the array index expression
Severity	16
SQLCODE	-1598
SQLSTATE	2202E
Sybase error code	12508

Probable cause

You tried to access an array element with an index outside the declared size of the array. For an array of size N, valid array elements are numbered 1 through N.

Related Information

[ROW and ARRAY Composite Data Types](#)
[ARRAY Constructor \[Composite\]](#)

1.1.4.69 At least one of the specified dbspaces was not calibrated

Error constant	SQLE_DBSPACE_NOT_CALIBRATED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-860
SQLSTATE	WW028
Sybase error code	13864

Probable cause

You attempted to calibrate a dspace that was not open or was too small.

1.1.4.70 ATTACH TRACING could not connect to the tracing database

Error constant	SQLE_ATTACH_TRACING_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1097
SQLSTATE	08W95
Sybase error code	13418

Probable cause

A connection to the tracing database could not be established. Check your connection string and verify that other clients can connect. Note that if you are trying to attach tracing to another server, perhaps the connection is being blocked by a firewall. You can also receive this error if the database server running either the production database or the tracing database is not using the TCP/IP protocol.

Related Information

[ATTACH TRACING Statement \(Deprecated\)](#)
[-x Database Server Option](#)

1.1.4.71 ATTACH TRACING TO LOCAL DATABASE cannot be used with a strongly encrypted database

Error constant	SQLE_NO_LOCAL_CONNECTIONS_TO_ENCRYPTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1088
SQLSTATE	WW069
Sybase error code	13426

Probable cause

The local database is strongly encrypted, so you cannot use the LOCAL DATABASE clause of the ATTACH TRACING statement. You must specify a connection string with the encryption key for the database.

Related Information

[ATTACH TRACING Statement \(Deprecated\)](#)
[DatabaseKey \(DBKEY\) Connection Parameter](#)

1.1.4.72 Attempt to allocate memory for LDAP server "%1" failed

Error constant	SQLE_LDAPSERVER_ALLOC_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the LDAP Server.

Severity	16
SQLCODE	-1570
SQLSTATE	WW203
Sybase error code	12535

Probable cause

An attempt to allocate memory for an LDAP Server class object failed.

1.1.4.73 Attempt to alter unnamed column constraint when named constraints exist

Error constant	SQLE_AMBIGUOUS_CONSTRAINT
ODBC 2 state	S0002
ODBC 3 state	42S24
Severity	16
SQLCODE	-930
SQLSTATE	42U05
Sybase error code	13555

Probable cause

You have asked for an unnamed column constraint to be altered, but there is at least one named constraint.

1.1.4.74 Attempt to start a second snapshot in a transaction

Error constant	SQLE_SNAPSHOT_ALREADY_STARTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1232
SQLSTATE	42WC9

Probable cause

A transaction tried to start a snapshot (for example, using the BEGIN SNAPSHOT statement) while another snapshot was already active.

1.1.4.75 Attempt to use snapshot isolation in a non-snapshot transaction

Error constant	SQLE_NON_SNAPSHOT_TRANSACTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1065
SQLSTATE	42WBB
Sybase error code	13449

Probable cause

A transaction tried to use snapshot isolation but did not begin with snapshot isolation.

1.1.4.76 Attempted two active database requests

Error constant	SQLE_DOUBLE_REQUEST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-298
SQLSTATE	42W22
Sybase error code	13663

Probable cause

In Embedded SQL, you attempted to submit a database request while you have another request in progress. You should either use a separate SQLCA and connection for each thread accessing the database, or use thread synchronization calls to ensure that a SQLCA is only accessed by one thread at a time.

Related Information

[SQLCA Management for Multithreaded or Reentrant Code](#)

[Multiple SQLCAs](#)

[The SQL Communication Area \(SQLCA\)](#)

[Cancellation of Changes](#)

[Using Multiple SQLCAs to Manage Multiple Database Connections](#)

1.1.4.77 Authentication failed

Error constant	SQLC_AUTHENTICATION_FAILED
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-218
SQLSTATE	08W48
Sybase error code	13621

Probable cause

You set the database_authentication or connection_authentication option incorrectly.

1.1.4.78 Authentication violation

Error constant	SQLC_AUTHENTICATION_VIOLATION
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16

SQLCODE	-98
SQLSTATE	08W21
Sybase error code	13620

Probable cause

You attempted to connect to a server that has been authenticated for exclusive use with a specific application.

1.1.4.79 Automatic database upgrade applied

Error constant	SQLE_DATABASE_UPGRADE_WARNING
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	149
SQLSTATE	WW234
Sybase error code	13684

Probable cause

The database is from an older version of the software. An automatic database upgrade occurs during startup. Subsequently the database can no longer be opened with the older version of the software.

Related Information

[UltraLite Upgrades](#)

1.1.4.80 BACKINT configuration file error, %1

Error constant	SQLE_BACKUP_BKINT_HANA_CONF_FILE_ERR
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	error thrown during the read operation
Severity	16
SQLCODE	-1919
SQLSTATE	WB029
Sybase error code	12265

Probable cause

Error opening IQ SAP HANA configuration file for BACKINT

1.1.4.81 BACKUP clause '%1' conflicts with '%2'

Error constant	SQLE_INVALID_BACKUP_STATEMENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	First BACKUP clause.
Parameter 2	Second BACKUP clause.
Severity	16
SQLCODE	-1057
SQLSTATE	WB016
Sybase error code	13456

Probable cause

Clauses specified in the BACKUP STATEMENT are mutually exclusive.

1.1.4.82 Backup file '%1' already exists

Error constant	SQLE_BACKUP_FILE_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	Name of the file.
Severity	16
SQLCODE	-967
SQLSTATE	WB012
Sybase error code	13523

Probable cause

A file that would normally be created by this BACKUP statement already exists.

1.1.4.83 Backup file format is invalid

Error constant	SQL_E_RESTORE_INVALID_FORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	21
SQLCODE	-716
SQLSTATE	WB007
Sybase error code	13725

Probable cause

The format of an archive file to be used during a RESTORE is invalid.

1.1.4.84 Backup is unable to open database file '%1'

Error constant	SQL_E_BACKUP_UNABLE_TO_OPEN_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the file.
Severity	16
SQLCODE	-1079

SQLSTATE	WB017
Sybase error code	13435

Probable cause

The database file cannot be opened by the backup. It may have been erased or otherwise corrupted.

1.1.4.85 Backward scrolling cursors are not supported for remote objects

Error constant	SQLE_OMNI_BACKWARDS_CURSOR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-661
SQLSTATE	W0006
Sybase error code	13733

Probable cause

Backward scrolling cursors are not supported for remote objects. Use forward scrolling cursors only.

1.1.4.86 Bind to LDAP server %1 without a password is not allowed

Error constant	SQLE_LDAPUA_UTP
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The LDAP server name or search URL specifying the search.
Severity	16
SQLCODE	-1622
SQLSTATE	WW219

Probable cause

An LDAPUA search or validate failed returning LDAP_UNWILLING_TO_PERFORM due to invalid settings for the target LDAP server. Check access account values for the named LDAP server or search URL.

1.1.4.87 Call to %1 failed - the authorization code specified for the secure feature key named '%2' is incorrect

Error constant	SQLE_SFC_NOT_MATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Severity	14
SQLCODE	-1695
SQLSTATE	08S11
Sybase error code	12449

Probable cause

The provided authorization code did not match the value stored for the specified named key.

Related Information

[Secured Features](#)
[-sf Database Server Option](#)
[sa_server_option System Procedure](#)

1.1.4.88 Call to %1 failed - the key named '%2' is the last key with the MANAGE_FEATURES and MANAGE_KEYS features

Error constant	SQLE_SFC_CANNOT_REMOVE_LAST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Severity	16
SQLCODE	-1696
SQLSTATE	08S12
Sybase error code	12450

Probable cause

The call attempted to remove the last secure feature key that would enable both MANAGE_FEATURES and MANAGE_KEYS and this is not allowed.

Related Information

[Secured Features](#)
[-sf Database Server Option](#)
[sa_server_option System Procedure](#)

1.1.4.89 Call to %1 failed - the maximum number of secure feature keys has already been created

Error constant	SQLE_SFC_HIT_MAX_LIMIT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Severity	17
SQLCODE	-1692

SQLSTATE	08S08
Sybase error code	12446

Probable cause

The limit on the number of secure feature keys has been reached.

Related Information

[Secured Features](#)
[-sf Database Server Option](#)
[sa_server_option System Procedure](#)

1.1.4.90 Call to %1 failed - the secure feature key named '%2' already exists

Error constant	SQLE_SFC_KEY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Severity	15
SQLCODE	-1693
SQLSTATE	08S09
Sybase error code	12447

Probable cause

The user attempted to create a secure feature key with the name of a key that already exists.

Related Information

[Secured Features](#)

1.1.4.91 Call to %1 failed - the secure feature key named '%2' does not exist

Error constant	SQLE_SFC_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Severity	15
SQLCODE	-1694
SQLSTATE	08S10
Sybase error code	12448

Probable cause

The user attempted to reference a secure feature key that does not exist.

Related Information

[Secured Features](#)
[-sf Database Server Option](#)
[sa_server_option System Procedure](#)

1.1.4.92 Calling functions outside the database server is not supported

Error constant	SQLE_EXTERNAL_CALLS_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-617
SQLSTATE	WW003
Sybase error code	13674

Probable cause

You attempted to call a stored procedure that, in turn, calls a function in a dynamically loaded module. The operating system on which this stored procedure was called does not support such an action.

1.1.4.93 Can only describe a SELECT statement

Error constant	SQLE_DESCRIBE_NONSELECT
ODBC 2 state	OK
ODBC 3 state	OK
Severity	16
SQLCODE	-160
SQLSTATE	07005
Sybase error code	3819

Probable cause

In the C language interface, you attempted to describe the SELECT list of a statement other than a SELECT statement. In UltraLite this error can result from trying to retrieve the schema of any statement other than a SELECT.

Related Information

[DESCRIBE Statement \[ESQL\]](#)

1.1.4.94 Cannot access a table that is part of a text index

Error constant	SQLE_TEXT_CANNOT_USE_TEXT_INDEX
----------------	---------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1169
SQLSTATE	WT013
Sybase error code	13344

Probable cause

It is not possible to directly manipulate tables created as part of a text index.

1.1.4.95 Cannot access file '%1' -- %2

Error constant	SQLE_CANNOT_ACCESS_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name.
Parameter 2	The cause of the error.
Severity	19
SQLCODE	-602
SQLSTATE	WL002
Sybase error code	13670

Probable cause

A file cannot be accessed. For example, a file referenced by LOAD TABLE does not exist or cannot be read. The message will contain the reason for the error.

Related Information

[LOAD TABLE Statement](#)
[LOAD TABLE Statement \[UltraLite\]](#)

1.1.4.96 Cannot access schema file '%1'

Error constant	SQLE_CANNOT_ACCESS_SCHEMA_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the file or indication that no name was given.
Severity	16
SQLCODE	-951
SQLSTATE	WW031
Sybase error code	13537

Probable cause

UltraLite requires a schema file to perform the current operation. Either no schema file was specified or the one specified was not accessible or was corrupt.

1.1.4.97 Cannot add a comment to a table declared as LOCAL TEMPORARY

Error constant	SQLE_COMMENT_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1042
SQLSTATE	WW065
Sybase error code	13469

Probable cause

You attempted to add a comment to a table that has been declared as LOCAL TEMPORARY. This is not allowed.

1.1.4.98 Cannot alter a column in an index

Error constant	SQLE_COLUMN_IN_INDEX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-127
SQLSTATE	53W05
Sybase error code	4939

Probable cause

You may have attempted to delete or modify the definition of a column that is part of a primary or foreign key. You may have attempted to delete a column that has an index on it. In this case, DROP the index or key, perform the ALTER statement, and then add the index or key again.

Related Information

[Primary Keys](#)

[Foreign Keys](#)

[UltraLite Tables and Columns](#)

[ALTER TABLE Statement](#)

[ALTER TABLE Statement \[UltraLite\]](#)

1.1.4.99 Cannot ALTER LDAP SERVER '%1' while LDAP server is in active state

Error constant	SQLE_LDAPSERVER_IS_ACTIVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The LDAP SERVER name.
Severity	16
SQLCODE	-1612
SQLSTATE	WW215
Sybase error code	12494

Probable cause

When an LDAP server is active, an ALTER statement may not change the LDAP server options without also specifying WITH SUSPEND clause to also put the server in suspended state. This is an invalid LDAP server state change.

1.1.4.100 Cannot alter or drop a text configuration referenced by a text index

Error constant	SQLE_TEXT_CANNOT_ALTER_CONFIG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1168
SQLSTATE	WT012
Sybase error code	13345

Probable cause

It is not possible to alter or drop a text configuration referenced by a populated text index or currently being used by a text procedure. Either copy the configuration and alter the copy, or close all cursors on text procedures and truncate all indexes that use the configuration.

1.1.4.101 Cannot append when using compression or encryption

Error constant	SQLE_UNLOAD_CANNOT_APPEND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1187
SQLSTATE	WL012
Sybase error code	13328

Probable cause

The UNLOAD statement cannot append to a file when using compression or encryption. Either the compressed or encrypted keywords were specified, or the file being appended to is compressed or encrypted.

1.1.4.102 Cannot assign automatic mirror server parent

Error constant	SQLE_CANNOT_ASSIGN_AUTO_PARENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1360
SQLSTATE	WW156
Sybase error code	13202

Probable cause

A CREATE MIRROR SERVER or ALTER MIRROR SERVER statement requested that a mirror parent be automatically assigned, but a parent server could not be found. The auto_add_server option may not be set, or might be set to an invalid server name.

Related Information

[Automatically Assign the Parent of a Copy Node](#)
[SET MIRROR OPTION Statement](#)

1.1.4.103 Cannot change password because change_password_dual_control process is in progress

Error constant	SQLE_CHANGE_PWD_DUAL_CONTROL_INPROGRESS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1665
SQLSTATE	28W20
Sybase error code	12458

Probable cause

You attempted to change password while changing password by change_password_dual_control option is in progress.

1.1.4.104 Cannot change synchronization user_name when status of the last upload is unknown

Error constant	SQLE_CANNOT_CHANGE_USER_NAME
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-867
SQLSTATE	0AW13
Sybase error code	13871

Probable cause

The MobiLink server uses the user_name to track synchronizations. If the status of the previous upload is unknown then you must resolve this condition before changing the user.

Related Information

[MobiLink Users in a Synchronization System](#)

[MobiLink Users](#)

[User Name Synchronization Parameter](#)

1.1.4.105 Cannot change the mirror server type from %1 to %2

Error constant	SQLE_CANNOT_CHANGE_MIRROR_SERVER_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The original mirror server type
Parameter 2	The proposed new mirror server type
Severity	16
SQLCODE	-1683
SQLSTATE	42WF2
Sybase error code	12442

Probable cause

You attempted to use the CREATE OR REPLACE MIRROR SERVER or ALTER MIRROR SERVER statement to change the mirror server type, but the proposed change is not supported.

Related Information

[User-initiated Role Switches \(Failovers\)](#)

[Troubleshooting: The Primary Server Cannot be Restarted](#)

[CREATE MIRROR SERVER Statement](#)

[ALTER MIRROR SERVER Statement](#)

1.1.4.106 Cannot change the MobiLink remote ID when the status of the last upload is unknown

Error constant	SQLE_CANNOT_CHANGE_ML_REMOTE_ID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1118
SQLSTATE	0AW17

Probable cause

The MobiLink server uses the remote ID to track synchronization progress. If the status of the previous upload is unknown then you must resolve this condition before changing the remote ID.

Related Information

[Remote IDs](#)

[Remote ID Settings](#)

[UltraLite ml_remote_id Option](#)

1.1.4.107 Cannot change the setting of the SingleCLRInstanceVersion server option after the CLR external environment has already been started

Error constant	SQLC_CANNOT_CHANGE_SETTING_OF_SINGLE_CLR_INSTANCE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1842
SQLSTATE	WJ033
Sybase error code	12302

Probable cause

You attempted to change the setting of the SingleCLRInstanceVersion server option after starting a CLR external environment. Restart the database server to change this server option.

1.1.4.108 Cannot change the setting of the UseSingleJVMInstance server option after Java has already been started

Error constant	SQL_E_CANNOT_CHANGE_SETTING_OF_SINGLE_JVM_INSTANCE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1825
SQLSTATE	WJ032
Sybase error code	12319

Probable cause

You attempted to change the setting of the UseSingleJVMInstance server option after starting a Java VM. Restart the database server to change this server option.

1.1.4.109 Cannot close a remote JDBC connection that is not the current connection

Error constant	SQL_E_CANNOT_CLOSE_JDBC_CONNECTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-998
SQLSTATE	W0026
Sybase error code	711

Probable cause

When attempting to close a remote JDBC connection, the specified connection must be the local connection.

1.1.4.110 Cannot commit or rollback while enlisted in a transaction

Error constant	SQLE_CANNOT_COMMIT_OR_ROLLBACK_WHILE_ENLISTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-800
SQLSTATE	55W09
Sybase error code	13810

Probable cause

You tried to explicitly commit or rollback on a connection that is enlisted in a transaction. You must use the Commit/Abort protocol of the transaction instead.

1.1.4.111 Cannot connect to mirror server. Use server name '%1' to find the primary server

Error constant	SQLE_CONNECTED_TO_MIRROR_SERVER
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The server name for the mirroring system.
Severity	11
SQLCODE	-1039
SQLSTATE	08W91
Sybase error code	13472

Probable cause

You have attempted to connect to the mirror server in a mirroring system. You should change your connection string or DSN to use the server name for the mirroring system.

1.1.4.112 Cannot convert %1 to %2

Error constant	SQLE_CONVERSION_ERROR
ODBC 2 state	07006
ODBC 3 state	07006
Parameter 1	The value that could not be converted.
Parameter 2	The name of the type for the conversion.
Severity	16
SQLCODE	-157
SQLSTATE	53018
Sybase error code	257

Probable cause

An error occurred while trying to convert a value to another data type.

Related Information

[Data Type Conversions](#)

[Data Type Conversion Functions](#)

1.1.4.113 Cannot convert %1 to %2. The bad value was supplied for column '%3' on row %4 of the data file

Error constant	SQLE_CONVERSION_ERROR_LOAD_TABLE
ODBC 2 state	07006
ODBC 3 state	07006
Parameter 1	Value that could not be converted.
Parameter 2	Destination data type.
Parameter 3	Name of the column where the value was to be inserted.
Parameter 4	Line number of the data file where the invalid data occurred.
Severity	16
SQLCODE	-162
SQLSTATE	53017

Probable cause

The data file supplied to LOAD TABLE contains a value that cannot be converted to the required data type.

Related Information

[LOAD TABLE Statement](#)

[LOAD TABLE Statement \[UltraLite\]](#)

1.1.4.114 Cannot convert between requested character set '%1' and database character set '%2'

Error constant	SQLE_FAILED_TO_START_CONVERTER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the requested character set encoding.
Parameter 2	The name of the database character set encoding.
Severity	16
SQLCODE	-870
SQLSTATE	WC002
Sybase error code	13874

Probable cause

The server is unable to convert between the connection character set that was specified and the database character set. This could happen when the dbicu and dbicudt DLLs are not installed.

1.1.4.115 Cannot convert between requested character sets '%1' and '%2'

Error constant	SQLE_FAILED_TO_START_CONVERTER_2_CHARSETS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the first requested character set encoding.
Parameter 2	The name of the second requested character set encoding.
Severity	16
SQLCODE	-891
SQLSTATE	WC008
Sybase error code	13592

Probable cause

The server is unable to convert between the two specified character sets. This could happen when the dbicu and dbicudt DLLs are not installed.

1.1.4.116 Cannot convert from %1 to %2 (near %3)

Error constant	SQLE_SLERR_ST_TO_XXX_FAILN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The geometry type of the value.
Parameter 2	The geometry type of the target.
Parameter 3	The value or method where the error was detected.
Severity	16
SQLCODE	-1411
SQLSTATE	2FF16
Sybase error code	13161

Probable cause

The value could not be converted to the specified target type.

1.1.4.117 Cannot convert value to a timestamp

Error constant	SQLE_BAD_TIMESTAMP_FORMAT
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1769
SQLSTATE	42WF3
Sybase error code	12371

Probable cause

Cannot convert the provided value to a timestamp. The timestamp format must match the date_order option.

1.1.4.118 Cannot create a materialized view because option '%1' has an inappropriate setting

Error constant	SQLE_CANNOT_CREATE_MATVIEW
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Name of the option with the incorrect setting.
Severity	14
SQLCODE	-1051
SQLSTATE	42WB6
Sybase error code	13460

Probable cause

You attempted to create a materialized view, but one of the database options is currently set to a value not permitted while creating a materialized view.

1.1.4.119 Cannot create a proxy table LIKE another table

Error constant	CANNOT_CREATE_PROXY_LIKE_TABLE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1979
SQLSTATE	0AW44
Sybase error code	12203

Probable cause

You attempted to create a proxy table LIKE another table.

1.1.4.120 Cannot create an index on Java class '%1'

Error constant	SQLE_CANNOT_INDEX_ON_JAVA_CLASS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the class.
Severity	16
SQLCODE	-704
SQLSTATE	WW022
Sybase error code	13748

Probable cause

An operation requiring an index was attempted in which an attempt was made to create an index on a Java class type.

1.1.4.121 Cannot create base table '%1': A global temporary table with the same name exists

Error constant	SQLE_CREATE_TABLE_GLOBAL_TEMP_TO_BASE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1729
SQLSTATE	42U11
Sybase error code	12405

Probable cause

The user attempted to replace a global temporary table with a base table and this is not allowed.

1.1.4.122 Cannot create global temporary table '%1': A base table with the same name exists

Error constant	SQLE_CREATE_TABLE_BASE_TO_GLOBAL_TEMP
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1730
SQLSTATE	42U10
Sybase error code	12406

Probable cause

The user attempted to replace a base table with a global temporary table and this is not allowed.

1.1.4.123 Cannot create item (%1) in the specified dbspace

Error constant	SQL_INVALID_DBSPACE_FOR_CREATE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the item that could not be created.
Severity	16
SQLCODE	-648
SQLSTATE	08W36
Sybase error code	13702

Probable cause

The specified dbspace is invalid. For example, an index must be created in a dbspace of the same type as the underlying table.

1.1.4.124 Cannot create mutex "%1" as a temporary mutex with this name already exists

Error constant	SQL_TEMP_MUTEX_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the mutex.
Severity	16
SQLCODE	-1802
SQLSTATE	42U38
Sybase error code	12342

Probable cause

A temporary mutex with the name specified for the permanent mutex already exists.

1.1.4.125 Cannot create mutex "%1": %2 with this name already exists

Error constant	SQLE_MUTEX_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the mutex.
Parameter 2	The type of the object.
Severity	16
SQLCODE	-1799
SQLSTATE	42U35
Sybase error code	12345

Probable cause

Object names must be unique across mutexes and semaphores. Semaphore cannot be replaced with a mutex.

1.1.4.126 Cannot create semaphore "%1" as a temporary semaphore with this name already exists

Error constant	SQLE_TEMP_SEM_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the semaphore.
Severity	16
SQLCODE	-1801
SQLSTATE	42U37
Sybase error code	12343

Probable cause

A temporary semaphore with the name specified for the permanent semaphore already exists.

1.1.4.127 Cannot create semaphore "%1": %2 with this name already exists

Error constant	SQLE_SEM_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the semaphore.
Parameter 2	The type of the object.
Severity	16
SQLCODE	-1800
SQLSTATE	42U36
Sybase error code	12344

Probable cause

Object names must be unique across mutexes and semaphores. Mutex cannot be replaced with a semaphore.

1.1.4.128 Cannot create synchronization entry for table '%1' with BLOB primary key

Error constant	SQLE_BLOB_IN_SYNC_TABLE_PK
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the table.
Severity	16
SQLCODE	-779
SQLSTATE	5RW18
Sybase error code	13789

Probable cause

You attempted to create a synchronization entry on a table with a BLOB primary key.

1.1.4.129 Cannot create table '%1': Name is used by a non-table object

Error constant	SQLE_CREATE_TABLE_EXISTING_OBJECT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1738
SQLSTATE	42U12
Sybase error code	12399

Probable cause

The user attempted to create a table, but the same name is used by another object that is not a table.

1.1.4.130 Cannot create text configuration '%1' because option '%2' has an inappropriate setting

Error constant	SQLE_TEXT_BAD_OPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the configuration.
Parameter 2	Name of the option with the incorrect setting.
Severity	16
SQLCODE	-1174
SQLSTATE	WT014
Sybase error code	13339

Probable cause

You attempted an operation that needs to create or alter the database options settings for a text configuration, but one of the options is currently set to a value not permitted for a text configuration.

1.1.4.131 Cannot delete or rename a column referenced in a trigger definition

Error constant	SQLC_COLUMN_IN_TRIGGER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-269
SQLSTATE	53W06
Sybase error code	102

Probable cause

You attempted to delete or rename a column referenced in a trigger definition. Drop the trigger before performing the ALTER statement.

1.1.4.132 Cannot delete PUBLIC option '%1' since user settings exist

Error constant	SQLC_UNSET_PUBLIC_ID
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the option.
Severity	15
SQLCODE	-896
SQLSTATE	42W82
Sybase error code	13587

Probable cause

You tried to delete a PUBLIC option, but there are user settings for the same option. The user settings must be deleted before the PUBLIC option is deleted.

1.1.4.133 Cannot deregister '%1' since active registered connection exists

Error constant	SQLE_DEREG_APP_IN_USE
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-786
SQLSTATE	5RW25
Sybase error code	13796

Probable cause

You attempted to deregister an application while there are still active connections registered to that application.

1.1.4.134 Cannot deregister application because of invalid cookie

Error constant	SQLE_DEREG_APP_NOT_FOUND
ODBC 2 state	42000
ODBC 3 state	42S02
Severity	16
SQLCODE	-785
SQLSTATE	5RW24
Sybase error code	13795

Probable cause

The application has not been registered successfully or it was previously deregistered.

1.1.4.135 Cannot deserialize Java object

Error constant	SQLE_JAVA_DESERIALIZATION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-663
SQLSTATE	WW018
Sybase error code	13745

Probable cause

The persistent Java object cannot be read from the database column. Possibly, the class of the object has been removed or modified.

1.1.4.136 Cannot drop a role that owns events in runtime server

Error constant	SQLE_USER_OWNS_EVENTS
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-1564
SQLSTATE	55W39
Sybase error code	12541

Probable cause

You attempted to drop a role that owns events while using the runtime server. This operation would result in dropping events. The runtime server cannot drop events.

1.1.4.137 Cannot drop a role that owns external environment objects in runtime server

Error constant	SQLE_USER_OWNS_EXTERNENVOBJECTS
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-1566
SQLSTATE	55W41
Sybase error code	12539

Probable cause

You attempted to drop a role that owns external environment objects while using the runtime server. This operation would result in dropping external environment objects. The runtime server cannot drop external environment objects.

Related Information

[ROW and ARRAY Composite Data Types](#)
[ARRAY Constructor \[Composite\]](#)

1.1.4.138 Cannot drop a role that owns sequences in runtime server

Error constant	SQLE_USER_OWNS_SEQUENCES
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-1563
SQLSTATE	55W38
Sybase error code	12542

Probable cause

You attempted to drop a role that owns sequences while using the runtime server. This operation would result in dropping sequences. The runtime server cannot drop sequences.

1.1.4.139 Cannot drop a role that owns web services in runtime server

Error constant	SQL_E_USER_OWNS_WEB_SERVICES
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-1565
SQLSTATE	55W40
Sybase error code	12540

Probable cause

You attempted to drop a role that owns web services while using the runtime server. This operation would result in dropping web services. The runtime server cannot drop web services.

1.1.4.140 Cannot drop a user that owns messages or data types

Error constant	SQL_E_USER_OWNS_MESSAGES_OR_DATATYPES
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-614
SQLSTATE	55W05
Sybase error code	13632

Probable cause

You attempted to drop a user that is the creator of a message or user-defined data type. The message or user-defined data type must be dropped first.

1.1.4.141 Cannot drop a user that owns objects involved in replication

Error constant	SQLCODE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-731
SQLSTATE	55W06
Sybase error code	13633

Probable cause

You attempted to drop a user that is the creator of a database object involved in replication. For example, the user may own a table that is part of a publication.

1.1.4.142 Cannot drop a user that owns procedures in runtime server

Error constant	SQLCODE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-270
SQLSTATE	55W04
Sybase error code	13641

Probable cause

You attempted to drop a user that owns procedures while using the runtime server. This operation would result in dropping procedures. The runtime server cannot drop procedures. Use the full server.

1.1.4.143 Cannot drop a user that owns tables in runtime system

Error constant	SQLCODE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLSTATE	-128
SQLSTATE	55W03
Sybase error code	13731

Probable cause

You attempted to drop a user that owns tables while running the runtime server. This operation would result in dropping tables. The runtime server cannot drop tables. Use the full server.

1.1.4.144 Cannot drop a user that owns text configurations

Error constant	SQLCODE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-1167
SQLSTATE	55W12
Sybase error code	13346

Probable cause

You attempted to drop a user that is the creator of a text configuration. The text configuration must be dropped first.

1.1.4.145 Cannot drop last unique index of an immediate materialized view

Error constant	SQLE_DELETE_UPDATABLE_MATVIEW_INDEX_ERR
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1184
SQLSTATE	55W21
Sybase error code	13331

Probable cause

You attempted to drop the last unique index on non-nullable columns of an immediate materialized view. Immediate materialized view needs at least one unique index on non-nullable columns to be valid.

1.1.4.146 Cannot drop or modify object '%1' because at least one other object (%2 '%3') depends upon it

Error constant	SQLE_OBJECT_HAS_DEPENDENTS
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	The name of the object that could not be dropped or modified.
Parameter 2	The type of the object that depends on the object that could not be dropped or modified.
Parameter 3	The name of the object that depends on the object that could not be dropped or modified.
Severity	16
SQLCODE	-1037

SQLSTATE	55W16
Sybase error code	13474

Probable cause

You attempted to drop or modify an object, such as a table or a column, that is used by another object, such as a materialized view, that cannot be automatically invalidated. The dependent object must be disabled or dropped before a drop or modification can be permitted.

1.1.4.147 Cannot drop the database's current time zone

Error constant	SQLE_CANNOT_DROP_CURRENT_TIMEZONE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1797
SQLSTATE	55W52
Sybase error code	12381

Probable cause

The database's time_zone option is set to the time zone you are attempting to drop.

1.1.4.148 Cannot enlist in a transaction while already enlisted in a transaction

Error constant	SQLE_CANNOT_ENLIST_WHILE_ALREADY_ENLISTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-801
SQLSTATE	55W10
Sybase error code	13811

Probable cause

You tried to enlist a second transaction on a connection that is already enlisted in a transaction.

1.1.4.149 Cannot enlist in a transaction with uncommitted data pending

Error constant	SQLE_CANNOT_ENLIST_WITH_UNCOMMITTED_DATA
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-802
SQLSTATE	55W11
Sybase error code	13812

Probable cause

You tried to enlist a transaction on a connection that has pending uncommitted data.

1.1.4.150 Cannot find index named '%1'

Error constant	SQLE_INDEX_NOT_FOUND
ODBC 2 state	S0012
ODBC 3 state	42S12
Parameter 1	Name of the index that cannot be found.
Severity	16
SQLCODE	-183
SQLSTATE	52W03
Sybase error code	6226

Probable cause

You attempted to perform an operation using an index that does not exist. Check for spelling errors. Check whether the index name must be qualified with a user ID.

Related Information

[Database Object Names and Prefixes](#)

1.1.4.151 Cannot find synchronization subscription with the name '%1'

Error constant	SQLE_SYNCHRONIZATION_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the subscription.
Severity	16
SQLCODE	-767
SQLSTATE	5RW12
Sybase error code	13777

Probable cause

You misspelled the name of a synchronization subscription or you did not qualify it correctly with a user name.

1.1.4.152 Cannot find synchronization user with the name '%1'

Error constant	SQLE_SYNC_SITE_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the synchronization user.
Severity	16
SQLCODE	-843
SQLSTATE	5RW37
Sybase error code	13849

Probable cause

You misspelled the name of a synchronization site or you did not qualify it correctly with a user name.

1.1.4.153 Cannot force failover when current server is marked as preferred

Error constant	SQL_E_CANNOT_FORCE_FAILOVER_ON_PREFERRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1314
SQLSTATE	WW136
Sybase error code	13242

Probable cause

An attempt was made to execute ALTER DATABASE SET PARTNER FAILOVER but the current server is marked as preferred. Attempting to force a failover in this situation is not allowed.

1.1.4.154 Cannot handle expressions involving remote tables inside stored procedures

Error constant	SQL_E_OMNI_EXPRESSION_IN_PROC
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	12
SQLCODE	-823
SQLSTATE	W0023
Sybase error code	13829

Probable cause

The server encountered an expression involving remote tables inside a stored procedure. The expression was too complicated to process.

1.1.4.155 Cannot insert or update computed column '%1'

Error constant	SQLLE_COMPUTED_COLUMN_WRITE_ATTEMPTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the column.
Severity	16
SQLCODE	-703
SQLSTATE	WW023
Sybase error code	4406

Probable cause

Computed column values cannot be modified explicitly. Their value is determined implicitly from the computed expression value.

1.1.4.156 Cannot load encryption DLL %1: version mismatch

Error constant	SQLLE_SACI_VERSION_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the encryption DLL.
Severity	16
SQLCODE	-1740
SQLSTATE	08WDO
Sybase error code	12397

Probable cause

The SACI version of the provided encryption DLL doesn't match the version of the software.

1.1.4.157 Cannot map a login ID to the sys or public user ID

Error constant	SQLE_LOGON_SYSMAP
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-248
SQLSTATE	28W07
Sybase error code	13696

Probable cause

You attempted to map a login ID to either SYS or PUBLIC.

1.1.4.158 Cannot modify column '%1' in table '%2'

Error constant	SQLE_CANNOT_MODIFY
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the column that cannot be changed.
Parameter 2	Name of the table containing the column.
Severity	14
SQLCODE	-191
SQLSTATE	42W32
Sybase error code	230

Probable cause

You may have tried to modify a column that you do not have permission to modify. You may have tried to modify a column defined as an expression (such as column1+column2) in a view.

1.1.4.159 Cannot modify publication entry using ALTER SYNCHRONIZATION

Error constant	SQLE_CANNOT_MODIFY_PUB_AS_SYNC
ODBC 2 state	42000
ODBC 3 state	42S02
Severity	16
SQLCODE	-770
SQLSTATE	5RW15
Sybase error code	13780

Probable cause

You attempted to modify a publication entry using an ALTER SYNCHRONIZATION statement.

1.1.4.160 Cannot modify synchronization entry using ALTER PUBLICATION

Error constant	SQLE_CANNOT_MODIFY_SYNC_AS_PUB
ODBC 2 state	42000
ODBC 3 state	42S02
Severity	16
SQLCODE	-769
SQLSTATE	5RW14
Sybase error code	13779

Probable cause

You attempted to modify a synchronization entry using an ALTER PUBLICATION statement.

1.1.4.161 Cannot open transaction log file -- %1

Error constant	SQLE_CANNOT_OPEN_LOG
ODBC 2 state	08003
ODBC 3 state	08003
Parameter 1	Reason why the transaction log file cannot be opened.
Severity	16
SQLCODE	-106
SQLSTATE	08W05
Sybase error code	2561

Probable cause

The database server was unable to open the named transaction log file. The transaction log file name may include an invalid device or directory. If this is the case, you can use the Transaction Log utility (dblog) to find out where the transaction log should be and perhaps change it.

Related Information

[The Transaction Log](#)
[Transaction Log Utility \(dblog\)](#)

1.1.4.162 Cannot output the histogram for string column '%1'

Error constant	SQLE_CANNOT_DUMP_STRING_HISTOGRAM
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	Name of the column containing string data.
Severity	10
SQLCODE	132
SQLSTATE	01W23
Sybase error code	13585

Probable cause

You tried to get the histogram for a column containing strings. Histograms on string information cannot be output in a readable format; as a result, no information was retrieved. Consider using the ESTIMATE function to get information on a specific value or range in the column.

Related Information

[Histogram Utility \(dbhist\)](#)

[ESTIMATE Function \[Miscellaneous\]](#)

1.1.4.163 Cannot perform specified operation, number of administrators for role '%1' falls below min_role_admins option value

Error constant	SQL_E_MIN_ROLE_ADMIN_VIOLATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the role that violates minimum number of administrators condition
Severity	16
SQLCODE	-1525
SQLSTATE	55W36
Sybase error code	12579

Probable cause

Specified operation cannot be performed because it will make the number of administrators for the specified role go below the threshold value set through database option min_role_admins.

1.1.4.164 Cannot perform specified operation, set user condition violated

Error constant	SQL_E_SET_USER_VIOLATION
----------------	--------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1553
SQLSTATE	55W37
Sybase error code	12552

Probable cause

Specified operation cannot be performed because it will invalidate the on going SET USER statements in the database.

Related Information

[Impersonation](#)
[GRANT Statement](#)
[SETUSER Statement](#)

1.1.4.165 Cannot proceed with online backup, SQLA log guid is ahead

Error constant	SQLA_LOG_GUID_IS_AHEAD
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1984
SQLSTATE	WB038
Sybase error code	12200

Probable cause

SQLA Log guid is ahead, cannot proceed with online backup.

1.1.4.166 Cannot register '%1' since another exclusive instance is running

Error constant	SQLE_SAME_EXCLUSIVE_APP_RUNNING
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-782
SQLSTATE	5RW21
Sybase error code	13792

Probable cause

You attempted to start an application, but another exclusive instance of the same application is already registered.

1.1.4.167 Cannot register '%1' since registration cookie exhausted

Error constant	SQLE_APP_REG_COOKIE_EXHAUSTED
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-789
SQLSTATE	5RW28
Sybase error code	13799

Probable cause

Cannot register the application until one is unregistered.

1.1.4.168 Cannot register another '%1' as an exclusive application

Error constant	SQLE_SAME_APP_RUNNING
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-783
SQLSTATE	5RW22
Sybase error code	13793

Probable cause

You attempted to register an exclusive application but another instance of the same application is already registered.

1.1.4.169 Cannot register connection because of invalid application cookie

Error constant	SQLE_CANNOT_REG_CONN
ODBC 2 state	42000
ODBC 3 state	42S02
Severity	16
SQLCODE	-784
SQLSTATE	5RW23
Sybase error code	13794

Probable cause

Application registration cannot be found for the given cookie.

1.1.4.170 Cannot register connection to '%1' since automatic label exhausted

Error constant	SQLC_CONN_REG_AUTO_LABEL_EXHAUSTED
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the application.
Severity	16
SQLCODE	-790
SQLSTATE	5RW29
Sybase error code	13800

Probable cause

You may register using a specified label instead.

1.1.4.171 Cannot remove class '%1': member of JAR

Error constant	SQLC_CLASS_MEMBER_OF_JAR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the class file that cannot be removed.
Severity	16
SQLCODE	-653
SQLSTATE	WP004
Sybase error code	13743

Probable cause

You attempted to remove a class file that is still part of a JAR. It must be removed with the JAR.

1.1.4.172 Cannot return NULL result as requested data type

Error constant	SQLE_VALUE_IS_NULL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1050
SQLSTATE	22030
Sybase error code	13461

Probable cause

You tried to retrieve a value from the database that was NULL and assign it to a variable that cannot be NULL.

1.1.4.173 Cannot revoke these permissions while user '%1' is actively replicating transactions

Error constant	SQLE_MUST_NOT_BE_REPLICATING
ODBC 2 state	40001
ODBC 3 state	40001
Parameter 1	The name of the user.
Severity	16
SQLCODE	-1080
SQLSTATE	42WBE
Sybase error code	13434

Probable cause

You attempted to revoke permissions from a user while there are transactions currently being replicated for that user. This is not allowed.

1.1.4.174 Cannot save SQL Anywhere Cockpit to existing file '%1'

Error constant	COCKPIT_FILE_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the file that already exists.
Severity	16
SQLCODE	-1955
SQLSTATE	WW258
Sybase error code	12224

Probable cause

The request to create a file failed because the file already exists.

1.1.4.175 Cannot serialize Java object with class '%1'

Error constant	SQL_E_JAVA_SERIALIZATION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The class of the value that cannot be serialized.
Severity	16
SQLCODE	-662
SQLSTATE	WI009
Sybase error code	13744

Probable cause

The Java object cannot be serialized as a persistent database column.

1.1.4.176 Cannot set a temporary option for user '%1'

Error constant	SQLE_TEMPORARY_NOT_ALLOWED
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	User ID whose option was to be changed.
Severity	16
SQLCODE	-203
SQLSTATE	42W45
Sybase error code	13687

Probable cause

TEMPORARY options are set on a connection basis, and only for specific options known to the database server. To change an option for another user, do not specify TEMPORARY in the SET OPTION statement.

1.1.4.177 Cannot set audit_log to the transaction log: The transaction log is not enabled for the database

Error constant	SQLE_CANNOT_SET_AUDIT_LOG_TO_TRANSLOG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1731
SQLSTATE	WE040
Sybase error code	12407

Probable cause

You are attempting to set the audit_log option to use the transaction log, but the transaction log is not enabled. You can specify a file in the audit_log option, or enable the transaction log and then specify to use the transaction log.

1.1.4.178 Cannot set database option "%1" because it is on the options watch list

Error constant	SQLE_OPTION_ON_WATCH_LIST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the option.
Severity	16
SQLCODE	-1180
SQLSTATE	WW096
Sybase error code	13335

Probable cause

An attempt was made to set a database option that is on the options watch list. The options watch list is used to help find references to options that have been removed or deprecated.

1.1.4.179 Cannot specify range that excludes next value for sequence %1

Error constant	SQLE_INVALID_ALTER_SEQUENCE
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the sequence.
Severity	16
SQLCODE	-1510
SQLSTATE	52W54
Sybase error code	13080

Probable cause

You attempted to modify either the MINVAL or MAXVAL boundary of a sequence to a value that would make the next invocation of the nextval expression for the sequence invalid. If you want to change the range boundaries to these values, you must also specify a RESTART WITH clause and supply a value within the new range.

Related Information

[Use of a Sequence to Generate Unique Values](#)
[ALTER SEQUENCE Statement](#)

1.1.4.180 Cannot specify read only in both the READ ONLY clause and the USING clause

Error constant	SQL_E_DIR_ACCESS_READ_ONLY_IN_TWO_PLACES
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1832
SQLSTATE	0AW32
Sybase error code	12312

Probable cause

You attempted to set the read only flag in both the READ ONLY clause and the USING clause.

1.1.4.181 Cannot stop the database server

Error constant	SQL_E_CANNOT_STOP_SERVER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-607
SQLSTATE	WW002
Sybase error code	13673

Probable cause

The server has determined that it cannot be shut down at this time. Normally, this error should not occur.

1.1.4.182 Cannot subscribe to '%1'

Error constant	SQL_E_CANNOT_SUBSCRIBE
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the publication.
Severity	16
SQLCODE	-768
SQLSTATE	5RW13
Sybase error code	13778

Probable cause

Some publications cannot be subscribed to, such as a synchronization publication.

1.1.4.183 Cannot synchronize table '%1' since it does not have a primary key

Error constant	SQL_E_CANNOT_SYNC_TABLE_WITHOUT_PK
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the table.
Severity	16
SQLCODE	-777
SQLSTATE	5RW16
Sybase error code	13787

Probable cause

Tables being synchronized must contain a primary key.

1.1.4.184 Cannot treat value '%1' as type %2. The dynamic type is %3

Error constant	SQL_E_TREAT_AS_DYNAMIC_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value that could not be converted.
Parameter 2	The name of the type for the conversion.
Parameter 3	The type of the value that could not be converted.
Severity	16
SQLCODE	-1362
SQLSTATE	53021
Sybase error code	13200

Probable cause

An error occurred while trying to treat a value as another data type. The dynamic type of the value does not match the destination type.

1.1.4.185 Cannot turn on auditing: The audit settings currently require a transaction log file

Error constant	SQL_E_AUDITING_WITHOUT_TRANSACTION_LOG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-913
SQLSTATE	42W91
Sybase error code	13571

Probable cause

This database is running without a transaction log file; however, the audit_log option is set to require one. Either use the Transaction Log utility (dblog) to create a transaction log file, or change the audit_log option to specify a file before turning auditing on.

Related Information

[Database Activity Audits](#)
[Transaction Log Utility \(dblog\)](#)

1.1.4.186 Cannot uniquely identify rows in cursor

Error constant	SQL_E_CANNOT_UNIQUELY_IDENTIFY_ROWS
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-295
SQLSTATE	09W05
Sybase error code	311

Probable cause

You opened a UNIQUE cursor on a SELECT statement for which a set of columns uniquely identifying each row cannot be generated. One of the tables may not be defined with a primary key or uniqueness constraint, or the SELECT statement may involve a UNION, INTERSECT, EXCEPT, or GROUP BY.

1.1.4.187 Cannot update an expression

Error constant	SQL_E_NON_UPDATEABLE_COLUMN
ODBC 2 state	37000
ODBC 3 state	42000
Severity	14
SQLCODE	-190
SQLSTATE	53W02
Sybase error code	230

Probable cause

You tried to update a column in a query that is a database expression rather than a column in a table.

Related Information

[Expressions in SQL Statements](#)
[Expressions in UltraLite](#)

1.1.4.188 Cannot update column '%1' since it appears in the ORDER BY clause

Error constant	SQLE_CANNOT_UPDATE_ORDER_BY_COLUMN
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the column that appears in the ORDER BY clause.
Severity	15
SQLCODE	-814
SQLSTATE	42W37
Sybase error code	6267

Probable cause

You attempted to update a column that appears in the ORDER BY clause. The ansi_update_constraints option controls whether this update is allowed.

1.1.4.189 Cannot update column '%1' since it does not appear in the SELECT clause

Error constant	SQLE_UPDATE_NOT_IN_SELECT
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the column that does not appear in the SELECT clause.
Severity	15
SQLCODE	-815
SQLSTATE	42W38
Sybase error code	7740

Probable cause

You attempted to update a column that does not explicitly appear in the SELECT list. The `ansi_update_constraints` option controls whether this update is allowed.

1.1.4.190 Cannot update materialized view because option '%1' has an inappropriate setting

Error constant	SQL_E_CANNOT_UPDATE_MATVIEW
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Name of the option with the incorrect setting.
Severity	14
SQLCODE	-1052
SQLSTATE	42WB7
Sybase error code	13461

Probable cause

You attempted to update/refresh a materialized view but one of the database options is currently set to a value that is not permitted while updating a materialized view, or, the option's setting does not match the value when the view was created.

1.1.4.191 Cannot update multiple tables immediate materialized view %1 depends on

Error constant	SQL_E_CANNOT_UPDATE_TWO_TABLES_IMV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the view that depends on two or more tables in the update statement.
Severity	16
SQLCODE	-1192
SQLSTATE	55W29

Probable cause

You attempted to simultaneously update two or more tables initialized immediate materialized view depends on. No more than one base table an immediate materialized view depends on can be updated in a statement.

1.1.4.192 Cannot update or delete an all-NULL row from table '%1'

Error constant	SQL_E_CANNOT_UPDATE_NULL_ROW
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	The name of the table that cannot be modified.
Severity	16
SQLCODE	-734
SQLSTATE	09W08
Sybase error code	13750

Probable cause

You attempted to modify or delete a row in the specified table, which is part of the NULL-supplying side of an outer join. However, the cursor is currently positioned on a derived row that contains an all-NULL row for this table, which is the result of the failure of one or more ON conditions to evaluate to TRUE. Verify that the UPDATE or DELETE statement is correct.

1.1.4.193 Cannot update primary key for table '%1' involved in a publication

Error constant	SQL_E_ARTICLE_PK_CANNOT_BE_UPDATED
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the table.

Severity	16
SQLCODE	-780
SQLSTATE	5RW19
Sybase error code	13790

Probable cause

The primary key of a table involved in a publication cannot be updated. The prevent_article_pkey_update database option can be set to Off to allow updates to the primary key of the table involved in the publication.

1.1.4.194 Cannot update the audit_log option: one or more of the specified targets is invalid

Error constant	SQL_E_CANNOT_UPDATE_AUDIT_LOG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1732
SQLSTATE	WE041
Sybase error code	12408

Probable cause

An error occurred while updating the audit_log option. Ensure that the target parameters are correct and that you have sufficient permissions to access any file target.

1.1.4.195 Cannot use both the OR REPLACE and IF NOT EXISTS clauses

Error constant	OR_REPLACE_IF_NOT_EXISTS
ODBC 2 state	08001
ODBC 3 state	08001

Severity	15
SQLCODE	-1934
SQLSTATE	42U48
Sybase error code	12243

Probable cause

You have specified both the OR REPLACE and IF NOT EXISTS clauses. These clauses cannot be used together.

1.1.4.196 Cannot use CLEAR LOG clause with offline log backups

Error constant	SQL_E_RESTORE_CLEAR_LOG_ON_OFFLINE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1909
SQLSTATE	42X16
Sybase error code	12254

Probable cause

Offline log is not backed up during a clear log restore

1.1.4.197 Cannot use materialized view '%1' because it has not yet been initialized

Error constant	SQL_E_CANNOT_USE_MATVIEW
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Name of the materialized view.
Severity	14

SQLCODE	-1077
SQLSTATE	42WBC
Sybase error code	13437

Probable cause

You attempted to use a materialized view but it has not yet been initialized. In order for a materialized view to become available for first use after being created or enabled, it must be initialized at least once using the REFRESH MATERIALIZED VIEW statement.

1.1.4.198 Cannot use view '%1' because it has been disabled

Error constant	SQLE_VIEW_DISABLED
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	The name of the view.
Severity	16
SQLCODE	-1038
SQLSTATE	55W17
Sybase error code	13473

Probable cause

You attempted to reference a view that has been disabled. The view must be enabled before it can be used again.

1.1.4.199 Cannot use view '%1' because it is invalid

Error constant	SQLE_VIEW_INVALID
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	The name of the view.
Severity	16

SQLCODE	-1040
SQLSTATE	55W18
Sybase error code	13471

Probable cause

You attempted to reference an invalid view. The view must be enabled before it can be used again.

1.1.4.200 CATALOG ONLY and MULTIPLEX cannot be used together

Error constant	SQL_E_CATALOG_ONLY_WITH_MPX_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1787
SQLSTATE	42WF1
Sybase error code	12600

Probable cause

Since MULTIPLEX option is used to restore the DAS files, CATALOG ONLY option cannot be specified.

1.1.4.201 CDATA has a name

Error constant	SQL_E_FOR_XML_EXPLICIT_NAMED_CDATA
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-903
SQLSTATE	WX011
Sybase error code	13580

Probable cause

A CDATA directive in a FOR XML EXPLICIT query must not be given a name.

1.1.4.202 Certificate '%1' not found

Error constant	SQLE_CERTIFICATE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the certificate that could not be found
Severity	16
SQLCODE	-1589
SQLSTATE	55W44
Sybase error code	12516

Probable cause

You misspelled the name of a certificate, or the certificate does not exist.

1.1.4.203 change_password_dual_control is enabled for this user. Use ALTER USER to change password

Error constant	SQLE_CHANGE_PWD_DUAL_CONTROL_ENABLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1698
SQLSTATE	28W21
Sybase error code	12437

Probable cause

You attempted to change a password while the change_password_dual_control option is set for this user. When this option is set, you must use the ALTER USER statement to change the dual password.

Related Information

[Dual Control Passwords](#)

1.1.4.204 CHAR configuration provided for NCHAR column for text index \"%1\" on table \"%2\"

Error constant	TEXT_INDEX_BAD_CONFIGURATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the text index.
Parameter 2	The name of the table.
Severity	16
SQLCODE	-1991
SQLSTATE	WT042
Sybase error code	12193

Probable cause

A text configuration object provided in the create index statement cannot be used for the columns of the text index.

1.1.4.205 Character conversion error or warning report is not available when the single-byte converter is used

Error constant	SQLC_CHARACTER_CONVERSION_REPORT_NOT_AVAILABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-883
SQLSTATE	WC007
Sybase error code	13898

Probable cause

You attempted to set the `on_charset_conversion_failure` option to produce either a warning or error report. This setting is not available when the single-byte to single-byte converter is used.

1.1.4.206 Character set conversion to '%1' cannot be performed; '%2' is used instead

Error constant	SQL_E_CANNOT_PERFORM_CHAR_TRANSLATION
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	Name of character set the application requested.
Parameter 2	Name of character set the database will be using.
Severity	10
SQLCODE	114
SQLSTATE	01W12
Sybase error code	13613

Probable cause

The server is unable to perform a character conversion from the character set the database is using to the character set the application requested.

Related Information

[Character Set Conversion](#)

1.1.4.207 Character substitution occurred when converting from %1 to %2

Error constant	SQL_E_SIMPLE_SUBSTITUTION_WARNING
ODBC 2 state	01000
ODBC 3 state	01000

Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	10
SQLCODE	127
SQLSTATE	01WC3
Sybase error code	13896

Probable cause

While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. Those characters were substituted. See `on_charset_conversion_failure` option.

Related Information

[on_charset_conversion_failure Option](#)

1.1.4.208 Character substitution was required when converting from %1 to %2

Error constant	SQL_E_SIMPLE_SUBSTITUTION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	16
SQLCODE	-881
SQLSTATE	WC005
Sybase error code	13894

Probable cause

While the server was performing character set conversion on an input string, some characters could not be represented in the database character set. The operation was aborted. See `on_charset_conversion_failure` option.

1.1.4.209 CHECKPOINT statement requires a rollback log

Error constant	SQLCHECKPOINT_REQUIRES_UNDO
ODBC 2 state	40001
ODBC 3 state	40001
Severity	16
SQLCODE	-212
SQLSTATE	42W20
Sybase error code	13653

Probable cause

You cannot use a CHECKPOINT statement when the database server is running in bulk mode without a rollback log.

1.1.4.210 Checksums are not enabled in this database

Error constant	SQLCHECKSUMS_NOT_ENABLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-971
SQLSTATE	WW042
Sybase error code	13517

Probable cause

An attempt was made to perform checksum validation but the database does not have checksums enabled.

1.1.4.211 CircularString with 3 points has been converted to use 5 points

Error constant	SQLE_SLWARN_CIRCULARSTRING_3POINT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1491
SQLSTATE	01FW2
Sybase error code	13081

Probable cause

A curve containing a CircularString with a 3-point circle has been converted to use a 5-point circle. This is a notification only.

Related Information

[ST_CircularString Type](#)

1.1.4.212 Class '%1' has no public field '%2'

Error constant	SQLE_FIELD_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the class in which the named field could not be found.
Parameter 2	The name of the field that could not be found.
Severity	16
SQLCODE	-93
SQLSTATE	WW013
Sybase error code	13703

Probable cause

An expression referenced a field that either does not exist or is not public.

1.1.4.213 Clause '%1' has invalid attribute '%2'

Error constant	SQLE_INVALID_PROCEDURE_ATTRIBUTE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The attribute value or cause of failure.
Severity	16
SQLCODE	-991
SQLSTATE	WW060
Sybase error code	13498

Probable cause

The attribute value specified on the procedure is not valid.

1.1.4.214 Client application disallowed the transfer of data ('%1')

Error constant	SQLE_CLIENT_TRANSFER_DISALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1172
SQLSTATE	WW093
Sybase error code	13341

Probable cause

The client application rejected the transfer of server initiated data. To allow transfer of server initiated data, the application registered a validation callback which rejected the transfer of requested data.

1.1.4.215 Client application does not allow transfer of data ('%1')

Error constant	SQLE_CLIENT_TRANSFER_NO_VALIDATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1171
SQLSTATE	WW092
Sybase error code	13342

Probable cause

The client application does not allow the transfer of server initiated data. To allow transfer of server initiated data, the application must register a validation callback mechanism with the client library.

1.1.4.216 Client library reported a permissions error accessing object ('%1') during transfer

Error constant	SQLE_CLIENT_TRANSFER_PERMS_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1200
SQLSTATE	WW103
Sybase error code	13315

Probable cause

The client application reported a permissions error while attempting to access the object for a data transfer request from the server. The client application likely does not have the necessary operating system authorization required to access the object.

1.1.4.217 Client library reported an error accessing data during transfer ('%1')

Error constant	SQLE_CLIENT_TRANSFER_ACCESS_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1173
SQLSTATE	WW094
Sybase error code	13340

Probable cause

The client application reported an error while attempting to access the data for a transfer request from the server. Reasons could include the client application lacking permissions to the data object or other operating system reported errors.

1.1.4.218 Client library reported an error opening object ('%1') during transfer

Error constant	SQLE_CLIENT_TRANSFER_OPEN_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the object being transferred to/from the application.
Severity	16
SQLCODE	-1201

SQLSTATE	WW102
Sybase error code	13314

Probable cause

The client application reported an error while attempting to open the object for a data transfer request from the server. Reasons could include an invalid name for the object or a missing object.

1.1.4.219 Client out of memory

Error constant	SQLE_CLIENT_OUT_OF_MEMORY
ODBC 2 state	S1001
ODBC 3 state	HY001
Severity	17
SQLCODE	-876
SQLSTATE	08W65
Sybase error code	13882

Probable cause

A failure occurred when the database client was trying to allocate memory.

1.1.4.220 Client redirected more than once

Error constant	SQLE_TOO_MANY_REDIRECTS
ODBC 2 state	08S01
ODBC 3 state	08S01
Severity	21
SQLCODE	-1380
SQLSTATE	08WA4
Sybase error code	13188

Probable cause

The connection was redirected by the primary server to another server, which also attempted to redirect the connection.

1.1.4.221 Client/database server version mismatch

Error constant	SQLE_DBLIB_ENGINE_MISMATCH
ODBC 2 state	08001
ODBC 3 state	08001
Severity	21
SQLCODE	-231
SQLSTATE	08W19
Sybase error code	13658

Probable cause

Your executable uses a database interface library that does not match the version number of the database server.

Related Information

[SQL Anywhere Server Upgrades](#)
[UltraLite Upgrades](#)

1.1.4.222 Client/server communications protocol version mismatch

Error constant	SQLE_PROTOCOL_MISMATCH
ODBC 2 state	08S01
ODBC 3 state	08S01
Severity	21
SQLCODE	-88

SQLSTATE	08W15
Sybase error code	1602

Probable cause

The connection failed because the protocol versions of the client and the server do not match. Ensure the client and server software are the same version.

1.1.4.223 Collation '%1' not supported on this platform

Error constant	SQL_E_COLLATION_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The collation that is not supported.
Severity	16
SQLCODE	-1116
SQLSTATE	WC013
Sybase error code	13398

Probable cause

The specified collation is not supported on the current platform.

1.1.4.224 Collection types not supported

Error constant	SQL_E_COLLECTION_TYPES_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1702
SQLSTATE	0AW28
Sybase error code	176

1.1.4.226 Column '%1' in foreign key has a different definition than primary key

Error constant	SQL_E_INVALID_FOREIGN_KEY_DEF
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the problematic column.
Severity	16
SQLCODE	-113
SQLSTATE	53030
Sybase error code	1721

Probable cause

The data type of the column in the foreign key is not the same as the data type of the column in the primary key. Change the definition of one of the columns using ALTER TABLE.

Related Information

[ALTER TABLE Statement](#)

[ALTER TABLE Statement \[UltraLite\]](#)

1.1.4.227 Column '%1' in table '%2' cannot be NULL

Error constant	SQL_E_COLUMN_CANNOT_BE_NULL
ODBC 2 state	23000
ODBC 3 state	23000
Parameter 1	Name of the column that cannot be NULL.
Parameter 2	Name of the table containing the column.
Severity	16
SQLCODE	-195
SQLSTATE	23502
Sybase error code	233

Probable cause

You have not supplied a value where a value is required. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

1.1.4.228 Column '%1' in table '%2' cannot be NULL. The invalid data was supplied to LOAD TABLE in a data file on line %3

Error constant	SQLE_COLUMN_CANNOT_BE_NULL_LOAD_TABLE
ODBC 2 state	23000
ODBC 3 state	23000
Parameter 1	Name of the column that cannot be NULL.
Parameter 2	Name of the table containing the column.
Parameter 3	The line number of the data file containing the invalid data.
Severity	16
SQLCODE	-184
SQLSTATE	23501
Sybase error code	13885

Probable cause

You either have not supplied a value where a value is required or a data conversion was necessary that resulted in a NULL value. The column definition prohibits NULL values or the column is part of a NOT NULL foreign key.

1.1.4.229 Column '%1' not found

Error constant	SQLE_COLUMN_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S22
Parameter 1	Name of the column that could not be found.
Severity	16
SQLCODE	-143
SQLSTATE	52003

Probable cause

You misspelled the name of a column, or the column you are looking for is in a different table.

1.1.4.230 Column '%1' not found in table '%2'

Error constant	SQLE_COLUMN_NOT_FOUND_IN_TABLE
ODBC 2 state	S0002
ODBC 3 state	42S22
Parameter 1	Name of the column that could not be found.
Parameter 2	Name of the table that was supposed to contain the column.
Severity	11
SQLCODE	-834
SQLSTATE	52005
Sybase error code	13840

Probable cause

You misspelled the name of a column, or the column you are looking for is in a different table.

1.1.4.231 Column '%1' not found in variable '%2'

Error constant	SQLE_COLUMN_NOT_FOUND_IN_VARIABLE
ODBC 2 state	S0002
ODBC 3 state	42S22
Parameter 1	Name of the column that could not be found.
Parameter 2	Name of the row variable that was supposed to contain the column.
Severity	11
SQLCODE	-1595

SQLSTATE	52006
Sybase error code	13853

Probable cause

You misspelled the name of a column or variable, or the variable has a different schema than you expect.

1.1.4.232 Column '%1' not part of any indexes in its containing table

Error constant	SQLE_COLUMN_NOT_INDEXED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the column not found in any index.
Severity	16
SQLCODE	-1101
SQLSTATE	WW073
Sybase error code	13413

Probable cause

The specified column is not part of any indexes belonging to the containing table.

1.1.4.233 Column must be named: %1

Error constant	SQLE_NO_XML_IDENTIFIER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The number of the column that must be named.
Severity	16
SQLCODE	-874
SQLSTATE	WX001

Probable cause

Unnamed columns cannot be used as XML element or attribute names. Unnamed JSON columns can only be used within the top-level SELECT where the tag and parent are defined. In this context, the unnamed column is a directive to generate a JSON value rather than a JSON object for the given column. Name unnamed columns in the SELECT list by using AS.

Related Information

[SELECT Statement](#)
[SELECT Statement](#)

1.1.4.234 Column subset for table '%1' in publication '%2' does not match that specified in publication '%3'

Error constant	SQLE_COLUMN_SUBSET_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of table
Parameter 2	Name of first publication
Parameter 3	Name of second publication
Severity	16
SQLCODE	-1325
SQLSTATE	WW138
Sybase error code	13231

Probable cause

The columns included for a table must be identical for all subscribed publications which reference the table.

1.1.4.235 Command '%1' received BACKINT_ERROR from HANA

Error constant	COMMAND_RECEIVED_BACKINT_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	hdbnsutil command which returned the error
Severity	16
SQLCODE	-1967
SQLSTATE	WB036
Sybase error code	12215

Probable cause

Error while trying to execute hdbnsutil command.

1.1.4.236 COMMIT/ROLLBACK not allowed within atomic operation

Error constant	SQLE_ATOMIC_OPERATION
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-267
SQLSTATE	42W28
Sybase error code	13640

Probable cause

You attempted a COMMIT or ROLLBACK statement while executing within an atomic operation.

1.1.4.237 COMMIT/ROLLBACK not allowed within trigger actions

Error constant	SQLE_INVALID_TRIGGER_STATEMENT
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-273
SQLSTATE	2D501
Sybase error code	102

Probable cause

You attempted to execute a statement that is not allowed while performing a trigger action. COMMIT and ROLLBACK statements cannot be executed from a trigger.

1.1.4.238 Communication error

Error constant	SQLE_COMMUNICATIONS_ERROR
ODBC 2 state	08S01
ODBC 3 state	08S01
Severity	21
SQLCODE	-85
SQLSTATE	08W12
Sybase error code	1602

Probable cause

There is a communication problem between the application and the server.

Related Information

[Communication Protocols](#)
[Troubleshooting Network Communications](#)

1.1.4.239 Composite ORDER BY not allowed with RANGE

Error constant	SQLE_ILLEGAL_COMPOSITE_ORDERBY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-966
SQLSTATE	42WAA
Sybase error code	13524

Probable cause

Window functions that use the RANGE keyword may only ORDER BY a single column.

1.1.4.240 Compression error: %1

Error constant	SQLE_COMPRESSION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Error message.
Severity	16
SQLCODE	-959
SQLSTATE	WW037
Sybase error code	13529

Probable cause

An error occurred during compression.

1.1.4.241 Computed columns are not supported in this database

Error constant	SQLE_COMPUTED_COLUMNS_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-709
SQLSTATE	0AW06
Sybase error code	13722

Probable cause

The current database is an older database and does not have catalog support for computed (materialized) columns. To use this feature, upgrade your database to the most recent version.

1.1.4.242 Configuration cannot not be modified while in use

Error constant	SQLE_CONFIG_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	42000
Severity	16
SQLCODE	-1276
SQLSTATE	55W34
Sybase error code	13863

Probable cause

You attempted to modify a configuration object that is in use by an open connection.

1.1.4.243 Conflicting INSTEAD OF trigger and WITH CHECK OPTION on view '%1'

Error constant	SQLE_CHECK_TRIGGER_CONFLICT
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the view with an INSTEAD OF trigger
Severity	15
SQLCODE	-1125
SQLSTATE	42W39
Sybase error code	13388

Probable cause

You attempted an operation that involves a WITH CHECK OPTION clause that conflicts with an INSTEAD OF trigger. A view defined with the WITH CHECK OPTION clause cannot refer to a view (possibly nested) with an INSTEAD OF trigger.

1.1.4.244 Connection attempting BACKUP has uncommitted transactions

Error constant	SQLE_BACKUP_HAS_UNCOMMITTED_TRANS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1028
SQLSTATE	WB014
Sybase error code	13482

Probable cause

A connection attempting to perform a BACKUP..WAIT BEFORE START or BACKUP..WAIT AFTER END has uncommitted transactions. A COMMIT or ROLLBACK must be performed before executing the backup.

1.1.4.245 Connection disallowed by login policy for this user

Error constant	SQLE_CONNECTION_DISALLOWED_BY_LOGIN_POLICY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1212
SQLSTATE	28W15
Sybase error code	13303

Probable cause

A connection attempt was disallowed based on the login policy for the user. It may be necessary for a user with DBA authority to reset this user via the ALTER USER statement.

1.1.4.246 Connection error: %1

Error constant	SQLE_CONNECTION_ERROR
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Description of the connection error.
Severity	16
SQLCODE	-832
SQLSTATE	08W60
Sybase error code	13838

Probable cause

An error occurred while attempting to establish a connection with the database server, but before attempting to connect to a database. Failure to initialize a communication link during the connection attempt is an example of this error. Creating a debug log file using the LogFile connection parameter may provide more information.

1.1.4.247 Connection is not allowed to have table locks when executing this statement

Error constant	SQL_E_CONNECTION_HAS_LOCKS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1324
SQLSTATE	WW142
Sybase error code	13232

Probable cause

An attempt was made to execute a statement by a connection that is holding table locks. Because the statement could release all locks, including those held before the statement started, the locks must be released before the statement can be executed.

1.1.4.248 Connection not found

Error constant	SQL_E_CONNECTION_NOT_FOUND
ODBC 2 state	08003
ODBC 3 state	08003
Severity	16
SQLCODE	-108
SQLSTATE	08W02
Sybase error code	4224

Probable cause

The specified connection name on a DISCONNECT or SET CONNECTION statement is invalid.

Related Information

[DISCONNECT Statement \[ESQL\]](#) [\[Interactive SQL\]](#)

1.1.4.249 Connection timed out

Error constant	SQL_E_REMOTE_CONNECTION_TIMED_OUT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-982
SQLSTATE	WW051
Sybase error code	13507

Probable cause

The connection to the remote host timed out due to inactivity.

1.1.4.250 Connection was terminated

Error constant	SQL_E_CONNECTION_TERMINATED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-308
SQLSTATE	40W07
Sybase error code	4224

Probable cause

Your database connection has been terminated and your transaction has been rolled back. The connection may have been terminated because a DBA executed a DROP CONNECTION statement, or because the database server was shut down, or because your network connection to the database server was interrupted.

Related Information

[DROP CONNECTION Statement](#)

[ROLLBACK Statement](#)

[ROLLBACK Statement \[UltraLite\]](#)

1.1.4.251 Connections to database have been disabled

Error constant	SQL_E_CONNECTIONS_DISABLED
ODBC 2 state	08005
ODBC 3 state	08005
Severity	16
SQLCODE	-99
SQLSTATE	08W04
Sybase error code	4224

Probable cause

Connections to the network database server have been disabled. You will receive this error until connections have been enabled.

1.1.4.252 Constant expressions must not appear in GROUP BY clause

Error constant	SQL_E_NO_CONSTANTS_IN_GROUP_BY
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-928
SQLSTATE	42W9D
Sybase error code	13557

Probable cause

You used a constant in the GROUP BY clause. Constants must not appear in the GROUP BY clause for a query. References to columns in a view that are constant are permitted in a GROUP BY clause. Also, expressions that use a view column that is constant are permitted.

1.1.4.253 Constraint '%1' not found

Error constant	SQLC.CONSTRAINT_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S23
Parameter 1	Name of the constraint that could not be found.
Severity	16
SQLCODE	-929
SQLSTATE	42U04
Sybase error code	13556

Probable cause

You misspelled the name of a constraint, or the constraint you are looking for is on a different table.

Related Information

[Table and Column Constraints](#)
[ALTER TABLE Statement](#)
[ALTER TABLE Statement \[UltraLite\]](#)

1.1.4.254 Constraint '%1' violated: Invalid value for column '%2' in table '%3'

Error constant	SQLC.INVALID_COLUMN_VALUE
ODBC 2 state	42000
ODBC 3 state	23000

Parameter 1	Name of the constraint (if defined) that was violated by an invalid value.
Parameter 2	Name of the column that was assigned an invalid value.
Parameter 3	Name of the table containing the column.
Severity	16
SQLCODE	-209
SQLSTATE	23506
Sybase error code	548

Probable cause

You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

1.1.4.255 Constraint '%1' violated: Invalid value in table '%2'

Error constant	SQL_E_TABLE_CONSTRAINT_VIOLATED
ODBC 2 state	42000
ODBC 3 state	23000
Parameter 1	Name of the constraint (if defined) that was violated by an invalid value.
Parameter 2	Name of the table containing the column.
Severity	16
SQLCODE	-1091
SQLSTATE	23508
Sybase error code	548

Probable cause

You attempted an insert or update that violates a CHECK constraint. A CHECK constraint is violated if it evaluates to FALSE; it is deemed to hold if the condition evaluates to TRUE or UNKNOWN.

1.1.4.256 Contents of backup files are inconsistent

Error constant	SQLE_RESTORE_INCONSISTENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	23
SQLCODE	-715
SQLSTATE	WB006
Sybase error code	13724

Probable cause

During a RESTORE, the contents of a backup that was done to two or more disk devices were found to be inconsistent.

1.1.4.257 Control character in XML output

Error constant	SQLE_CONTROL_CHARACTER_IN_XML_OUTPUT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-911
SQLSTATE	WX015
Sybase error code	13573

Probable cause

A non-space character less than hex 20 was encountered while generating XML content. Consider base64 encoding strings that contain control characters before using them as XML content. This can be accomplished in a FOR XML query or SQLX function by casting the string to a type such as LONG BINARY.

1.1.4.258 Coordinate bounds missing for coordinate %1

Error constant	SQLE_SLERR_DDL_SRS_MUSTBOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The coordinate name.
Severity	16
SQLCODE	-1467
SQLSTATE	2FW60
Sybase error code	13105

Probable cause

No bounds were specified for the named coordinate.

1.1.4.259 Correlation name '%1' is not valid for use with the ROWID function

Error constant	SQLE_INVALID_CORRELATION_FOR_ROWID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the invalid correlation name.
Severity	15
SQLCODE	-1113
SQLSTATE	42WBF
Sybase error code	13401

Probable cause

The correlation name used was not valid for the ROWID function. Only the correlation names of base tables, temporary tables, global temporary tables or proxy tables may be used with the ROWID function. The argument of a ROWID function should not refer to a view, derived table, common table expression, or a procedure.

1.1.4.260 Correlation name '%1' not found

Error constant	SQLE_CORRELATION_NAME_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the invalid correlation name.
Severity	16
SQLCODE	-142
SQLSTATE	52W02
Sybase error code	208

Probable cause

You misspelled a correlation name, or you used a table name instead of the correlation name.

1.1.4.261 Could not access column information for the table '%1'

Error constant	SQLE_OMNI_RMT_COLUMNS_NOTFOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The complete name of the remote table.
Severity	11
SQLCODE	-667
SQLSTATE	W0008
Sybase error code	11207

Probable cause

Column information for the table could not be accessed. Check permissions for the table.

1.1.4.262 Could not allocate resources to call external function

Error constant	SQLE_ERROR_CALLING_FUNCTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-622
SQLSTATE	WW008
Sybase error code	13679

Probable cause

The external function could not be called due to a shortage of operating system resources. If the operating system supports threads, the maximum thread count should be increased.

1.1.4.263 Could not create a new text index for this table with the same settings as "%1"

Error constant	SQLE_TEXT_INDEX_SAME_SETTING_IDX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the other text index with the same settings.
Severity	16
SQLCODE	-1304
SQLSTATE	WT021
Sybase error code	13455

Probable cause

Two text indexes with the same column list and configuration settings cannot be created for a table.

1.1.4.264 Could not create a text index with external prefilter library on column "%1"

Error constant	SQLTEXTINDEX_PREFILTER_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the column for which external prefilter library is not allowed.
Severity	16
SQLCODE	-1493
SQLSTATE	WT031
Sybase error code	13210

Probable cause

A text configuration object without external prefilter library is required if any column in the text index is not of a binary or string data type.

Related Information

[What to Specify When Creating or Altering Text Configuration Objects](#)
[CREATE TEXT CONFIGURATION Statement](#)

1.1.4.265 Could not create a text index without external prefilter library on column "%1"

Error constant	SQLTEXTINDEX_NO_PREFILTER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the column for which external prefilter library is required.
Severity	16
SQLCODE	-1492
SQLSTATE	WT030
Sybase error code	13198

Probable cause

A text configuration object with a specified external prefilter library is required to build a text index on a binary column.

Related Information

[What to Specify When Creating or Altering Text Configuration Objects](#)
[CREATE TEXT CONFIGURATION Statement](#)

1.1.4.266 Could not decompress class '%1' from JAR

Error constant	SQLE_CANNOT_DECOMPRESS_CLASS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the class file in the JAR.
Severity	16
SQLCODE	-652
SQLSTATE	WP003
Sybase error code	13742

Probable cause

The Java runtime library must be installed to extract class files from ZIP or JAR files.

1.1.4.267 Could not execute backup/restore DLL (%1) entry point

Error constant	SQLE_BACKUP_ENTRY_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the entry point that could not be found.
Severity	19

SQLCODE	-692
SQLSTATE	08W45
Sybase error code	13719

Probable cause

An attempt to locate or execute the backup/restore DLL entry point failed.

1.1.4.268 Could not execute store DLL (%1) entry point

Error constant	SQLE_STORE_ENTRY_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the store DLL where the entry point failed.
Severity	19
SQLCODE	-647
SQLSTATE	08W35
Sybase error code	13700

Probable cause

An attempt to locate or execute the store DLL entry point failed.

1.1.4.269 Could not find '%1' in dynamic library '%2'

Error constant	SQLE_COULD_NOT_FIND_FUNCTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the function that could not be found.
Parameter 2	Name of the dynamic library in which the function could not be found.
Severity	19

SQLCODE	-621
SQLSTATE	WW007
Sybase error code	13678

Probable cause

The external function could not be found in the dynamic library.

Related Information

[External Call Interface](#)
[How to Build and Deploy UltraLite C++ Applications](#)

1.1.4.270 Could not initialize the encryption DLL: '%1'

Error constant	SQLE_ENCRYPTION_INITIALIZATION_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Reason the initialization failed, if known.
Severity	19
SQLCODE	-984
SQLSTATE	WW053
Sybase error code	13505

Probable cause

An attempt to initialize the encryption DLL failed.

Related Information

[Transport Layer Security](#)
[Encryption \(ENC\) Connection Parameter](#)

1.1.4.271 Could not load dynamic library '%1'

Error constant	SQLE_COULD_NOT_LOAD_LIBRARY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the dynamic library that could not be loaded.
Severity	19
SQLCODE	-620
SQLSTATE	WW006
Sybase error code	13677

Probable cause

This error is usually caused by a failure to load a dynamic library named in an external function call.

Related Information

[External Call Interface](#)
[How to Build and Deploy UltraLite C++ Applications](#)

1.1.4.272 Could not load the backup/restore DLL "%1"

Error constant	SQLE_BACKUP_NOT_LOADED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the DLL that could not be loaded.
Severity	19
SQLCODE	-691
SQLSTATE	08W44
Sybase error code	13718

Probable cause

An attempt to load the backup/restore DLL failed.

1.1.4.273 Could not load the encryption DLL "%1"

Error constant	SQLE_MISSING_ENCRYPTION_DLL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the encryption DLL that could not be loaded.
Severity	19
SQLCODE	-976
SQLSTATE	08W70
Sybase error code	13513

Probable cause

An attempt to load the encryption DLL failed.

1.1.4.274 Could not load the store DLL "%1"

Error constant	SQLE_STORE_NOT_LOADED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the store DLL that could not be loaded.
Severity	19
SQLCODE	-646
SQLSTATE	08W34
Sybase error code	13699

Probable cause

An attempt to load the store DLL failed.

1.1.4.275 Could not refresh tracing: at least one enabled tracing level must be specified

Error constant	SQLE_NO_TRACING_LEVELS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1081
SQLSTATE	55W24
Sybase error code	13433

Probable cause

Table sa_diagnostic_tracing_level contains no rows (tracing levels) or no tracing levels are enabled.

1.1.4.276 Could not refresh tracing: failed to find object %1 on row %2

Error constant	SQLE_TRACING_OBJ_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified name of the object.
Parameter 2	The primary key of the row on which the check failed.
Severity	11
SQLCODE	-1083
SQLSTATE	WW067
Sybase error code	13431

Probable cause

You misspelled the object name, or you did not qualify the name with user (and, possibly, table) name. For example, you might have referred to table_name instead of "owner"."table_name", or you might have referred to table_name_trigger instead of "owner"."table_names"."table_name_trigger".

1.1.4.277 Could not refresh tracing: invalid tracing specification on sa_diagnostic_tracing_level row %1

Error constant	SQLE_INVALID_TRACING_SPEC
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The primary key of the row that is invalid.
Severity	16
SQLCODE	-1082
SQLSTATE	WW066
Sybase error code	13432

Probable cause

You specified an invalid combination of values for the tracing level. Some invalid combinations are: specified condition is not valid for the tracing type, or specified tracing type is not valid for the scope.

1.1.4.278 Could not refresh tracing: volatile_statistics have to be collected in order for %1 specified on row %2 to be collected

Error constant	SQLE_NO_VOLATILE_LEVEL_SPEC
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The tracing level that caused the error.
Parameter 2	The primary key of the row on which the check failed.
Severity	16
SQLCODE	-1087
SQLSTATE	WW068
Sybase error code	13427

Probable cause

Volatile statistics have to be collected in order for the non-volatile and connection statistics to be collected.

1.1.4.279 Could not start a new profiling session because the previous session is still being processed.

Error constant	PROFILER_PROCESSING_PREVIOUS_SESSION_START
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2071
SQLSTATE	WW270
Sybase error code	12116

Probable cause

Could not start a new profiling session because the previous session is still being processed. Wait for the processing to be finished or clear the profiler data to stop the processing.

1.1.4.280 Could not write the profiler data because the previous session is still being processed.

Error constant	PROFILER_PROCESSING_PREVIOUS_SESSION_WRITE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2072
SQLSTATE	WW271
Sybase error code	12115

Probable cause

Could not write the profiler data because the previous session is still being processed. Wait for the processing to be finished.

1.1.4.281 CREATE/DROP STATISTICS statement cannot refer to virtual tables

Error constant	SQLE_HISTOGRAMS_NOT_SUPPORTED_ON_OBJECT
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-858
SQLSTATE	42W67
Sybase error code	13861

Probable cause

You attempted to use CREATE/DROP STATISTICS to create/drop one or more histograms on a virtual database object, such as a view or remote table. The CREATE STATISTICS and DROP STATISTICS statements can only refer to base tables, local temporary tables, or global temporary tables in the SQL Anywhere database that you are connected to.

1.1.4.282 Creating remote tables with computed columns is not supported

Error constant	SQLE_OMNI_COMPUTED_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	12
SQLCODE	-732
SQLSTATE	W0021
Sybase error code	11205

Probable cause

Computed columns are not supported in CREATE TABLE statements that specify a remote location.

1.1.4.283 Current connection is already registered to '%1' as '%2'

Error constant	SQLE_CONN_ALREADY_REGISTERED
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the application.
Parameter 2	Registered connection label.
Severity	16
SQLCODE	-787
SQLSTATE	5RW26
Sybase error code	13797

Probable cause

You attempted to register this connection more than once.

1.1.4.284 Cursor %1 cannot be used to declare a row variable using %ROWTYPE

Error constant	SQLE_CURSOR_NOT_SUPPORTED_IN_DECLARE_ROW_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of cursor.
Severity	16
SQLCODE	-1735
SQLSTATE	WP026
Sybase error code	12402

Probable cause

Use of %ROWTYPE is not supported for the cursor. You attempted to use a cursor that cannot be used for declaring a row variable using cursor %ROWTYPE.

1.1.4.285 Cursor already open

Error constant	SQLE_CURSOR_ALREADY_OPEN
ODBC 2 state	24000
ODBC 3 state	24000
Severity	16
SQLCODE	-172
SQLSTATE	24502
Sybase error code	558

Probable cause

You attempted to OPEN a cursor that is already open.

Related Information

[Cursor Principles](#)

[OPEN Statement \[ESQL\] \[SP\]](#)

1.1.4.286 Cursor has not been declared

Error constant	SQLE_CURSOR_NOT_DECLARED
ODBC 2 state	24000
ODBC 3 state	24000
Severity	16
SQLCODE	-170
SQLSTATE	24W01
Sybase error code	557

Probable cause

You attempted to OPEN a cursor that has not been declared.

Related Information

[Cursor Principles](#)

[OPEN Statement \[ESQL\] \[SP\]](#)

[DECLARE CURSOR Statement \[ESQL\] \[SP\]](#)

1.1.4.287 Cursor is restricted to FETCH NEXT operations

Error constant	SQLE_NO_SCROLL_CURSOR
ODBC 2 state	S1106
ODBC 3 state	HY106
Severity	16
SQLCODE	-668
SQLSTATE	09W06
Sybase error code	13710

Probable cause

An illegal FETCH operation has been detected for a NO SCROLL cursor. For a forward-only cursor the only permitted FETCH operations are FETCH RELATIVE 0 and FETCH NEXT (FETCH RELATIVE 1).

1.1.4.288 Cursor not in a valid state

Error constant	SQLE_CURSOR_INVALID_STATE
ODBC 2 state	24000
ODBC 3 state	24000
Severity	16
SQLCODE	-853
SQLSTATE	24000
Sybase error code	557

Probable cause

You attempted to use a cursor that is not in a valid state for the attempted operation. For example, the cursor may have encountered an error. In UltraLite, this error occurs if you attempt to set parameters for a prepared statement while a result set (cursor) is open for the statement.

Related Information

[Cursor Usage](#)
[Prepared Statements](#)

1.1.4.289 Cursor not open

Error constant	SQLC_CURSOR_NOT_OPEN
ODBC 2 state	34000
ODBC 3 state	34000
Severity	16
SQLCODE	-180
SQLSTATE	24501
Sybase error code	559

Probable cause

You attempted to use a cursor that has not been opened.

Related Information

[Cursor Principles](#)
[OPEN Statement \[ESQL\] \[SP\]](#)

1.1.4.290 Cursor option values changed

Error constant	SQLC_CURSOR_OPTIONS_CHANGED
----------------	-----------------------------

ODBC 2 state	01S02
ODBC 3 state	01S02
Severity	10
SQLCODE	121
SQLSTATE	01S02
Sybase error code	13857

Probable cause

The database server could not support the requested cursor option values for the associated query. Similar option settings were substituted.

1.1.4.291 Curve contains nearly antipodal points %1 and %2 (near '%3')

Error constant	SQLE_SLERR_NEARLY_ANTIPODAL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The first point.
Parameter 2	The second point.
Parameter 3	The value or method where the error was detected.
Severity	16
SQLCODE	-1482
SQLSTATE	2FW77
Sybase error code	13090

Probable cause

A curve contains two points that are nearly antipodal. These define an ambiguous segment in a round-Earth spatial reference system.

Related Information

[How Flat-earth and Round-earth Representations Work](#)

1.1.4.292 Cycle in common table expression references

Error constant	SQLCODE	SQLSTATE	SQL_ERROR_MESSAGE
SQLCODE	-914	42W93	SQLCODE -914, SQLSTATE 42W93: Cycle in common table expression references
SQLSTATE	42W93		SQLCODE -914, SQLSTATE 42W93: Cycle in common table expression references
Sybase error code	13570		Sybase error code 13570: Cycle in common table expression references

Probable cause

Cycles involving multiple common table expressions are not allowed.

1.1.4.293 Cycle in computed column dependencies

Error constant	SQLCODE	SQLSTATE	SQL_ERROR_MESSAGE
SQLCODE	-1078	42WBD	SQLCODE -1078, SQLSTATE 42WBD: Cycle in computed column dependencies
SQLSTATE	42WBD		SQLCODE -1078, SQLSTATE 42WBD: Cycle in computed column dependencies
Sybase error code	13436		Sybase error code 13436: Cycle in computed column dependencies

Probable cause

The table has a cycle in the dependencies between its computed columns. Cycles are not allowed.

1.1.4.294 Data definition statements not allowed in procedures or triggers

Error constant	SQL_E_DDL_NOT_ALLOWED_IN_PROCEDURES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-623
SQLSTATE	52W21
Sybase error code	154

Probable cause

The procedure or trigger definition contains a data definition statement (such as CREATE, DROP, GRANT, REVOKE, or ALTER). These statements are not allowed within procedures or triggers.

1.1.4.295 Data modifications are not allowed in a synchronization schema change

Error constant	SQL_E_SYNC_SCHEMA_CHANGE_DISALLOWS_DML
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1342
SQLSTATE	5RW42
Sybase error code	13214

Probable cause

You attempted a data modification operation within a synchronization schema change.

1.1.4.296 Database "%1" needs recovery

Error constant	SQLE_DATABASE_NEEDS_RECOVERY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the database that needs recovery.
Severity	21
SQLCODE	-665
SQLSTATE	08W41
Sybase error code	13709

Probable cause

The database quit abnormally the last time it was used. Database recovery must be performed before proceeding.

1.1.4.297 Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/indian_cant_change_platform.html

Error constant	SQLE_DATABASE_ENDIAN_FAILURE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the database.
Severity	11
SQLCODE	-1149
SQLSTATE	08W99
Sybase error code	840

Probable cause

It was determined that the database cannot be started on the current platform because doing so could possibly cause an endian related database file corruption. It will continue to start without problems on a platform with the opposite endian. More information and instructions on how to proceed are available at:

http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/ endian_cant_change_platform.html

1.1.4.298 Database '%1' cannot be started on this platform. See http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/ endian_corruption_warning.html

Error constant	SQLE_POSSIBLE_DATABASE_CORRUPTION
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the database.
Severity	11
SQLCODE	-1147
SQLSTATE	08W98
Sybase error code	840

Probable cause

It was determined that the database may be corrupt. More information and instructions on how to proceed are available at: http://ianywhere.com/developer/product_manuals/sqlanywhere/notes/en/ endian_corruption_warning.html

1.1.4.299 Database alter failed: %1

Error constant	SQLE_DATABASE_NOT_ALTERED
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	Reason that the database was not altered.
Severity	14
SQLCODE	-1639
SQLSTATE	08WB8
Sybase error code	12468

Probable cause

Your attempt to alter a database failed.

1.1.4.300 Database backup not started

Error constant	SQLE_BACKUP_NOT_STARTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	20
SQLCODE	-241
SQLSTATE	WB002
Sybase error code	3206

Probable cause

A database backup could not be started. Either a backup is already running, or you do not have the required system privileges or authority (SYS_AUTH_BACKUP_ROLE, SYS_AUTH_DBA_ROLE, or SYS_RUN_REPLICATION_ROLE).

1.1.4.301 Database cannot be started -- %1

Error constant	SQLE_UNABLE_TO_CONNECT
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Reason that database cannot be started.
Severity	11
SQLCODE	-105
SQLSTATE	08001
Sybase error code	4001

Probable cause

The specified database cannot be started. Either it does not exist, it is not a database, it is corrupt, or it is an older, unsupported format.

1.1.4.302 Database connection limit exceeded

Error constant	SQLE_TOO_MANY_DB_CONNECTIONS
ODBC 2 state	08004
ODBC 3 state	08004
Severity	21
SQLCODE	-1777
SQLSTATE	08W77
Sybase error code	12363

Probable cause

You exceeded the number of connections allowed for this database. This limit is specified by the `max_connections` database option.

Related Information

[Connection Limits for Databases and Database Servers](#)
[max_connections Option](#)

1.1.4.303 Database contains no tables to synchronize

Error constant	SQLE_NO_TABLES_TO_SYNCHRONIZE
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	150
SQLSTATE	01W28

Probable cause

The database has no tables to synchronize. No attempt was made to contact the MobiLink server.

1.1.4.304 Database contains users with 'SYS_' prefix and '_ROLE' suffix

Error constant	SQLE_INVALID_USER_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1596
SQLSTATE	08WB3
Sybase error code	12510

Probable cause

The database to be upgraded contains users with 'SYS_' prefix and '_ROLE' suffix. Drop or migrate these users before upgrading the database.

1.1.4.305 Database creation failed: %1

Error constant	SQLE_DATABASE_NOT_CREATED
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	Reason that the database was not created.
Severity	14
SQLCODE	-645
SQLSTATE	08W33
Sybase error code	928

Probable cause

Your attempt to initialize a file for a database failed.

Related Information

[Database Creation](#)

[UltraLite Options](#)

[UltraLite Initialize Database Utility \(ulinit\)](#)

1.1.4.306 Database is active

Error constant	SQLC_DATABASE_ACTIVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-664
SQLSTATE	08W40
Sybase error code	13708

Probable cause

The attempted operation (CREATE ENCRYPTED, CREATE DECRYPTED, ALTER DATABASE) cannot be performed while the database is running. Stop the database to perform the operation.

1.1.4.307 Database mirroring options are not supported for this database

Error constant	SQLC_MIRRORING_OPTIONS_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1307

SQLSTATE	WW130
Sybase error code	13443

Probable cause

The current database does not have catalog support for database mirroring servers and options. To use this feature, upgrade your database to the most recent version.

1.1.4.308 Database name must be specified when connecting to a cloud database server

Error constant	SQLE_NO_DEFAULT_DATABASE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-1581
SQLSTATE	08WA7
Sybase error code	12524

Probable cause

When connecting to a cloud database server, a database name must be specified by the connection string. Cloud database servers do not have a default database.

1.1.4.309 Database name not unique

Error constant	SQLE_ALIAS_CLASH
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-77
SQLSTATE	08W27
Sybase error code	1801

Probable cause

The database cannot be started as its name conflicts with a previously started database.

1.1.4.310 Database name required to start server

Error constant	SQLE_DATABASE_NAME_REQUIRED
ODBC 2 state	08001
ODBC 3 state	08001
Severity	17
SQLCODE	-87
SQLSTATE	08W14
Sybase error code	840

Probable cause

You did not supply a database name. A database name is required to start a database server.

Related Information

[How to Start the Database Server
UltraLite Engine Utility \(uleng17\)](#)

1.1.4.311 Database needs to be upgraded to support the use of external libraries with text indexes

Error constant	SQLE_TEXT_EXT_UPGRADE_REQUIRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1522
SQLSTATE	WT035
Sybase error code	12582

Probable cause

The current database does not have catalog support for prefilter and term breaker external libraries. To use this feature, upgrade your database to the most recent version.

Related Information

[SQL Anywhere Server Upgrades](#)

[Text Index Concepts and Reference](#)

[Advanced: External Term Breaker and Prefilter Libraries](#)

1.1.4.312 Database option '%1' for user '%2' has an invalid setting

Error constant	SQLE_INVALID_OPTION_ON_CONNECT
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	Name of the database option that has the invalid value.
Parameter 2	Name of the user attempting to connect.
Severity	10
SQLCODE	113
SQLSTATE	01W11
Sybase error code	13688

Probable cause

Upon processing a connection request for a specific user, the server processed a database option that has an invalid setting. The server will use the default option value.

1.1.4.313 Database page size too big: %1

Error constant	SQLE_PAGE_SIZE_TOO_BIG
ODBC 2 state	08004
ODBC 3 state	08004

Parameter 1	Database name.
Severity	14
SQLCODE	-97
SQLSTATE	08W22
Sybase error code	927

Probable cause

You attempted to start a database with a page size that exceeds the maximum page size of the running server. Either restart the server and include this database name on the command line, or restart the server with the required page size.

1.1.4.314 Database page size too small: %1

Error constant	SQL_E_PAGE_SIZE_TOO_SMALL
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	Database name.
Severity	14
SQLCODE	-972
SQLSTATE	54W03
Sybase error code	13516

Probable cause

You attempted to load statistics that were too large for the current database page size. Rebuilding this database with a larger page size could prevent this error.

1.1.4.315 Database page validation failed with code: %1

Error constant	SQL_E_CORRUPT_ULTRALITE_DATABASE
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	The specific kind of corruption that was found.
Severity	23
SQLCODE	-1186
SQLSTATE	WI003
Sybase error code	13329

Probable cause

UltraLite database validation failed while validating the database pages. The code provides more specific information on the validation failure.

Related Information

[Validating an UltraLite Database](#)
[UltraLite Validate Database Utility \(ulvalid\)](#)

1.1.4.316 Database server already running

Error constant	SQL_E_ENGINE_ALREADY_RUNNING
ODBC 2 state	S1000
ODBC 3 state	HY000
Severity	18
SQLCODE	-96
SQLSTATE	08W23
Sybase error code	7950

Probable cause

The database server was not able to start because a server with the same name was already running.

Related Information

[Troubleshooting: Connections](#)

1.1.4.317 Database server cannot convert data from/to character set '%1'

Error constant	SQL_E_UNSUPPORTED_CHARACTER_SET_ERROR
ODBC 2 state	08S01
ODBC 3 state	08S01
Parameter 1	Name of the requested character set.
Severity	21
SQLCODE	-869
SQLSTATE	08W64
Sybase error code	13873

Probable cause

The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection fails.

1.1.4.318 Database server cannot convert data from/to character set '%1', conversion may not be correct

Error constant	SQL_E_UNSUPPORTED_CHARACTER_SET_WARNING
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	Name of the requested character set.
Severity	10
SQLCODE	115
SQLSTATE	01W13
Sybase error code	13614

Probable cause

The database server cannot convert character data from/to the character set requested by the application because the character set is not supported. The connection succeeds, but character conversion may not be correct for all characters.

Related Information

[Character Set Conversion](#)

1.1.4.319 Database server connection limit exceeded

Error constant	SQLLE_TOO_MANY_CONNECTIONS
ODBC 2 state	08004
ODBC 3 state	08004
Severity	21
SQLCODE	-102
SQLSTATE	08W03
Sybase error code	1601

Probable cause

You exceeded the number of computers allowed to connect to the server. If you are running the network database server, the limit is specified in your license agreement. The server may be running low on cache, and as a result it cannot accept any more database connections. The personal database server is restricted to 10 connections.

Related Information

[Editions and Licensing](#)
[Connection Limits for Databases and Database Servers](#)
[Server Licensing Utility \(dblic\)](#)
[-gm Database Server Option](#)

1.1.4.320 Database server name '%1' cannot be the same as either the primary or mirror server

Error constant	SQLE_MIRROR_SERVER_NAME_CONFLICT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The server name
Severity	16
SQLCODE	-1381
SQLSTATE	WW159
Sybase error code	13187

Probable cause

The mirror servers defined with type PRIMARY or MIRROR cannot have names that match actual server names.

Related Information

[CREATE MIRROR SERVER Statement](#)

1.1.4.321 Database server not found

Error constant	SQLE_ENGINE_NOT_RUNNING
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-100
SQLSTATE	08W01
Sybase error code	7950

Probable cause

The database server is not running, or is in the process of starting up or shutting down, or the interface library is unable to find it.

Related Information

[Troubleshooting: Connections](#)
[UltraLite Engine Utility \(uleng17\)](#)

1.1.4.322 Database server not running in multi-user mode

Error constant	SQLE_ENGINE_NOT_MULTUSER
ODBC 2 state	08001
ODBC 3 state	08001
Severity	17
SQLCODE	-89
SQLSTATE	08W16
Sybase error code	7203

Probable cause

The database server was started for bulk loading (the -b option) and cannot be used as a network server. Stop the database server, and start again without -b.

Related Information

[-b Database Server Option](#)

1.1.4.323 Database upgrade failed

Error constant	SQLE_DATABASE_UPGRADE_FAILED
ODBC 2 state	08004

ODBC 3 state	08004
Severity	20
SQLCODE	-672
SQLSTATE	08W42
Sybase error code	3451

Probable cause

Your attempt to upgrade a database failed. This could be caused by a failure to locate one of the SQL script files used to define the system table changes.

1.1.4.324 Database upgrade not possible

Error constant	SQL_E_DATABASE_UPGRADE_NOT_POSSIBLE
ODBC 2 state	08004
ODBC 3 state	08004
Severity	21
SQLCODE	-673
SQLSTATE	08W43
Sybase error code	3451

Probable cause

An attempt to upgrade a database failed. The database is too old to be upgraded.

1.1.4.325 Database upgrade not possible; database has auditing enabled

Error constant	UPGRADE_DATABASE_WITH_AUDITING
ODBC 2 state	08004
ODBC 3 state	08004
Severity	21

SQLCODE	-1987
SQLSTATE	08WC4
Sybase error code	12196

Probable cause

An attempt to upgrade a database failed. The specified database has auditing enabled. You must disable auditing before upgrading the database.

1.1.4.326 Database upgrade not possible; RowGenerator table not owned by user dbo

Error constant	SQLE_DBO_DOES_NOT_OWN_ROWGENERATOR
ODBC 2 state	08004
ODBC 3 state	08004
Severity	21
SQLCODE	-826
SQLSTATE	08W57
Sybase error code	13832

Probable cause

An attempt to upgrade a database failed. The RowGenerator table is not owned by user dbo.

1.1.4.327 Database upgrade not possible; user tables have table IDs in system table range

Error constant	SQLE_USER_TABLES_IN_SYSTEM_RANGE
ODBC 2 state	08004
ODBC 3 state	08004
Severity	21
SQLCODE	-827

SQLSTATE	08W58
Sybase error code	13833

Probable cause

An attempt to upgrade a database failed. User table IDs should not be in system table ID range.

1.1.4.328 Database upgrade not possible; user-defined database option "%1" conflicts with the system-defined database option with the same name

Error constant	SQL_E_UPGRADE_CONFLICTING_OPTION
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	Name of the conflicting option.
Severity	21
SQLCODE	-1778
SQLSTATE	08W78
Sybase error code	12362

Probable cause

An attempt to upgrade a database failed. Remove the conflicting database option before upgrading.

1.1.4.329 db_init has not been called or the call to db_init failed

Error constant	SQL_E_DB_INIT_NOT_CALLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-739

SQLSTATE	55W07
Sybase error code	13752

Probable cause

The SQLCA passed to a dblib entry point has not been initialized by a call to db_init or the call to db_init failed.

Related Information

[The SQL Communication Area \(SQLCA\)](#)
[db_init Function](#)

1.1.4.330 DBA password must be specified in the CREATE DATABASE statement

Error constant	SQLLE_NO_DBA_PASSWORD_CREATE_DB_OPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1742
SQLSTATE	42U21
Sybase error code	12395

Probable cause

You have not specified DBA PASSWORD option when executing the CREATE DATABASE statement.

1.1.4.331 DBA user ID must be specified in the CREATE DATABASE statement

Error constant	SQLLE_NO_DBA_USER_CREATE_DB_OPTION
----------------	------------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1741
SQLSTATE	42U20
Sybase error code	12396

Probable cause

You have not specified DBA USER option when executing the CREATE DATABASE statement.

1.1.4.332 DBF parameter cannot be used when the SQL Anywhere Cockpit is being prepared to save.

Error constant	COCKPITDB_CANNOT_USE_DBF_PARM_WHEN_PREPARE_SAVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1958
SQLSTATE	08WJ1
Sybase error code	12222

Probable cause

The DBF parameter cannot be used when the SQL Anywhere Cockpit is preparing to save.

1.1.4.333 DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is active

Error constant	SQLC_COCKPITDB_CANNOT_USE_DBF_PARM_WHEN_DB_ACTIVE
----------------	---

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1869
SQLSTATE	08WH4
Sybase error code	12278

Probable cause

The DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is currently active.

1.1.4.334 DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is being started

Error constant	SQL_E_COCKPITDB_CANNOT_USE_DBF_PARM_WHEN_DB_BEING_STARTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1867
SQLSTATE	08WH2
Sybase error code	12280

Probable cause

The DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is being started.

1.1.4.335 DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is starting

Error constant	SQLE_COCKPITDB_CAN- NOT_USE_DBF_PARM_WHEN_DB_STARTING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1868
SQLSTATE	08WH3
Sybase error code	12279

Probable cause

The DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is starting.

1.1.4.336 DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is stopping

Error constant	SQLE_COCKPITDB_CAN- NOT_USE_DBF_PARM_WHEN_DB_STOPPING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1870
SQLSTATE	08WH5
Sybase error code	12277

Probable cause

The DBF parameter cannot be used when the SQL Anywhere Cockpit is not stopped. The SQL Anywhere Cockpit is stopping.

1.1.4.337 dbicu libraries are required but not installed

Error constant	SQLLE_ICU_NOT_AVAILABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1076
SQLSTATE	WC012
Sybase error code	13438

Probable cause

The server is unable to load ICU components that are required by this database. Ensure that the dbicu and dbicudt DLLs are installed.

1.1.4.338 Dbspace '%1' not found

Error constant	SQLLE_DBSPACE_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the dbspace that could not be found.
Severity	11
SQLCODE	-138
SQLSTATE	52W13
Sybase error code	1802

Probable cause

You tried to access a dbspace that the database server could not find.

1.1.4.339 Dbspace for table '%1' not found

Error constant	SQLLE_DBSPACE_FOR_TABLE_UNAVAILABLE
----------------	-------------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the table whose dbspace could not be found.
Severity	11
SQLCODE	-821
SQLSTATE	52W19
Sybase error code	13827

Probable cause

You tried to access a table in a dbspace that the database server could not find. You may need to change the file name associated with the dbspace using the ALTER DBSPACE statement.

1.1.4.340 Deadlock detected

Error constant	SQLE_DEADLOCK
ODBC 2 state	40001
ODBC 3 state	40001
Severity	13
SQLCODE	-306
SQLSTATE	40001
Sybase error code	1205

Probable cause

You attempted to read or write a row and it is locked by another user. Also, the other user is blocked directly or indirectly on your own transaction. This is a deadlock situation and your transaction has been chosen as the one to rollback.

1.1.4.341 Deadlock involving a mutex detected

Error constant	SQLE_MUTEX_DEADLOCK
ODBC 2 state	40001

ODBC 3 state	40001
Severity	13
SQLCODE	-1806
SQLSTATE	40002
Sybase error code	12338

Probable cause

You were waiting to lock a mutex and it is not available. Also, the other user is blocked directly or indirectly on your transaction. This is a deadlock situation and your transaction has been chosen as the one to roll back.

1.1.4.342 Debugger error: %1

Error constant	SQLE_DEBUGGER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Description of the error that occurred.
Severity	16
SQLCODE	-1736
SQLSTATE	WW248
Sybase error code	12401

Probable cause

An error occurred during a SQL Anywhere debugger operation.

1.1.4.343 Decompression error: %1

Error constant	SQLE_DECOMPRESSION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Error message.

Severity	16
SQLCODE	-960
SQLSTATE	WW038
Sybase error code	13530

Probable cause

An error occurred during decompression.

1.1.4.344 Decryption error: %1

Error constant	SQLE_DECRYPT_ERROR
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Description of the error that occurred.
Severity	11
SQLCODE	-851
SQLSTATE	08W63
Sybase error code	13855

Probable cause

An error occurred during decryption.

1.1.4.345 Default dbspace '%1' not found

Error constant	SQLE_DEFAULT_DBSPACE_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the default dbspace that could not be found.
Severity	11
SQLCODE	-1068

SQLSTATE	52W43
Sybase error code	13446

Probable cause

You tried to create a table with the default_dbSPACE option set to a dbSPACE that could not be found.

1.1.4.346 Definition for alias '%1' must appear before its first reference

Error constant	SQL_E_ALIAS_NOT_YET_DEFINED
ODBC 2 state	37000
ODBC 3 state	ERROR
Parameter 1	Name of the alias.
Severity	15
SQLCODE	-831
SQLSTATE	42W61
Sybase error code	13837

Probable cause

An expression contains a reference to an alias, but the alias is defined later in the SELECT list. The alias definition must appear before its first reference.

Related Information

[Renamed Columns in Query Results](#)
[SELECT Statement](#)
[SELECT Statement \[UltraLite\]](#)

1.1.4.347 Definition for sequence '%1' is invalid

Error constant	SQLE_INVALID_SEQUENCE_DEFINITION
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the sequence.
Severity	16
SQLCODE	-1356
SQLSTATE	52W49
Sybase error code	13204

Probable cause

An invalid combination of modifiers has been used for the sequence. Make sure that the MAXVAL is greater than the MINVAL and that START WITH is between MINVAL and MAXVAL.

1.1.4.348 Derived table '%1' has no name for column %2

Error constant	SQLE_NO_COLUMN_NAME
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the derived table.
Parameter 2	Number of the column for which there is no name.
Severity	16
SQLCODE	-163
SQLSTATE	52004
Sybase error code	209

Probable cause

The specified column of the derived table has no column name. Use a SELECT list alias in the query specification or use a derived columns specifier.

Related Information

[The FROM Clause: Specifying Tables](#)

[SELECT Statement](#)

[SELECT Statement \[UltraLite\]](#)

1.1.4.349 Dialect '%1' is not supported by this database

Error constant	DIALECT_NOT_SUPPORTED_BY_DATABASE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the invalid dialect
Severity	16
SQLCODE	-1949
SQLSTATE	08WF6
Sybase error code	12228

Probable cause

The database you are trying to connect to does not support the specified SQL dialect.

1.1.4.350 Directory for output file does not exist

Error constant	SQL_DIRECTORY_INACCESSIBLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	20
SQLCODE	-978
SQLSTATE	WW047
Sybase error code	13511

Probable cause

The file cannot be written because the directory does not exist.

1.1.4.351 Disallowed language extension detected in syntax near '%1' on line %2

Error constant	SQLE_INVALID_SYNTAX_EXTENSION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The word or symbol where the syntax has been detected.
Parameter 2	Line number.
Severity	16
SQLCODE	-627
SQLSTATE	0AW03
Sybase error code	538

Probable cause

The statement you are trying to execute contains syntax that is not allowed with the current setting of the option `sql_flagger_error_level`. Modify the offending statement or set the `sql_flagger_error_level` option to a different value.

1.1.4.352 Disk full '%1' -- transaction rolled back

Error constant	SQLE_DEVICE_FULL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the file that could not be written to the disk.
Severity	17
SQLCODE	-304
SQLSTATE	40W03
Sybase error code	3618

Probable cause

Your hard disk is out of space. A ROLLBACK statement has been automatically executed.

1.1.4.353 Disk write failure '%1' -- transaction rolled back

Error constant	SQLE_DISK_WRITE_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the file that could not be written.
Severity	21
SQLCODE	-303
SQLSTATE	40W05
Sybase error code	13868

Probable cause

A disk write failed. A ROLLBACK statement has been automatically executed.

1.1.4.354 Division by zero

Error constant	SQLE_DIV_ZERO_ERROR
ODBC 2 state	22012
ODBC 3 state	22012
Severity	16
SQLCODE	-628
SQLSTATE	22012
Sybase error code	36007

Probable cause

A division by zero operation was detected.

Related Information

[divide_by_zero_error Option](#)

1.1.4.355 Download failed because of conflicts with existing rows on table '%1' (row: %2)

Error constant	SQLE_DOWNLOAD_CONFLICT
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the table with the conflict.
Parameter 2	The value of the primary key of the row that conflicted.
Severity	16
SQLCODE	-839
SQLSTATE	OAW11
Sybase error code	13845

Probable cause

During synchronization, there was a conflict between one or more rows in the download stream and rows modified locally in the UltraLite database. The download has been rolled back. You can avoid this error by coordinating local database modifications with synchronization, or synchronizing again when the local modifications are complete.

Related Information

[Conflict Detection](#)

[Conflict Detection and Resolution](#)

[Conflict Handling Overview](#)

[Synchronization Setup for Your UltraLite Application](#)

1.1.4.356 Download failed due to an invalid or unsupported row value

Error constant	SQLE_INVALID_DOWNLOAD_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1382

SQLSTATE	OAW26
Sybase error code	13186

Probable cause

The synchronization download failed because a downloaded row contained a column value that was either invalid or not supported.

Related Information

[Failed Downloads](#)

1.1.4.357 Dropping all columns from table '%1' is not allowed

Error constant	SQLLE_TOO_MANY_COLUMNS_DELETED
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the table from which the columns could not be dropped.
Severity	16
SQLCODE	-124
SQLSTATE	42W44
Sybase error code	207

Probable cause

The number of columns in a table can never fall below one. Your ALTER TABLE has more drop/delete column clauses than the current number of columns in the table.

1.1.4.358 Dropping or altering arbiter "%1" requires a connection to the partner

Error constant	SQLE_MIRROR_DROP_ARBITER_REQUIRES_PARTNER_CONN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the arbiter server.
Severity	16
SQLCODE	-1632
SQLSTATE	WW242
Sybase error code	12474

Probable cause

An attempt was made to drop or alter an arbiter that is not connected to the partner server.

Related Information

[Arbiter Server](#)

[ALTER MIRROR SERVER Statement](#)

[DROP MIRROR SERVER Statement](#)

1.1.4.359 DTC transactions are not supported on this platform

Error constant	SQLE_DTC_TRANSACTIONS_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-799
SQLSTATE	0AW10
Sybase error code	13809

Probable cause

You tried to enlist a DTC transaction on a platform that does not support this feature.

1.1.4.360 Duplicate attribute '%1' in service

Error constant	SQLE_SERVICE_PARM_DUPLICATE_PROPERTY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the duplicate attribute.
Severity	16
SQLCODE	-1025
SQLSTATE	42WB0
Sybase error code	13485

Probable cause

The service definition contains a duplicate attribute.

1.1.4.361 Duplicate insert column

Error constant	SQLE_DUPLICATE_INSERT_COLUMN
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-637
SQLSTATE	42W41
Sybase error code	264

Probable cause

You supplied a duplicate column name in the list of insert columns.

1.1.4.362 Duplicate key column (%1)

Error constant	SQLCODE
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The name of the duplicate column.
Severity	16
SQLCODE	-1085
SQLSTATE	42WC0
Sybase error code	13429

Probable cause

You supplied a duplicate column name in the list of columns for the key of a primary key, foreign key, or unique constraint, or an index.

1.1.4.363 Duplicate options not allowed in %1!s!

Error constant	DUPLICATE_CLAUSE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	A string indicating the statement used.
Severity	15
SQLCODE	-1933
SQLSTATE	42U47
Sybase error code	12244

Probable cause

You have specified an option more than once when executing the given SQL statement.

1.1.4.364 Duplicate options not allowed in the CREATE DATABASE statement

Error constant	SQL_E_DUPLICATE_CREATE_DB_OPTION
ODBC 2 state	S0002
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1221
SQLSTATE	42U08
Sybase error code	13296

Probable cause

You have specified one of the options more than once when executing CREATE DATABASE.

1.1.4.365 Duplicate referencing column

Error constant	SQL_E_DUPLICATE_REFERENCING_COLUMN
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-636
SQLSTATE	42W40
Sybase error code	1909

Probable cause

You supplied a duplicate column name in the list of referencing columns.

1.1.4.366 Dynamic memory exhausted during %1

Error constant	SQL_E_DYNAMIC_MEMORY_EXHAUSTED
----------------	--------------------------------

ODBC 2 state	S1001
ODBC 3 state	HY001
Parameter 1	Description of what the server was doing when the error occurred
Severity	17
SQLCODE	-78
SQLSTATE	08W26
Sybase error code	9119

Probable cause

A failure occurred when the database server was trying to allocate dynamic memory.

Related Information

[-ca Database Server Option](#)

1.1.4.367 Element is an empty set (near '%1')

Error constant	SQLE_SLERR_ELEMENT_IS_EMPTY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value or method where the empty geometry has been detected.
Severity	16
SQLCODE	-1401
SQLSTATE	2FF06
Sybase error code	13171

Probable cause

An element of a geometry is the empty set. Empty geometries cannot be used as the points in linestrings or circularstrings; empty curves cannot be used as elements of compoundcurves; empty curves cannot be used as rings of polygons.

1.1.4.368 Ellipsoid parameters missing for geographic spatial reference system

Error constant	SQLI_SLERR_DDL_SRS_NOELLIPSOID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1465
SQLSTATE	2FW58
Sybase error code	13107

Probable cause

When creating a geographic spatial reference system, the ellipsoid parameters must be specified, either in the DEFINITION clause or explicitly. These parameters are used to calculate the distance between points.

1.1.4.369 Ellipsoid parameters specified for non-geographic spatial reference system

Error constant	SQLI_SLERR_DDL_SRS_ELLIPSOID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1466
SQLSTATE	2FW59
Sybase error code	13106

Probable cause

The ELLIPSOID parameters can only be specified for geographic spatial reference systems.

1.1.4.370 Encryption error: %1

Error constant	SQLE_ENCRYPT_ERROR
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Description of the error that occurred.
Severity	11
SQLCODE	-895
SQLSTATE	08W66
Sybase error code	13589

Probable cause

An error occurred during encryption.

1.1.4.371 Encryption failed for the SQL Anywhere Cockpit setting file. Error message '%1'

Error constant	SQLE_COCKPITDB_SETTING_FILE_CIPHER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The error message reported by block encrypter.
Severity	16
SQLCODE	-1877
SQLSTATE	WW255
Sybase error code	12273

Probable cause

Run-time block encrypter initialization failed.

1.1.4.372 Encryption has not been enabled

Error constant	SQLE_ENCRYPTION_NOT_ENABLED_WARNING
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	140
SQLSTATE	01005
Sybase error code	13369

Probable cause

An encryption key was provided, but encryption has not been enabled, nor is the database encrypted.

Related Information

[Cache Size Adjustment for an UltraLite Database](#)
[Data Encryption with UltraLite Embedded SQL](#)

1.1.4.373 Encryption has not been enabled

Error constant	SQLE_ENCRYPTION_NOT_ENABLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1143
SQLSTATE	55W27
Sybase error code	13370

Probable cause

You attempted to use encryption without first enabling it. Call `ULEnableAesDBEncryption` or `ULEnableAesFipsDBEncryption` to enable encryption.

Related Information

[Cache Size Adjustment for an UltraLite Database](#)

1.1.4.374 Error at offset '%1': expected JSON name/value pair

Error constant	SQLE_PARSE_JSON_EXPECTED_PAIR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The offset where the error occurred.
Severity	16
SQLCODE	-1678
SQLSTATE	WX022
Sybase error code	12445

Probable cause

A name/value pair was expected within the JSON object.

Related Information

[Use of the FOR JSON Clause to Retrieve Query Results as JSON](#)
[sp_parse_json System Procedure](#)

1.1.4.375 Error at offset '%1': expected token '%2'

Error constant	SQLE_PARSE_JSON_EXPECTED_TOKEN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The offset where the error occurred.
Parameter 2	The token that was expected.
Severity	16

SQLCODE	-1677
SQLSTATE	WX021
Sybase error code	12446

Probable cause

The expected token was missing in the JSON data.

Related Information

[Use of the FOR JSON Clause to Retrieve Query Results as JSON](#)
[sp_parse_json System Procedure](#)

1.1.4.376 Error at offset '%1': invalid data

Error constant	SQLE_PARSE_JSON_INVALID_DATA
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The offset where the error occurred.
Severity	16
SQLCODE	-1676
SQLSTATE	WX020
Sybase error code	12447

Probable cause

A JSON object or array contains invalid data.

Related Information

[Use of the FOR JSON Clause to Retrieve Query Results as JSON](#)
[sp_parse_json System Procedure](#)

1.1.4.377 Error at offset '%1': mismatched object or array terminator

Error constant	SQLE_PARSE_JSON_MISMATCH_TERMINATOR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The offset where the error occurred.
Severity	16
SQLCODE	-1679
SQLSTATE	WX023
Sybase error code	12444

Probable cause

Encountered a mismatched terminator for a JSON object or array.

Related Information

[Use of the FOR JSON Clause to Retrieve Query Results as JSON](#)
[sp_parse_json System Procedure](#)

1.1.4.378 Error at offset '%1': unexpected token '%2'

Error constant	SQLE_PARSE_JSON_UNEXPECTED_TOKEN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The offset where the error occurred.
Parameter 2	The unexpected token.
Severity	16
SQLCODE	-1674
SQLSTATE	WX018
Sybase error code	12449

Probable cause

An unexpected token such as a comma, bracket, or brace was encountered.

Related Information

[Use of the FOR JSON Clause to Retrieve Query Results as JSON
sp_parse_json System Procedure](#)

1.1.4.379 Error at offset '%1': unexpected trailing text

Error constant	SQLE_PARSE_JSON_UNEXPECTED_TEXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The offset where the error occurred.
Severity	16
SQLCODE	-1675
SQLSTATE	WX019
Sybase error code	12448

Probable cause

Trailing text was encountered after parsing the JSON data.

Related Information

[Use of the FOR JSON Clause to Retrieve Query Results as JSON
sp_parse_json System Procedure](#)

1.1.4.380 Error backing up existing log area. Found '%1' logs in '%2' directory

Error constant	RESTORE_NO_OFFLINE_TRANSLOG_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The number of valid transaction log files found.
Parameter 2	The directory where the logs were searched.
Severity	16
SQLCODE	-1928
SQLSTATE	WB034
Sybase error code	12247

Probable cause

No transaction log was found during the backup of the existing log area.

1.1.4.381 Error creating text index "%1" on table "%2"

Error constant	SQLTEXT_INDEX_CREATION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the text index.
Parameter 2	The name of the table.
Severity	16
SQLCODE	-1165
SQLSTATE	WT010
Sybase error code	13348

Probable cause

There was an internal error creating a text index.

1.1.4.382 Error during backup/restore: %1

Error constant	SQLE_BACKUP_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	A message describing the error that occurred.
Severity	21
SQLCODE	-697
SQLSTATE	08W46
Sybase error code	13720

Probable cause

An error occurred during a BACKUP or RESTORE statement.

1.1.4.383 Error executing BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_STMT_EXECUTE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1944
SQLSTATE	WI012
Sybase error code	12233

Probable cause

The database server was unable to execute BEGIN PARALLEL WORK...END PARALLEL WORK statement. This is a SQL Anywhere internal error. If this error can be reproduced, report it to SAP.

1.1.4.384 Error from external library: -%1: %2

Error constant	SQLE_TEXT_USER_SPECIFIED_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Error number specified by the external library
Parameter 2	Error message specified by the external library
Severity	16
SQLCODE	-1504
SQLSTATE	WT032
Sybase error code	13156

Probable cause

The external library used by the text index has reported the specified error.

Related Information

[Text Index Concepts and Reference](#)
[Database Options That Impact Text Configuration Objects](#)
[CREATE TEXT INDEX Statement](#)

1.1.4.385 Error in assignment

Error constant	SQLE_ERROR_IN_ASSIGNMENT
ODBC 2 state	22005
ODBC 3 state	22018
Severity	20
SQLCODE	-641
SQLSTATE	22005
Sybase error code	8205

Probable cause

In a GET DESCRIPTOR statement, the data type of the host variable must correspond to the data type of the descriptor item.

Related Information

[GET DESCRIPTOR Statement \[ESQL\]](#)

1.1.4.386 Error in parsing BACKINT configuration file

Error constant	SQL_E_BACKUP_BKINT_CONF_FILE_PARSE_ERR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1922
SQLSTATE	WB032
Sybase error code	12268

Probable cause

Error in parsing pipelInfoFile

1.1.4.387 Error initializing external prefilter

Error constant	SQL_E_ERROR_INITIALIZING_EXT_PREFILTER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1396
SQLSTATE	WT027
Sybase error code	13178

Probable cause

The external prefilter could not be initialized because of an internal error.

1.1.4.388 Error initializing external term breaker

Error constant	SQLE_ERROR_INITIALIZING_EXT_TERMBREAKER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1393
SQLSTATE	WT028
Sybase error code	13177

Probable cause

The external term breaker could not be initialized because of an internal error.

1.1.4.389 Error modifying refresh type for text index "%1" on materialized view "%2"

Error constant	SQLE_TEXT_INDEX_MV_ALTER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the text index.
Parameter 2	The name of the materialized view.
Severity	16
SQLCODE	-1586
SQLSTATE	WT039
Sybase error code	12519

Probable cause

Internal error encountered while changing the refresh type of the text index dependent on the materialized view.

1.1.4.390 Error number %1 for RAISERROR must not be less than 17000

Error constant	SQLE_ERROR_NUMBER_OUT_OF_RANGE
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Error number.
Severity	16
SQLCODE	-296
SQLSTATE	53W07
Sybase error code	2732

Probable cause

You supplied an invalid error number in a RAISERROR statement. The number must be greater than or equal to 17000.

1.1.4.391 Error opening cursor

Error constant	SQLE_OPEN_CURSOR_ERROR
ODBC 2 state	24000
ODBC 3 state	24000
Severity	15
SQLCODE	-171
SQLSTATE	07003
Sybase error code	102

Probable cause

You attempted to open a cursor on a statement that is not SELECT, CALL or EXEC.

1.1.4.392 Error parsing connection parameter string

Error constant	SQLE_GEN_PARSE_ERROR
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-655
SQLSTATE	08W38
Sybase error code	13707

Probable cause

The connection string could not be parsed. The string or connection parameter file contains a syntax error.

1.1.4.393 Error parsing definition string '%1'

Error constant	SQLE_SLERR_DDL_SRS_BADWKT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Coordinate system name
Severity	16
SQLCODE	-1463
SQLSTATE	2FW56
Sybase error code	13109

Probable cause

The provided definition string is not a valid well known text of the coordinate system.

1.1.4.394 Error parsing geometry internal serialization at offset %1

Error constant	SQLE_SLERR_SERIAL_PARSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The byte offset within the internal serialization.
Severity	16
SQLCODE	-1415
SQLSTATE	2FW06
Sybase error code	13157

Probable cause

There was an error parsing the internal serialization string.

1.1.4.395 Error parsing shapefile attributes

Error constant	SQLE_SLERR_SHAPE_PARSE_ATTRIBUTES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1423
SQLSTATE	2FW14
Sybase error code	13149

Probable cause

The shapefile contains invalid attributes.

1.1.4.396 Error parsing shapefile record

Error constant	SQLE_SLERR_SHAPE_PARSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1422
SQLSTATE	2FW13
Sybase error code	13150

Probable cause

The shapefile contains an invalid record.

1.1.4.397 Error parsing well-known-binary (WKB) at offset %1

Error constant	SQLE_SLERR_WKB_PARSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The byte offset within the binary string where the error was detected.
Severity	16
SQLCODE	-1407
SQLSTATE	2FF23
Sybase error code	13165

Probable cause

An error was detected while parsing the well-known binary of a geometry.

1.1.4.398 Error parsing well-known-binary (WKB): inconsistent dimensions at offset %1

Error constant	SQLE_SLERR_WKB_PARSE_INCONSISTENT_ZM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The byte offset within the binary string where the error was detected.
Severity	16
SQLCODE	-1420
SQLSTATE	2FW11
Sybase error code	13152

Probable cause

The well-known binary string contains geometries with different numbers of coordinate dimensions. For example, it could contain a point with a Z value and another without a Z value.

1.1.4.399 Error parsing well-known-binary (WKB): invalid byte order mark %1 at offset %2

Error constant	SQLE_SLERR_WKB_PARSE_INVALID_BOM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value of the byte-order mark.
Parameter 2	The byte offset within the binary string where the error was detected.
Severity	16
SQLCODE	-1421
SQLSTATE	2FW12
Sybase error code	13151

Probable cause

The well-known binary string has an invalid byte order mark. This could happen if a binary string that is not in the well-known binary format is used.

1.1.4.400 Error parsing well-known-binary (WKB): type code %1 at offset %2 is invalid

Error constant	SQLE_SLERR_WKB_PARSE_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unsupported type code value.
Parameter 2	The byte offset within the binary string where the error was detected.
Severity	16
SQLCODE	-1417
SQLSTATE	2FW08
Sybase error code	13155

Probable cause

The well-known binary string contains a type code that is not supported.

1.1.4.401 Error parsing well-known-binary (WKB): type code %1 at offset %2 is not a valid subtype of the parent

Error constant	SQLE_SLERR_WKB_PARSE_TYPE_NOT_PERMITTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unsupported type code value.
Parameter 2	The byte offset within the binary string where the error was detected.
Severity	16
SQLCODE	-1418
SQLSTATE	2FW09
Sybase error code	13154

Probable cause

The well-known binary string contains a child geometry within a parent geometry and the child is not one of the types allowed by the parent.

1.1.4.402 Error parsing well-known-binary (WKB): unexpected end of input

Error constant	SQLE_SLERR_WKB_PARSE_UNEXPECTED_EOF
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1419
SQLSTATE	2FW10
Sybase error code	13153

Probable cause

A well-known binary string was shorter than expected.

1.1.4.403 Error parsing well-known-text (WKT) scanning '%1' at offset %2

Error constant	SQLE_SLERR_WKT_PARSE_NEAR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The text where the problem was detected.
Parameter 2	The offset within the input string where the problem was detected.
Severity	16
SQLCODE	-1406
SQLSTATE	2FF22
Sybase error code	13166

Probable cause

An error was detected while parsing the well-known text of a geometry.

1.1.4.404 Error parsing well-known-text (WKT): inconsistent dimensions at offset %1

Error constant	SQLE_SLERR_WKT_PARSE_INCONSISTENT_ZM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The offset within the well-known text string where the error was detected.
Severity	16
SQLCODE	-1414
SQLSTATE	2FW05
Sybase error code	13158

Probable cause

There was a mixture of coordinate dimensions detected at the specified offset. For example, one geometry in a collection might have a Z value while another doesn't.

1.1.4.405 Error processing SAP HANA strategy

Error constant	SQLE_RESTORE_INCORRECT_STRATEGY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1907
SQLSTATE	WB020
Sybase error code	12252

Probable cause

Error in SAP HANA strategy file provided during restore.

1.1.4.406 Error reading configuration file

Error constant	SQLE_SLERR_CONFIG_FILE_ERR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1438
SQLSTATE	2FW31
Sybase error code	13134

Probable cause

An error occurred while reading a configuration file for spatial support. This error can occur if the "st_geometry_config.tgz" file is not installed.

1.1.4.407 Error writing to transaction log file

Error constant	SQLE_ERROR_WRITING_LOG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	17
SQLCODE	-107
SQLSTATE	08W17
Sybase error code	3619

Probable cause

The database server got an I/O error writing the transaction log file. The disk may be full or the log file name could be invalid.

1.1.4.408 Escape character conflict '%1'

Error constant	SQLE_ESCAPE_CHARACTER_CONFLICT
ODBC 2 state	S1000
ODBC 3 state	2200B
Parameter 1	The escape character that is invalid.
Severity	16
SQLCODE	-1137
SQLSTATE	2200B
Sybase error code	13376

Probable cause

The specified escape character cannot be used.

1.1.4.409 Event '%1' already exists

Error constant	SQLE_EVENT_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the event that already exists.
Severity	16
SQLCODE	-772
SQLSTATE	WE002
Sybase error code	13782

Probable cause

You have attempted to create an event with a name that already exists in the database.

1.1.4.410 Event '%1' in use

Error constant	SQLE_EVENT_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the event that is in use.
Severity	16
SQLCODE	-835
SQLSTATE	WE009
Sybase error code	13841

Probable cause

You have attempted to drop an event that is currently in use.

1.1.4.411 Event '%1' not found

Error constant	SQLE_EVENT_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the event that could not be found.
Severity	11
SQLCODE	-771
SQLSTATE	WE001
Sybase error code	13781

Probable cause

You have attempted to reference an event with a name that does not exist in the database.

Related Information

[Events](#)

1.1.4.412 Event notification queue '%1' is full, notification discarded

Error constant	SQLE_EVENT_NOTIFICATION_QUEUE_FULL
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The name of the event notification queue.
Severity	10
SQLCODE	146
SQLSTATE	WE011
Sybase error code	13785

Probable cause

The named queue is full and will not receive any event notifications until notifications are read from the queue. The pending notification has been discarded.

Related Information

[UltraLite Event Notifications](#)

1.1.4.413 Event notification queue '%1' not found

Error constant	SQLE_EVENT_NOTIFICATION_QUEUE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the event notification queue
Severity	11
SQLCODE	-1263
SQLSTATE	WE014
Sybase error code	13247

Probable cause

The named event notification queue was not found. The operation failed.

Related Information

[UltraLite Event Notifications](#)

1.1.4.414 Event notification queue '%1' not found warning

Error constant	SQL_E_EVENT_NOTIFICATION_QUEUE_NOT_FOUND_WARN
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The name of the event notification queue.
Severity	10
SQLCODE	148
SQLSTATE	WE013
Sybase error code	13248

Probable cause

The named event notification queue was not found. The operation will be skipped.

Related Information

[UltraLite Event Notifications](#)

1.1.4.415 Event notifications lost on queue '%1'

Error constant	SQL_E_EVENT_NOTIFICATIONS_LOST
ODBC 2 state	OK
ODBC 3 state	OK

Parameter 1	The name of the event notification queue.
Severity	10
SQLCODE	147
SQLSTATE	WE012
Sybase error code	13249

Probable cause

Event notifications have been lost on the named queue. This behavior occurs if there are pending notifications when the queue is destroyed. The notifications are discarded.

Related Information

[UltraLite Event Notifications](#)

1.1.4.416 Event object name '%1' is not valid

Error constant	SQLE_INVALID_EVENT_OBJECT_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the event object
Severity	16
SQLCODE	-1264
SQLSTATE	WE015
Sybase error code	13246

Probable cause

The given name is not valid for an event object (notification queue or user event). Names are limited in length to 32 characters (bytes), and cannot contain certain characters such as '*' or '@'.

Related Information

[UltraLite Event Notifications](#)

1.1.4.417 Event object named '%1' already exists

Error constant	SQLE_EVENT_OBJECT_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the event object
Severity	16
SQLCODE	-1265
SQLSTATE	WE016
Sybase error code	13245

Probable cause

An event object (notification queue or user event) with the given name already exists.

Related Information

[UltraLite Event Notifications](#)

1.1.4.418 Event parameter '%1' not found

Error constant	SQLE_EVENT_PARAMETER_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the event parameter
Severity	11
SQLCODE	-1267
SQLSTATE	WE018
Sybase error code	13243

Probable cause

The named event parameter was not found in the event notification.

Related Information

[UltraLite Event Notifications](#)

1.1.4.419 Exceeded maximum of '%1' allowable parameters

Error constant	SQLE_INVALID_MAXIMUM_PARAMETERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The maximum number of allowable parameters
Severity	16
SQLCODE	-1122
SQLSTATE	WW084
Sybase error code	13391

Probable cause

The maximum allowable parameters for the given web client procedure or function has been exceeded.

1.1.4.420 Expression has unsupported data type

Error constant	SQLE_DATATYPE_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	14
SQLCODE	-624
SQLSTATE	WW009
Sybase error code	10356

Probable cause

Either an external function or Java method was declared with a parameter or result data type that is not supported, or a Java field reference with an unsupported result type was attempted.

Related Information

[SQL Data Types](#)
[SQL Data Types](#)

1.1.4.421 Expression is not an array

Error constant	SQLE_NOT_AN_ARRAY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1666
SQLSTATE	42X07
Sybase error code	12457

Probable cause

You either tried to apply an ARRAY dereference (using double square brackets) to an expression that does not evaluate to an array, or else you tried to pass a non-ARRAY expression to UNNEST.

Related Information

[ROW and ARRAY Composite Data Types](#)
[ARRAY Constructor \[Composite\]](#)

1.1.4.422 Expression of type %1 is not allowed in this context (near: %2)

Error constant	SQLE_EXPR_TYPE_NOT_ALLOWED_IN_THIS_CONTEXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The disallowed expression type
Parameter 2	The context in which that type is disallowed
Severity	16
SQLCODE	-1795
SQLSTATE	42X12
Sybase error code	12348

Probable cause

You tried to use an expression in a context that does not permit expressions of that type.

1.1.4.423 External environment '%1' could not be found

Error constant	SQLE_EXTERN_ENV_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the external environment.
Severity	11
SQLCODE	-1205
SQLSTATE	WJ030
Sybase error code	13310

Probable cause

You attempted to define an object for an external environment that has not been added.

1.1.4.424 External environment cannot be started during database startup

Error constant	SQLE_EXTENV_START_ON_STARTUP
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1557
SQLSTATE	WP018
Sybase error code	12548

Probable cause

An external environment cannot be started while a database is starting up. Wait for the database startup to complete before attempting to start an external environment.

Related Information

[External Environment Support](#)
[START EXTERNAL ENVIRONMENT Statement](#)

1.1.4.425 External environment cannot be started, external process terminated on start up

Error constant	SQLE_EXTENV_PID_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1567
SQLSTATE	WP019
Sybase error code	12538

Probable cause

The request to start an external environment could not be completed due to the fact that the external process terminated on start up. This problem is usually due to a client configuration issue.

Related Information

[External Environment Support](#)
[START EXTERNAL ENVIRONMENT Statement](#)

1.1.4.426 External environment could not be started, '%1' could not be found

Error constant	SQLLE_EXTENV_NOT_STARTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The component (executable or file) that could not be found and is needed to run the VM.
Severity	16
SQLCODE	-675
SQLSTATE	WP006
Sybase error code	13747

Probable cause

A problem was encountered starting the External Environment. A component that is needed to run the environment could not be found.

1.1.4.427 External environment does not support result sets

Error constant	SQLLE_EXTERN_ENV_NO_RESULT_SET_SUPPORT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11

SQLCODE	-1213
SQLSTATE	WJ031
Sybase error code	13301

Probable cause

You attempted to define dynamic result sets for an external environment that does not support result sets.

1.1.4.428 External environment failed to start and establish a connection within the %1 second timeout

Error constant	SQLE_EXTENV_START_TIMED_OUT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The amount of time in seconds the server will wait for the external environment to start and establish a connection.
Severity	16
SQLCODE	-1556
SQLSTATE	WPO17
Sybase error code	12549

Probable cause

The External Environment took too long to start up and establish a connection with the server. The problem may be due to the system being over stressed or incorrectly configured.

Related Information

[External Environment Support](#)
[START EXTERNAL ENVIRONMENT Statement](#)

1.1.4.429 External environments are not supported for this database

Error constant	SQLE_EXTERN_ENV_UPGRADE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1206
SQLSTATE	WW104
Sybase error code	13309

Probable cause

The current database does not have catalog support for external environments. To use this feature, upgrade your database to the most recent version.

1.1.4.430 External library '%1' is in use

Error constant	SQLE_EXTERNAL_LIBRARY_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The external library that is in use
Severity	16
SQLCODE	-1214
SQLSTATE	WW108
Sybase error code	13897

Probable cause

The external library cannot be unloaded as it is currently in use.

1.1.4.431 External library '%1' not loaded

Error constant	SQLE_EXTERNAL_LIBRARY_NOT_LOADED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The external library that is not loaded
Severity	16
SQLCODE	-1215
SQLSTATE	WW109
Sybase error code	13895

Probable cause

The external library cannot be unloaded as it is not current loaded.

1.1.4.432 External login for server '%1' could not be found

Error constant	SQLE_OMNI_EXTLOGIN_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the remote server.
Severity	11
SQLCODE	-712
SQLSTATE	W0013
Sybase error code	11221

Probable cause

An external login for the server and user does not exist.

1.1.4.433 External object '%1' not found

Error constant	SQLE_EXTENV_OBJECT_NOT_FOUND
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the Java class or external object.
Severity	16
SQLCODE	-810
SQLSTATE	42W57
Sybase error code	13820

Probable cause

The Java class or external object with this name does not exist in the database.

1.1.4.434 External procedures or functions are not allowed across server types

Error constant	SQLE_PROC_NOT_ALLOWED_ACROSS_SERVERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1579
SQLSTATE	W0031
Sybase error code	12526

Probable cause

External procedure or function calls are not allowed across server types if the query is not processed in full-passthrough mode.

1.1.4.435 Fail to compare %1 and %2

Error constant	SQLE_FILE_COMPARE_FAIL
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The source file or directory name that fails to compare
Parameter 2	The target file or directory name that fails to compare
Severity	16
SQLCODE	-1660
SQLSTATE	08WC1
Sybase error code	12462

Probable cause

Failed to compare files or directories.

1.1.4.436 Failed to access the SQL Anywhere Cockpit file '%1': %2

Error constant	SQLE_COCKPITDB_FAILED_TO_ACCESS_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the file to be accessed
Parameter 2	Reason the file could not be accessed, if known.
Severity	16
SQLCODE	-1863
SQLSTATE	WW251
Sybase error code	12284

Probable cause

The request to access the SQL Anywhere Cockpit file failed.

1.1.4.437 Failed to close pipe %1 during BACKUP using BACKINT %2

Error constant	SQLE_BACKUP_BKINT_ERROR_CLOSING_PIPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the pipe on which close failed
Parameter 2	OS error thrown during the read operation
Severity	16
SQLCODE	-1913
SQLSTATE	WB023
Sybase error code	12259

Probable cause

Error occurred while closing pipe during backup using BACKINT

1.1.4.438 Failed to connect to the dbmlsync server

Error constant	SQLE_SYNCCMD_CONNECT_SERVER_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1376
SQLSTATE	5RW46
Sybase error code	13192

Probable cause

The database server failed to make a connection to the dbmlsync server.

1.1.4.439 Failed to connect to the dbmlsync server. Check the dbmlsync log file for more details

Error constant	SQLE_MLA_SYNC_CONNECT_SERVER_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1386
SQLSTATE	WW162
Sybase error code	13182

Probable cause

The MobiLink agent adapter failed to make a connection to the dbmlsync server. Check the dbmlsync log file for more details.

1.1.4.440 Failed to convert from character set '%1' to '%2'

Error constant	SQLE_FAILED_TO_CONVERT_CHARSET
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The character set of the input string.
Parameter 2	The character set of the output string.
Severity	16
SQLCODE	-1075
SQLSTATE	WC011
Sybase error code	13439

Probable cause

The server failed to convert between the two specified character sets. This could happen when the dbicu and dbicudt DLLs are not installed.

1.1.4.441 Failed to copy the SQL Anywhere Cockpit template file '%1' to destination '%2'

Error constant	SQLE_FAILED_TO_COPY_SQLACOCKPITDB_TEMPLATE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the SQL Anywhere Cockpit template
Parameter 2	The file name of the destination
Severity	16
SQLCODE	-1859
SQLSTATE	08WG1
Sybase error code	12288

Probable cause

The SQL Anywhere Cockpit template file could not be copied to the requested destination.

1.1.4.442 Failed to create pipe %1 during BACKUP using BACKINT %2

Error constant	SQLE_BACKUP_BKINT_ERROR_CREATING_PIPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the pipe on which create failed
Parameter 2	OS error thrown during the read operation
Severity	16
SQLCODE	-1911
SQLSTATE	WB021
Sybase error code	12257

Probable cause

Error occurred while creating pipe during backup using BACKINT

1.1.4.443 Failed to delete the SQL Anywhere Cockpit file '%1': %2

Error constant	SQL_E_COCKPITDB_FAILED_TO_DELETE_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the file to be deleted
Parameter 2	Reason the file could not be deleted, if known.
Severity	16
SQLCODE	-1861
SQLSTATE	WW250
Sybase error code	12286

Probable cause

The request to delete the SQL Anywhere Cockpit file failed.

1.1.4.444 Failed to get BACKUP id for file name %1

Error constant	SQL_E_BACKUP_BKINT_NO_EBID_FOR_FILENAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	error thrown during the read operation
Severity	16
SQLCODE	-1921
SQLSTATE	WB031
Sybase error code	12267

Probable cause

EBID does not exist for the given file name.

1.1.4.445 Failed to get file system statistics for the path '%1'

Error constant	SQLE_FAILED_TO_GET_FILE_SYSTEM_STATISTICS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The path that the file system statistics are requested.
Severity	16
SQLCODE	-1880
SQLSTATE	WW257
Sybase error code	12270

Probable cause

The request to get the file system statistics failed.

1.1.4.446 Failed to get status information on the path '%1': %2

Error constant	SQLE_FAILED_TO_GET_FILE_STATUS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The path that the status information is requested.
Parameter 2	Reason the status information of the file could not be returned, if known.
Severity	16
SQLCODE	-1879
SQLSTATE	WW256
Sybase error code	12271

Probable cause

The request to get the file status failed.

1.1.4.447 Failed to load %1 HANA library

Error constant	BACKUP_LIBRARY_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Library handle not available
Severity	16
SQLCODE	-1990
SQLSTATE	WB039
Sybase error code	12194

Probable cause

Given library not found

1.1.4.448 Failed to load the MobiLink client support libraries

Error constant	SQLLE_COULD_NOT_LOAD_SYNC_LIBRARY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-1580
SQLSTATE	WW207
Sybase error code	12525

Probable cause

To use the SYNCHRONIZE command, a MobiLink client must be installed on the same computer where the database server is running.

1.1.4.449 Failed to open pipe %1 during BACKUP using BACKINT %2

Error constant	SQLE_BACKUP_BKINT_ERROR_OPENING_PIPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the pipe on which open failed
Parameter 2	OS error thrown during the read operation
Severity	16
SQLCODE	-1912
SQLSTATE	WB022
Sybase error code	12258

Probable cause

Error occurred while opening pipe during backup using BACKINT

1.1.4.450 Failed to read pipe %1 during BACKUP using BACKINT %2

Error constant	SQLE_BACKUP_BKINT_ERROR_READING_PIPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the pipe on which close failed
Parameter 2	OS error thrown during the read operation
Severity	16
SQLCODE	-1915
SQLSTATE	WB025
Sybase error code	12261

Probable cause

Error occurred while reading pipe during backup using BACKINT

1.1.4.451 Failed to read the SQL Anywhere Cockpit setting file '%1'

Error constant	SQL_E_COCKPITDB_FAILED_TO_READ_SETTING_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the file to be read
Severity	16
SQLCODE	-1864
SQLSTATE	WW253
Sybase error code	12283

Probable cause

The request to read the SQL Anywhere Cockpit setting file failed.

1.1.4.452 Failed to rename the SQL Anywhere Cockpit file '%1' to '%2': %3

Error constant	SQL_E_COCKPITDB_FAILED_TO_RENAME_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the file to be renamed
Parameter 2	New file name of the file
Parameter 3	Reason the file could not be renamed, if known.
Severity	16
SQLCODE	-1876
SQLSTATE	WW252
Sybase error code	12274

Probable cause

The request to rename the SQL Anywhere Cockpit file failed.

1.1.4.453 Failed to set up audit log session for database '%1'

Error constant	SQLE_AUDIT_SESSION_FAILED_TO_START
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database.
Severity	11
SQLCODE	-1725
SQLSTATE	WE039
Sybase error code	12412

Probable cause

The audit log session for the specified database cannot be created.

1.1.4.454 Failed to shut down the dbmlsync server. Check the dbmlsync log file for more details

Error constant	SQLE_MLA_SYNC_SHUTDOWN_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1387
SQLSTATE	WW163
Sybase error code	13181

Probable cause

The MobiLink agent adapter encountered an error while attempting to shut down the server. Check the dbmlsync log file for more details.

1.1.4.455 Failed to start the dbmlsync server

Error constant	SQLE_SYNCCMD_START_SERVER_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1375
SQLSTATE	5RW45
Sybase error code	13191

Probable cause

The database server failed to start a new dbmlsync process or failed to connect to an existing dbmlsync server running on the port number specified in the SYNCHRONIZE statement.

1.1.4.456 Failed to start the dbmlsync server. Check the dbmlsync log file for more details

Error constant	SQLE_MLA_SYNC_START_SERVER_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1388
SQLSTATE	WW164
Sybase error code	13180

Probable cause

The MobiLink agent adapter failed to start a new dbmlsync process or the server did not begin processing requests before the timeout expired. Check the dbmlsync log file for more details.

1.1.4.457 Failed to transform geometry (error %1)

Error constant	SQLE_SLERR_TRANSFORM_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The error code from the projection library.
Severity	16
SQLCODE	-1405
SQLSTATE	2FF15
Sybase error code	13167

Probable cause

An error occurred when performing a transform from one spatial reference system to another. This error may occur if a point in the first geometry is outside of the bounds for the transform definition. The error may also be reported for particular transform definitions. The integer error code from the transform library may be used to diagnose the transform definition.

1.1.4.458 Failed to transform point %1 (error %2)

Error constant	SQLE_SLERR_TRANSFORM_POINT_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The point that could not be transformed.
Parameter 2	The error code from the projection library.
Severity	16
SQLCODE	-1532
SQLSTATE	2FF17
Sybase error code	12573

Probable cause

An error occurred when performing a transform from one spatial reference system to another. This error may occur if a point in the first geometry is outside of the bounds for the transform definition. The error may also be reported for particular transform definitions. The integer error code from the transform library may be used to diagnose the transform definition.

1.1.4.459 Failed to write pipe %1 during BACKUP using BACKINT %2

Error constant	SQL_E_BACKUP_BKINT_ERROR_WRITING_PIPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the pipe on which close failed
Parameter 2	OS error thrown during the read operation
Severity	16
SQLCODE	-1914
SQLSTATE	WB024
Sybase error code	12260

Probable cause

Error occurred while writing pipe during backup using BACKINT

1.1.4.460 Failed to write the SQL Anywhere Cockpit setting file '%1'

Error constant	SQL_E_COCKPITDB_FAILED_TO_WRITE_SETTING_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name of the file to be written
Severity	16
SQLCODE	-1865
SQLSTATE	WW254
Sybase error code	12282

Probable cause

The request to write the SQL Anywhere Cockpit setting file failed.

1.1.4.461 Feature '%1' is locked because synchronization is in progress

Error constant	SQLE_FEATURE_LOCKED_SYNC
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Feature name
Severity	16
SQLCODE	-1343
SQLSTATE	WW147
Sybase error code	13213

Probable cause

You attempted to use a feature that was previously locked because a synchronization is in progress.

1.1.4.462 Feature '%1' is locked by another connection

Error constant	SQLE_FEATURE_LOCKED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Feature name
Severity	16
SQLCODE	-1334
SQLSTATE	WW146
Sybase error code	13222

Probable cause

You attempted to use a feature that was previously locked by another connection.

1.1.4.463 Feature '%1' is not supported for this database

Error constant	SQLE_FEATURE_REQUIRES_UPGRADE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The feature that is not supported for this database.
Severity	16
SQLCODE	-1887
SQLSTATE	0AW0A
Sybase error code	12263

Probable cause

You attempted to carry out an operation or use a feature that is not supported in the current database. To use this feature, upgrade your database to the most recent version.

1.1.4.464 Feature '%1' is unknown or invalid

Error constant	SQLE_FEATURE_UNKNOWN_OR_INVALID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Feature name
Severity	16
SQLCODE	-1332
SQLSTATE	WW144
Sybase error code	13224

Probable cause

You attempted to lock or unlock an unknown feature.

1.1.4.465 Feature '%1' not implemented

Error constant	SQLE_NOT_IMPLEMENTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unimplemented feature.
Severity	16
SQLCODE	-134
SQLSTATE	0A000
Sybase error code	401

Probable cause

You attempted to carry out an operation or use a feature that is not implemented in this version of SQL Anywhere. In UltraLite, this error often occurs because you attempted to perform an unsupported operation on a LONG VARCHAR or LONG BINARY column. For example, the SUBSTRING function cannot be used with a LONG VARCHAR column. As well, an index cannot be created on a LONG column.

1.1.4.466 Feature '%1' not supported

Error constant	SQLE_FEATURE_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The unsupported feature.
Severity	15
SQLCODE	-1965
SQLSTATE	0AW04
Sybase error code	176

Probable cause

You attempted to use a feature that is not supported in the context in which it is used.

1.1.4.467 Feature '%1' was not locked by this connection

Error constant	SQLE_FEATURE_NOT_LOCKED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Feature name
Severity	16
SQLCODE	-1333
SQLSTATE	WW145
Sybase error code	13223

Probable cause

You attempted to unlock a feature that was not previously locked by this connection.

1.1.4.468 Feature not available with UltraLite

Error constant	SQLE_NOT_SUPPORTED_IN_ULTRALITE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-749
SQLSTATE	0AW07
Sybase error code	13762

Probable cause

You attempted to execute a statement or use a feature that is not supported in an UltraLite database.

1.1.4.469 Feature not supported by the client version or the client interface

Error constant	SQLE_NOT_SUPPORTED_BY_CLIENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1148
SQLSTATE	OAW19
Sybase error code	13363

Probable cause

You have attempted to use a feature which the server supports but the client does not. To use the feature, you must upgrade the client library or use a different client interface. Some features are not supported by the jConnect or Open Client client interfaces.

1.1.4.470 Field '%1' of class '%2' cannot be NULL

Error constant	SQLE_FIELD_CANNOT_BE_NULL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the field that cannot be NULL.
Parameter 2	The name of the class that has the field.
Severity	16
SQLCODE	-649
SQLSTATE	WW015
Sybase error code	13741

Probable cause

An attempt was made to store a SQL NULL value in a Java object field that has a Java type that cannot be NULL. For example, the Java 'int' type cannot be NULL.

1.1.4.471 File %1 already exists

Error constant	SQL_FILE_ALREADY_EXISTS
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The file name of the file that already exists
Severity	16
SQLCODE	-1609
SQLSTATE	08WB5
Sybase error code	12497

Probable cause

The request to create a file or directory failed because the file or directory already exists.

1.1.4.472 File I/O failed for '%1'

Error constant	SQL_DEVICE_IO_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name.
Severity	16
SQLCODE	-974
SQLSTATE	WW043
Sybase error code	13959

Probable cause

An error occurred while trying to access the file. If the file is located on a removable media card, the card may have been removed.

1.1.4.473 File or directory %1 not found

Error constant	SQLE_FILE_NOT_FOUND
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The file or directory name that does not exist or fail to access
Severity	16
SQLCODE	-1659
SQLSTATE	08WB9
Sybase error code	12461

Probable cause

You attempted to perform an operation using a file or directory name that does not exist or fail to access.

1.1.4.474 File system error: %1

Error constant	SQLE_OMNI_FILE_SYSTEM_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Error description.
Severity	12
SQLCODE	-1066
SQLSTATE	W0027
Sybase error code	13448

Probable cause

This error results from an error in the underlying file system that was encountered while accessing a file directory as a proxy table.

1.1.4.475 FOR UPDATE has been incorrectly specified for a READ ONLY cursor

Error constant	SQLE_NON_UPDATEABLE_CURSOR
ODBC 2 state	42000
ODBC 3 state	42000
Severity	15
SQLCODE	-813
SQLSTATE	42W36
Sybase error code	7301

Probable cause

You attempted to declare a cursor FOR UPDATE on a query that is not updatable. Queries that contain DISTINCT, GROUP BY, HAVING, INTERSECT, EXCEPT, or UNION, or that contain aggregate functions are read-only. If the ansi_update_constraints option is on, then queries that contain a join are read-only. If the query references a view then the view may be non-updatable.

Related Information

[ansi_update_constraints Option](#)
[SELECT Statement](#)
[SELECT Statement \[UltraLite\]](#)

1.1.4.476 FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR)

Error constant	SQLE_CURSOR_UPDATABILITY_CHANGED
ODBC 2 state	S1009
ODBC 3 state	HY092
Severity	16
SQLCODE	-1290
SQLSTATE	42WD4
Sybase error code	13651

Probable cause

You specified the FOR UPDATE or FOR READ ONLY clause on a DECLARE CURSOR statement. The FOR UPDATE or FOR READ ONLY clause must be specified on the PREPARE statement and not the DECLARE CURSOR statement.

1.1.4.477 Foreign key '%1' for table '%2' duplicates an existing foreign key

Error constant	SQLCODE	SQLLE_DUPLICATE_FOREIGN_KEY
ODBC 2 state		42000
ODBC 3 state		42000
Parameter 1		The role name of the new foreign key.
Parameter 2		The table containing the foreign key.
Severity		16
SQLCODE		-251
SQLSTATE		52W06
Sybase error code		1909

Probable cause

You attempted to define a foreign key that already exists.

Related Information

[Foreign Keys](#)
[CREATE TABLE Statement](#)
[CREATE TABLE Statement \[UltraLite\]](#)

1.1.4.478 Foreign key columns do not match the primary key or a uniqueness constraint in "%1"

Error constant	SQLCODE	SQLLE_NO_MATCHING_INDEX
ODBC 2 state		ERROR

ODBC 3 state	ERROR
Parameter 1	The name of the primary table.
Severity	16
SQLCODE	-1226
SQLSTATE	42R04
Sybase error code	13291

Probable cause

An attempt was made to create a foreign key, but the columns specified do not match the primary key or a uniqueness constraint for the referenced table.

1.1.4.479 Foreign key name '%1' not found

Error constant	SQLF_FOREIGN_KEY_NAME_NOT_FOUND
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the non-existing foreign key.
Severity	15
SQLCODE	-145
SQLSTATE	52W07
Sybase error code	102

Probable cause

You misspelled the name of a foreign key, or the foreign key does not exist.

Related Information

[Foreign Keys](#)
[CREATE TABLE Statement](#)
[CREATE TABLE Statement \[UltraLite\]](#)

1.1.4.480 Format '%1' is not supported in the UNLOAD statement

Error constant	SQLE_UNSUPPORTED_UNLOAD_FORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified format.
Severity	19
SQLCODE	-1530
SQLSTATE	WL018
Sybase error code	12575

Probable cause

An unsupported file format was specified for the UNLOAD statement.

1.1.4.481 Format string argument number %1 is invalid

Error constant	SQLE_INVALID_FORMAT_STRING_ARG_NUM
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Argument number.
Severity	16
SQLCODE	-294
SQLSTATE	53W08
Sybase error code	2749

Probable cause

You supplied an invalid argument number in the format string for a PRINT or RAISERROR statement. The number must be between 1 and 20 and must not exceed the number of arguments provided.

1.1.4.482 Format string contains invalid format specifiers: '%1'

Error constant	INVALID_FORMAT_SPECIFIERS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Format string
Severity	16
SQLCODE	-1970
SQLSTATE	53W10
Sybase error code	12212

Probable cause

You supplied an format string for `xp_sprintf` or `xp_scanf` that contains invalid format specifiers. Only string format specifiers are permitted.

1.1.4.483 Format string contains more than %2 format specifiers: '%1'

Error constant	TOO_MANY_FORMAT_SPECIFIERS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Format string
Parameter 2	Number of format specifiers
Severity	16
SQLCODE	-1971
SQLSTATE	53W11
Sybase error code	12211

Probable cause

You supplied an format string for `xp_sprintf` or `xp_scanf` that contains invalid format specifiers. Only string format specifiers are permitted.

1.1.4.484 Found a file '%1' with relative path in delta dbspace during backup existing log area.

Error constant	RESTORE_RELATIVE_DELTA_FILE_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The filename for file which had the error.
Severity	16
SQLCODE	-1929
SQLSTATE	WB035
Sybase error code	12248

Probable cause

No delta files were found during the backup of the existing log area.

1.1.4.485 Frame not allowed for window '%1'

Error constant	SQL_E_FRAME_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the window.
Severity	16
SQLCODE	-950
SQLSTATE	42WA6
Sybase error code	13538

Probable cause

Frames are not allowed on windows referenced from inline window specifications.

1.1.4.486 Function '%1' has invalid parameter '%2' ('%3')

Error constant	SQLE_SLERR_INVALID_PARAMETER_W_PARM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the function.
Parameter 2	The name of the parameter.
Parameter 3	Information about the parameter that caused the error.
Severity	16
SQLCODE	-1728
SQLSTATE	2FW93
Sybase error code	12409

Probable cause

An error occurred while evaluating a parameter.

1.1.4.487 Function '%1' has invalid parameter '%2' ('%3')

Error constant	SQLE_INVALID_PARAMETER_W_PARM
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	The name of the function.
Parameter 2	The name of the parameter.
Parameter 3	Information about the parameter that caused the error.
Severity	18
SQLCODE	-1090
SQLSTATE	08W94
Sybase error code	13424

Probable cause

An error occurred while evaluating a parameter.

1.1.4.488 Function-name clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_CREATEINDEX_FUNCTION_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1942
SQLSTATE	0AW39
Sybase error code	12235

Probable cause

The function-name clause of the CREATE INDEX statement is not supported when the statement is in the BEGIN PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.489 Function or column reference to '%1' in the ORDER BY clause is invalid

Error constant	SQLE_INVALID_ORDERBY_COLUMN
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the column referenced directly, or in an expression, in the ORDER BY clause.
Severity	15
SQLCODE	-854
SQLSTATE	42W65
Sybase error code	104

Probable cause

You specified a function or column reference in the ORDER BY clause that is semantically invalid. For example, for DISTINCT queries the ORDER BY clause may only refer to items in the query's SELECT list.

Related Information

[The GROUP BY Clause: Organizing Query Results into Groups](#)

[GROUP BY Clause](#)

[MAX Function \[Aggregate\]](#)

[SELECT Statement \[UltraLite\]](#)

1.1.4.490 Function or column reference to '%1' must also appear in a GROUP BY

Error constant	SQLI_INVALID_GROUP_SELECT
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the column referenced directly, or in an expression, that must be in the GROUP BY clause.
Severity	15
SQLCODE	-149
SQLSTATE	53003
Sybase error code	7321

Probable cause

You used a non-aggregate function or column reference in the SELECT list or in a nested query block that does not appear in the GROUP BY clause. In a query using GROUP BY, SELECT list items that are not aggregate functions must also appear in the GROUP BY clause. If the SELECT list item is a column reference or an alias, you may add the column name or alias to the GROUP BY clause. If the SELECT list item is a scalar function, ensure that the function's arguments in the GROUP BY clause match exactly with those in the SELECT list. You may be able to use the MAX function (or another aggregate function) on the column name instead of adding the column to the GROUP BY clause.

1.1.4.491 Geometries with CircularString are not supported in spatial reference system %1

Error constant	SQLI_SLERR_CIRCULAR_SRS
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	The SRID of the round-Earth spatial reference system.
Severity	16
SQLCODE	-1495
SQLSTATE	2FW85
Sybase error code	13607

Probable cause

The method does not support geometries with CircularString elements.

1.1.4.492 Geometries with CircularString not supported (near "%1")

Error constant	SQL_E_SLERR_CIRCULAR_METHOD
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The method or context where the CircularString was detected.
Severity	16
SQLCODE	-1494
SQLSTATE	2FW84
Sybase error code	13608

Probable cause

The method or operation does not support geometries with CircularString elements.

1.1.4.493 Geometry expressions cannot be used in the ORDER BY specification (near '%1')

Error constant	SQL_E_SLERR_GEOM_ORDER_BY
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The geometry expression.
Severity	16
SQLCODE	-1531
SQLSTATE	2FW92
Sybase error code	12574

Probable cause

Geometry expressions cannot be used in the ORDER BY clause. The ST_LinearHash() method may be used in the ORDER BY specification to order geometry values using the same rules used for spatial indexes, or a conversion method such as ST_AsText() may be used to order the rows by their string representation.

1.1.4.494 GRANT of column permission on view not allowed

Error constant	SQLE_NO_COLUMN_PERMS_FOR_VIEWS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-635
SQLSTATE	52W22
Sybase error code	102

Probable cause

You cannot grant permissions on columns for views.

1.1.4.495 Grouped query contains more than one distinct aggregate function

Error constant	SQLE_INVALID_DISTINCT_AGGREGATE
ODBC 2 state	37000
ODBC 3 state	42000

Severity	15
SQLCODE	-863
SQLSTATE	42W70
Sybase error code	13867

Probable cause

Two or more DISTINCT aggregate functions were specified in the same grouped query. This is only permitted if the Hash Group By operator is available. Any query block can only contain at most one DISTINCT aggregate function if the Hash Group By operator is not available.

Related Information

[Aggregate Functions in Queries](#)
[Aggregate Functions](#)
[Aggregate Expressions - UltraLite](#)

1.1.4.496 Hash error: %1

Error constant	SQLE_HASH_ERROR
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Description of the error that occurred.
Severity	11
SQLCODE	-1259
SQLSTATE	08W92
Sybase error code	13255

Probable cause

An error occurred during hashing.

1.1.4.497 Host variable reference in service definition must be named

Error constant	SQLE_HOSTVAR_MUST_BE_NAMED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-926
SQLSTATE	42W9B
Sybase error code	13559

Probable cause

You have attempted to create a service with an unnamed host variable reference.

1.1.4.498 Host variables must not be used in this context

Error constant	SQLE_HOSTVARS_NOT_ALLOWED_IN_THIS_CONTEXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1761
SQLSTATE	42X10
Sybase error code	12379

Probable cause

You have attempted to use a host variable in a statement at a location that does not support host variables.

1.1.4.499 Host variables must not be used within a batch

Error constant	SQLE_HOSTVARS_IN_BATCH
----------------	------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-807
SQLSTATE	07W07
Sybase error code	13817

Probable cause

You have attempted to execute a batch that contains host variable references. Host variables are not supported within a batch.

1.1.4.500 HTTP request failed. Status code '%1'

Error constant	SQLE_HTTP_REQUEST_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The HTTP status code.
Severity	19
SQLCODE	-983
SQLSTATE	WW052
Sybase error code	13506

Probable cause

The HTTP request returned a status code that indicated failure.

1.1.4.501 I/O error %1 -- transaction rolled back

Error constant	SQLE_DEVICE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	A message describing the error that occurred.
Severity	24
SQLCODE	-305
SQLSTATE	40W04
Sybase error code	3013

Probable cause

SQL Anywhere has detected a problem with your hard disk. A ROLLBACK statement has been automatically executed.

1.1.4.502 Identifier '%1' too long

Error constant	SQL_E_IDENTIFIER_TOO_LONG
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The identifier that is too long.
Severity	15
SQLCODE	-250
SQLSTATE	54003
Sybase error code	103

Probable cause

An identifier that was specified is longer than 128 bytes.

Related Information

[Identifiers in UltraLite Identifiers](#)

1.1.4.503 Identity attribute mismatch for column '%1'

Error constant	SQLE_OMNI_IDENTITY_MISMATCH
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The name of the column.
Severity	16
SQLCODE	-725
SQLSTATE	W0019
Sybase error code	11212

Probable cause

The identity attribute of the column specified in the CREATE EXISTING statement differs from the identity attribute of the actual column.

1.1.4.504 Illegal column definition: %1

Error constant	SQLE_ILLEGAL_COLUMN_DEFINITION
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	A message describing the error that occurred.
Severity	16
SQLCODE	-1046
SQLSTATE	55W19
Sybase error code	13465

Probable cause

You are attempting to define a column in a way that is not allowed.

1.1.4.505 Illegal column name: '%1'

Error constant	SQLE_BAD_FOR_XML_EXPLICIT_COLUMN_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The reason the column name was illegal.
Severity	16
SQLCODE	-899
SQLSTATE	WX007
Sybase error code	13582

Probable cause

FOR XML EXPLICIT and FOR JSON EXPLICIT column names can consist of up to four fields separated by exclamation marks. The first two columns must be named Tag and Parent.

Related Information

[FOR XML EXPLICIT](#)

1.1.4.506 Illegal cursor operation attempt

Error constant	SQLE_CURSOROP_NOT_ALLOWED
ODBC 2 state	07005
ODBC 3 state	07005
Severity	16
SQLCODE	-187
SQLSTATE	09W02
Sybase error code	9526

Probable cause

You attempted an illegal cursor operation. For example, you may be attempting to OPEN a cursor for a statement that is neither a SELECT nor a BATCH.

Related Information

[Cursor Usage](#)

[Multiple Row Fetching](#)

[OPEN Statement \[ESQL\] \[SP\]](#)

1.1.4.507 Illegal flags value passed to OPENXML

Error constant	SQLE_BAD_OPENXML_FLAG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-893
SQLSTATE	WX004
Sybase error code	13590

Probable cause

The flags value passed to OPENXML as the third argument must be either 1 (attribute-centric mapping), or 2 (element-centric mapping).

1.1.4.508 Illegal ORDER BY in aggregate function

Error constant	SQLE_INVALID_ORDERBY_IN_AGGREGATE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-904
SQLSTATE	42W90
Sybase error code	13579

Probable cause

An ORDER BY can be used in an aggregate function only if there are no DISTINCT aggregates in the SELECT list, or there is a single DISTINCT aggregate with the DISTINCT column equal to the first column of the ORDER

BY. Also, multiple ordered aggregates cannot be used in the same SELECT list unless they have the exact same ORDER BY clause.

1.1.4.509 Illegal reference to correlation name '%1'

Error constant	SQLE_INVALID_CORRELATION_NAME_REFERENCE
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The correlation name that is incorrectly referenced.
Severity	15
SQLCODE	-824
SQLSTATE	42U01
Sybase error code	13830

Probable cause

Your query contains a reference in a table expression to a correlation name that is not contained in that table expression.

1.1.4.510 Illegal tag value: '%1'

Error constant	SQLE_BAD_FOR_XML_EXPLICIT_TAG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The illegal tag value.
Severity	16
SQLCODE	-897
SQLSTATE	WX005
Sybase error code	13584

Probable cause

FOR XML EXPLICIT and FOR JSON EXPLICIT tag values must be greater than 0 and less than 256. NULL values are not allowed in the Tag column.

Related Information

[FOR XML EXPLICIT](#)

1.1.4.511 Illegal user selectivity estimate specified

Error constant	SQLE_INVALID_USER_ESTIMATE
ODBC 2 state	01000
ODBC 3 state	01000
Severity	10
SQLCODE	118
SQLSTATE	01W16
Sybase error code	13617

Probable cause

You specified a user selectivity estimate that is either not a literal constant or is outside the range 0.0 to 100.0 (estimates are specified as percentages). The estimate has been ignored.

Related Information

[ESTIMATE_SOURCE Function \[Miscellaneous\]](#)

1.1.4.512 Immediate materialized view definition cannot contain a SUM function over a nullable expression

Error constant	SQLE_UPDATABLE_MATVIEW_SUM_NULL_EXPR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1286
SQLSTATE	42WCD
Sybase error code	13668

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains a SUM function over a nullable expression.

1.1.4.513 IN-list is too long

Error constant	SQLE_IN_LIST_TOO_LONG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1898
SQLSTATE	54W24
Sybase error code	12255

Probable cause

The IN-list contains too many elements. Consider inserting the IN-list's values into a temporary table. Then rewrite the query to join this temporary table to the other table(s) in the original statement. Rebuilding the database with a larger page size could prevent this error.

1.1.4.514 Incomplete transactions prevent transaction log renaming

Error constant	SQLE_BACKUP_CANNOT_RENAME_LOG_YET
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	20
SQLCODE	-242
SQLSTATE	WB003
Sybase error code	3206

Probable cause

The last page in the transaction log was read by a call to db_backup. One or more currently active connections have partially completed transactions, preventing the transaction log file from being renamed. Reissue the db_backup call.

1.1.4.515 Incorrect database store DLL (%1) version

Error constant	SQLE_STORE_VERSION_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database store DLL.
Severity	19
SQLCODE	-711
SQLSTATE	08W47
Sybase error code	13701

Probable cause

The database store DLL and server DLL versions do not match.

1.1.4.516 Incorrect or missing encryption key

Error constant	SQLE_BAD_ENCRYPTION_KEY
ODBC 2 state	08001
ODBC 3 state	08001
Severity	21
SQLCODE	-840
SQLSTATE	08W62
Sybase error code	16846

Probable cause

The database is encrypted with a key. There was no key given to start the database, or the specified key was incorrect.

Related Information

[Database Encryption and Decryption](#)

[Database Security](#)

[-ek Database Option](#)

[DatabaseKey \(DBKEY\) Connection Parameter](#)

[UltraLite DBKEY Connection Parameter](#)

1.1.4.517 Incorrect volume ID for '%1'

Error constant	SQL_E_INCORRECT_VOLUME_ID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The file name.
Severity	16
SQLCODE	-975
SQLSTATE	WW044
Sybase error code	13960

Probable cause

The file can be accessed, but the volume ID has changed. Insert the original removable media card.

1.1.4.518 Index '%1' cannot be clustered

Error constant	SQL_E_CLUSTERED_INDEX_NOT_ALLOWED
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the index that could not be made clustered.

Severity	16
SQLCODE	-878
SQLSTATE	42W74
Sybase error code	13889

Probable cause

You attempted to create a clustered index (including key indexes) but the new index cannot be created, for example, because the table already has a clustered index.

1.1.4.519 Index '%1' for table '%2' would not be unique

Error constant	SQL_E_INDEX_NOT_UNIQUE
ODBC 2 state	23000
ODBC 3 state	23000
Parameter 1	Name of the index that would not be unique.
Parameter 2	Name of the table that contains the index.
Severity	16
SQLCODE	-196
SQLSTATE	23505
Sybase error code	548

Probable cause

You attempted to insert or update a row that has the same value as another row in some column, and there is a constraint that does not allow two rows to have the same value in that column.

Related Information

[CREATE INDEX Statement](#)

[INSERT Statement](#)

[CREATE INDEX Statement \[UltraLite\]](#)

[INSERT Statement \[UltraLite\]](#)

1.1.4.520 Index '%1' has no columns

Error constant	SQLE_INDEX_HAS_NO_COLUMNS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The name of the index.
Severity	16
SQLCODE	-1274
SQLSTATE	0EW01
Sybase error code	13884

Probable cause

You attempted to create an index without columns.

1.1.4.521 Index name '%1' is ambiguous

Error constant	SQLE_AMBIGUOUS_INDEX_NAME
ODBC 2 state	S0011
ODBC 3 state	42S11
Parameter 1	Name of the ambiguous index.
Severity	16
SQLCODE	-678
SQLSTATE	52W40
Sybase error code	1921

Probable cause

A statement has referred to an index name that is not unique. Preface the index name with the table and/or owner name.

Related Information

[CREATE INDEX Statement \[UltraLite\]](#)

1.1.4.522 Index name '%1' not unique

Error constant	SQLE_INDEX_NAME_NOT_UNIQUE
ODBC 2 state	S0011
ODBC 3 state	42S11
Parameter 1	Name of the invalid index.
Severity	16
SQLCODE	-111
SQLSTATE	52W04
Sybase error code	1921

Probable cause

You attempted to create an index with the same name as an existing index.

Related Information

[CREATE INDEX Statement](#)

[CREATE INDEX Statement \[UltraLite\]](#)

1.1.4.523 Index type specification of '%1' is invalid

Error constant	SQLE_INVALID_INDEX_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The index type specification that is invalid.
Severity	16
SQLCODE	-650
SQLSTATE	WW016
Sybase error code	13704

Probable cause

SAP IQ index types can be specified for SAP IQ indexes only. In UltraLite, you cannot specify indexes on LONG column types.

Related Information

[CREATE INDEX Statement \[UltraLite\]](#)

1.1.4.524 Index validation failed for table %1, index %2 with code: %3

Error constant	SQL_E_CORRUPT_ULTRALITE_INDEX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the table.
Parameter 2	The name of the index.
Parameter 3	The specific kind of corruption that was found.
Severity	23
SQLCODE	-1185
SQLSTATE	WI002
Sybase error code	13330

Probable cause

UltraLite database validation failed while validating the specified index. The code provides more specific information on the validation failure.

Related Information

[Database Validation](#)
[Validating an UltraLite Database](#)
[VALIDATE Statement](#)
[sa_validate System Procedure](#)
[Validation Utility \(dbvalid\)](#)

1.1.4.525 Indirect identifier `[%1]` yielded an invalid identifier name '%2'

Error constant	SQLE_INDIRECT_IDENT_INVALID
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The variable name for the indirect identifier
Parameter 2	The value of that variable that is invalid as an identifier name
Severity	16
SQLCODE	-1819
SQLSTATE	42X13
Sybase error code	12325

Probable cause

An indirect identifier must produce a name that would be accepted if it were specified without the use of indirect identifiers.

1.1.4.526 Indirect identifiers not supported

Error constant	SQLE_INDIRECT_IDENTS_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1818
SQLSTATE	0AW31
Sybase error code	12326

Probable cause

The current database is an older database and does not have support for indirect identifiers. To use this feature, upgrade your database to the most recent version.

1.1.4.527 Information for synchronization is incomplete or invalid, check '%1'

Error constant	SQLE_SYNC_INFO_INVALID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the parameter not properly initialized.
Severity	16
SQLCODE	-956
SQLSTATE	WW036
Sybase error code	13532

Probable cause

Information for synchronization is incomplete or invalid. Correct the indicated parameter before attempting to synchronize again. If 'init_verify' is indicated, the InitSyncInfo function was not called.

Related Information

[UltraLite Synchronization Parameters](#)

1.1.4.528 Information for synchronization was not provided

Error constant	SQLE_SYNC_INFO_REQUIRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1111
SQLSTATE	WW081
Sybase error code	13403

Probable cause

You must supply information for synchronization in the synchronization call.

1.1.4.529 Input parameter index out of range

Error constant	SQLE_BAD_PARAM_INDEX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-689
SQLSTATE	WJ005
Sybase error code	13717

Probable cause

The range for valid parameters is from 1 up to the number of host variables specified in the prepared/callable statement.

Related Information

[Executing Prepared Statements](#)

1.1.4.530 Input string is not base64-encoded

Error constant	SQLE_BASE64_DECODING_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-961
SQLSTATE	WW039
Sybase error code	13528

Probable cause

An error occurred during base64 decoding.

1.1.4.531 INSERT...ON EXISTING UPDATE not allowed: immediate materialized view %1 depends on %2

Error constant	SQLE_UPDATE_ON_EXISTING_DEP_IMV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of dependent immediate materialized view.
Parameter 2	The name of the base table into which the insert was performed.
Severity	16
SQLCODE	-1204
SQLSTATE	55W33
Sybase error code	13311

Probable cause

Insert statement with ON EXISTING clause is not permitted on a base table if the base table has dependent initialized immediate materialized view.

1.1.4.532 INSERT/DELETE on cursor can modify only one table

Error constant	SQLE_ONLY_ONE_TABLE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-199
SQLSTATE	09W04
Sybase error code	102

Probable cause

You attempted to insert into a cursor and have specified values for more than one table, or you attempted to delete from a cursor that involves a join. Insert into one table at a time. For DELETE, use the FROM clause to specify the table you want to delete from.

Related Information

[Cursor Usage](#)

[INSERT Statement](#)

[DELETE Statement \(Positioned\) \[ESQL\] \[SP\]](#)

[INSERT Statement \[UltraLite\]](#)

[DELETE Statement \[UltraLite\]](#)

1.1.4.533 Insufficient cache to start Java VM

Error constant	SQLC_JAVA_VM_INSUFFICIENT_CACHE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-686
SQLSTATE	WP015
Sybase error code	13878

Probable cause

Insufficient cache was available to start the Java VM. Restart the database server with a larger cache size.

1.1.4.534 Insufficient memory for OPENXML query

Error constant	SQLC_XQUERY_MEMORY_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	17
SQLCODE	-912
SQLSTATE	WX016
Sybase error code	13572

Probable cause

The memory used by an OPENXML query may be proportional to the maximum distance between elements or attributes returned by a single row. For example, a query where some row uses the value from both the first and

last element in the document may use memory proportional to the size of the document. One solution is to increase the cache size. Another is to break a query that refers to distant elements into several queries that refer to nearby elements and join the results.

1.1.4.535 Integrated login failed

Error constant	SQLE_INTEGRATED_LOGON_FAILED
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-245
SQLSTATE	28W04
Sybase error code	13691

Probable cause

The integrated login failed. You may not have a system account on the server computer.

1.1.4.536 Integrated logins are not permitted

Error constant	SQLE_INVALID_STANDARD_LOGON
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-205
SQLSTATE	28W02
Sybase error code	13689

Probable cause

The login_mode database option is set to Standard, and you attempted an integrated login. Change the option setting or supply an explicit user ID.

1.1.4.537 Integrated logins are not supported for this database

Error constant	SQLE_INTEGRATED_LOGON_UNSUPPORTED
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-246
SQLSTATE	28W05
Sybase error code	13694

Probable cause

The current database is an older database and does not have the information to map integrated login IDs to database user IDs. You must upgrade your database to use integrated logins.

1.1.4.538 Integrated logins are required, standard logins are not permitted

Error constant	SQLE_INVALID_INTEGRATED_LOGON
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-206
SQLSTATE	28W03
Sybase error code	13690

Probable cause

The login_mode database option is set to Integrated, and you attempted a standard login. Change the option setting or use an integrated login.

1.1.4.539 Internal database error %1 -- transaction rolled back

Error constant	SQLE_DATABASE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Identification of the error.
Severity	18
SQLCODE	-301
SQLSTATE	40W01
Sybase error code	13665

Probable cause

An internal database error occurred. If it can be reproduced, it should be reported to SAP. A ROLLBACK statement has been automatically executed.

Related Information

[ROLLBACK Statement](#)

[ROLLBACK Statement \[UltraLite\]](#)

1.1.4.540 Internal rollback log corrupted

Error constant	SQLE_LOG_CORRUPTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	22
SQLCODE	-311
SQLSTATE	WI004
Sybase error code	932

Probable cause

While processing a COMMIT or ROLLBACK, corruption was found in the internal rollback log. This is a fatal internal error.

1.1.4.541 Invalid absolute or relative offset in FETCH

Error constant	SQLE_INVALID_FETCH_POSITION
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-263
SQLSTATE	42W25
Sybase error code	6259

Probable cause

You specified an offset in a FETCH that was invalid or NULL.

1.1.4.542 Invalid address parameter "%1" provided to start a listener

Error constant	SQLE_START_LISTENER_INVALID_ADDRESS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener address parameter
Severity	16
SQLCODE	-1783
SQLSTATE	08WE2
Sybase error code	12357

Probable cause

You attempted to start a listener with an invalid IP address or port.

1.1.4.543 Invalid address parameter "%1" provided to stop a listener

Error constant	SQLE_STOP_LISTENER_INVALID_ADDRESS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener address parameter
Severity	16
SQLCODE	-1785
SQLSTATE	08WE3
Sybase error code	12356

Probable cause

You attempted to stop a listener with an invalid IP address or port.

1.1.4.544 Invalid backup operation

Error constant	SQLE_INVALID_BACKUP_OPERATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1021
SQLSTATE	WB013
Sybase error code	3206

Probable cause

The specified backup operation is not valid because of previous backup operation(s).

1.1.4.545 Invalid BACKUP operation or type specified: %1

Error constant	SQLE_BACKUP_BKINT_INVALID_PARAMS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of backup operation or type
Severity	16
SQLCODE	-1917
SQLSTATE	WB027
Sybase error code	12263

Probable cause

Either backup operation or type is invalid

1.1.4.546 Invalid backup parameter value

Error constant	SQLE_INVALID_BACKUP_PARM_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1045
SQLSTATE	WB015
Sybase error code	13466

Probable cause

One or more of the parameters supplied to the backup operation has an invalid value.

1.1.4.547 Invalid bounds for coordinate %1 (near "BETWEEN %2 AND %3")

Error constant	SQLE_SLERR_INVALID_BOUNDS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The coordinate with the invalid bounds.
Parameter 2	The first value of the invalid bounds.
Parameter 3	The second value of the invalid bounds.
Severity	16
SQLCODE	-1501
SQLSTATE	2FW88
Sybase error code	13602

Probable cause

The specified coordinate bounds are not valid.

1.1.4.548 Invalid class byte code

Error constant	SQLE_BAD_CLASS_BYTE_CODE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-670
SQLSTATE	WP005
Sybase error code	13746

Probable cause

A binary expression passed to the INSTALL JAVA statement was not a valid Java class.

1.1.4.549 Invalid cockpit parameter

Error constant	SQLE_COCKPITDB_INVALID_PARAMETERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1836
SQLSTATE	08WF1
Sybase error code	12308

Probable cause

An error occurred while evaluating a parameter. The SQL Anywhere Cockpit does not support this parameter or the parameter is specified with an invalid value.

1.1.4.550 Invalid collation: "%1"

Error constant	SQLE_TEXT_BAD_COLLATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid collation string.
Severity	16
SQLCODE	-1163
SQLSTATE	WT008
Sybase error code	13350

Probable cause

The collation was not found, or the tailoring options were invalid.

1.1.4.551 Invalid column number

Error constant	SQLE_INVALID_COLUMN_NUMBER
----------------	----------------------------

ODBC 2 state	42000
ODBC 3 state	42000
Severity	15
SQLCODE	-159
SQLSTATE	42W13
Sybase error code	182

Probable cause

You gave an invalid column number, or the column you are looking for is in a different table.

1.1.4.552 Invalid commit action for shared temporary table

Error constant	SQLE_INVALID_SHARED_COMMIT_ACTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1089
SQLSTATE	52W26
Sybase error code	13425

Probable cause

A global shared temporary table must be declared as ON COMMIT PRESERVE ROWS or NOT TRANSACTIONAL.

1.1.4.553 Invalid comparison

Error constant	SQLE_INVALID_COMPARISON
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16

SQLCODE	-710
SQLSTATE	52W25
Sybase error code	13749

Probable cause

An attempt was made to compare two arguments that do not support comparison. For example, it is not valid to compare a Java object with another Java object, unless the class of the object supports a valid compareTo method.

1.1.4.554 Invalid configuration name %1

Error constant	SQLE_SLERR_CONFIG_NO_SUBFILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid configuration name.
Severity	16
SQLCODE	-1439
SQLSTATE	2FW32
Sybase error code	13133

Probable cause

The named configuration is not supported.

1.1.4.555 Invalid data conversion

Error constant	SQLE_CANNOT_CONVERT
ODBC 2 state	01S01
ODBC 3 state	01S01
Severity	10
SQLCODE	103
SQLSTATE	01W03

Probable cause

The database could not convert a value to the required type. The value being converted was either supplied to the database on an insert, update, or as a host bind variable, or was a value retrieved from the database into a host variable or SQLDA.

1.1.4.556 Invalid data conversion: NULL was inserted for column '%1' on row %2

Error constant	SQL_E_CANNOT_CONVERT_LOAD_TABLE
ODBC 2 state	07006
ODBC 3 state	07006
Parameter 1	Name of the column where NULL was inserted.
Parameter 2	Row number in the data file where the invalid data conversion took place.
Severity	10
SQLCODE	124
SQLSTATE	01W01
Sybase error code	13886

Probable cause

The database could not convert a value to the required type. The value being converted was supplied to the database in a data file and inserted using LOAD TABLE. A NULL value has been inserted into the column.

Related Information

[Data Type Conversions](#)

1.1.4.557 Invalid data type for column in WRITETEXT or READTEXT

Error constant	SQLE_INVALID_TEXT_IMAGE_DATATYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-609
SQLSTATE	53W09
Sybase error code	7139

Probable cause

You referenced a column in a WRITETEXT or READTEXT statement that is not defined for storing text or image data.

1.1.4.558 Invalid database page size

Error constant	SQLE_PAGE_SIZE_INVALID
ODBC 2 state	42000
ODBC 3 state	42000
Severity	14
SQLCODE	-644
SQLSTATE	08W32
Sybase error code	927

Probable cause

You attempted to create a database with an invalid page size. The page size for a SQL Anywhere database must be either 2048, 4096, 8192, 16384, or 32768 bytes. The page size for an UltraLite database must be either 1024, 2048, 4096, 8192, or 16384 bytes.

Related Information

[UltraLite page_size Creation Option](#)

1.1.4.559 Invalid database server command line

Error constant	SQLE_INVALID_COMMAND_LINE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	18
SQLCODE	-81
SQLSTATE	08W08
Sybase error code	5864

Probable cause

It was not possible to start the database server because the command line was invalid.

Related Information

[SQL Anywhere Database Server Executable \(dbsrv17, dbeng17\)](#)

1.1.4.560 Invalid day of week or month '%1' for event '%2'

Error constant	SQLE_INVALID_EVENT_DAY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Day-of-week name or day-of-month number.
Parameter 2	Name of the event being scheduled.
Severity	15
SQLCODE	-791
SQLSTATE	WE005
Sybase error code	13801

Probable cause

You have attempted to create a schedule with an invalid day-of-week name or day-of-month number.

1.1.4.561 Invalid DEFAULT value near '%1' on line %2

Error constant	SQLE_INVALID_DEFAULT_VALUE
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The word or symbol where the invalid DEFAULT value has been detected.
Parameter 2	Line number.
Severity	15
SQLCODE	-1709
SQLSTATE	42W10
Sybase error code	12431

Probable cause

An invalid DEFAULT value was specified when creating or altering a table column.

1.1.4.562 Invalid descriptor index

Error constant	SQLE_INVALID_DESCRIPTOR_INDEX
ODBC 2 state	S1002
ODBC 3 state	07009
Severity	26
SQLCODE	-640
SQLSTATE	07009
Sybase error code	8201

Probable cause

The index number used with respect to a descriptor area is out of range.

Related Information

[The SQL Descriptor Area \(SQLDA\)](#)

1.1.4.563 Invalid domain '%1'

Error constant	SQLE_INVALID_DOMAIN
ODBC 2 state	ERROR
ODBC 3 state	42000
Parameter 1	The invalid domain specification.
Severity	16
SQLCODE	-1275
SQLSTATE	54W52
Sybase error code	13881

Probable cause

You attempted to create an invalid domain. The size/scale/precision is invalid.

1.1.4.564 Invalid empty string specified as 'ESCAPE CHARACTER' option of LOAD or UNLOAD TABLE

Error constant	SQLE_INVALID_LOAD_ESCAPE_CHAR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1874
SQLSTATE	WL019
Sybase error code	12281

Probable cause

The ESCAPE CHARACTER option does not support empty string as an input for LOAD TABLE and UNLOAD TABLE statements.

1.1.4.565 Invalid escape character '%1'

Error constant	SQLE_INVALID_ESCAPE_CHAR
ODBC 2 state	S1000
ODBC 3 state	22019
Parameter 1	The escape character that is invalid.
Severity	16
SQLCODE	-629
SQLSTATE	22019
Sybase error code	7707

Probable cause

The escape character string length must be exactly one.

1.1.4.566 Invalid escape sequence '%1'

Error constant	SQLE_INVALID_ESCAPE_SEQ
ODBC 2 state	S1000
ODBC 3 state	22025
Parameter 1	The escaped character.
Severity	16
SQLCODE	-630
SQLSTATE	22025
Sybase error code	7705

Probable cause

A LIKE pattern contains an invalid use of the escape character. The escape character may only precede the special characters '%', '_', '[', and the escape character itself.

1.1.4.567 Invalid event parameter for event '%1'

Error constant	SQLE_INVALID_EVENT_PARAMETER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the event being scheduled.
Severity	15
SQLCODE	-1853
SQLSTATE	WE043
Sybase error code	12292

Probable cause

You have specified an event parameter that is invalid.

1.1.4.568 Invalid expression in WHERE clause of Transact-SQL outer join

Error constant	SQLE_INVALID_TSQL_OJ_EXPRESSION
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-680
SQLSTATE	52W23
Sybase error code	301

Probable cause

An expression in the WHERE clause of a query that uses Transact-SQL syntax contains a comparison of a column from the NULL-supplying table with a subquery or an expression that references a column from another table.

1.1.4.569 Invalid expression near '%1'

Error constant	SQLE_EXPRESSION_ERROR
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The invalid expression.
Severity	16
SQLCODE	-156
SQLSTATE	42W08
Sybase error code	401

Probable cause

You supplied an expression that the database server cannot understand. For example, you may have tried to add two dates.

Related Information

[Expressions in SQL Statements](#)

[Expressions in UltraLite](#)

1.1.4.570 Invalid external prefilter name specified

Error constant	SQLE_INVALID_EXT_PREFILTER_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1394
SQLSTATE	WT029
Sybase error code	13176

Probable cause

External prefilter name specified in the text configuration is invalid.

Related Information

[What to Specify When Creating or Altering Text Configuration Objects](#)

[CREATE TEXT CONFIGURATION Statement](#)

[ALTER TEXT CONFIGURATION Statement](#)

1.1.4.571 Invalid external term breaker name specified

Error constant	SQLE_INVALID_EXT_TERMBREAKER_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1395
SQLSTATE	WT026
Sybase error code	13175

Probable cause

External term breaker name specified in the text configuration is invalid.

Related Information

[What to Specify When Creating or Altering Text Configuration Objects](#)

[CREATE TEXT CONFIGURATION Statement](#)

[ALTER TEXT CONFIGURATION Statement](#)

1.1.4.572 Invalid generated identifier '%1'

Error constant	SQLE_INVALID_GENERATED_IDENTIFIER
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The identifier that is generated.
Severity	16
SQLCODE	-1816

SQLSTATE	53032
Sybase error code	12328

Probable cause

An invalid identifier has been generated. The generated identifier is too long or contains characters that are not permitted in identifiers. Please provide valid alias names.

1.1.4.573 Invalid grid size %1

Error constant	SQLE_SLERR_INVALID_GRID_SIZE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The grid size that is not valid.
Severity	16
SQLCODE	-1499
SQLSTATE	2FW86
Sybase error code	13604

Probable cause

The specified grid size cannot be used with the spatial reference system. The grid size must be selected based on the bounds of space.

Related Information

[How Snap-to-grid and Tolerance Impact Spatial Calculations](#)

1.1.4.574 Invalid hint specified for table '%1'

Error constant	SQLE_INVALID_HINT
ODBC 2 state	37000

ODBC 3 state	42000
Parameter 1	The name of the table for which the hint was specified.
Severity	15
SQLCODE	-970
SQLSTATE	42U07
Sybase error code	13520

Probable cause

A hint was specified for the current statement is not valid in this context. In a single statement, all references to a table must specify the same hint or none at all.

1.1.4.575 Invalid host variable

Error constant	SQL_E_VARIABLE_INVALID
ODBC 2 state	37000
ODBC 3 state	42000
Severity	17
SQLCODE	-155
SQLSTATE	42W07
Sybase error code	7201

Probable cause

You supplied an invalid host variable to the database using the C language interface. You may have supplied the variable as a host variable or through a SQLDA.

Related Information

[Host Variables in Embedded SQL](#)
[Host Variable Declaration](#)

1.1.4.576 Invalid increment value for semaphore "%1": %2

Error constant	SQLE_INVALID_INCREMENT_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the semaphore.
Parameter 2	The value specified.
Severity	16
SQLCODE	-1810
SQLSTATE	22032
Sybase error code	12334

Probable cause

The increment value for a semaphore must be a non-negative integer.

1.1.4.577 Invalid intersection matrix '%1'

Error constant	SQLE_SLERR_INVALID_RELATE_MATRIX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The intersection matrix string.
Severity	16
SQLCODE	-1399
SQLSTATE	2FF04
Sybase error code	13173

Probable cause

The provided value is not a valid intersection matrix string. A valid string contains nine characters, each is one of T, F, *, 0, 1, or 2.

1.1.4.578 Invalid JAR file

Error constant	SQLE_BAD_JAR_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-730
SQLSTATE	WP010
Sybase error code	13737

Probable cause

A file passed to the INSTALL JAVA statement was not a valid JAR file.

1.1.4.579 Invalid join type used with Transact-SQL outer join

Error constant	SQLE_INVALID_TSQL_JOIN_TYPE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-681
SQLSTATE	52W24
Sybase error code	305

Probable cause

An invalid join type was used with a query that contains Transact-SQL outer join comparison operators.

1.1.4.580 Invalid local database option

Error constant	SQLE_INVALID_LOCAL_OPTION
ODBC 2 state	08001

ODBC 3 state	08001
Severity	18
SQLCODE	-79
SQLSTATE	08W25
Sybase error code	5864

Probable cause

An invalid database option was found in the DBS (DatabaseSwitches) connection parameter.

Related Information

[DatabaseSwitches \(DBS\) Connection Parameter](#)

1.1.4.581 Invalid mime type '%1'

Error constant	SQLE_INVALID_MIMETYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the mime type
Severity	16
SQLCODE	-1123
SQLSTATE	WW085
Sybase error code	13390

Probable cause

The mime type specifier is invalid.

1.1.4.582 Invalid operation '%2' on sequence '%1'

Error constant	SQLE_INVALID_SEQUENCE_OPERATION
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the operation attempted.
Parameter 2	Name of the sequence.
Severity	16
SQLCODE	-1353
SQLSTATE	52W46
Sybase error code	13207

Probable cause

An invalid operation has been attempted on a sequence object. The only valid operations on a sequence are currval and nextval.

1.1.4.583 Invalid operation on a closed object

Error constant	SQLE_ULTRALITE_OBJ_CLOSED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-908
SQLSTATE	55W14
Sybase error code	13575

Probable cause

An illegal attempt was made to access a closed UltraLite object.

1.1.4.584 Invalid option '%1' -- no PUBLIC setting exists

Error constant	SQLE_INVALID_OPTION
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the invalid option.
Severity	15
SQLCODE	-200
SQLSTATE	42W16
Sybase error code	155

Probable cause

You may have misspelled the name of an option in the SET OPTION statement. You can only define an option for a user if the database administrator has supplied a PUBLIC value for that option.

Related Information

[Database Options](#)

[UltraLite Database Options](#)

[SET OPTION Statement](#)

[SET OPTION Statement \[UltraLite\]](#)

1.1.4.585 Invalid options for UPGRADE: SCRIPT FILE can only be specified with RESTART

Error constant	SQLE_UPGRADE_SCRIPT_EXTRA_CLAUSE
ODBC 2 state	08004
ODBC 3 state	08004
Severity	21
SQLCODE	-1715
SQLSTATE	08X01
Sybase error code	12421

Probable cause

ALTER DATABASE UPGRADE statement with SCRIPT FILE clause cannot be combined with any other clause except for RESTART ON/OFF.

Related Information

[ALTER DATABASE Statement](#)

1.1.4.586 Invalid ORDER BY specification

Error constant	SQLCODE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-152
SQLSTATE	53005
Sybase error code	108

Probable cause

Either you used an integer in an ORDER BY list and the integer is larger than the number of columns in the SELECT list, or you specified an ORDER BY expression that is semantically invalid. For example, for UNION, EXCEPT, and INTERSECT queries you can only use integers or column names of the first SELECT query block to specify an ordering of the result.

Related Information

[SELECT Statement](#)
[SELECT Statement \[UltraLite\]](#)

1.1.4.587 Invalid parameter

Error constant	SQLE_INVALID_PARAMETER
ODBC 2 state	08004
ODBC 3 state	08004
Severity	18
SQLCODE	-735
SQLSTATE	08W24
Sybase error code	5864

Probable cause

An error occurred while evaluating a parameter.

1.1.4.588 Invalid parameter was used in the call to %1

Error constant	SQLE_SFC_INVALID_PARM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Severity	15
SQLCODE	-1686
SQLSTATE	08S02
Sybase error code	12440

Probable cause

An invalid parameter value was passed to the specified procedure.

Related Information

[Secured Features](#)
[-sf Database Server Option](#)
[sa_server_option System Procedure](#)

1.1.4.589 Invalid password: %1

Error constant	SQLE_INVALID_NEW_PASSWORD
ODBC 2 state	28000
ODBC 3 state	28000
Parameter 1	Reason the password is invalid, or the reason attempting to call the function to verify the password failed.
Severity	16
SQLCODE	-1044
SQLSTATE	28W11
Sybase error code	13467

Probable cause

The attempt to create a new user ID or change a password failed. The function specified by the `verify_password_function` option disallowed the password.

Related Information

[verify_password_function Option](#)

1.1.4.590 Invalid polygon format '%1'

Error constant	SQLE_SLERR_INVALID_POLY_ORD
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid polygon format.
Severity	16
SQLCODE	-1448
SQLSTATE	2FW41
Sybase error code	13124

Probable cause

The specified polygon format is not a valid format.

1.1.4.591 Invalid polygon nesting

Error constant	SQLE_SLERR_INVALID_POLY_NESTING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1450
SQLSTATE	2FW43
Sybase error code	13122

Probable cause

The provided rings cannot be interpreted as a valid polygons.

1.1.4.592 Invalid polygon: curve is not a ring

Error constant	SQLE_SLERR_INVALID_POLY_NON_RING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1487
SQLSTATE	2FW82
Sybase error code	13085

Probable cause

One of the curves is not a ring and cannot be used to form a polygon.

Related Information

[How Polygon Ring Orientation Works](#)

1.1.4.593 Invalid polygon: multiple exterior rings

Error constant	SQLE_SLERR_INVALID_POLY_MULT_EXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1451
SQLSTATE	2FW44
Sybase error code	13121

Probable cause

There are multiple exterior rings that do not form a single valid polygon.

1.1.4.594 Invalid polygon: no exterior ring

Error constant	SQLE_SLERR_INVALID_POLY_NO_EXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1449
SQLSTATE	2FW42
Sybase error code	13123

Probable cause

The provided polygon is invalid as it does not have an exterior ring.

1.1.4.595 Invalid polygon: ring has zero area (near '%1')

Error constant	SQLE_SLERR_INVALID_POLY_EMPTY_RING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value or method where the error was detected.
Severity	16
SQLCODE	-1486
SQLSTATE	2FW81
Sybase error code	13086

Probable cause

One of the provided rings has zero area and cannot be a valid polygon ring.

Related Information

[How Polygon Ring Orientation Works](#)

1.1.4.596 Invalid polygon: ring is larger than allowed for SRID=%1 (near '%2')

Error constant	SQLE_SLERR_INVALID_POLY_RE_SIZE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The spatial reference system identifier.
Parameter 2	The value or method where the error was detected.
Severity	16
SQLCODE	-1488
SQLSTATE	2FW83
Sybase error code	13084

Probable cause

One of the rings is larger than the specified spatial reference system supports.

Related Information

[How Polygon Ring Orientation Works](#)

1.1.4.597 Invalid polygon: ring is not closed (near '%1')

Error constant	SQLE_SLERR_INVALID_POLY_RING_CLOSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value or method where the error was detected.
Severity	16
SQLCODE	-1485
SQLSTATE	2FW80
Sybase error code	13087

Probable cause

One of the provided curves is not a closed ring.

Related Information

[How Polygon Ring Orientation Works](#)

1.1.4.598 Invalid preceding or following size in OLAP function

Error constant	SQLE_INVALID_FRAME_BOUNDARY
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Severity	16
SQLCODE	-957
SQLSTATE	22X13
Sybase error code	13531

Probable cause

The expression for the preceding or following size evaluated to NULL or a negative value.

1.1.4.599 Invalid prepared statement type

Error constant	SQLE_INVALID_STATEMENT_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-133
SQLSTATE	07W03
Sybase error code	13630

Probable cause

This is an internal error. If it can be reproduced, it should be reported to SAP.

1.1.4.600 Invalid procedure subtype '%1' for type '%2'

Error constant	SQLE_INVALID_PROCEDURE_SUBTYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The procedure subtype.
Parameter 2	The procedure type.
Severity	16
SQLCODE	-987

SQLSTATE	WW056
Sybase error code	13502

Probable cause

A procedure or function was specified with an invalid subtype for the given procedure type.

1.1.4.601 Invalid procedure type '%1'

Error constant	SQLE_INVALID_PROCEDURE_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The procedure type.
Severity	16
SQLCODE	-986
SQLSTATE	WW055
Sybase error code	13503

Probable cause

A procedure or function was specified with an invalid type.

1.1.4.602 Invalid recursive query

Error constant	SQLE_INVALID_RECURSION
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-921
SQLSTATE	42W99
Sybase error code	13563

Probable cause

A recursive query must consist of the UNION ALL of an initial query and an iteration query. The only set operation allowed in the iteration query is UNION ALL. A recursive reference to the name of the common table expression can only appear in the iteration query, and must not be in a SELECT that uses DISTINCT, ORDER BY, or an aggregate function. A recursive reference also cannot appear on the NULL-supplying side of an outer join, or in a subquery.

1.1.4.603 Invalid reference to or operation on constraint '%1'

Error constant	SQLI_INVALID_CONSTRAINT_REF
ODBC 2 state	S0002
ODBC 3 state	42S23
Parameter 1	Name of the constraint that cannot be used for the specified purpose.
Severity	16
SQLCODE	-937
SQLSTATE	42U06
Sybase error code	13550

Probable cause

You specified an invalid operation on a constraint. For example, you tried to alter a primary key constraint.

Related Information

[Table and Column Constraints](#)
[CREATE TABLE Statement](#)
[CREATE TABLE Statement \[UltraLite\]](#)

1.1.4.604 Invalid REFERENCES clause in trigger definition

Error constant	SQLI_INVALID_TRIGGER_COL_REFS
ODBC 2 state	37000
ODBC 3 state	42000

Severity	15
SQLCODE	-272
SQLSTATE	52W12
Sybase error code	102

Probable cause

You supplied an invalid REFERENCES clause in a trigger definition. You may have specified an OLD correlation name in a BEFORE INSERT trigger, or a NEW correlation name in an AFTER DELETE trigger. In both cases, the values do not exist and cannot be referenced.

1.1.4.605 Invalid regular expression: %1 in '%2'

Error constant	SQLE_INVALID_REGULAR_EXPRESSION
ODBC 2 state	S1000
ODBC 3 state	2201B
Parameter 1	The reason the regular expression is invalid.
Parameter 2	The invalid regular expression.
Severity	16
SQLCODE	-1135
SQLSTATE	2201B
Sybase error code	13378

Probable cause

The specified regular expression is invalid.

1.1.4.606 Invalid repeat interval for event '%1'

Error constant	SQLE_INVALID_EVENT_INTERVAL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the event being scheduled.

Severity	15
SQLCODE	-1852
SQLSTATE	WE042
Sybase error code	12293

Probable cause

You have specified an event period that is invalid.

1.1.4.607 Invalid request log format on line %1

Error constant	SQLE_INVALID_REQUEST_LOG_FORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The line number in the log file.
Severity	16
SQLCODE	-999
SQLSTATE	WW020
Sybase error code	13493

Probable cause

The request log file format is invalid. The request log may have been created with an older version of the software.

1.1.4.608 Invalid response from the HTTP server

Error constant	SQLE_INVALID_HTTP_RESPONSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-988

SQLSTATE	WW057
Sybase error code	13501

Probable cause

The response from the remote HTTP server was invalid. It may have been empty, malformed, missing header information, and so on.

1.1.4.609 Invalid ROW or ARRAY domain

Error constant	SQLE_INVALID_COLLECTION_DOMAIN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1820
SQLSTATE	WW249
Sybase error code	12324

Probable cause

Row and array domains cannot contain DEFAULT values or CHECK constraints.

1.1.4.610 Invalid scroll position '%1'

Error constant	SQLE_INVALID_POSITION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The scroll position that is invalid.
Severity	16
SQLCODE	-820
SQLSTATE	24504
Sybase error code	13826

Probable cause

You attempted to scroll to a position that is not supported. Scroll positions must be between -2147483647 and 2147483646.

1.1.4.611 Invalid service name '%1'

Error constant	SQLE_INVALID_SERVICE_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the service.
Severity	16
SQLCODE	-925
SQLSTATE	42W95
Sybase error code	13560

Probable cause

You have attempted to create a service with an invalid name. The name may contain characters that are not allowed, or it may conflict with the URL PATH setting specified for the service.

1.1.4.612 Invalid setting '%1' specified for option '%2' for target type '%3'

Error constant	SQLE_INVALID_SETTING_FOR_TARGET_TYPE_OPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The option value.
Parameter 2	The option name.
Parameter 3	The trace event target type.
Severity	11
SQLCODE	-1902
SQLSTATE	WE044
Sybase error code	12253

Probable cause

The specified option value is invalid for the target type.

1.1.4.613 Invalid setting for HTTP header '%1'

Error constant	SQLE_INVALID_HTTP_HEADER_SETTING
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the invalid HTTP header.
Severity	16
SQLCODE	-940
SQLSTATE	42W84
Sybase error code	13547

Probable cause

You supplied an invalid value for an HTTP header.

1.1.4.614 Invalid setting for HTTP option '%1'

Error constant	SQLE_INVALID_HTTP_OPTION_SETTING
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the invalid HTTP option.
Severity	16
SQLCODE	-939
SQLSTATE	42W83
Sybase error code	13548

Probable cause

You supplied an invalid value for an HTTP option. Some options allow only numeric values, while other options allow only the values On and Off.

1.1.4.615 Invalid setting for option '%1'

Error constant	SQLE_INVALID_OPTION_SETTING
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the invalid option.
Severity	16
SQLCODE	-201
SQLSTATE	42W17
Sybase error code	5849

Probable cause

You supplied an invalid value for an option in the SET statement. Some options allow only numeric values, while other options allow only the values On and Off.

Related Information

[SET OPTION Statement](#)

[SET OPTION Statement \[UltraLite\]](#)

1.1.4.616 Invalid setting for SOAP header '%1'

Error constant	SQLE_INVALID_SOAP_HEADER_SETTING
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the invalid SOAP header.
Severity	16
SQLCODE	-1114
SQLSTATE	42W86
Sybase error code	13400

Probable cause

You supplied an invalid value for a SOAP header.

1.1.4.617 Invalid shapefile filename

Error constant	SQLLE_SLERR_SHAPE_INVALID_FILENAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1424
SQLSTATE	2FW15
Sybase error code	13148

Probable cause

The specified shapefile filename is not valid.

1.1.4.618 Invalid spatial reference system well-known-text (WKT)

Error constant	SQLLE_SLERR_SRS_PARSE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1441
SQLSTATE	2FW34
Sybase error code	13131

Probable cause

The provided string does not represent a valid spatial reference system definition in well-known text format.

1.1.4.619 Invalid SQL descriptor name

Error constant	SQLSTATE
ODBC 2 state	33000
ODBC 3 state	33000
Severity	21
SQLCODE	-642
SQLSTATE	33000
Sybase error code	601

Probable cause

You attempted to deallocate a descriptor that has not been allocated.

Related Information

[DEALLOCATE DESCRIPTOR Statement \[ESQL\]](#)

1.1.4.620 Invalid SQL identifier

Error constant	SQLSTATE
ODBC 2 state	07001
ODBC 3 state	07W06
Severity	16
SQLCODE	-760
SQLSTATE	07W06
Sybase error code	13771

Probable cause

An invalid identifier was supplied through the C language interface. For example, you may have supplied a NULL string for a cursor name.

Related Information

[SQL Anywhere C API Support Identifiers in UltraLite Identifiers](#)

1.1.4.621 Invalid sqlen field in SQLDA

Error constant	SQLE_INVALID_SQLLEN
ODBC 2 state	HY090
ODBC 3 state	HY090
Severity	16
SQLCODE	-856
SQLSTATE	07W08
Sybase error code	13859

Probable cause

An invalid length was specified in a SQLDA sqlen field. All variable length types must have a non-negative length. The DT_BINARY and DT_VARCHAR types must have length greater than one.

1.1.4.622 Invalid start date/time for event '%1'

Error constant	SQLE_INVALID_EVENT_START
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the event being scheduled.
Severity	15
SQLCODE	-793
SQLSTATE	WE007
Sybase error code	13803

Probable cause

You have specified an event starting date that is invalid.

1.1.4.623 Invalid start value for semaphore "%1": %2

Error constant	SQLE_INVALID_START_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the semaphore.
Parameter 2	The value specified.
Severity	16
SQLCODE	-1803
SQLSTATE	22031
Sybase error code	12341

Probable cause

The start value for a semaphore must be a non-negative integer.

1.1.4.624 Invalid statement

Error constant	SQLE_INVALID_STATEMENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-130
SQLSTATE	07W02
Sybase error code	13628

Probable cause

The prepared statement is invalid. In Embedded SQL, an OPEN or EXECUTE failed.

Related Information

[Prepared Statements Overview](#)

1.1.4.625 Invalid stoplist value

Error constant	SQLTEXT_INVALID_STOPLIST_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1391
SQLSTATE	WT025
Sybase error code	13181

Probable cause

The value specified for the stoplist is not valid.

1.1.4.626 Invalid storage format '%1'

Error constant	SQLSLERR_DDL_SRS_STGFORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid storage format string.
Severity	16
SQLCODE	-1470
SQLSTATE	2FW63
Sybase error code	13102

Probable cause

The specified storage format string is not valid.

1.1.4.627 Invalid text index type for the materialized view

Error constant	SQLTEXT_MV_INVALID_COMBO
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1552
SQLSTATE	WT037
Sybase error code	12553

Probable cause

Text index with the specified refresh type cannot be created on the materialized view. Only IMMEDIATE REFRESH text indexes are allowed on materialized views.

1.1.4.628 Invalid TEXTPTR value used with WRITETEXT or READTEXT

Error constant	SQL_INVALID_TEXTPTR_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-608
SQLSTATE	22W03
Sybase error code	7123

Probable cause

You supplied an invalid value as the TEXTPTR for a WRITETEXT or READTEXT statement.

1.1.4.629 Invalid time '%1' for event '%2'

Error constant	SQL_INVALID_EVENT_TIME
----------------	------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Time value.
Parameter 2	Name of the event being scheduled.
Severity	15
SQLCODE	-792
SQLSTATE	WE006
Sybase error code	13802

Probable cause

You have attempted to create a schedule with an invalid start or stop time.

1.1.4.630 Invalid timeout value %1

Error constant	SQLE_INVALID_TIMEOUT_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The timeout value specified.
Severity	16
SQLCODE	-1811
SQLSTATE	22033
Sybase error code	12333

Probable cause

The timeout specified in the statement must be a positive integer.

1.1.4.631 Invalid tolerance %1

Error constant	SQLE_SLERR_INVALID_TOLERANCE
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The invalid tolerance.
Severity	16
SQLCODE	-1500
SQLSTATE	2FW87
Sybase error code	13603

Probable cause

The specified tolerance cannot be used with the spatial reference system. The tolerance must be selected based on the bounds of space.

1.1.4.632 Invalid tool name or admin user for generating security token

Error constant	SQL_E_INVALID_TOOL_NAME_OR_ADMIN_USER
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-1585
SQLSTATE	08WB1
Sybase error code	12520

Probable cause

The tool name or admin user supplied is invalid for generating a security token.

1.1.4.633 Invalid transform definition '%1'

Error constant	SQL_E_SLERR_INVALID_TRANSFORM_DEF
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	The invalid transform definition string.
Severity	16
SQLCODE	-1442
SQLSTATE	2FW35
Sybase error code	13130

Probable cause

The provided string does not represent a valid transform definition.

1.1.4.634 Invalid trigger type for view '%1'

Error constant	SQL_E_INVALID_TRIGGER_VIEW
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Name of the view
Severity	14
SQLCODE	-1133
SQLSTATE	42W3C
Sybase error code	13380

Probable cause

You attempted to create a trigger on a view, but the type of trigger is supported on base tables only. Only INSTEAD OF triggers can be created on views.

1.1.4.635 Invalid type for field reference

Error constant	SQL_E_INVALID_FIELD_REFERENCE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-94
SQLSTATE	WW014
Sybase error code	13738

Probable cause

An expression attempted to reference a field or a method of a non-Java value. Field references via `.` and `>>` are only valid when applied to Java objects.

1.1.4.636 Invalid type on DESCRIBE statement

Error constant	SQLE_INVALID_DESCRIBE_TYPE
ODBC 2 state	OK
ODBC 3 state	OK
Severity	16
SQLCODE	-161
SQLSTATE	07W01
Sybase error code	13634

Probable cause

A Java type specified on a DESCRIBE statement has no corresponding SQL type.

1.1.4.637 Invalid use of an aggregate function

Error constant	SQLE_AGGREGATES_NOT_ALLOWED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-150
SQLSTATE	42W06
Sybase error code	13204

Probable cause

You attempted to use an aggregate function inappropriately. For example, a SELECT statement cannot contain an aggregate function within a predicate in the WHERE clause unless the aggregate function constitutes an outer reference. Other invalid uses include specifying an aggregate function in the SET clause of an UPDATE statement, or using an aggregate function in a CHECK constraint.

Related Information

[Aggregate Functions That Summarize Query Results](#)

[Aggregate Functions](#)

[Aggregate Functions](#)

1.1.4.638 Invalid use of BEFORE operator in text query

Error constant	SQLTEXT_INVALID_BEFORE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1591
SQLSTATE	WT040
Sybase error code	12514

Probable cause

Only terms and prefixes are allowed as arguments to a BEFORE operator.

1.1.4.639 Invalid use of collection type

Error constant	SQL_INVALID_USE_OF_COLLECTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1599

SQLSTATE	WW210
Sybase error code	12507

Probable cause

You tried to use an ARRAY or ROW type in an unsupported context. You cannot store these values in tables or read them directly from client interfaces such as ODBC, ESQL, and JDBC. You must extract the individual values you are interested in.

1.1.4.640 Invalid use of escape character '%1'

Error constant	SQLE_INVALID_USE_OF_ESCAPE_CHARACTER
ODBC 2 state	S1000
ODBC 3 state	2200C
Parameter 1	The escape character that is invalid.
Severity	16
SQLCODE	-1136
SQLSTATE	2200C
Sybase error code	13377

Probable cause

The specified escape character cannot be used.

1.1.4.641 Invalid use of NEAR operator in text query

Error constant	SQLE_TEXT_INVALID_NEAR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1207
SQLSTATE	WT016
Sybase error code	13308

Probable cause

Only terms and prefixes are allowed as arguments to a NEAR operator.

1.1.4.642 Invalid use of table reference type

Error constant	SQL_INVALID_USE_OF_TABLEREF
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1792
SQLSTATE	WW223
Sybase error code	12351

Probable cause

You tried to use a table reference type in an unsupported context. You cannot store these values in tables or read them directly from client interfaces such as ODBC, ESQL, and JDBC.

1.1.4.643 Invalid user ID or password

Error constant	SQL_INVALID_LOGON
ODBC 2 state	28000
ODBC 3 state	28000
Severity	14
SQLCODE	-103
SQLSTATE	28000
Sybase error code	4002

Probable cause

You supplied an invalid user ID or an incorrect password.

Related Information

[Users](#)

[UltraLite Users](#)

1.1.4.644 Invalid user ID or password on preprocessed module

Error constant	SQLE_INVALID_MODULE_LOGON
ODBC 2 state	28000
ODBC 3 state	28000
Severity	14
SQLCODE	-104
SQLSTATE	28W01
Sybase error code	4002

Probable cause

You specified an invalid user ID or password when a module was preprocessed.

1.1.4.645 Invalid user ID or role name '%1' specified

Error constant	SQLE_INVALID_USER_ROLE_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the invalid user or role that was specified.
Severity	14
SQLCODE	-1536
SQLSTATE	28W25
Sybase error code	12569

Probable cause

You supplied an invalid name for a user or role.

1.1.4.646 Invalid value for attribute '%1' in service

Error constant	SQLE_SERVICE_PARM_INVALID_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the invalid attribute.
Severity	16
SQLCODE	-1022
SQLSTATE	42WAD
Sybase error code	13488

Probable cause

The service definition contains a USING, FORMAT, or GROUP attribute with an invalid value.

1.1.4.647 Invalid value for INSERT near '%1' on line %2

Error constant	SQLE_INVALID_INSERT_VALUE
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The word or symbol where the invalid value has been detected.
Parameter 2	Line number.
Severity	15
SQLCODE	-1710
SQLSTATE	42W11
Sybase error code	12432

Probable cause

An invalid value was specified for a value in an INSERT statements.

1.1.4.648 Invalid value for login policy option "%1"

Error constant	SQLE_INVALID_LOGIN_POLICY_OPTION_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of login policy option.
Severity	16
SQLCODE	-1655
SQLSTATE	WW243
Sybase error code	12464

Probable cause

The value supplied for login policy option is not within valid bounds.

1.1.4.649 Invalid variable or type

Error constant	SQLE_PARSE_JSON_INVALID_VARIABLE_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1680
SQLSTATE	WX024
Sybase error code	12443

Probable cause

The named variable is invalid or of the wrong data type for the JSON result.

1.1.4.650 Invalid XQuery constructor

Error constant	SQLE_INVALID_XQUERY_CONSTRUCTOR
----------------	---------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-905
SQLSTATE	WX012
Sybase error code	13578

Probable cause

The XQuery constructor passed as the first argument to XMLGEN was not valid.

1.1.4.651 Item '%1' already exists

Error constant	SQL_E_NAME_NOT_UNIQUE
ODBC 2 state	S0001
ODBC 3 state	42S01
Parameter 1	Name of the item that already exists.
Severity	16
SQLCODE	-110
SQLSTATE	52010
Sybase error code	12006

Probable cause

You attempted to create a file, table, view, column, constraint, foreign key, publication, certificate, or OData Producer with the same name as an existing one.

1.1.4.652 JAR '%1' not found

Error constant	SQL_E_JAR_NOT_FOUND
ODBC 2 state	42000
ODBC 3 state	42000

Parameter 1	Name of the JAR.
Severity	16
SQLCODE	-811
SQLSTATE	42W58
Sybase error code	13821

Probable cause

The JAR with this name does not exist in the database.

1.1.4.653 Java VM heap exhausted at internal function: %1

Error constant	SQLE_JAVA_VM_HEAP_EXHAUSTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The internal function is for debugging purposes.
Severity	16
SQLCODE	-165
SQLSTATE	WP008
Sybase error code	13740

Probable cause

The amount of space allocated for the Java VM is insufficient to continue allocating new objects. Increase the size by using: SET OPTION PUBLIC.java_heap_size = nnnnnnnn.

1.1.4.654 jConnect does not support encryption

Error constant	SQLE_NO_ENCRYPTION_FOR_JCONNECT
ODBC 2 state	08004
ODBC 3 state	08004
Severity	18

SQLCODE	-941
SQLSTATE	08W69
Sybase error code	13548

Probable cause

You supplied an encryption type for a connection using jConnect. jConnect does not support encryption.

1.1.4.655 JSON array contains too many elements

Error constant	SQLE_PARSE_JSON_LIMIT_ARRAY_ELEMENTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1893
SQLSTATE	WX028
Sybase error code	12262

Probable cause

The JSON text contains an array with too many elements. The number of elements in an array is limited to 65535.

1.1.4.656 JSON nesting too deep

Error constant	SQLE_PARSE_JSON_LIMIT_NESTING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1900
SQLSTATE	WX026
Sybase error code	12260

Probable cause

The JSON text contains objects that are nested too deeply. The nesting depth is limited to 60000 levels.

1.1.4.657 JSON object contains too many properties

Error constant	SQLE_PARSE_JSON_LIMIT_OBJECT_PROPERTIES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1892
SQLSTATE	WX027
Sybase error code	12261

Probable cause

The JSON text contains an object with too many properties. The number of properties in an object is limited to 45000.

1.1.4.658 JWT Provider '%1' does not exist

Error constant	INVALID_JWT_PROVIDER_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the JWT provider name that could not be found.
Severity	16
SQLCODE	-2000
SQLSTATE	28W37
Sybase error code	12185

Probable cause

You used a JWT provider name that does not exist.

1.1.4.659 Kerberos login failed

Error constant	SQLE_KERBEROS_LOGON_FAILED
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-1069
SQLSTATE	28W12
Sybase error code	13445

Probable cause

The Kerberos login failed due to a failure of the client to authenticate the user's principal with the KDC or a failure of the server to authenticate the client. The most likely causes are the Kerberos principal may not be signed in, the principal's ticket may have expired, or the client, server, or KDC's system time are not within a few minutes of each other. The LogFile connection parameter or the server's -z option may provide more information.

1.1.4.660 Kerberos logins are not supported

Error constant	SQLE_KERBEROS_LOGONS_UNSUPPORTED
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-1070
SQLSTATE	28W13
Sybase error code	13444

Probable cause

The client and/or server does not support Kerberos logins. Kerberos may not be supported by the platform, the Kerberos client software including the GSS-API runtime may not be installed or found on the client, or Kerberos was not enabled on the server. The LogFile connection parameter or the server's -z option may provide more information.

1.1.4.661 Key constraint between temporary tables requires a primary key (not unique constraint)

Error constant	SQLI_INVALID_FOREIGN_KEY_INDEX
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-865
SQLSTATE	42R03
Sybase error code	1709

Probable cause

The key constraint between temporary tables requires a primary key (not a UNIQUE constraint) if the database uses combined indexes. Change the definition of the primary table using ALTER TABLE or rebuild the database.

1.1.4.662 Label '%1' not found

Error constant	SQLI_LABEL_NOT_FOUND
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the label that could not be found.
Severity	15
SQLCODE	-262
SQLSTATE	42W24
Sybase error code	133

Probable cause

You reference a label in a LEAVE statement, but the label could not be found.

1.1.4.663 Language '%1' is not supported, '%2' will be used

Error constant	SQLE_UNSUPPORTED_LANGUAGE
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	Name of the language that was requested by the client.
Parameter 2	Name of the language that the server will use to send message strings.
Severity	10
SQLCODE	116
SQLSTATE	01W14
Sybase error code	13615

Probable cause

The language that the application requested is not supported by the server to which the application is connecting. Instead, the server will send message strings in the language stated.

1.1.4.664 Language extension

Error constant	SQLE_LANGUAGE_EXTENSION
ODBC 2 state	37000
ODBC 3 state	ERROR
Severity	16
SQLCODE	-135
SQLSTATE	0AW01
Sybase error code	401

Probable cause

You used a SQL statement that may be valid in some versions of SQL, but not in SQL Anywhere.

1.1.4.665 Language extension detected in syntax near '%1' on line %2

Error constant	SQLE_SYNTAX_EXTENSION_WARNING
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	The word or symbol where the syntax has been detected.
Parameter 2	Line number.
Severity	10
SQLCODE	107
SQLSTATE	01W07
Sybase error code	5703

Probable cause

The statement you are executing contains syntax that is not allowed with the current setting of the option `SQL_FLAGGER_WARNING_LEVEL`. Modify the offending statement or set the `SQL_FLAGGER_WARNING_LEVEL` option to a different value.

Related Information

[sql_flagger_warning_level Option](#)

1.1.4.666 LDAP Server "%1" already exists

Error constant	SQLE_LDAPSERVER_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the LDAP Server.
Severity	16
SQLCODE	-1569
SQLSTATE	WW202
Sybase error code	12536

Probable cause

An attempt was made to create an LDAP server that already exists in the database.

1.1.4.667 LDAP server "%1" is in use by login policy "%2"

Error constant	SQLE_LDAPSERVER_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the LDAP server.
Parameter 2	The name of the login policy.
Severity	16
SQLCODE	-1576
SQLSTATE	WW206
Sybase error code	12529

Probable cause

The named login policy references the LDAP server. The login policy must be changed to avoid referencing the LDAP server before the LDAP server can be dropped. Otherwise, use `DROP LDAP SERVER <server name> WITH DROP ALL REFERENCES` to remove any references in login policies to the LDAP server.

1.1.4.668 LDAP server %1 may not accept anonymous binds

Error constant	SQLE_LDAPUA_ANONBINDERR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The LDAP server name or search URL specifying the search.
Severity	16
SQLCODE	-1621
SQLSTATE	WW218
Sybase error code	12485

Probable cause

An LDAPUA search or validate failed returning LDAP_INAPPROPRIATE_AUTH due to invalid settings for the target LDAP server. Check the access account values for the named LDAP server or search URL.

1.1.4.669 LDAP server definition of "%1" is incomplete. A search URL, access distinguished name, password, and authentication URL are required

Error constant	SQLE_LDAPSERVER_INCOMPLETE_DEF
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the LDAP server.
Severity	16
SQLCODE	-1594
SQLSTATE	WW208
Sybase error code	12511

Probable cause

The named LDAP server is missing one or more of the values required to search for a user's distinguished name or authenticate a user. Use ALTER LDAP SERVER <server name> to specify any missing values.

1.1.4.670 LDAP User Authentication feature is not supported in this database

Error constant	SQLE_LDAPUA_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1572
SQLSTATE	WW205
Sybase error code	12533

Probable cause

The current database is an older database and does not have catalog support for LDAP User Authentication feature. To use this feature, upgrade your database to the most recent version.

1.1.4.671 LineString must contain at least 2 points (near '%1')

Error constant	SQLE_SLERR_LINESTRING_MIN_POINTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value or method where the error was detected.
Severity	16
SQLCODE	-1483
SQLSTATE	2FW78
Sybase error code	13089

Probable cause

The linestring contains only a single point.

Related Information

[Supported Spatial Data Types and Their Hierarchy](#)

1.1.4.672 Listener type "%1" failed to initialize when starting a listener

Error constant	SQLE_START_LISTENER_PORT_INIT_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener type
Severity	16
SQLCODE	-1782

SQLSTATE	O8WE1
Sybase error code	12358

Probable cause

An error occurred during starting a listener.

1.1.4.673 Load-source for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_LOADTABLE_SOURCE_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1939
SQLSTATE	OAW36
Sybase error code	12238

Probable cause

The load-source specified for the LOAD TABLE statement is not supported when the LOAD TABLE statement is in the BEGIN PARALLEL WORK...END PARALLEL WORK statement. Only FROM and USING FILE are supported load-sources in this context.

1.1.4.674 LOAD TABLE ... WITH FILE NAME LOGGING not permitted on mirrored database

Error constant	SQL_LOAD_TABLE_ON_MIRRORED_DB
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1035
SQLSTATE	WL008
Sybase error code	13476

Probable cause

LOAD TABLE ... WITH FILE NAME LOGGING statements are not permitted when a database is being mirrored, since the file being loaded might not be accessible by the other server.

1.1.4.675 LOAD TABLE error: %1

Error constant	SQLE_LOAD_TABLE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Description of the failure encountered
Severity	16
SQLCODE	-1188
SQLSTATE	WL013
Sybase error code	13327

Probable cause

The LOAD TABLE statement failed. The message specifies the actual problem that occurred.

Related Information

[LOAD TABLE Statement](#)
[LOAD TABLE Statement \[UltraLite\]](#)

1.1.4.676 LOAD TABLE error: Invalid content encountered on row %1 of the data file

Error constant	SQLE_LOAD_TABLE_DATA_FILE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Line number of the data file where the invalid content occurred.
Severity	16
SQLCODE	-1496
SQLSTATE	WL017
Sybase error code	13606

Probable cause

The LOAD TABLE statement failed because a scanning error occurred on the indicated line of the data file specified in the statement. This error can occur if a line is truncated or if delimiters are missing.

Related Information

[LOAD TABLE Statement](#)

[LOAD TABLE Statement \[UltraLite\]](#)

1.1.4.677 LOAD TABLE is not allowed on a materialized view %1

Error constant	SQLE_LOAD_TABLE_ON_MATVIEW_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the materialized view on which load was attempted.
Severity	16
SQLCODE	-1190
SQLSTATE	WL014
Sybase error code	13325

Probable cause

LOAD TABLE statement is not allowed on a materialized view.

1.1.4.678 LOAD TABLE not allowed on temporary table which has foreign key references from another table

Error constant	SQL_E_INVALID_LOAD_TABLE_WITH_FOREIGN_KEY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1146
SQLSTATE	WL009
Sybase error code	13366

Probable cause

The LOAD TABLE statement removes all rows in a temporary table upon failure. If a temporary table being loaded caused an error then the foreign rows would be orphaned.

1.1.4.679 LOAD TABLE not allowed on temporary table with ON COMMIT DELETE ROWS

Error constant	SQL_E_INVALID_TEMP_TABLE_COMMIT_ACTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-993
SQLSTATE	WL007
Sybase error code	13496

Probable cause

The LOAD TABLE statement automatically commits at completion. If a temporary table being loaded was declared with ON COMMIT DELETE ROWS, the rows are discarded at completion.

1.1.4.680 LOAD TABLE not allowed: initialized immediate materialized view %1 depends on %2

Error constant	SQL_LOAD_TABLE_WITH_IMV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the dependent initialized immediate materialized view.
Parameter 2	Name of the table on which load was performed.
Severity	16
SQLCODE	-1191
SQLSTATE	WL015
Sybase error code	13324

Probable cause

LOAD TABLE is not permitted on any table that has dependent initialized immediate materialized views.

1.1.4.681 LOAD TABLE option '%1' not allowed with FORMAT %2

Error constant	SQL_INVALID_LOAD_TABLE_OPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the option.
Parameter 2	The load table format.
Severity	16
SQLCODE	-1289
SQLSTATE	WL016

Probable cause

The specified LOAD TABLE option is not meaningful for the LOAD TABLE FORMAT.

1.1.4.682 Local connection ID does not refer to the current database

Error constant	SQLC_LOCAL_CONNECTION_NOT_TO_CURRENT_DB
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-997
SQLSTATE	W0025
Sybase error code	710

Probable cause

The specified connection ID is for a connection to a database other than the current database.

1.1.4.683 Logging type ('%1') for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_LOADTABLE_LOGGING_TYPE_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified logging type.
Severity	16
SQLCODE	-1940

SQLSTATE	0AW37
Sybase error code	12237

Probable cause

The specified logging type for the LOAD TABLE statement is not supported when the statement is in the BEGIN PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.684 Login mode '%1' not permitted by login_mode setting

Error constant	SQL_E_LOGON_MODE_NOT_PERMITTED
ODBC 2 state	28000
ODBC 3 state	28000
Parameter 1	Name of the login mode not included in the current login_mode database option setting.
Severity	16
SQLCODE	-1074
SQLSTATE	28W14
Sybase error code	13440

Probable cause

You attempted to connect using a login mode not included in the current login_mode database option setting. Change the option setting or connect using a different login mode.

1.1.4.685 Login policies are not supported for this database

Error constant	SQL_E_LOGIN_POLICY_UPGRADE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1196

SQLSTATE	WW099
Sybase error code	13319

Probable cause

The current database does not have catalog support for login policies. To use this feature, upgrade your database to the most recent version.

1.1.4.686 Login policy "%1" already exists

Error constant	SQLE_LOGIN_POLICY_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the login policy.
Severity	16
SQLCODE	-1194
SQLSTATE	WW097
Sybase error code	13321

Probable cause

An attempt was made to create a login policy that already exists in the database.

1.1.4.687 Login policy "%1" in use

Error constant	SQLE_LOGIN_POLICY_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the login policy.
Severity	16
SQLCODE	-1197
SQLSTATE	WW100

Probable cause

The named login policy is associated with a user in the database. Any users associated with the login policy must be assigned a different login policy before the named login policy can be dropped.

1.1.4.688 Login policy "%1" not found

Error constant	SQLE_LOGIN_POLICY_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the login policy.
Severity	16
SQLCODE	-1195
SQLSTATE	WW098
Sybase error code	13320

Probable cause

The named login policy was not found in the database.

1.1.4.689 Login redirection is required to complete the connection, but it is not supported by the client

Error constant	SQLE_LOGIN_REDIRECTION_REQUIRED
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-1551
SQLSTATE	08WA6
Sybase error code	12554

Probable cause

The connection needs to be redirected to another server, but the version of the client library does not support login redirection. You must upgrade the client library to use login redirection. Alternatively, you can connect to a different server or change the logical server configuration.

Related Information

[External Environment Support](#)
[START EXTERNAL ENVIRONMENT Statement](#)

1.1.4.690 Maintenance of dependent immediate materialized view(s) failed

Error constant	SQLE_MAINTENANCE_OF_IMV_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1219
SQLSTATE	42WC8
Sybase error code	13298

Probable cause

Maintenance of immediate materialized view(s) dependent on the base table failed.

1.1.4.691 Materialized View '%1' not found

Error constant	SQLE_MATVIEW_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the materialized view that could not be found.
Severity	11

SQLCODE	-1041
SQLSTATE	42WB5
Sybase error code	13470

Probable cause

You misspelled the name of a materialized view, or you did not qualify a materialized view name with a user name. For example, you might have referred to "mat_view" instead of "owner"."mat_view".

1.1.4.692 Maximum row size for table '%1' would be exceeded

Error constant	SQLE_MAX_ROW_SIZE_EXCEEDED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Table name.
Severity	16
SQLCODE	-1132
SQLSTATE	WW089
Sybase error code	13381

Probable cause

You tried to create or alter a table with a maximum row size greater than 64 KB. In UltraLite, tables must be defined such that the maximum row size (the sum of the bytes required to store each column) is less than 64 KB.

Related Information

[Physical Limitations on Size and Number of Databases](#)
[UltraLite Database Limitations](#)
[UltraLite Tables and Columns](#)
[UltraLite Database Limitations](#)

1.1.4.693 Maximum string length exceeded

Error constant	SQL_E_MAX_STRING_LENGTH_EXCEEDED
ODBC 2 state	37000
ODBC 3 state	54000
Severity	15
SQLCODE	-1313
SQLSTATE	54W17
Sybase error code	13266

Probable cause

A string operation attempted to create a string longer than the maximum allowed by the server. Strings must not exceed 2147483647 bytes in length.

1.1.4.694 Memory error -- transaction rolled back

Error constant	SQL_E_MEMORY_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	24
SQLCODE	-309
SQLSTATE	40W08
Sybase error code	3013

Probable cause

The UltraLite runtime has received an unexpected error from the system calls being used to store the UltraLite database. For example, a write to persistent memory failed. This is an internal error and indicates faulty or corrupt persistent storage on the device. A ROLLBACK statement has been automatically executed.

Related Information

[UltraLite Transaction Processing](#)

1.1.4.695 MERGE statement ANSI cardinality violation on table '%1'

Error constant	SQL_E_MERGE_CARDINALITY_VIOLATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the table being updated
Severity	16
SQLCODE	-1211
SQLSTATE	23509
Sybase error code	13304

Probable cause

You have attempted to execute the MERGE statement and the same row is the target of a WHEN MATCHED clause more than once.

1.1.4.696 MERGE statement for table '%1' failed because of a RAISERROR specification in the statement

Error constant	SQL_E_MERGE_USER_SPECIFIED_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the table being merged into
Severity	16
SQLCODE	-1254
SQLSTATE	23510
Sybase error code	13259

Probable cause

You have attempted to execute a MERGE statement that contains the RAISERROR clause in one or more merge operation branches and one of the input rows satisfies the conditions for one of these branches.

1.1.4.697 Method '%1' cannot be called at this time

Error constant	SQLE_METHOD_CANNOT_BE_CALLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the method.
Severity	16
SQLCODE	-669
SQLSTATE	WJ001
Sybase error code	13711

Probable cause

The method cannot be called at this time. Check that the method is not being called out of order.

1.1.4.698 Method '%1' cannot be called with %2 arguments (near '%3')

Error constant	SQLE_METHOD_NO_OVERLOAD_N_ARGS
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The name of the method.
Parameter 2	The number of arguments supplied.
Parameter 3	The invalid expression.
Severity	11
SQLCODE	-1339
SQLSTATE	42X04
Sybase error code	13217

Probable cause

No overload of the specified method can be called with the number of arguments provided.

1.1.4.699 Method invocation '%1' does not match an overload (near '%2'). Available overloads are '%3'

Error constant	SQLE_METHOD_NO_OVERLOAD
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The method name and data types used in the method invocation.
Parameter 2	The invalid expression.
Parameter 3	The available method overloads.
Severity	11
SQLCODE	-1337
SQLSTATE	42X02
Sybase error code	13219

Probable cause

When attempting to match a method invocation, none of the defined overloads was found to match the provided argument types. You may need to use CAST to select the appropriate call.

1.1.4.700 Mirror child server creation failed

Error constant	SQLE_CHILD_SERVER_CREATION_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1351
SQLSTATE	WW154
Sybase error code	13206

Probable cause

The creation of a child server on the primary server failed or was disallowed.

1.1.4.701 Mirror file requires higher checksum_level

Error constant	SQLE_MIRROR_FILE_REQUIRES_CHECKSUMS
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	144
SQLSTATE	WW116
Sybase error code	13274

Probable cause

To effectively protect against media failures, page checksums must be enabled when using the mirror file. Specify the checksum_level database creation option.

Related Information

[UltraLite checksum_level Creation Option](#)

1.1.4.702 Mirror server "%1" already exists

Error constant	SQLE_MIRROR_SERVER_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the mirror server.
Severity	16
SQLCODE	-1309
SQLSTATE	WW132
Sybase error code	13365

Probable cause

An attempt was made to create a mirror server that already exists in the database.

1.1.4.703 Mirror server "%1" defined with type COPY does not include a parent definition

Error constant	SQL_E_COPY_SERVER_NEEDS_PARENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The mirror server name
Severity	16
SQLCODE	-1505
SQLSTATE	42WE6
Sybase error code	13135

Probable cause

In a CREATE MIRROR SERVER statement for a server with type COPY, a parent server is not defined.

Related Information

[How Child Copy Nodes Are Added](#)
[CREATE MIRROR SERVER Statement](#)

1.1.4.704 Mirror server "%1" is not a valid parent server

Error constant	SQL_E_INVALID_MIRROR_PARENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the mirror server.
Severity	16
SQLCODE	-1312
SQLSTATE	WW135
Sybase error code	13267

Probable cause

An attempt was made to define a parent for a mirror server that would result in a cycle.

1.1.4.705 Mirror server "%1" is referenced by another server

Error constant	SQLE_MIRROR_SERVER_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the mirror server.
Severity	16
SQLCODE	-1310
SQLSTATE	WW133
Sybase error code	13364

Probable cause

An attempt was made to drop a mirror server that is referenced by another mirror server in the database.

1.1.4.706 Mirror server "%1" not found

Error constant	SQLE_MIRROR_SERVER_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the mirror server.
Severity	16
SQLCODE	-1308
SQLSTATE	WW131
Sybase error code	13409

Probable cause

The named mirror server was not found in the database.

1.1.4.707 MIRROR server class is not supported for SAP IQ databases

Error constant	SQLE_OMNI_NO_MIRROR_FOR_IQ
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1573
SQLSTATE	W0029
Sybase error code	12532

Probable cause

You attempted to create a remote data access server of type MIRROR while connected to an SAP IQ database. The MIRROR server class is not supported for SAP IQ databases.

1.1.4.708 Mirror server name '%1' does not match current server name

Error constant	SQLE_INVALID_CHILD_SERVER_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The server name
Severity	16
SQLCODE	-1348
SQLSTATE	WW151
Sybase error code	13209

Probable cause

The server name specified in a CREATE MIRROR SERVER statement must match the current server name when the statement is executed on a child server.

1.1.4.709 Mirror server with type '%1' is already defined

Error constant	SQLE_MIRROR_SERVER_TYPE_ALREADY_DEFINED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The server type
Severity	16
SQLCODE	-1352
SQLSTATE	WW155
Sybase error code	13205

Probable cause

A CREATE MIRROR SERVER statement specified a server type that has already been defined.

1.1.4.710 Missing value for attribute '%1' in service

Error constant	SQLE_SERVICE_PARM_MISSING_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the invalid attribute.
Severity	16
SQLCODE	-1023
SQLSTATE	42WAE
Sybase error code	13487

Probable cause

The service definition contains a USING, FORMAT, or GROUP attribute with a missing value.

1.1.4.711 Mixed coordinate dimensions

Error constant	SQLE_SLERR_MIXED_DIM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1408
SQLSTATE	2FF25
Sybase error code	13164

Probable cause

The method contains geometries that have a mixture of coordinate dimensions (Z and M values).

1.1.4.712 Mixed spatial reference systems %1 and %2 (near %3)

Error constant	SQLE_SLERR_MIXED_SRS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The SRID of the first spatial reference system.
Parameter 2	The SRID of the second spatial reference system.
Parameter 3	The value or method where the mixed spatial reference systems were detected.
Severity	16
SQLCODE	-1402
SQLSTATE	2FF10
Sybase error code	13170

Probable cause

The method does not support working with geometries from different spatial reference systems.

1.1.4.713 MobiLink communication error -- code: %1, parameter: %2, system code: %3

Error constant	SQLE_MOBILINK_COMMUNICATIONS_ERROR
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The MobiLink communication error code.
Parameter 2	The parameter to the MobiLink communication error if one exists.
Parameter 3	The system error code.
Severity	16
SQLCODE	-1305
SQLSTATE	0AWD5
Sybase error code	13454

Probable cause

An error was encountered while communicating with a MobiLink server.

Related Information

[MobiLink Communication Error Messages Sorted by Error Code \[page 1185\]](#)

1.1.4.714 Modifications not permitted for read-only database

Error constant	SQLE_READ_ONLY_DATABASE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	14
SQLCODE	-757
SQLSTATE	55W08
Sybase error code	13768

Probable cause

You attempted an update operation on a database that was declared as read-only.

1.1.4.715 More articles are being dropped from publication '%1' than are defined

Error constant	SQLE_TOO_MANY_ARTICLES_DELETED
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the publication from which the article could not be dropped.
Severity	16
SQLCODE	-1318
SQLSTATE	42W89
Sybase error code	13238

Probable cause

The number of articles in a publication can never fall below one. Your ALTER PUBLICATION has more drop/delete article clauses than the current number of articles in the publication.

1.1.4.716 More information required

Error constant	SQLE_MORE_INFO
ODBC 2 state	37000
ODBC 3 state	OK
Severity	10
SQLCODE	112
SQLSTATE	01W09
Sybase error code	13686

Probable cause

More information is required to complete the request. This is used internally in the database interface library to process a unified login. It should not be returned to an application.

1.1.4.717 More than one table is identified as '%1'

Error constant	SQL_E_CORRELATION_NAME_AMBIGUOUS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Ambiguous correlation name.
Severity	16
SQLCODE	-139
SQLSTATE	52012
Sybase error code	7364

Probable cause

You identified two tables in the same FROM clause with the same correlation name.

1.1.4.718 Multiple consolidated users cannot be defined

Error constant	SQL_E_CONSOLIDATED_USER_ALREADY_EXISTS
ODBC 2 state	S0002
ODBC 3 state	42S02
Severity	16
SQLCODE	-289
SQLSTATE	5RW10
Sybase error code	13767

Probable cause

You attempted to grant consolidated permissions when your database already has a consolidated user, or attempted to grant consolidated permissions to multiple users in a single statement.

1.1.4.719 Multiple settings of same option specified for sequence '%1'

Error constant	SQLD_DUPLICATE_SEQUENCE_OPTION
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the sequence.
Severity	16
SQLCODE	-1357
SQLSTATE	52W50
Sybase error code	13203

Probable cause

Multiple settings of the same sequence option have been specified in the sequence definition. Even if the setting is the same, you can only specify each option once.

1.1.4.720 Multiple table parameters are not supported

Error constant	SQLD_ONLY_SINGLE_TABLE_PARM_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1606
SQLSTATE	WPO21
Sybase error code	12501

Probable cause

Table parameterized functions are limited to only having at most a single table parameter.

1.1.4.721 Must include primary key for table '%1' in the synchronization

Error constant	SQLE_PK_NOT_IN_SYNC_ARTICLE
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	Name of the table.
Severity	16
SQLCODE	-778
SQLSTATE	5RW17
Sybase error code	13788

Probable cause

The primary key of the table must be included in the synchronization entry.

1.1.4.722 Must own table '%1' to make an immediate view reference it

Error constant	SQLE_NO_PERMS_FOR_IMV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the table
Severity	16
SQLCODE	-1270
SQLSTATE	42WD3
Sybase error code	13754

Probable cause

You have attempted to change the refresh type of a materialized view to immediate and the view references a table that is not owned by you. To perform this operation, you must either own all the tables referenced by the materialized view or have DBA privileges.

1.1.4.723 Mutex "%1" is locked by another connection

Error constant	SQLE_MUTEX_LOCKED_NO_REPLACE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Mutex name.
Severity	16
SQLCODE	-1831
SQLSTATE	WW150
Sybase error code	12313

Probable cause

You attempted to replace a mutex that is locked by another connection. A mutex can only be replaced when not held by a connection other than the current connection.

1.1.4.724 Mutex "%1" not found

Error constant	SQLE_MUTEX_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of mutex that could not be found.
Severity	11
SQLCODE	-1807
SQLSTATE	55W53
Sybase error code	12337

Probable cause

You misspelled the name of a mutex, or the mutex does not exist.

1.1.4.725 Mutex "%1" was not locked by this connection

Error constant	SQLE_MUTEX_NOT_LOCKED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Mutex name.
Severity	16
SQLCODE	-1813
SQLSTATE	WW149
Sybase error code	12331

Probable cause

You attempted to release a mutex that was not previously locked by this connection.

1.1.4.726 Mutex "%1" with transaction scope cannot be released

Error constant	SQLE_NO_RELEASE_TRANSACTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Mutex name.
Severity	16
SQLCODE	-1812
SQLSTATE	55W55
Sybase error code	12332

Probable cause

Mutexes created with a transaction scope cannot be explicitly released. Locked transaction scope mutexes are released at commit or rollback time.

1.1.4.727 Mutex was dropped

Error constant	SQLE_MUTEX_DROPPED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1804
SQLSTATE	WPO27
Sybase error code	12340

Probable cause

The mutex this connection was attempting to lock was dropped during the wait. The mutex is no longer available. This could happen if the mutex was explicitly dropped, or if the connection owning the temporary mutex has disconnected.

1.1.4.728 NAMESPACE attribute is not valid with procedure type '%1'

Error constant	SQLE_INVALID_NAMESPACE_ATTRIBUTE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The NAMESPACE attribute on the procedure.
Severity	16
SQLCODE	-989
SQLSTATE	WW058
Sybase error code	13500

Probable cause

The NAMESPACE attribute is only applicable to procedures of type SOAP.

1.1.4.729 Namespace heap exhausted at internal function: %1

Error constant	SQLE_NAMESPACE_HEAP_EXHAUSTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The internal function is for debugging purposes.
Severity	16
SQLCODE	-164
SQLSTATE	WP007
Sybase error code	13739

Probable cause

The amount of space allocated for the Java Namespace is insufficient to continue loading Java classes. Increase the size by using: SET OPTION PUBLIC.java_namespace_size = nnnnnnnn.

1.1.4.730 Need a dynamic library name

Error constant	SQLE_REQUIRE_DLL_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-619
SQLSTATE	WW005
Sybase error code	13676

Probable cause

You must provide a library name specifier in the name of the external function to call.

1.1.4.731 Need a function entry point

Error constant	SQLE_REQUIRE_FUNCTION_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-1739
SQLSTATE	WW021
Sybase error code	12398

Probable cause

You must provide an entry point to an external function in a dynamically loaded module.

1.1.4.732 No column list for recursive query

Error constant	SQLE_NO_RECURSIVE_COLUMN_LIST
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-922
SQLSTATE	42W9A
Sybase error code	13562

Probable cause

A common table expression defining a recursive query must have a column list.

1.1.4.733 No current row of cursor

Error constant	SQLE_NO_CURRENT_ROW
ODBC 2 state	24000

ODBC 3 state	24000
Severity	16
SQLCODE	-197
SQLSTATE	24503
Sybase error code	560

Probable cause

You attempted to perform an operation on the current row of a cursor, but the cursor is not positioned on a row. The cursor is before the first row of the cursor, after the last row, or is on a row that has since been deleted.

Related Information

[Cursor Usage](#)

[Multiple Row Fetching](#)

1.1.4.734 No database file specified

Error constant	SQL_E_NO_DATABASE_FILE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	11
SQLCODE	-72
SQLSTATE	08W39
Sybase error code	4001

Probable cause

The database server was started but there was no specified database file. The server is stopped.

Related Information

[Database Starting and Stopping](#)

1.1.4.735 No entry point specified for the current system configuration

Error constant	SQLE_EXTERNAL_PLATFORM_FAILURE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-618
SQLSTATE	WW004
Sybase error code	13675

Probable cause

The call to an external entry point in a dynamically loaded module was not specified for the system configuration on which the server is currently executing.

1.1.4.736 No external backup identity found for archive file '%1' in HANA strategy document

Error constant	RESTORE_STRATEGY_NO_EBID_FOR_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	File name of the archive file for which external backup identity was not found.
Severity	16
SQLCODE	-1927
SQLSTATE	WB033
Sybase error code	12248

Probable cause

Could not find an external backup ID corresponding to an archive file while processing HANA backup strategy document.

1.1.4.737 No indicator variable provided for NULL result

Error constant	SQL_NO_INDICATOR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-181
SQLSTATE	22002
Sybase error code	13635

Probable cause

You tried to retrieve a value from the database that was NULL, but you did not provide an indicator variable for that value.

Related Information

[Embedded SQL Indicator Variables](#)
[Summary of Indicator Variable Values](#)
[Indicator Variables](#)

1.1.4.738 No matching text index

Error constant	SQL_TEXT_NO_MATCHING_INDEX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1158
SQLSTATE	WT003
Sybase error code	13355

Probable cause

A single text index must exist on all columns referenced in a CONTAINS query.

1.1.4.739 No more role grant permitted

Error constant	SQLE_ROLE_GRANT_ID_NOT_AVAILABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1528
SQLSTATE	28W19
Sybase error code	12577

Probable cause

Maximum limit for role grants has been reached. No more role grants are permitted. Remove some role grants and try again.

1.1.4.740 No more values available in sequence %1

Error constant	SQLE_SEQUENCE_EXHAUSTED
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the sequence.
Severity	16
SQLCODE	-1355
SQLSTATE	52W48
Sybase error code	13205

Probable cause

No more values can be supplied by the sequence; the next value to be supplied would be either larger than the maximum value, or smaller than the minimum value, and this sequence has been specified with NO CYCLE.

1.1.4.741 No name for argument

Error constant	SQLE_NO_SQLX_ARGUMENT_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-907
SQLSTATE	WX014
Sybase error code	13576

Probable cause

Unnamed arguments cannot be used as XML element or attribute names. Name unnamed items in the argument list using AS.

1.1.4.742 No notification within timeout on queue '%1'

Error constant	SQLE_EVENT_NOTIFICATION_QUEUE_TIMEOUT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the event notification queue
Severity	16
SQLCODE	-1266
SQLSTATE	WE017
Sybase error code	13244

Probable cause

The pending get-notification operation has timed out. No notification arrived before the given timeout elapsed.

Related Information

[ML_GET_SERVER_NOTIFICATION function \[System\]](#)

1.1.4.743 No partial download was found

Error constant	SQLE_PARTIAL_DOWNLOAD_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1103
SQLSTATE	WW075
Sybase error code	13411

Probable cause

A partial download was not found for the synchronizing user. This error could occur if trying to resume from a non-existent partial download or trying to rollback a non-existent partial download.

Related Information

[Resumption of Failed Downloads](#)

1.1.4.744 No primary key value for foreign key '%1' in table '%2'

Error constant	SQLE_INVALID_FOREIGN_KEY
ODBC 2 state	23000
ODBC 3 state	23000
Parameter 1	Name of the foreign key.
Parameter 2	Name of the table with the foreign key.
Severity	16
SQLCODE	-194
SQLSTATE	23503
Sybase error code	546

Probable cause

You attempted to insert or update a row that has a foreign key for another table. The value for the foreign key is not NULL and there is not a corresponding value in the primary key.

Related Information

[Integrity Checks on INSERT](#)
[LOAD TABLE Statement](#)
[INSERT Statement](#)
[LOAD TABLE Statement \[UltraLite\]](#)
[INSERT Statement \[UltraLite\]](#)

1.1.4.745 No running shared memory listener was found

Error constant	SQLLE_STOP_SHM_LISTENER_NOT_FOUND_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1780
SQLSTATE	08WD8
Sybase error code	12360

Probable cause

You attempted to stop the shared memory listener when it is not running.

1.1.4.746 No stored cache pages

Error constant	SQLLE_NO_STORED_CACHE_PAGES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1889

SQLSTATE	55W56
Sybase error code	12261

Probable cause

You executed ALTER DATABASE RESTORE CACHE but there were no stored cache pages. Use the ALTER DATABASE SAVE CACHE to save the contents of the cache.

1.1.4.747 No workload capture currently exists

Error constant	SQL_E_WORKLOAD_CAPTURE_DOES_NOT_EXIST
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-943
SQLSTATE	WW030
Sybase error code	13545

Probable cause

You have tried to stop, pause, resume, or get the status of a workload capture, but no workload captures exist.

1.1.4.748 Non-constant or unknown text query string

Error constant	SQL_E_TEXT_QUERY_NOT_KNOWN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1159
SQLSTATE	WT004
Sybase error code	13354

Probable cause

The query string argument to a CONTAINS query must be a constant, or a non-null value in a variable.

1.1.4.749 Non-contiguous curves near '%1'

Error constant	SQLE_SLERR_COMPOUNDCURVE_NOT_CONTIGUOUS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value or method where the non-contiguous curves were detected.
Severity	16
SQLCODE	-1403
SQLSTATE	2FF11
Sybase error code	13169

Probable cause

A compoundcurve geometry is composed of curves, and adjacent curves must be joined at their endpoints.

1.1.4.750 Not allowed while '%1' is using the database

Error constant	SQLE_MUST_BE_ONLY_CONNECTION
ODBC 2 state	40001
ODBC 3 state	40001
Parameter 1	Name of the connection that is using the database.
Severity	16
SQLCODE	-211
SQLSTATE	42W19
Sybase error code	13652

Probable cause

You attempted a data definition language operation that cannot be completed while another user is connected.

1.1.4.751 Not connected to a database

Error constant	SQLE_NOT_CONNECTED
ODBC 2 state	08003
ODBC 3 state	08003
Severity	16
SQLCODE	-101
SQLSTATE	08003
Sybase error code	13622

Probable cause

You are not connected to a database, or you executed the DISCONNECT statement and have not connected to a database again.

1.1.4.752 Not enough fields allocated in SQLDA

Error constant	SQLE_SQLDA_TOO_SMALL
ODBC 2 state	07001
ODBC 3 state	07002
Severity	16
SQLCODE	-182
SQLSTATE	07002
Sybase error code	13636

Probable cause

There are not enough fields in the SQLDA to retrieve all of the values requested.

1.1.4.753 Not enough free space on device to grow dbspace '%1' by requested amount

Error constant	SQLE_NO_ROOM_TO_GROW_DBSPACE
----------------	------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the dbspace
Severity	16
SQLCODE	-1121
SQLSTATE	57W03
Sybase error code	13392

Probable cause

You attempted to grow a dbspace using the ALTER DBSPACE statement, but there is not enough free space on the device to grow by the amount specified.

1.1.4.754 Not enough memory to start

Error constant	SQLLE_NO_MEMORY
ODBC 2 state	S1001
ODBC 3 state	HY001
Severity	17
SQLCODE	-86
SQLSTATE	08W13
Sybase error code	708

Probable cause

The database server started, but stopped because there was not enough memory.

1.1.4.755 Not enough values for host variables

Error constant	SQLLE_NOT_ENOUGH_HOST_VARS
ODBC 2 state	07001
ODBC 3 state	07002

Severity	16
SQLCODE	-188
SQLSTATE	07001
Sybase error code	13638

Probable cause

You have not provided enough host variables for either the number of bind variables, or the statement, or the number of SELECT list items.

1.1.4.756 NULL attribute mismatch for column '%1'

Error constant	SQLE_OMNI_NULL_MISMATCH
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The name of the column.
Severity	16
SQLCODE	-724
SQLSTATE	W0018
Sybase error code	11211

Probable cause

The NULL attribute of the column specified in the CREATE EXISTING statement differs from the NULL attribute of the actual column.

1.1.4.757 Null value eliminated in aggregate function

Error constant	SQLE_NULL_VALUE_ELIMINATED
ODBC 2 state	01000
ODBC 3 state	01003
Severity	10
SQLCODE	109

SQLSTATE	01003
Sybase error code	409

Probable cause

The expression argument of the aggregate function evaluated to NULL for one or more rows.

1.1.4.758 Number of columns allowing NULLs exceeds limit

Error constant	SQL_E_TOO_MANY_NULL_COLUMNS
ODBC 2 state	23000
ODBC 3 state	23000
Severity	16
SQLCODE	-733
SQLSTATE	23504
Sybase error code	233

Probable cause

You attempted to create or modify a table definition such that the number of columns that allow NULLS is now more than the limit on such columns. The limit is a function of database page size and is approximately $8 * (\text{page-size} - 30)$.

1.1.4.759 Number of columns defined for the table does not match SELECT statement

Error constant	SQL_E_TABLE_DEFINITION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1737
SQLSTATE	21W02
Sybase error code	12400

Probable cause

You attempted to create a table from a SELECT statement, but the column name list specified as part of the CREATE TABLE statement does not correspond to the list of items in the AS SELECT statement.

1.1.4.760 Number of columns defined for the view does not match SELECT statement

Error constant	SQL_E_VIEW_DEFINITION_ERROR
ODBC 2 state	21S02
ODBC 3 state	21S02
Severity	20
SQLCODE	-114
SQLSTATE	53011
Sybase error code	4409

Probable cause

You attempted to create a view, but the column list specified as part of the CREATE VIEW statement does not correspond to the list of items in the view's SELECT statement.

1.1.4.761 OData Producer '%1' not found

Error constant	SQL_E_ODATA_PRODUCER_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the OData Producer that could not be found
Severity	16
SQLCODE	-1773
SQLSTATE	55W46
Sybase error code	12367

Probable cause

You misspelled the name of an OData Producer, or the Producer does not exist.

1.1.4.762 OData Producer option error: %1

Error constant	SQLE_ODATA_PRODUCER_OPTION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Text of the option error
Severity	16
SQLCODE	-1774
SQLSTATE	55W47
Sybase error code	12366

Probable cause

An option error was found when creating or altering an OData Producer.

1.1.4.763 Offline reset password failed: %1

Error constant	OFFLINE_RESET_PASSWORD_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The reason the password could not be reset, if known.
Severity	16
SQLCODE	-1992
SQLSTATE	28W40
Sybase error code	12192

Probable cause

You attempted to reset a password for a user, but the reset failed or was denied.

1.1.4.764 Offline reset password is not allowed for user ID '%1' that has no password

Error constant	OFFLINE_RESET_PASSWORD_NOT_ALLOWED_NULL_PASSWORD_USER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the user whose password is being reset
Severity	16
SQLCODE	-1993
SQLSTATE	28W41
Sybase error code	12191

Probable cause

You attempted to reset the password for a user ID that has no password.

1.1.4.765 Offline reset password not supported

Error constant	OFFLINE_RESET_PASSWORD_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1994
SQLSTATE	0AW48
Sybase error code	12190

Probable cause

The current database is an older database and does not have support for offline reset password. To use this feature, upgrade your database to the most recent version.

1.1.4.766 One or more targets in the trace event session '%1' failed to start

Error constant	SQLE_ONE_OR_MORE_TRACE_SESSION_TARGETS_FAILED_TO_START
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Severity	11
SQLCODE	-1642
SQLSTATE	WE027
Sybase error code	12469

Probable cause

The specified trace event session is already active.

1.1.4.767 Only one IDENTIFIED BY value may be specified

Error constant	SQLE_LDAPUA_TOO_MANY_IDENTBY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1629
SQLSTATE	WW241
Sybase error code	12477

Probable cause

The LDAP server is specified with more than one password or is specified with both IDENTIFIED BY and IDENTIFIED BY ENCRYPTED. Set only one password.

1.1.4.768 Only PUBLIC settings are allowed for option '%1'

Error constant	SQL_E_NOT_PUBLIC_ID
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the option.
Severity	16
SQLCODE	-202
SQLSTATE	42W43
Sybase error code	13685

Probable cause

The option specified in the SET OPTION statement is PUBLIC only. You cannot define this option for any other user.

1.1.4.769 Operation '%1' failed for reason: '%2'

Error constant	SQL_E_ULTRALITEJ_OPERATION_FAILED
ODBC 2 state	ERROR
ODBC 3 state	42000
Parameter 1	The name of the operation.
Parameter 2	The cause of the failure.
Severity	16
SQLCODE	-1279
SQLSTATE	WW231
Sybase error code	13808

Probable cause

The requested operation failed.

1.1.4.770 Operation cannot be performed while AUTOCOMMIT_DDL is 'OFF'

Error constant	NOT_PERMITTED_AUTOCOMMIT_DDL_OFF
ODBC 2 state	OK
ODBC 3 state	OK
Severity	16
SQLCODE	-1977
SQLSTATE	0A008
Sybase error code	12205

Probable cause

You tried to perform an operation that is not supported while AUTOCOMMIT_DDL is 'OFF'.

1.1.4.771 Operation conflict with publication type

Error constant	SQLC_CONFLICTING_PUB_TYPE
ODBC 2 state	42000
ODBC 3 state	42S02
Severity	16
SQLCODE	-1060
SQLSTATE	5RW38
Sybase error code	13453

Probable cause

You attempted to perform an operation not applicable to the type of publication. For example, you applied operations specific to a scripted upload publication to a logscan publication.

1.1.4.772 Operation failed - could not complete checkpoint

Error constant	OPERATION_FAILED
----------------	------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	18
SQLCODE	-1969
SQLSTATE	40W10
Sybase error code	12213

Probable cause

You attempted to perform an operation that requires a checkpoint. However, the checkpoint could not complete due to another operation that was running concurrently. Retry the operation you requested.

1.1.4.773 Operation failed because table or view '%1' has an INSTEAD OF trigger

Error constant	SQL_E_INSTEAD_TRIGGER
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the view or table with an INSTEAD OF trigger
Severity	15
SQLCODE	-1126
SQLSTATE	42W3A
Sybase error code	13387

Probable cause

You attempted an operation that cannot succeed because an INSTEAD OF trigger is defined on a target table or view (possibly nested in another view).

Related Information

[CREATE VIEW Statement](#)
[ALTER VIEW Statement](#)

1.1.4.774 Operation is not allowed

Error constant	SQLLE_ULTRALITEJ_OPERATION_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	42000
Severity	16
SQLCODE	-1278
SQLSTATE	WW230
Sybase error code	13846

Probable cause

The requested operation is not allowed while schema is being modified.

1.1.4.775 Operation not allowed on a table with dependent immediate materialized views

Error constant	SQLLE_INVALID_OPERATION_FOR_TBL_WITH_IMV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1202
SQLSTATE	55W31
Sybase error code	13313

Probable cause

Requested operation cannot be applied to a table with dependent immediate materialized views.

1.1.4.776 Operation not supported for ST_GeomCollection with intersecting elements (near "%1")

Error constant	SQLE_SLERR_GEOM_COLL_INTERSECT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The method or context where the invalid ST_GeomCollection was detected.
Severity	16
SQLCODE	-1503
SQLSTATE	2FW90
Sybase error code	13197

Probable cause

The ST_GeomCollection contains elements that intersect in a way that is not valid for an ST_MultiSurface. The operation is not supported for this kind of geometry.

Related Information

[ST_GeomCollection Type](#)

[ST_MultiSurface Type](#)

1.1.4.777 Operation would cause a group cycle

Error constant	SQLE_GROUP_CYCLE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-122
SQLSTATE	42W02
Sybase error code	314

Probable cause

You attempted to add a member to group that would result in a member belonging to itself. The membership may be direct or indirect.

1.1.4.778 Operation would cause a role cycle

Error constant	SQL_ROLE_CYCLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	14
SQLCODE	-1540
SQLSTATE	28W29
Sybase error code	12565

Probable cause

You attempted to grant role to a grantee that would result in a grantee belonging to itself. Role membership may be direct or indirect.

1.1.4.779 Option '%1' cannot be used with HSQL COMPATIBLE

Error constant	ILLEGAL_OPTION_WITH_HSQL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the invalid option
Severity	16
SQLCODE	-1950
SQLSTATE	08WFA
Sybase error code	12227

Probable cause

You are trying to use an option that is unsupported on an HSQL-compatible database.

1.1.4.780 Option '%1' specified more than once

Error constant	SQL_E_DUPLICATE_OPTION
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The name of the duplicated option.
Severity	10
SQLCODE	139
SQLSTATE	01W26
Sybase error code	13415

Probable cause

A particular option has been specified multiple times. Only the last instance of the option is used; the previous ones are ignored.

Related Information

[UltraLite Connection Strings and Parameters](#)

[UltraLite Synchronization Parameters](#)

[UltraLite Network Protocol Options](#)

[UltraLite Synchronization Profile Options](#)

1.1.4.781 ORDER BY not allowed in window '%1'

Error constant	SQL_E_ORDERBY_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the window.
Severity	16

SQLCODE	-949
SQLSTATE	42WA5
Sybase error code	13539

Probable cause

When an existing window name is referenced from an inline window specification, either the inline window or the referenced window may have an ORDER BY, but not both.

1.1.4.782 Outer reference not permitted in DML derived table

Error constant	SQLE_SELECT_DML_OUTER_REFERENCE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1529
SQLSTATE	42U09
Sybase error code	12576

Probable cause

Outer references are not permitted in derived tables based on INSERT, UPDATE, DELETE, or MERGE statements. These derived tables may only appear in subqueries that are uncorrelated.

1.1.4.783 Outer references are not allowed for TPF input tables

Error constant	SQLE_TPF_OUTER_REFERENCES_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1607
SQLSTATE	WP022

Probable cause

Outer references in the select list for a TPF input table are not allowed.

1.1.4.784 Output file cannot be written

Error constant	SQLE_CANNOT_WRITE_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	20
SQLCODE	-979
SQLSTATE	WW048
Sybase error code	13510

Probable cause

Unable to create or write an output file. The file may be locked or read-only.

1.1.4.785 Owner '%1' used in a qualified column reference does not match correlation name '%2'

Error constant	SQLE_INVALID_COLUMN_QUALIFICATION
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The owner name specified in the column reference.
Parameter 2	The correlation name that is incorrectly referenced.
Severity	15
SQLCODE	-845
SQLSTATE	42U02
Sybase error code	13851

Probable cause

Your query contains a qualified column reference to a table name, but either a correlation name has been used for that table, or the owner of the table does not match the owner name specified in the column reference. Remove the owner qualification, and qualify column references only by correlation name.

1.1.4.786 Parameter '%1' cannot be null

Error constant	SQLE_PARAMETER_CANNOT_BE_NULL
ODBC 2 state	ERROR
ODBC 3 state	42000
Parameter 1	Name of the parameter.
Severity	16
SQLCODE	-1277
SQLSTATE	WW229
Sybase error code	13862

Probable cause

The specified parameter cannot be null.

1.1.4.787 Parameter '%1' in procedure or function '%2' does not have a default value

Error constant	SQLE_NO_DEFAULT_FOR_PARM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the parameter.
Parameter 2	The name of the procedure or function.
Severity	16
SQLCODE	-1001
SQLSTATE	08W71
Sybase error code	13491

Probable cause

An attempt was made to use DEFAULT as a procedure or function argument, but the corresponding parameter does not have a default value.

1.1.4.788 Parameter '%1' not found in procedure '%2'

Error constant	SQLE_INVALID_PARAMETER_NAME
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the parameter that was not found.
Parameter 2	Name of the procedure where the parameter was not found.
Severity	16
SQLCODE	-615
SQLSTATE	42W47
Sybase error code	201

Probable cause

You supplied a procedure parameter name that does not match a parameter for this procedure. Check the spelling of the parameter name.

1.1.4.789 Parameter name missing in call to procedure '%1'

Error constant	SQLE_PARAMETER_NAME_MISSING
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The name of the procedure.
Severity	16
SQLCODE	-639
SQLSTATE	42W42
Sybase error code	201

Probable cause

Positional parameters were specified after named parameters in a call to this procedure.

1.1.4.790 Parent not open: '%1'

Error constant	SQLE_EXPLICIT_TAG_NOT_OPEN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The parent tag ID that is not among the open tags.
Severity	16
SQLCODE	-900
SQLSTATE	WX008
Sybase error code	13581

Probable cause

FOR XML EXPLICIT and FOR JSON EXPLICIT require the parent tag for a row to be opened when that row is read. Check the order of the rows returned by the query with the FOR XML EXPLICIT or FOR JSON EXPLICIT clause removed.

Related Information

[FOR XML EXPLICIT](#)
[FOR JSON EXPLICIT](#)

1.1.4.791 Parse error: %1

Error constant	SQLE_INVALID_PARSE_PARAMETER
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	Description of the parsing error.
Severity	18

SQLCODE	-95
SQLSTATE	08W49
Sybase error code	5864

Probable cause

An error occurred while parsing a connection string.

1.1.4.792 Parse error: %1

Error constant	SQLE_INVALID_DSN_NAME
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	The invalid data source name.
Severity	18
SQLCODE	-754
SQLSTATE	08W54
Sybase error code	5864

Probable cause

An invalid data source name was used in the connection string.

Related Information

[Connection Parameters and Connection Strings](#)
[Alphabetical List of Connection Parameters](#)
[UltraLite Connection Strings and Parameters](#)
[UltraLite Connection Parameters](#)

1.1.4.793 PARTITION BY not allowed in reference to window '%1'

Error constant	SQLE_PARTITIONBY_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the window.
Severity	16
SQLCODE	-948
SQLSTATE	42WA4
Sybase error code	13540

Probable cause

When an existing window name is referenced from an inline window specification, the inline specification must not have a PARTITION BY clause.

1.1.4.794 Passthrough statement inconsistent with current passthrough

Error constant	SQLE_PASSTHROUGH_INCONSISTENT
ODBC 2 state	S0002
ODBC 3 state	42S02
Severity	16
SQLCODE	-287
SQLSTATE	5RW08
Sybase error code	13649

Probable cause

Passthrough is additive, in that subsequent PASSTHROUGH statements add to the list of users receiving passthrough. The PASSTHROUGH statements must all be PASSTHROUGH ONLY or none should be PASSTHROUGH ONLY.

1.1.4.795 Password cannot be longer than %1 characters

Error constant	SQLE_PASSWORD_TOO_LONG
ODBC 2 state	37000
ODBC 3 state	54000
Parameter 1	Maximum length of password.
Severity	15
SQLCODE	-958
SQLSTATE	54W08
Sybase error code	13530

Probable cause

The password is longer than that allowed by the server.

1.1.4.796 Password contains an illegal character

Error constant	SQLE_ILLEGAL_PASSWORD
ODBC 2 state	28000
ODBC 3 state	28000
Severity	11
SQLCODE	-963
SQLSTATE	08005
Sybase error code	13528

Probable cause

The specified password contains an illegal character.

1.1.4.797 Password encryption failed. Error message '%1'

Error constant	SQLE_PWD_CIPHER_ERROR
----------------	-----------------------

ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The error message reported by block encrypter.
Severity	16
SQLCODE	-1601
SQLSTATE	WW212
Sybase error code	12505

Probable cause

Run-time block encrypter initialization failed.

1.1.4.798 Password has expired

Error constant	SQLE_PASSWORD_EXPIRED
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-1152
SQLSTATE	08WAO
Sybase error code	13361

Probable cause

You attempted to connect using a valid user ID, but with an expired password. You can change your password by supplying the NewPassword connection parameter along with the current expired password.

1.1.4.799 Password has expired but cannot be changed because the database is read-only

Error constant	SQLE_PASSWORD_EXPIRED_READONLY_DB
ODBC 2 state	28000

ODBC 3 state	28000
Severity	16
SQLCODE	-1153
SQLSTATE	08WA1
Sybase error code	13360

Probable cause

You attempted to connect to a read-only database using a valid user ID, but with an expired password. The password cannot be changed unless the database is started without the -r option on the database server command line. Removing -r will permit modifications to the database.

1.1.4.800 Password must be at least %1 characters

Error constant	SQLE_PASSWORD_TOO_SHORT
ODBC 2 state	37000
ODBC 3 state	54000
Parameter 1	Minimum length of password.
Severity	14
SQLCODE	-738
SQLSTATE	54W07
Sybase error code	573

Probable cause

The password is shorter than that allowed by the current min_password_length option setting.

Related Information

[min_password_length Option](#)

1.1.4.801 PBKDF2 error: %1!s!

Error constant	PBKDF2_ERROR
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	A string indicating the error.
Severity	15
SQLCODE	-1931
SQLSTATE	42WF7
Sybase error code	12245

Probable cause

An error related to PBKDF2 key derivation occurred.

1.1.4.802 Permission denied: %1

Error constant	SQLE_PERMISSION_DENIED
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Description of the type of permission required.
Severity	16
SQLCODE	-121
SQLSTATE	42501
Sybase error code	262

Probable cause

You do not have the required permission to perform the specified action. The message specifies the actual permission required and the object being acted upon.

Related Information

[Inheritance of Roles and Privileges](#)

1.1.4.803 PIVOT error: An IN clause item does not contain the same number of items as the FOR clause

Error constant	SQLE_PIVOT_INVALID_IN_CLAUSE_ITEM
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1798
SQLSTATE	53031
Sybase error code	12346

Probable cause

You specified a PIVOT, but the number of items in the FOR clause does not match the number of items in one IN clause item.

1.1.4.804 PIVOT error: only one aggregate function can be specified without an alias

Error constant	SQLE_PIVOT_AGGR_AMBIGUOUS
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1826
SQLSTATE	53034
Sybase error code	12318

Probable cause

You specified a PIVOT that has more than one aggregate function without an alias. Please provide valid aliases for the aggregate functions.

1.1.4.805 PIVOT error: PIVOT XML does not contain a valid subquery, ANY, or ALL in the IN clause

Error constant	SQLE_PIVOT_INVALID_SUBQUERY
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1846
SQLSTATE	53037
Sybase error code	12298

Probable cause

You specified a PIVOT XML clause, but the IN clause does not contain a valid subquery, ANY or ALL.

1.1.4.806 PIVOT error: Too many aggregate functions and IN clause items

Error constant	SQLE_PIVOT_TOO_MANY_EXPRESSIONS
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1845
SQLSTATE	53036
Sybase error code	12300

Probable cause

You specified a PIVOT, but the number of items in the IN clause times the number of aggregate functions exceeds the number of expressions allowed in the SELECT list of the result set.

1.1.4.807 Plan cannot be generated for this type of statement

Error constant	SQLE_STMT_NOT_ALLOWED_IN_PLAN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-894
SQLSTATE	OAW14
Sybase error code	13589

Probable cause

You tried to get the execution plan for a statement type that is not supported.

1.1.4.808 Plan may contain virtual indexes

Error constant	SQLE_USING_VIRTUAL_INDEXES
ODBC 2 state	01S01
ODBC 3 state	01S01
Severity	10
SQLCODE	129
SQLSTATE	01W20
Sybase error code	13596

Probable cause

Virtual indexes are currently enabled in this connection. Any plans that are generated may contain virtual indexes.

Related Information

[Optimize Indexes to Improve Performance](#)
[CREATE INDEX Statement](#)

1.1.4.809 Point is duplicated %1

Error constant	SQLE_SLERR_DUPLICATE_POINT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The duplicated point
Severity	16
SQLCODE	-1400
SQLSTATE	2FF05
Sybase error code	13172

Probable cause

A linestring or circularstring geometry contains two adjacent points that are identical. This represents an invalid geometry.

1.1.4.810 Polygon ring order has been reoriented

Error constant	SQLE_SLWARN_POLYGON_RING_REORIENTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1490
SQLSTATE	01FW1
Sybase error code	13082

Probable cause

The rings of a polygon were automatically reoriented on input. This is a notification only.

1.1.4.811 Position %1 is invalid (should be between %2 and %3)

Error constant	SQLE_SLWARN_INVALID_POSITION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The provided position.
Parameter 2	The minimum supported position.
Parameter 3	The maximum supported position.
Severity	16
SQLCODE	-1489
SQLSTATE	01F01
Sybase error code	13083

Probable cause

The provided position is not valid. It should be between the specified minimum and maximum.

1.1.4.812 Positioned update operation attempted on a view with an INSTEAD OF trigger

Error constant	SQLE_INSTEAD_TRIGGER_POSITIONED
ODBC 2 state	42000
ODBC 3 state	42000
Severity	15
SQLCODE	-1127
SQLSTATE	42W3B
Sybase error code	13386

Probable cause

You attempted a positioned update, positioned delete, put, or wide insert operation that would involve an INSTEAD OF trigger on a view (possibly nested). These operations are not supported with INSTEAD OF triggers on views.

1.1.4.813 Possible database corruption found: %1

Error constant	SQLE_CORRUPT_PAGE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Description of the suspected database corruption
Severity	16
SQLCODE	-1925
SQLSTATE	08W10
Sybase error code	12251

Probable cause

The server has encountered possible database corruption. You will need to restore the database from a backup.

1.1.4.814 Prevented removal of LDAP server "%1" because it is the only LDAP server and the value of login_mode is "LDAPUA"

Error constant	SQLE_ONLY_LDAP_SERVER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the LDAP server.
Severity	16
SQLCODE	-1664
SQLSTATE	WW246
Sybase error code	12459

Probable cause

The setting for server-wide login_mode option is LDAPUA so to avoid locking out users from connecting, prevent the removal of the only LDAP server. Change login_mode before proceeding to DROP LDAP SERVER <server name>.

1.1.4.815 Prevented removal of LDAP server because it is referenced by login policy "%1" which is the only login policy with an LDAP server and the value of login_mode is "LDAPUA"

Error constant	SQLE_ONLY_LDAP_POLICY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the login policy.
Severity	16
SQLCODE	-1663
SQLSTATE	WW245
Sybase error code	12460

Probable cause

The setting for server-wide login_mode option is LDAPUA so to avoid locking out users from connecting, prevent the only login policy supporting LDAPUA reference removal. Change login_mode before proceeding to DROP LDAP SERVER <server name> WITH DROP ALL REFERENCES.

1.1.4.816 Previous error lost before RESIGNAL

Error constant	SQLE_PREVIOUS_ERROR_LOST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-825
SQLSTATE	WP011
Sybase error code	13831

Probable cause

A RESIGNAL statement in an exception handler of a stored procedure was executed but the context of the previous error was unavailable. A possible cause of this error is a SELECT statement that returns a result set in the exception handler.

1.1.4.817 Primary key column '%1' already defined

Error constant	SQL_E_PRIMARY_KEY_COLUMN_DEFINED
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the column that is already in the primary key.
Severity	16
SQLCODE	-119
SQLSTATE	52009
Sybase error code	1909

Probable cause

You listed the same column name twice in the definition of a primary key.

1.1.4.818 Primary key for row in table '%1' is referenced by foreign key '%2' in table '%3'

Error constant	SQL_E_PRIMARY_KEY_VALUE_REF
ODBC 2 state	23000
ODBC 3 state	23000
Parameter 1	The name of the table containing the row being modified.
Parameter 2	The name of the foreign index (or role) of the referencing table.
Parameter 3	The name of the foreign table referencing the primary row.
Severity	16
SQLCODE	-198
SQLSTATE	23W05
Sybase error code	547

Probable cause

You attempted to delete or modify a row whose primary key value is referenced elsewhere in the database.

Related Information

[Deletion of Data Using DELETE](#)
[Foreign Keys Enforce Referential Integrity](#)
[DELETE Statement](#)
[DELETE Statement \[UltraLite\]](#)

1.1.4.819 Primary key for table '%1' is not unique: Primary key value ('%2')

Error constant	SQL_E_PRIMARY_KEY_NOT_UNIQUE
ODBC 2 state	23000
ODBC 3 state	23000
Parameter 1	Name of the table where the problem was detected.
Parameter 2	Duplicate primary key values that caused the error.
Severity	14
SQLCODE	-193
SQLSTATE	23W01
Sybase error code	2601

Probable cause

You attempted to add a new row to a table, but the new row has the same primary key as an existing row. The database has not added the incorrect row to the database. For example, you might have added a student with student number 86004 and there is already a row for a student with that number.

Related Information

[Primary Keys](#)
[INSERT Statement](#)
[LOAD TABLE Statement](#)
[INSERT Statement \[UltraLite\]](#)
[LOAD TABLE Statement \[UltraLite\]](#)

1.1.4.820 Principal mirror servers are already defined

Error constant	SQLE_MIRROR_PARTNERS_ALREADY_DEFINED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1311
SQLSTATE	WW134
Sybase error code	13278

Probable cause

An attempt was made to create a mirror server without a parent server, but two principal mirror servers are already defined in the database.

1.1.4.821 Procedure '%1' is no longer valid

Error constant	SQLE_PROCEDURE_NO_LONGER_VALID
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the procedure.
Severity	15
SQLCODE	-836
SQLSTATE	42W63
Sybase error code	13842

Probable cause

A procedure definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words. If this procedure is an internal procedure, you may have an older version. Database upgrade may be needed to run it successfully.

1.1.4.822 Procedure '%1' needs a RESULT clause for returned ROW or ARRAY

Error constant	SQL_E_ROW_ARRAY_NEEDS_RESULT_CLAUSE
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the procedure.
Severity	15
SQLCODE	-1881
SQLSTATE	42WF6
Sybase error code	12269

Probable cause

A procedure definition failed to be loaded from the catalog. The procedure returns a result set that includes a ROW or ARRAY type, but does not specify the RESULT clause. The RESULT clause is required if a procedure has a ROW or ARRAY type in its result set. If this is a Transact-SQL procedure, it must be converted to Watcom SQL.

1.1.4.823 Procedure '%1' not found

Error constant	SQL_E_PROCEDURE_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the procedure that could not be found.
Severity	11
SQLCODE	-265
SQLSTATE	52W09
Sybase error code	504

Probable cause

You misspelled the name of a procedure, or you did not qualify a procedure name with a user name.

1.1.4.824 Procedure '%1' terminated with unhandled exception '%2'

Error constant	SQLE_UNHANDLED_EXTENV_EXCEPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure that returned the unhandled exception.
Parameter 2	The fully qualified Java class name of the unhandled exception.
Severity	16
SQLCODE	-91
SQLSTATE	WP001
Sybase error code	13735

Probable cause

A Java procedure terminated with an active exception, and this exception is reflected in SQL as an error status.

1.1.4.825 Procedure has completed

Error constant	SQLE_PROCEDURE_COMPLETE
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	105
SQLSTATE	01W05
Sybase error code	13618

Probable cause

There are no more result sets available for this procedure. An OPEN or a RESUME statement may have caused the procedure to execute to completion.

1.1.4.826 Procedure in use by '%1'

Error constant	SQLE_PROCEDURE_IN_USE
ODBC 2 state	40001
ODBC 3 state	40001
Parameter 1	Name of user.
Severity	16
SQLCODE	-215
SQLSTATE	42W23
Sybase error code	3702

Probable cause

You attempted to DROP a procedure that is being used by other active users of the database.

1.1.4.827 Procedure is currently being altered or dropped

Error constant	SQLE_PROCEDURE_IN_USE_DDL
ODBC 2 state	40001
ODBC 3 state	40001
Severity	16
SQLCODE	-1681
SQLSTATE	42WF0
Sybase error code	12452

Probable cause

You have attempted to use a procedure that is currently being altered or dropped.

1.1.4.828 Procedure or trigger calls have nested too deeply

Error constant	SQLE_NESTING_TOO_DEEP
----------------	-----------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-274
SQLSTATE	42W29
Sybase error code	217

Probable cause

You may have defined a procedure or trigger that causes unlimited recursion.

1.1.4.829 Publication '%1' not found

Error constant	SQL_E_PUBLICATION_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the publication that could not be found.
Severity	16
SQLCODE	-280
SQLSTATE	5RW01
Sybase error code	13642

Probable cause

You misspelled the name of a publication, or you did not qualify a publication name with a user name.

Related Information

[Publications](#)
[UltraLite Publications](#)

1.1.4.830 Publication predicates were not evaluated

Error constant	SQLE_PUBLICATION_PREDICATE_IGNORED
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	138
SQLSTATE	01W25
Sybase error code	13423

Probable cause

Publication predicates were not evaluated because UltraLite was initialized without SQL support. The table will be uploaded as if no publication predicate was specified for the table.

1.1.4.831 RAISERROR executed: %1

Error constant	SQLE_RAISERROR_STMT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	RAISERROR message string.
Severity	16
SQLCODE	-631
SQLSTATE	WW012
Sybase error code	0

Probable cause

A RAISERROR statement has been executed. The string associated with the RAISERROR statement is included in the text of the error message.

1.1.4.832 Reading %1 database pages exceeds available cache of %2 pages

Error constant	SQLE_READ_DB_PAGES_CACHE_TOO_SMALL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The number of database pages you tried to read.
Parameter 2	The maximum number of pages that can be read into the cache.
Severity	16
SQLCODE	-1888
SQLSTATE	54W54
Sybase error code	12262

Probable cause

You attempted to read pages into the cache using the ALTER DATABASE RESTORE CACHE statement or the sp_read_db_pages system procedure, and the number of pages that would be read exceeded the maximum cache size. Restart the server with a larger cache size.

1.1.4.833 READTEXT or WRITETEXT statement cannot refer to a view

Error constant	SQLE_TEXT_OPERATION_ON_VIEW
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-708
SQLSTATE	42W50
Sybase error code	285

Probable cause

A Transact-SQL READTEXT or WRITETEXT statement cannot refer to text columns in a view. Replace the view reference with the name of a base table.

1.1.4.834 RECOVER UNTIL and FOR REPLICATION cannot be used together

Error constant	NETBU_WITH_PITR_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1962
SQLSTATE	42WE11
Sybase error code	12219

Probable cause

Point in time recovery using NETWORK BACKUP for replication is not allowed.

1.1.4.835 Recursion is not allowed without the RECURSIVE keyword

Error constant	SQLE_RECURSIVE_KEYWORD_REQUIRED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-938
SQLSTATE	42WA0
Sybase error code	13549

Probable cause

The common table expressions for a recursive query must be defined using a WITH RECURSIVE clause.

1.1.4.836 Recursive column %1: conversion from '%2' to '%3' loses precision

Error constant	SQLE_BAD_RECURSIVE_COLUMN_CONVERSION
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Column number of the recursive subquery.
Parameter 2	Type converted from.
Parameter 3	Type converted to.
Severity	16
SQLCODE	-945
SQLSTATE	42WA2
Sybase error code	13543

Probable cause

Every column in the recursive subquery must be convertible to the type of the corresponding column in the initial subquery without loss of precision. Try casting the column in the initial subquery to an appropriate type.

1.1.4.837 Referential integrity actions other than RESTRICT not allowed for temporary tables

Error constant	SQLE_INVALID_FOREIGN_KEY_ACTION
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-849
SQLSTATE	42R01
Sybase error code	1709

Probable cause

You attempted to specify an unsupported referential integrity action for a temporary table.

1.1.4.838 Remote column %1 has been specified with the wrong case

Error constant	SQLE_OMNI_RMT_COLUMN_WRONG_CASE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The complete name of the remote column.
Severity	11
SQLCODE	-1704
SQLSTATE	W0035
Sybase error code	12432

Probable cause

The remote server requires that columns be specified in the correct case.

1.1.4.839 Remote message type '%1' not found

Error constant	SQLE_NOT_REMOTE_TYPE
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of remote message type.
Severity	16
SQLCODE	-286
SQLSTATE	5RW07
Sybase error code	13648

Probable cause

You referred to a remote message type that is not defined in this database. Use CREATE REMOTE TYPE to define remote message types.

1.1.4.840 Remote server '%1' could not be found

Error constant	SQLE_OMNI_SERVER_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the remote server.
Severity	11
SQLCODE	-659
SQLSTATE	W0004
Sybase error code	11214

Probable cause

You attempted to define an object on a server that has not been added. Use CREATE SERVER to add the remote server definition.

1.1.4.841 Remote server '%1' is currently configured as read-only

Error constant	SQLE_OMNI_READONLY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the remote server.
Severity	16
SQLCODE	-658
SQLSTATE	W0003
Sybase error code	11248

Probable cause

You attempted to perform an update on an object located on a server that is configured as read-only. Use ALTER SERVER to reconfigure the remote server to be updatable.

1.1.4.842 Remote server does not have the ability to support this statement

Error constant	SQLE_OMNI_SERVER_NOT_CAPABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-706
SQLSTATE	W0012
Sybase error code	11227

Probable cause

You attempted to execute a statement that requires a capability that is not supported by a remote server.

1.1.4.843 Remote server is currently in use and cannot be dropped

Error constant	SQLE_OMNI_SERVER_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1855
SQLSTATE	W0036
Sybase error code	12290

Probable cause

You attempted to drop a remote server that was still in use by another connection.

1.1.4.844 Remote statement failed

Error constant	SQLE_REMOTE_STATEMENT_FAILED
ODBC 2 state	S0002
ODBC 3 state	42S02
Severity	16
SQLCODE	-288
SQLSTATE	5RW09
Sybase error code	13650

Probable cause

This SQLSTATE can be signaled within a trigger to prevent the SQL Remote Message Agent (dbremote) from displaying an error message in the output. This exception will only occur when a trigger or procedure signals it. This is useful for ignoring replication errors that are permitted by design.

Related Information

[How to Ignore Replication Errors](#)

1.1.4.845 RENAME and FOR REPLICATION cannot be used together

Error constant	NETBU_WITH_RENAME_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1963
SQLSTATE	42WE12
Sybase error code	12218

Probable cause

Rename cannot be used during NETWORK BACKUP for replication.

1.1.4.846 Reorganize table is already being run on table "%1"

Error constant	SQLLE_REORG_ALREADY_IN_PROGRESS
ODBC 2 state	54000
ODBC 3 state	54000
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1229
SQLSTATE	54W51
Sybase error code	13288

Probable cause

There is already a REORGANIZE TABLE statement being run on this table. Only one such statement can be executing on a table at any time.

1.1.4.847 REORGANIZE TABLE ran out of space

Error constant	SQLLE_REORG_OUT_OF_SPACE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1764
SQLSTATE	54W53
Sybase error code	12376

Probable cause

REORGANIZE TABLE ran out of allocated space.

1.1.4.848 Request denied -- no active databases

Error constant	SQLLE_REQUEST_DENIED_NO_DATABASES
----------------	-----------------------------------

ODBC 2 state	08004
ODBC 3 state	08004
Severity	14
SQLCODE	-76
SQLSTATE	08W28
Sybase error code	950

Probable cause

The server has denied your request as there are currently no running databases.

1.1.4.849 Request interrupted due to timeout

Error constant	SQL_E_REQUEST_TIMEOUT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1043
SQLSTATE	57W01
Sybase error code	13468

Probable cause

The current request was canceled during its execution since it ran for longer than the request_timeout database option value. The database was able to stop the operation without doing a rollback. If the statement is an INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

1.1.4.850 Request to start/stop database denied

Error constant	SQL_E_START_STOP_DATABASE_DENIED
ODBC 2 state	42000

ODBC 3 state	42000
Severity	14
SQLCODE	-75
SQLSTATE	08W29
Sybase error code	6004

Probable cause

You do not have permission to start or stop a database. The required permission is determined on the server command line.

Related Information

[Database Starting and Stopping](#)

[-gd Database Server Option](#)

[-gk Database Server Option](#)

1.1.4.851 Required operators excluded

Error constant	SQL_E_REQUIRED_OPERATORS_EXCLUDED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	18
SQLCODE	-969
SQLSTATE	WI011
Sybase error code	13521

Probable cause

The database server was unable to construct a valid access plan for the given request because required data flow operators were excluded by the `exclude_operators` option. Re-enable the required operators to execute the statement.

1.1.4.852 Resource governor for '%1' exceeded

Error constant	SQLE_RESOURCE_GOVORNOR_EXCEEDED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The resource whose limit has been exceeded.
Severity	19
SQLCODE	-685
SQLSTATE	WP009
Sybase error code	13715

Probable cause

The resource governor for the stated resource has determined that the usage of the resource has exceeded its limit.

Related Information

[max_cursor_count Option](#)
[max_statement_count Option](#)
[max_priority Option](#)
[priority Option](#)

1.1.4.853 RESTORE statement missing a FROM clause

Error constant	SQLE_RESTORE_MISSING_FROM_CLAUSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1908
SQLSTATE	42X15
Sybase error code	12253

Probable cause

No FROM clause has been provided for the restore.

1.1.4.854 RESTORE unable to find a log backup on the latest timeline

Error constant	SQL_E_RESTORE_UNABLE_TO_FIND_LOG_BACKUP
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1857
SQLSTATE	WB019
Sybase error code	12306

Probable cause

RESTORE was unable to find a log backup on the latest timeline

1.1.4.855 RESTORE unable to open file '%1'

Error constant	SQL_E_RESTORE_UNABLE_TO_OPEN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	File name of database file.
Severity	21
SQLCODE	-717
SQLSTATE	WB008
Sybase error code	13726

Probable cause

RESTORE was unable to open one of the database files.

1.1.4.856 RESTORE unable to start database '%1'

Error constant	SQL restore unable to start
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	File name of database file.
Severity	21
SQLCODE	-719
SQLSTATE	WB010
Sybase error code	13728

Probable cause

After a RESTORE, the resulting database could not be started.

1.1.4.857 RESTORE unable to write to file '%1'

Error constant	SQL restore unable to write
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	File name of database file.
Severity	21
SQLCODE	-718
SQLSTATE	WB009
Sybase error code	13727

Probable cause

RESTORE was unable to write to one of the database files.

1.1.4.858 Restoring database from an upgrade image

Error constant	FILE_RESTORE_DATABASE_UPGRADE_IMAGE
ODBC 2 state	OK
ODBC 3 state	OK
Severity	16
SQLCODE	-1975
SQLSTATE	WW259
Sybase error code	12207

Probable cause

The server is replaying an ALTER DATABASE UPGRADE statement, which restores the database from an upgrade image.

1.1.4.859 Result set not allowed from within an atomic compound statement

Error constant	SQLE_RESULT_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-222
SQLSTATE	3BW02
Sybase error code	13655

Probable cause

You used a SELECT statement with no INTO clause or a RESULT CURSOR statement within an atomic compound statement.

1.1.4.860 Result set not permitted in '%1'

Error constant	SQL_RESULT_SET_NOT_PERMITTED
ODBC 2 state	07005
ODBC 3 state	07005
Parameter 1	Name of object containing the invalid statement.
Severity	16
SQLCODE	-946
SQLSTATE	09W03
Sybase error code	13542

Probable cause

You attempted to execute a SELECT statement in a context where a result set is not permitted.

1.1.4.861 Retrying read of corrupt page (page '%1')

Error constant	SQL_CORRUPT_PAGE_READ_RETRY
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The page ID.
Severity	10
SQLCODE	143
SQLSTATE	WW115
Sybase error code	13275

Probable cause

UltraLite detected a corrupt database page and will attempt the read operation again. If a mirror file is enabled, it is used for the retry. If the retry fails, an error will be signaled.

Related Information

[Corruption Detection Using Checksums](#)

1.1.4.862 Return type of void from procedure '%1' cannot be used in any expression

Error constant	SQLE_PROCEDURE_RETURNS_VOID
ODBC 2 state	07006
ODBC 3 state	07006
Parameter 1	Name of the procedure.
Severity	16
SQLCODE	-705
SQLSTATE	53019
Sybase error code	257

Probable cause

The Java type void does not map onto any SQL type, hence a procedure returning void cannot be used in any SQL expression.

1.1.4.863 Right truncation of string data

Error constant	SQLE_STRING_RIGHT_TRUNCATION
ODBC 2 state	22001
ODBC 3 state	22001
Severity	16
SQLCODE	-638
SQLSTATE	22001
Sybase error code	9502

Probable cause

Non-space characters were truncated upon the assignment of string data.

Related Information

[Transact-SQL and ANSI/ISO SQL Standard Compatibility Options](#)
[string_truncation Option](#)

1.1.4.864 Role "%1" already exists

Error constant	SQL_E_ROLE_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the role.
Severity	16
SQLCODE	-1537
SQLSTATE	28W26
Sybase error code	12568

Probable cause

An attempt was made to create a role that already exists in the database.

1.1.4.865 Rollback occurred due to blocking_others_timeout

Error constant	SQL_E_BLOCKING_OTHERS_ROLLBACK
ODBC 2 state	40001
ODBC 3 state	40001
Severity	13
SQLCODE	-1344
SQLSTATE	WW148
Sybase error code	13212

Probable cause

This connection has been rolled back because another connection was blocked on this connection for longer than the `blocking_others_timeout` option setting. All requests on this connection will get this error until it is disconnected.

Related Information

[blocking_others_timeout Option](#)

1.1.4.866 Rollback occurred due to deadlock during prefetch

Error constant	SQL_E_ROLLBACK_ON_PREFETCH
ODBC 2 state	40001
ODBC 3 state	40001
Severity	13
SQLCODE	-684
SQLSTATE	WW019
Sybase error code	1205

Probable cause

One of the cursors that was opened with prefetch enabled was performing fetch operations, and a deadlock occurred during a prefetch. This is a deadlock situation and your transaction has been chosen as the one to rollback. The request that received this error was not executed, unless the request was to close the cursor, in which case the cursor was closed.

1.1.4.867 ROLLBACK TO SAVEPOINT not allowed

Error constant	SQL_E_ROLLBACK_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-221

SQLSTATE	3B002
Sybase error code	13654

Probable cause

You attempted a ROLLBACK TO SAVEPOINT within an atomic operation to a savepoint established before the atomic operation.

1.1.4.868 Row has been updated since last time read

Error constant	SQLLE_ROW_UPDATED_WARNING
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	104
SQLSTATE	01W04
Sybase error code	532

Probable cause

You fetched a row from a SCROLL cursor. The row was previously fetched from the same cursor, and one or more columns in the row has been updated since the previous fetch. The column(s) updated may or may not be fetched by the cursor; this warning just indicates that the row from the table has been updated. If the cursor involves more than one table, a row from one or more of the tables has been updated.

1.1.4.869 Row has changed since last read -- operation canceled

Error constant	SQLLE_ROW_UPDATED_SINCE_READ
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-208

SQLSTATE	22W02
Sybase error code	554

Probable cause

You attempted an UPDATE (positioned) or DELETE (positioned) operation on a cursor declared as a SCROLL cursor, and the row you are changing has been updated since you read it. This error prevents the lost update problem.

Related Information

[Lost Updates](#)

[Row Locks](#)

[Benefits of Using Cursors](#)

[Cursor Sensitivity and Isolation Levels](#)

[DECLARE CURSOR Statement \[ESQL\] \[SP\]](#)

1.1.4.870 Row in table '%1' was modified or deleted in BEFORE trigger

Error constant	SQL_ROW_REMODIFIED_OR_DELETED
ODBC 2 state	37000
ODBC 3 state	ERROR
Parameter 1	Name of the table.
Severity	16
SQLCODE	-833
SQLSTATE	42W62
Sybase error code	13839

Probable cause

A BEFORE trigger has updated or deleted the row that caused the trigger to fire, preventing the original operation from completing. The trigger must be re-written so that it does not attempt to change the row via UPDATE or DELETE statements.

1.1.4.871 Row not found

Error constant	SQLE_NOTFOUND
ODBC 2 state	OK
ODBC 3 state	OK
Severity	16
SQLCODE	100
SQLSTATE	02000
Sybase error code	560

Probable cause

You positioned a cursor beyond the beginning or past the end of the query. There is no row at that position.

Related Information

[Cursors in Embedded SQL](#)

1.1.4.872 Row was dropped from table %1 to maintain referential integrity

Error constant	SQLE_ROW_DELETED_TO_MAINTAIN_REFERENTIAL_INTEGRITY
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The name of the table.
Severity	10
SQLCODE	137
SQLSTATE	01W24
Sybase error code	13489

Probable cause

A delete of a primary row during a download forced its foreign row(s) to also be deleted to maintain referential integrity.

Related Information

[Foreign Keys](#)
[CREATE TABLE Statement \[UltraLite\]](#)

1.1.4.873 Run time SQL error -- %1

Error constant	SQLE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Identification of the error.
Severity	18
SQLCODE	-300
SQLSTATE	40000
Sybase error code	13664

Probable cause

An internal database error occurred. If it can be reproduced, it should be reported to SAP. You may be able to work around this problem by modifying the associated query statement.

1.1.4.874 SAP HANA environment error, unable to ping name server

Error constant	SQLE_BACKUP_BKINT_PING_NS_ERR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1920
SQLSTATE	WB030
Sybase error code	12266

Probable cause

name server is not available

1.1.4.875 SAP HANA environment error, unable to execute command on name server

Error constant	SQLE_BACKUP_BKINT_NO_HANA_ENV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1916
SQLSTATE	WB026
Sybase error code	12262

Probable cause

hdbnsutil is not available.

1.1.4.876 Savepoint '%1' not found

Error constant	SQLE_SAVEPOINT_NOTFOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of savepoint.
Severity	16
SQLCODE	-220
SQLSTATE	3B001

Probable cause

You attempted to rollback to a savepoint that does not exist.

1.1.4.877 Savepoints require a rollback log

Error constant	SQLE_SAVEPOINTS_REQUIRE_UNDO
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-213
SQLSTATE	3BW01
Sybase error code	13656

Probable cause

You cannot use savepoints when the database server is running in bulk mode without a rollback log.

1.1.4.878 Scalar variable '%1' not found

Error constant	SQLE_SCALAR_VARIABLE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the scalar variable that could not be found.
Severity	15
SQLCODE	-1886
SQLSTATE	42X14
Sybase error code	12264

Probable cause

You attempted to use a variable that was not found, or did not have a scalar value. A non-scalar variable can be a row, an array or a table reference.

1.1.4.879 Schedule '%1' for event '%2' already exists

Error constant	SQLE_SCHEDULE_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the schedule that already exists.
Parameter 2	Name of the event being scheduled.
Severity	16
SQLCODE	-774
SQLSTATE	WE004
Sybase error code	13784

Probable cause

You have attempted to create a schedule with a name that already exists in the database for the named event.

1.1.4.880 Schedule '%1' for event '%2' not found

Error constant	SQLE_SCHEDULE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the schedule that could not be found.
Parameter 2	Name of the event being scheduled.
Severity	11
SQLCODE	-773
SQLSTATE	WE003
Sybase error code	13783

Probable cause

You have attempted to reference a schedule with a name that does not exist in the database for the named event.

1.1.4.881 Script file missing statement "go" delimiter on a separate line

Error constant	SQLE_SCRIPT_MISSING_DELIMITER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1315
SQLSTATE	WW046
Sybase error code	13241

Probable cause

For UltraLite, all non-comment SQL statements in a script file (including the final one) must be followed by "go" on a line by itself. For strings, you can use "\ngo" to end a statement.

Related Information

[Interactive SQL for UltraLite Utility \(dbisql\)](#)

1.1.4.882 Secure HTTP connections are not supported on this platform

Error constant	SQLE_SECURE_CONNECTION_UNAVAILABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-1030

SQLSTATE	WW063
Sybase error code	13480

Probable cause

A Secure HTTP connection was attempted, but is not supported on this platform.

1.1.4.883 Select lists in UNION, INTERSECT, or EXCEPT do not match in length

Error constant	SQLE_INVALID_UNION
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-153
SQLSTATE	53026
Sybase error code	205

Probable cause

You specified a UNION, INTERSECT, or EXCEPT, but the SELECT statements involved in the operation do not have the same number of columns in the SELECT list.

Related Information

[SELECT Statement](#)
[UNION Statement](#)
[INTERSECT Statement](#)
[EXCEPT Statement](#)
[SELECT Statement \[UltraLite\]](#)
[UNION Statement \[UltraLite\]](#)

1.1.4.884 SELECT returns more than one row

Error constant	SQLLE_TOO_MANY_RECORDS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-185
SQLSTATE	21000
Sybase error code	13637

Probable cause

You tried to use a SELECT statement without a cursor, but the statement cursor returns more than one row. Only a single row SELECT statement can be used in this context.

1.1.4.885 Semaphore "%1" not found

Error constant	SQLLE_SEMAPHORE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the semaphore that could not be found.
Severity	11
SQLCODE	-1808
SQLSTATE	55W54
Sybase error code	12336

Probable cause

You misspelled the name of a semaphore, or the semaphore does not exist.

1.1.4.886 Semaphore was dropped

Error constant	SQLLE_SEMAPHORE_DROPPED
----------------	-------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1805
SQLSTATE	WP028
Sybase error code	12339

Probable cause

The semaphore this connection was waiting for was dropped during the wait. The semaphore is no longer available. This could happen if the semaphore was explicitly dropped, or if the connection owning the temporary semaphore has disconnected.

1.1.4.887 Sequence '%1' already exists

Error constant	SQL_E_SEQUENCE_ALREADY_EXISTS
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the sequence.
Severity	16
SQLCODE	-1354
SQLSTATE	52W47
Sybase error code	13206

Probable cause

A sequence with the specified name already exists.

Related Information

[CREATE SEQUENCE Statement](#)
[ALTER SEQUENCE Statement](#)

1.1.4.888 Sequence '%1' in use by another connection

Error constant	SQLE_SEQUENCE_IN_USE
ODBC 2 state	40001
ODBC 3 state	40001
Parameter 1	Name of user.
Severity	16
SQLCODE	-1366
SQLSTATE	42WE3
Sybase error code	13196

Probable cause

You have attempted to drop a sequence that is currently being used by another connection.

1.1.4.889 Sequence '%1' not found

Error constant	SQLE_SEQUENCE_NOT_FOUND
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the sequence.
Severity	16
SQLCODE	-1359
SQLSTATE	52W44
Sybase error code	13209

Probable cause

The sequence with this name does not exist in the database.

1.1.4.890 Sequence generators are not supported for this database

Error constant	SQL_E_SEQUENCES_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1369
SQLSTATE	52W52
Sybase error code	13193

Probable cause

The current database does not have catalog support for sequence generators. To use this feature, upgrade your database to the most recent version.

Related Information

[Use of a Sequence to Generate Unique Values](#)
[CREATE SEQUENCE Statement](#)

1.1.4.891 Sequence name '%1' is ambiguous

Error constant	SQL_E_AMBIGUOUS_SEQUENCE_NAME
ODBC 2 state	S0013
ODBC 3 state	42S13
Parameter 1	Name of an ambiguous sequence.
Severity	16
SQLCODE	-1358
SQLSTATE	52W45
Sybase error code	13208

Probable cause

A statement has referred to a sequence name that is not unique. Preface the sequence name by an owner name.

1.1.4.892 Server '%1': %2

Error constant	SQLE_OMNI_REMOTE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the remote server.
Parameter 2	The message from the remote server.
Severity	16
SQLCODE	-660
SQLSTATE	W0005
Sybase error code	13732

Probable cause

A message was generated by a remote server. The message text is included.

1.1.4.893 Server capability name '%1' could not be found in the database

Error constant	SQLE_CAPABILITY_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of server capability.
Severity	16
SQLCODE	-761
SQLSTATE	W0014
Sybase error code	13723

Probable cause

An ALTER SERVER statement was attempted on a capability that was not defined.

1.1.4.894 Server name can only be specified when connecting to a cloud database server with NODETYPE=DIRECT

Error constant	SQLE_SERVER_NAME_NOT_ALLOWED
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-1582
SQLSTATE	08WA8
Sybase error code	12523

Probable cause

When connecting to a cloud database server, specifying a server name on the connection string is only allowed for NODETYPE=DIRECT. When using other NODETYPE values to connect to a cloud database server, specifying the server name is not allowed. Typically, for connections to a cloud database server the HOST connection parameter or HOST protocol option is used to specify the address of one or more cloud database servers.

1.1.4.895 Server not found and unable to automatically start

Error constant	SQLE_UNABLE_TO_CONNECT_OR_START
ODBC 2 state	08001
ODBC 3 state	08001
Severity	11
SQLCODE	-764
SQLSTATE	08W55
Sybase error code	13774

Probable cause

The client could not connect to a server, and was unable to automatically start a server. The automatic start may have failed because no database file was specified.

Related Information

[Troubleshooting: Database Server Startup](#)
[SQL Anywhere Database Server Executable \(dbsrv17, dbeng17\)](#)
[UltraLite Engine Utility \(uleng17\)](#)

1.1.4.896 Service '%1' already exists

Error constant	SQLE_SERVICE_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the service that already exists.
Severity	16
SQLCODE	-919
SQLSTATE	42W97
Sybase error code	13565

Probable cause

You have attempted to create a service with a name that already exists in the database.

1.1.4.897 Service '%1' in use

Error constant	SQLE_SERVICE_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the service that is in use.
Severity	16

SQLCODE	-924
SQLSTATE	55W15
Sybase error code	13567

Probable cause

You have attempted to drop a service that is currently in use.

1.1.4.898 Service '%1' not found

Error constant	SQLE_SERVICE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the specified service that could not be found.
Severity	16
SQLCODE	-920
SQLSTATE	42W98
Sybase error code	13564

Probable cause

You have attempted to reference a service with a name that does not exist in the database.

1.1.4.899 Service definition requires a statement when authorization is off

Error constant	SQLE_SERVICE_AUTH_REQUIRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-931
SQLSTATE	42W9E

Probable cause

The service definition for the specified service type requires a statement to be specified when authorization is set to Off.

1.1.4.900 Service statement definition is inconsistent with service type

Error constant	SQLE_SERVICE_STATEMENT_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-927
SQLSTATE	42W9C
Sybase error code	13558

Probable cause

Either no statement was provided for a service whose type requires one, or a statement was provided when the service type does not allow one to be defined.

1.1.4.901 Service statement definition is invalid or unsupported

Error constant	SQLE_SERVICE_STATEMENT_INVALID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1269
SQLSTATE	42WCC

Probable cause

Either the statement provided is invalid or it is unsupported within the context of a service.

1.1.4.902 Service type does not allow '%1' attribute

Error constant	SQLE_SERVICE_ATTR_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the attribute that is not allowed.
Severity	16
SQLCODE	-1027
SQLSTATE	42WB2
Sybase error code	13483

Probable cause

The service definition for the specified service type does not allow the given attribute to be specified.

1.1.4.903 Service type required for CREATE SERVICE

Error constant	SQLE_SERVICE_TYPE_REQUIRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-915
SQLSTATE	42W92
Sybase error code	13569

Probable cause

The CREATE SERVICE statement requires a service type to be specified.

1.1.4.904 SET clause for column '%1' used incorrectly

Error constant	SQL_INVALID_SET_CLAUSE
ODBC 2 state	S0002
ODBC 3 state	42S03
Parameter 1	The SET clause that is invalid.
Severity	15
SQLCODE	-846
SQLSTATE	42U03
Sybase error code	13852

Probable cause

Your UPDATE statement contains an invalid SET clause, for example, there are multiple SET clauses for the same column.

1.1.4.905 SETUSER not allowed in procedures, triggers, events, or batches

Error constant	SQL_SETUSER_NOT_IN_PROCEDURES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-877
SQLSTATE	42W09
Sybase error code	13888

Probable cause

The SETUSER statement is not allowed in stored procedures, triggers, event handlers, or batches, and cannot be called from an EXECUTE IMMEDIATE statement.

1.1.4.906 Shared memory listener already started

Error constant	SQLE_START_SHM_LISTENER_CONFLICT_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1779
SQLSTATE	08WD7
Sybase error code	12361

Probable cause

You attempted to start the shared memory listener that already is running.

1.1.4.907 Signature '%1' does not match procedure parameters

Error constant	SQLE_SIGNATURE_MISMATCH
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The value of the signature.
Severity	16
SQLCODE	-737
SQLSTATE	42W54
Sybase error code	201

Probable cause

The number of types in the signature must match the number of procedure parameters. If a DYNAMIC RESULT SETS clause was specified, the number of dynamic result sets must match the quantity found in the signature.

1.1.4.908 Snapshot isolation disabled or pending

Error constant	SQL_E_SNAPSHOT_ISOLATION_DISABLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1054
SQLSTATE	55W23
Sybase error code	13459

Probable cause

Snapshot isolation is disabled or its activation is still pending. You must enable snapshot isolation before using it.

1.1.4.909 Spatial column '%1' cannot be included in a primary key or unique index

Error constant	SQL_E_SLERR_CREATE_INDEX_UNIQUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the spatial column.
Severity	16
SQLCODE	-1453
SQLSTATE	2FW46
Sybase error code	13119

Probable cause

A spatial column cannot be included in a primary key or unique index.

Related Information

[Primary Keys](#)

[CREATE TABLE Statement](#)

[ALTER TABLE Statement](#)

[CREATE TABLE Statement \[UltraLite\]](#)

[ALTER TABLE Statement \[UltraLite\]](#)

1.1.4.910 Spatial column '%1' cannot be included in an index because it is not constrained to a single SRID

Error constant	SQLE_SLERR_CREATE_INDEX_NOSRID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the spatial column.
Severity	16
SQLCODE	-1454
SQLSTATE	2FW47
Sybase error code	13118

Probable cause

The named spatial column cannot be included in a spatial index because the column is not constrained to have values from a single spatial reference system. The column definition should be of the form "col ST_Geometry(SRID=0)".

1.1.4.911 Spatial feature %1 is not supported

Error constant	SQLE_SLERR_NYI
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The name of the unsupported feature.
Severity	16
SQLCODE	-1413
SQLSTATE	2FW03
Sybase error code	13159

Probable cause

The specified feature is not supported.

1.1.4.912 Spatial reference system "%1" is reserved

Error constant	SQLLE_SLERR_DDL_SRS_RESERVED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the reserved spatial reference system.
Severity	16
SQLCODE	-1472
SQLSTATE	2FW65
Sybase error code	13100

Probable cause

The named spatial reference system is reserved for system use.

Related Information

[CREATE SPATIAL REFERENCE SYSTEM Statement](#)

1.1.4.913 Spatial reference system %1 cannot be modified because it is in use

Error constant	SQLE_SLERR_DDL_SRS_INUSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The coordinate system name
Severity	16
SQLCODE	-1471
SQLSTATE	2FW64
Sybase error code	13101

Probable cause

The coordinate system is currently in use and cannot be dropped.

Related Information

[ALTER SPATIAL REFERENCE SYSTEM Statement](#)

1.1.4.914 Spatial reference system '%1' already exists

Error constant	SQLE_SLERR_DDL_SRS_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the spatial reference system.
Severity	16
SQLCODE	-1461
SQLSTATE	2FW54
Sybase error code	13111

Probable cause

The named spatial reference system already exists.

1.1.4.915 Spatial reference system '%1' not found

Error constant	SQLE_SLERR_DDL_NO_SRS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the spatial reference system.
Severity	16
SQLCODE	-1459
SQLSTATE	2FW52
Sybase error code	13113

Probable cause

The named spatial reference system is not defined.

1.1.4.916 Spatial reference system must specify the SRID to use

Error constant	SQLE_SLERR_DDL_SRS_NOSRID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1462
SQLSTATE	2FW55
Sybase error code	13110

Probable cause

When creating a spatial reference system, the statement must specify IDENTIFIED BY to specify the SRID to use.

1.1.4.917 Spatial unit of measure "%1" is reserved

Error constant	SQLE_SLERR_DDL_UOM_RESERVED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the reserved unit of measure.
Severity	16
SQLCODE	-1473
SQLSTATE	2FW66
Sybase error code	13099

Probable cause

The named unit of measure is reserved for system use.

Related Information

[CREATE SPATIAL REFERENCE SYSTEM Statement](#)

1.1.4.918 Specified database file already in use

Error constant	SQLE_FILE_IN_USE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	14
SQLCODE	-816
SQLSTATE	08W56
Sybase error code	924

Probable cause

The database server could not start the specified database because the file is already in use.

Related Information

[Database Connections](#)

[UltraLite Database Connections](#)

[Connecting to a Database \(Interactive SQL, SQL Central\)](#)

1.1.4.919 Specified database is invalid

Error constant	SQLE_INVALID_DATABASE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	11
SQLCODE	-84
SQLSTATE	08W11
Sybase error code	4001

Probable cause

The database file you specified is invalid. The database server is stopped.

1.1.4.920 Specified database not found

Error constant	SQLE_DATABASE_NOT_FOUND
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-83
SQLSTATE	08W10
Sybase error code	911

Probable cause

The database server was unable to find the specified database. The database server may be attempting to start a database file that cannot be opened or that cannot be found on the network. You may be attempting to connect to a database name that is not running.

1.1.4.921 Specified file system volume not found for database '%1'

Error constant	SQLE_FILE_VOLUME_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database.
Severity	16
SQLCODE	-1112
SQLSTATE	WW082
Sybase error code	13402

Probable cause

The file system volume you specified in the database file name was not found. Check the volume name or ordinal.

1.1.4.922 Specified LDAP server '%1' is not found

Error constant	SQLE_UNKNOWN_LDAP_SERVER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the LDAP server.
Severity	11
SQLCODE	-1554
SQLSTATE	28W31
Sybase error code	12551

Probable cause

The LDAP server specified does not exist in the database.

1.1.4.923 Specified local connection ID not found

Error constant	SQLE_LOCAL_CONNECTION_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-996
SQLSTATE	W0024
Sybase error code	709

Probable cause

There is no connection with the specified connection ID.

1.1.4.924 Specified role '%1' is a user extended as role

Error constant	SQLE_AN_EXTENDED_USER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the role being dropped.
Severity	14
SQLCODE	-1560
SQLSTATE	28W34
Sybase error code	12545

Probable cause

Specified role is a user extended as role but FROM USER clause is not specified in DROP ROLE command.

1.1.4.925 Specified role '%1' is not a user extended as role

Error constant	SQLE_NOT_AN_EXTENDED_USER
----------------	---------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the role being dropped.
Severity	14
SQLCODE	-1559
SQLSTATE	28W33
Sybase error code	12546

Probable cause

The role name provided is not a user extended as role. Use of FROM USER clause is not allowed in such cases.

1.1.4.926 Specified System Privilege '%1' is Invalid

Error constant	SQLE_INVALID_SYSTEM_PRIVILEGE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the system privilege.
Severity	14
SQLCODE	-1541
SQLSTATE	28W30
Sybase error code	12564

Probable cause

System Privilege specified does not exist in the database.

1.1.4.927 Specified user '%1' is a role

Error constant	SQLE_CAN_NOT_DROP_ROLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	Name of the user being dropped.
Severity	14
SQLCODE	-1558
SQLSTATE	28W32
Sybase error code	12547

Probable cause

You attempted to drop a role. Use DROP ROLE statement.

1.1.4.928 SQL statement error

Error constant	SQLSTATE_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-132
SQLSTATE	26501
Sybase error code	13629

Probable cause

The prepared statement identifier is invalid. In Embedded SQL, an OPEN or EXECUTE failed.

1.1.4.929 SQL statements in BEGIN PARALLEL WORK...END PARALLEL WORK statement are not of the same type

Error constant	PARALLEL_STMT_TYPE_DIFFERENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1936
SQLSTATE	0AW34
Sybase error code	12241

Probable cause

You can only specify one type of SQL statement within a BEGIN PARALLEL WORK...END PARALLEL WORK statement. For example, you cannot specify both a LOAD TABLE and an UNLOAD TABLE statement in the same BEING PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.930 SQL statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_STMT_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1935
SQLSTATE	0AW33
Sybase error code	12242

Probable cause

You specified a SQL statement that is not supported in the BEGIN PARALLEL WORK...END PARALLEL WORK statement or the current database does not support.

1.1.4.931 SQLDA data type invalid

Error constant	SQLE_SQLDA_INVALID_DATATYPE
ODBC 2 state	07001
ODBC 3 state	07W05
Severity	16
SQLCODE	-759

SQLSTATE	07W05
Sybase error code	13770

Probable cause

The data type specified for a SQLDA variable is invalid.

1.1.4.932 SQLDA fields inconsistent for a multi-row SQLDA

Error constant	SQLE_SQLDA_INCONSISTENT
ODBC 2 state	07001
ODBC 3 state	07W04
Severity	16
SQLCODE	-700
SQLSTATE	07W04
Sybase error code	13721

Probable cause

Not all of the rows in a multi-row SQLDA have been defined identically for an array operation (insert, fetch, or execute). A given column must be defined the same (type and length) in each row.

1.1.4.933 sqlpp/dblib version mismatch

Error constant	SQLE_PP_DBLIB_MISMATCH
ODBC 2 state	08801
ODBC 3 state	08001
Severity	21
SQLCODE	-230
SQLSTATE	08W18
Sybase error code	13657

Probable cause

Your executable has Embedded SQL source files that were preprocessed with a version of sqlpp that does not match the database interface library.

1.1.4.934 SRID %1 is referenced by column '%2' of table '%3'

Error constant	SQLE_SLERR_SRS_INUSE_TAB
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The spatial reference system identifier.
Parameter 2	The name of the referencing column.
Parameter 3	The name of the referencing table.
Severity	16
SQLCODE	-1474
SQLSTATE	2FW67
Sybase error code	13098

Probable cause

The specified spatial reference system is in use by the column of a table, and it cannot be modified.

1.1.4.935 SRID %1 is referenced by domain "%3"."%2"

Error constant	SQLE_SLERR_SRS_INUSE_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The spatial reference system identifier.
Parameter 2	The owner of the domain.
Parameter 3	The name of the domain.
Severity	16
SQLCODE	-1476
SQLSTATE	2FW69

Probable cause

The specified spatial reference system is in use by a user-defined domain, and it cannot be modified.

1.1.4.936 SRID %1 is referenced by parameter '%2' of procedure '%3'

Error constant	SQLE_SLERR_SRS_INUSE_PROC
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The spatial reference system identifier.
Parameter 2	The referencing parameter name.
Parameter 3	The referencing procedure name.
Severity	16
SQLCODE	-1475
SQLSTATE	2FW68
Sybase error code	13097

Probable cause

The specified spatial reference system is in use by the parameter of a procedure, and it cannot be modified.

1.1.4.937 ST_Geometry arguments not supported by SQL function %1

Error constant	SQLE_SLERR_SPATIAL_IN_BUILTIN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the SQL function.
Severity	16

SQLCODE	-1478
SQLSTATE	2FW71
Sybase error code	13094

Probable cause

The specified SQL function does not support geometry parameters.

1.1.4.938 ST_MultiSurface contains elements with an invalid intersection (near "%1")

Error constant	SQLE_SLERR_INVALID_MULTISURF_I
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The method or context where the invalid ST_MultiSurface was detected.
Severity	16
SQLCODE	-1502
SQLSTATE	2FW89
Sybase error code	13601

Probable cause

The interiors of any two ST_Surface values in an ST_MultiSurface shall not intersect. The boundaries of any two elements in an ST_MultiSurface may intersect at a finite number of points (and not, for example, in a line segment).

Related Information

[ST_Surface Type](#)
[ST_MultiSurface Type](#)

1.1.4.939 Start date/time for non-recurring event '%1' is in the past

Error constant	SQLE_EVENT_START_TIME_IN_PAST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the event being scheduled.
Severity	15
SQLCODE	-1128
SQLSTATE	WE010
Sybase error code	13385

Probable cause

You have specified an event starting date or time that has already passed, and the event is not recurring.

1.1.4.940 Start listener error: %1

Error constant	SQLE_START_LISTENER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Error text or internal error code
Severity	16
SQLCODE	-1821
SQLSTATE	08WE4
Sybase error code	12323

Probable cause

An error occurred starting a listener.

1.1.4.941 Statement %1 disallowed during upgrade from script

Error constant	SQLE_UPGRADE_DISALLOWED_STMT
ODBC 2 state	08004
ODBC 3 state	08004
Parameter 1	Disallowed statement.
Severity	21
SQLCODE	-1716
SQLSTATE	08X02
Sybase error code	12422

Probable cause

Upgrade from script is not allowed to use the following statements: BACKUP, ALTER DATABASE UPGRADE.

Related Information

[ALTER DATABASE Statement](#)
[BACKUP DATABASE Statement](#)

1.1.4.942 Statement cannot be executed

Error constant	SQLE_CANNOT_EXECUTE_STMT
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	111
SQLSTATE	01W08
Sybase error code	590

Probable cause

You specified a SQL statement for the PREPARE...WITH EXECUTE statement that cannot be executed. If you specified an output SQLDA, it may contain a DESCRIBE of the prepared statement. It is normal for this warning to appear in the request log during the successful execution of a statement.

Related Information

[The SQL Descriptor Area \(SQLDA\)](#)
[PREPARE Statement \[ESQL\]](#)

1.1.4.943 Statement contains an illegal usage of the non-deterministic function '%1'

Error constant	SQLE_NONDETERMINISTIC_FUNCTION
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The name of the non-deterministic user-defined function used in error.
Severity	15
SQLCODE	-889
SQLSTATE	42W79
Sybase error code	13594

Probable cause

Non-deterministic functions cannot appear in a CHECK constraint, or any other type of integrity constraint. They may appear anywhere within a query, view, or derived table. However, if an aliased SELECT list expression contains a non-deterministic function, that alias cannot be referred to elsewhere in the query.

1.1.4.944 Statement contains an illegal usage of the NUMBER(*) function

Error constant	SQLE_INVALID_NUMBER
----------------	---------------------

ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-864
SQLSTATE	42W71
Sybase error code	13869

Probable cause

The NUMBER and IDENTITY functions can only appear in the SELECT list of the outer-most SELECT block. It cannot be used in any subquery or in a predicate.

1.1.4.945 Statement interrupted by user

Error constant	SQLE_INTERRUPTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-299
SQLSTATE	57014
Sybase error code	3621

Probable cause

You canceled a statement during its execution. The database was able to stop the operation without doing a rollback. If the statement is an INSERT, UPDATE, or DELETE, any changes made by the statement will be canceled. If the statement is a data definition statement (for example CREATE TABLE), the statement will be canceled, but the COMMIT that was done as a side effect will not be canceled.

1.1.4.946 Statement is not allowed in passthrough mode

Error constant	SQLE_STMT_NOT_ALLOWED_IN_PASSTHROUGH
ODBC 2 state	37000

ODBC 3 state	42000
Severity	16
SQLCODE	-707
SQLSTATE	0AW05
Sybase error code	13631

Probable cause

You tried to execute a statement that cannot be executed while in passthrough mode. For example, you may have executed a batch statement.

1.1.4.947 Statement not allowed during snapshot

Error constant	SQLSTATE_STATEMENT_NOT_ALLOWED_IN_SNAPSHOT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1062
SQLSTATE	42WB9
Sybase error code	13451

Probable cause

A connection with an outstanding snapshot attempted to use CREATE INDEX, DROP INDEX, ALTER INDEX or ALTER TABLE. Make sure all cursors for the connection are closed.

1.1.4.948 Statement not allowed on IMMEDIATE REFRESH text index

Error constant	SQLSTATE_TEXT_IMMEDIATE_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1182
SQLSTATE	WT015
Sybase error code	13333

Probable cause

You cannot use REFRESH TEXT INDEX or TRUNCATE TEXT INDEX on an index that is created with immediate refresh. You cannot alter a text index to use or stop using immediate refresh.

1.1.4.949 Statement not allowed on text index for a materialized view

Error constant	SQLE_TEXT_MV_TIND_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1555
SQLSTATE	WT038
Sybase error code	12550

Probable cause

You cannot use REFRESH TEXT INDEX or TRUNCATE TEXT INDEX on a text index that is created for a materialized view. You cannot alter the text index to use a different refresh type.

1.1.4.950 Statement requires too much memory during %1

Error constant	SQLE_DYNAMIC_MEMORY_LIMIT
ODBC 2 state	37000
ODBC 3 state	54000
Parameter 1	Description of what the server was doing when the error occurred
Severity	19

SQLCODE	-1899
SQLSTATE	54W19
Sybase error code	12259

Probable cause

The statement requires more dynamic memory than it is allowed to use. Increasing the maximum cache size or reducing the multiprogramming level may resolve this error. Consider rewriting the query so that the internal limit is not exceeded.

1.1.4.951 Statement size or complexity exceeds server limits

Error constant	SQLLE_SYNTACTIC_LIMIT
ODBC 2 state	37000
ODBC 3 state	54000
Severity	19
SQLCODE	-890
SQLSTATE	54W01
Sybase error code	404

Probable cause

The statement contains one or more constructs whose size make it impossible to process. Increasing the maximum cache size, page size, or stack size may resolve this error. Consider rewriting the query so that the internal limit is not exceeded.

1.1.4.952 Statement timed out: '%1'

Error constant	SQLLE_STATEMENT_TIMEOUT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Statement type
Severity	16

SQLCODE	-1231
SQLSTATE	57W05
Sybase error code	13286

Probable cause

The statement failed because it did not complete within the allotted or specified time.

1.1.4.953 Statement's size limit is invalid

Error constant	SQLE_INVALID_CURSOR_RANGE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	15
SQLCODE	-674
SQLSTATE	09W07
Sybase error code	13713

Probable cause

FIRST or TOP n are used in a SELECT statement to limit the size of a result. The size limit must be an integer greater than 0 and less than 9223372036854775807 ($2^{64}-1$).

1.1.4.954 Stop listener error: %1

Error constant	SQLE_STOP_LISTENER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Error text or internal error code
Severity	16
SQLCODE	-1885
SQLSTATE	08WEI

Probable cause

An error occurred stopping a listener.

1.1.4.955 Storing certificates is not supported for this database

Error constant	SQLE_CERTIFICATES_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1587
SQLSTATE	55W42
Sybase error code	12518

Probable cause

The current database does not have catalog support for certificates. To use this feature, upgrade your database to the most recent version.

1.1.4.956 Storing OData Producers is not supported for this database

Error constant	SQLE_ODATA_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1772
SQLSTATE	55W45
Sybase error code	12368

Probable cause

The current database does not have catalog support for OData Producers. To use this feature, upgrade your database to the most recent version.

1.1.4.957 Storing time zone information is not supported for this database

Error constant	SQLC_TIMEZONES_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1789
SQLSTATE	55W49
Sybase error code	12354

Probable cause

The current database does not have catalog support for time zone information. To use this feature, upgrade your database to the most recent version.

1.1.4.958 String '%1' cannot be used as quote when QUOTE ALL is specified

Error constant	UNSUPPORTED_QUOTE_CHARACTER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified quote string.
Severity	19
SQLCODE	-1932
SQLSTATE	WL020
Sybase error code	12244

Probable cause

The specified string cannot be used as a quote for the UNLOAD statement when the QUOTE ALL option is specified.

1.1.4.959 Subquery allowed only one SELECT list item

Error constant	SQLCODE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLSTATE	-151
SQLSTATE	53023
Sybase error code	102

Probable cause

You entered a subquery that has more than one column in the SELECT list. Change the SELECT list to have only one column.

Related Information

[Use of Subqueries](#)
[Subqueries in Expressions - UltraLite](#)

1.1.4.960 Subquery cannot return more than one row

Error constant	SQLCODE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-186
SQLSTATE	21W01

Probable cause

You used a subquery that returns more than one row, in a context where only a single row can be used. If the subquery is in the WHERE clause, you might be able to use the IN keyword.

Related Information

[Use of Subqueries](#)

[Subqueries in Expressions - UltraLite](#)

1.1.4.961 Subscription '%1' not found

Error constant	SQL_E_SUBSCRIPTION_NAME_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of subscription
Severity	16
SQLCODE	-1326
SQLSTATE	5RW40
Sybase error code	13230

Probable cause

You attempted to ALTER, DROP, or otherwise reference a subscription that does not exist.

1.1.4.962 Subscription to '%1' for '%2' already exists

Error constant	SQL_E_SUBSCRIPTION_NOT_UNIQUE
ODBC 2 state	S0002
ODBC 3 state	42S02

Parameter 1	Name of the publication.
Parameter 2	Name of the user.
Severity	16
SQLCODE	-282
SQLSTATE	5RW03
Sybase error code	13644

Probable cause

You attempted to create a subscription that already exists.

1.1.4.963 Subscription to '%1' for '%2' not found

Error constant	SQL_E_SUBSCRIPTION_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the publication.
Parameter 2	Name of the user.
Severity	16
SQLCODE	-283
SQLSTATE	5RW04
Sybase error code	13645

Probable cause

You attempted to drop, start, or synchronize a subscription that does not exist.

1.1.4.964 Subscription to publication '%1' for '%2' omitted from statement

Error constant	SQL_E_SUBSCRIPTION_OMITTED
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	Name of publication
Parameter 2	Name of MobiLink user
Severity	16
SQLCODE	-1323
SQLSTATE	WW141
Sybase error code	13233

Probable cause

A START SYNCHRONIZATION SCHEMA CHANGE statement lists a table that will be modified, but a subscription which refers to that table was omitted from the statement.

1.1.4.965 Support for materialized views is not available for this database

Error constant	SQL_E_MAT_VIEWS_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1029
SQLSTATE	OAW15
Sybase error code	13481

Probable cause

The statement being executed requires support for materialized views, but the database being used does not have the materialized view capability.

1.1.4.966 Support for permissions on dbspaces is not available for this database

Error constant	SQLLE_DBSPACE_PERMS_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1183
SQLSTATE	OAW22
Sybase error code	13332

Probable cause

The statement being executed requires support for permissions on dbspaces, but the database being used does not have this capability. The database must be recreated or upgraded using a version of the server that supports permissions on dbspaces.

1.1.4.967 Support for spatial is not available for this CPU

Error constant	SQLLE_SLERR_CPU_NEED_SSE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1515
SQLSTATE	2FW91
Sybase error code	12589

Probable cause

Spatial data support for 32-bit Windows and 32-bit Linux requires a CPU that supports the SSE2 instructions.

Related Information

[Spatial Data](#)

1.1.4.968 Support for spatial is not available for this database

Error constant	SQLE_SLERR_NEED_UPGRADE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1412
SQLSTATE	2FW02
Sybase error code	13160

Probable cause

Operations involving spatial support cannot be used with this database because it needs to be upgraded to use spatial features.

1.1.4.969 Synchronization download failed to complete

Error constant	SQLE_INCOMPLETE_SYNCHRONIZATION
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1271
SQLSTATE	0AW23
Sybase error code	13899

Probable cause

You attempted to synchronize an UltraLite database. During the synchronization session, an incomplete download stream was received from the consolidated database. The reason for the upload failure can be found in the synchronization log file.

1.1.4.970 Synchronization failed due to an error on the MobiLink server: %1

Error constant	SQLSERVER_SYNCHRONIZATION_ERROR
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The description of the error from the MobiLink server.
Severity	16
SQLCODE	-857
SQLSTATE	0AW12
Sybase error code	13860

Probable cause

Synchronization failed at the MobiLink server. More details can be found in the MobiLink server log file.

1.1.4.971 Synchronization failed with internal error: %1

Error constant	SQLSYNCCMD_INTERNAL_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The internal error number
Severity	16
SQLCODE	-1373
SQLSTATE	5RW43
Sybase error code	13189

Probable cause

An internal error occurred during the execution of the SYNCHRONIZE statement.

1.1.4.972 Synchronization failed. Check the dbmlsync log file for more details

Error constant	SQLE_MLA_SYNC_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1385
SQLSTATE	WW161
Sybase error code	13183

Probable cause

The synchronization was not successful. Check the dbmlsync log file for more details.

1.1.4.973 Synchronization failed. Check the results of the call to `sp_get_last_synchronize_result(%1)` for more information

Error constant	SQLE_SYNCCMD_SYNCH_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The connection ID on which the failed synchronization took place
Severity	16
SQLCODE	-1374
SQLSTATE	5RW44
Sybase error code	13190

Probable cause

The synchronization completed, but the exit code from the synchronization indicates that the synchronization was not successful. Check the results of the call to `sp_get_last_synchronize_result()` for more information.

1.1.4.974 Synchronization is already in progress

Error constant	SQLE_SYNCHRONIZATION_IN_PROGRESS
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1272
SQLSTATE	0AW24
Sybase error code	13893

Probable cause

You attempted to synchronize an UltraLite database but this database is being synchronized on another thread.

1.1.4.975 Synchronization message type '%1' not found

Error constant	SQLE_NOT_SYNC_TYPE
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of synchronization message type.
Severity	16
SQLCODE	-765
SQLSTATE	5RW11
Sybase error code	13775

Probable cause

You referred to a synchronization message type that is not defined in this database.

1.1.4.976 Synchronization option '%1' contains semicolon, equal sign, curly brace, or is null

Error constant	SQLE_BAD_SYNC_OPTION_VALUE
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	The name of the synchronization option.
Severity	16
SQLCODE	-797
SQLSTATE	5RW32
Sybase error code	13807

Probable cause

You attempted to set a synchronization option with an invalid value.

1.1.4.977 Synchronization option '%1' not found

Error constant	SQLE_SYNC_OPTION_NOT_FOUND
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	The name of the synchronization option.
Severity	16
SQLCODE	-805
SQLSTATE	5RW33
Sybase error code	13815

Probable cause

You attempted to delete an undefined synchronization option.

1.1.4.978 Synchronization option is too long

Error constant	SQLE_SYNC_OPTION_TOO_LONG
ODBC 2 state	42000
ODBC 3 state	42S02
Severity	16
SQLCODE	-809
SQLSTATE	5RW34
Sybase error code	13819

Probable cause

Synchronization option list cannot be longer than the database page size.

1.1.4.979 Synchronization profile '%1' already exists

Error constant	SQLE_SYNC_PROFILE_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the synchronization profile.
Severity	16
SQLCODE	-1223
SQLSTATE	42W76
Sybase error code	13294

Probable cause

You tried to create a synchronization profile that already exists.

Related Information

[MobiLink Synchronization Profiles](#)
[CREATE SYNCHRONIZATION PROFILE Statement \[MobiLink\]](#)
[UltraLite Synchronization Profile Options](#)

1.1.4.980 Synchronization profile '%1' has invalid parameter '%2'

Error constant	SQLE_SYNC_PROFILE_INVALID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the synchronization profile that is invalid.
Parameter 2	Name of the parameter in the profile that has the problem.
Severity	16
SQLCODE	-1224
SQLSTATE	42W77
Sybase error code	13293

Probable cause

You tried to create or alter a synchronization profile using a string containing an invalid parameter setting.

Related Information

[MobiLink Synchronization Profiles](#)

[CREATE SYNCHRONIZATION PROFILE Statement \[MobiLink\]](#)

[UltraLite Synchronization Profile Options](#)

[CREATE SYNCHRONIZATION PROFILE Statement \[UltraLite\]](#)

1.1.4.981 Synchronization profile '%1' not found

Error constant	SQLE_SYNC_PROFILE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the synchronization profile.
Severity	16

SQLCODE	-1217
SQLSTATE	42W75
Sybase error code	13302

Probable cause

You tried to access a synchronization profile that the database could not find.

Related Information

[MobiLink Synchronization Profiles](#)

[CREATE SYNCHRONIZATION PROFILE Statement \[MobiLink\]](#)

[UltraLite Synchronization Profile Options](#)

[CREATE SYNCHRONIZATION PROFILE Statement \[UltraLite\]](#)

1.1.4.982 Synchronization profiles are not supported for this database

Error constant	SQLE_SYNC_PROFILE_UPGRADE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1225
SQLSTATE	42W78
Sybase error code	13292

Probable cause

The current database does not have catalog support for synchronization profiles. To use this feature, upgrade your database to the most recent version.

1.1.4.983 Synchronization schema changes and script versions are not supported for this database

Error constant	SQLE_SYNC_SCHEMA_UPGRADE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1319
SQLSTATE	WW137
Sybase error code	13237

Probable cause

The current database does not have catalog support for synchronization schema changes and script versions. To use this feature, upgrade your database to the most recent version.

1.1.4.984 Synchronization server failed to commit the upload

Error constant	SQLE_UPLOAD_FAILED_AT_SERVER
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-794
SQLSTATE	0AW09
Sybase error code	13804

Probable cause

You attempted to synchronize an UltraLite database. During the synchronization session, a complete upload stream was sent that could not be committed to the consolidated database. The reason for the upload failure can be found in the synchronization log file.

Related Information

[How the Upload Is Processed](#)

1.1.4.985 Syntax error near '%1' %2 %3

Error constant	SQLE_SYNTAX_ERROR
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The word or symbol where the syntax error has been detected.
Parameter 2	Line number.
Parameter 3	SQL dialect.
Severity	15
SQLCODE	-131
SQLSTATE	42W04
Sybase error code	102

Probable cause

The database server cannot understand the statement you are trying to execute. If you used a keyword (such as DATE) for a column name, try enclosing the keyword in quotation marks ("DATE") or brackets ([DATE]).

1.1.4.986 Syntax error near '%1' -- Materialized view definition must not use the following construct: '%2'

Error constant	SQLE_MATVIEW_SYNTAX_ERROR
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Location of the feature used that is not permitted.
Parameter 2	The feature used that is not permitted.
Severity	15
SQLCODE	-1031

SQLSTATE	42WB3
Sybase error code	13479

Probable cause

You attempted to create a materialized view whose definition violates one of the restrictions.

1.1.4.987 Syntax error near '%1' -- The materialized view cannot be changed to immediate because its definition contains an illegal construct: '%2'

Error constant	SQLE_UPDATABLE_MATVIEW_SYNTAX_ERROR
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Location of the feature used that is not permitted.
Parameter 2	The feature used that is not permitted.
Severity	15
SQLCODE	-1032
SQLSTATE	42WB4
Sybase error code	13480

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition violates one of the restrictions.

1.1.4.988 System command failed with return code %1

Error constant	SQLE_SYSTEM_COMMAND_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Return code value.

Severity	16
SQLCODE	-910
SQLSTATE	38W01
Sybase error code	13574

Probable cause

A non-zero return code resulted when executing a system command.

1.1.4.989 System event type '%1' not found

Error constant	SQLE_EVENT_TYPE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the system event type that could not be found.
Severity	11
SQLCODE	-806
SQLSTATE	WE008
Sybase error code	13816

Probable cause

You have attempted to create an event with a system event type name that does not exist in the database.

1.1.4.990 System Privileges and Roles feature is not supported in this database

Error constant	SQLE_ROLES_NOT_SUPPORTED
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-1535

SQLSTATE	OAW27
Sybase error code	12570

Probable cause

The current database is an older database and does not have catalog support for System Privileges and Roles feature. To use this feature, upgrade your database to the most recent version.

1.1.4.991 Table '%1' contains a spatial column '%2' and no primary key

Error constant	SQLI_SLERR_UPDDEL_NO_PK
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The table name.
Parameter 2	The spatial column name.
Severity	16
SQLCODE	-1452
SQLSTATE	2FW45
Sybase error code	13120

Probable cause

An update or delete statement cannot be performed for a table that contains a spatial column unless there is a primary key defined for the table.

1.1.4.992 Table '%1' contains an invalid reference to the ROWID function

Error constant	SQLI_INVALID_ROWID_PLACEMENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	Name of the table that contains the invalid reference.
Severity	15
SQLCODE	-1115
SQLSTATE	42WC1
Sybase error code	13399

Probable cause

The ROWID function cannot be used in a computed column expression or in a CHECK constraint.

1.1.4.993 Table '%1' for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_LOADTABLE_TABLE_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified table name.
Severity	16
SQLCODE	-1946
SQLSTATE	OAW42
Sybase error code	12231

Probable cause

The specified table for the LOAD TABLE statement is not supported when the statement is in the BEGIN PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.994 Table '%1' has a foreign key with a referential action

Error constant	SQL_E_TABLE_HAS_REFACTION
----------------	---------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the table with the referential action.
Severity	16
SQLCODE	-677
SQLSTATE	56001
Sybase error code	547

Probable cause

The table could not be renamed as it has a foreign key with a referential action. To rename the table, first drop the foreign key constraints.

1.1.4.995 Table '%1' has no columns

Error constant	SQL_E_TABLE_HAS_NO_COLUMNS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1273
SQLSTATE	0EW00
Sybase error code	13891

Probable cause

You attempted to create a table without columns.

1.1.4.996 Table '%1' has no primary key

Error constant	SQL_E_NO_PRIMARY_KEY
ODBC 2 state	42000

ODBC 3 state	42000
Parameter 1	Name of the table that does not have a primary key.
Severity	16
SQLCODE	-118
SQLSTATE	55008
Sybase error code	1719

Probable cause

You attempted an operation that required the referenced table to have a primary key. Examples of these operations include adding a foreign key, or using the ON EXISTING clause of an INSERT statement, while referring to a table that does not have a primary key. You must add a primary key to the referenced table.

Related Information

[Primary Keys](#)

[Primary Key Uniqueness in UltraLite](#)

[Creating UltraLite Tables](#)

1.1.4.997 Table '%1' has publications

Error constant	SQL_E_TABLE_HAS_PUBLICATIONS
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the table that has publications.
Severity	16
SQLCODE	-281
SQLSTATE	5RW02
Sybase error code	13643

Probable cause

You attempted to drop a table that has publications defined.

Related Information

[Dropping a Table](#)

[Deleting UltraLite Tables](#)

1.1.4.998 Table '%1' is already included

Error constant	SQLE_TABLE_ALREADY_INCLUDED
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	The name of the table.
Severity	16
SQLCODE	-822
SQLSTATE	5RW36
Sybase error code	13828

Probable cause

You attempted to add or modify a publication or synchronization definition such that the same table is included twice.

Related Information

[CREATE PUBLICATION Statement \[MobiLink\] \[SQL Remote\]](#)

[ALTER PUBLICATION Statement \[MobiLink\] \[SQL Remote\]](#)

[CREATE PUBLICATION Statement \[UltraLite\]](#)

[ALTER PUBLICATION Statement \[UltraLite\]](#)

1.1.4.999 Table '%1' is in an outer join cycle

Error constant	SQLE_OUTER_JOIN_CYCLE
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of a table in the cycle.

Severity	16
SQLCODE	-136
SQLSTATE	52W14
Sybase error code	315

Probable cause

You specified outer joins that create a cycle of tables.

1.1.4.1000 Table '%1' is part of a synchronization subscription and can only be ALTERed within a synchronization schema change

Error constant	SQLE_SYNC_CONTAINS_TABLE
ODBC 2 state	42000
ODBC 3 state	42S02
Parameter 1	The name of the table.
Severity	16
SQLCODE	-819
SQLSTATE	5RW35
Sybase error code	13825

Probable cause

A table belonging to a synchronization subscription cannot be altered except within a synchronization schema change or by using dbmlsync.

1.1.4.1001 Table '%1' must synchronize to be in publication '%2'

Error constant	SQLE_TABLE_MUST_SYNCHRONIZE_IN_PUB
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	Name of table
Parameter 2	Name of publication
Severity	16
SQLCODE	-1328
SQLSTATE	WW143
Sybase error code	13228

Probable cause

A publication cannot contain a table with a SYNCHRONIZE OFF constraint; all tables in a publication must synchronize. You attempted to add a table with a SYNCHRONIZE OFF constraint to a publication, or to alter a table to use SYNCHRONIZE OFF when the table is already in a publication.

Related Information

[ALTER TABLE Statement](#)
[ALTER TABLE Statement \[UltraLite\]](#)

1.1.4.1002 Table '%1' not found

Error constant	SQL_E_TABLE_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the table that could not be found.
Severity	11
SQLCODE	-141
SQLSTATE	42W33
Sybase error code	2706

Probable cause

You misspelled the name of a table, or you did not qualify a table name with the owner name. For example, you might have referred to "table_name" instead of "owner"."table_name".

Related Information

[Database Object Names and Prefixes](#)

[User-extended Roles](#)

[FROM Clause](#)

[FROM Clause \[UltraLite\]](#)

1.1.4.1003 Table '%1' requires a unique correlation name

Error constant	SQLC_CORRELATION_NAME_NEEDED
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the table that needs a unique correlation name.
Severity	16
SQLCODE	-137
SQLSTATE	52W15
Sybase error code	315

Probable cause

You specified a join that joins a table to itself. You need to use unique correlation names to have multiple instances of a table.

1.1.4.1004 Table '%1' specified more than once in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_STMT_DUPLICATE_TABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1937
SQLSTATE	42WF8
Sybase error code	12240

Probable cause

You specified the same table more than once in the BEGIN PARALLEL WORK...END PARALLEL WORK statement. Remove the duplicated database table from the statement in the BEGIN PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.1005 Table already has a primary key

Error constant	SQLE_EXISTING_PRIMARY_KEY
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-112
SQLSTATE	55013
Sybase error code	1923

Probable cause

You attempted to add a primary key on a table that already has a primary key defined. You must delete the current primary key before adding a new one.

1.1.4.1006 Table cannot have two primary keys

Error constant	SQLE_PRIMARY_KEY_TWICE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-126
SQLSTATE	52W05
Sybase error code	1923

Probable cause

You specified the primary key twice in a CREATE TABLE statement.

Related Information

[CREATE TABLE Statement](#)

[CREATE TABLE Statement \[UltraLite\]](#)

1.1.4.1007 Table created or altered after start of snapshot

Error constant	SQL_E_SNAPSHOT_TABLE_CHANGED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1061
SQLSTATE	42WB8
Sybase error code	13452

Probable cause

A snapshot transaction attempted to use a table that was created or altered after the transaction began.

1.1.4.1008 Table in use

Error constant	SQL_E_TABLE_IN_USE
ODBC 2 state	40001
ODBC 3 state	40001
Severity	16
SQLCODE	-214
SQLSTATE	42W21
Sybase error code	3702

Probable cause

You attempted to ALTER or DROP a table that is being used by other active users of the database.

Related Information

[Table Alteration](#)
[Dropping a Table](#)
[Altering UltraLite Column Definitions](#)
[Deleting UltraLite Tables](#)
[ALTER TABLE Statement](#)
[DROP TABLE Statement](#)
[ALTER TABLE Statement \[UltraLite\]](#)
[DROP TABLE Statement \[UltraLite\]](#)

1.1.4.1009 Table must be empty

Error constant	SQLE_TABLE_MUST_BE_EMPTY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-116
SQLSTATE	55W02
Sybase error code	4901

Probable cause

You attempted to modify a table, and the database server can only perform the change if there are no rows in the table.

1.1.4.1010 Table name '%1' is ambiguous

Error constant	SQLE_AMBIGUOUS_TABLE_NAME
ODBC 2 state	S0013
ODBC 3 state	42S13
Parameter 1	Name of an ambiguous table.
Severity	16
SQLCODE	-852
SQLSTATE	52W42

Probable cause

A statement has referred to a table name that is not unique. Preface the table name by an owner name.

1.1.4.1011 Table or view '%1' is not valid for use with this statement

Error constant	SQLE_INVALID_TABLE_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of table
Severity	16
SQLCODE	-1321
SQLSTATE	WW139
Sybase error code	13235

Probable cause

The named table or view cannot be used with this statement. For example, the statement may not allow temporary tables or views.

1.1.4.1012 Table Parameterized Functions and V4 TableUDFs are not supported for this database

Error constant	SQLE_TPF_UPGRADE_REQUIRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1605
SQLSTATE	WP020

Probable cause

The current database does not have catalog support for table parameterized functions. To use this feature, upgrade your database to the most recent version.

1.1.4.1013 Table parameterized functions are not allowed across server types

Error constant	SQL_E_TPF_NOT_ALLOWED_ACROSS_SERVERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1578
SQLSTATE	W0009
Sybase error code	12527

Probable cause

Table parameterized functions are not allowed across server types if a query is not processed in full-passthrough mode.

1.1.4.1014 Table reference '%1' has been invalidated

Error constant	SQL_E_TABLEREF_INVALIDATED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the table reference variable
Severity	16
SQLCODE	-1794
SQLSTATE	42X11
Sybase error code	12349

Probable cause

You tried to use a table reference whose referent has been dropped since the table reference was created.

1.1.4.1015 Table reference types not supported

Error constant	SQLE_TABLeref_TYPES_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1793
SQLSTATE	0AW30
Sybase error code	12350

Probable cause

The current database is an older database and does not have support for table reference types. To use this feature, upgrade your database to the most recent version.

1.1.4.1016 Tables related by key constraint must both be permanent, or both be temporary and not created with ON COMMIT DELETE ROWS. For global temporary tables they must both be shared if one is shared

Error constant	SQLE_INVALID_FOREIGN_KEY_TABLE
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-850
SQLSTATE	42R02
Sybase error code	1709

Probable cause

Tables involved in a key constraint relationship must both be permanent user tables or both be temporary tables not created with ON COMMIT DELETE ROWS. Change the definition of one or both tables using ALTER TABLE.

1.1.4.1017 Tag ID: '%1' specifies a value not bounded by an array

Error constant	SQLE_FOR_JSON_EXPLICIT_NOT_IN_ARRAY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value of the tag ID which is not bounded by an array.
Severity	16
SQLCODE	-1613
SQLSTATE	WX017
Sybase error code	12493

Probable cause

A union of multiple queries whose tags have the same parent may generate this error when the queries mix object and value notation.

Related Information

[ROW and ARRAY Composite Data Types](#)
[ARRAY Constructor \[Composite\]](#)

1.1.4.1018 Task '%1' is not allowed

Error constant	SQLSYSPRIV_CREATION_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the internal task that was provided by the user.

Severity	16
SQLCODE	-1527
SQLSTATE	28W18
Sybase error code	12578

Probable cause

Creation of system privilege is an internal task, allowed only during database creation or upgrade.

1.1.4.1019 TDS login requests with RSA encrypted passwords must also use a nonce

Error constant	SQLE_RSA_ENCRYPTED_TDS_LOGIN_MUST_HAVE_NONCE
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-1701
SQLSTATE	28W23
Sybase error code	12434

Probable cause

You attempted to perform a TDS login with a client that does not use a nonce with the RSA encrypted password. The current TDS login setting does not allow RSA encrypted TDS login requests without a nonce. Change the tds1 server option setting or connect using a TDS client that supports a nonce with the RSA encrypted password.

Related Information

[-tds1 Database Server Option](#)

1.1.4.1020 TDS login requests with unencrypted passwords are not permitted

Error constant	SQLE_UNENCRYPTED_TDS_LOGIN_REQUESTS_NOT_PERMITTED
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-1700
SQLSTATE	28W22
Sybase error code	12435

Probable cause

You attempted to perform a TDS login without using RSA encryption for the password. The current TDS login setting does not allow unencrypted TDS login requests. Change the tds server option setting or connect using an RSA encrypted password.

Related Information

[-tdsl Database Server Option](#)

1.1.4.1021 Temporary mutex or semaphore can only be dropped by the connection that created it

Error constant	SQLE_NOT_TEMP_OWNER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	14
SQLCODE	-1809
SQLSTATE	28W24
Sybase error code	12335

Probable cause

A temporary mutex or semaphore object can only be dropped by the connection that created it.

1.1.4.1022 Temporary space limit exceeded

Error constant	SQLE_TEMP_SPACE_LIMIT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-1000
SQLSTATE	54W05
Sybase error code	13492

Probable cause

The connection has exceeded its temporary-space usage limit. This limit is based in part on the amount of free-space remaining on the drive containing the temporary file. Try deleting unused files from the drive, or placing the temporary file on a drive with more space available. See the -dt server option to specify a directory for temporary files.

1.1.4.1023 Term length outside allowed range

Error constant	SQLE_TEXT_BAD_TERM_LENGTH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1162
SQLSTATE	WT007
Sybase error code	13351

Probable cause

The minimum and maximum term lengths must both be greater than 0 and less than or equal to 60 characters.

1.1.4.1024 Terminated by user -- transaction rolled back

Error constant	SQL_E_TERMINATED_BY_USER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-302
SQLSTATE	40W02
Sybase error code	3618

Probable cause

You canceled a statement while the database was executing. A ROLLBACK statement has been automatically executed.

1.1.4.1025 Text configuration "%1" already exists

Error constant	SQL_E_TEXT_CONFIG_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The text configuration name.
Severity	16
SQLCODE	-1161
SQLSTATE	WT006
Sybase error code	13352

Probable cause

The specified text configuration name already exists.

1.1.4.1026 Text configuration "%1"."%2" not found

Error constant	SQL_E_TEXT_CONFIG_NOT_FOUND
----------------	-----------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The text configuration creator.
Parameter 2	The text configuration name.
Severity	16
SQLCODE	-1160
SQLSTATE	WT005
Sybase error code	13353

Probable cause

The specified text configuration does not exist.

1.1.4.1027 Text index \"%1\" on table \"%2\" exists. Table with text index is not supported for LOAD TABLE statement in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_LOADTABLE_TEXTINDEX_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the text index.
Parameter 2	The name of the table.
Severity	16
SQLCODE	-1947
SQLSTATE	OAW43
Sybase error code	12230

Probable cause

The specified table for the LOAD TABLE statement is not supported when it has a text index and the statement is in the BEGIN PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.1028 Text index %1 cannot be used with text procedure %2

Error constant	SQLE_TEXT_INVALID_INDEX_FOR_PROC
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the text index.
Parameter 2	The name of the procedure for which the specified index is invalid.
Severity	16
SQLCODE	-1526
SQLSTATE	WT036
Sybase error code	12579

Probable cause

The specified text procedure cannot be used with the text index. The text procedure charset has to correspond to the charset of the text index it is accessing.

Related Information

[Text Index Concepts and Reference](#)

1.1.4.1029 Text index with external prefilter cannot contain both binary and string columns

Error constant	SQLE_TEXT_INDEX_MIXED_COLUMNS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1512
SQLSTATE	WT034
Sybase error code	12592

Probable cause

One or more, but not all, of the columns specified for the text index is of type binary, and the text configuration object has a prefilter library specified. Text indexes using a prefilter library can contain either binary columns or string data type columns, but not both.

Related Information

[Text Index Concepts and Reference](#)
[CREATE TEXT INDEX Statement](#)

1.1.4.1030 Text indexes are not allowed across server types

Error constant	SQL_E_TEXT_NOT_ALLOWED_ACROSS_SERVERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1511
SQLSTATE	WT033
Sybase error code	12593

Probable cause

Text indexes are not allowed across server types if the query is processed in full-passthrough mode.

Related Information

[Text Index Concepts and Reference](#)
[CREATE TEXT INDEX Statement](#)

1.1.4.1031 Text indexes are not supported for this database

Error constant	SQL_E_TEXT_UPGRADE_REQUIRED
----------------	-----------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1166
SQLSTATE	WT011
Sybase error code	13347

Probable cause

The current database does not have catalog support for text indexes. To use this feature, upgrade your database to the most recent version.

1.1.4.1032 Text indexes on materialized views are not supported for this database

Error constant	SQL_E_TEXT_MV_UPGRADE_REQUIRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1592
SQLSTATE	WT041
Sybase error code	12513

Probable cause

The current database does not have catalog support for text indexes on materialized views. To use this feature, upgrade your database to the most recent version.

1.1.4.1033 Text queries cannot contain more than 300 terms

Error constant	SQL_E_TEXT_QUERY_TOO_LONG
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Severity	16
SQLCODE	-1370
SQLSTATE	WT022
Sybase error code	13192

Probable cause

A text query should contain 300 terms or less.

1.1.4.1034 Text query parser error: %1

Error constant	SQLE_TEXT_PARSER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The error message returned by the text query parser.
Severity	16
SQLCODE	-1164
SQLSTATE	WT009
Sybase error code	13349

Probable cause

The text query could not be parsed.

1.1.4.1035 The %1 algorithm is not available in FIPS mode

Error constant	SQLE_FIPS_NOT_AVAILABLE
ODBC 2 state	ERROR
ODBC 3 state	08001
Parameter 1	Name of the algorithm.
Severity	19
SQLCODE	-1071

SQLSTATE	OAW16
Sybase error code	13442

Probable cause

The specified algorithm is not available when the server is running in FIPS mode.

1.1.4.1036 The %1 remote data access class is no longer supported, please use %2 instead

Error constant	SQL_E_OMNI_JDBC_NO_LONGER_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The JDBC based remote data access class.
Parameter 2	The preferred ODBC based remote data access class.
Severity	16
SQLCODE	-1617
SQLSTATE	W0033
Sybase error code	12489

Probable cause

You attempted to use a JDBC based remote data access class which is no longer supported. Please use the appropriate ODBC based class instead.

1.1.4.1037 The '%1' attribute contains mismatched parentheses within '%2'

Error constant	SQL_E_INVALID_ATTRIBUTE_MISMATCH_BRACES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The attribute on the procedure.

Parameter 2	The value of the attribute.
Severity	16
SQLCODE	-1129
SQLSTATE	WW086
Sybase error code	13384

Probable cause

The value of the attribute is not valid due to mismatched parenthesis (or possibly braces if specifying a port option).

1.1.4.1038 The '%1' attribute is missing a comma within '%2'

Error constant	SQLE_INVALID_ATTRIBUTE_MISSING_COMMA
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The value of the attribute.
Severity	16
SQLCODE	-1130
SQLSTATE	WW087
Sybase error code	13383

Probable cause

The value of the attribute is not valid due to a missing comma.

1.1.4.1039 The '%1' attribute is not valid with procedure type '%2'

Error constant	SQLE_INVALID_ATTRIBUTE_WITH_TYPE
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The procedure type.
Severity	16
SQLCODE	-1034
SQLSTATE	WW064
Sybase error code	13477

Probable cause

This attribute is not applicable to the given procedure type.

1.1.4.1040 The '%1' property is no longer supported

Error constant	SQLE_UNSUPPORTED_PROPERTY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the invalid property.
Severity	16
SQLCODE	-1119
SQLSTATE	42WC2
Sybase error code	13394

Probable cause

The specified property is not supported in the current release.

1.1.4.1041 The 'currval' operator is not defined yet for sequence '%1' for this connection

Error constant	SQLE_SEQUENCE_CURRVAL_NOT_DEFINED
ODBC 2 state	42000

ODBC 3 state	42000
Parameter 1	Name of the sequence.
Severity	16
SQLCODE	-1363
SQLSTATE	52W51
Sybase error code	13199

Probable cause

The currval operator of a sequence generator is only defined once nextval has been called for the sequence within the current connection.

1.1.4.1042 The address parameter "%1" conflicts with an existing %2 listener

Error constant	SQLLE_START_LISTENER_CONFLICT_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener address parameter
Parameter 2	The listener type
Severity	16
SQLCODE	-1765
SQLSTATE	08WD1
Sybase error code	12375

Probable cause

You attempted to start a listener that already is running. The specified address parameter conflicts with an existing listener.

1.1.4.1043 The address parameter "%1" provided to stop a listener has an invalid IP address or no port

Error constant	SQL_E_STOP_LISTENER_INVALID_ADDRESS_OR_NO_PORT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The listener address parameter
Severity	16
SQLCODE	-1884
SQLSTATE	08WEH
Sybase error code	12266

Probable cause

You attempted to stop a listener with an invalid IP address or no port number. For example, a port number should be specified when stopping a listener.

1.1.4.1044 The aggregate expression '%1' must appear in either the SELECT list or a HAVING clause subquery

Error constant	SQL_E_INVALID_AGGREGATE_PLACEMENT
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The aggregated expression in error.
Severity	15
SQLCODE	-862
SQLSTATE	42W69
Sybase error code	13866

Probable cause

An aggregated expression containing an outer reference must either appear in a SELECT list expression (a subselect), or in a HAVING clause subquery in the query whose FROM clause contains the table with the column being aggregated.

1.1.4.1045 The arguments to this procedure must be literal strings

Error constant	SQLE_TEXT_NEED_CONSTANT_ARGUMENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1216
SQLSTATE	WT017
Sybase error code	13297

Probable cause

This procedure only accepts literal strings as arguments.

1.1.4.1046 The attempt to drop LDAP server "%1" failed, suspend the server to drop it

Error constant	SQLE_INVALID_STATE_CHANGE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the LDAP Server.
Severity	16
SQLCODE	-1571
SQLSTATE	WW204
Sybase error code	12534

Probable cause

An attempt to drop an LDAP Server failed because it was in the READY or ACTIVE state. Use WITH SUSPEND to change state before dropping server.

1.1.4.1047 The attribute '%1' sets an option '%2' that is incompatible with '%3'

Error constant	SQL_INVALID_ATTRIBUTE_OPTIONS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The attribute on the procedure.
Parameter 2	The first option of the attribute.
Parameter 3	The second option of the attribute.
Severity	16
SQLCODE	-1131
SQLSTATE	WW088
Sybase error code	13382

Probable cause

The options specified for this attribute are not compatible.

1.1.4.1048 The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2'

Error constant	SQL_LDAPUA_BINDFAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The LDAP URL used with bind().
Parameter 2	The LDAP API error message.
Severity	16
SQLCODE	-1600
SQLSTATE	WW211
Sybase error code	12506

Probable cause

The message is reported from the LDAP API client with context from the LDAP User Authentication methods. An LDAP administrator or SAP Tech Support may use these low level messages to direct the DBA how to resolve a problem.

1.1.4.1049 The column '%1' does not exist in the remote table

Error constant	SQLE_OMNI_NOSUCH_COLUMN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the column.
Severity	11
SQLCODE	-722
SQLSTATE	W0016
Sybase error code	11208

Probable cause

The column specified in the CREATE EXISTING statement does not exist in the remote table.

1.1.4.1050 The communications environment could not be created

Error constant	SQLE_FAILED_TO_CREATE_STREAMS_ENV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-740
SQLSTATE	WW024
Sybase error code	13753

Probable cause

The communications environment could not be created. Either there are insufficient resources to create the environment or the language resource file cannot be found.

1.1.4.1051 The comparison '%1' cannot be used with geometries

Error constant	SQLE_SLERR_COMPARISON_PREDICATE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The type of comparison relation.
Severity	16
SQLCODE	-1440
SQLSTATE	2FW33
Sybase error code	13132

Probable cause

Geometry values cannot be compared with operators such as < or >. Geometries can only be compared with = and <>.

1.1.4.1052 The connection parameters file could not be found

Error constant	SQLE_NO_PROFILE_FILE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-654
SQLSTATE	08W37
Sybase error code	13706

Probable cause

An attempt was made to parse a connection string containing a connection profile but the connection parameters file could not be found.

1.1.4.1053 The CONVERT USING clause must be specified when creating a unit of measure

Error constant	SQLE_SLERR_DDL_UOM_NOFACT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1455
SQLSTATE	2FW48
Sybase error code	13117

Probable cause

A CREATE SPATIAL UNIT OF MEASURE statement was used without including the CONVERT USING clause.

1.1.4.1054 The cursor name '%1' already exists

Error constant	SQLE_DUPLICATE_CURSOR_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the cursor.
Severity	16
SQLCODE	-683
SQLSTATE	WJ004
Sybase error code	13714

Probable cause

You attempted to declare a cursor with a name that already exists. Cursor names must be unique within a connection.

Related Information

[Cursor Usage](#)

1.1.4.1055 The data is not in a recognized format

Error constant	SQLE_SLERR_UNKOWNN_FORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1434
SQLSTATE	2FW27
Sybase error code	13138

Probable cause

The provided string is not in a recognized format to parse a geometry.

1.1.4.1056 The data type of column or variable '%1' is not supported

Error constant	SQLE_OMNI_UNSUPPORTED_DATATYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the column or variable.
Severity	12
SQLCODE	-736
SQLSTATE	W0022

Probable cause

The column is defined with a data type that is not supported for remote tables or the variable is defined with a datatype that is not supported for using and location clauses.

1.1.4.1057 The data type specified for column '%1' is not compatible with the actual data type

Error constant	SQLE_OMNI_DATATYPE_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the column.
Severity	12
SQLCODE	-721
SQLSTATE	W0015
Sybase error code	11209

Probable cause

The data type of the column specified in the CREATE EXISTING statement is not compatible with the actual data type of the column in the remote table.

1.1.4.1058 The database '%1' cannot be used for the SQL Anywhere Cockpit

Error constant	SQLE_CANNOT_USE_NON_COCKPIT_DATABASE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database file.
Severity	16

SQLCODE	-1840
SQLSTATE	08WF4
Sybase error code	12304

Probable cause

The specified database file cannot be used for the SQL Anywhere Cockpit.

1.1.4.1059 The database '%1' was not found

Error constant	SQLE_ULTRALITE_DATABASE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the database specified or the default database name.
Severity	16
SQLCODE	-954
SQLSTATE	WW034
Sybase error code	13534

Probable cause

The named database was not found. Ensure your connection string properly names the desired database.

Related Information

[UltraLite Database Connections](#)

1.1.4.1060 The database must be upgraded to use the KEY option on the SYNCHRONIZE command

Error constant	SYNC_PROFILE_UPGRADE_KEY
----------------	--------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1986
SQLSTATE	42W7B
Sybase error code	12197

Probable cause

The current database does not allow the use of the KEY option on the SYNCHRONIZE command. To use this feature, upgrade your database to the most recent version.

1.1.4.1061 The database name 'utility_db' is reserved for the utility database

Error constant	SQL_E_DB_ALIAS_RESERVED_UTILDB
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-985
SQLSTATE	08W20
Sybase error code	13504

Probable cause

You are attempting to start a database with the name "utility_db". This name is reserved for the utility database.

1.1.4.1062 The database name is reserved for SQL Anywhere Cockpit

Error constant	SQL_E_DB_ALIAS_RESERVED_SQLACOCKPITDB
----------------	---------------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1843
SQLSTATE	08WF7
Sybase error code	12301

Probable cause

You are attempting to start a database with the reserved name. This name is reserved for the SQL Anywhere Cockpit.

1.1.4.1063 The database server failed to shut down the dbmlsync server

Error constant	SQL_E_SYNCCMD_SHUTDOWN_FAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1378
SQLSTATE	5RW48
Sybase error code	13194

Probable cause

The database server started a new dbmlsync server to process the SYNCHRONIZE statement, but encountered an error while attempting to shut the process down.

1.1.4.1064 The database was created

Error constant	SQL_E_DATABASE_CREATED
ODBC 2 state	OK
ODBC 3 state	OK

Severity	10
SQLCODE	136
SQLSTATE	WW061
Sybase error code	13494

Probable cause

The specified UltraLite database was created using the specified schema when the connection was opened.

1.1.4.1065 The dbicu library and server versions do not match

Error constant	SQLLE_ICU_DLL_VERSION_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1124
SQLSTATE	WC014
Sybase error code	13389

Probable cause

The server is unable to load ICU components that are required by this database. Ensure that the correct version of the dbicu libraries are installed.

1.1.4.1066 The dbmlsync server did not have sufficient database permissions

Error constant	SQLLE_SYNCCMD_CANT_ACCESS_RESULT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1714

SQLSTATE	5RW50
Sybase error code	12424

Probable cause

The SYNCHRONIZE statement attempts to store the results of the synchronization in the synchronize_results and synchronize_parameters tables. The user who executed the command, or the user specified in the USER clause of the SYNCHRONIZE statement must have permission to insert rows into these tables.

Related Information

[SYNCHRONIZE Statement \[MobiLink\]](#)

1.1.4.1067 The dbmlsync server failed to shut down in a timely manner

Error constant	SQL_E_SYNCCMD_SHUTDOWN_SLOW
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1379
SQLSTATE	5RW49
Sybase error code	13195

Probable cause

The database server started a new dbmlsync server to process the SYNCHRONIZE statement, was successful in requesting that the process shut down, but the process did not shut down within the timeout value that was specified.

1.1.4.1068 The DBN/DBF parameters do not match the database for this alternate server name

Error constant	SQLE_WRONG_DB_ON_ALT_SERVER_NAME
ODBC 2 state	08001
ODBC 3 state	08001
Severity	11
SQLCODE	-1036
SQLSTATE	08W90
Sybase error code	13475

Probable cause

The DBN or DBF parameters specified do not match the database using the specified alternate server name.

1.1.4.1069 The dbspace '%1' cannot be dropped because it contains tables or indexes

Error constant	SQLE_DBSPACE_CONTAINS_TABLES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the dbspace
Severity	16
SQLCODE	-1120
SQLSTATE	55W26
Sybase error code	13393

Probable cause

You attempted to drop the named dbspace, but it contains tables or indexes. You must drop the tables and/or indexes before dropping the dbspace.

1.1.4.1070 The definition of temporary table '%1' has changed since last used

Error constant	SQLE_TEMP_TABLE_DEFINITION_CHANGED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The table name
Severity	16
SQLCODE	-1397
SQLSTATE	WW165
Sybase error code	13174

Probable cause

The definition of a temporary table has changed since it was last used in a stored procedure or trigger. The procedure must be recompiled.

1.1.4.1071 The embedded SRID (%1) conflicts with the provided SRID (%2)

Error constant	SQLE_SLERR_SRID_CONFLICT_EMBED_PARAM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The SRID within the parsed string.
Parameter 2	The SRID provided as a parameter.
Severity	16
SQLCODE	-1426
SQLSTATE	2FW19
Sybase error code	13146

Probable cause

A call to a spatial method had a string with an embedded SRID that differed from the SRID parameter to the method.

1.1.4.1072 The embedded SRID are inconsistent (%1 and %2)

Error constant	SQL_E_SLERR_SRID_CONFLICT_EMBED_EMBED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The first SRID.
Parameter 2	The second SRID.
Severity	16
SQLCODE	-1427
SQLSTATE	2FW20
Sybase error code	13145

Probable cause

A geometry in a string representation contains objects from different spatial reference systems.

1.1.4.1073 The file '%1' is invalid when the disk sandbox feature is enabled for database '%2'

Error constant	SQL_E_DISKSANDBOX_INVALID_PATH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the invalid file.
Parameter 2	The name of the database that the disk sandbox feature is enabled for.
Severity	15
SQLCODE	-1671
SQLSTATE	57W06
Sybase error code	12452

Probable cause

The file passed to the operation is invalid when the sandbox feature is enabled.

Related Information

[-sbx Database Option](#)
[-sbx Database Server Option](#)
[disk_sandbox Option](#)

1.1.4.1074 The format specification option '%1' is not recognized

Error constant	SQLC_SLERR_INVALID_FORMAT_SPECIFICATION_OPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid option.
Severity	16
SQLCODE	-1432
SQLSTATE	2FW25
Sybase error code	13140

Probable cause

The named option is not supported for the format specification.

1.1.4.1075 The format specification syntax is invalid

Error constant	SQLC_SLERR_INVALID_FORMAT_SPECIFICATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1431
SQLSTATE	2FW24
Sybase error code	13141

Probable cause

The format specification is invalid.

1.1.4.1076 The format type '%1' cannot be used here

Error constant	SQLE_SLERR_FMT_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid format type.
Severity	16
SQLCODE	-1429
SQLSTATE	2FW22
Sybase error code	13143

Probable cause

The specified format type cannot be used in this context.

1.1.4.1077 The format type '%1' is not recognized

Error constant	SQLE_SLERR_FMT_UNKNOWN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid format type.
Severity	16
SQLCODE	-1428
SQLSTATE	2FW21
Sybase error code	13144

Probable cause

The specified format type is not recognized.

1.1.4.1078 The function '%1' does not allow use of the '%2' clause

Error constant	SQLE_FUNCTION_DOES_NOT_ALLOW
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the function.
Parameter 2	The SQL clause not allowed.
Severity	16
SQLCODE	-1330
SQLSTATE	42WE0
Sybase error code	13226

Probable cause

You have attempted to use the specified SQL clause within the context of a function that does not permit such use. Note that the function may have been used directly in the query or indirectly within a named window.

1.1.4.1079 The function '%1' requires the use of the '%2' clause

Error constant	SQLE_FUNCTION_REQUIRES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the function.
Parameter 2	The SQL clause required.
Severity	16
SQLCODE	-1331
SQLSTATE	42WE1
Sybase error code	13225

Probable cause

You have attempted to invoke the specified function without the use of a mandatory SQL clause within the context of the function. Note that the function may have been used directly in the query or indirectly within a named window.

1.1.4.1080 The HTTP header '%1' is reserved and cannot be modified

Error constant	SQLE_HTTP_HEADER_ATTRIBUTE_RESERVED_XXX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The header causing the failure.
Severity	16
SQLCODE	-1094
SQLSTATE	WW070
Sybase error code	13421

Probable cause

The specified HTTP header is reserved and cannot be modified.

1.1.4.1081 The ICU collation '%1' has defaulted to another collation

Error constant	SQLE_COLLATION_DEFAULT_WARNING
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	The ICU collation specifier.
Severity	10
SQLCODE	201
SQLSTATE	01WC4
Sybase error code	13397

Probable cause

The specified ICU collation is not available. Another collation was substituted, which may or may not produce suitable results. Due to the structure of ICU, the collation that was used is not known, but was the best alternative to the specified collation. If this database is used on another platform, a different collation may be chosen and the operation may generate different results.

Related Information

[What Is ICU and When Is It Needed?](#)

1.1.4.1082 The instantiation '%1' does not match an overload (near '%2'). Available overloads are '%3'

Error constant	SQL_METHOD_NO_CONSTRUCTOR_OVERLOAD
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The type name and data types used in the new specification.
Parameter 2	The invalid expression.
Parameter 3	The available constructor overloads.
Severity	11
SQLCODE	-1341
SQLSTATE	42X06
Sybase error code	13215

Probable cause

When attempting to match a new specification, none of the defined constructor overloads was found to match the provided argument types. You may need to use CAST to select the appropriate call.

1.1.4.1083 The integrated login ID guest can only be mapped to the guest database user ID

Error constant	SQL_INTEGRATED_LOGON_GUESTMAP
----------------	-------------------------------

ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-247
SQLSTATE	28W06
Sybase error code	13695

Probable cause

You attempted to map the guest login ID to something other than guest.

1.1.4.1084 The intermediate point (%3) of the ST_CircularString segment between %1 and %2 is collinear with but not between the start and end points

Error constant	SQLE_SLERR_CIRC_COLLINEAR_MIDPOINT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The start point of the ST_CircularString segment
Parameter 2	The end point of the ST_CircularString segment
Parameter 3	The specified intermediate point of the ST_CircularString segment
Severity	16
SQLCODE	-1516
SQLSTATE	2FF72
Sybase error code	12588

Probable cause

When the intermediate point of a ST_CircularString segment is collinear with the start and end point the result is interpreted as a straight line between the start and the end point. In this case, the intermediate point must be located on the line segment between the start and end point.

1.1.4.1085 The last HTTP or HTTPS listener cannot be stopped without using the force parameter

Error constant	SQLE_STOP_HTTP_LISTENER_CANNOT_STOP_THE_LAST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1781
SQLSTATE	08WD9
Sybase error code	12359

Probable cause

You attempted to stop the last HTTP or HTTPS listener. You may want to use the force parameter to stop the last listener.

1.1.4.1086 The last shared memory or TCPIP listener cannot be stopped without using the force parameter

Error constant	SQLE_STOP_LISTENER_CANNOT_STOP_THE_LAST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1768
SQLSTATE	08WD4
Sybase error code	12372

Probable cause

You attempted to stop the last shared memory or TCP/IP listener. You may want to use the force parameter to stop the last listener.

1.1.4.1087 The length of the value specified is too long, it exceeds the limit of %1 bytes

Error constant	SQLE_LDAPUA_OPT_TOO_LONG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The maximum length of the value.
Severity	16
SQLCODE	-1624
SQLSTATE	WW216
Sybase error code	12482

Probable cause

The specified value for an LDAP server option is too long. Specify a shorter string.

1.1.4.1088 The length of the variable '%1' is too long in this context; it exceeds the limit of %2 bytes

Error constant	SQLE_VARIABLE_PARM_TOO_LONG_IN_THIS_CONTEXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the variable that is longer than that allowed by the server.
Parameter 2	The maximum length allowed by the server in this context.
Severity	15
SQLCODE	-1723
SQLSTATE	54W18
Sybase error code	12414

Probable cause

The length of the variable is longer than allowed by the server in this context.

1.1.4.1089 The length specified for column '%1' is different than the actual length

Error constant	SQLLE_OMNI_LENGTH_MISMATCH
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	The name of the column.
Severity	16
SQLCODE	-723
SQLSTATE	W0017
Sybase error code	11210

Probable cause

The length of the column specified in the CREATE EXISTING statement is different than the length of the column in the remote table.

1.1.4.1090 The licensed maximum number of mirror servers with type COPY has been exceeded

Error constant	SQLLE_MIRROR_COPY_SERVER_LIMIT_EXCEEDED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1383
SQLSTATE	WW160
Sybase error code	13185

Probable cause

The maximum number of mirror servers with type COPY that may be defined is limited by the database server license. An attempt was made to create a new mirror server with type COPY when the maximum allowed number of such servers already existed.

1.1.4.1091 The logging type ('%1') specified is invalid, not supported or incompatible

Error constant	SQLE_INVALID_LOAD_LOGGING_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified logging type.
Severity	19
SQLCODE	-1151
SQLSTATE	WL010
Sybase error code	13261

Probable cause

The logging type specified for LOAD TABLE is not supported for the version of the database being used, is incompatible with other specifications of the statement or is not supported for the specific table being loaded into.

1.1.4.1092 The login ID '%1' has not been mapped to any database user ID

Error constant	SQLE_LOGON_UNMAPPED
ODBC 2 state	28000
ODBC 3 state	28000
Parameter 1	Name of the login ID that is not mapped.
Severity	16
SQLCODE	-313
SQLSTATE	28W09
Sybase error code	13698

Probable cause

You attempted to connect using a login ID that is not mapped to a database user ID and there is no guest database user ID, or you attempted to revoke a login ID that has not been mapped. This can also occur when attempting to connect using an integrated login ID that is a member of more than one mapped group.

1.1.4.1093 The login ID '%1' is already mapped to user ID '%2'

Error constant	SQLE_LOGON_MAPPED
ODBC 2 state	28000
ODBC 3 state	28000
Parameter 1	Name of the login ID that is already mapped.
Parameter 2	Name of the user that the login ID is already mapped to.
Severity	16
SQLCODE	-249
SQLSTATE	28W08
Sybase error code	13697

Probable cause

You attempted to map a login ID twice.

1.1.4.1094 The materialized view %1 cannot be changed to immediate because it does not have a unique index on non-nullable columns

Error constant	SQLE_IMMEDIATE_MV_NO_UNIQUE_INDEX
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Name of the materialized view.
Severity	14
SQLCODE	-1233
SQLSTATE	42WCA
Sybase error code	13284

Probable cause

You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-nullable columns. Create a unique index on the materialized view before changing the refresh type.

1.1.4.1095 The materialized view %1 cannot be changed to immediate because it has already been initialized

Error constant	SQLE_IMMEDIATE_MV_REFRESH_NOT_ALLOWED
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Name of the materialized view.
Severity	14
SQLCODE	-1170
SQLSTATE	42WC3
Sybase error code	13343

Probable cause

You attempted to change the refresh type to immediate for a materialized view which is already in an initialized state. Truncate the view before changing the refresh type.

1.1.4.1096 The materialized view cannot be changed to immediate because at least one non-nullable column from any null-supplying side of an OUTER JOIN must exist in the SELECT list

Error constant	SQLE_UPDATABLE_MATVIEW_ISNOTNULL
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1508
SQLSTATE	42WE8
Sybase error code	12595

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose SELECT list doesn't contain at least one non-nullable column for any null-supplying side of an OUTER JOIN.

Related Information

[Materialized Views](#)

[ALTER MATERIALIZED VIEW Statement](#)

1.1.4.1097 The materialized view cannot be changed to immediate because COUNT(*) must be part of the SELECT list

Error constant	SQLE_UPDATABLE_MATVIEW_MISSING_COUNT
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1199
SQLSTATE	42WC6
Sybase error code	13316

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition does not include COUNT(*) in the SELECT list.

1.1.4.1098 The materialized view cannot be changed to immediate because it does not have a unique index on non-aggregate, non-nullable columns

Error constant	SQLE_UPDATABLE_MATVIEW_NON_AGGR_INDEX
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1218
SQLSTATE	42WC7
Sybase error code	13299

Probable cause

You attempted to change the refresh type to immediate for a materialized view which does not have a unique index on non-aggregate non-nullable columns. Create a unique index on the materialized view before changing the refresh type.

1.1.4.1099 The materialized view cannot be changed to immediate because its definition contains an illegal construct

Error constant	SQLE_UPDATABLE_MATVIEW_ERR
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1268
SQLSTATE	42WCB
Sybase error code	13786

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal construct.

1.1.4.1100 The materialized view cannot be changed to immediate because its definition must not contain more than one query block

Error constant	SQLE_UPDATABLE_MATVIEW_MULTIBLE_BLOCK_ERR
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1181
SQLSTATE	42WC5
Sybase error code	13334

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains more than one query block.

1.1.4.1101 The materialized view cannot be changed to immediate because its SELECT list contains a SUM function over a nullable expression and it doesn't contain a COUNT function over the same expression

Error constant	SQLU_UPDATABLE_MATVIEW_COUNT_NULL_EXPR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1327
SQLSTATE	42WCE
Sybase error code	13229

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains a SUM function over a nullable expression but it doesn't contain COUNT function over the same expression.

1.1.4.1102 The materialized view cannot be changed to immediate because the ON conditions must refer to both sides of the OUTER JOIN

Error constant	SQLU_UPDATABLE_MATVIEW_PSNS_ON_CONDITION
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1371
SQLSTATE	42WE4

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal ON condition.

1.1.4.1103 The materialized view cannot be changed to immediate because the ON conditions refer to tables which are not in the null-supplying and preserved sides of the OUTER JOINS

Error constant	SQLUPDATABLE_MATVIEW_OUTERREFERENCE_ON_CONDITION
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1507
SQLSTATE	42WE7
Sybase error code	12596

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose definition contains an illegal ON condition.

Related Information

[Materialized Views](#)
[Materialized Views Restrictions](#)
[ALTER MATERIALIZED VIEW Statement](#)

1.1.4.1104 The materialized view cannot be changed to immediate because the primary key columns of any table in the preserved side of an OUTER JOIN must exist in the SELECT list

Error constant	SQLE_UPDATABLE_MATVIEW_PK
ODBC 2 state	42000
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1509
SQLSTATE	42WE9
Sybase error code	12594

Probable cause

You attempted to change the refresh type to immediate for a materialized view whose SELECT list doesn't contain the primary key columns of any table in the preserved side of an OUTER JOIN.

Related Information

[Materialized Views](#)
[ALTER MATERIALIZED VIEW Statement](#)

1.1.4.1105 The method you attempted to invoke was not enabled for your application

Error constant	SQLE_FEATURE_NOT_ENABLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1092
SQLSTATE	0A001
Sybase error code	13442

Probable cause

You attempted to call a method or use a feature that has not been enabled. In UltraLite, features are enabled using ULEnable functions or by using ULEnableDatabaseManager instead of ULEnableDatabaseManagerNoSQL.

1.1.4.1106 The minimum percentage '%1' is invalid. The minimum percentage must be between 0 and 100.

Error constant	PROFILER_INVALID_MIN_PERCENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The specified minimum percentage.
Severity	16
SQLCODE	-2068
SQLSTATE	WW267
Sybase error code	12119

Probable cause

The specified minimum percentage is invalid. The minimum percentage must be between 0 and 100.

1.1.4.1107 The mirror '%1' does not match database '%2'

Error constant	SQL_E_MIRROR_FILE_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the mirror file
Parameter 2	The name of the database file
Severity	16
SQLCODE	-1138
SQLSTATE	WW090
Sybase error code	13375

Probable cause

The named mirror file does not correspond to the database file. This could happen if the database was not shut down properly, or if the wrong mirror file was specified. The mirror file must be moved or discarded before proceeding, or a different mirror specified.

1.1.4.1108 The multi patch shapefile shape is not supported

Error constant	SQLE_SLERR_SHAPE_MULTIPATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1425
SQLSTATE	2FW16
Sybase error code	13147

Probable cause

The shapefile contains a multi patch object; this type is not supported.

1.1.4.1109 The OData server returned an error: %1

Error constant	SQLE_ODATA_SERVER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Text of the error
Severity	16
SQLCODE	-1796
SQLSTATE	55W51
Sybase error code	12347

Probable cause

An error was returned from the OData server when executing an OData statement.

1.1.4.1110 The operation cannot be executed while the profiler is running

Error constant	INVALID_WHILE_PROFILER_IS_RUNNING
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2061
SQLSTATE	55W61
Sybase error code	12129

Probable cause

The operation cannot be executed while the profiler is running. Stop the profiler by calling the procedure `sp_stop_profiling` and try again.

1.1.4.1111 The operation failed because column '%1's type does not support streaming

Error constant	SQLC_COLUMN_NOT_STREAMABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The number of the column whose type is invalid.
Severity	16
SQLCODE	-1100
SQLSTATE	WW045
Sybase error code	13414

Probable cause

The only column types that support streaming are: BINARY, LONG BINARY, VARCHAR and LONG VARCHAR. This error could also occur when allocating a stream object twice on the same column.

1.1.4.1112 The optimizer was unable to construct a valid access plan

Error constant	SQLE_CANNOT_OPTIMIZE_QUERY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	18
SQLCODE	-727
SQLSTATE	WI010
Sybase error code	13730

Probable cause

The database server was unable to construct a valid access plan for the given request. This is a SQL Anywhere internal error. If it can be reproduced, it should be reported to SAP. You may be able to work around this problem by modifying the query statement.

1.1.4.1113 The option '%1' can only be set as a temporary option

Error constant	SQLE_OPTION_IS_TEMP_ONLY
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the option that could not be set.
Severity	14
SQLCODE	-216
SQLSTATE	42W52
Sybase error code	5878

Probable cause

The option specified in the SET OPTION statement can only be set as a temporary option.

1.1.4.1114 The option '%1' cannot be set from within a procedure

Error constant	SQLE_OPTION_IN_PROCEDURE
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the option that could not be set.
Severity	14
SQLCODE	-217
SQLSTATE	42W53
Sybase error code	5878

Probable cause

The option specified in the SET OPTION statement cannot be set from within a procedure.

1.1.4.1115 The option '%1' is not recognized

Error constant	SQLE_UNRECOGNIZED_OPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the option.
Severity	16
SQLCODE	-1002
SQLSTATE	WW062
Sybase error code	13494

Probable cause

The specified option was not recognized. The option may have been spelled incorrectly.

Related Information

[UltraLite Connection Strings and Parameters](#)

1.1.4.1116 The option '%1' was not specified for target type '%2'

Error constant	SQL_E_OPTION_FOR_TARGET_TYPE_NOT_SPECIFIED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The option name.
Parameter 2	The trace event target type.
Severity	11
SQLCODE	-1648
SQLSTATE	WE033
Sybase error code	12475

Probable cause

A required option for target type was not specified.

1.1.4.1117 The output path '%1' is invalid

Error constant	PROFILER_INVALID_OUTPUT_PATH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2065
SQLSTATE	WW265
Sybase error code	12125

Probable cause

The specified output path is invalid.

1.1.4.1118 The PAM User Authentication (PAMUA) feature is not supported on this computer

Error constant	SQLE_PAMUA_FEATURE_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1749
SQLSTATE	0AW29
Sybase error code	12394

Probable cause

You attempted to use the PAM User Authentication feature; however, PAM is not supported on this computer.

1.1.4.1119 The parent of this mirror server is not currently connected

Error constant	SQLE_PARENT_NOT_CONNECTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1349
SQLSTATE	WW152
Sybase error code	13208

Probable cause

The statement being executed requires a connection from this mirror server to its parent, but the parent is not currently connected.

1.1.4.1120 The parent of this mirror server is not the primary server

Error constant	SQLE_PARENT_NOT_PRIMARY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1350
SQLSTATE	WW153
Sybase error code	13207

Probable cause

The statement being executed requires a connection from this mirror server to the primary server, but the parent is not the primary server. The connection string to this server's parent does not match the connection string for the primary server.

1.1.4.1121 The pattern is too long

Error constant	SQLE_PATTERN_TOO_LONG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-606
SQLSTATE	WW001
Sybase error code	7706

Probable cause

The pattern for the LIKE operator is too long. All patterns of 126 characters or less are supported. Some patterns as long as 254 characters are supported, depending on their contents. Patterns longer than 254 characters are not supported.

1.1.4.1122 The profiler has not been initialized. Contact SAP support.

Error constant	PROFILER_NOT_INITIALIZED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	18
SQLCODE	-2064
SQLSTATE	W1114
Sybase error code	12126

Probable cause

The profiler has not been initialized. Contact SAP support.

1.1.4.1123 The profiler is already running

Error constant	PROFILER_ALREADY_STARTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2063
SQLSTATE	55W63
Sybase error code	12127

Probable cause

The profiler is already running.

1.1.4.1124 The profiler is not running

Error constant	PROFILER_NOT_STARTED
----------------	----------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2062
SQLSTATE	55W62
Sybase error code	12128

Probable cause

The profiler is not running.

1.1.4.1125 The profiler is not supported

Error constant	PROFILER_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2058
SQLSTATE	0AW49
Sybase error code	12132

Probable cause

The profiler is not supported.

1.1.4.1126 The provided stoplist is too long

Error constant	SQLTEXT_STOPLIST_TOO_LONG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1240

SQLSTATE	WT018
Sybase error code	13277

Probable cause

A text configuration stop list must be less than 8000 bytes.

1.1.4.1127 The remote data access feature is not supported on this platform

Error constant	SQLE_OMNI_FEATURE_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1139
SQLSTATE	OAW18
Sybase error code	13374

Probable cause

You attempted to use a remote data access feature; however, remote data access is not supported on this platform.

1.1.4.1128 The remote server does not support an auto-incrementing data type

Error constant	SQLE_OMNI_AUTOINC_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	12
SQLCODE	-698
SQLSTATE	W0011

Probable cause

Auto-incrementing data types can only be supported in a proxy table when the remote server supports this feature.

1.1.4.1129 The remote table '%1' could not be found

Error constant	SQLE_OMNI_RMT_TABLE_NOTFOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The complete name of the remote table.
Severity	11
SQLCODE	-666
SQLSTATE	W0007
Sybase error code	11214

Probable cause

The table could not be found on the remote server. Check the remote table name and the user privileges on that table.

1.1.4.1130 The result returned is non-deterministic

Error constant	SQLE_NONDETERMINISTIC_RESULT
ODBC 2 state	01000
ODBC 3 state	01000
Severity	10
SQLCODE	122
SQLSTATE	01W18
Sybase error code	13883

Probable cause

FIRST or TOP n are used in a SELECT statement to limit the size of a result. The statement must also have an ORDER BY if the result is to be well-defined. If it does not have an ORDER BY, then the server is free to return any subset of the result that has the requested number of rows.

Related Information

[Row Limitation Clauses in SELECT, UPDATE, and DELETE Query Blocks](#)
[SELECT Statement](#)

1.1.4.1131 The role '%1' was not dropped because it is granted to other users or roles. Use the 'WITH REVOKE' option to drop it

Error constant	SQLE_CONTAINS_PRIV_GRANTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the role being dropped.
Severity	14
SQLCODE	-1562
SQLSTATE	28W36
Sybase error code	12543

Probable cause

The role being dropped has been granted to other users or roles with WITH NO ADMIN OPTION or with WITH ADMIN OPTION. A role can be dropped when either all of its grants are with WITH ADMIN ONLY OPTION or WITH REVOKE option is specified in DROP ROLE command. Either revoke all such grants or use WITH REVOKE option for DROP ROLE.

1.1.4.1132 The sample wait time cannot be changed once samples have been collected. Clear the sample data and then set the option.

Error constant	PROFILER_WAIT_TIME_CANNOT_CHANGE_ONCE_SAMPLES_COLLECTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2069
SQLSTATE	WW268
Sybase error code	12118

Probable cause

The sample wait time cannot be changed once samples have been collected. Clear the sample data and then set the option.

1.1.4.1133 The search on LDAP server %1 completed with no matching results

Error constant	SQLLE_LDAPUA_NO_SEARCH_RESULTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The LDAP server name or search URL specifying the search.
Severity	16
SQLCODE	-1623
SQLSTATE	WW220
Sybase error code	12483

Probable cause

An LDAPUA search or validate failed returning LDAP_NO_RESULTS_RETURNED. This error is expected when the user does not exist in the LDAP server.

1.1.4.1134 The search using '%1' failed due to one or more invalid values set

Error constant	SQLE_LDAPUA_SEARCHFAIL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The LDAP server name or search URL specifying the search.
Severity	16
SQLCODE	-1603
SQLSTATE	WW214
Sybase error code	12503

Probable cause

An LDAPUA search or validate failed returning LDAP_INVALID_CREDENTIALS, LDAP_INSUFFICIENT_ACCESS, LDAP_INVALID_DN_SYNTAX, LDAP_NO_SUCH_OBJECT, or LDAP_FILTER_ERROR due to the invalid settings. Check the access account values for the named LDAP server or search URL.

1.1.4.1135 The secure connection to the remote host failed: %1

Error constant	SQLE_SECURE_CONNECTION_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	A message describing the error that occurred.
Severity	19
SQLCODE	-990
SQLSTATE	WW059
Sybase error code	13499

Probable cause

The server was unable to initiate a secure connection with the remote host.

1.1.4.1136 The secure feature key name '%2' is not valid in the call to %1

Error constant	SQLE_SFC_INVALID_NAME
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Severity	15
SQLCODE	-1687
SQLSTATE	08S03
Sybase error code	12441

Probable cause

An invalid secure feature key name was passed to the specified procedure.

Related Information

[Secured Features](#)

[-sf Database Server Option](#)

[sa_server_option System Procedure](#)

1.1.4.1137 The SELECT list for the derived table '%1' has no expression to match '%2'

Error constant	SQLE_NO_MATCHING_SELECT_ITEM
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the derived table.
Parameter 2	Name of the alias for which there is no matching expression.
Severity	15
SQLCODE	-812
SQLSTATE	42W59

Probable cause

The specified alias from the derived table's AS clause has no matching expression from the SELECT statement for that derived table. Ensure that each SELECT list item has a matching alias in the derived table's AS clause, and vice-versa.

Related Information

[The FROM Clause: Specifying Tables](#)
[FROM Clause](#)
[Subqueries in Expressions - UltraLite](#)

1.1.4.1138 The selected database is currently inactive

Error constant	SQL_E_DATABASE_NOT_ACTIVE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	14
SQLCODE	-74
SQLSTATE	08W30
Sybase error code	950

Probable cause

The selected database is in an inactive state. The database may be in the process of being started or shut down.

1.1.4.1139 The server attempted to access a page beyond the end of the maximum allowable dbspace file size

Error constant	SQL_E_ACCESS_BEYOND_END_OF_MAX_DBSPACE
----------------	--

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-605
SQLSTATE	04W08
Sybase error code	5006

Probable cause

The database attempted to access a page whose page number is beyond the maximum possible number of disk pages. This is a fatal internal error.

1.1.4.1140 The server is not able to establish TCP/IP connections

Error constant	SQL_E_TCP_CONNECTIONS_NOT_ENABLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1372
SQLSTATE	08WA3
Sybase error code	13190

Probable cause

This database server is not able to establish TCP/IP connections. The personal server (dbeng) does not permit TCP/IP connections by default. This error may also occur if a network server (dbsrv) was started with the -xd command line option. The ability to establish TCP/IP connections is required to use diagnostic tracing.

Related Information

[Creating a Connection Listener \(SQL Central\)](#)
[sp_start_listener System Procedure](#)

1.1.4.1141 The size of the character column, variable, or value data type exceeds 32767

Error constant	SQLE_CHAR_FIELD_SIZE_EXCEEDED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-1093
SQLSTATE	54W09
Sybase error code	13422

Probable cause

The declaration or conversion has specified a character type with byte length greater than 32767.

1.1.4.1142 The spatial reference system type is not supported ('%1')

Error constant	SQLE_SLERR_DDL_SRS_BAD_SRS_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unsupported spatial reference system type.
Severity	16
SQLCODE	-1464
SQLSTATE	2FW57
Sybase error code	13108

Probable cause

The specified spatial reference system type is not supported.

1.1.4.1143 The specified axis order is not supported for this type of spatial reference system

Error constant	SQLE_SLERR_DDL_SRS_AXISORD
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1468
SQLSTATE	2FW61
Sybase error code	13104

Probable cause

The specified axis order is not supported for this type of spatial reference system.

1.1.4.1144 The specified certificate is not valid

Error constant	SQLE_INVALID_CERTIFICATE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1588
SQLSTATE	55W43
Sybase error code	12517

Probable cause

The certificate value does not represent a valid certificate.

Related Information

[Server Authentication](#)
[skip_certificate_name_check Protocol Option \(Client Side Only\)](#)

1.1.4.1145 The specified distinguished name '%1' does not match the search result '%2'

Error constant	SQLE_LDAPUA_DN_NOMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The expected distinguished name that was specified in command.
Parameter 2	The result distinguished name returned by LDAP search.
Severity	16
SQLCODE	-1602
SQLSTATE	WW213
Sybase error code	12504

Probable cause

VALIDATE LDAP SERVER command did a successful search to find a user distinguished name, but the value differs from the expected distinguished name specified in the command.

1.1.4.1146 The specified foreign key (%1) cannot be enforced

Error constant	SQLE_UNENFORCEABLE_FOREIGN_KEY
ODBC 2 state	23000
ODBC 3 state	23000
Parameter 1	Name of the foreign key.
Severity	16
SQLCODE	-729
SQLSTATE	23507
Sybase error code	549

Probable cause

You attempted to create a foreign key that cannot be enforced. To be enforceable, the primary and foreign table for the specified key must exist on the same server. You can use the UNENFORCED keyword to create a foreign key specification that is not to be enforced.

1.1.4.1147 The specified HTTP header contains illegal or non-ASCII characters

Error constant	SQLE_HTTP_HEADER_ATTRIBUTE_ASCII
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1095
SQLSTATE	WW071
Sybase error code	13420

Probable cause

HTTP headers must contain printable ASCII characters.

1.1.4.1148 The specified HTTP header is malformed

Error constant	SQLE_HTTP_HEADER_ATTRIBUTE_MALFORMED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1096
SQLSTATE	WW072
Sybase error code	13419

Probable cause

The HTTP header is missing the colon delimiter or a folding construct is malformed.

1.1.4.1149 The specified listener could not be registered

Error constant	SQLE_CANNOT_REGISTER_LISTENER
----------------	-------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	17
SQLCODE	-992
SQLSTATE	54W04
Sybase error code	13497

Probable cause

The specified listener could not be registered because the maximum number of listeners has been reached, the class name is already in use, or system resources are not available.

1.1.4.1150 The specified polygon format '%1' is not supported for this type of spatial reference system

Error constant	SQLE_SLERR_DDL_SRS_POLYFORMAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The polygon format string.
Severity	16
SQLCODE	-1469
SQLSTATE	2FW62
Sybase error code	13103

Probable cause

The specified polygon format is not supported for this type of spatial reference system.

1.1.4.1151 The specified session name '%1' is not valid

Error constant	SQLE_INVALID_TRACE_EVENT_SESSION_NAME
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Severity	11
SQLCODE	-1634
SQLSTATE	WE020
Sybase error code	12469

Probable cause

The specified trace event session name is not valid.

1.1.4.1152 The specified target type '%1' is not valid

Error constant	SQL_E_INVALID_TRACE_EVENT_TARGET_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event target type.
Severity	11
SQLCODE	-1646
SQLSTATE	WE031
Sybase error code	12473

Probable cause

The specified trace event target type is not valid.

1.1.4.1153 The specified transaction isolation is invalid

Error constant	SQL_E_INVALID_TRANSACTION_ISOLATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15

SQLCODE	-676
SQLSTATE	WJ003
Sybase error code	7374

Probable cause

The specified transaction isolation is invalid.

1.1.4.1154 The SQL Anywhere Cockpit '%1' cannot be used for the current operation

Error constant	SQL_E_CANNOT_USE_COCKPIT_DATABASE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the file.
Severity	16
SQLCODE	-1841
SQLSTATE	08WF5
Sybase error code	12303

Probable cause

You cannot use this operation with the SQL Anywhere Cockpit.

1.1.4.1155 The SQL Anywhere Cockpit template '%1' cannot be used for the current operation

Error constant	SQL_E_COCKPITDB_TEMPLATE_USE_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the SQL Anywhere Cockpit template file.
Severity	16

SQLCODE	-1878
SQLSTATE	08WF9
Sybase error code	12272

Probable cause

You cannot use this operation with the SQL Anywhere Cockpit template.

1.1.4.1156 The SQL Anywhere Cockpit template file '%1' not found

Error constant	SQLE_SQLACOCKPITDB_TEMPLATE_FILE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The SQL Anywhere Cockpit template file name that does not exist or fail to access
Severity	16
SQLCODE	-1860
SQLSTATE	08WG2
Sybase error code	12287

Probable cause

You attempted to perform an operation using the SQL Anywhere Cockpit template that does not exist or fail to access.

1.1.4.1157 The SQL scripts DLL cannot be loaded

Error constant	SQLE_INVALID_SCRIPT_DLL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1150

SQLSTATE	WW091
Sybase error code	13362

Probable cause

The SQL scripts DLL cannot be loaded. The DLL might be missing or the version found might not match the version of the database server being used.

1.1.4.1158 The SRID %1 does not identify a geographic spatial reference system

Error constant	SQLE_SLERR_NOT_GEOGRAPHIC
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The spatial reference system identifier.
Severity	16
SQLCODE	-1477
SQLSTATE	2FW70
Sybase error code	13095

Probable cause

The methods ST_Lat() and ST_Long() can only be used for geographic spatial reference systems.

1.1.4.1159 The status of the last synchronization upload is unknown

Error constant	SQLE_SYNC_STATUS_UNKNOWN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-952

SQLSTATE	WW032
Sybase error code	13536

Probable cause

The status of the last synchronization upload is unknown. The current operation cannot proceed until a successful upload is synchronized.

Related Information

[How the Upload Is Processed](#)

1.1.4.1160 The string '%1' is not a valid axis order

Error constant	SQLE_SLERR_DDL_SRS_AXISORDER
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid axis order.
Severity	16
SQLCODE	-1456
SQLSTATE	2FW49
Sybase error code	13116

Probable cause

The specified string is not a valid axis order.

1.1.4.1161 The string '%1' is not a valid coordinate name

Error constant	SQLE_SLERR_DDL_SRS_COORDNAME
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The invalid coordinate name.
Severity	16
SQLCODE	-1457
SQLSTATE	2FW50
Sybase error code	13115

Probable cause

The provided string is not the name of a coordinate. Coordinate names are X, Y, Z, M, Latitude and Longitude.

1.1.4.1162 The string is too long (%1)

Error constant	SQLE_STRING_PARM_TOO_LONG
ODBC 2 state	37000
ODBC 3 state	54000
Parameter 1	The string that is longer than that allowed by the server.
Severity	15
SQLCODE	-973
SQLSTATE	54W06
Sybase error code	13515

Probable cause

The string is longer than that allowed by the server.

1.1.4.1163 The synchronization failed because MobiLink returned authentication status '%1' with value '%2'

Error constant	SQLE_MOBILINK_AUTHENTICATION_FAILED
ODBC 2 state	28000
ODBC 3 state	28000

Parameter 1	The authentication status number.
Parameter 2	The authentication value number.
Severity	14
SQLCODE	-1497
SQLSTATE	28W17
Sybase error code	4002

Probable cause

MobiLink returned an authentication status to the remote database indicating failure. The status and value numbers indicate why the authentication failed. For example, the password was invalid, or a synchronization is already in progress for this remote.

Related Information

[Authentication Process](#)

[authenticate_parameters Connection Event](#)

[authenticate_user Connection Event](#)

1.1.4.1164 The SYNCHRONIZE statement timed out

Error constant	SQLE_SYNCCMD_TIMEOUT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1377
SQLSTATE	5RW47
Sybase error code	13193

Probable cause

The SYNCHRONIZE statement did not complete within the timeout value specified. Check the results of the call to `sp_get_last_synchronize_result()` for more information.

1.1.4.1165 The table specification '%1' identifies more than one remote table

Error constant	SQLE_OMNI_RMT_TABLE_NOTUNIQUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The complete name of the remote table.
Severity	11
SQLCODE	-726
SQLSTATE	W0020
Sybase error code	11215

Probable cause

More than one table was found on the remote server for the given table specification. Add a database or owner name to the specification.

1.1.4.1166 The text index %1 needs to be refreshed

Error constant	SQLE_TEXT_MATCHING_INDEX_NOT_REFRESHED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the text index that needs to be refreshed.
Severity	16
SQLCODE	-1253
SQLSTATE	WT019
Sybase error code	13260

Probable cause

There is a text index that matches the query, but it needs to be refreshed before it is used.

1.1.4.1167 The transaction may not be committed because the primary server lost quorum

Error constant	SQLE_LOST_QUORUM_ON_COMMIT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1597
SQLSTATE	WW166
Sybase error code	12509

Probable cause

You attempted to commit a transaction on a primary server that just lost quorum with the partner and arbiter servers. The transaction may or may not have been committed. The partner servers will attempt to determine which server will become the new primary server.

Related Information

[Database Mirroring](#)

[Troubleshooting: How to Recover from Primary Server Failure](#)

[Recovering Uncommitted Operations \(SQL Central\)](#)

1.1.4.1168 The UltraLite database deploy file is invalid (code: %1, file: %2)

Error constant	SQLE_ULTRALITE_DEPLOY_FILE_INVALID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The diagnostic code.
Parameter 2	The associated filename, if applicable.
Severity	16
SQLCODE	-1625
SQLSTATE	WU002

Probable cause

The UltraLite database deploy file is invalid. This can occur if the wrong file is deployed, or if the file is damaged. Diagnostic code 1 indicates the file is not a deploy file or has subsequently been corrupted. Diagnostic code 2 indicates the file is not a valid size.

1.1.4.1169 The URI '%1' is invalid

Error constant	SQLE_INVALID_URI
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid URI.
Severity	16
SQLCODE	-980
SQLSTATE	WW049
Sybase error code	13509

Probable cause

The specified URI is not valid.

1.1.4.1170 The user name specified must be the user name of the current connection

Error constant	SQLE_CREATE_SCHEMA_USER_DOES_NOT_MATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1703
SQLSTATE	42WD5
Sybase error code	12433

Probable cause

In the CREATE SCHEMA AUTHORIZATION clause, you specified a user name other than the user name of the current connection.

Related Information

[CREATE SCHEMA Statement](#)

1.1.4.1171 The USING LOG PATH clause must be used in conjunction with the RECOVER UNTIL clause

Error constant	SQL restore_INVALID_LOG_PATH_CLAUSE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-1770
SQLSTATE	42WF4
Sybase error code	12370

Probable cause

The USING LOG PATH clause can only be used to specify the location of files required for point-in-time recovery, and so either an offset or timestamp must be specified as a point to recover to using the RECOVER UNTIL clause.

1.1.4.1172 The UTF-16 endian specified does not match the Byte Order Mark found in the data

Error constant	SQL_UTF16_ENDIAN_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1189
SQLSTATE	WC004
Sybase error code	13326

Probable cause

The specified UTF-16 encoding explicitly specifies the expected endian of the data; however, the Byte Order Mark found at the beginning of the data indicates that the data is encoded in the opposite endian.

1.1.4.1173 The value '%2' is not a valid setting for the '%1' format specification option

Error constant	SQLE_SLERR_INVALID_FORMAT_SPECIFICATION_OPTION_VALUE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The invalid value.
Parameter 2	The format specification option.
Severity	16
SQLCODE	-1433
SQLSTATE	2FW26
Sybase error code	13139

Probable cause

The value is not accepted by the specification option.

1.1.4.1174 The value for the stoplist cannot be NULL

Error constant	SQLE_TEXT_STOPLIST_NULL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1389
SQLSTATE	WT023
Sybase error code	13179

Probable cause

The value for a text configuration stoplist cannot be NULL. To remove a stoplist, use the ALTER TEXT CONFIGURATION...DROP STOPLIST statement.

1.1.4.1175 The value specified is not within the required range %1 to %2

Error constant	SQLE_LDAPUA_OPT_OUT_OF_RANGE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The minimum value for this option.
Parameter 2	The maximum value for this option.
Severity	16
SQLCODE	-1620
SQLSTATE	WW217
Sybase error code	12486

Probable cause

The specified value for an LDAP server option is too big or too small.

1.1.4.1176 The variable '%1' must be %2 in this context

Error constant	SQLE_VARIABLE_MUST_BE_OF_DIFFERENT_DOMAIN_IN_THIS_CONTEXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the variable.

Parameter 2	The type that the variable must be in this context.
Severity	15
SQLCODE	-1724
SQLSTATE	42X09
Sybase error code	12413

Probable cause

The variable passed to the statement has the incorrect type.

1.1.4.1177 The variable '%1' must not be NULL in this context

Error constant	SQL_E_VARIABLE_MUST_NOT_BE_NULL_IN_THIS_CONTEXT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the variable that must not be NULL in this context.
Severity	15
SQLCODE	-1722
SQLSTATE	42X08
Sybase error code	12415

Probable cause

The variable passed to the statement must not be NULL in this context.

1.1.4.1178 The variable in the INTO clause is not a row type

Error constant	SQL_E_INTO_CLAUSE_NOT_A_ROW_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1814
SQLSTATE	WP029
Sybase error code	12330

Probable cause

You attempted to assign more than one fetched value into a single variable, but it is not a row data type.

1.1.4.1179 There is already a database variable named '%1'

Error constant	SQLE_DATABASE_VARIABLE_EXISTS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the database variable that already exists.
Severity	15
SQLCODE	-1882
SQLSTATE	WP031
Sybase error code	12268

Probable cause

You attempted to create a database variable with the name of another database variable that already exists.

1.1.4.1180 There are still active database connections

Error constant	SQLE_STILL_ACTIVE_CONNECTIONS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-109
SQLSTATE	08W06
Sybase error code	6001

Probable cause

You attempted to shut down a database that still has active connections.

1.1.4.1181 There is already a variable named '%1'

Error constant	SQLE_VARIABLE_EXISTS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the variable that already exists.
Severity	15
SQLCODE	-261
SQLSTATE	42W15
Sybase error code	134

Probable cause

You attempted to create a variable with the name of another variable that already exists.

1.1.4.1182 There is more than one way to join '%1' to '%2'

Error constant	SQLE_AMBIGUOUS_JOIN
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of first table that cannot be joined.
Parameter 2	Name of second table that cannot be joined.
Severity	16
SQLCODE	-147
SQLSTATE	52W08
Sybase error code	301

Probable cause

You are attempting to KEY JOIN two tables, and there are two or more foreign keys relating the two tables. There may be two foreign keys from the first table to the second table. It may be that each table has a foreign

key to the other table. You must use a correlation name for the primary key table that is the same as the role name of the desired foreign key relationship.

1.1.4.1183 There is no profiler data available

Error constant	NO_PROFILER_DATA
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-2060
SQLSTATE	55W60
Sybase error code	12130

Probable cause

There is no profiler data available. To get profiling data a profiling session must be started and stopped using the procedures `sp_start_profiling` and `sp_stop_profiling`.

1.1.4.1184 There is no way to join '%1' to '%2'

Error constant	SQLE_CANNOT_JOIN
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of first table that cannot be joined.
Parameter 2	Name of second table that cannot be joined.
Severity	16
SQLCODE	-146
SQLSTATE	53W04
Sybase error code	301

Probable cause

You may have attempted a KEY JOIN between two tables and there is no foreign key on one of the tables that references the primary key of the other table. You may have attempted a NATURAL JOIN between two tables that have no common column names.

1.1.4.1185 There is no way to join to '%1'

Error constant	SQLE_CANNOT_JOIN_TABEXPR
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of table or view that cannot be joined.
Severity	15
SQLCODE	-875
SQLSTATE	42W73
Sybase error code	102

Probable cause

The server cannot discover a valid join condition involving this table. If the join is an outer join, you may be missing an ON clause. If the join is a KEY JOIN, the server cannot discover a foreign key-primary key relationship with this table that can be used to generate the join condition. If the join is a NATURAL JOIN, the table has no common column names with the table expression it is being joined to.

1.1.4.1186 There was insufficient memory to complete the %1 operation

Error constant	SQLE_SFC_MEM_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure that detected the error.
Severity	17
SQLCODE	-1685
SQLSTATE	08S01
Sybase error code	12439

Probable cause

A call to the specified procedure could not complete the operation due to insufficient memory.

1.1.4.1187 This connection already exists

Error constant	SQLE_CONNECTION_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-955
SQLSTATE	WW035
Sybase error code	13533

Probable cause

A connection with the given SQLCA and name (or no name) already exists. Before connecting you must disconnect the existing connection, or specify a different connection name.

Related Information

[CONNECT Statement \[ESQL\]](#) [[Interactive SQL](#)]

1.1.4.1188 This database does not support encrypted tables

Error constant	SQLE_ENCRYPTED_TABLES_NOT_SUPPORTED
ODBC 2 state	42000
ODBC 3 state	42000
Severity	16
SQLCODE	-1047
SQLSTATE	55W20
Sybase error code	13464

Probable cause

You tried to create an encrypted table in a database that does not support them.

1.1.4.1189 This edition of SQL Anywhere is not available on this platform

Error constant	SQLE_PLATFORM_NOT_LICENSED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1262
SQLSTATE	0A004
Sybase error code	13251

Probable cause

This edition of SQL Anywhere is not available on this platform. You must use a different license key to use SQL Anywhere on this platform.

1.1.4.1190 This operation is only allowed within a synchronization schema change

Error constant	SQLE_REQUIRES_SYNC_SCHEMA_CHANGE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1329
SQLSTATE	5RW41
Sybase error code	13227

Probable cause

You attempted an operation that is only allowed within a synchronization schema change.

1.1.4.1191 This server is not licensed to support '%1' connections

Error constant	SQLE_CONNECTION_PROTOCOL_NOT_LICENSED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unlicensed connection type.
Severity	16
SQLCODE	-1261
SQLSTATE	0A003
Sybase error code	13252

Probable cause

You attempted to use a connection protocol or API that is not licensed in this edition of SQL Anywhere.

1.1.4.1192 This server is not licensed to support the '%1' feature

Error constant	SQLE_FEATURE_NOT_LICENSED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unlicensed feature.
Severity	16
SQLCODE	-1260
SQLSTATE	0A002
Sybase error code	13253

Probable cause

You attempted to carry out an operation or use a feature that is not licensed in this edition of SQL Anywhere.

1.1.4.1193 Time zone '%1' not found

Error constant	SQLTIMEZONE_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the time zone that could not be found
Severity	16
SQLCODE	-1788
SQLSTATE	55W48
Sybase error code	12355

Probable cause

You misspelled the name of a time zone stored in the database, or the time zone does not exist.

1.1.4.1194 Time zone option error: %1

Error constant	SQLTIMEZONE_OPTION_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Text of the option error
Severity	16
SQLCODE	-1790
SQLSTATE	55W50
Sybase error code	12353

Probable cause

An option error was found when creating or altering a time zone.

1.1.4.1195 TLS handshake failure

Error constant	SQLE_TLS_HANDSHAKE_FAILED
ODBC 2 state	08S01
ODBC 3 state	08S01
Severity	21
SQLCODE	-829
SQLSTATE	08W59
Sybase error code	13835

Probable cause

The connection failed because of a failure in the TLS handshaking process.

1.1.4.1196 TLS initialization on server failed

Error constant	SQLE_TLS_INIT_FAILED_ON_SRV
ODBC 2 state	08S01
ODBC 3 state	08S01
Severity	21
SQLCODE	-838
SQLSTATE	08W61
Sybase error code	13844

Probable cause

The connection failed because the initialization of the TLS library on the server failed.

1.1.4.1197 TLS ON cannot be used with URL %1

Error constant	SQLE_LDAPUA_TLS_WITH_LDAPS
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The LDAP URL that is using Secure LDAP.
Severity	16
SQLCODE	-1627
SQLSTATE	WW240
Sybase error code	12479

Probable cause

The LDAP server is specified with TLS ON and the specified LDAP URL uses Secure LDAP, that is, 'ldaps' instead of 'ldap', which is not a valid combination. Use either TLS ON or an 'ldaps' URL.

1.1.4.1198 Too few columns

Error constant	SQL_E_FOR_XML_EXPLICIT_TOO_FEW_COLUMNS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-902
SQLSTATE	WX010
Sybase error code	13581

Probable cause

FOR XML EXPLICIT and FOR JSON EXPLICIT require at least three columns: the tag column, the parent column, and one or more data columns.

Related Information

[FOR XML EXPLICIT](#)

1.1.4.1199 Too many active trace event sessions

Error constant	SQL_E_TOO_MANY_ACTIVE_TRACE_SESSIONS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1640
SQLSTATE	WE025
Sybase error code	12467

Probable cause

Too many active trace sessions.

1.1.4.1200 Too many arguments for function or procedure '%1'

Error constant	SQL_E_TOO_MANY_ARGUMENTS
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	The name of the function or procedure.
Severity	16
SQLCODE	-994
SQLSTATE	42WAC
Sybase error code	401

Probable cause

You supplied an argument list that the database server cannot handle. This can happen if the argument list of the function or stored procedure is too long. Rebuilding the database with a larger page size could prevent this error.

1.1.4.1201 Too many arguments for trace event '%1'

Error constant	SQLLE_TOO_MANY_PARAMETERS_FOR_TRACE_EVENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event name.
Severity	11
SQLCODE	-1638
SQLSTATE	WE024
Sybase error code	12471

Probable cause

Too many arguments were provided for the trace event specified.

1.1.4.1202 Too many columns

Error constant	SQLLE_FOR_XML_EXPLICIT_TOO_MANY_COLUMNS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-909
SQLSTATE	WX025
Sybase error code	13582

Probable cause

You executed a FOR XML EXPLICIT or FOR JSON EXPLICIT statement with too many expressions in the SELECT list. Rebuilding the database with a larger page size could prevent this error.

1.1.4.1203 Too many columns in procedure result set

Error constant	SQLLE_TOO_MANY_COLUMNS_IN_PROC_RES
----------------	------------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1237
SQLSTATE	54W15
Sybase error code	13281

Probable cause

You executed a CREATE PROCEDURE or ALTER PROCEDURE statement. The resulting number of columns in the result set of the procedure would exceed the server's limit of 45000.

1.1.4.1204 Too many columns in row type

Error constant	SQL_E_TOO_MANY_COLUMNS_IN_ROWTYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1896
SQLSTATE	54W22
Sybase error code	12258

Probable cause

You attempted to create a row type with too many columns. The number of columns in a row type is limited to 45000.

1.1.4.1205 Too many columns in schema

Error constant	SQL_E_TOO_MANY_COLUMNS_IN_OPENSTRING_SCHEMA
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1895
SQLSTATE	54W21
Sybase error code	12257

Probable cause

You executed an OPENSTRING, OPENXML, or LOAD TABLE FORMAT XML statement with too many columns in the schema. The number of columns is limited to 4000.

1.1.4.1206 Too many columns in SELECT list

Error constant	SQLE_TOO_MANY_COLUMNS_IN_SELECT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1235
SQLSTATE	54W13
Sybase error code	13283

Probable cause

You executed a statement with too many expressions in the SELECT list. The number of expressions within a SELECT list is limited to 100000.

1.1.4.1207 Too many columns in table

Error constant	SQLE_TOO_MANY_COLUMNS_IN_TABLE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-616
SQLSTATE	52W20
Sybase error code	1702

Probable cause

You executed a CREATE TABLE or ALTER TABLE statement that attempted to add a column to a table. The resulting number of columns in the table would exceed the limit for the current database page size.

1.1.4.1208 Too many constraints in database

Error constant	SQL_E_TOO_MANY_CONSTRAINTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-936
SQLSTATE	54W02
Sybase error code	13551

Probable cause

An attempt to create a new constraint failed because the corresponding system table is full. Reloading the database will reclaim any unused space. No more than 4294967295 constraints may be used in a database.

1.1.4.1209 Too many distinct group mappings for integrated user

Error constant	SQL_E_INTEGRATED_LOGON_TOO_MANY_MAPPINGS
ODBC 2 state	28000
ODBC 3 state	28000
Severity	16
SQLCODE	-1003
SQLSTATE	28W10
Sybase error code	13490

Probable cause

The integrated user does not have an explicit mapping in the database but does have group mappings. There are too many distinct group mappings. You must either reduce the number of distinct group mappings or add an explicit mapping for the user.

1.1.4.1210 Too many expressions in GROUP BY list

Error constant	SQLE_TOO_MANY_COLUMNS_IN_GROUPBY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1236
SQLSTATE	54W14
Sybase error code	13282

Probable cause

You executed a statement with too many expressions in the GROUP BY list. The number of expressions within a GROUP BY list is limited to 100000.

1.1.4.1211 Too many expressions in GROUP BY list for ROLLUP, CUBE, or GROUPING SETS operation

Error constant	SQLE_TOO_MANY_GROUPING_EXPRESSIONS
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-944
SQLSTATE	42WA1
Sybase error code	13544

Probable cause

You specified too many expressions in the GROUP BY list for the requested ROLLUP, CUBE, or GROUPING SETS operation. The current environment where SQL Anywhere is executing cannot support this number of expressions in the GROUP BY list for the requested operation.

1.1.4.1212 Too many MESSAGE...FOR CONNECTION messages

Error constant	SQLC_CONNECTION_MESSAGE_QUEUE_FULL
ODBC 2 state	37000
ODBC 3 state	54000
Severity	19
SQLCODE	-1303
SQLSTATE	54W16
Sybase error code	13457

Probable cause

You executed a MESSAGE...FOR CONNECTION statement and the maximum number of messages for the connection have already been queued. The maximum number of queued messages is 10.

1.1.4.1213 Too many mutexes and semaphores created

Error constant	SQLC_TOO_MANY_MUTEXES_SEM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1850
SQLSTATE	WW168
Sybase error code	12295

Probable cause

A CREATE MUTEX or CREATE SEMAPHORE statement attempted to create a mutex or semaphore, but the resulting number of distinct mutex and semaphore IDs used for permanent objects would exceed the limit.

1.1.4.1214 Too many open cursors

Error constant	SQLLE_TOO_MANY_CURSORS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	17
SQLCODE	-1230
SQLSTATE	54W12
Sybase error code	13287

Probable cause

You exceeded the number of cursors that can be open on a single UltraLite database. Check to ensure you are freeing statements when you are done with them.

Related Information

[UltraLite C++ Application Development Using Embedded SQL
Multiple Row Fetching](#)

1.1.4.1215 Too many parameters to this external procedure call

Error constant	SQLLE_TOO_MANY_PARAMETERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	19
SQLCODE	-625
SQLSTATE	WW010
Sybase error code	13680

Probable cause

There is a maximum of 256 parameters to an external function call in 32-bit Windows.

1.1.4.1216 Too many publications specified for operation

Error constant	SQL_E_TOO_MANY_PUBLICATIONS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1106
SQLSTATE	WW077
Sybase error code	13408

Probable cause

You have specified too many publications for the required operation. For example, when retrieving the last download timestamp, you are only allowed to select one publication.

1.1.4.1217 Too many recursive iterations

Error constant	SQL_E_TOO_MANY_RECURSIVE_ITERATIONS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-923
SQLSTATE	57015
Sybase error code	13561

Probable cause

A recursive query ran for more iterations than allowed by the current `max_recursive_iterations` option setting.

1.1.4.1218 Too many references to a BLOB

Error constant	SQL_E_TOO_MANY_BLOB_REFS
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Severity	16
SQLCODE	-1107
SQLSTATE	54W11
Sybase error code	13407

Probable cause

You have exceeded the maximum number of references to a particular BLOB. In UltraLite you may have at most 256 references to any one particular BLOB.

1.1.4.1219 Too many tables in query

Error constant	SQL_E_TOO_MANY_TABLES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1894
SQLSTATE	54W20
Sybase error code	12256

Probable cause

You executed a statement that references too many tables. Rebuilding the database with a larger page size could prevent this error.

1.1.4.1220 Too many temporary mutexes and semaphores created

Error constant	SQL_E_TOO_MANY_TEMP_MUTEXES_SEM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1849
SQLSTATE	WW167
Sybase error code	12296

Probable cause

A CREATE TEMPORARY MUTEX or CREATE TEMPORARY SEMAPHORE statement attempted to create a temporary mutex or semaphore, but the resulting number of distinct mutex and semaphore IDs used for temporary objects would exceed the limit.

1.1.4.1221 Too many temporary tables in connection

Error constant	SQLE_TOO_MANY_TEMP_TABLES
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-817
SQLSTATE	52W41
Sybase error code	13823

Probable cause

A CREATE TABLE or DECLARE LOCAL TEMPORARY TABLE statement attempted to create a temporary table, but the resulting number of distinct table IDs used for temporary tables in the current connection would exceed the limit.

Related Information

[CREATE TABLE Statement](#)
[DECLARE LOCAL TEMPORARY TABLE Statement](#)
[CREATE TABLE Statement \[UltraLite\]](#)

1.1.4.1222 Too many users in database

Error constant	SQL_E_TOO_MANY_USERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1104
SQLSTATE	54W10
Sybase error code	13410

Probable cause

You have exceeded the maximum number of users permitted to access the database. The maximum number of users that are allowed granted access to a single UltraLite database is four.

1.1.4.1223 Trace event '%1' already exists

Error constant	SQL_E_TRACE_EVENT_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event name.
Severity	11
SQLCODE	-1635
SQLSTATE	WE021
Sybase error code	12470

Probable cause

The specified trace event name already exists.

1.1.4.1224 Trace event '%1' is not valid

Error constant	SQL_E_INVALID_TRACE_EVENT_NAME
----------------	--------------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event name.
Severity	11
SQLCODE	-1633
SQLSTATE	WE019
Sybase error code	12473

Probable cause

The specified trace event name is not valid.

1.1.4.1225 Trace event '%1' is referenced by one or more sessions. Drop referencing sessions first

Error constant	SQL_E_TRACE_EVENT_IS_IN_USE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event name.
Severity	11
SQLCODE	-1636
SQLSTATE	WE022
Sybase error code	12476

Probable cause

The specified trace event name is used and cannot be dropped before dropping referencing sessions.

1.1.4.1226 Trace event session '%1' already active

Error constant	SQL_E_TRACE_SESSION_ALREADY_ACTIVE
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Severity	11
SQLCODE	-1641
SQLSTATE	WE026
Sybase error code	12468

Probable cause

The specified trace event session is already active.

1.1.4.1227 Trace event session '%1' already exists

Error constant	SQL_E_TRACE_SESSION_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Severity	11
SQLCODE	-1652
SQLSTATE	WE037
Sybase error code	12479

Probable cause

A trace event session with that name already exists.

1.1.4.1228 Trace event session '%1' already has target type '%2'

Error constant	SQL_E_TRACE_SESSION_ALREADY_HAS_TARGET_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Parameter 1	The trace event session name.
Parameter 2	The trace event target type.
Severity	11
SQLCODE	-1649
SQLSTATE	WE034
Sybase error code	12476

Probable cause

The specified trace event session already has the specified target type.

1.1.4.1229 Trace event session '%1' already has trace event '%2'

Error constant	SQLLE_TRACE_SESSION_ALREADY_HAS_EVENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Parameter 2	The trace event name.
Severity	11
SQLCODE	-1645
SQLSTATE	WE030
Sybase error code	12472

Probable cause

The specified trace event session already has the specified event.

1.1.4.1230 Trace event session '%1' does not have target type '%2'

Error constant	SQLLE_TRACE_SESSION_DOES_NOT_HAVE_TARGET_TYPE
----------------	---

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Parameter 2	The trace event target type.
Severity	11
SQLCODE	-1651
SQLSTATE	WE036
Sybase error code	12478

Probable cause

The trace event session does not have the specified trace target type.

1.1.4.1231 Trace event session '%1' does not have trace event '%2'

Error constant	SQL_E_TRACE_SESSION_DOES_NOT_HAVE_TRACE_EVENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Parameter 2	The trace event name.
Severity	11
SQLCODE	-1650
SQLSTATE	WE035
Sybase error code	12477

Probable cause

The trace event session does not have the specified trace event.

1.1.4.1232 Trace event session '%1' failed to start

Error constant	SQL_TRACE_SESSION_FAILED_TO_START
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Severity	11
SQLCODE	-1643
SQLSTATE	WE028
Sybase error code	12470

Probable cause

The specified trace event session failed to start.

1.1.4.1233 Trace event session '%1' is active. Stop active session before dropping the session

Error constant	SQL_TRACE_EVENT_SESSION_IS_ACTIVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Severity	11
SQLCODE	-1637
SQLSTATE	WE023
Sybase error code	12472

Probable cause

The specified trace event session is active. The session must be not be active in order to be dropped.

1.1.4.1234 Trace event session '%1' is already stopped

Error constant	SQLE_TRACE_SESSION_ALREADY_STOPPED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace event session name.
Severity	11
SQLCODE	-1644
SQLSTATE	WE029
Sybase error code	12471

Probable cause

The specified trace event session is already stopped.

1.1.4.1235 Trace target option '%1' conflicts with option '%2'

Error constant	SQLE_TARGET_OPTIONS_CONFLICT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The trace target option name.
Parameter 2	The trace target option name.
Severity	11
SQLCODE	-1684
SQLSTATE	WE038
Sybase error code	12440

Probable cause

A trace target option conflict with another target option.

Related Information

[Event Tracing](#)

1.1.4.1236 Traced query (%1, %2) does not exist

Error constant	SQLE_INVALID_TRACED_PLAN
ODBC 2 state	28000
ODBC 3 state	28000
Parameter 1	The specified logging session ID.
Parameter 2	The specified query ID.
Severity	16
SQLCODE	-1154
SQLSTATE	55W28
Sybase error code	13359

Probable cause

You attempted to generate a graphical plan for a query saved by diagnostic tracing, identified by a logging_session_id and query ID. However, no such query exists in this database. If it was traced, it was sent to a different database.

1.1.4.1237 Transact-SQL expression in a non-Transact-SQL statement near '%1' %2

Error constant	SQLE_DIALECT_MIX_TSQL_IN_WATCOM
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	The word or symbol where the incompatible syntax has been detected.
Parameter 2	Location of the incompatible expression.
Severity	15
SQLCODE	-1753
SQLSTATE	42WD6
Sybase error code	12389

Probable cause

You executed a statement written in the Watcom SQL dialect with an expression written in the Transact-SQL dialect.

1.1.4.1238 Transact-SQL feature not supported

Error constant	SQLE_TSQL_FEATURE_NOT_SUPPORTED
ODBC 2 state	37000
ODBC 3 state	42000
Severity	15
SQLCODE	-611
SQLSTATE	0AW02
Sybase error code	176

Probable cause

You attempted to use a Transact-SQL feature that is not supported in SQL Anywhere.

1.1.4.1239 Transact-SQL outer joins are currently disabled

Error constant	SQLE_TSQL_OUTER_JOINS_DISABLED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1099
SQLSTATE	55W25
Sybase error code	13416

Probable cause

The ability to specify a Transact-SQL outer join in a query is currently disabled by the setting of the `tsql_outer_joins` connection option. Transact-SQL outer joins are deprecated in this release of SQL Anywhere.

1.1.4.1240 Transaction log backup page only partially full

Error constant	SQLE_BACKUP_PAGE_INCOMPLETE
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	110
SQLSTATE	01W10
Sybase error code	13683

Probable cause

A DB_LOG_BACKUP_READ_WAIT was issued against the transaction log and the page returned was not full. The application should reissue the request for the same page.

1.1.4.1241 Transaction log mirroring cannot be used with database mirroring

Error constant	SQLE_MIRROR_LOG_WITH_DB_MIRROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1178
SQLSTATE	WW095
Sybase error code	13336

Probable cause

Transaction log mirroring cannot be used with database mirroring. Use the dblog utility to disable transaction log mirroring.

1.1.4.1242 Transaction log was truncated

Error constant	SQLLE_LOG_TRUNCATED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-244
SQLSTATE	WB005
Sybase error code	13661

Probable cause

While an operation was occurring on the transaction log, the transaction log was truncated by another operation.

1.1.4.1243 Transform definition is too long

Error constant	SQLLE_SLERR_TRANSFORM_DEF_TOO_LONG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1443
SQLSTATE	2FW36
Sybase error code	13129

Probable cause

The provided transform definition is too long.

1.1.4.1244 Transform from SRID %1 not supported

Error constant	SQLLE_SLERR_NO_SRC_XFORM_DEF
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Parameter 1	The SRID of the value.
Severity	16
SQLCODE	-1445
SQLSTATE	2FW38
Sybase error code	13127

Probable cause

There is no way to transform from values of the specified spatial reference system.

Related Information

[ST_SRID Method](#)
[ALTER SPATIAL REFERENCE SYSTEM Statement](#)
[Spatial Data Types](#)

1.1.4.1245 Transform from SRID %1 to %2 not supported

Error constant	SQLE_SLERR_NO_XFORM_DEF
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The SRID of the value.
Parameter 2	The SRID of the destination.
Severity	16
SQLCODE	-1444
SQLSTATE	2FW37
Sybase error code	13128

Probable cause

There is no way to transform from the value's spatial reference system to the specified target. This error can occur when you attempt to call ST_Transform between two spatial reference systems and one or both do not have a TRANSFORM DEFINITION in the SRS definition (specified using a PROJ.4 projection description using

the TRANSFORMATION DEFINITION clause of the ALTER SPATIAL REFERENCE SYSTEM statement). You can also get this error while performing a CAST from one SRID to another. Add TRANSFORMATION DEFINITION to the SRSs involved. Alternatively, if both SRIDs use the same coordinate system, then you can use the ST_SRID method to change a value's SRID without changing the values.

1.1.4.1246 TREAT AS can only be used with extended types. Cannot treat %1 as a %2

Error constant	SQL_E_TREAT_AS_ONLY_EXTENDED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value that could not be converted.
Parameter 2	The name of the type for the conversion.
Severity	16
SQLCODE	-1361
SQLSTATE	53020
Sybase error code	13201

Probable cause

An error occurred while trying to treat a value as another data type.

1.1.4.1247 Trigger '%1' not found

Error constant	SQL_E_TRIGGER_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of the trigger that could not be found.
Severity	11
SQLCODE	-268
SQLSTATE	52W10
Sybase error code	9819

Probable cause

You misspelled the name of a trigger, or you did not qualify a trigger name with a user name.

1.1.4.1248 Trigger definition conflicts with existing triggers

Error constant	SQLE_TRIGGER_DEFN_CONFLICT
ODBC 2 state	S0002
ODBC 3 state	42S01
Severity	15
SQLCODE	-271
SQLSTATE	52W11
Sybase error code	102

Probable cause

You attempted to create a trigger, but a trigger with the same name or type already exists. To allow multiple triggers with the same event and time to be created, use the ORDER clause to specify firing order.

1.1.4.1249 Trigger name '%1' is ambiguous

Error constant	SQLE_AMBIGUOUS_TRIGGER_NAME
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the ambiguous trigger.
Severity	16
SQLCODE	-855
SQLSTATE	42W66
Sybase error code	13858

Probable cause

A statement has referred to a trigger name that is not unique. Qualify the trigger name with the table and/or owner name.

1.1.4.1250 Trigger or foreign key for table '%1' is no longer valid

Error constant	SQL_E_TRIGGER_NO_LONGER_VALID
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the table.
Severity	15
SQLCODE	-837
SQLSTATE	42W64
Sybase error code	13843

Probable cause

A trigger definition cannot be loaded from the catalog. Check for tables or columns that have been renamed or that may be reserved words. The trigger may be a system-generated trigger to enforce the referential actions of a foreign key.

1.1.4.1251 Triggers cannot be created on materialized view '%1'

Error constant	SQL_E_INVALID_TRIGGER_MATVIEW
ODBC 2 state	42000
ODBC 3 state	ERROR
Parameter 1	Name of the materialized view
Severity	14
SQLCODE	-1134
SQLSTATE	42W3D
Sybase error code	13379

Probable cause

You attempted to create a trigger on a materialized view. A materialized view is not a valid target for a trigger.

1.1.4.1252 TRUNCATE TABLE not allowed: initialized immediate materialized view %1 depends on %2

Error constant	SQLE_TRUNCATE_TABLE_WITH_IMV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the dependent initialized immediate materialized view.
Parameter 2	Name of the table on which TRUNCATE TABLE was performed.
Severity	16
SQLCODE	-1193
SQLSTATE	55W30
Sybase error code	13322

Probable cause

TRUNCATE TABLE is not permitted on any table that has dependent initialized immediate materialized views.

1.1.4.1253 TRUNCATE TABLE statement cannot be used on a view

Error constant	SQLE_CANNOT_TRUNCATE_VIEW
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-702
SQLSTATE	42W49
Sybase error code	4708

Probable cause

You attempted to use TRUNCATE TABLE on a view, which is not permitted.

1.1.4.1254 Two rows with the same primary key have been downloaded for table '%1'

Error constant	SQLE_DUPLICATE_ROW_FOUND_IN_DOWNLOAD
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	Name of the table being downloaded.
Severity	10
SQLCODE	145
SQLSTATE	01W27
Sybase error code	13254

Probable cause

The synchronization scripts are producing duplicate rows with the same primary key in your download. Generally this behavior indicates a problem with the synchronization scripts. No guarantees are made about which of the downloaded rows will be applied to the database.

Related Information

[Synchronization Scripts](#)

1.1.4.1255 Type '%1' cannot be instantiated with %2 arguments (near '%3')

Error constant	SQLE_METHOD_NO_CONSTRUCTOR_N_ARGS
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The name of the type that cannot be instantiated.
Parameter 2	The number of arguments supplied.
Parameter 3	The invalid expression.
Severity	11
SQLCODE	-1340
SQLSTATE	42X05

Probable cause

A NEW expression was used for a data type that does not define any constructor methods.

1.1.4.1256 Type '%1' does not support method calls (near '%2')

Error constant	SQLE_METHOD_ON_NON_EXT
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The name of the data type.
Parameter 2	The invalid expression.
Severity	11
SQLCODE	-1335
SQLSTATE	42X00
Sybase error code	13221

Probable cause

You attempted to invoke a method on a value of a data type that does not define any methods.

1.1.4.1257 Type '%1' has no method named '%2' (near '%3')

Error constant	SQLE_METHOD_NOT_FOUND
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The name of the type with the unmatched method.
Parameter 2	Name of the method that could not be matched.
Parameter 3	The invalid expression.
Severity	11

SQLCODE	-1336
SQLSTATE	42X01
Sybase error code	13220

Probable cause

When attempting to match a method invocation, no method was found with the appropriate name. Check for spelling errors.

1.1.4.1258 Type '%1' is not instantiable (near '%2')

Error constant	SQLE_METHOD_NO_CONSTRUCTOR
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	The name of the type that is not instantiable.
Parameter 2	The invalid expression.
Severity	11
SQLCODE	-1338
SQLSTATE	42X03
Sybase error code	13218

Probable cause

A NEW expression was used for a data type that does not define any constructor methods.

1.1.4.1259 UltraLite cannot synchronize because a synchronization is already running

Error constant	SQLE_SYNC_NOT_REENTRANT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16

SQLCODE	-1110
SQLSTATE	WW080
Sybase error code	13404

Probable cause

You attempted to synchronize an UltraLite database which is already synchronizing. You must wait until the current synchronization completes before starting another. UltraLite allows most operations to run concurrently with synchronization, but only a single synchronization can be active at a time. This is generally caused by two different threads attempting a synchronize call or statement at the same time.

1.1.4.1260 UltraLite connection was restored

Error constant	SQLE_CONNECTION_RESTORED
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	133
SQLSTATE	WW040
Sybase error code	13519

Probable cause

The connection attempt completed successfully and the transaction was restored from a suspended state.

1.1.4.1261 UltraLite cursor (or result set or table) was restored

Error constant	SQLE_CURSOR_RESTORED
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	134

SQLSTATE	WW041
Sybase error code	13518

Probable cause

The cursor (or result set or table) was opened successfully and the cursor position was restored from the suspended state.

1.1.4.1262 UltraLite database state was restored

Error constant	SQL_E_DATABASE_STATE_RESTORED
ODBC 2 state	OK
ODBC 3 state	OK
Severity	10
SQLCODE	142
SQLSTATE	WW114
Sybase error code	13276

Probable cause

The database state was restored from the temporary file. This includes suspended connections, transactions, and cursors.

Related Information

[Manage Temporary Tables](#)

1.1.4.1263 UltraLite performed database recovery on startup

Error constant	SQL_E_DATABASE_RECOVERED
ODBC 2 state	OK
ODBC 3 state	OK

Severity	10
SQLCODE	151
SQLSTATE	WW247
Sybase error code	12423

Probable cause

The database file was not shut down cleanly. Any uncommitted rows have been rolled back. This indicates that not all connections were closed when the application terminated.

1.1.4.1264 Unable to access the file system on the device

Error constant	SQLE_CANNOT_ACCESS_FILESYSTEM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1108
SQLSTATE	WW078
Sybase error code	13406

Probable cause

On a Palm device, you have tried to utilize the VFS file system, but that feature has not been enabled on the device.

1.1.4.1265 Unable to acquire table locks in specified time

Error constant	SQLE_LOCK_TIMEOUT
ODBC 2 state	40001
ODBC 3 state	40001
Severity	21
SQLCODE	-1175
SQLSTATE	42WC4

Probable cause

The LOCK TABLE statement could not acquire all the locks in specified time period.

1.1.4.1266 Unable to clean directory %1

Error constant	UNABLE_TO_CLEAN_DIRECTORY
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The file name of the directory that could not be cleaned
Severity	16
SQLCODE	-1968
SQLSTATE	08WBA
Sybase error code	12214

Probable cause

You attempted to perform an operation using a file or directory name that does not exist or fail to access.

1.1.4.1267 Unable to close the cursor on table "%1". LOAD TABLE cannot be executed

Error constant	SQLC_CANNOT_LOAD_TEMP_WITH_CURSOR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the table.
Severity	16
SQLCODE	-1155
SQLSTATE	WL011
Sybase error code	13358

Probable cause

You cannot perform LOAD TABLE on a temporary table that has an open cursor on it. An attempt to close the cursor failed. A failed LOAD TABLE would cause all of the rows in the temporary table to be deleted thereby invalidating the cursor.

1.1.4.1268 Unable to connect to server '%1': %2

Error constant	SQLE_OMNI_CONNECT_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the server that could not be connected to.
Parameter 2	A more specific reason returned from the server class driver.
Severity	16
SQLCODE	-656
SQLSTATE	W0001
Sybase error code	11206

Probable cause

You attempted to connect to a remote server. Check that the remote server is running.

1.1.4.1269 Unable to connect to the remote host specified by '%1'

Error constant	SQLE_UNABLE_TO_CONNECT_TO_HOST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The URI referencing the remote host.
Severity	19
SQLCODE	-981
SQLSTATE	WW050
Sybase error code	13508

Probable cause

A connection could not be initiated to the remote server.

1.1.4.1270 Unable to connect, server definition is circular

Error constant	SQLE_OMNI_CIRCULAR_CONNECT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-657
SQLSTATE	W0002
Sybase error code	13593

Probable cause

You attempted to connect to a remote server that maps to the local database.

1.1.4.1271 Unable to connect: The server did not accept the requested encryption type

Error constant	SQLE_ENCRYPTION_TYPE_NOT_ACCEPTED
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-1145
SQLSTATE	08W97
Sybase error code	13367

Probable cause

The server only accepts certain encryption types, and the connection's encryption type is not one of the accepted types. The -ec server option is used to configure the encryption types that the server accepts.

1.1.4.1272 Unable to copy file %1

Error constant	SQL_E_UNABLE_TO_COPY_FILE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The file name of the file to be copied
Severity	16
SQLCODE	-1611
SQLSTATE	08WB7
Sybase error code	12495

Probable cause

The request to copy a file failed.

1.1.4.1273 Unable to copy file %1 to destination %2

Error constant	SQL_E_UNABLE_TO_COPY_DB_FILE_INTO_CLOUD
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The file name of the file on the client computer
Parameter 2	The file name of the destination within the cloud
Severity	16
SQLCODE	-1593
SQLSTATE	08WB2
Sybase error code	12512

Probable cause

The client database file could not be copied to the requested cloud destination.

1.1.4.1274 Unable to create directory %1

Error constant	SQLE_UNABLE_TO_CREATE_DIRECTORY
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The file name of the directory that could not be created
Severity	16
SQLCODE	-1610
SQLSTATE	08WB6
Sybase error code	12496

Probable cause

The request to create a directory failed.

1.1.4.1275 Unable to declare a row variable from the cursor using %ROWTYPE; invalid name for field %1

Error constant	SQLE_INVALID_FIELD_NAME_IN_DECLARE_ROW_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Number of the field for which there is no name.
Severity	16
SQLCODE	-1733
SQLSTATE	WP024
Sybase error code	12404

Probable cause

The field name used to declare a row type using cursor %ROWTYPE is not defined or is invalid. Use a SELECT list alias in the query specification or specify the result set in the procedure definition.

1.1.4.1276 Unable to declare a row variable from the cursor using %ROWTYPE; no fields were found in the cursor

Error constant	SQLE_NO_FIELD_IN_DECLARE_ROW_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1734
SQLSTATE	WP025
Sybase error code	12403

Probable cause

No fields were found when attempting to declare the row type using cursor %ROWTYPE.

1.1.4.1277 Unable to delete database file

Error constant	SQLE_BACKUP_UNABLE_TO_DELETE_FILE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-243
SQLSTATE	WB004
Sybase error code	13660

Probable cause

You attempted to delete a database file, but it could not be deleted. The file name should not be the same as any database file that is currently in use.

1.1.4.1278 Unable to delete file %1

Error constant	SQLE_UNABLE_TO_DELETE_FILE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The file name of the file to be deleted
Severity	16
SQLCODE	-1608
SQLSTATE	08WB4
Sybase error code	12498

Probable cause

The request to delete a file failed.

1.1.4.1279 Unable to enlist transaction; DTC may be down

Error constant	SQLE_FAILED_TO_ENLIST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	17
SQLCODE	-803
SQLSTATE	WL005
Sybase error code	13813

Probable cause

You tried to enlist a transaction but DTC does not seem to be available at this time.

1.1.4.1280 Unable to find in index '%1' for table '%2'

Error constant	SQLE_NOT_FOUND_IN_INDEX
----------------	-------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of invalid index.
Parameter 2	Name of table containing the invalid index.
Severity	11
SQLCODE	-189
SQLSTATE	WI005
Sybase error code	2727

Probable cause

This is an internal error. If it can be reproduced, it should be reported to SAP. You should be able to work around the error by dropping and recreating the index.

1.1.4.1281 Unable to find the cockpit parameters used to start or stop

Error constant	SQLC_COCKPITDB_UNABLE_TO_FIND_PARAMETERS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1875
SQLSTATE	O8WF2
Sybase error code	12285

Probable cause

Unable to find the cockpit parameters that were used to start or stop the SQL Anywhere Cockpit. While starting, stopping, or upgrading the SQL Anywhere Cockpit, either the database server failed to manage the parameters properly or the memory that is used to store the cockpit parameters may be corrupted. This is a fatal internal error.

1.1.4.1282 Unable to finish upgrade the SQL Anywhere Cockpit when it is not active

Error constant	SQLE_COCKPITDB_CANNOT_FINISH_UPGRADE_WHEN_DB_NOT_ACTIVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1873
SQLSTATE	08WH8
Sybase error code	12305

Probable cause

You are attempting to finish upgrading the SQL Anywhere Cockpit while it is not active.

1.1.4.1283 Unable to load the dbrsakp shared object

Error constant	SQLE_RSA_LOAD_FAILED
ODBC 2 state	08001
ODBC 3 state	08001
Severity	16
SQLCODE	-1584
SQLSTATE	08WA9
Sybase error code	12521

Probable cause

The server was unable to load the dbrsakp DLL on Microsoft Windows platforms or the libdbrsakp shared object on UNIX/Linux platforms.

1.1.4.1284 Unable to open backup log '%1'

Error constant	SQL_E_UNABLE_TO_OPEN_BACKUP_LOG
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	Backup log file name.
Severity	10
SQLCODE	119
SQLSTATE	WB011
Sybase error code	13776

Probable cause

The server was unable to open the backup log to record the execution of a BACKUP or RESTORE statement. Check the settings of the environment variables used to locate the backup log file. The directory to contain the log must already exist.

Related Information

[SALOGDIR Environment Variable](#)
[BACKUP DATABASE Statement](#)

1.1.4.1285 Unable to open the SQL Anywhere Cockpit template -- '%1'

Error constant	SQL_E_CANNOT_OPEN_SQLACOCKPITDB_TEMPLATE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Reason the SQL Anywhere Cockpit template could not be opened, if known.
Severity	16
SQLCODE	-1858
SQLSTATE	08WGO
Sybase error code	12289

Probable cause

The database server was unable to open the SQL Anywhere Cockpit template file. This could happen when the SQL Anywhere Cockpit template is not installed properly.

1.1.4.1286 Unable to perform requested operation since this database uses keyless encryption

Error constant	SQL_E_KEYLESS_ENCRYPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1109
SQLSTATE	WW079
Sybase error code	13405

Probable cause

The operation you requested on the encryption key failed since the UltraLite database uses keyless encryption. This can occur when you try to change the encryption key for a database that uses keyless encryption (obfuscation for example).

1.1.4.1287 Unable to prepare to save the SQL Anywhere Cockpit when it is not active.

Error constant	COCKPIT_CANNOT_PREPARE_SAVE_WHEN_DB_NOT_ACTIVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1954
SQLSTATE	08WH9
Sybase error code	12225

Probable cause

You are attempting to prepare to save the SQL Anywhere Cockpit while it is not active.

1.1.4.1288 Unable to prepare to save the SQL Anywhere Cockpit when it is already being prepared.

Error constant	COCKPIT_CANNOT_PREPARE_SAVE_WHEN_PREPARE_SAVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1959
SQLSTATE	08WJ3
Sybase error code	12223

Probable cause

You are attempting to save and restart the SQL Anywhere Cockpit while it is already being prepared.

1.1.4.1289 Unable to re-enlist transaction; DTC may be down

Error constant	SQLE_FAILED_TO_REENLIST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	17
SQLCODE	-804
SQLSTATE	WL006
Sybase error code	13814

Probable cause

You tried to recover a transaction but DTC does not seem to be available at this time.

1.1.4.1290 Unable to retry download because upload is not finished

Error constant	SQLE_DOWNLOAD_RESTART_FAILED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1102
SQLSTATE	WW074
Sybase error code	13412

Probable cause

The MobiLink server could not restart the download because the MobiLink server has not received the entire upload stream.

Related Information

[Authentication Process](#)
[Resumption of Failed Downloads](#)

1.1.4.1291 Unable to save and restart the SQL Anywhere Cockpit when it is not prepared.

Error constant	COCKPIT_CANNOT_SAVE_RESTART_WHEN_NOT_SAVE_PREPARED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1960
SQLSTATE	08WJ4
Sybase error code	12221

Probable cause

You are attempting to save and restart the SQL Anywhere Cockpit while it is not prepared.

1.1.4.1292 Unable to start database "%1": CHAR collation or tailoring not supported on this platform

Error constant	SQLE_CHAR_COLLATION_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The database name.
Severity	16
SQLCODE	-1140
SQLSTATE	WC015
Sybase error code	13373

Probable cause

The specified CHAR collation is not supported on the current platform.

1.1.4.1293 Unable to start database "%1": NCHAR collation or tailoring not supported on this platform

Error constant	SQLE_NCHAR_COLLATION_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The database name.
Severity	16
SQLCODE	-1141
SQLSTATE	WC016
Sybase error code	13372

Probable cause

The specified NCHAR collation is not supported on the current platform.

1.1.4.1294 Unable to start database %1: Cannot use read-only mode since auditing is currently logging to the transaction log

Error constant	SQLE_AUDITING_DB_READ_ONLY
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Name of the database.
Severity	11
SQLCODE	-1063
SQLSTATE	08W93
Sybase error code	840

Probable cause

The specified database has auditing enabled, and the current settings are preventing it from being started read-only. The `audit_log` option is set to require the transaction log, so auditing must be turned off or the `audit_log` option must be changed before the database will start in read-only mode.

1.1.4.1295 Unable to start database server

Error constant	SQLE_UNABLE_TO_START_ENGINE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	17
SQLCODE	-80
SQLSTATE	08W07
Sybase error code	708

Probable cause

It was not possible to start the database server. There may not be enough memory to run the database server. It may also be that the executable cannot be found.

Related Information

[Troubleshooting: Connections](#)
[UltraLite Engine Utility \(uleng17\)](#)

1.1.4.1296 Unable to start database server: missing license file

Error constant	SQL_E_UNABLE_TO_START_ENGINE_MISSING_LICENSE
ODBC 2 state	08001
ODBC 3 state	08001
Severity	17
SQLCODE	-1179
SQLSTATE	08WA2
Sybase error code	708

Probable cause

It was not possible to start the database server because the server license file was not found. The server license file has the same name as the server executable with the extension ".lic". For example, if you have a database server executable named myserver.exe, then the database server looks for a license file named myserver.lic that is located in the same directory as the database server executable.

Related Information

[How SQL Anywhere Locates Files](#)
[Database Server Ddeployment](#)
[Server Licensing Utility \(dblic\)](#)

1.1.4.1297 Unable to start database server: Server fatal error

Error constant	SQLE_UNABLE_TO_START_ENGINE_FATAL_ERROR
ODBC 2 state	08001
ODBC 3 state	08001
Severity	17
SQLCODE	-1033
SQLSTATE	08W89
Sybase error code	13478

Probable cause

The database server failed to start because a fatal error or assertion failure occurred. More information may be available in the Microsoft Windows event log or UNIX/Linux system log or by manually starting the database server.

1.1.4.1298 Unable to start specified database: %1

Error constant	SQLE_UNABLE_TO_START_DATABASE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Reason the database could not be started, if known.
Severity	11
SQLCODE	-82
SQLSTATE	08W09
Sybase error code	840

Probable cause

The database server was unable to start the specified database. Check the database server messages window for more details. If the server was being started automatically, you can use the database server -o option to view messages from the database server or start the server manually to try to obtain more information about why the database cannot be started.

1.1.4.1299 Unable to start specified database: '%1' is an invalid transaction log

Error constant	SQL_E_CORRUPT_REDO
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1007
SQLSTATE	08W88
Sybase error code	840

Probable cause

The specified file is not a valid transaction log.

1.1.4.1300 Unable to start specified database: '%1' is an invalid transaction log mirror

Error constant	SQL_E_CORRUPT_REDO_MIRROR
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log mirror file.
Severity	11
SQLCODE	-1008
SQLSTATE	08W72
Sybase error code	840

Probable cause

The specified file is not a valid transaction log mirror.

1.1.4.1301 Unable to start specified database: '%1' is not a database

Error constant	SQLE_FILE_NOT_DB
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the database file.
Severity	11
SQLCODE	-1004
SQLSTATE	08W85
Sybase error code	840

Probable cause

The specified file is not a valid database file.

1.1.4.1302 Unable to start specified database: '%1' is not a valid database file

Error constant	SQLE_FILE_BAD_DB
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the database file.
Severity	11
SQLCODE	-1006
SQLSTATE	08W87
Sybase error code	840

Probable cause

The specified file is not a valid database.

Related Information

[Database Starting and Stopping](#)
[How to Start the Database Server](#)
[UltraLite Database Connections](#)

1.1.4.1303 Unable to start specified database: '%1' must be upgraded to start with this server (capability %2 missing)

Error constant	SQLE_UPGRADE_DATABASE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the database file.
Parameter 2	The capability that is missing from the database file.
Severity	11
SQLCODE	-1012
SQLSTATE	08W76
Sybase error code	840

Probable cause

The specified database must be upgraded to start with this server.

1.1.4.1304 Unable to start specified database: '%1' not expecting any operations in transaction log

Error constant	SQLE_EXPECTING_NO_REDO
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1010
SQLSTATE	08W74

Probable cause

The transaction log contains operations, but the database server was not expecting any.

1.1.4.1305 Unable to start specified database: '%1' was created by a different version of the software

Error constant	SQLE_FILE_WRONG_VERSION
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the database file.
Severity	11
SQLCODE	-1005
SQLSTATE	08W86
Sybase error code	840

Probable cause

The specified database file was created by a different version of the software, and it cannot be read by this version.

1.1.4.1306 Unable to start specified database: '%1': transaction log file not found

Error constant	SQLE_LOG_NOT_FOUND
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1017

SQLSTATE	08W81
Sybase error code	840

Probable cause

The transaction log file was not found.

1.1.4.1307 Unable to start specified database: Cannot use log file '%1' since it has been used more recently than the database file

Error constant	SQLLE_LOG_NEWER_THAN_DB
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log mirror file.
Severity	11
SQLCODE	-1016
SQLSTATE	08W80
Sybase error code	840

Probable cause

The transaction log file has been used more recently than the database file.

1.1.4.1308 Unable to start specified database: Cannot use log file '%1' since it is shorter than expected

Error constant	SQLLE_LOG_TOO_SHORT
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log file.
Severity	11

SQLCODE	-1020
SQLSTATE	08W84
Sybase error code	840

Probable cause

The transaction log file is shorter than expected.

1.1.4.1309 Unable to start specified database: Cannot use log file '%1' since the database file has been used more recently

Error constant	SQLE_LOG_OLDER_THAN_DB
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1019
SQLSTATE	08W83
Sybase error code	840

Probable cause

The database file has been used more recently than the transaction log file.

1.1.4.1310 Unable to start specified database: Cannot use log file '%1' since the offsets do not match the offsets in the database file

Error constant	SQLE_LOG_OFFSETS_DONT_MATCH
ODBC 2 state	08001
ODBC 3 state	08001

Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1018
SQLSTATE	08W82
Sybase error code	840

Probable cause

The transaction log file has an offset that does not match the offset expected by the database file.

1.1.4.1311 Unable to start specified database: Cannot use log file '%1' since the timeline does do not match the timeline of the database file

Error constant	SQLE_LOG_TIMELINES_DONT_MATCH
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	The name of the transaction log file.
Severity	11
SQLCODE	-1834
SQLSTATE	08WEC
Sybase error code	12310

Probable cause

The transaction log file has a timeline that does not match the timeline expected by the database file.

1.1.4.1312 Unable to start specified database: Log file error

Error constant	SQLE_UNABLE_TO_START_DATABASE_LOG_ERROR
ODBC 2 state	08001
ODBC 3 state	08001

Severity	11
SQLCODE	-935
SQLSTATE	08W68
Sybase error code	13553

Probable cause

The database server was unable to start the database since the log file is missing, for a different database, or some other reason. Check the server messages window for more details.

1.1.4.1313 Unable to start specified database: Server must be upgraded to start database %1

Error constant	SQLE_UNABLE_TO_START_DATABASE_VER_NEWER
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Name of the database that could not be started, if known.
Severity	11
SQLCODE	-934
SQLSTATE	08W67
Sybase error code	13552

Probable cause

The database server was unable to start the database since the database version is newer than the server version. The server must be upgraded to at least the version of the database to be able to start the database.

1.1.4.1314 Unable to start specified database: The transaction log '%1' or its mirror '%2' is invalid

Error constant	SQLE_CORRUPT_REDO_OR_MIRROR
ODBC 2 state	08001

ODBC 3 state	08001
Parameter 1	The name of the transaction log file.
Parameter 2	The name of the transaction log mirror file.
Severity	11
SQLCODE	-1009
SQLSTATE	08W73
Sybase error code	840

Probable cause

The transaction log differs from the transaction log mirror. Either the transaction log or its mirror is invalid.

1.1.4.1315 Unable to start specified database: Unknown encryption algorithm

Error constant	SQL_E_UNKNOWN_ENCRYPTION_ALGORITHM
ODBC 2 state	08001
ODBC 3 state	08001
Severity	11
SQLCODE	-1011
SQLSTATE	08W75
Sybase error code	840

Probable cause

The database is encrypted with an algorithm not supported by this server.

1.1.4.1316 Unable to start the SQL Anywhere Cockpit when it is stopping

Error constant	SQL_E_COCKPITDB_CANNOT_START_WHEN_DB_STOPPING
----------------	---

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1866
SQLSTATE	08WH1
Sybase error code	12281

Probable cause

You are attempting to start the SQL Anywhere Cockpit while it is stopping.

1.1.4.1317 Unable to start the SQL Anywhere Cockpit: %1

Error constant	SQLE_UNABLE_TO_START_COCKPIT_DATABASE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Reason the SQL Anywhere Cockpit could not be started, if known.
Severity	16
SQLCODE	-1851
SQLSTATE	08WF8
Sybase error code	12294

Probable cause

The database server was unable to start SQL Anywhere Cockpit.

1.1.4.1318 Unable to start the SQL Anywhere Cockpit: Please restart the server with a minimum page size of 4096

Error constant	SQLE_COCKPITDB_SERVER_PAGE_SIZE_TOO_SMALL
----------------	---

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1926
SQLSTATE	08WG3
Sybase error code	12249

Probable cause

You attempted to start the SQL Anywhere Cockpit when the server is running with the page size less than 4096. Restart the server with a minimum page size of 4096.

1.1.4.1319 Unable to stop specified database: %1

Error constant	SQLU_UNABLE_TO_STOP_DATABASE
ODBC 2 state	08001
ODBC 3 state	08001
Parameter 1	Reason the database could not be stopped, if known.
Severity	11
SQLCODE	-1384
SQLSTATE	08WA5
Sybase error code	13184

Probable cause

The database server was unable to stop the specified database.

1.1.4.1320 Unable to stop the SQL Anywhere Cockpit when it is being started

Error constant	SQLC_COCKPITDB_CANNOT_STOP_WHEN_DB_STARTING
ODBC 2 state	ERROR

ODBC 3 state	ERROR
Severity	16
SQLCODE	-1871
SQLSTATE	08WH6
Sybase error code	12276

Probable cause

You are attempting to stop the SQL Anywhere Cockpit while it is being started.

1.1.4.1321 Unable to stop the SQL Anywhere Cockpit when it is being prepared to save.

Error constant	COCKPITDB_CANNOT_STOP_WHEN_PREPARE_SAVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1957
SQLSTATE	08WJ0
Sybase error code	12275

Probable cause

You are attempting to stop the SQL Anywhere Cockpit while it is preparing to save.

1.1.4.1322 Unable to upgrade the SQL Anywhere Cockpit when it is not active

Error constant	SQLC_COCKPITDB_CANNOT_UPGRADE_WHEN_DB_NOT_ACTIVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR

Severity	16
SQLCODE	-1872
SQLSTATE	08WH7
Sybase error code	12275

Probable cause

You are attempting to upgrade the SQL Anywhere Cockpit while it is not active.

1.1.4.1323 Undeclared tag ID: '%1'

Error constant	SQL_E_UNDECLARED_FOR_XML_EXPLICIT_TAG
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value of the undeclared tag ID.
Severity	16
SQLCODE	-901
SQLSTATE	WX009
Sybase error code	13580

Probable cause

Every value appearing in the Tag column of the table must be declared in the TagNumber field of at least one column name.

1.1.4.1324 Underflow when converting '%1'

Error constant	SQL_E_UNDERFLOW
ODBC 2 state	ERROR
ODBC 3 state	42000
Parameter 1	The type being converted.
Severity	16

SQLCODE	-1280
SQLSTATE	WW232
Sybase error code	13806

Probable cause

An underflow occurred when converting the specified type. The source type may be too small (for example zero length binary) or value may be too small to be represented by the destination type.

1.1.4.1325 Unique indexes with the clause WITH NULLS NOT DISTINCT are not supported for this database

Error constant	SQLU_UNIQUE_INDEX_NULLS_NOT_DISTINCT_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1392
SQLSTATE	52W53
Sybase error code	13178

Probable cause

The current database does not have support for unique indexes with the clause WITH NULLS NOT DISTINCT. To use this feature, upgrade your database to the most recent version.

1.1.4.1326 Unit of measure "%1" is not a linear unit

Error constant	SQLS_SLERR_UOM_NOT_LINEAR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the invalid unit of measure.
Severity	16

SQLCODE	-1446
SQLSTATE	2FW39
Sybase error code	13126

Probable cause

The specified unit of measure is not a linear unit of measure.

1.1.4.1327 Unit of measure "%1" is not an angular unit

Error constant	SQLE_SLERR_UOM_NOT_ANGULAR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the invalid unit of measure.
Severity	16
SQLCODE	-1447
SQLSTATE	2FW40
Sybase error code	13125

Probable cause

The specified unit of measure is not a linear unit of measure.

1.1.4.1328 Unit of measure '%1' already exists

Error constant	SQLE_SLERR_DDL_UOM_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the unit of measure.
Severity	16
SQLCODE	-1460
SQLSTATE	2FW53

Probable cause

The named unit of measure is already defined.

1.1.4.1329 Unit of measure '%1' not found

Error constant	SQLE_SLERR_DDL_NO_UOM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unit of measure name.
Severity	16
SQLCODE	-1458
SQLSTATE	2FW51
Sybase error code	13114

Probable cause

The named unit of measure is not defined.

1.1.4.1330 Unknown backup operation

Error constant	SQLE_UNKNOWN_BACKUP_OPERATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	20
SQLCODE	-240
SQLSTATE	WB001
Sybase error code	3206

Probable cause

You specified an invalid backup statement operation in a call to db_backup.

1.1.4.1331 Unknown collation '%1'

Error constant	SQL_E_UNKNOWN_COLLATION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name that is not a database collation.
Severity	16
SQLCODE	-1506
SQLSTATE	WC018
Sybase error code	12597

Probable cause

The specified collation is unknown. Ensure the name is spelled correctly.

Related Information

[Alternate Collations](#)
[CREATE DATABASE Statement](#)
[Initialization Utility \(dbinit\)](#)
[UltraLite collation Creation Option](#)
[UltraLite Supported Collations](#)

1.1.4.1332 Unknown FOR XML EXPLICIT directive: '%1'

Error constant	SQL_E_BAD_FOR_XML_EXPLICIT_DIRECTIVE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The unknown directive.
Severity	16

SQLCODE	-898
SQLSTATE	WX006
Sybase error code	13583

Probable cause

Legal FOR XML EXPLICIT directives are: id, idref, idrefs, hide, element, xml, and cdata. Legal FOR JSON EXPLICIT directives are: hide, and element.

Related Information

[FOR XML EXPLICIT](#)
[FOR JSON EXPLICIT](#)

1.1.4.1333 Unknown function '%1'

Error constant	SQLE_UNKNOWN_FUNC
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Function name that is not a database function.
Severity	15
SQLCODE	-148
SQLSTATE	42W05
Sybase error code	176

Probable cause

You misspelled the name of a database function (such as MAXIMUM instead of MAX) in a query definition or in a query column name.

Related Information

[SQL Functions](#)

1.1.4.1334 Unknown option '%1' specified for target type '%2'

Error constant	SQLE_UNKNOWN_OPTION_FOR_TARGET_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The option name.
Parameter 2	The trace event target type.
Severity	11
SQLCODE	-1647
SQLSTATE	WE032
Sybase error code	12474

Probable cause

An unknown option name was specified for given target type.

1.1.4.1335 Unknown spatial reference system (%1)

Error constant	SQLE_SLERR_SRID_UNKNOWN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The spatial reference system identifier.
Severity	16
SQLCODE	-1409
SQLSTATE	2FF59
Sybase error code	13163

Probable cause

The provided SRID does not match a defined spatial reference system.

Related Information

[Spatial Reference Systems \(SRS\) and Spatial Reference Identifiers \(SRID\)](#)

[ST_Geometry Type](#)

[ST_GEOMETRY Data Type - UltraLite](#)

1.1.4.1336 Unknown unit of measure '%1'

Error constant	SQLE_SLERR_UNKNOWN_UOM
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the unit of measure.
Severity	16
SQLCODE	-1404
SQLSTATE	2FF14
Sybase error code	13168

Probable cause

The name does not match a defined unit of measure.

1.1.4.1337 UNLOAD TABLE cannot be used to unload a view

Error constant	SQLE_CANNOT_UNLOAD_A_VIEW
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-643
SQLSTATE	WL004
Sybase error code	13672

Probable cause

UNLOAD TABLE was specified with the name of a view. UNLOAD TABLE may only be used to unload tables.

1.1.4.1338 UNPIVOT error: An IN clause item does not contain the same number of items as the FOR clause

Error constant	SQLE_UNPIVOT_INVALID_IN_CLAUSE
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1817
SQLSTATE	53033
Sybase error code	12327

Probable cause

You specified an UNPIVOT, but the number of items in the FOR clause does not match the number of items in one IN clause item.

1.1.4.1339 UNPIVOT error: Cannot create valid identifiers for IN clause items

Error constant	SQLE_UNPIVOT_INVALID_IDENTIFIER
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-1847
SQLSTATE	53038
Sybase error code	12297

Probable cause

You specified an UNPIVOT clause, but the IN clause contains items for which no valid identifiers can be created. Provide valid aliases for the IN clause items.

1.1.4.1340 Unsupported character set '%1' and unsupported language '%2'; language used is '%3' instead

Error constant	SQL_E_UNSUPPORTED_CHARSET_AND_LANGUAGE
ODBC 2 state	01000
ODBC 3 state	01000
Parameter 1	Name of the character set that could not be supported.
Parameter 2	Name of the language that could not be supported.
Parameter 3	Name of the language that the server will use to send language strings.
Severity	10
SQLCODE	117
SQLSTATE	01W15
Sybase error code	13616

Probable cause

The character set that the application requested is not supported by the server to which the application is connecting. The language that the application requested is not supported either. Language strings will be sent in the language specified.

Related Information

[Character Set Conversion](#)

1.1.4.1341 Unsupported extended storage syntax

Error constant	SQL_E_RESTORE_UNSUPPORTED_HANA_SYNTAX
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1910
SQLSTATE	42X17
Sybase error code	12256

Probable cause

Cannot use extended storage syntax when not in an SAP HANA environment.

1.1.4.1342 Unsupported property '%1' in service USING attribute

Error constant	SQLE_SERVICE_PARM_UNSUPPORTED_PROPERTY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the unsupported property.
Severity	16
SQLCODE	-1024
SQLSTATE	42WAF
Sybase error code	13486

Probable cause

The service definition contains a USING attribute with an unsupported property.

1.1.4.1343 Unsupported use of ROW type in an INTO clause

Error constant	SQLE_INTRO_CLAUSE_UNSUPPORTED_USE_OF_ROW_TYPE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1815
SQLSTATE	WP030
Sybase error code	12329

1.1.4.1346 Update operation attempted on a read-only cursor

Error constant	SQLE_READ_ONLY_CURSOR
ODBC 2 state	S1009
ODBC 3 state	HY092
Severity	16
SQLCODE	-633
SQLSTATE	42W30
Sybase error code	7732

Probable cause

You attempted an update operation on a cursor that was explicitly declared as read-only.

1.1.4.1347 Update operation attempted on non-updatable query

Error constant	SQLE_NON_UPDATEABLE_VIEW
ODBC 2 state	42000
ODBC 3 state	42000
Severity	15
SQLCODE	-192
SQLSTATE	42W31
Sybase error code	7301

Probable cause

You attempted an insert, update, or delete operation on a query that is implicitly read-only. Queries that contain DISTINCT, GROUP BY, HAVING, EXCEPT, INTERSECT or UNION, or that contain aggregate functions, or that involve a join, are implicitly read-only. If the query references a view then the view may be non-updatable.

1.1.4.1348 Update operation attempted on non-updatable remote query

Error constant	SQLE_NON_UPDATEABLE_EXT_TAB
ODBC 2 state	42000
ODBC 3 state	42000
Severity	15
SQLCODE	-728
SQLSTATE	42W35
Sybase error code	7338

Probable cause

You attempted an update or delete operation on a remote table that is currently not supported. Examples of such operations include positioned updates or deletes and updates or deletes that involve a join between local and proxy tables. Updates or deletes that involve a join between proxy tables on different remote servers will also give this error.

1.1.4.1349 Use of %TYPE or %ROWTYPE is not allowed for variable or temporary objects

Error constant	SQLE_TEMPORARY_OR_VARIABLE_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1727
SQLSTATE	WP023
Sybase error code	12410

Probable cause

You tried to use %TYPE or %ROWTYPE with a temporary object such as procedure parameters or a result set, which is not allowed.

1.1.4.1350 Use of feature '%1' is not allowed

Error constant	SQLE_SECURE_FEATURE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the SQL statement or feature.
Severity	14
SQLCODE	-1084
SQLSTATE	57W02
Sybase error code	13430

Probable cause

You have attempted to use a feature that was disabled by the server administrator when the database server was started.

1.1.4.1351 Use of statement '%1', which requires feature '%2', is not allowed

Error constant	SQLE_SECURE_STATEMENT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the SQL statement.
Parameter 2	Name of the feature.
Severity	14
SQLCODE	-1142
SQLSTATE	57W04
Sybase error code	13371

Probable cause

You have attempted to use a statement which requires a feature that was disabled by the server administrator when the database server was started.

1.1.4.1352 Use of table privilege '%1' is not supported on the current database

Error constant	SQLE_TABPRIV_LOAD_TRUNCATE_UNSUPPORTED
ODBC 2 state	28000
ODBC 3 state	28000
Parameter 1	The table privilege, load or truncate.
Severity	16
SQLCODE	-1631
SQLSTATE	0A007
Sybase error code	12475

Probable cause

The current database is an older database and does not have the capability to support table privileges load or truncate. You must upgrade your database to use these table privileges.

1.1.4.1353 Use of WITH DROP OBJECTS is not allowed with '%1'

Error constant	SQLE_WITH_DROP_OBJECTS_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the role being dropped.
Severity	14
SQLCODE	-1561
SQLSTATE	28W35
Sybase error code	12544

Probable cause

Use of WITH DROP OBJECTS is not allowed with user extended as role.

1.1.4.1354 Use of WITH NO SYSTEM PRIVILEGE INHERITANCE option is not allowed with %1

Error constant	SQLE_INVALID_ROLE_GRANT_OPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the role.
Severity	14
SQLCODE	-1539
SQLSTATE	28W28
Sybase error code	12566

Probable cause

WITH NO SYSTEM PRIVILEGE INHERITANCE option can be specified only with user defined roles corresponding to legacy non-inheritable authorities.

1.1.4.1355 User "%1" already exists

Error constant	SQLE_USER_ALREADY_EXISTS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the user.
Severity	16
SQLCODE	-1198
SQLSTATE	WW101
Sybase error code	13317

Probable cause

An attempt was made to create a user that already exists in the database.

Related Information

[Users](#)

[Creating an UltraLite User with SQL Central](#)

[CREATE USER Statement](#)

[CREATE USER Statement \[UltraLite\]](#)

1.1.4.1356 User '%1' already has EXECUTE permission

Error constant	SQLE_ALREADY_HAS_EXEC_PERMS
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the user that already has EXECUTE permission.
Severity	16
SQLCODE	-968
SQLSTATE	42WAB
Sybase error code	13522

Probable cause

You attempted to give EXECUTE permission on a stored procedure to a user that already has EXECUTE permission on that procedure.

1.1.4.1357 User '%1' already has GRANT OPTION

Error constant	SQLE_ALREADY_HAS_GRANT_PERMS
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the user that already has GRANT OPTION.
Severity	16
SQLCODE	-120
SQLSTATE	42W01
Sybase error code	13625

Probable cause

You attempted to give GRANT OPTION to a user that already has it.

1.1.4.1358 User '%1' already has membership in group '%2'

Error constant	SQLE_ALREADY_HAS_GROUP_MEMBERSHIP
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the user that already has membership.
Parameter 2	Name of the group.
Severity	16
SQLCODE	-312
SQLSTATE	42W34
Sybase error code	13627

Probable cause

You attempted to give a membership in a group to a user that already has such membership.

1.1.4.1359 User '%1' has the row in '%2' locked

Error constant	SQLE_LOCKED
ODBC 2 state	40001
ODBC 3 state	40001
Parameter 1	Name of another user.
Parameter 2	Table that generates the error.
Severity	21
SQLCODE	-210
SQLSTATE	42W18
Sybase error code	8405

Probable cause

The operation failed because another connection holds a lock on the same object you are attempting to modify. With INSERT, UPDATE, DELETE, SELECT, or MERGE statements this error is typically caused by attempting to read or write a row that is locked by another user, while the database option 'blocking' is set to Off. With data definition statements, including CREATE, DROP, GRANT, REVOKE, REFRESH, or ALTER, this error can be generated when the connection executing the DDL statement is unable to obtain an exclusive lock on the object to be modified (table, view, materialized view, or index) so that the operation can proceed. During some operations (for example, refreshing a materialized view), a connection can temporarily set blocking to Off to complete the operation. The temporary setting only applies to the connection and is reset after the operation completes if the initial setting was On. However, a SQLCODE -210 SQLSTATE 42W18 error can be generated during the time that blocking is set to Off.

Related Information

[blocking Option](#)

1.1.4.1360 User '%1' is already the publisher for this database

Error constant	SQLCODE	SQLSTATE	SQLCODE	SQLSTATE
ODBC 2 state	S0002	42S02	-284	5RW05
ODBC 3 state	42S02			
Parameter 1	Name of the publisher.			
Severity	16			
SQLCODE	-284			
SQLSTATE	5RW05			
Sybase error code	13646			

Probable cause

You attempted to GRANT PUBLISH to a user ID, when a publisher already exists.

1.1.4.1361 User '%1' is not a remote user for this database

Error constant	SQLE_NOT_REMOTE_USER
ODBC 2 state	S0002
ODBC 3 state	42S02
Parameter 1	Name of user.
Severity	16
SQLCODE	-285
SQLSTATE	5RW06
Sybase error code	13647

Probable cause

You attempted to execute a CREATE SUBSCRIPTION or PASSTHROUGH for a user that is not a remote user of this database. You must GRANT REMOTE or GRANT CONSOLIDATE for this user before proceeding with this operation.

1.1.4.1362 User '%1' is not a user group

Error constant	SQLE_NOT_A_GROUP
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of user you thought was a group.
Severity	16
SQLCODE	-123
SQLSTATE	42W03
Sybase error code	13626

Probable cause

You attempted to add a member to group, but the user ID specified as a group has not been granted GROUP permission.

1.1.4.1363 User cannot be dropped because external logins exist for this user

Error constant	SQLE_USER_HAS_EXTERNLOGINS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	11
SQLCODE	-1220
SQLSTATE	W0028
Sybase error code	13300

Probable cause

The user cannot be dropped while an external login for the user still exists.

1.1.4.1364 User ID '%1' does not exist

Error constant	SQLE_UNKNOWN_USERID
ODBC 2 state	28000
ODBC 3 state	28000
Parameter 1	Name of the user that could not be found.
Severity	11
SQLCODE	-140
SQLSTATE	08004
Sybase error code	509

Probable cause

You used a user ID that does not exist.

Related Information

[Users](#)
[Creating an UltraLite User with SQL Central](#)

1.1.4.1365 User message %1 already exists

Error constant	SQLE_MESSAGE_ALREADY_EXISTS
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Error number of the user message that exists in the database.
Severity	16
SQLCODE	-610
SQLSTATE	52W16
Sybase error code	13624

Probable cause

The message with this error number already exists in the database.

1.1.4.1366 User message %1 not found

Error constant	SQLE_MESSAGE_NOT_FOUND
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Message number.
Severity	16
SQLCODE	-612
SQLSTATE	52W17
Sybase error code	2748

Probable cause

The message with this error number does not exist in the database.

1.1.4.1367 User or Role ID '%1' does not exist

Error constant	SQLE_UNKNOWN_USER_ROLE_ID
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the user or role that could not be found.
Severity	14
SQLCODE	-1538
SQLSTATE	28W27
Sybase error code	12567

Probable cause

You used a user or role ID that does not exist.

1.1.4.1368 User owns locked mutexes

Error constant	SQLE_USER_OWNS_MUTEXES_IN_USE
ODBC 2 state	40001
ODBC 3 state	40001
Severity	16
SQLCODE	-1830
SQLSTATE	42WF5
Sybase error code	12314

Probable cause

You attempted to drop a user that owns a (possibly deleted) mutex currently locked by other active users of the database, or a mutex/semaphore that is being created or dropped.

1.1.4.1369 User owns procedures in use

Error constant	SQLE_USER_OWNS_PROCEDURES_IN_USE
----------------	----------------------------------

ODBC 2 state	40001
ODBC 3 state	40001
Severity	16
SQLCODE	-750
SQLSTATE	42W55
Sybase error code	3702

Probable cause

You attempted to drop a user that owns a procedure being used by other active users of the database.

1.1.4.1370 User owns sequences in use

Error constant	SQL_USER_OWNS_SEQUENCES_IN_USE
ODBC 2 state	40001
ODBC 3 state	40001
Severity	16
SQLCODE	-1367
SQLSTATE	42WE2
Sybase error code	13195

Probable cause

You attempted to drop a user that owns a sequence being used by other active users of the database.

1.1.4.1371 User owns tables in use

Error constant	SQL_USER_OWNS_TABLES_IN_USE
ODBC 2 state	40001
ODBC 3 state	40001
Severity	16
SQLCODE	-751

SQLSTATE	42W56
Sybase error code	3702

Probable cause

You attempted to REVOKE CONNECT from a user that owns a table being used by other active users of the database.

1.1.4.1372 User-defined exception signaled

Error constant	SQL_USER_DEFINED_EXCEPTION
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-297
SQLSTATE	99999
Sybase error code	13662

Probable cause

A stored procedure or trigger signaled a user-defined exception. This error state is reserved for use within stored procedures or triggers that contain exception handlers, as a way of signaling an exception that can be guaranteed to not have been caused by the database server. Valid SQLSTATE values range from 99000 to 99999 and are set by the user when executing the signal SQL statement.

1.1.4.1373 User-defined type '%1' not found

Error constant	SQL_USER_TYPE_NOT_FOUND
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the user-defined type.
Severity	16
SQLCODE	-613

SQLSTATE	52W18
Sybase error code	2715

Probable cause

The user-defined type with this name does not exist in the database.

1.1.4.1374 USING attribute cannot coexist with FORMAT or GROUP attributes

Error constant	SQLE_SERVICE_ATTR_COEXIST
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1026
SQLSTATE	42WB1
Sybase error code	13484

Probable cause

The service definition for the specified service type cannot specify a USING attribute along with a FORMAT or GROUP attribute.

1.1.4.1375 Using temporary table

Error constant	SQLE_TEMPORARY_TABLE
ODBC 2 state	01000
ODBC 3 state	01000
Severity	10
SQLCODE	102
SQLSTATE	01W02
Sybase error code	13075

Probable cause

A temporary table has been created to satisfy the query. This warning can only occur on an OPEN statement.

Related Information

[OPEN Statement \[ESQL\] \[SP\]](#)

1.1.4.1376 VALIDATE statement must refer to a base table

Error constant	SQLE_CANNOT_VALIDATE_OBJECT
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16
SQLCODE	-720
SQLSTATE	42W51
Sybase error code	13729

Probable cause

The VALIDATE statement must refer to a local base table; it cannot refer to a view, an SAP IQ table, or an object on a remote server.

1.1.4.1377 Value %1 out of range for coordinate %2 (SRS bounds [%3, %4] exceeded by more than 50%)

Error constant	SQLE_SLERR_OBJECT_OUT_OF_SRS_BOUNDS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The value is out of the defined bounds.
Parameter 2	The coordinate name that is out of range.
Parameter 3	The minimum value allowed by the spatial reference system.
Parameter 4	The maximum value allowed by the spatial reference system.

Severity	16
SQLCODE	-1484
SQLSTATE	2FW79
Sybase error code	13088

Probable cause

The geometry contains a point outside of the bounds specified by the spatial reference system.

1.1.4.1378 Value %1 out of range for destination

Error constant	SQL_E_OVERFLOW_ERROR
ODBC 2 state	22003
ODBC 3 state	22003
Parameter 1	The value that caused the overflow.
Severity	16
SQLCODE	-158
SQLSTATE	22003
Sybase error code	220

Probable cause

You supplied to or fetched from the database a value that is out of range for the destination column or host variable. For example, the value 10 may have been supplied for a DECIMAL(3,2) field.

Related Information

[Data Type Conversions](#)
[CAST Function \[Data Type Conversion\]](#)
[SQL Data Types](#)
[Embedded SQL Host Variable Data Types](#)

1.1.4.1379 Value for column '%1' in table '%2' has changed

Error constant	SQLC_COLUMN_VALUE_CHANGED
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	Name of the column whose value has changed.
Parameter 2	Name of the table containing the column.
Severity	10
SQLCODE	106
SQLSTATE	01W06
Sybase error code	532

Probable cause

A replicated UPDATE has found a value in an updated column that does not match the value when the original UPDATE was made.

1.1.4.1380 Value truncated

Error constant	SQLC_TRUNCATED
ODBC 2 state	01004
ODBC 3 state	01004
Severity	10
SQLCODE	101
SQLSTATE	01004
Sybase error code	7337

Probable cause

You may have fetched data into a host variable or SQLDA variable not large enough to receive the value.

Related Information

[Host Variables in Embedded SQL](#)

1.1.4.1381 Value-sensitive cursor used after a TRUNCATE

Error constant	SQLE_HOLD_CURSOR_AFTER_TRUNCATE
ODBC 2 state	24000
ODBC 3 state	24000
Severity	16
SQLCODE	-1241
SQLSTATE	24001
Sybase error code	13273

Probable cause

You attempted to use a value-sensitive cursor opened WITH HOLD after a TRUNCATE or after a COMMIT removed all rows from a temporary table declared as ON COMMIT DELETE ROWS.

1.1.4.1382 Variable '%1' not found

Error constant	SQLE_VARIABLE_NOT_FOUND
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the variable that could not be found.
Severity	15
SQLCODE	-260
SQLSTATE	42W14
Sybase error code	137

Probable cause

You attempted to DROP or SET the value of a SQL variable that was not created or was previously dropped.

1.1.4.1383 VERIFY and FOR REPLICATION cannot be used together

Error constant	NETBU_WITH_VERIFY_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1961
SQLSTATE	42WE10
Sybase error code	12220

Probable cause

VERIFY during NETWORK BACKUP for replication is not allowed.

1.1.4.1384 VERIFY and RENAME cannot be used together

Error constant	SQLRENAME_WITH_VERIFY_NOT_ALLOWED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	15
SQLCODE	-1398
SQLSTATE	42WE5
Sybase error code	12599

Probable cause

Since VERIFY will never write to any dbspaces, renaming dbspaces cannot be done during restore verification.

1.1.4.1385 Verify fails, bytes written to pipe %1 and bytes written to file %2

Error constant	SQLE_BACKUP_BKINT_ERROR_SIZE_MISMATCH
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The number of bytes written to pipe
Parameter 2	The number of bytes written to file
Severity	16
SQLCODE	-1918
SQLSTATE	WB028
Sybase error code	12264

Probable cause

Backup size returned by SAP HANA does not match with bytes written into Pipe

1.1.4.1386 Version 'V%1' interface used by external function call '%2' is not supported for execution in the current context

Error constant	SQLE_INCOMPATIBLE_EXTERNAL_CALL
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	API version of the external function that is being called.
Parameter 2	Name of the external function that is being called.
Severity	16
SQLCODE	-818
SQLSTATE	WW026
Sybase error code	13824

Probable cause

You attempted to call an external function. The attempt to load the associated library failed because of incompatibility with the server. Incompatibility may arise because the dynamic library is using an external

function API that is either not supported by the server or is newer than the one supported by the server. It may also arise if the external API is not compatible with the data in the current context.

1.1.4.1387 View references '%1', which is a temporary object. Views can only refer to permanent objects

Error constant	SQL_E_VIEW_OVER_TEMP_OBJECT
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Temporary object name.
Severity	16
SQLCODE	-766
SQLSTATE	42U00
Sybase error code	4412

Probable cause

Views must refer only to permanent objects, not to temporary objects such as local temporary tables.

1.1.4.1388 VIRTUAL clause for CREATE INDEX statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_CREATEINDEX_VIRTUAL_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1945
SQLSTATE	OAW41
Sybase error code	12232

Probable cause

The VIRTUAL clause of the CREATE INDEX statement is not supported when the statement is in the BEGIN PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.1389 Virtual index creation with more than %1 columns

Error constant	SQL_E_TOO_MANY_VIRTUAL_INDEX_COLUMNS
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The maximum number of virtual index columns.
Severity	16
SQLCODE	-887
SQLSTATE	54W50
Sybase error code	13597

Probable cause

You attempted to create a virtual index with more than the maximum number of columns.

1.1.4.1390 Warning detected when optimizing SELECT INTO is treated as an error

Error constant	SQL_E_SELECT_INTO_WARNING_TREATED_AS_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-995
SQLSTATE	WP016
Sybase error code	13495

Probable cause

The SELECT...INTO #TEMPTABLE statement cannot proceed if a warning is detected while optimizing the query. To fix the problem, test the query by removing the INTO clause, and resolve the reported warning.

1.1.4.1391 Warning: %1

Error constant	SQLWARNING
ODBC 2 state	OK
ODBC 3 state	OK
Parameter 1	Warning message.
Severity	10
SQLCODE	200
SQLSTATE	01000
Sybase error code	13619

Probable cause

A warning has occurred. The message indicates the condition that caused the warning.

1.1.4.1392 When wait_for_commit database option is enabled, LOAD TABLE statement is not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_LOADTABLE_WAIT_FOR_COMMIT_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1938
SQLSTATE	0AW35
Sybase error code	12239

Probable cause

When the `wait_for_commit` database option is set to on, the `LOAD TABLE` statement is not supported in the `BEGIN PARALLEL WORK...END PARALLEL WORK` statement. Set the `wait_for_commit` database option to off, or drop the foreign keys of the target tables and recreate them after loading the table.

1.1.4.1393 Window '%1' not found

Error constant	SQL_E_WINDOW_NOT_FOUND
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the window that could not be found.
Severity	16
SQLCODE	-947
SQLSTATE	42WA3
Sybase error code	13541

Probable cause

You have attempted to reference a window name that is not defined in the window list of the `SELECT` statement.

1.1.4.1394 Window function requires ORDER BY

Error constant	SQL_E_OBSOLETE_ORDERBY_REQUIRED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-965
SQLSTATE	42WA9
Sybase error code	13525

Probable cause

Rank functions and window functions that use the RANGE keyword must specify an ORDER BY clause.

1.1.4.1395 Window function used in predicate

Error constant	SQLI_ILLEGAL_WINDOW_PREDICATE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-964
SQLSTATE	42WA8
Sybase error code	13526

Probable cause

A window function was used in the WHERE or HAVING clause of a SELECT statement. Consider making the SELECT into a derived table, putting the window function in the SELECT list of the derived table, and changing the predicate to reference the derived column.

1.1.4.1396 WITH CHECK OPTION violated for insert/update on base table '%1'

Error constant	SQLI_WITH_CHECK_OPTION_VIOLATION
ODBC 2 state	S1000
ODBC 3 state	44000
Parameter 1	Name of the base table being updated.
Severity	16
SQLCODE	-632
SQLSTATE	44000
Sybase error code	550

Probable cause

You attempted an insert or update operation on the indicated base table through a view (possibly nested). However, one or more values in the modified row(s) triggered a WITH CHECK OPTION violation. This violation occurs when a modified value causes one or more rows to fall outside the range of the view by making the view's WHERE clause evaluate to FALSE or UNKNOWN for that row.

1.1.4.1397 WITH CHECKPOINT ON clause for LOAD TABLE statement not supported in BEGIN PARALLEL WORK...END PARALLEL WORK statement

Error constant	PARALLEL_LOADTABLE_WITH_CHECKPOINT_ON_NOT_SUPPORTED
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1941
SQLSTATE	0AW38
Sybase error code	12236

Probable cause

The WITH CHECKPOINT ON clause of the LOAD TABLE statement is not supported when the statement is in the BEGIN PARALLEL WORK...END PARALLEL WORK statement.

1.1.4.1398 WRITETEXT not allowed: immediate materialized view %1 depends on %2

Error constant	SQLE_WRITETEXT_TABLE_WITH_IMV
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	Name of the dependent immediate materialized view.
Parameter 2	Name of the base table.
Severity	16
SQLCODE	-1203

SQLSTATE	55W32
Sybase error code	13312

Probable cause

WRITETEXT is not allowed on base tables that have dependent initialized immediate materialized views. No operation that does not fire triggers is allowed on base tables with dependent initialized immediate materialized views.

1.1.4.1399 Wrong number of parameters to function '%1'

Error constant	SQL_E_WRONG_PARAMETER_COUNT
ODBC 2 state	37000
ODBC 3 state	42000
Parameter 1	Name of the function.
Severity	15
SQLCODE	-154
SQLSTATE	37505
Sybase error code	174

Probable cause

You supplied an incorrect number of parameters to a database function.

Related Information

[SQL Functions](#)
[SQL Functions](#)

1.1.4.1400 Wrong number of values for INSERT

Error constant	SQL_E_WRONG_NUM_OF_INSERT_COLS
----------------	--------------------------------

ODBC 2 state	21S01
ODBC 3 state	21S01
Severity	16
SQLCODE	-207
SQLSTATE	53002
Sybase error code	213

Probable cause

The number of values you are trying to insert does not match the number of columns specified in the INSERT statement, or the number of columns in the table if no columns are specified.

Related Information

[INSERT Statement](#)

[INSERT Statement \[UltraLite\]](#)

1.1.4.1401 Wrong number of variables in FETCH

Error constant	SQLW_WRONG_NUM_OF_FETCH_VARIABLES
ODBC 2 state	S1002
ODBC 3 state	07009
Severity	16
SQLCODE	-264
SQLSTATE	42W26
Sybase error code	553

Probable cause

You specified a number of variables in a FETCH statement that does not match the number of SELECT list items.

1.1.4.1402 XML parser error: %1

Error constant	SQLE_XML_PARSER_ERROR
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The error message returned by the XML parser.
Severity	16
SQLCODE	-888
SQLSTATE	WX002
Sybase error code	13595

Probable cause

An XML instance will only parse correctly if it is well-formed as defined by the XML 1.0 specification.

1.1.4.1403 XMLGEN evaluation failure

Error constant	SQLE_XMLGEN_EVALUATION_FAILURE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-906
SQLSTATE	WX013
Sybase error code	13577

Probable cause

One of the variables referenced in the XQuery constructor was not found in the list of arguments.

1.1.4.1404 XPath parser error: %1

Error constant	SQLE_XQUERY_PARSER_ERROR
----------------	--------------------------

ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The error message returned by the XPath parser.
Severity	16
SQLCODE	-892
SQLSTATE	WX003
Sybase error code	13591

Probable cause

The XPath expression is illegal or uses features that are not currently supported.

1.1.4.1405 You are not authorized to assign the feature list '%2' to a secure feature key using %1

Error constant	SQLE_SFC_NO_AUTH_FOR_FEAT
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature list.
Severity	14
SQLCODE	-1690
SQLSTATE	08S06
Sybase error code	12444

Probable cause

An attempt was made to define a secure feature key to use a secure feature that the user is not authorized to use or assign.

Related Information

[Secured Features](#)

1.1.4.1406 You are not authorized to change the secure feature key named '%2' using %1

Error constant	SQLE_SFC_NO_AUTH_FOR_KEY
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Parameter 1	The name of the procedure.
Parameter 2	The secure feature key name.
Severity	14
SQLCODE	-1691
SQLSTATE	08S07
Sybase error code	12445

Probable cause

The user is not authorized to change the named secure feature key.

Related Information

[Secured Features](#)
[-sf Database Server Option](#)
[sa_server_option System Procedure](#)

1.1.4.1407 You cannot synchronize or upgrade with uncommitted transactions

Error constant	SQLE_UNCOMMITTED_TRANSACTIONS
ODBC 2 state	37000
ODBC 3 state	42000
Severity	16

SQLCODE	-755
SQLSTATE	0AW08
Sybase error code	13765

Probable cause

You attempted to synchronize or upgrade the schema of an UltraLite database and there are changes in the UltraLite database that have not been committed.

Related Information

[Transactions](#)

[UltraLite Transaction Processing](#)

1.1.4.1408 You cannot use a security token when making remote connections

Error constant	SQL_INVALID_USE_OF_SECURITY_TOKEN
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1590
SQLSTATE	W0032
Sybase error code	12515

Probable cause

A security token cannot be used to make remote data access connections.

1.1.4.1409 You do not have '%1' system privilege or authority to set the option '%2'

Error constant	SQLE_OPTION_REQUIRES_DBA
ODBC 2 state	42000
ODBC 3 state	42000
Parameter 1	Name of the system privilege or authority required to set the option.
Parameter 2	Name of the option that could not be set.
Severity	14
SQLCODE	-204
SQLSTATE	42W46
Sybase error code	5878

Probable cause

The option specified in the SET OPTION statement can only be set by a user with DBA authority or by a user with SET ANY SYSTEM OPTION / SET ANY SECURITY OPTION / SET ANY PUBLIC OPTION depending on the option.

1.1.4.1410 You must upgrade your database in order to use the MIRROR server class

Error constant	SQLE_OMNI_MIRROR_NEEDS_UPGRADE
ODBC 2 state	ERROR
ODBC 3 state	ERROR
Severity	16
SQLCODE	-1574
SQLSTATE	W0030
Sybase error code	12531

Probable cause

You attempted to create a remote data access server of type mirror while connected to a database that was created with older software. You must upgrade your database in order to make use of the mirror server class.

1.2 SQL Preprocessor Error Messages

The SQL preprocessor generates messages depending on which command-line options are set. Each message may be an error, a warning, or a non-conformance flag, which itself can be an error or a warning.

In this section:

[SQL Preprocessor Error Messages Sorted by Error Code \[page 936\]](#)

[SQL Preprocessor Error Messages Listed by Message Text \[page 938\]](#)

Related Information

[The Embedded SQL Preprocessor](#)

1.2.1 SQL Preprocessor Error Messages Sorted by Error Code

Error code	Message text
2601	Subscript value %1 too large [page 962]
2602	Combined pointer and arrays not supported for host types [page 945]
2603	Only one-dimensional arrays supported for CHAR type [page 960]
2604	VARCHAR type must have a length [page 966]
2605	Arrays of VARCHAR not supported [page 943]
2606	VARCHAR host variables cannot be pointers [page 966]
2607	Initializer not allowed on VARCHAR host variable [page 952]
2608	FIXCHAR type must have a length [page 947]
2609	Arrays of FIXCHAR not supported [page 943]
2610	Arrays of this type not supported [page 943]
2611	Precision must be specified for DECIMAL type [page 960]
2612	Arrays of DECIMAL not supported [page 942]
2613	Unknown host variable type [page 964]
2614	Invalid integer [page 954]
2615	'%1' host variable must be a C string type [page 940]
2617	'%1' symbol already defined [page 941]

Error code	Message text
2618	Invalid type for SQL statement variable [page 955]
2619	Cannot find include file '%1' [page 944]
2620	Host variable '%1' is unknown [page 949]
2621	Indicator variable '%1' is unknown [page 952]
2622	Invalid type for indicator variable '%1' [page 955]
2623	Invalid host variable type on '%1' [page 954]
2625	Host variable '%1' has two different definitions [page 948]
2626	Statement '%1' not previously prepared [page 961]
2627	Cursor '%1' not previously declared [page 945]
2628	Unknown statement '%1' [page 965]
2629	Host variables not supported for this cursor [page 949]
2630	Host variables specified twice (on DECLARE and OPEN) [page 950]
2631	Must specify a host list or USING clause on %1 [page 957]
2633	No INTO clause for a SELECT statement [page 959]
2636	Incorrect Embedded SQL syntax [page 951]
2637	Missing ending quote of string literal [page 957]
2639	Token too long [page 963]
2640	'%1' host variable must be an integer type [page 941]
2641	Must specify a SQLDA for a DESCRIBE statement [page 958]
2642	Two SQLDAs specified of the same type (INTO or USING) [page 963]
2646	Cannot describe static cursors [page 944]
2647	Macros cannot be redefined [page 956]
2648	Invalid array dimension [page 953]
2649	Invalid descriptor index [page 953]
2650	Invalid field for SET DESCRIPTOR [page 953]
2651	Field used more than once in SET DESCRIPTOR statement [page 947]
2652	Data value must be a host variable [page 946]
2660	The INTO clause is not supported in DECLARE CURSOR statements - ignored [page 962]
2661	Unrecognized SQL syntax [page 965]
2662	Unknown SQL function '%1' [page 964]
2663	Wrong number of arguments for SQL function '%1' [page 967]

Error code	Message text
2664	Static statement names do not work properly if used by two threads [page 961]
2665	Host variable '%1' has been redefined [page 948]
2666	Unsupported language extension detected in syntax [page 965]
2667	Language extension detected in syntax [page 956]
2680	No DECLARE SECTION and no INCLUDE SQLCA statement [page 958]
2681	Unable to open temporary file [page 964]
2682	Error reading temporary file [page 946]
2683	Error writing output file [page 946]
2690	Inconsistent number of host variables for this cursor [page 951]
2691	Inconsistent host variable types for this cursor [page 950]
2692	Inconsistent indicator variables for this cursor [page 951]
2694	No OPEN for cursor '%1' [page 959]
2695	No FETCH or PUT for cursor '%1' [page 958]
2696	Host variable '%1' is in use more than once with different indicators [page 948]
2697	LONG BINARY/LONG VARCHAR size limit is 65535 for UltraLite [page 956]
2698	WCHAR and TCHAR host variable types are not supported [page 966]
2699	char, WCHAR, and TCHAR string parameters cannot be mixed [page 945]
2700	SQL syntax is only supported by UltraLite [page 961]
2701	A FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR) [page 942]

1.2.2 SQL Preprocessor Error Messages Listed by Message Text

In this section:

- '%1' host variable must be a C string type [page 940]
- '%1' host variable must be an integer type [page 941]
- '%1' symbol already defined [page 941]

[A FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE \(not on DECLARE CURSOR\) \[page 942\]](#)

[Arrays of DECIMAL not supported \[page 942\]](#)

[Arrays of FIXCHAR not supported \[page 943\]](#)

[Arrays of this type not supported \[page 943\]](#)

[Arrays of VARCHAR not supported \[page 943\]](#)

[Cannot describe static cursors \[page 944\]](#)

[Cannot find include file '%1' \[page 944\]](#)

[char, WCHAR, and TCHAR string parameters cannot be mixed \[page 945\]](#)

[Combined pointer and arrays not supported for host types \[page 945\]](#)

[Cursor '%1' not previously declared \[page 945\]](#)

[Data value must be a host variable \[page 946\]](#)

[Error reading temporary file \[page 946\]](#)

[Error writing output file \[page 946\]](#)

[Field used more than once in SET DESCRIPTOR statement \[page 947\]](#)

[FIXCHAR type must have a length \[page 947\]](#)

[Host variable '%1' has been redefined \[page 948\]](#)

[Host variable '%1' has two different definitions \[page 948\]](#)

[Host variable '%1' is in use more than once with different indicators \[page 948\]](#)

[Host variable '%1' is unknown \[page 949\]](#)

[Host variables not supported for this cursor \[page 949\]](#)

[Host variables specified twice \(on DECLARE and OPEN\) \[page 950\]](#)

[Inconsistent host variable types for this cursor \[page 950\]](#)

[Inconsistent indicator variables for this cursor \[page 951\]](#)

[Inconsistent number of host variables for this cursor \[page 951\]](#)

[Incorrect Embedded SQL syntax \[page 951\]](#)

[Indicator variable '%1' is unknown \[page 952\]](#)

[Initializer not allowed on VARCHAR host variable \[page 952\]](#)

[Invalid array dimension \[page 953\]](#)

[Invalid descriptor index \[page 953\]](#)

[Invalid field for SET DESCRIPTOR \[page 953\]](#)

[Invalid host variable type on '%1' \[page 954\]](#)

[Invalid integer \[page 954\]](#)

[Invalid type for indicator variable '%1' \[page 955\]](#)

[Invalid type for SQL statement variable \[page 955\]](#)

[Language extension detected in syntax \[page 956\]](#)

[LONG BINARY/LONG VARCHAR size limit is 65535 for UltraLite \[page 956\]](#)

[Macros cannot be redefined \[page 956\]](#)

[Missing ending quote of string literal \[page 957\]](#)

[Must specify a host list or USING clause on %1 \[page 957\]](#)

[Must specify a SQLDA for a DESCRIBE statement \[page 958\]](#)

[No DECLARE SECTION and no INCLUDE SQLCA statement \[page 958\]](#)

[No FETCH or PUT for cursor '%1' \[page 958\]](#)

[No INTO clause for a SELECT statement \[page 959\]](#)

[No OPEN for cursor '%1' \[page 959\]](#)

[Only one-dimensional arrays supported for CHAR type \[page 960\]](#)

[Precision must be specified for DECIMAL type \[page 960\]](#)

[SQL syntax is only supported by UltraLite \[page 961\]](#)

[Statement '%1' not previously prepared \[page 961\]](#)

[Static statement names do not work properly if used by two threads \[page 961\]](#)

[Subscript value %1 too large \[page 962\]](#)

[The INTO clause is not supported in DECLARE CURSOR statements - ignored \[page 962\]](#)

[Token too long \[page 963\]](#)

[Two SQLDAs specified of the same type \(INTO or USING\) \[page 963\]](#)

[Unable to open temporary file \[page 964\]](#)

[Unknown host variable type \[page 964\]](#)

[Unknown SQL function '%1' \[page 964\]](#)

[Unknown statement '%1' \[page 965\]](#)

[Unrecognized SQL syntax \[page 965\]](#)

[Unsupported language extension detected in syntax \[page 965\]](#)

[VARCHAR host variables cannot be pointers \[page 966\]](#)

[VARCHAR type must have a length \[page 966\]](#)

[WCHAR and TCHAR host variable types are not supported \[page 966\]](#)

[Wrong number of arguments for SQL function '%1' \[page 967\]](#)

1.2.2.1 '%1' host variable must be a C string type

Error code

2615

Probable cause

A C string was required in an Embedded SQL statement (for a cursor name, option name, and so on), but the supplied value was not a C string.

Related Information

[Embedded SQL Host Variable Data Types](#)

1.2.2.2 '%1' host variable must be an integer type

Error code

2640

Probable cause

You used a host variable that is not of integer type in a statement where only an integer type host variable is allowed.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.3 '%1' symbol already defined

Error code

2617

Probable cause

You defined a host variable twice.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.4 A FOR UPDATE or FOR READ ONLY clause must be specified on PREPARE (not on DECLARE CURSOR)

Error code

2701

Probable cause

You specified the FOR UPDATE or FOR READ ONLY clause in a DECLARE CURSOR statement. The FOR UPDATE or FOR READ ONLY clause must be specified in the PREPARE statement, not the DECLARE CURSOR statement. For compatibility with previous versions (but with reduced performance), the `sqlpp -m HISTORICAL` option can be used to allow the FOR UPDATE or FOR READ ONLY clause in the DECLARE CURSOR statement.

Related Information

[DECLARE CURSOR Statement \[ESQL\] \[SP\]](#)

[PREPARE Statement \[ESQL\]](#)

[The Embedded SQL Preprocessor](#)

1.2.2.5 Arrays of DECIMAL not supported

Error code

2612

Probable cause

You attempted to declare a host variable as a DECIMAL array. A DECIMAL array is not a supported host variable type.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.6 Arrays of FIXCHAR not supported

Error code

2609

Probable cause

You attempted to declare a host variable as an array of FIXCHAR arrays. This is not a supported host variable type.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.7 Arrays of this type not supported

Error code

2610

Probable cause

You attempted to declare a host variable array of a data type that is not supported.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.8 Arrays of VARCHAR not supported

Error code

2605

Probable cause

You attempted to declare a host variable as a VARCHAR or BINARY array. This data type is not a supported host variable type.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.9 Cannot describe static cursors

Error code

2646

Probable cause

You have described a static cursor. When describing a cursor, the cursor name must be specified in a host variable.

Related Information

[Insensitive Cursors](#)

1.2.2.10 Cannot find include file '%1'

Error code

2619

Probable cause

The specified include file was not found. The preprocessor uses the INCLUDE environment variable to search for include files.

1.2.2.11 char, WCHAR, and TCHAR string parameters cannot be mixed

Error code

2699

Probable cause

You attempted to use parameters for a statement that are not all char strings, WCHAR strings or TCHAR strings. String parameters (other than INTO and USING parameters) for one statement must all be the same type of string. Literal strings are treated as char strings.

1.2.2.12 Combined pointer and arrays not supported for host types

Error code

2602

Probable cause

You used an array of pointers as a host variable. This is not supported.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.13 Cursor '%1' not previously declared

Error code

2627

Probable cause

An Embedded SQL cursor name has been used (for example, in a FETCH, OPEN, or CLOSE statement) without being declared.

Related Information

[DECLARE CURSOR Statement \[ESQL\] \[SP\]](#)

1.2.2.14 Data value must be a host variable

Error code	2652
------------	------

Probable cause

The variable used in the SET DESCRIPTOR statement has not been declared as a host variable.

Related Information

[Embedded SQL Host Variable Usage](#)
[SET DESCRIPTOR Statement \[ESQL\]](#)

1.2.2.15 Error reading temporary file

Error code	2682
------------	------

Probable cause

An error occurred while reading from a temporary file.

1.2.2.16 Error writing output file

Error code	2683
------------	------

Probable cause

An error occurred while writing to the output file.

Related Information

[The Embedded SQL Preprocessor](#)

1.2.2.17 Field used more than once in SET DESCRIPTOR statement

Error code	2651
------------	------

Probable cause

The same keyword has been used more than once inside a SET DESCRIPTOR statement.

Related Information

[SET DESCRIPTOR Statement \[ESQL\]](#)

1.2.2.18 FIXCHAR type must have a length

Error code	2608
------------	------

Probable cause

You have used the DECL_FIXCHAR macro to declare a host variable of type FIXCHAR but have not specified a length.

1.2.2.19 Host variable '%1' has been redefined

Error code

2665

Probable cause

You redefined the same host variable with a different host type. Host variables are global; two host variables with different types cannot have the same name.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.20 Host variable '%1' has two different definitions

Error code

2625

Probable cause

The same host variable name was defined with two different types within the same module. Host variable names are global to a C module.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.21 Host variable '%1' is in use more than once with different indicators

Error code

2696

Probable cause

You have used the same host variable multiple times with different indicator variables in the same statement. This is not supported.

Related Information

[Embedded SQL Indicator Variables](#)
[Embedded SQL Host Variable Usage](#)

1.2.2.22 Host variable '%1' is unknown

Error code

2620

Probable cause

You used a host variable in a statement, but it was not declared in a DECLARE SECTION.

Related Information

[Host Variables in Embedded SQL](#)
[Structure of Embedded SQL Programs](#)

1.2.2.23 Host variables not supported for this cursor

Error code

2629

Probable cause

The DECLARE statement does not support host variables for the specified cursor. If the cursor name is provided through a host variable, then you should use full dynamic SQL and prepare the statement. A prepared statement can have host variables in it.

Related Information

[Host Variables in Embedded SQL
DECLARE Statement](#)

1.2.2.24 Host variables specified twice (on DECLARE and OPEN)

Error code

2630

Probable cause

You specified host variables for a cursor in both the DECLARE and the OPEN statements. In the static case, specify the host variables in the DECLARE statement. In the dynamic case, specify them in the OPEN statement.

Related Information

[DECLARE Statement](#)
[OPEN Statement \[ESQL\] \[SP\]](#)

1.2.2.25 Inconsistent host variable types for this cursor

Error code

2691

Probable cause

You have used a host variable with a different type or length than the type or length previously used with the cursor. Host variable types must be consistent for the cursor.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.26 Inconsistent indicator variables for this cursor

Error code

2692

Probable cause

You have used an indicator variable when one was not previously used with the cursor, or you have not used an indicator variable when one was previously used with the cursor. Indicator variable usage must be consistent for the cursor.

Related Information

[Embedded SQL Indicator Variables](#)

1.2.2.27 Inconsistent number of host variables for this cursor

Error code

2690

Probable cause

You used a different number of host variables than the number previously used with the cursor. The number of host variables must be consistent for the cursor.

1.2.2.28 Incorrect Embedded SQL syntax

Error code

2636

Probable cause

An Embedded SQL specific statement (such as OPEN, DECLARE, or FETCH) has a syntax error.

Related Information

[SQL Statement Execution in Applications](#)

1.2.2.29 Indicator variable '%1' is unknown

Error code

2621

Probable cause

You used an indicator variable in a statement that was not declared in a DECLARE SECTION.

Related Information

[Embedded SQL Indicator Variables
Declaration Section \[ESQL\]](#)

1.2.2.30 Initializer not allowed on VARCHAR host variable

Error code

2607

Probable cause

You cannot specify a C variable initializer for a host variable of type VARCHAR or BINARY. You must initialize this variable in regular C executable code.

Related Information

[Embedded SQL Host Variable Data Types](#)

1.2.2.31 Invalid array dimension

Error code

2648

Probable cause

The array dimension of the variable is negative.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.32 Invalid descriptor index

Error code

2649

Probable cause

You have allocated fewer than one variables with the ALLOCATE DESCRIPTOR statement.

Related Information

[ALLOCATE DESCRIPTOR Statement \[ESQL\]](#)

1.2.2.33 Invalid field for SET DESCRIPTOR

Error code

2650

Probable cause

An invalid or unknown keyword is present in a SET DESCRIPTOR statement. The supported keywords are TYPE, PRECISION, SCALE, LENGTH, INDICATOR, and DATA.

Related Information

[SET DESCRIPTOR Statement \[ESQL\]](#)

1.2.2.34 Invalid host variable type on '%1'

Error code

2623

Probable cause

You have used a host variable that is not a string type where the preprocessor was expecting a host variable of a string type.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.35 Invalid integer

Error code

2614

Probable cause

An integer was required in an Embedded SQL statement (for a fetch offset, or a host variable array index, and so on) and the preprocessor was unable to convert the supplied value into an integer.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.36 Invalid type for indicator variable '%1'

Error code

2622

Probable cause

Indicator variables must be of type `a_sql_len`. You used a variable of an unsupported type as an indicator variable.

Related Information

[Embedded SQL Indicator Variables](#)

1.2.2.37 Invalid type for SQL statement variable

Error code

2618

Probable cause

A host variable used as a statement identifier should be of type `a_sql_statement_number`. You attempted to use a host variable of an unsupported type as a statement identifier.

Related Information

[Embedded SQL Host Variable Usage](#)

1.2.2.38 Language extension detected in syntax

Error code

2667

Probable cause

You have used a SQL Anywhere feature that is not supported by the current flagging level (set using the -w option).

Related Information

[The Embedded SQL Preprocessor](#)

1.2.2.39 LONG BINARY/LONG VARCHAR size limit is 65535 for UltraLite

Error code

2697

Probable cause

When using DECL_LONGBINARY or DECL_LONGVARCHAR with UltraLite, the maximum size for the array is 64 KB.

Related Information

[Data Types](#)

1.2.2.40 Macros cannot be redefined

Error code

2647

Probable cause

A preprocessor macro has been defined twice, possibly in a header file.

Related Information

[Database Tools Programming](#)

1.2.2.41 Missing ending quote of string literal

Error code

2637

Probable cause

You specified a string literal in an Embedded SQL statement that is missing an ending quote before the end of line or end of file.

Related Information

[The Embedded SQL Preprocessor](#)

1.2.2.42 Must specify a host list or USING clause on %1

Error code

2631

Probable cause

The specified statement requires host variables to be specified either in a host variable list or from a SQLDA.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.43 Must specify a SQLDA for a DESCRIBE statement

Error code

2641

Probable cause

You have a DESCRIBE statement that does not specify a SQLDA. A SQLDA is required.

Related Information

[DESCRIBE Statement \[ESQL\]](#)

1.2.2.44 No DECLARE SECTION and no INCLUDE SQLCA statement

Error code

2680

Probable cause

The EXEC SQL INCLUDE SQLCA statement is missing from the source file.

Related Information

[INCLUDE Statement \[ESQL\]](#)

1.2.2.45 No FETCH or PUT for cursor '%1'

Error code

2695

Probable cause

A cursor is declared and opened but is not used.

Related Information

[FETCH Statement \[ESQL\] \[SP\]](#)

1.2.2.46 No INTO clause for a SELECT statement

Error code

2633

Probable cause

You specified an embedded static SELECT statement without specifying an INTO clause for the results.

Related Information

[SELECT Statement](#)

1.2.2.47 No OPEN for cursor '%1'

Error code

2694

Probable cause

A cursor is declared, and possibly used, but is never opened.

Related Information

[Cursor Principles](#)

1.2.2.48 Only one-dimensional arrays supported for CHAR type

Error code

2603

Probable cause

You attempted to declare a host variable as an array of character arrays. This is not a supported host variable type.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.49 Precision must be specified for DECIMAL type

Error code

2611

Probable cause

You must specify the precision when declaring a packed decimal host variable using the DECL_DECIMAL macro. The scale is optional.

Related Information

[SQLDA sqlLen Field Values After a DESCRIBE](#)
[Embedded SQL Data Types](#)

1.2.2.50 SQL syntax is only supported by UltraLite

Error code

2700

Probable cause

You attempted to use a statement that is only supported by UltraLite when you are not generating code for UltraLite.

Related Information

[Embedded SQL](#)

1.2.2.51 Statement '%1' not previously prepared

Error code

2626

Probable cause

An Embedded SQL statement name has been used in a statement (such as EXECUTE or DROP) without being prepared.

Related Information

[Prepared Statements](#)
[PREPARE Statement \[ESQL\]](#)

1.2.2.52 Static statement names do not work properly if used by two threads

Error code

2664

Probable cause

You have used a static statement name and preprocessed with the -r reentrancy option. Static statement names generate static variables that are filled in by the database. If two threads use the same statement, contention arises over the variable. Use a local host variable as the statement identifier instead of a static name.

Related Information

[Static SQL Statements](#)
[The Embedded SQL Preprocessor](#)

1.2.2.53 Subscript value %1 too large

Error code

2601

Probable cause

You attempted to index a host variable that has a value too large for the array.

Related Information

[Wide Fetches Using Embedded SQL](#)

1.2.2.54 The INTO clause is not supported in DECLARE CURSOR statements - ignored

Error code

2660

Probable cause

You used an INTO clause in a DECLARE cursor statement. The INTO clause is ignored.

Related Information

[DECLARE CURSOR Statement \[ESQL\] \[SP\]](#)

1.2.2.55 Token too long

Error code

2639

Probable cause

The SQL preprocessor has a maximum token length of 2 KB. Any token longer than 2 KB produces this error. For constant strings in Embedded SQL commands, use string concatenation to make a longer string.

Related Information

[The Embedded SQL Preprocessor](#)

1.2.2.56 Two SQLDAs specified of the same type (INTO or USING)

Error code

2642

Probable cause

You have specified two INTO DESCRIPTOR or two USING DESCRIPTOR clauses for this statement.

Related Information

[PREPARE Statement \[ESQL\]](#)

[GET DATA Statement \[ESQL\]](#)

[OPEN Statement \[ESQL\] \[SP\]](#)

[UPDATE \(Positioned\) Statement \[ESQL\] \[SP\]](#)

[EXPLAIN Statement \[ESQL\]](#)

1.2.2.57 Unable to open temporary file

Error code	2681
------------	------

Probable cause

An error occurred while attempting to open a temporary file.

1.2.2.58 Unknown host variable type

Error code	2613
------------	------

Probable cause

You declared a host variable of a type that is unknown to the SQL preprocessor.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.59 Unknown SQL function '%1'

Error code	2662
------------	------

Probable cause

You have used a SQL function that is unknown to the preprocessor and may cause an error when the statement is sent to the database server.

1.2.2.60 Unknown statement '%1'

Error code

2628

Probable cause

You attempted to drop an Embedded SQL statement that does not exist.

1.2.2.61 Unrecognized SQL syntax

Error code

2661

Probable cause

You have used a SQL statement that may cause a syntax error when the statement is sent to the database server.

1.2.2.62 Unsupported language extension detected in syntax

Error code

2666

Probable cause

You have used a SQL Anywhere feature that is not supported by the current flagging level (set by using the sqlpp -e option).

Related Information

[The Embedded SQL Preprocessor](#)

1.2.2.63 VARCHAR host variables cannot be pointers

Error code

2606

Probable cause

You have attempted to declare a host variable as a pointer to a VARCHAR or BINARY type. This type is not a supported host variable type.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.64 VARCHAR type must have a length

Error code

2604

Probable cause

You have attempted to declare a VARCHAR or BINARY host variable using the DECL_VARCHAR or DECL_BINARY macro but have not specified a size for the array.

Related Information

[Host Variables in Embedded SQL](#)

1.2.2.65 WCHAR and TCHAR host variable types are not supported

Error code

2698

Probable cause

You have attempted to declare a host variable as a WCHAR or TCHAR string. These types are only supported by UltraLite on Windows platforms.

1.2.2.66 Wrong number of arguments for SQL function '%1'

Error code

2663

Probable cause

You have used a SQL function with the wrong number of parameters. Specifying the wrong number of parameters can cause an error when the statement is sent to the database server.

1.3 MobiLink Server Error Messages

Each MobiLink server error has a numeric error code: error codes are always negative, warning codes are always positive, and zero means no error or warning.

Many of the error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.

In this section:

[MobiLink Server Error Messages Sorted by Error Code \[page 968\]](#)

[MobiLink Server Error Messages Listed by Message Text \[page 982\]](#)

Related Information

[MobiLink Server Warning Messages \[page 1137\]](#)

[MobiLink Communication Error Messages \[page 1184\]](#)

1.3.1 MobiLink Server Error Messages Sorted by Error Code

Error code	Message text
0	No error [page 1043]
-10001	Protocol error: '%1' [page 1048]
-10002	Consolidated database server or ODBC error: '%1' [page 1014]
-10003	Memory allocation failed, attempted to allocate '%1' bytes [page 1041]
-10004	Protocol version mismatch -- expecting '%1' but received '%2' [page 1049]
-10013	Version '%1' not found in the ml_script_version table. Cannot synchronize [page 1134]
-10016	Cannot convert '%1' to Unicode [page 1010]
-10018	Error fetching connection script '%1' [page 1021]
-10019	Error fetching table script '%1'.%2 [page 1021]
-10020	Unable to flush scripts [page 1106]
-10021	Unable to retry the current transaction after deadlock in the consolidated database. The retry limit has been reached [page 1124]
-10024	Unrecognized domain id '%1' [page 1132]
-10028	Unable to connect to the consolidated database. Aborting the synchronization [page 1099]
-10029	Attempt to set non-null column to null [page 1007]
-10030	A network read failed. Unable to read data from the remote client [page 1001]
-10031	An error occurred when trying to store progress information in the consolidated database [page 1002]
-10032	Upload failed with client error '%1' [page 1133]
-10035	Download failed with client error '%1' [page 1020]
-10038	A downloaded value for table '%1' (column #%2) was either too big or invalid for the remote schema type [page 998]
-10041	INTERNAL ERROR: occurred while retrieving a BLOB -- read [page 1030]
-10047	Expecting '%1' parameters in script, but only found '%2': '%3' [page 1026]
-10048	Expecting at least '%1' parameters in script, but only found '%2': '%3' [page 1026]
-10050	Expecting '%1' columns in cursor, but found '%2' [page 1025]
-10052	The '%1' script returned '%2' [page 1059]

Error code	Message text
-10054	Unable to insert user name '%1' into the ml_user table [page 1111]
-10055	Unable to authenticate user '%1' [page 1096]
-10056	User name '%1' not found in the ml_user table [page 1134]
-10057	Invalid password for user '%1' [page 1034]
-10058	Unable to open '%1' [page 1118]
-10060	Memory allocation failed [page 1041]
-10061	An error occurred while uploading an insert row into table '%1'. The inserted column values are as follows: [page 1003]
-10062	An error occurred while uploading a deleted row into table '%1'. The deleted column values are as follows: [page 1002]
-10063	An error occurred while uploading an updated row into table '%1'. The updated column values are as follows: [page 1003]
-10064	Unable to ROLLBACK transaction: '%1' [page 1125]
-10065	Unable to COMMIT transaction: '%1' -- Attempting to ROLLBACK [page 1098]
-10066	Unable to initialize ODBC [page 1110]
-10067	Unable to allocate a connection [page 1094]
-10071	Unable to fetch from table '%1' using '%2' [page 1104]
-10072	Unable to insert into table '%1' using '%2' [page 1110]
-10073	Unable to delete from table '%1' using '%2' [page 1102]
-10074	Unable to update table '%1' using '%2' [page 1130]
-10075	Required ODBC function '%1' is not supported by the driver [page 1051]
-10076	The synchronization server was unable to calculate the timestamp precision on the consolidated database using the ml_scripts_modified table. Timestamp precision related warnings will not be generated [page 1081]
-10081	The synchronization server DLL or shared object version does not match the data layer DLL or shared object version [page 1079]
-10083	Unable to delete user name '%1' from the ml_user_table [page 1103]
-10084	LANG: '%1' - Failed to attach thread [page 1039]
-10085	LANG: '%1' - Failed to allocate database connection [page 1039]
-10086	Cannot load DLL or shared object: '%1' for Script Language: '%2' [page 1011]
-10087	Version mismatch with DLL or shared object: '%1' Expected version: '%2' got version: '%3' [page 1135]

Error code	Message text
-10088	Unable to load entry points from DLL: '%1' [page 1114]
-10091	This connection will be abandoned due to previous errors [page 1088]
-10094	Expecting '%1' authentication parameter(s) from client, but received '%2' for script '%3' [page 1025]
-10099	Unable to load UNLIB collation '%1': '%2' [page 1116]
-10100	The synchronization server system table '%1' is missing or a table column is missing [page 1080]
-10101	Table '%1' has no entry in the ml_table table [page 1058]
-10105	Bad stream specification: '%1' [page 1008]
-10107	Unable to load DLL or shared object: '%1' [page 1113]
-10108	Unable to load DLL or shared object '%1' for stream '%2': '%3' [page 1113]
-10110	Unable to initialize communications stream '%1': '%2' [page 1109]
-10112	Unable to create the background thread [page 1102]
-10117	Stream Error: '%1' [page 1056]
-10118	Caught Java exception with type: '%1'. Exception message: '%2' [page 1011]
-10119	Unable to dump exception information. Received exception while processing exception [page 1103]
-10120	%1 is an unknown subclass of ScriptExecutionException [page 993]
-10121	Unable to load the Java VM due to a version error [page 1114]
-10122	Unable to load the Java VM due to a memory error [page 1114]
-10123	Unable to load the Java VM due to an unknown error [page 1115]
-10124	The following non-daemon threads were destroyed: '%1' [page 1064]
-10125	Unable to parse class and method name from script: '%1' [page 1119]
-10126	Error while attaching thread to Java VM [page 1023]
-10127	Failed to load necessary Java class: '%1' from classpath: '%2' [page 1028]
-10128	Failed to load necessary method: '%1' for Java class: '%2' [page 1028]
-10130	Not enough arguments to execute script: '%1.%2'. '%3' arguments are needed but only '%4' are provided [page 1045]

Error code	Message text
-10133	%1 [page 992]
-10136	Invalid line found in the JVM config file: '%1'. All lines must begin with either '#' or '-' [page 1032]
-10137	Invalid line found in the JVM config file: '%1'. Line is too long [page 1033]
-10138	There are no entries in the JVM config file: '%1' [page 1087]
-10139	The options '%1' and '%2' must not be used together [page 1067]
-10140	The option '%1' needs a path [page 1067]
-10142	Unable to find the JAR file: '%1' in install directory or class-path [page 1106]
-10143	Unable to find shared components directory. JRE location is not specified in options. JRE location is unknown [page 1105]
-10144	Shared install directory is incorrect: '%1' [page 1055]
-10145	Unable to access the JRE at: '%1' [page 1093]
-10146	Too many options sent to Java VM [page 1091]
-10147	There are too many entries in the JVM config file: '%1' [page 1088]
-10148	Java exception [page 1038]
-10149	Exception thrown in initializer of class: '%1'. Error description: '%2'. Stack trace: '%3' [page 1024]
-10150	Linkage error while loading class: '%1' Error description: '%2' [page 1040]
-10151	No public methods found in script class: '%1' [page 1043]
-10153	No suitable constructor found in class: '%1' [page 1044]
-10154	Exception thrown in constructor of class: '%1'. Error description: '%2'. Stack trace: '%3' [page 1023]
-10155	System exception thrown in constructor of class: '%1'. Error description: '%2' [page 1057]
-10156	Internal error: '%1' [page 1030]
-10157	Could not call method: '%1' with arguments of type '%2' [page 1015]
-10158	Exception thrown in method: '%1'. Error description: '%2'. Stack trace: '%3' [page 1024]
-10159	Unable to create new database connection [page 1101]
-10160	Unable to attach JDBC connection [page 1095]
-10161	No valid constructor was found for class '%1' [page 1044]
-10162	Option '%1' was previously defined on the synchronization server command line with value '%2' [page 1047]

Error code	Message text
-10163	Option '%1' is invalid or was not specified correctly on synchronization server command line [page 1047]
-10164	Unable to load .NET Framework CLR Version '%1' [page 1112]
-10165	Unable to load .NET CLR Host DLL [page 1112]
-10166	Unable to find file '%1' [page 1105]
-10167	.NET CLR Host encountered unexpected error [page 995]
-10168	Unable to attach thread to .NET runtime [page 1096]
-10169	Unable to detach worker from VM [page 1103]
-10170	Unable to allocate memory needed for script execution [page 1095]
-10171	Assembly '%1' was compiled against version '%2' of '%3'. Please recompile against version '%4' [page 1004]
-10172	Assembly '%1' does not contain '%2' [page 1004]
-10174	The .NET scripting VM requires version '%1' of the synchronization server ODBC Bridge DLL, but was supplied version '%2' instead [page 1060]
-10175	The .NET scripting VM requires version '%1' of the synchronization server Script DLL, but was supplied version '%2' instead [page 1060]
-10176	.NET Domain Configuration File is corrupt [page 995]
-10177	The name '%1' is not a valid name for a .NET start class [page 1066]
-10178	Domain '%1' was not specified in Domain configuration file [page 1020]
-10179	No Assembly in domain '%1' contains type '%2' [page 1042]
-10180	Unable to shutdown .NET scripting VM [page 1127]
-10181	Unable to shutdown .NET scripting VM. '%1' workers still attached [page 1128]
-10182	Invalid format used for script '%1' [page 1032]
-10183	Only one domain can be used per script version. Domain '%1' was in use when script '%2' attempted to use domain '%3' [page 1045]
-10186	Script '%1' reported a synchronization error [page 1055]
-10187	Failed to load .NET start class '%1' [page 1027]
-10188	Script '%1' reported a server error [page 1054]
-10189	Script '%1' encountered an error [page 1053]
-10190	Script '%1' reported a fatal error [page 1054]
-10191	Unable to locate .NET Domain Configuration File '%1' [page 1116]

Error code	Message text
-10192	Could not create domain '%1' [page 1015]
-10193	Unable to load Assembly '%1' into domain '%2' [page 1112]
-10194	Attempt to prepare SQL statement '%1' after MLDBCommand.Close() was called [page 1007]
-10195	Attempt to prepare null SQL statement. Set value of MLDBCommand.CommandText before calling MLDBCommand.Prepare() [page 1006]
-10196	Attempt to execute null SQL statement. Set value of MLDBCommand.CommandText before calling a MLDBCommand.Execute method [page 1005]
-10197	Attempt to execute SQL statement '%1' after MLDBCommand.Close() was called [page 1006]
-10198	The prepared SQL statement '%1' requires '%2' parameters, but parameter '%3' was not supplied [page 1069]
-10199	Attempt to execute a SQL statement with bound parameters before MLDBCommand.Prepare() was called [page 1005]
-10200	The prepared SQL statement '%1' requires '%2' parameters, but '%3' parameters were supplied [page 1068]
-10201	Binding of parameter '%1' requires value to be of type '%2', but a '%3' was supplied [page 1009]
-10202	Transactions on this connection cannot be committed or rolled back [page 1091]
-10203	Attempt to use a connection with an invalid handle [page 1007]
-10204	Script '%1' is a member of '%2', but only '%3' classes are permitted per script version [page 1053]
-10205	Failure executing script '%1' [page 1028]
-10206	'%1' [page 994]
-10207	Unrecognized event name: '%1' [page 1133]
-10209	Unable to load the Java VM shared library. Make sure that the shared library path is set correctly and that LD_PRELOAD is set correctly and supported by your version of the dynamic loader [page 1115]
-10211	A downloaded value for table '%1' (column #%2) contains character data that cannot be converted [page 997]
-10212	Unable to open temporary file '%1' [page 1118]
-10213	Unable to convert the string '%1' to a numeric value [page 1100]
-10214	Invalid return value (%2) from the '%1' script. Using the default action code (%3) [page 1037]
-10215	Invalid parameter '%1' [page 1034]

Error code	Message text
-10216	A downloaded value for table '%1' (column #%2) was an invalid unique identifier string [page 998]
-10220	Only one of the upload_fetch and upload_fetch_column_conflict scripts may be defined for table '%1' [page 1046]
-10221	Unable to allocate memory for the DownloadData instance [page 1094]
-10222	Unable to allocate memory for the UploadData instance [page 1095]
-10223	The handle_UploadData event script must be void or return null [page 1064]
-10224	Column-level conflict detection is not available for table '%1', because it contains BLOBs [page 1012]
-10225	User exception: '%1' [page 1029]
-10226	Invalid named parameter (too short or long) for script '%1' [page 1033]
-10227	Unknown system parameter '%1' for script '%2' [page 1132]
-10228	Invalid system parameter '%1' for script '%2' [page 1038]
-10229	System parameter '%1' has been set to NULL [page 1057]
-10230	Parameter '%1' has been set to NULL [page 1048]
-10231	The script '%1' cannot process row data [page 1073]
-10232	Column names must be set in the ml_column table or uploaded from the remote client to use named row parameters [page 1012]
-10233	Table '%1' does not have a column named '%2' [page 1058]
-10234	The script '%1' cannot process pre-image row data [page 1072]
-10235	The script '%1' contains an invalid character in a named parameter [page 1073]
-10236	The script '%1' contains invalid syntax for using named parameters [page 1075]
-10237	The script '%1' references the in out parameter '%2' more than one time [page 1076]
-10239	The script '%1' contains an invalid parameter reference: '%2' [page 1074]
-10240	The script '%1' contains an invalid user parameter: '%2' [page 1074]
-10241	The script '%1' references table '%2' column '%3', but there are only '%4' columns [page 1076]
-10242	The script '%1' references authentication parameter '%2' but there are only '%3' [page 1075]

Error code	Message text
-10243	The script '%1' references unknown authentication parameter '%2' [page 1077]
-10244	The synchronization server has encountered an error and the synchronization has been aborted [page 1079]
-10245	The upload table '%1' (column #%2) has the data type '%3', but your ODBC driver doesn't support '%4' [page 1085]
-10246	Unable to retry the current transaction after conflict-update with snapshot isolation in the consolidated database. The retry limit has been reached [page 1123]
-10247	Unable to set transaction isolation level to snapshot [page 1126]
-10249	Could not find file transfer root directory: '%1' [page 1016]
-10250	Could not transfer requested file. The transfer root was not set [page 1018]
-10251	Could not find requested file '%1' in the download root directory or the '%2' sub-directory [page 1017]
-10252	Could not open file for transfer: '%1' [page 1017]
-10253	Could not read file for transfer: '%1' [page 1018]
-10254	Could not add script version: '%1' [page 1014]
-10255	Unable to start the restartable synchronization [page 1128]
-10258	Unable to create an I/O completion port (system error '%1') [page 1100]
-10259	Network address '%1' is not local [page 1042]
-10260	Unable to create listener socket (system error '%1') [page 1101]
-10261	Unable to bind listener socket to port (system error '%1') [page 1096]
-10262	Unable to listen on port (system error '%1') [page 1111]
-10263	Could not associate socket with completion port (system error '%1') [page 1015]
-10264	Unable to create connection socket (system error '%1') [page 1101]
-10265	Unable to start accepting connections (system error '%1') [page 1128]
-10266	Unable to perform a hard close on a socket '%1' [page 1120]
-10267	Unable to post socket deletion request to completion queue (system error '%1') [page 1121]
-10268	Unable to perform a hard close on a listener socket [page 1119]
-10269	Unable to post listener deletion request to completion queue (system error '%1') [page 1120]

Error code	Message text
-10270	Unable to wait on completion port (system error '%1') [page 1131]
-10271	Unable to close socket (system error '%1') [page 1097]
-10272	Unable to create unix pipe for socket selector notification (system error '%1') [page 1102]
-10273	Unable to reuse address (system error '%1') [page 1124]
-10274	Unable to poll sockets (system error '%1') [page 1120]
-10275	Unable to notify (system error '%1') [page 1117]
-10276	Unable to accept an incoming connection (system error '%1') [page 1093]
-10277	Error in reading from notification pipe (system error '%1') [page 1022]
-10278	Error on notification pipe [page 1023]
-10279	Connection was dropped due to lack of network activity [page 1013]
-10280	The number of columns in client table '%1' does not agree with the number defined in ml_column [page 1066]
-10281	In table '%1', the column named '%2' in the ml_column table has an index greater than the number of remote columns [page 1030]
-10282	Unable to create a shared memory file [page 1100]
-10283	Unable to resolve host name '%1' (error: '%2') [page 1123]
-10286	Unable to get the DTC transaction manager -- system error: '%1' [page 1107]
-10287	Unable to initialize a distributed transaction -- system error: '%1' [page 1109]
-10288	Unable to enlist the database in the Distributed Transaction Coordinator [page 1104]
-10289	Unable to commit the distributed transaction (event: '%1') -- system error: '%2' [page 1097]
-10290	Unable to abort the distributed transaction (event: '%1') -- system error: '%2' [page 1092]
-10291	A corrupt or invalid subscription list was received from the client [page 996]
-10292	Unable to accept new connections on network listener port [page 1093]
-10295	The synchronization server and client implementation IDs mismatch [page 1078]
-10296	Unable to support MLSD [page 1130]
-10297	Unable to send SQL Passthrough script due to an unknown script flag: '%1' [page 1125]

Error code	Message text
-10306	The character set (%1) used by the remote client cannot be mapped by the synchronization server [page 1061]
-10307	The character set (%1) used by the remote client cannot be mapped by the synchronization server [page 1062]
-10308	Upload data for column '%1' of table '%2' is invalid [page 1133]
-10309	This server is not licensed to connect to a consolidated database of the following type: '%1' [page 1088]
-10312	This server is not licensed to use the direct row API [page 1089]
-10314	This server is not licensed to use dbmlsync [page 1089]
-10316	Unable to open the file '%1' for recording [page 1118]
-10317	Unable to set the thread affinity mask which is required by the recorder [page 1126]
-10318	Unable to record part of the synchronization [page 1122]
-10319	Unable to write to the file [page 1131]
-10320	Could not find file upload root directory: '%1' [page 1016]
-10321	Could not upload the requested file. The upload root directory was not set [page 1019]
-10322	Could not write file for transfer: '%1' [page 1019]
-10323	The file name or subdirectory for a file upload is invalid: '%1' [page 1063]
-10324	Unable to close the recorded protocol file [page 1097]
-10325	The server failed to initialize the recorder [page 1078]
-10327	The '-rrp' option has been used but no local server connect string has been specified. A local server connect string must be specified using the '-lsc' option to use the '-rrp' option [page 1059]
-10329	A downloaded value for table '%1' (column #%2) was not a valid timestamp with time zone [page 1000]
-10330	Spatial library error: '%1' [page 1055]
-10331	A downloaded value for table '%1' (column #%2) contains a null SRID that is not allowed in the remote database [page 996]
-10332	Invalid qualifier found on spatial geometry parameter '%1' [page 1036]
-10333	Invalid qualifier found on spatial geometry parameter '%1' [page 1036]
-10334	You have not specified a request_cursor for notifier '%1' [page 1135]

Error code	Message text
-10335	RTNotifier does not recognize the property named '%1' [page 1052]
-10336	The poll_every property for notifier, '%1', is invalid. The valid format is <num> for number of seconds [page 1068]
-10337	Invalid property name prefix '%1' [page 1035]
-10338	The property set name, '%1', does not contain a correct bracket [page 1069]
-10339	Unable to execute an RTNotifier's request cursor due to previous errors [page 1104]
-10340	A notifier was unable to connect to the consolidated database [page 1001]
-10341	The remote database identified by remote ID '%1' may already be synchronizing: unable to lock that remote ID [page 1072]
-10342	The remote database identified by remote ID '%1' is already synchronizing: the lock for that remote ID has been changed by another synchronization [page 1070]
-10343	The remote database identified by remote ID '%1' is already synchronizing or the database connection is unusable: unable to access the lock for that remote ID [page 1070]
-10344	The remote database identified by remote ID '%1' may already be synchronizing: orphaned UltraLite synchronization detected [page 1071]
-10345	Two or more synchronization server clients are simultaneously uploading the file '%1' [page 1092]
-10346	Two or more MobiLink clients are either simultaneously uploading the file '%1', or opening the temporary file '%2' failed [page 1091]
-10347	Unable to get the user ID for user '%1' [page 1108]
-10348	Unable to get the RID for remote ID '%1' [page 1107]
-10349	Unable to connect to the arbiter server [page 1099]
-10350	Configuration problem detected when connecting to the arbiter server [page 1013]
-10351	Unable to lock the primary synchronization server [page 1117]
-10352	Unable to store the primary server information [page 1129]
-10353	Lost the primary server lock [page 1041]
-10354	<OE>: '%1' [page 994]
-10355	The table '%1' has no '%2' script [page 1082]
-10357	Requires both the -lsc and -ca options specified [page 1051]

Error code	Message text
-10359	A critical component of the synchronization server failed to start correctly [page 996]
-10360	Error in command line near '%1' [page 1022]
-10361	The update_poll_every property is invalid. The valid format is <num> for number of seconds [page 1084]
-10362	No overload matching '%1' was found in class '%2' [page 1043]
-10366	The table '%1' has no '%2' script [page 1082]
-10367	The table '%1' has the upload_fetch script, but no conflict resolution script defined [page 1083]
-10368	Unable to complete the request [page 1098]
-10369	This synchronization server is not licensed to run in High Availability mode [page 1090]
-10370	The upload_fetch or upload_fetch_column_conflict script for table '%1' cannot be defined as an ignored script [page 1085]
-10371	Support for spatial is not available for this CPU [page 1056]
-10372	This synchronization has been aborted by client request [page 1090]
-10373	The upload of file '%1' failed because the file received does not match the expected file [page 1084]
-10374	Aborting request that started during shutdown [page 1002]
-10375	Unable to set value for user parameter '%1' -- value larger than '%2' characters [page 1127]
-10376	Received unexpected HTTP traffic on port '%1' [page 1050]
-10377	Received unexpectedly encrypted traffic on port '%1' [page 1051]
-10378	Received unexpected end-to-end encrypted traffic on port '%1' [page 1050]
-10379	The ODBC connection string specifies a driver that is not compatible with a 64-bit synchronization server [page 1067]
-10380	Unable to process the request, because synchronization requires access to the ORACLE 'gv\$transaction' table [page 1121]
-10381	The synchronization server must be run as a 64-bit application on a 64-bit operating system [page 1080]
-10382	The synchronization server has failed to start [page 1080]
-10383	Only one file transfer request can be processed at a time [page 1046]
-10384	Invalid port '%2' specified for '%1' stream [page 1035]
-10385	Unable to translate the authentication message [page 1130]

Error code	Message text
-10386	The table '%1' has the conflict resolution script(s), but no upload_fetch script defined [page 1083]
-10387	Unable to process a synchronization request at this time [page 1121]
-10388	Unable to process the synchronization request because its sync sequence number '%1' is smaller than or equal to the one '%2' in consolidated database [page 1122]
-10389	Invalid sync key '%1' for remote ID '%2' [page 1037]
-10390	The search using '%1' failed due to one or more invalid values set [page 1077]
-10391	LDAP server '%1' may not accept anonymous binds [page 1039]
-10392	Bind to LDAP server '%1' without a password is not allowed [page 1008]
-10393	The search on LDAP server '%1' completed with no matching results [page 1077]
-10394	The LDAP server '%1' is not properly defined [page 1065]
-10395	TLS ON cannot be used with URL '%1' [page 1090]
-10396	The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2' [page 1061]
-10397	The user authentication policy '%1' contains a NULL primary LDAP server [page 1086]
-10398	Unable to retrieve data from table '%1' [page 1123]
-10399	Failed to authenticate the user '%1' against LDAP server [page 1027]
-10400	Invalid sync sequence ID for remote ID '%1' [page 1037]
-10401	The client aborted the request because of a network protocol version mismatch [page 1062]
-10402	The method matching '%1' found in class '%2' must return void [page 1065]
-10403	The method matching '%1' found in class '%2' must return void [page 1065]
-10405	The table '%1' must have the '%2' script written in SQL [page 1083]
-10406	QAnywhere is no longer supported [page 1049]
-10407	LDAP user authentication is not available on the current platform [page 1040]
-10408	The client is not authorized to download the requested file: '%1' [page 1063]
-10409	The client is not authorized to upload the requested file: '%1' [page 1063]

Error code	Message text
-10410	The client failed to send a complete sequence of commands [page 1062]
-10411	Unable to load '%1' [page 1111]
-10412	%1 [page 993]
-10413	ERP Communication error [page 1021]
-10414	Invalid NW RFC handle [page 1034]
-10415	Other ERP error [page 1048]
-10416	Call returned an exception [page 1009]
-10417	RETURN structure contained an error [page 1052]
-10418	A downloaded value for table '%1' (column #%2) was not a valid timestamp [page 1000]
-10419	A downloaded value for table '%1' (column #%2) was not a valid time [page 999]
-10420	A downloaded value for table '%1' (column #%2) was not a valid date [page 999]
-10421	Call aborted with ABAP message [page 1009]
-10422	Invalid connection parameters [page 1031]
-10423	Column '%1' cannot be null [page 1012]
-10424	Cannot convert '%1' to REAL [page 1010]
-10425	Cannot convert column '%1' to Unicode [page 1010]
-10426	A value for column '%1' was truncated to '%2' [page 1001]
-10427	Table '%1' could not be found [page 1058]
-10428	'%1' is not a valid script language [page 994]
-10429	Invalid -sl switch: '%1' [page 1031]
-10430	The user authentication policy '%1' is not defined in the database [page 1087]
-10431	The user authentication policy '%1' contains an invalid setting '%2' for the ldap_failover_to_std property [page 1086]
-10432	File download failed with client error '%1' [page 1029]
-10433	A downloaded value for table '%1' (column #%2) contains an invalid date part [page 997]
-10434	Unable to initialize SAP Native Component Supportability (NCS) [page 1110]
-10435	Invalid connection string '%1' [page 1031]
-10436	Unable to get an assertion ticket: '%1' [page 1107]
-10438	Unable to validate the synchronization server license [page 1131]

Error code	Message text
-10439	The synchronization server was locked down because its license is expired [page 1081]

1.3.2 MobiLink Server Error Messages Listed by Message Text

In this section:

[%1 \[page 992\]](#)

[%1 \[page 993\]](#)

[%1 is an unknown subclass of ScriptExecutionException \[page 993\]](#)

[<OE>: '%1' \[page 994\]](#)

['%1' \[page 994\]](#)

['%1' is not a valid script language \[page 994\]](#)

[.NET CLR Host encountered unexpected error \[page 995\]](#)

[.NET Domain Configuration File is corrupt \[page 995\]](#)

[A corrupt or invalid subscription list was received from the client \[page 996\]](#)

[A critical component of the synchronization server failed to start correctly \[page 996\]](#)

[A downloaded value for table '%1' \(column #%2\) contains a null SRID that is not allowed in the remote database \[page 996\]](#)

[A downloaded value for table '%1' \(column #%2\) contains an invalid date part \[page 997\]](#)

[A downloaded value for table '%1' \(column #%2\) contains character data that cannot be converted \[page 997\]](#)

[A downloaded value for table '%1' \(column #%2\) was an invalid unique identifier string \[page 998\]](#)

[A downloaded value for table '%1' \(column #%2\) was either too big or invalid for the remote schema type \[page 998\]](#)

[A downloaded value for table '%1' \(column #%2\) was not a valid date \[page 999\]](#)

[A downloaded value for table '%1' \(column #%2\) was not a valid time \[page 999\]](#)

[A downloaded value for table '%1' \(column #%2\) was not a valid timestamp \[page 1000\]](#)

[A downloaded value for table '%1' \(column #%2\) was not a valid timestamp with time zone \[page 1000\]](#)

[A network read failed. Unable to read data from the remote client \[page 1001\]](#)

[A notifier was unable to connect to the consolidated database \[page 1001\]](#)

[A value for column '%1' was truncated to '%2' \[page 1001\]](#)

[Aborting request that started during shutdown \[page 1002\]](#)

[An error occurred when trying to store progress information in the consolidated database \[page 1002\]](#)

[An error occurred while uploading a deleted row into table '%1'. The deleted column values are as follows: \[page 1002\]](#)

An error occurred while uploading an insert row into table '%1'. The inserted column values are as follows: [page 1003]

An error occurred while uploading an updated row into table '%1'. The updated column values are as follows: [page 1003]

Assembly '%1' does not contain '%2' [page 1004]

Assembly '%1' was compiled against version '%2' of '%3'. Please recompile against version '%4' [page 1004]

Attempt to execute a SQL statement with bound parameters before MLDBCommand.Prepare() was called [page 1005]

Attempt to execute null SQL statement. Set value of MLDBCommand.CommandText before calling a MLDBCommand.Execute method [page 1005]

Attempt to execute SQL statement '%1' after MLDBCommand.Close() was called [page 1006]

Attempt to prepare null SQL statement. Set value of MLDBCommand.CommandText before calling MLDBCommand.Prepare() [page 1006]

Attempt to prepare SQL statement '%1' after MLDBCommand.Close() was called [page 1007]

Attempt to set non-null column to null [page 1007]

Attempt to use a connection with an invalid handle [page 1007]

Bad stream specification: '%1' [page 1008]

Bind to LDAP server '%1' without a password is not allowed [page 1008]

Binding of parameter '%1' requires value to be of type '%2', but a '%3' was supplied [page 1009]

Call aborted with ABAP message [page 1009]

Call returned an exception [page 1009]

Cannot convert '%1' to REAL [page 1010]

Cannot convert '%1' to Unicode [page 1010]

Cannot convert column '%1' to Unicode [page 1010]

Cannot load DLL or shared object: '%1' for Script Language: '%2' [page 1011]

Caught Java exception with type: '%1'. Exception message: '%2' [page 1011]

Column '%1' cannot be null [page 1012]

Column names must be set in the ml_column table or uploaded from the remote client to use named row parameters [page 1012]

Column-level conflict detection is not available for table '%1', because it contains BLOBs [page 1012]

Configuration problem detected when connecting to the arbiter server [page 1013]

Connection was dropped due to lack of network activity [page 1013]

Consolidated database server or ODBC error: '%1' [page 1014]

Could not add script version: '%1' [page 1014]

Could not associate socket with completion port (system error '%1') [page 1015]

Could not call method: '%1' with arguments of type '%2' [page 1015]

Could not create domain '%1' [page 1015]

Could not find file transfer root directory: '%1' [page 1016]

Could not find file upload root directory: '%1' [page 1016]

Could not find requested file '%1' in the download root directory or the '%2' sub-directory [page 1017]

Could not open file for transfer: '%1' [page 1017]

Could not read file for transfer: '%1' [page 1018]

Could not transfer requested file. The transfer root was not set [page 1018]

Could not upload the requested file. The upload root directory was not set [page 1019]

Could not write file for transfer: '%1' [page 1019]

Domain '%1' was not specified in Domain configuration file [page 1020]

Download failed with client error '%1' [page 1020]

ERP Communication error [page 1021]

Error fetching connection script '%1' [page 1021]

Error fetching table script '%1'.%2 [page 1021]

Error in command line near '%1' [page 1022]

Error in reading from notification pipe (system error '%1') [page 1022]

Error on notification pipe [page 1023]

Error while attaching thread to Java VM [page 1023]

Exception thrown in constructor of class: '%1'. Error description: '%2'. Stack trace: '%3' [page 1023]

Exception thrown in initializer of class: '%1'. Error description: '%2'. Stack trace: '%3' [page 1024]

Exception thrown in method: '%1'. Error description: '%2'. Stack trace: '%3' [page 1024]

Expecting '%1' authentication parameter(s) from client, but received '%2' for script '%3' [page 1025]

Expecting '%1' columns in cursor, but found '%2' [page 1025]

Expecting '%1' parameters in script, but only found '%2': '%3' [page 1026]

Expecting at least '%1' parameters in script, but only found '%2': '%3' [page 1026]

Failed to authenticate the user '%1' against LDAP server [page 1027]

Failed to load .NET start class '%1' [page 1027]

Failed to load necessary Java class: '%1' from classpath: '%2' [page 1028]

Failed to load necessary method: '%1' for Java class: '%2' [page 1028]

Failure executing script '%1' [page 1028]

User exception: '%1' [page 1029]

File download failed with client error '%1' [page 1029]

In table '%1', the column named '%2' in the ml_column table has an index greater than the number of remote columns [page 1030]

INTERNAL ERROR: occurred while retrieving a BLOB -- read [page 1030]

Internal error: '%1' [page 1030]

Invalid -sl switch: '%1' [page 1031]

Invalid connection parameters [page 1031]

Invalid connection string '%1' [page 1031]

Invalid format used for script '%1' [page 1032]

Invalid line found in the JVM config file: '%1'. All lines must begin with either '#' or '-' [page 1032]

Invalid line found in the JVM config file: '%1'. Line is too long [page 1033]

Invalid named parameter (too short or long) for script '%1' [page 1033]

Invalid NW RFC handle [page 1034]

Invalid parameter '%1' [page 1034]

Invalid password for user '%1' [page 1034]

Invalid port '%2' specified for '%1' stream [page 1035]

Invalid property name prefix '%1' [page 1035]

Invalid qualifier found on spatial geometry parameter '%1' [page 1036]

Invalid qualifier found on spatial geometry parameter '%1' [page 1036]

Invalid return value (%2) from the '%1' script. Using the default action code (%3) [page 1037]

Invalid sync key '%1' for remote ID '%2' [page 1037]

Invalid sync sequence ID for remote ID '%1' [page 1037]

Invalid system parameter '%1' for script '%2' [page 1038]

Java exception [page 1038]

LANG: '%1' - Failed to allocate database connection [page 1039]

LANG: '%1' - Failed to attach thread [page 1039]

LDAP server '%1' may not accept anonymous binds [page 1039]

LDAP user authentication is not available on the current platform [page 1040]

Linkage error while loading class: '%1' Error description: '%2' [page 1040]

Lost the primary server lock [page 1041]

Memory allocation failed [page 1041]

Memory allocation failed, attempted to allocate '%1' bytes [page 1041]

Network address '%1' is not local [page 1042]

No Assembly in domain '%1' contains type '%2' [page 1042]

No error [page 1043]

No overload matching '%1' was found in class '%2' [page 1043]

No public methods found in script class: '%1' [page 1043]

No suitable constructor found in class: '%1' [page 1044]

No valid constructor was found for class '%1' [page 1044]

Not enough arguments to execute script: '%1.%2'. '%3' arguments are needed but only '%4' are provided [page 1045]

Only one domain can be used per script version. Domain '%1' was in use when script '%2' attempted to use domain '%3' [page 1045]

Only one file transfer request can be processed at a time [page 1046]

Only one of the upload_fetch and upload_fetch_column_conflict scripts may be defined for table '%1' [page 1046]

Option '%1' is invalid or was not specified correctly on synchronization server command line [page 1047]

Option '%1' was previously defined on the synchronization server command line with value '%2' [page 1047]

Other ERP error [page 1048]

Parameter '%1' has been set to NULL [page 1048]

Protocol error: '%1' [page 1048]

Protocol version mismatch -- expecting '%1' but received '%2' [page 1049]

QAnywhere is no longer supported [page 1049]

Received unexpected end-to-end encrypted traffic on port '%1' [page 1050]

Received unexpected HTTP traffic on port '%1' [page 1050]

Received unexpectedly encrypted traffic on port '%1' [page 1051]

Required ODBC function '%1' is not supported by the driver [page 1051]

Requires both the -lsc and -ca options specified [page 1051]

RETURN structure contained an error [page 1052]

RTNotifier does not recognize the property named '%1' [page 1052]

Script '%1' encountered an error [page 1053]

Script '%1' is a member of '%2', but only '%3' classes are permitted per script version [page 1053]

Script '%1' reported a fatal error [page 1054]

Script '%1' reported a server error [page 1054]

Script '%1' reported a synchronization error [page 1055]

Shared install directory is incorrect: '%1' [page 1055]

Spatial library error: '%1' [page 1055]

Stream Error: '%1' [page 1056]

Support for spatial is not available for this CPU [page 1056]

System exception thrown in constructor of class: '%1'. Error description: '%2' [page 1057]

System parameter '%1' has been set to NULL [page 1057]

Table '%1' could not be found [page 1058]

Table '%1' does not have a column named '%2' [page 1058]

Table '%1' has no entry in the ml_table table [page 1058]

The '%1' script returned '%2' [page 1059]

The '-rrp' option has been used but no local server connect string has been specified. A local server connect string must be specified using the '-lsc' option to use the '-rrp' option [page 1059]

The .NET scripting VM requires version '%1' of the synchronization server ODBC Bridge DLL, but was supplied version '%2' instead [page 1060]

The .NET scripting VM requires version '%1' of the synchronization server Script DLL, but was supplied version '%2' instead [page 1060]

The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2' [page 1061]

The character set (%1) used by the remote client cannot be mapped by the synchronization server [page 1061]

The character set (%1) used by the remote client cannot be mapped by the synchronization server [page 1062]

The client aborted the request because of a network protocol version mismatch [page 1062]

The client failed to send a complete sequence of commands [page 1062]

The client is not authorized to download the requested file: '%1' [page 1063]

The client is not authorized to upload the requested file: '%1' [page 1063]

The file name or subdirectory for a file upload is invalid: '%1' [page 1063]

The following non-daemon threads were destroyed: '%1' [page 1064]

The handle_UploadData event script must be void or return null [page 1064]

The LDAP server '%1' is not properly defined [page 1065]

The method matching '%1' found in class '%2' must return void [page 1065]

The method matching '%1' found in class '%2' must return void [page 1065]

The name '%1' is not a valid name for a .NET start class [page 1066]

The number of columns in client table '%1' does not agree with the number defined in ml_column [page 1066]

The ODBC connection string specifies a driver that is not compatible with a 64-bit synchronization server [page 1067]

The option '%1' needs a path [page 1067]

The options '%1' and '%2' must not be used together [page 1067]

The poll_every property for notifier, '%1', is invalid. The valid format is <num> for number of seconds [page 1068]

The prepared SQL statement '%1' requires '%2' parameters, but '%3' parameters were supplied [page 1068]

The prepared SQL statement '%1' requires '%2' parameters, but parameter '%3' was not supplied [page 1069]

The property set name, '%1', does not contain a correct bracket [page 1069]

The remote database identified by remote ID '%1' is already synchronizing or the database connection is unusable: unable to access the lock for that remote ID [page 1070]

The remote database identified by remote ID '%1' is already synchronizing: the lock for that remote ID has been changed by another synchronization [page 1070]

The remote database identified by remote ID '%1' may already be synchronizing: orphaned UltraLite synchronization detected [page 1071]

The remote database identified by remote ID '%1' may already be synchronizing: unable to lock that remote ID [page 1072]

The script '%1' cannot process pre-image row data [page 1072]

The script '%1' cannot process row data [page 1073]

The script '%1' contains an invalid character in a named parameter [page 1073]

The script '%1' contains an invalid parameter reference: '%2' [page 1074]

The script '%1' contains an invalid user parameter: '%2' [page 1074]

The script '%1' contains invalid syntax for using named parameters [page 1075]

The script '%1' references authentication parameter '%2' but there are only '%3' [page 1075]

The script '%1' references table '%2' column '%3', but there are only '%4' columns [page 1076]

The script '%1' references the in out parameter '%2' more than one time [page 1076]

The script '%1' references unknown authentication parameter '%2' [page 1077]

The search on LDAP server '%1' completed with no matching results [page 1077]

The search using '%1' failed due to one or more invalid values set [page 1077]

The server failed to initialize the recorder [page 1078]

The synchronization server and client implementation IDs mismatch [page 1078]

The synchronization server DLL or shared object version does not match the data layer DLL or shared object version [page 1079]

The synchronization server has encountered an error and the synchronization has been aborted [page 1079]

The synchronization server has failed to start [page 1080]

The synchronization server must be run as a 64-bit application on a 64-bit operating system [page 1080]

The synchronization server system table '%1' is missing or a table column is missing [page 1080]

The synchronization server was locked down because its license is expired [page 1081]

The synchronization server was unable to calculate the timestamp precision on the consolidated database using the ml_scripts_modified table. Timestamp precision related warnings will not be generated [page 1081]

The table '%1' has no '%2' script [page 1082]

The table '%1' has no '%2' script [page 1082]

The table '%1' has the conflict resolution script(s), but no upload_fetch script defined [page 1083]

The table '%1' has the upload_fetch script, but no conflict resolution script defined [page 1083]

The table '%1' must have the '%2' script written in SQL [page 1083]

The update_poll_every property is invalid. The valid format is <num> for number of seconds [page 1084]

The upload of file '%1' failed because the file received does not match the expected file [page 1084]

The upload table '%1' (column #%2) has the data type '%3', but your ODBC driver doesn't support '%4' [page 1085]

The upload_fetch or upload_fetch_column_conflict script for table '%1' cannot be defined as an ignored script [page 1085]

The user authentication policy '%1' contains a NULL primary LDAP server [page 1086]

The user authentication policy '%1' contains an invalid setting '%2' for the ldap_failover_to_std property [page 1086]

The user authentication policy '%1' is not defined in the database [page 1087]

There are no entries in the JVM config file: '%1' [page 1087]

There are too many entries in the JVM config file: '%1' [page 1088]

This connection will be abandoned due to previous errors [page 1088]

This server is not licensed to connect to a consolidated database of the following type: '%1' [page 1088]

This server is not licensed to use dbmsync [page 1089]

This server is not licensed to use the direct row API [page 1089]

This synchronization has been aborted by client request [page 1090]

This synchronization server is not licensed to run in High Availability mode [page 1090]

TLS ON cannot be used with URL '%1' [page 1090]

Too many options sent to Java VM [page 1091]

Transactions on this connection cannot be committed or rolled back [page 1091]

Two or more MobiLink clients are either simultaneously uploading the file '%1', or opening the temporary file '%2' failed [page 1091]

Two or more synchronization server clients are simultaneously uploading the file '%1' [page 1092]

Unable to abort the distributed transaction (event: '%1') -- system error: '%2' [page 1092]

Unable to accept an incoming connection (system error '%1') [page 1093]

Unable to accept new connections on network listener port [page 1093]

Unable to access the JRE at: '%1' [page 1093]

Unable to allocate a connection [page 1094]

Unable to allocate memory for the DownloadData instance [page 1094]

Unable to allocate memory for the UploadData instance [page 1095]

Unable to allocate memory needed for script execution [page 1095]

Unable to attach JDBC connection [page 1095]

Unable to attach thread to .NET runtime [page 1096]

Unable to authenticate user '%1' [page 1096]

Unable to bind listener socket to port (system error '%1') [page 1096]

Unable to close socket (system error '%1') [page 1097]

Unable to close the recorded protocol file [page 1097]

Unable to commit the distributed transaction (event: '%1') -- system error: '%2' [page 1097]

Unable to COMMIT transaction: '%1' -- Attempting to ROLLBACK [page 1098]

Unable to complete the request [page 1098]

Unable to connect to the arbiter server [page 1099]

Unable to connect to the consolidated database. Aborting the synchronization [page 1099]

Unable to convert the string '%1' to a numeric value [page 1100]

Unable to create a shared memory file [page 1100]

Unable to create an I/O completion port (system error '%1') [page 1100]

Unable to create connection socket (system error '%1') [page 1101]

Unable to create listener socket (system error '%1') [page 1101]

Unable to create new database connection [page 1101]

Unable to create the background thread [page 1102]

Unable to create unix pipe for socket selector notification (system error '%1') [page 1102]

Unable to delete from table '%1' using '%2' [page 1102]

Unable to delete user name '%1' from the ml_user_table [page 1103]

Unable to detach worker from VM [page 1103]

Unable to dump exception information. Received exception while processing exception [page 1103]

Unable to enlist the database in the Distributed Transaction Coordinator [page 1104]

Unable to execute an RTNotifier's request cursor due to previous errors [page 1104]

Unable to fetch from table '%1' using '%2' [page 1104]

Unable to find file '%1' [page 1105]

Unable to find shared components directory. JRE location is not specified in options. JRE location is unknown [page 1105]

Unable to find the JAR file: '%1' in install directory or classpath [page 1106]

Unable to flush scripts [page 1106]

Unable to get an assertion ticket: '%1' [page 1107]

Unable to get the DTC transaction manager -- system error: '%1' [page 1107]

Unable to get the RID for remote ID '%1' [page 1107]

Unable to get the user ID for user '%1' [page 1108]

Unable to initialize a distributed transaction -- system error: '%1' [page 1109]

Unable to initialize communications stream '%1': '%2' [page 1109]

Unable to initialize ODBC [page 1110]

Unable to initialize SAP Native Component Supportability (NCS) [page 1110]

Unable to insert into table '%1' using '%2' [page 1110]

Unable to insert user name '%1' into the ml_user table [page 1111]

Unable to listen on port (system error '%1') [page 1111]

Unable to load '%1' [page 1111]

Unable to load .NET CLR Host DLL [page 1112]

Unable to load .NET Framework CLR Version '%1' [page 1112]

Unable to load Assembly '%1' into domain '%2' [page 1112]

Unable to load DLL or shared object '%1' for stream '%2': '%3' [page 1113]

Unable to load DLL or shared object: '%1' [page 1113]

Unable to load entry points from DLL: '%1' [page 1114]

Unable to load the Java VM due to a memory error [page 1114]

Unable to load the Java VM due to a version error [page 1114]

Unable to load the Java VM due to an unknown error [page 1115]

Unable to load the Java VM shared library. Make sure that the shared library path is set correctly and that LD_PRELOAD is set correctly and supported by your version of the dynamic loader [page 1115]

Unable to load UNILIB collation '%1': '%2' [page 1116]

Unable to locate .NET Domain Configuration File '%1' [page 1116]

Unable to lock the primary synchronization server [page 1117]

Unable to notify (system error '%1') [page 1117]

Unable to open '%1' [page 1118]

Unable to open temporary file '%1' [page 1118]

Unable to open the file '%1' for recording [page 1118]

Unable to parse class and method name from script: '%1' [page 1119]

Unable to perform a hard close on a listener socket [page 1119]

Unable to perform a hard close on a socket '%1' [page 1120]

Unable to poll sockets (system error '%1') [page 1120]

Unable to post listener deletion request to completion queue (system error '%1') [page 1120]

Unable to post socket deletion request to completion queue (system error '%1') [page 1121]

Unable to process a synchronization request at this time [page 1121]

Unable to process the request, because synchronization requires access to the ORACLE 'gv\$transaction' table [page 1121]

Unable to process the synchronization request because its sync sequence number '%1' is smaller than or equal to the one '%2' in consolidated database [page 1122]

Unable to record part of the synchronization [page 1122]

Unable to resolve host name '%1' (error: '%2') [page 1123]

Unable to retrieve data from table '%1' [page 1123]

Unable to retry the current transaction after conflict-update with snapshot isolation in the consolidated database. The retry limit has been reached [page 1123]

Unable to retry the current transaction after deadlock in the consolidated database. The retry limit has been reached [page 1124]

Unable to reuse address (system error '%1') [page 1124]

Unable to ROLLBACK transaction: '%1' [page 1125]

Unable to send SQL Passthrough script due to an unknown script flag: '%1' [page 1125]

Unable to set the thread affinity mask which is required by the recorder [page 1126]

Unable to set transaction isolation level to snapshot [page 1126]

Unable to set value for user parameter '%1' -- value larger than '%2' characters [page 1127]

Unable to shutdown .NET scripting VM [page 1127]

Unable to shutdown .NET scripting VM. '%1' workers still attached [page 1128]

Unable to start accepting connections (system error '%1') [page 1128]

Unable to start the restartable synchronization [page 1128]

Unable to store the primary server information [page 1129]

Unable to support MLSD [page 1130]

Unable to translate the authentication message [page 1130]

Unable to update table '%1' using '%2' [page 1130]

Unable to validate the synchronization server license [page 1131]

Unable to wait on completion port (system error '%1') [page 1131]

Unable to write to the file [page 1131]

Unknown system parameter '%1' for script '%2' [page 1132]

Unrecognized domain id '%1' [page 1132]

Unrecognized event name: '%1' [page 1133]

Upload data for column '%1' of table '%2' is invalid [page 1133]

Upload failed with client error '%1' [page 1133]

User name '%1' not found in the ml_user table [page 1134]

Version '%1' not found in the ml_script_version table. Cannot synchronize [page 1134]

Version mismatch with DLL or shared object: '%1' Expected version: '%2' got version: '%3' [page 1135]

You have not specified a request_cursor for notifier '%1' [page 1135]

The synchronization server has failed a memory allocation and will probably soon crash [page 1136]

Unable to shared object: '%1' from library path '%2' [page 1136]

1.3.2.1 %1

Error code	-10133
Parameter 1	Message string.

Probable cause

A generic error for Java synchronization logic. The details are in the message.

Related Information

[Setting up Java Synchronization Logic](#)

1.3.2.2 %1

Error code	-10412
Parameter 1	Message string.

Probable cause

Messages sent to the console by the Java Virtual Machine are redirected to the synchronization server output log.

1.3.2.3 %1 is an unknown subclass of ScriptExecutionException

Error code	-10120
Parameter 1	Class name.

Probable cause

The given class name is an unknown subclass of ScriptExecutionException. Expected subclass names include 'SynchronizationException' and 'ServerException'.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.4 <OE>: '%1'

Error code	-10354
Parameter 1	The error.

Probable cause

The integrated outbound enabler had an error.

Related Information

[-x mlsrv17 Option](#)

1.3.2.5 '%1'

Error code	-10206
Parameter 1	An error message.

Probable cause

Generic error message generated by the .Net CLR or by a method invoked during synchronization.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[-sl dnet mlsrv17 Option](#)

1.3.2.6 '%1' is not a valid script language

Error code	-10428
------------	--------

Parameter 1

The language from the script_language column of the ml_script table

Probable cause

A script has been defined with an invalid language. This can happen if the ml_script table has been modified directly or you called ml_add_lang_table_script_chk or ml_add_lang_connection_script_chk. Instead, add scripts only with ml_add_table_script, ml_add_connection_script, ml_add_java_table_script, ml_add_java_connection_script, ml_add_dnet_table_script, or ml_add_dnet_connection_script

1.3.2.7 .NET CLR Host encountered unexpected error

Error code

-10167

Probable cause

The synchronization server received an error while performing a routine .NET call. Please examine your .NET installation.

Related Information

[MobiLink Server Deployment](#)
[-sl dnet mlsrv17 Option](#)

1.3.2.8 .NET Domain Configuration File is corrupt

Error code

-10176

Probable cause

Examine the contents of the .NET configuration file for errors.

Related Information

[.NET Assembly Loading](#)

[MobiLink Server .NET API Reference](#)

1.3.2.9 A corrupt or invalid subscription list was received from the client

Error code	-10291
------------	--------

Probable cause

The synchronization server has received corrupt data from the client. Please contact technical support.

1.3.2.10 A critical component of the synchronization server failed to start correctly

Error code	-10359
------------	--------

Probable cause

Look for other errors during startup that may have caused a problem. If there were no other errors, this is an internal error. Please contact technical support.

1.3.2.11 A downloaded value for table '%1' (column #%2) contains a null SRID that is not allowed in the remote database

Error code	-10331
------------	--------

Parameter 1	Table name.
-------------	-------------

Parameter 2	Column index.
-------------	---------------

Probable cause

Both the SQL Anywhere and UltraLite remote databases do not accept spatial data with a null SRID. Please always specify a valid SRID, when spatial data was entered in the consolidated database.

Related Information

[Spatial Reference Systems \(SRS\) and Spatial Reference Identifiers \(SRID\)](#)
[Spatial Data Types](#)

1.3.2.12 A downloaded value for table '%1' (column #%2) contains an invalid date part

Error code	-10433
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The column in the consolidated database for the given table contains an invalid date part that should be in the range of 0001 and 9999. Please make sure the date part can fit into that in the remote database.

1.3.2.13 A downloaded value for table '%1' (column #%2) contains character data that cannot be converted

Error code	-10211
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

Character data originating from the consolidated database needs to be converted to the client character set before being sent to the client. However the synchronization server was not able to convert the data.

Related Information

[Character Set Conversion During Synchronization](#)

1.3.2.14 A downloaded value for table '%1' (column #%2) was an invalid unique identifier string

Error code	-10216
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The synchronization server cannot convert the string to a unique identifier. Please use a CHAR or VARCHAR data type in the non-SQL Anywhere consolidated database to map UNIQUEIDENTIFIER in the remote database and make sure the string in the consolidated database is a valid unique identifier.

Related Information

[MobiLink Data Mappings Between Remote and Consolidated Databases](#)

1.3.2.15 A downloaded value for table '%1' (column #%2) was either too big or invalid for the remote schema type

Error code	-10038
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The column width for the given table may not be defined consistently in the consolidated and remote databases. Please check the table definition.

Related Information

[ALTER TABLE Statement](#)

[ALTER TABLE Statement \[UltraLite\]](#)

1.3.2.16 A downloaded value for table '%1' (column #%2) was not a valid date

Error code	-10420
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The column in the consolidated database for the given table contains an invalid date. Please make sure this column is formatted as 'yyyymmdd'.

1.3.2.17 A downloaded value for table '%1' (column #%2) was not a valid time

Error code	-10419
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The column in the consolidated database for the given table contains an invalid time. Please make sure this column is formatted as 'hhnnss'.

1.3.2.18 A downloaded value for table '%1' (column #%2) was not a valid timestamp

Error code	-10418
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The column in the consolidated database for the given table contains an invalid timestamp. Please make sure this column is formatted as 'yyyymmdd hhnss.sssss'.

1.3.2.19 A downloaded value for table '%1' (column #%2) was not a valid timestamp with time zone

Error code	-10329
Parameter 1	Table name.
Parameter 2	Column index.

Probable cause

The column in the consolidated database for the given table contains invalid a timestamp with time zone. Please make sure this column contains valid timestamps with time zone and the data is formatted as 'yyyy-mm-dd hh:nn:ss.Sssss [+|-]hh:mm', if it is defined as VARCHAR or CHAR in the table definition.

Related Information

[MobiLink Data Mappings Between Remote and Consolidated Databases](#)

1.3.2.20 A network read failed. Unable to read data from the remote client

Error code	-10030
------------	--------

Probable cause

The synchronization server was unable to complete a network read. Please check the network.

1.3.2.21 A notifier was unable to connect to the consolidated database

Error code	-10340
------------	--------

Probable cause

A notifier was unable to connect to the consolidated database.

Related Information

[Notifiers](#)

[Notifier Events and Properties Configuration](#)

1.3.2.22 A value for column '%1' was truncated to '%2'

Error code	-10426
Parameter 1	The column name of the value being truncated
Parameter 2	The partial value that could be fetched

Probable cause

A value in the SAP system was too large to be downloaded.

1.3.2.23 Aborting request that started during shutdown

Error code	-10374
------------	--------

Probable cause

The synchronization server aborted a request that started after it received a shutdown request.

1.3.2.24 An error occurred when trying to store progress information in the consolidated database

Error code	-10031
------------	--------

Probable cause

The synchronization server is unable to save the synchronization status into the consolidated database. Please make sure that the database server is running and the network is okay.

Related Information

[SQL Anywhere Database Server Executable \(dbsrv17, dbeng17\)](#)

1.3.2.25 An error occurred while uploading a deleted row into table '%1'. The deleted column values are as follows:

Error code	-10062
Parameter 1	The script name.

Probable cause

A failure occurred when the synchronization server was uploading a deleted row into the given table in the consolidated database.

Related Information

[download_delete_cursor Scripts](#)

1.3.2.26 An error occurred while uploading an insert row into table '%1'. The inserted column values are as follows:

Error code	-10061
Parameter 1	The script name.

Probable cause

A failure occurred when the synchronization server was uploading an inserted row into the given table in the consolidated database.

Related Information

[download_cursor Scripts](#)

1.3.2.27 An error occurred while uploading an updated row into table '%1'. The updated column values are as follows:

Error code	-10063
Parameter 1	The script name.

Probable cause

A failure occurred when the synchronization server was uploading an updated row into the given table in the consolidated database.

Related Information

[download_cursor Scripts](#)

1.3.2.28 Assembly '%1' does not contain '%2'

Error code	-10172
Parameter 1	The assembly name.
Parameter 2	The missing method name.

Probable cause

If the method is implemented but the name is wrong, change it. If the method is missing, you must add it to the assembly.

Related Information

[.NET Assembly Loading](#)
[Implementing Synchronization Scripts in .NET](#)

1.3.2.29 Assembly '%1' was compiled against version '%2' of '%3'. Please recompile against version '%4'

Error code	-10171
Parameter 1	The assembly name.
Parameter 2	The assembly version.
Parameter 3	The DLL name.
Parameter 4	The desired assembly version.

Probable cause

Please fix the version mismatch displayed and run again.

Related Information

[.NET Assembly Loading](#)
[Implementing Synchronization Scripts in .NET](#)

1.3.2.30 Attempt to execute a SQL statement with bound parameters before `MLDBCommand.Prepare()` was called

Error code	-10199
------------	--------

Probable cause

An attempt was made to bind a parameter to a statement that was not prepared. Please prepare the statement before binding parameters.

Related Information

[Prepared Statements](#)
[Executing Prepared Statements](#)
[Executing Statements with Bound Parameters](#)

1.3.2.31 Attempt to execute null SQL statement. Set value of `MLDBCommand.CommandText` before calling a `MLDBCommand.Execute` method

Error code	-10196
------------	--------

Probable cause

A null SQL statement is being executed. Make sure the SQL statement is non-null before executing it.

1.3.2.32 Attempt to execute SQL statement '%1' after MLDBCommand.Close() was called

Error code	-10197
Parameter 1	The SQL statement.

Probable cause

The SQL statement is being executed when the database connection is closed. Make sure the database connection is open before executing a statement.

1.3.2.33 Attempt to prepare null SQL statement. Set value of MLDBCommand.CommandText before calling MLDBCommand.Prepare()

Error code	-10195
------------	--------

Probable cause

A null SQL statement is being prepared. Make sure the SQL statement is non-null before preparing it.

Related Information

[Prepared Statements](#)

1.3.2.34 Attempt to prepare SQL statement '%1' after MLDBCommand.Close() was called

Error code	-10194
Parameter 1	The SQL statement.

Probable cause

The SQL statement is being prepared when the database connection is closed. Make sure the database connection is open before preparing a statement.

Related Information

[Prepared Statements](#)

1.3.2.35 Attempt to set non-null column to null

Error code	-10029
------------	--------

Probable cause

The synchronization server attempted to download a null into a non-nullable column.

Related Information

[Conflict Resolution](#)

1.3.2.36 Attempt to use a connection with an invalid handle

Error code	-10203
------------	--------

Probable cause

Make sure the connection handle is valid before using it.

1.3.2.37 Bad stream specification: '%1'

Error code	-10105
Parameter 1	The stream name.

Probable cause

The stream name was specified incorrectly. Please consult the documentation for the -x and -xo switches.

Related Information

[-x mlsrv17 Option](#)

1.3.2.38 Bind to LDAP server '%1' without a password is not allowed

Error code	-10392
Parameter 1	The LDAP server name or search URL specifying the search.

Probable cause

An LDAPUA search or validate failed returning LDAP_UNWILLING_TO_PERFORM due to invalid settings for the target LDAP server. Check access account values for the named LDAP server or search URL.

1.3.2.39 Binding of parameter '%1' requires value to be of type '%2', but a '%3' was supplied

Error code	-10201
Parameter 1	The parameter number.
Parameter 2	The expected type.
Parameter 3	The supplied type.

Probable cause

The supplied parameter type is incorrect. Change the parameter to the proper type.

Related Information

[Prepared Statements](#)

1.3.2.40 Call aborted with ABAP message

Error code	-10421
------------	--------

Probable cause

Details of the message will follow.

1.3.2.41 Call returned an exception

Error code	-10416
------------	--------

Probable cause

details follow

1.3.2.42 Cannot convert '%1' to REAL

Error code	-10424
Parameter 1	The value to convert

Probable cause

The value store in the SAP system is too large to be downloaded into a REAL column.

1.3.2.43 Cannot convert '%1' to Unicode

Error code	-10016
Parameter 1	String to be converted.

Probable cause

The synchronization server was not able to convert the given string to Unicode using Unilib.

Related Information

[Character Set Conversion During Synchronization](#)

1.3.2.44 Cannot convert column '%1' to Unicode

Error code	-10425
Parameter 1	The column name of the value being converted

Probable cause

There was an error converting the column's value.

1.3.2.45 Cannot load DLL or shared object: '%1' for Script Language: '%2'

Error code	-10086
Parameter 1	The DLL or shared object name.
Parameter 2	The script language name.

Probable cause

Please make sure that the script language is valid. Currently the script languages supported by the synchronization server are SQL (sql), Java (java) and .NET (dnet).

Related Information

[Options for Writing Server-side Synchronization Logic](#)

1.3.2.46 Caught Java exception with type: '%1'. Exception message: '%2'

Error code	-10118
Parameter 1	Class name.
Parameter 2	Error message.

Probable cause

A Java script caused the given exception. Either correct the condition that caused the exception, or change the code to avoid the exception.

Related Information

[Java Synchronization Logic](#)
[MobiLink Server .NET API Reference](#)

1.3.2.47 Column '%1' cannot be null

Error code	-10423
Parameter 1	The column with a null value

Probable cause

Null values may not be uploaded.

1.3.2.48 Column names must be set in the ml_column table or uploaded from the remote client to use named row parameters

Error code	-10232
------------	--------

Probable cause

The remote column names to be used in scripts must be defined in the ml_column table or uploaded from remote databases (via the SendColumnNames option) for the named parameter feature to be used.

Related Information

[Named Script Parameters](#)
[ml_add_column System Procedure \(Deprecated\)](#)

1.3.2.49 Column-level conflict detection is not available for table '%1', because it contains BLOBs

Error code	-10224
Parameter 1	Table name.

Probable cause

The column-level conflict detection is not available for tables that contain BLOBs. Please use the row-level conflict detection script, `upload_fetch` for any tables that contain BLOBs.

Related Information

[Conflict Detection and Resolution](#)
[upload_fetch Scripts](#)
[upload_fetch Table Event](#)

1.3.2.50 Configuration problem detected when connecting to the arbiter server

Error code	-10350
------------	--------

Probable cause

The synchronization server detected a configuration problem when it tried to connect to the arbiter server. Please check your installation.

Related Information

[MobiLink Arbiter Server Utility for Windows \(mlarbiter\)](#)
[MobiLink Arbiter Server Utility for UNIX/Linux \(mlarbiter.sh\)](#)
[-ca mlsrv17 Option](#)
[-lsc mlsrv17 Option](#)

1.3.2.51 Connection was dropped due to lack of network activity

Error code	-10279
------------	--------

Probable cause

The synchronization server has dropped this connection because of lack of activity. The remote may have lost network connectivity.

1.3.2.52 Consolidated database server or ODBC error: '%1'

Error code	-10002
Parameter 1	The actual error message sent by the database server or ODBC driver.

Probable cause

This may be a SQL error such as a syntax error.

1.3.2.53 Could not add script version: '%1'

Error code	-10254
Parameter 1	Version string.

Probable cause

The server was unable to automatically add the given script version. This error usually happens when connecting the Monitor, which uses the script version called for_ML_Monitor_only. Check database permissions or add the script version directly.

i Note

Adobe will stop updating and distributing the Flash Player at the end of 2020. Because the SQL Anywhere Monitor is based on Flash, you cannot use it once Flash support ends. In many cases, tasks that were previously performed in the Monitor can be performed in the SQL Anywhere Cockpit. See [SQL Anywhere Monitor Non-GUI User Guide](#).

Related Information

[Script Versions](#)

1.3.2.54 Could not associate socket with completion port (system error '%1')

Error code	-10263
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.55 Could not call method: '%1' with arguments of type '%2'

Error code	-10157
Parameter 1	The method name.
Parameter 2	The type name.

Probable cause

Please refer to the synchronization server documentation to determine what argument types the synchronization server expects for this call.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.56 Could not create domain '%1'

Error code	-10192
------------	--------

Parameter 1	The domain name.
-------------	------------------

Probable cause

The .NET CLR refused to create the indicated domain. Fix the domain configuration and try again.

Related Information

[.NET Assembly Loading](#)
[-sl dnet mlsrv17 Option](#)

1.3.2.57 Could not find file transfer root directory: '%1'

Error code	-10249
Parameter 1	Root path specified by user.

Probable cause

The server could not find the specified path. Please check that the path given is correct.

Related Information

[-ftr mlsrv17 Option](#)
[-ftru mlsrv17 Option](#)
[MobiLink File Transfer Utility \(mlfiletransfer\)](#)

1.3.2.58 Could not find file upload root directory: '%1'

Error code	-10320
Parameter 1	Root path specified by user.

Probable cause

The server could not find the specified path. Please check that the path given is correct.

Related Information

[-ftru mlsrv17 Option](#)

[-ftr mlsrv17 Option](#)

1.3.2.59 Could not find requested file '%1' in the download root directory or the '%2' sub-directory

Error code	-10251
Parameter 1	File name.
Parameter 2	Subdirectory of the root download directory.

Probable cause

The server could not find the file requested for transfer.

Related Information

[MobiLink File Transfer Utility \(mfiletransfer\)](#)

1.3.2.60 Could not open file for transfer: '%1'

Error code	-10252
Parameter 1	File name.

Probable cause

The server found the file requested for transfer but was unable to open the file. Check file permissions.

Related Information

[MobiLink File Transfer Utility \(mlfiletransfer\)](#)

1.3.2.61 Could not read file for transfer: '%1'

Error code	-10253
Parameter 1	File name.

Probable cause

The server found the file requested for transfer but was unable to read the file. Check file permissions.

Related Information

[MobiLink File Transfer Utility \(mlfiletransfer\)](#)

1.3.2.62 Could not transfer requested file. The transfer root was not set

Error code	-10250
------------	--------

Probable cause

The server received a client file transfer request but the transfer root directory has not been set on the server.

Related Information

[-ftr mlsrv17 Option](#)

[-ftru mlsrv17 Option](#)

[MobiLink File Transfer Utility \(mlfiletransfer\)](#)

1.3.2.63 Could not upload the requested file. The upload root directory was not set

Error code	-10321
------------	--------

Probable cause

The server received a client file upload request but the root directory for uploads has not been set on the server.

Related Information

[-ftru mlsrv17 Option](#)
[-ftr mlsrv17 Option](#)

1.3.2.64 Could not write file for transfer: '%1'

Error code	-10322
Parameter 1	File name.

Probable cause

The server found is unable to write a file uploaded from a client. Check file permissions.

Related Information

[authenticate_file_transfer Connection Event](#)
[authenticate_file_upload Connection Event](#)

1.3.2.65 Domain '%1' was not specified in Domain configuration file

Error code	-10178
Parameter 1	The domain name.

Probable cause

The event script domain name does not match any of the domains that have been configured.

Related Information

[.NET Assembly Loading](#)
[-sl dnet mlsrv17 Option](#)
[MobiLink Server .NET API Reference](#)

1.3.2.66 Download failed with client error '%1'

Error code	-10035
Parameter 1	An error number sent by the client.

Probable cause

The synchronization server aborts the synchronization when the client indicates there is a problem on the remote site during download.

Related Information

[Failed Downloads](#)

1.3.2.67 ERP Communication error

Error code	-10413
------------	--------

Probable cause

Details follow.

1.3.2.68 Error fetching connection script '%1'

Error code	-10018
Parameter 1	Connection script name.

Probable cause

The synchronization server was not able to refresh connection scripts. Please make sure that the database server is running and the network is okay.

Related Information

[Debug Network Communications Startup Problems](#)
[SQL Anywhere Database Server Executable \(dbsrv17, dbeng17\)](#)
[-x mlsrv17 Option](#)

1.3.2.69 Error fetching table script '%1'.%2

Error code	-10019
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

The synchronization server was not able to refresh table scripts. Please make sure that the database server is running and the network is okay.

Related Information

[Debug Network Communications Startup Problems](#)
[SQL Anywhere Database Server Executable \(dbsrv17, dbeng17\)](#)
[-x mlsrv17 Option](#)

1.3.2.70 Error in command line near '%1'

Error code	-10360
Parameter 1	Command line option.

Probable cause

The command line option is invalid. Please make sure all the synchronization server command line options and settings are valid.

Related Information

[mlsrv17 Syntax](#)

1.3.2.71 Error in reading from notification pipe (system error '%1')

Error code	-10277
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.72 Error on notification pipe

Error code	-10278
------------	--------

Probable cause

Please contact technical support.

1.3.2.73 Error while attaching thread to Java VM

Error code	-10126
------------	--------

Probable cause

This is an internal startup error. Please consult technical support.

1.3.2.74 Exception thrown in constructor of class: '%1'. Error description: '%2'. Stack trace: '%3'

Error code	-10154
Parameter 1	The class name.
Parameter 2	The error text.
Parameter 3	The stack trace.

Probable cause

A user exception was thrown when invoking the constructor of a user class. Please examine the stack trace and fix the error.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.75 Exception thrown in initializer of class: '%1'. Error description: '%2'. Stack trace: '%3'

Error code	-10149
Parameter 1	The class name.
Parameter 2	The error text.
Parameter 3	The stack trace.

Probable cause

The stack initializers in a user supplied class have thrown an exception. Please examine the Stack trace and fix the problem.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.76 Exception thrown in method: '%1'. Error description: '%2'. Stack trace: '%3'

Error code	-10158
Parameter 1	The method name.
Parameter 2	The error text.
Parameter 3	The stack trace.

Probable cause

An error has occurred in user supplied code. Please examine the Exception information and fix the error.

Related Information

[MobiLink Server Error Handling in Java](#)
[MobiLink Server .NET API Reference](#)

1.3.2.77 Expecting '%1' authentication parameter(s) from client, but received '%2' for script '%3'

Error code	-10094
Parameter 1	The number of parameters expected.
Parameter 2	The number of parameters passed up from the client.
Parameter 3	The script that needs the parameters.

Probable cause

The number of authentication parameters received from the client does not match the number expected. The number of client parameters should be two less than the number required by the authenticate_parameters script.

Related Information

[Authentication Parameters](#)

1.3.2.78 Expecting '%1' columns in cursor, but found '%2'

Error code	-10050
Parameter 1	The number of columns expected.
Parameter 2	The number of columns found.

Probable cause

The number of parameters found in the upload or download script does not match the number of columns or the number of primary key columns for the given table. Please check the number of parameters for the given script.

Related Information

[Script Parameters](#)
[Synchronization Events](#)

1.3.2.79 Expecting '%1' parameters in script, but only found '%2': '%3'

Error code	-10047
Parameter 1	The number of parameters expected.
Parameter 2	The number of parameters found.
Parameter 3	The script name.

Probable cause

There are too many parameters found in the given script. Please check the number of parameters for the given script.

Related Information

[Script Parameters](#)
[Synchronization Events](#)

1.3.2.80 Expecting at least '%1' parameters in script, but only found '%2': '%3'

Error code	-10048
Parameter 1	The minimum number of parameters expected.
Parameter 2	The number of parameters found.
Parameter 3	The script name.

Probable cause

There are not enough parameters found in the given script. Please check the number of parameters for the given script.

Related Information

[Script Parameters](#)
[Synchronization Events](#)

1.3.2.81 Failed to authenticate the user '%1' against LDAP server

Error code	-10399
Parameter 1	The user name.

Probable cause

The synchronization server was not able to authenticate the user against the LDAP servers. Please verify the user password and/or the LDAP server configurations for the current user.

1.3.2.82 Failed to load .NET start class '%1'

Error code	-10187
Parameter 1	The class name.

Probable cause

The synchronization server was unable to load the given class on startup.

Related Information

[Synchronization Scripts in Microsoft .NET](#)

1.3.2.83 Failed to load necessary Java class: '%1' from classpath: '%2'

Error code	-10127
Parameter 1	Method name.
Parameter 2	Class name.

Probable cause

This is an internal startup error. Please consult technical support.

1.3.2.84 Failed to load necessary method: '%1' for Java class: '%2'

Error code	-10128
Parameter 1	Method name.
Parameter 2	Class name.

Probable cause

This is an internal startup error. Please consult technical support.

1.3.2.85 Failure executing script '%1'

Error code	-10205
Parameter 1	The script.

Probable cause

The synchronization server was unable to invoke the given script. Check for previous errors in the synchronization server log.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[-sl dnet mlsrv17 Option](#)

1.3.2.86 User exception: '%1'

Error code	-10225
Parameter 1	User's error string

Probable cause

A failure occurred while attempting to execute user supplied code. Examine the server log and fix the user supplied code.

Related Information

[MobiLink Server Log Viewing](#)

1.3.2.87 File download failed with client error '%1'

Error code	-10432
Parameter 1	An error number sent by the client.

Probable cause

If the nonblocking_file_transfer_ack script is defined, it will not be invoked.

1.3.2.88 In table '%1', the column named '%2' in the ml_column table has an index greater than the number of remote columns

Error code	-10281
Parameter 1	Name of table.
Parameter 2	Name of column from the ml_column table.

Probable cause

A synchronization script has an invalid named parameter reference. Check the ml_column table for this script version and table, to make sure the number and order of columns match the number and order coming up from the remote. The most likely cause is either an invalid column named in the named parameter, or invalid entries in the ml_column table before the valid column entry.

Related Information

[ml_add_column System Procedure \(Deprecated\)](#)

1.3.2.89 INTERNAL ERROR: occurred while retrieving a BLOB -- read

Error code	-10041
------------	--------

Probable cause

The synchronization server cannot retrieve the upload data from memory or a temporary file. This is an internal error. Please contact technical support.

1.3.2.90 Internal error: '%1'

Error code	-10156
Parameter 1	The error text.

Probable cause

The synchronization server experienced a Java internal error. Please examine the error information printed and try to fix the problem.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.91 Invalid -sl switch: '%1'

Error code	-10429
Parameter 1	The language specified

Probable cause

The only valid -sl switches are "-sl java" and "-sl dnet".

1.3.2.92 Invalid connection parameters

Error code	-10422
------------	--------

Probable cause

The given connection parameters are invalid. Please supply the valid connection parameters. Please supply valid connection parameters.

1.3.2.93 Invalid connection string '%1'

Error code	-10435
Parameter 1	Connection string.

Probable cause

The supplied connection string is invalid. Please verify the connection parameters.

1.3.2.94 Invalid format used for script '%1'

Error code	-10182
Parameter 1	The script.

Probable cause

The script format is invalid. The proper format is either myDomain:myClass.myMethod or just myClass.myMethod.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[Implementing Synchronization Scripts in .NET](#)
[MobiLink Server .NET API Reference](#)

1.3.2.95 Invalid line found in the JVM config file: '%1'. All lines must begin with either '#' or '-'

Error code	-10136
Parameter 1	Config file name.

Probable cause

The synchronization server was unable to parse the jvm.cfg config file. Please check that the contents of this file are valid.

Related Information

[MobiLink Server .NET API Reference](#)

[-sl java mlsrv17 Option](#)

1.3.2.96 Invalid line found in the JVM config file: '%1'. Line is too long

Error code	-10137
Parameter 1	Config file name.

Probable cause

The synchronization server was unable to parse the jvm.cfg config file. A line exceeded the maximum line length. Please check that the contents of this file are valid.

Related Information

[MobiLink Server .NET API Reference](#)

[-sl java mlsrv17 Option](#)

1.3.2.97 Invalid named parameter (too short or long) for script '%1'

Error code	-10226
Parameter 1	Name of script.

Probable cause

A named parameter was encountered where there was no name or the name length was too long.

Related Information

[Script Parameters](#)

1.3.2.98 Invalid NW RFC handle

Error code	-10414
------------	--------

Probable cause

internal error

1.3.2.99 Invalid parameter '%1'

Error code	-10215
Parameter 1	Name of the invalid parameter.

Probable cause

One or more invalid parameters were detected in the communication protocol. Please check the command line options and make sure all the protocol options valid.

Related Information

[-x mlsrv17 Option](#)
[MobiLink Client Network Protocol Options](#)

1.3.2.100 Invalid password for user '%1'

Error code	-10057
Parameter 1	The user name.

Probable cause

The password sent up from the remote is invalid for the given user. Please note: passwords are case sensitive.

Related Information

[MobiLink Users in a Synchronization System](#)

[MobiLink User Authentication Utility \(mluser\)](#)

1.3.2.101 Invalid port '%2' specified for '%1' stream

Error code	-10384
Parameter 1	Stream name.
Parameter 2	Host port.

Probable cause

The port specified is invalid. It must be a number between 1 and 65535.

1.3.2.102 Invalid property name prefix '%1'

Error code	-10337
Parameter 1	notifier type.

Probable cause

The given property name prefix is invalid.

Related Information

[ml_add_property System Procedure](#)

1.3.2.103 Invalid qualifier found on spatial geometry parameter '%1'

Error code	-10332
Parameter 1	The column number of the parameter.

Probable cause

The parameter must be qualified with :srid or :data.

Related Information

[Synchronization of Spatial Data](#)

1.3.2.104 Invalid qualifier found on spatial geometry parameter '%1'

Error code	-10333
Parameter 1	The column name of the parameter.

Probable cause

The parameter must be qualified with :srid or :data.

Related Information

[Synchronization of Spatial Data](#)

1.3.2.105 Invalid return value (%2) from the '%1' script. Using the default action code (%3)

Error code	-10214
Parameter 1	Name of the script returning the bad value.
Parameter 2	Action value return from script.
Parameter 3	Action value to be used.

Probable cause

The error handler script called returned a value outside of the allowable range. The default value will be used.

Related Information

[Scripts to Handle Errors](#)

1.3.2.106 Invalid sync key '%1' for remote ID '%2'

Error code	-10389
Parameter 1	Sync key.
Parameter 2	Remote ID.

Probable cause

The sync key in the consolidated database for the given remote ID is neither an integer nor a GUID. You can reset it to '0'. Please make sure no instance of the current client is running before resetting its sync key.

1.3.2.107 Invalid sync sequence ID for remote ID '%1'

Error code	-10400
Parameter 1	Remote ID.

Probable cause

The sync sequence ID in the consolidated database does not match the sequence ID sent by the client. Please make sure the remote ID is unique. If you restored the database from a backup, please reset the sync state for the remote ID by executing the ml_reset_sync_state stored procedure.

1.3.2.108 Invalid system parameter '%1' for script '%2'

Error code	-10228
Parameter 1	Name of invalid system parameter.
Parameter 2	Name of script.

Probable cause

The named system parameter cannot be used with the given script.

Related Information

[Script Parameters](#)

1.3.2.109 Java exception

Error code	-10148
------------	--------

Probable cause

Examine the synchronization server log error message adjacent to this error for more information.

Related Information

[MobiLink Server .NET API Reference](#)
[-o mlsrv17 Option](#)

1.3.2.110 LANG: '%1' - Failed to allocate database connection

Error code	-10085
Parameter 1	The name of the script language.

Probable cause

A connection cannot be made to the database server.

Related Information

[MobiLink Server](#)

1.3.2.111 LANG: '%1' - Failed to attach thread

Error code	-10084
Parameter 1	The name of the script language.

Probable cause

A synchronization server thread could not attach itself to the DLL or shared object used to process the given script language. Please make sure that the synchronization server installation contains all of the required DLLs or shared objects.

Related Information

[MobiLink Server](#)

1.3.2.112 LDAP server '%1' may not accept anonymous binds

Error code	-10391
------------	--------

Parameter 1	The LDAP server name or search URL specifying the search.
-------------	---

Probable cause

An LDAPUA search or validate failed returning LDAP_INAPPROPRIATE_AUTH due to invalid settings for the target LDAP server. Check the access account values for the named LDAP server or search URL.

1.3.2.113 LDAP user authentication is not available on the current platform

Error code	-10407
------------	--------

Probable cause

The synchronization server does not support LDAP user authentication on the current platform.

1.3.2.114 Linkage error while loading class: '%1' Error description: '%2'

Error code	-10150
------------	--------

Parameter 1	The class name.
-------------	-----------------

Parameter 2	The error text.
-------------	-----------------

Probable cause

The Java VM was unable to load a class. Please examine the Error description printed and fix the problem.

Related Information

[Setting up Java Synchronization Logic](#)
[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.115 Lost the primary server lock

Error code	-10353
------------	--------

Probable cause

The synchronization server lost its primary server status. Please make sure the arbiter is running.

Related Information

[MobiLink Arbiter Server Utility for Windows \(mlarbiter\)](#)
[MobiLink Arbiter Server Utility for UNIX/Linux \(mlarbiter.sh\)](#)

1.3.2.116 Memory allocation failed

Error code	-10060
------------	--------

Probable cause

Your system is running out of memory. You may need to close some applications or add more memory to your system.

1.3.2.117 Memory allocation failed, attempted to allocate '%1' bytes

Error code	-10003
Parameter 1	The number of bytes it was trying to allocate.

Probable cause

Your system is running out of memory. You may need to close some applications or add more memory to your system.

1.3.2.118 Network address '%1' is not local

Error code	-10259
Parameter 1	Host name.

Probable cause

The network address provided does not resolve to a network adapter on this machine.

Related Information

[-x mlsrv17 Option](#)

1.3.2.119 No Assembly in domain '%1' contains type '%2'

Error code	-10179
Parameter 1	The domain name.
Parameter 2	The type name.

Probable cause

Make sure the type is defined in the given domain.

Related Information

[.NET Assembly Loading](#)
[-sl dnet mlsrv17 Option](#)
[MobiLink Server .NET API Reference](#)

1.3.2.120 No error

Error code	0
------------	---

Probable cause

This code indicates there was no error.

1.3.2.121 No overload matching '%1' was found in class '%2'

Error code	-10362
Parameter 1	The method signature searched for.
Parameter 2	The class.

Probable cause

There was no method matching the supplied parameters.

Related Information

[Java Methods](#)

1.3.2.122 No public methods found in script class: '%1'

Error code	-10151
Parameter 1	The class name.

Probable cause

A script class must have public methods so that the synchronization server can call its methods. Please supply a fixed class.

Related Information

[Java Methods](#)

[MobiLink Server .NET API Reference](#)

1.3.2.123 No suitable constructor found in class: '%1'

Error code	-10153
Parameter 1	The class name.

Probable cause

Please make sure that the user supplied class has a public constructor that the synchronization server can invoke to create an instance.

Related Information

[Constructors](#)

[MobiLink Server .NET API Reference](#)

1.3.2.124 No valid constructor was found for class '%1'

Error code	-10161
Parameter 1	The class name.

Probable cause

The synchronization server was unable to find a valid constructor for the given class.

Related Information

[Implementing Synchronization Scripts in .NET](#)

[MobiLink Server .NET API Reference](#)

1.3.2.125 Not enough arguments to execute script: '%1.%2'. '%3' arguments are needed but only '%4' are provided

Error code	-10130
Parameter 1	Class name.
Parameter 2	Method name.
Parameter 3	Number of parameters expected.
Parameter 4	Number of parameters provided.

Probable cause

Consult the documentation for the event associated with this script.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.126 Only one domain can be used per script version. Domain '%1' was in use when script '%2' attempted to use domain '%3'

Error code	-10183
Parameter 1	The domain name.
Parameter 2	The script.
Parameter 3	The extra domain name.

Probable cause

The script is of the form myDomain:myClass.myMethod, and another script in the same script version used a different domain name. Make sure all scripts for the same script version use the same domain.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[Implementing Synchronization Scripts in .NET](#)
[MobiLink Server .NET API Reference](#)

1.3.2.127 Only one file transfer request can be processed at a time

Error code	-10383
------------	--------

Probable cause

The client has requested concurrent file transfers.

1.3.2.128 Only one of the `upload_fetch` and `upload_fetch_column_conflict` scripts may be defined for table '%1'

Error code	-10220
Parameter 1	Table name.

Probable cause

The synchronization server uses one of these scripts for conflict detection. Please only define one of these two scripts.

Related Information

[upload_fetch Scripts](#)
[upload_fetch Table Event](#)
[upload_fetch_column_conflict Table Event](#)

1.3.2.129 Option '%1' is invalid or was not specified correctly on synchronization server command line

Error code	-10163
Parameter 1	The option name.

Probable cause

The given option is improperly specified.

Related Information

[-sl dnet mlsrv17 Option](#)
[MobiLink Server .NET API Reference](#)

1.3.2.130 Option '%1' was previously defined on the synchronization server command line with value '%2'

Error code	-10162
Parameter 1	The option name.
Parameter 2	The extra option value.

Probable cause

The given option may not be specified more than once.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.131 Other ERP error

Error code	-10415
------------	--------

Probable cause

details follow.

1.3.2.132 Parameter '%1' has been set to NULL

Error code	-10230
Parameter 1	Number of parameter

Probable cause

Parameter may be modified but not set to NULL.

Related Information

[Script Parameters](#)

1.3.2.133 Protocol error: '%1'

Error code	-10001
Parameter 1	The error number.

Probable cause

The synchronization server does not understand the request sent by the client. This could happen if the client is newer than the synchronization server. Please contact technical support

Related Information

[Version Considerations](#)
[SQL Anywhere MobiLink Client Upgrades](#)
[MobiLink Upgrades](#)

1.3.2.134 Protocol version mismatch -- expecting '%1' but received '%2'

Error code	-10004
Parameter 1	The maximum version accepted.
Parameter 2	The version as sent from the client.

Probable cause

The synchronization server is communicating with the client using different protocol versions. If the client sends a version that is not supported by the synchronization server, it will give this error. Please make sure that you are not using a newer client (DBMLSync or an UltraLite application) to talk to an older version of the synchronization server.

Related Information

[Version Considerations](#)
[SQL Anywhere MobiLink Client Upgrades](#)
[MobiLink Upgrades](#)

1.3.2.135 QAnywhere is no longer supported

Error code	-10406
------------	--------

Probable cause

QAnywhere is no longer supported.

1.3.2.136 Received unexpected end-to-end encrypted traffic on port '%1'

Error code	-10378
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received end-to-end encrypted traffic on a port that was not expecting it. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.3.2.137 Received unexpected HTTP traffic on port '%1'

Error code	-10376
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received HTTP traffic on a port that was servicing non-HTTP traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.3.2.138 Received unexpectedly encrypted traffic on port '%1'

Error code	-10377
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received traffic that was likely encrypted on a port that was servicing non-encrypted traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.3.2.139 Required ODBC function '%1' is not supported by the driver

Error code	-10075
Parameter 1	The ODBC function name.

Probable cause

The synchronization server was not able to find the function from the ODBC driver. Please start the synchronization server with the recommended ODBC drivers.

1.3.2.140 Requires both the -lsc and -ca options specified

Error code	-10357
------------	--------

Probable cause

The synchronization server requires both the -lsc and -ca settings in order to enable the primary-secondary server logic required by the Notifier when the synchronization server is running in a server farm.

Related Information

[MobiLink Server in a Server Farm](#)

[-lsc mlsrv17 Option](#)

[-ca mlsrv17 Option](#)

[MobiLink Arbiter Server Utility for Windows \(mlarbiter\)](#)

[MobiLink Arbiter Server Utility for UNIX/Linux \(mlarbiter.sh\)](#)

1.3.2.141 RETURN structure contained an error

Error code	-10417
------------	--------

Probable cause

details follow

1.3.2.142 RTNotifier does not recognize the property named '%1'

Error code	-10335
Parameter 1	property name.

Probable cause

The RTNotifier does not recognize the given property.

Related Information

[Remote Task Notifier \(RTNotifier\)](#)
[ml_add_property System Procedure](#)

1.3.2.143 Script '%1' encountered an error

Error code	-10189
Parameter 1	The script.

Probable cause

When invoked, the script triggered a ScriptExecutionException.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[Implementing Synchronization Scripts in .NET](#)

1.3.2.144 Script '%1' is a member of '%2', but only '%3' classes are permitted per script version

Error code	-10204
Parameter 1	The method name.
Parameter 2	The class name.
Parameter 3	The number of classes permitted.

Probable cause

A script version cannot explicitly reference more than the given number of classes. If you encounter this error, create a wrapper class containing all of the methods used by different events.

Related Information

[Script Versions](#)

[MobiLink Server .NET API Reference](#)

1.3.2.145 Script '%1' reported a fatal error

Error code	-10190
Parameter 1	The script.

Probable cause

When invoked, the script triggered a FatalException.

Related Information

[Synchronization Scripts in Microsoft .NET](#)

1.3.2.146 Script '%1' reported a server error

Error code	-10188
Parameter 1	The script.

Probable cause

When invoked, the script triggered a ServerException.

Related Information

[Synchronization Scripts in Microsoft .NET](#)

[Implementing Synchronization Scripts in .NET](#)

1.3.2.147 Script '%1' reported a synchronization error

Error code	-10186
Parameter 1	The script.

Probable cause

When invoked, the script triggered a SynchronizationException.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[Implementing Synchronization Scripts in .NET](#)

1.3.2.148 Shared install directory is incorrect: '%1'

Error code	-10144
Parameter 1	SQL Anywhere shared directory.

Probable cause

Please fix the shared components environment variable so that it points to the correct location.

Related Information

[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.149 Spatial library error: '%1'

Error code	-10330
------------	--------

Parameter 1	The actual error code or error message generated by the spatial library.
-------------	--

Probable cause

Please look at the actual spatial library error message to find the cause of the error.

1.3.2.150 Stream Error: '%1'

Error code	-10117
Parameter 1	Error message.

Probable cause

A generic stream error. The details of the error are in the message.

1.3.2.151 Support for spatial is not available for this CPU

Error code	-10371
------------	--------

Probable cause

Spatial data support for 32-bit Windows and 32-bit Linux requires a CPU that supports SSE2 instructions.

Related Information

[Spatial Data](#)

1.3.2.152 System exception thrown in constructor of class: '%1'. Error description: '%2'

Error code	-10155
Parameter 1	The class name.
Parameter 2	The error text.

Probable cause

A system exception was thrown when invoking the constructor of a user class. Please examine the stack trace and fix the error.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.153 System parameter '%1' has been set to NULL

Error code	-10229
Parameter 1	Name of system parameter.

Probable cause

System parameters may be modified but not set to NULL.

Related Information

[Script Parameters](#)

1.3.2.154 Table '%1' could not be found

Error code	-10427
Parameter 1	The required table

Probable cause

A required table parameter is missing from the BAPI.

1.3.2.155 Table '%1' does not have a column named '%2'

Error code	-10233
Parameter 1	Name of table.
Parameter 2	Name of column.

Probable cause

The column name referenced in the script does not appear in the list of column names for the table.

Related Information

[Script Parameters](#)

1.3.2.156 Table '%1' has no entry in the ml_table table

Error code	-10101
Parameter 1	Table name.

Probable cause

The tables ml_table, ml_table_script, ml_script contain the scripts for every table that participates in synchronization. The synchronization server will show this warning for all the synchronization tables that have no script or that have no entry in the table ml_table.

Related Information

[Table Scripts](#)

[MobiLink Server System Tables](#)

1.3.2.157 The '%1' script returned '%2'

Error code	-10052
Parameter 1	The user authentication script name.
Parameter 2	The script returning value.

Probable cause

The user authentication script returned a value greater than 3000.

Related Information

[Authentication Process](#)

[Authentication Parameters](#)

1.3.2.158 The '-rrp' option has been used but no local server connect string has been specified. A local server connect string must be specified using the '-lsc' option to use the '-rrp' option

Error code	-10327
------------	--------

Probable cause

The '-rrp' option has been used but no local server connect string has been specified. A local server connect string must be specified using the '-lsc' option to use the '-rrp' option.

Related Information

[-rrp mlsrv17 Option](#)
[MobiLink Replay Utility \(mlreplay\)](#)

1.3.2.159 The .NET scripting VM requires version '%1' of the synchronization server ODBC Bridge DLL, but was supplied version '%2' instead

Error code	-10174
Parameter 1	The required version.
Parameter 2	The supplied version.

Probable cause

This is likely an install problem. Please contact technical support.

1.3.2.160 The .NET scripting VM requires version '%1' of the synchronization server Script DLL, but was supplied version '%2' instead

Error code	-10175
Parameter 1	The required version.
Parameter 2	The supplied version.

Probable cause

This is likely an install problem. Please contact technical support.

1.3.2.161 The bind to URL '%1' failed. The most recently reported LDAP API error is: '%2'

Error code	-10396
Parameter 1	The LDAP URL used with bind().
Parameter 2	The LDAP API error message.

Probable cause

The message is reported from the LDAP API client with context from the LDAP User Authentication methods. An LDAP administrator or SAP customer support may use these low level messages to help the database administrator resolve a problem.

1.3.2.162 The character set (%1) used by the remote client cannot be mapped by the synchronization server

Error code	-10306
Parameter 1	Character set ID.

Probable cause

The character data supplied by the remote cannot be translated into the character set required by the consolidated database.

Related Information

[Character Set Considerations](#)
[Character Set Conversion During Synchronization](#)
[ODBC Driver Character Set Conversion](#)

1.3.2.163 The character set (%1) used by the remote client cannot be mapped by the synchronization server

Error code	-10307
Parameter 1	Character set label.

Probable cause

The character data supplied by the remote cannot be translated into the character set required by the consolidated database.

Related Information

[Character Set Considerations](#)
[Character Set Conversion During Synchronization](#)
[ODBC Driver Character Set Conversion](#)

1.3.2.164 The client aborted the request because of a network protocol version mismatch

Error code	-10401
------------	--------

Probable cause

The client is either too old or too new to communicate with this server. You must upgrade one to proceed.

1.3.2.165 The client failed to send a complete sequence of commands

Error code	-10410
------------	--------

Probable cause

The client did not send its entire set of commands to perform a synchronization. This may be due to the client aborting or a network interruption.

1.3.2.166 The client is not authorized to download the requested file: '%1'

Error code	-10408
Parameter 1	File name.

Probable cause

The `authenticate_file_transfer` script returned a value ≥ 2000 .

1.3.2.167 The client is not authorized to upload the requested file: '%1'

Error code	-10409
Parameter 1	File name.

Probable cause

The `authenticate_file_upload` script returned a value ≥ 2000 .

1.3.2.168 The file name or subdirectory for a file upload is invalid: '%1'

Error code	-10323
Parameter 1	Path name.

Probable cause

File names for file upload must not contain slashes.

Related Information

[MobiLink File Transfer Utility \(mlfiletransfer\)](#)

1.3.2.169 The following non-daemon threads were destroyed: '%1'

Error code	-10124
Parameter 1	The list of thread identifiers.

Probable cause

The given Java threads were forcibly destroyed during shutdown. Use the ShutdownListener interface to destroy threads gracefully during the synchronization server shutdown.

1.3.2.170 The handle_UploadData event script must be void or return null

Error code	-10223
------------	--------

Probable cause

Rewrite this handle_UploadData script so that it has a void return type or returns null.

Related Information

[Direct Row Handling](#)
[handle_UploadData Connection Event](#)

1.3.2.171 The LDAP server '%1' is not properly defined

Error code	-10394
Parameter 1	The LDAP server name.

Probable cause

The LDAP server was not properly defined, because at least one of the parameters, search URL, access account DN, access password, and authentication URL is NULL.

1.3.2.172 The method matching '%1' found in class '%2' must return void

Error code	-10402
Parameter 1	The method signature searched for.
Parameter 2	The class.

Probable cause

Methods executed by the synchronization server are not allowed to return any object.

1.3.2.173 The method matching '%1' found in class '%2' must return void

Error code	-10403
Parameter 1	The method signature searched for.
Parameter 2	The class.

Probable cause

Methods executed by the synchronization server are not allowed to return any object.

1.3.2.174 The name '%1' is not a valid name for a .NET start class

Error code	-10177
Parameter 1	The start class name.

Probable cause

The start class name is not well formed please fix the name and run again.

Related Information

[User-Defined Start Classes in .NET](#)
[MobiLink Server .NET API Reference](#)

1.3.2.175 The number of columns in client table '%1' does not agree with the number defined in ml_column

Error code	-10280
Parameter 1	Name of table.

Probable cause

The number of columns sent for the table from the client is greater than the number as defined in ml_column. Ensure that ml_column is up to date.

Related Information

[ml_add_column System Procedure \(Deprecated\)](#)

1.3.2.176 The ODBC connection string specifies a driver that is not compatible with a 64-bit synchronization server

Error code	-10379
------------	--------

Probable cause

The driver being used is not safe to use for a 64-bit synchronization server. You may need to reconfigure the driver or specify a different one. Please refer to the list of Recommended ODBC Drivers for MobiLink.

1.3.2.177 The option '%1' needs a path

Error code	-10140
Parameter 1	Option name.

Probable cause

The given option must be followed by a path.

Related Information

[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.178 The options '%1' and '%2' must not be used together

Error code	-10139
Parameter 1	Option name.
Parameter 2	Option name.

Probable cause

Consider using one option or the other, or neither, but not both.

Related Information

[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.179 The poll_every property for notifier, '%1', is invalid. The valid format is <num> for number of seconds

Error code	-10336
Parameter 1	notifier name.

Probable cause

The poll_every property for the given notifier is invalid. The valid format is <num> for number of seconds.

1.3.2.180 The prepared SQL statement '%1' requires '%2' parameters, but '%3' parameters were supplied

Error code	-10200
Parameter 1	The SQL statement.
Parameter 2	The expected number of parameters.
Parameter 3	The supplied number of parameters.

Probable cause

The statement was executed with the wrong number of parameters. Please supply the correct number of parameters before executing the statement.

Related Information

[Prepared Statements](#)

[Executing Prepared Statements](#)

[Executing Statements with Bound Parameters](#)

1.3.2.181 The prepared SQL statement '%1' requires '%2' parameters, but parameter '%3' was not supplied

Error code	-10198
Parameter 1	The SQL statement.
Parameter 2	The expected number of parameters.
Parameter 3	The supplied number of parameters.

Probable cause

The statement was executed too few parameters. Please supply the correct number of parameters before executing the statement.

Related Information

[Prepared Statements](#)

[Executing Prepared Statements](#)

[Executing Statements with Bound Parameters](#)

1.3.2.182 The property set name, '%1', does not contain a correct bracket

Error code	-10338
Parameter 1	property set name.

Probable cause

The given property set name does not contain a correct bracket.

Related Information

[ml_add_property System Procedure](#)

1.3.2.183 The remote database identified by remote ID '%1' is already synchronizing or the database connection is unusable: unable to access the lock for that remote ID

Error code	-10343
Parameter 1	Remote ID.

Probable cause

The synchronization server could not access the lock for the remote ID in the consolidated database or the synchronization server system database. The remote ID may have been locked by another synchronization, or the database connection may be unusable. Please check the database connection and try the synchronization later.

Related Information

[Remote IDs](#)

1.3.2.184 The remote database identified by remote ID '%1' is already synchronizing: the lock for that remote ID has been changed by another synchronization

Error code	-10342
Parameter 1	Remote ID.

Probable cause

A concurrent synchronization was detected when the synchronization server checked the lock for the remote ID. This can happen if another synchronization for the same remote database has already locked the remote ID. Please try the synchronization later.

Related Information

[Remote IDs](#)

1.3.2.185 The remote database identified by remote ID '%1' may already be synchronizing: orphaned UltraLite synchronization detected

Error code	-10344
Parameter 1	Remote ID.

Probable cause

An orphaned UltraLite synchronization was detected when the synchronization server checked the lock for the remote ID. If an UltraLite client cancels a synchronization that is queued while waiting for a synchronization server database worker thread, the synchronization has been orphaned. If the orphaned synchronization later obtains a database worker thread when another synchronization has changed the lock for that remote ID, the orphaned synchronization is closed with this error.

Related Information

[Remote IDs](#)

[The Synchronization Process](#)

1.3.2.186 The remote database identified by remote ID '%1' may already be synchronizing: unable to lock that remote ID

Error code	-10341
Parameter 1	Remote ID.

Probable cause

The synchronization server could not lock the remote ID in the consolidated database or the synchronization server system database. The remote ID may have been locked by another synchronization, or the database connection may be unusable. Please try the synchronization later.

Related Information

[Remote IDs](#)

1.3.2.187 The script '%1' cannot process pre-image row data

Error code	-10234
Parameter 1	Name of script.

Probable cause

Only scripts that process pre-image row data may use named parameters that reference pre-image row data.

Related Information

[Script Parameters](#)

1.3.2.188 The script '%1' cannot process row data

Error code	-10231
Parameter 1	Name of script.

Probable cause

Only scripts that process row data may use named parameters that reference row data.

Related Information

[Named Script Parameters](#)

1.3.2.189 The script '%1' contains an invalid character in a named parameter

Error code	-10235
Parameter 1	Name of script.

Probable cause

The rules for naming a SQL Anywhere identifier must be followed.

Related Information

[Script Parameters](#)
[Identifiers](#)

1.3.2.190 The script '%1' contains an invalid parameter reference: '%2'

Error code	-10239
Parameter 1	Name of script.
Parameter 2	Number of parameter.

Probable cause

The script contains a numeric reference to a parameter which is either zero or too large.

Related Information

[Script Parameters](#)

1.3.2.191 The script '%1' contains an invalid user parameter: '%2'

Error code	-10240
Parameter 1	Name of script.
Parameter 2	Number of parameter.

Probable cause

The script contains a numeric reference to a user parameter.

Related Information

[Script Parameters](#)

1.3.2.192 The script '%1' contains invalid syntax for using named parameters

Error code	-10236
Parameter 1	Name of script.

Probable cause

The script does not contain a properly formed named parameter sequence. To reference a script parameter by name, enclose the parameter in curly braces and prefix it with ml, as in {ml parameter}. For example, {ml s.action_code}.

Related Information

[Script Parameters](#)

1.3.2.193 The script '%1' references authentication parameter '%2' but there are only '%3'

Error code	-10242
Parameter 1	Name of script.
Parameter 2	Number of parameter.
Parameter 3	Number of parameters.

Probable cause

The script contains a reference to an authentication parameter which does not exist.

Related Information

[Authentication Parameters](#)

1.3.2.194 The script '%1' references table '%2' column '%3', but there are only '%4' columns

Error code	-10241
Parameter 1	Name of script.
Parameter 2	Name of table.
Parameter 3	Number of parameter.
Parameter 4	Number of table columns.

Probable cause

The script contains a reference to a parameter which is either zero or too large.

Related Information

[Script Parameters](#)

1.3.2.195 The script '%1' references the in out parameter '%2' more than one time

Error code	-10237
Parameter 1	Name of script.
Parameter 2	Name of parameter.

Probable cause

In out parameters may only be passed to a script once.

Related Information

[Script Parameters](#)

1.3.2.196 The script '%1' references unknown authentication parameter '%2'

Error code	-10243
Parameter 1	Name of script.
Parameter 2	Name of parameter.

Probable cause

The script contains a reference to an authentication parameter which does not exist.

Related Information

[Authentication Parameters](#)

1.3.2.197 The search on LDAP server '%1' completed with no matching results

Error code	-10393
Parameter 1	The LDAP server name or search URL specifying the search.

Probable cause

An LDAPUA search or validate failed returning LDAP_NO_RESULTS_RETURNED. This error is expected when the user does not exist in the LDAP server.

1.3.2.198 The search using '%1' failed due to one or more invalid values set

Error code	-10390
Parameter 1	The LDAP server name or search URL specifying the search.

Probable cause

An LDAPUA search or validate failed returning LDAP_INVALID_CREDENTIALS, LDAP_INSUFFICIENT_ACCESS, LDAP_INVALID_DN_SYNTAX, LDAP_NO_SUCH_OBJECT, or LDAP_FILTER_ERROR due to the invalid settings. Check the access account values for the named LDAP server or search URL.

1.3.2.199 The server failed to initialize the recorder

Error code	-10325
------------	--------

Probable cause

The server was unable to close a recorded synchronization file.

Related Information

[MobiLink Replay Utility \(mlreplay\)](#)

[-rp mlsrv17 Option](#)

[-rrp mlsrv17 Option](#)

1.3.2.200 The synchronization server and client implementation IDs mismatch

Error code	-10295
------------	--------

Probable cause

The synchronization server was not able to accept the synchronization request due to the server and client implementation IDs mismatch.

1.3.2.201 The synchronization server DLL or shared object version does not match the data layer DLL or shared object version

Error code

-10081

Probable cause

The synchronization server DLL or shared object that processes the upload and download data is not consistent with the version of the data layer DLL or shared object (ODBC) that is used to interact with the databases. Please check your synchronization server installation.

Related Information

[MobiLink Server Deployment](#)

1.3.2.202 The synchronization server has encountered an error and the synchronization has been aborted

Error code

-10244

Probable cause

An error has occurred in the synchronization server. Please see the synchronization server message log for more details about this error.

Related Information

[-dl mlsrv17 Option](#)

[-o mlsrv17 Option](#)

1.3.2.203 The synchronization server has failed to start

Error code	-10382
------------	--------

Probable cause

The server will not run due to an error occurring during startup.

Related Information

[Troubleshooting MobiLink Server Startup](#)

1.3.2.204 The synchronization server must be run as a 64-bit application on a 64-bit operating system

Error code	-10381
------------	--------

Probable cause

Running the 32-bit version of the synchronization server on a 64-bit operating system is not supported. Please use the 64-bit version.

Related Information

[MobiLink Server](#)

1.3.2.205 The synchronization server system table '%1' is missing or a table column is missing

Error code	-10100
Parameter 1	Table name.

Probable cause

The table or table column cannot be found in the consolidated database. The synchronization server tables may not have been installed or an upgrade may be required.

Related Information

[MobiLink Server System Tables](#)

1.3.2.206 The synchronization server was locked down because its license is expired

Error code	-10439
------------	--------

Probable cause

The synchronization server was locked down, because its license has expired. Please get and install a new license.

1.3.2.207 The synchronization server was unable to calculate the timestamp precision on the consolidated database using the ml_scripts_modified table. Timestamp precision related warnings will not be generated

Error code	-10076
------------	--------

Probable cause

The synchronization server must calculate the maximum timestamp precision of the consolidated database to properly synchronize all time-related values. This error typically comes up when a non-recommended ODBC driver is used. Please start the synchronization server with a recommended ODBC driver.

1.3.2.208 The table '%1' has no '%2' script

Error code	-10355
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

The upload data from the client contains data but no script is available to process it. To ignore this data provide the script written with `--{ml_ignore}`.

Related Information

[Synchronization Scripts](#)
[Script Additions and Deletions](#)
[Ignored Scripts](#)

1.3.2.209 The table '%1' has no '%2' script

Error code	-10366
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

The download data script is missing. To ignore this script, please provide the script written with `--{ml_ignore}`.

Related Information

[Scripts to Download Rows](#)
[Ignored Scripts](#)

1.3.2.210 The table '%1' has the conflict resolution script(s), but no upload_fetch script defined

Error code	-10386
Parameter 1	Table name.

Probable cause

The conflict resolution script(s) is defined for the given table, but there is no upload_fetch script defined. Please either remove the conflict resolution scripts or add an upload_fetch script.

1.3.2.211 The table '%1' has the upload_fetch script, but no conflict resolution script defined

Error code	-10367
Parameter 1	Table name.

Probable cause

The upload_fetch script is defined for the given table, but there is no conflict resolution script defined. Please either remove the upload_fetch script or add at least one conflict resolution script.

Related Information

[upload_fetch Scripts](#)
[Conflict Handling Overview](#)
[upload_fetch Table Event](#)

1.3.2.212 The table '%1' must have the '%2' script written in SQL

Error code	-10405
Parameter 1	Table name.

Parameter 2

Script name.

Probable cause

Table scripts which process row data must be written in SQL. Scripts written in Java or .NET may no longer return SQL.

1.3.2.213 The update_poll_every property is invalid. The valid format is <num> for number of seconds

Error code

-10361

Probable cause

The update_poll_every SIRT global property is invalid. The valid format is <num> for number of seconds. Please ensure that update_poll_every has a valid format in the ml_property table.

Related Information

[Remote Task Notifier \(RTNotifier\)](#)

1.3.2.214 The upload of file '%1' failed because the file received does not match the expected file

Error code

-10373

Parameter 1

Filename.

Probable cause

The file transfer failed because the file received by the synchronization server did not match what was expected. Re-try the file transfer.

Related Information

[MobiLink File Transfer Utility \(mfiletransfer\)](#)

1.3.2.215 The upload table '%1' (column #%2) has the data type '%3', but your ODBC driver doesn't support '%4'

Error code	-10245
Parameter 1	Table name.
Parameter 2	Column index.
Parameter 3	SQL Anywhere data type.
Parameter 4	ODBC data type.

Probable cause

The upload table contains a column with a data type that is not supported by your ODBC driver. Please make sure that the synchronization server is using a recommended ODBC driver.

Related Information

[MobiLink Data Mappings Between Remote and Consolidated Databases](#)

[MobiLink Consolidated Databases](#)

1.3.2.216 The upload_fetch or upload_fetch_column_conflict script for table '%1' cannot be defined as an ignored script

Error code	-10370
Parameter 1	Table name.

Probable cause

The synchronization server requires the `upload_fetch` or `upload_fetch_column_conflict` script defined as a real SQL script or left undefined.

Related Information

[Events During Upload](#)

[upload_fetch Table Event](#)

[upload_fetch_column_conflict Table Event](#)

1.3.2.217 The user authentication policy '%1' contains a NULL primary LDAP server

Error code	-10397
Parameter 1	The user authentication policy name.

Probable cause

The primary LDAP server for a user authentication policy cannot be NULL. If you are not using LDAP server for user authentication, please create the users without specifying any user authentication policies for them, then the synchronization server will use the default script-based logic for user authentication.

1.3.2.218 The user authentication policy '%1' contains an invalid setting '%2' for the `ldap_failover_to_std` property

Error code	-10431
Parameter 1	The user authentication policy name.
Parameter 2	The setting for the <code>ldap_failover_to_std</code> property.

Probable cause

The valid setting for the `ldap_failover_to_std` property in a user authentication policy can be 0, 1, or 2. Please either define the user authentication policy in the database or remove the default user authentication policy name from the synchronization server command line.

1.3.2.219 The user authentication policy '%1' is not defined in the database

Error code	-10430
Parameter 1	The user authentication policy name.

Probable cause

The default user authentication policy has not been defined in the database. Please either define the user authentication policy in the database or remove the default user authentication policy name from the synchronization server command line.

1.3.2.220 There are no entries in the JVM config file: '%1'

Error code	-10138
Parameter 1	Config file name.

Probable cause

If a `jvm.cfg` file is found it is expected to have at least one line. Please remove or populate the `jvm.cfg`.

Related Information

[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.221 There are too many entries in the JVM config file: '%1'

Error code	-10147
Parameter 1	The config file.

Probable cause

The jvm.cfg is probably corrupt. Please check the contents of the jvm.cfg file.

Related Information

[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.222 This connection will be abandoned due to previous errors

Error code	-10091
------------	--------

Probable cause

Due to the severity of error(s) encountered processing the upload stream, further work will be futile. This is probably due to an I/O error or a protocol problem.

1.3.2.223 This server is not licensed to connect to a consolidated database of the following type: '%1'

Error code	-10309
Parameter 1	Consolidated database type.

Probable cause

Some synchronization server licenses are restricted to specific consolidated database types. Use a DSN that connects to a consolidated database type you are licensed for.

Related Information

[Server Licensing Utility \(dblic\)](#)

1.3.2.224 This server is not licensed to use dbmlsync

Error code	-10314
------------	--------

Probable cause

Some synchronization server licenses are not allowed to use dbmlsync. You may not use dbmlsync to sync with this server.

Related Information

[Server Licensing Utility \(dblic\)](#)

1.3.2.225 This server is not licensed to use the direct row API

Error code	-10312
------------	--------

Probable cause

Some synchronization server licenses are not allowed to use the direct row API. You may not have any handle_UploadData or handle_DownloadData scripts.

Related Information

[Server Licensing Utility \(dblic\)](#)

1.3.2.226 This synchronization has been aborted by client request

Error code	-10372
------------	--------

Probable cause

The client has requested that the current synchronization be terminated.

1.3.2.227 This synchronization server is not licensed to run in High Availability mode

Error code	-10369
------------	--------

Probable cause

Another synchronization server was detected using the same consolidated database. This is not allowed with the current license.

1.3.2.228 TLS ON cannot be used with URL '%1'

Error code	-10395
Parameter 1	The LDAP URL that is using Secure LDAP.

Probable cause

The LDAP server is specified with TLS ON and the specified LDAP URL uses Secure LDAP, that is, 'ldaps' instead of 'ldap', which is not a valid combination. Use either TLS ON or an 'ldaps' URL.

1.3.2.229 Too many options sent to Java VM

Error code	-10146
------------	--------

Probable cause

The number of options passed to the Java VM is exceedingly large. Please reduce the number of command line arguments.

Related Information

[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.230 Transactions on this connection cannot be committed or rolled back

Error code	-10202
------------	--------

Probable cause

An attempt was made to commit or roll back a transaction on a database connection that synchronization server controls. Do not attempt to commit or roll back a synchronization server database connection from a method invoked as a script.

1.3.2.231 Two or more MobiLink clients are either simultaneously uploading the file '%1', or opening the temporary file '%2' failed

Error code	-10346
Parameter 1	Upload filename.
Parameter 2	Temporary upload filename.

Probable cause

The file is being uploaded by more than one client or the synchronization server could not open the temporary file. A file can only be uploaded by one client at a time, and a temporary file is required.

Related Information

[Resumption of Failed Downloads](#)

1.3.2.232 Two or more synchronization server clients are simultaneously uploading the file '%1'

Error code	-10345
Parameter 1	Upload filename.

Probable cause

The file is being uploaded by more than one client. A file can only be uploaded by one client at a time.

Related Information

[The Synchronization Process](#)

1.3.2.233 Unable to abort the distributed transaction (event: '%1') -- system error: '%2'

Error code	-10290
------------	--------

Probable cause

The synchronization server was not able to abort the distributed transaction.

Related Information

[MobiLink System Database](#)

[-cs mlsrv17 Option](#)

1.3.2.234 Unable to accept an incoming connection (system error '%1')

Error code	-10276
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.235 Unable to accept new connections on network listener port

Error code	-10292
------------	--------

Probable cause

The synchronization server was unable to accept an incoming connection. Please contact technical support.

1.3.2.236 Unable to access the JRE at: '%1'

Error code	-10145
Parameter 1	The JRE path.

Probable cause

Please fix the argument to the -jrepath option so that the synchronization server may load the required Java VM.

Related Information

[MobiLink Server .NET API Reference](#)
[-sl java mlsrv17 Option](#)

1.3.2.237 Unable to allocate a connection

Error code

-10067

Probable cause

The synchronization server was not able to allocate a connection. Please make sure that there is enough memory to start the synchronization server. Also, make sure that the database server is running, and that the user ID and password are valid.

Related Information

[SQL Anywhere Database Server Executable \(dbsrv17, dbeng17\)](#)

1.3.2.238 Unable to allocate memory for the DownloadData instance

Error code

-10221

Probable cause

The Java VM has run out of memory. Try increasing the amount of memory available to the Java VM.

1.3.2.239 Unable to allocate memory for the UploadData instance

Error code -10222

Probable cause

The Java VM has run out of memory. Try increasing the amount of memory available to the Java VM.

1.3.2.240 Unable to allocate memory needed for script execution

Error code -10170

Probable cause

Consider adding more RAM, or shutting down other programs, or reducing the memory required by the .NET synchronization scripts.

Related Information

[MobiLink Performance](#)
[MobiLink Server .NET API Reference](#)

1.3.2.241 Unable to attach JDBC connection

Error code -10160

Probable cause

The synchronization server was unable to wrap an ODBC connection to create a JDBC connection.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.242 Unable to attach thread to .NET runtime

Error code	-10168
------------	--------

Probable cause

This is an internal startup error. Please contact technical support.

1.3.2.243 Unable to authenticate user '%1'

Error code	-10055
Parameter 1	The user name.

Probable cause

The synchronization server was not able to authenticate the given user.

Related Information

[MobiLink User Authentication Utility \(mluser\)](#)

1.3.2.244 Unable to bind listener socket to port (system error '%1')

Error code	-10261
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.245 Unable to close socket (system error '%1')

Error code	-10271
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.246 Unable to close the recorded protocol file

Error code	-10324
------------	--------

Probable cause

The server was unable to close a recorded protocol file.

Related Information

[MobiLink Replay Utility \(mlreplay\)](#)

[-rp mlsrv17 Option](#)

[-rrp mlsrv17 Option](#)

1.3.2.247 Unable to commit the distributed transaction (event: '%1') -- system error: '%2'

Error code	-10289
------------	--------

Probable cause

The synchronization server was not able to commit the distributed transaction.

Related Information

[MobiLink System Database](#)
[-cs mlsrv17 Option](#)

1.3.2.248 Unable to COMMIT transaction: '%1' -- Attempting to ROLLBACK

Error code	-10065
Parameter 1	The script name.

Probable cause

The synchronization server was not able to commit the transaction for the given script. Writing scripts to avoid deadlocks is always a good practice.

Related Information

[Synchronization Scripts](#)

1.3.2.249 Unable to complete the request

Error code	-10368
------------	--------

Probable cause

The synchronization server was not able to complete the client request. Please check the synchronization server message log for more details.

Related Information

[-o mlsrv17 Option](#)
[-dl mlsrv17 Option](#)

1.3.2.250 Unable to connect to the arbiter server

Error code	-10349
------------	--------

Probable cause

The synchronization server was not able connect to the arbiter server. Please make sure the arbiter server is running and check your connection parameters.

Related Information

[MobiLink Arbiter Server Utility for Windows \(mlarbiter\)](#)
[MobiLink Arbiter Server Utility for UNIX/Linux \(mlarbiter.sh\)](#)
[-ca mlsrv17 Option](#)
[-lsc mlsrv17 Option](#)

1.3.2.251 Unable to connect to the consolidated database. Aborting the synchronization

Error code	-10028
------------	--------

Probable cause

The synchronization server was not able to make a connection to the consolidated database server. Please make sure that the database server is running and the network is okay.

Related Information

[SQL Anywhere Database Server Executable \(dbsrv17, dbeng17\)](#)

1.3.2.252 Unable to convert the string '%1' to a numeric value

Error code	-10213
Parameter 1	String to be converted.

Probable cause

The synchronization server cannot convert the string to a numeric value. This is an internal error. Please contact technical support.

1.3.2.253 Unable to create a shared memory file

Error code	-10282
------------	--------

Probable cause

The synchronization server was not able to create a shared memory file using the given synchronization server name. Please check if a synchronization server with the same name is currently running on the local machine.

1.3.2.254 Unable to create an I/O completion port (system error '%1')

Error code	-10258
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.255 Unable to create connection socket (system error '%1')

Error code	-10264
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.256 Unable to create listener socket (system error '%1')

Error code	-10260
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.257 Unable to create new database connection

Error code	-10159
------------	--------

Probable cause

The synchronization server was unable to create a new ODBC connection needed to create a new JDBC wrapper.

Related Information

[MobiLink Server .NET API Reference](#)

1.3.2.258 Unable to create the background thread

Error code	-10112
------------	--------

Probable cause

The synchronization server was unable to create a thread for background processing. The most likely cause is insufficient memory.

1.3.2.259 Unable to create unix pipe for socket selector notification (system error '%1')

Error code	-10272
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.260 Unable to delete from table '%1' using '%2'

Error code	-10073
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

A failure occurred when the synchronization server was deleting row(s) from the given table in the consolidated database.

1.3.2.261 Unable to delete user name '%1' from the ml_user_table

Error code	-10083
Parameter 1	The name of the user to be deleted.

Probable cause

Please check if the synchronization user is valid and is not currently in use by other threads.

Related Information

[MobiLink Users in a Synchronization System](#)

1.3.2.262 Unable to detach worker from VM

Error code	-10169
------------	--------

Probable cause

This is an internal shutdown error. Please contact technical support.

1.3.2.263 Unable to dump exception information. Received exception while processing exception

Error code	-10119
------------	--------

Probable cause

A Java script caused an exception, but the synchronization server could not display the exception information because of a subsequent exception.

1.3.2.264 Unable to enlist the database in the Distributed Transaction Coordinator

Error code	-10288
------------	--------

Probable cause

The synchronization server was not able to enlist the database in the Distributed Transaction Coordinator.

Related Information

[MobiLink System Database](#)
[-cs mlsrv17 Option](#)

1.3.2.265 Unable to execute an RTNotifier's request cursor due to previous errors

Error code	-10339
------------	--------

Probable cause

Unable to execute an RTNotifier's request cursor due to previous errors.

Related Information

[Remote Task Notifier \(RTNotifier\)](#)

1.3.2.266 Unable to fetch from table '%1' using '%2'

Error code	-10071
------------	--------

Parameter 1	Table name.
-------------	-------------

Parameter 2

Script name.

Probable cause

A failure occurred when the synchronization server was retrieving row(s) from the given table in the consolidated database.

1.3.2.267 Unable to find file '%1'

Error code

-10166

Parameter 1

The filename.

Probable cause

The synchronization server was unable to find one of the files it needs to start .NET scripting. Please check your installation and environment variables.

Related Information

[MobiLink Server Deployment](#)

1.3.2.268 Unable to find shared components directory. JRE location is not specified in options. JRE location is unknown

Error code

-10143

Probable cause

Set the shared components environment variable or specify a JRE location using the -jrepath option.

Related Information

[MobiLink Server .NET API Reference](#)

[-sl java mlsrv17 Option](#)

1.3.2.269 Unable to find the JAR file: '%1' in install directory or classpath

Error code	-10142
Parameter 1	JAR file name.

Probable cause

Install the missing JAR file.

Related Information

[MobiLink Server Deployment](#)

[Setting up Java Synchronization Logic](#)

[-sl java mlsrv17 Option](#)

1.3.2.270 Unable to flush scripts

Error code	-10020
------------	--------

Probable cause

If the -zf option has been provided on the synchronization server start line, then the synchronization server always checks whether it needs to update its cached scripts at the beginning of each synchronization by connecting to the consolidated database server and querying the ml_scripts_modified table.

1.3.2.271 Unable to get an assertion ticket: '%1'

Error code	-10436
Parameter 1	Error message.

Probable cause

The synchronization server was not able to get an assertion ticket for logon.

1.3.2.272 Unable to get the DTC transaction manager -- system error: '%1'

Error code	-10286
------------	--------

Probable cause

The synchronization server was not able to get the transaction manager. Please make sure the service of the Distributed Transaction Coordinator (DTC) is running on the local computer.

Related Information

[MobiLink System Database](#)
[-cs mlsrv17 Option](#)

1.3.2.273 Unable to get the RID for remote ID '%1'

Error code	-10348
Parameter 1	Remote ID.

Probable cause

The synchronization server was not able to get the RID from the ml_database table in the consolidated database or the synchronization server system database (MLSD). Please make sure the consolidated database or MLSD is running.

Related Information

[Consolidated Database Setup](#)

[MobiLink System Database](#)

[Remote IDs](#)

[-cs mlsrv17 Option](#)

1.3.2.274 Unable to get the user ID for user '%1'

Error code	-10347
Parameter 1	The user name.

Probable cause

The synchronization server was not able to get the user_id from the ml_user table in the consolidated database or the synchronization server system database (MLSD). Please make sure the consolidated database or MLSD is running.

Related Information

[Consolidated Database Setup](#)

[MobiLink System Database](#)

[MobiLink Users in a Synchronization System](#)

[-cs mlsrv17 Option](#)

1.3.2.275 Unable to initialize a distributed transaction -- system error: '%1'

Error code	-10287
------------	--------

Probable cause

The synchronization server was not able to initialize a distributed transaction. Please make sure the transaction log of the database is not full.

Related Information

[MobiLink System Database](#)
[-cs mlsrv17 Option](#)

1.3.2.276 Unable to initialize communications stream '%1': '%2'

Error code	-10110
Parameter 1	Stream number.
Parameter 2	Stream specification.

Probable cause

The given stream could not be initialized. Ensure that the stream name and stream options are valid.

Related Information

[-x mlsrv17 Option](#)

1.3.2.277 Unable to initialize ODBC

Error code	-10066
------------	--------

Probable cause

The synchronization server was not able to initialize the ODBC layer. Please make sure that there is enough memory to start the synchronization server and then start the synchronization server with a recommended ODBC driver.

1.3.2.278 Unable to initialize SAP Native Component Supportability (NCS)

Error code	-10434
------------	--------

Probable cause

The -ncs, -ncsd, or -ncsp option was specified, but the NCS layer was unable to initialize.

1.3.2.279 Unable to insert into table '%1' using '%2'

Error code	-10072
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

A failure occurred when the synchronization server was inserting row(s) into the given table in the consolidated database.

1.3.2.280 Unable to insert user name '%1' into the ml_user table

Error code	-10054
Parameter 1	The user name.

Probable cause

The synchronization server was not able to add the given user into the ml_user table. Please verify that the consolidated database server is running and that the synchronization server's database login ID has permission to modify the ml_user table.

Related Information

[Required Privileges for MobiLink Server Consolidated Database Upgrades](#)

1.3.2.281 Unable to listen on port (system error '%1')

Error code	-10262
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.282 Unable to load '%1'

Error code	-10411
------------	--------

Probable cause

The required DLL could not be found. Please check your synchronization server installation.

1.3.2.283 Unable to load .NET CLR Host DLL

Error code	-10165
------------	--------

Probable cause

The .NET CLR refused to load. Please use the .NET CLR utilities for logging binding and loading activity to determine the problem.

Related Information

[-sl dnet mlsrv17 Option](#)

1.3.2.284 Unable to load .NET Framework CLR Version '%1'

Error code	-10164
Parameter 1	The CLR version.

Probable cause

Make sure the given CLR version is installed.

Related Information

[-sl dnet mlsrv17 Option](#)

1.3.2.285 Unable to load Assembly '%1' into domain '%2'

Error code	-10193
Parameter 1	The assembly name.
Parameter 2	The domain name.

Probable cause

The named assembly could not be loaded. Please use the .NET CLR utilities for logging binding and loading activity to determine the problem.

Related Information

[.NET Assembly Loading](#)
[-sl dnet mlsrv17 Option](#)

1.3.2.286 Unable to load DLL or shared object '%1' for stream '%2': '%3'

Error code	-10108
Parameter 1	The DLL or shared object name.
Parameter 2	Stream type.
Parameter 3	Stream name.

Probable cause

The given DLL or shared object could not be loaded for the given stream. Ensure the correct version of the DLL or shared object is present and in the proper location.

Related Information

[-x mlsrv17 Option](#)

1.3.2.287 Unable to load DLL or shared object: '%1'

Error code	-10107
Parameter 1	The DLL or shared object name.

Probable cause

The given DLL or shared object could not be loaded. Ensure the correct version of the DLL or shared object is present and in the proper location.

1.3.2.288 Unable to load entry points from DLL: '%1'

Error code	-10088
Parameter 1	The DLL or shared object name.

Probable cause

Please check your synchronization server installation.

Related Information

[MobiLink Server Deployment](#)

1.3.2.289 Unable to load the Java VM due to a memory error

Error code	-10122
------------	--------

Probable cause

The synchronization server was unable to load the Java VM. Consider increasing RAM or freeing up memory by shutting down other processes.

1.3.2.290 Unable to load the Java VM due to a version error

Error code	-10121
------------	--------

Probable cause

The synchronization server was unable to load the Java VM. Ensure the correct Java VM is installed.

Related Information

[Setting up Java Synchronization Logic](#)
[-sl java mlsrv17 Option](#)

1.3.2.291 Unable to load the Java VM due to an unknown error

Error code	-10123
------------	--------

Probable cause

The synchronization server was unable to load the Java VM. The reason is likely displayed in previous output.

Related Information

[Setting up Java Synchronization Logic](#)

1.3.2.292 Unable to load the Java VM shared library. Make sure that the shared library path is set correctly and that LD_PRELOAD is set correctly and supported by your version of the dynamic loader

Error code	-10209
------------	--------

Probable cause

The synchronization server was not able to load the Java VM shared library. Please make sure that the Java VM shared library is installed, the path is set correctly, and the LD_PRELOAD is set correctly and supported by your version of the dynamic loader

Related Information

[-sl java mlsrv17 Option](#)

1.3.2.293 Unable to load UNILIB collation '%1': '%2'

Error code	-10099
Parameter 1	Unilib charset ID.
Parameter 2	Unilib error string.

Probable cause

The synchronization server cannot initialize the Unilib converter. The installation may be damaged or the required collation is unavailable.

1.3.2.294 Unable to locate .NET Domain Configuration File '%1'

Error code	-10191
Parameter 1	The filename.

Probable cause

The domain configuration file specified could not be found. Please check the file location and configuration file setting.

Related Information

[.NET Assembly Loading](#)

[-sl dnet mlsrv17 Option](#)

1.3.2.295 Unable to lock the primary synchronization server

Error code	-10351
------------	--------

Probable cause

The synchronization server was not able to lock the primary server. Please make sure the table ml_primary_server_lock table exists and contains only one row.

Related Information

[MobiLink Arbiter Server Utility for Windows \(mlarbiter\)](#)

[MobiLink Arbiter Server Utility for UNIX/Linux \(mlarbiter.sh\)](#)

[-ca mlsrv17 Option](#)

[-lsc mlsrv17 Option](#)

1.3.2.296 Unable to notify (system error '%1')

Error code	-10275
------------	--------

Parameter 1	System error.
-------------	---------------

Probable cause

Please contact technical support.

1.3.2.297 Unable to open '%1'

Error code	-10058
Parameter 1	The script name.

Probable cause

The synchronization server failed to execute the given table script. Please make sure that the script contains valid SQL.

Related Information

[Table Scripts](#)

1.3.2.298 Unable to open temporary file '%1'

Error code	-10212
Parameter 1	File name.

Probable cause

The synchronization server may use temporary files to store intermediate data. Please make sure the synchronization server has permission to create temporary files.

Related Information

[Required Privileges for MobiLink Server](#)

1.3.2.299 Unable to open the file '%1' for recording

Error code	-10316
------------	--------

Parameter 1

File name.

Probable cause

The server was unable to open the file for recording.

Related Information

[MobiLink Replay Utility \(mlreplay\)](#)

[-rrp mlsrv17 Option](#)

[-rp mlsrv17 Option](#)

[-lsc mlsrv17 Option](#)

1.3.2.300 Unable to parse class and method name from script: '%1'

Error code

-10125

Parameter 1

Script name.

Probable cause

The proper format for Java synchronization scripts is 'myPackage.myClass.myMethod'.

Related Information

[Setting up Java Synchronization Logic](#)

1.3.2.301 Unable to perform a hard close on a listener socket

Error code

-10268

Probable cause

Please contact technical support.

1.3.2.302 Unable to perform a hard close on a socket '%1'

Error code	-10266
Parameter 1	Socket.

Probable cause

Please contact technical support.

1.3.2.303 Unable to poll sockets (system error '%1')

Error code	-10274
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.304 Unable to post listener deletion request to completion queue (system error '%1')

Error code	-10269
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.305 Unable to post socket deletion request to completion queue (system error '%1')

Error code	-10267
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.306 Unable to process a synchronization request at this time

Error code	-10387
------------	--------

Probable cause

The synchronization request is unable to proceed as the consolidated database seems to be unavailable.

1.3.2.307 Unable to process the request, because synchronization requires access to the ORACLE 'gv\$transaction' table

Error code	-10380
------------	--------

Probable cause

Accessing the Oracle gv\$transaction table for the synchronization server is necessary in order to ensure no data missing in a timestamp based download. Please try to grant a select permission on gv\$transaction to the synchronization server database login ID.

Related Information

[Oracle Consolidated Database](#)

1.3.2.308 Unable to process the synchronization request because its sync sequence number '%1' is smaller than or equal to the one '%2' in consolidated database

Error code	-10388
Parameter 1	Sync sequence number of the remote.
Parameter 2	Sync sequence number in the consolidated database.

Probable cause

The synchronization server has refused to process the synchronization request, because its sync sequence number is smaller than or equal to the one in consolidated database. This problem can happen, when a synchronization server has already applied a later sync request from the same remote database.

1.3.2.309 Unable to record part of the synchronization

Error code	-10318
------------	--------

Probable cause

The server was unable to record part of the synchronization. Check that the server was able to open the file for recording.

Related Information

[MobiLink Replay Utility \(mlreplay\)](#)
[-rp mlsrv17 Option](#)

1.3.2.310 Unable to resolve host name '%1' (error: '%2')

Error code	-10283
Parameter 1	Host name.
Parameter 2	Error number.

Probable cause

The host name specified could not be resolved. An OS-specific error number is given.

1.3.2.311 Unable to retrieve data from table '%1'

Error code	-10398
Parameter 1	The synchronization server system table name.

Probable cause

The synchronization server was not able to fetch data from its system table in the consolidated database. Please see the previous errors for the cause of the problem.

1.3.2.312 Unable to retry the current transaction after conflict-update with snapshot isolation in the consolidated database. The retry limit has been reached

Error code	-10246
------------	--------

Probable cause

The synchronization server has retried the current transaction, but the conflict-update problem still occurred. Please commit all open transactions running against the consolidated database and try to run the synchronization again.

Related Information

[MobiLink Isolation Levels](#)

[Snapshot Isolation](#)

1.3.2.313 Unable to retry the current transaction after deadlock in the consolidated database. The retry limit has been reached

Error code	-10021
------------	--------

Probable cause

The synchronization server has retried the current transaction, but the deadlock problem still occurred. Please redesign your synchronization logic or use the -r synchronization server command line option.

Related Information

[Synchronization Scripts](#)

[MobiLink Application Design](#)

[-r mlsrv17 Option](#)

1.3.2.314 Unable to reuse address (system error '%1')

Error code	-10273
------------	--------

Parameter 1	System error.
-------------	---------------

Probable cause

Please contact technical support.

1.3.2.315 Unable to ROLLBACK transaction: '%1'

Error code	-10064
Parameter 1	The script name.

Probable cause

The synchronization server was not able to roll back the transaction.

Related Information

[Synchronization Scripts](#)

1.3.2.316 Unable to send SQL Passthrough script due to an unknown script flag: '%1'

Error code	-10297
------------	--------

Probable cause

The synchronization server found an unknown SQL Passthrough script flag for this user. Check the scripts for this user.

Related Information

[ml_add_passthrough_script System Procedure](#)
[ml_add_passthrough_repair System Procedure](#)

1.3.2.317 Unable to set the thread affinity mask which is required by the recorder

Error code

-10317

Probable cause

The server was unable to set the thread affinity mask which is required by the recorder.

Related Information

[MobiLink Replay Utility \(mlreplay\)](#)

1.3.2.318 Unable to set transaction isolation level to snapshot

Error code

-10247

Probable cause

The synchronization server was not able to set the transaction isolation level to snapshot. Please make sure the database login ID used to connect the synchronization server to the consolidated database has the permission to change the isolation level and the database allows snapshot isolation.

Related Information

[MobiLink Isolation Levels](#)
[Snapshot Isolation](#)
[How to Enable Snapshot Isolation](#)

1.3.2.319 Unable to set value for user parameter '%1' -- value larger than '%2' characters

Error code	-10375
Parameter 1	User parameter name.

Probable cause

A user defined variable cannot be set longer than specified.

Related Information

[User-defined Named Parameters](#)

1.3.2.320 Unable to shutdown .NET scripting VM

Error code	-10180
------------	--------

Probable cause

The synchronization server was unable to shut down the .NET scripting VM. Shutdown actions performed by start classes may not complete properly.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[Implementing Synchronization Scripts in .NET](#)
[MobiLink Server .NET API Reference](#)

1.3.2.321 Unable to shutdown .NET scripting VM. '%1' workers still attached

Error code	-10181
Parameter 1	The number of worker threads.

Probable cause

The synchronization server was unable to shutdown the .NET scripting VM because there are worker threads still attached. There may be a start class that is not respecting the shutdown, or is delaying its response to the shutdown.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[Implementing Synchronization Scripts in .NET](#)
[MobiLink Server .NET API Reference](#)

1.3.2.322 Unable to start accepting connections (system error '%1')

Error code	-10265
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.323 Unable to start the restartable synchronization

Error code	-10255
------------	--------

Probable cause

The synchronization server was unable to start the restartable synchronization requested by the client because the synchronization may already have been completed or the synchronization server may have been restarted.

Remarks

That error can occur for a number of reasons, including:

- The server restarts
- The data is emptied out of the download cache to make room for more recent active syncs
- The download was too large to fit in the download cache and the synchronization had to be restarted (possibly due to a temporary drop in network activity)

When this error occurs, the client must retry the synchronization. Increasing the size of the download cache may prevent this error.

Related Information

[Resumption of Failed Downloads](#)
[-ds mlsrv17 Option](#)

1.3.2.324 Unable to store the primary server information

Error code	-10352
------------	--------

Probable cause

The synchronization server was not able to store the primary server information into the consolidated database or the synchronization server system database.

Related Information

[MobiLink Arbiter Server Utility for Windows \(mlarbiter\)](#)
[MobiLink Arbiter Server Utility for UNIX/Linux \(mlarbiter.sh\)](#)
[-ca mlsrv17 Option](#)
[-lsc mlsrv17 Option](#)

1.3.2.325 Unable to support MLSD

Error code	-10296
------------	--------

Probable cause

The synchronization server was not able to support its system objects stored in a database other than the consolidated database, because the ODBC driver for this database server doesn't support the Microsoft Distributed Transactions. Please install the synchronization server system objects on the consolidated database and remove the -cs option from the command line.

Related Information

[MobiLink System Database](#)
[-cs mlsrv17 Option](#)

1.3.2.326 Unable to translate the authentication message

Error code	-10385
------------	--------

Probable cause

The synchronization server was not able to translate the authentication message returned by the authentication scripts into the character set required by the remote database. Please check the authentication scripts.

1.3.2.327 Unable to update table '%1' using '%2'

Error code	-10074
Parameter 1	Table name.
Parameter 2	Script name.

Probable cause

A failure occurred when the synchronization server was updating row(s) for the given table in the consolidated database.

1.3.2.328 Unable to validate the synchronization server license

Error code	-10438
------------	--------

Probable cause

The synchronization server was not able to validate its license against the SAP HANA server. Please make sure the remote data sync server license is registered in the SAP HANA server correctly.

1.3.2.329 Unable to wait on completion port (system error '%1')

Error code	-10270
Parameter 1	System error.

Probable cause

Please contact technical support.

1.3.2.330 Unable to write to the file

Error code	-10319
------------	--------

Probable cause

The server was unable to record part of the synchronization because it could not write to the file.

Related Information

[MobiLink Replay Utility \(mlreplay\)](#)
[-rp mlsrv17 Option](#)

1.3.2.331 Unknown system parameter '%1' for script '%2'

Error code	-10227
Parameter 1	Name of unknown system parameter.
Parameter 2	Name of script.

Probable cause

The named system parameter is not in the list of valid system parameters.

Related Information

[Script Parameters](#)

1.3.2.332 Unrecognized domain id '%1'

Error code	-10024
Parameter 1	Domain ID.

Probable cause

The client-requested domain ID (data type) is not supported. Please make sure that your synchronization server is up-to-date.

Related Information

[Domains](#)
[MobiLink Upgrades](#)

1.3.2.333 Unrecognized event name: '%1'

Error code	-10207
Parameter 1	The name of the unrecognized event.

Probable cause

The synchronization server only recognizes a set of connection and table events and these events are stored in the tables of ml_connection_script and ml_table_script. Please make sure all the connection and table events are valid.

Related Information

[Synchronization Events](#)

1.3.2.334 Upload data for column '%1' of table '%2' is invalid

Error code	-10308
Parameter 1	Column index.
Parameter 2	Table name.

Probable cause

The data uploaded from the client cannot be processed, either it is out of range or cannot be translated.

1.3.2.335 Upload failed with client error '%1'

Error code	-10032
Parameter 1	An error number sent by the client.

Probable cause

The synchronization server aborted the synchronization because the client indicates there is a problem on the remote site during upload.

Related Information

[Failed Downloads](#)

1.3.2.336 User name '%1' not found in the ml_user table

Error code	-10056
Parameter 1	The user name.

Probable cause

The synchronization server could not find the user from the ml_user table. Please add this user to the ml_user table using mluser or start the synchronization server with the -zu+ option.

Related Information

[MobiLink Users in a Synchronization System](#)
[MobiLink User Authentication Utility \(mluser\)](#)
[-zu mlsrv17 Option](#)

1.3.2.337 Version '%1' not found in the ml_script_version table. Cannot synchronize

Error code	-10013
Parameter 1	Version string.

Probable cause

The client-specified version does not exist in the consolidated database. Please create a script version.

Related Information

[Script Versions](#)

[Adding a Script Version to a Consolidated Database](#)

1.3.2.338 Version mismatch with DLL or shared object: '%1' Expected version: '%2' got version: '%3'

Error code	-10087
Parameter 1	The DLL or shared object name.
Parameter 2	The expected version number.
Parameter 3	The supplied version number.

Probable cause

Please check your synchronization server installation.

Related Information

[MobiLink Server Deployment](#)

1.3.2.339 You have not specified a request_cursor for notifier '%1'

Error code	-10334
Parameter 1	notifier name.

Probable cause

You have not specified a request_cursor for the given notifier.

Related Information

[request_cursor Event](#)

1.3.2.340 The synchronization server has failed a memory allocation and will probably soon crash

Error code	-10440
------------	--------

Probable cause

With 32-bit servers, the server's address space is probably exhausted. Lower -nc or -sm or switch to a 64-bit system. With 64-bit servers, you have probably run out of virtual memory. You must reconfigure your operating system to increase it.

1.3.2.341 Unable to shared object: '%1' from library path '%2'

Error code	-10441
Parameter 1	The shared object name.
Parameter 2	The library path.

Probable cause

You have not specified a request_cursor for the given notifier.

1.4 MobiLink Server Warning Messages

The MobiLink server warning messages are written to the MobiLink server message log. Each error has a numeric error code: both error and warning codes are positive, while warning codes are greater than 10000.

Many of the error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.

In this section:

[MobiLink Server Warning Messages Sorted by Error Code \[page 1137\]](#)

[MobiLink Server Warning Messages Listed by Message Text \[page 1142\]](#)

Related Information

[MobiLink Server Error Messages \[page 967\]](#)

[MobiLink Communication Error Messages \[page 1184\]](#)

1.4.1 MobiLink Server Warning Messages Sorted by Error Code

Error code	Message text
10001	Maximum number of database connections set to '%1' (must be at least the number of database worker threads) [page 1155]
10003	ODBC Isolation level (%1) is not supported [page 1157]
10004	ODBC function '%1' is not supported by the driver [page 1157]
10005	ODBC statement option '%1' has changed from '%2' ('%3') to '%4' ('%5') [page 1158]
10006	ODBC statement option '%1' has changed from '%2' to '%3' [page 1158]
10007	Retrying the begin_connection transaction after deadlock in the consolidated database [page 1162]
10009	Synchronization server table '%1' is damaged [page 1165]
10010	No handle_error script is defined. The default action code (%1) will decide the error behavior [page 1156]

Error code	Message text
10012	The consolidated and remote databases disagree on when the last synchronization took place, the progress offsets are '%1' in the consolidated database and '%2' in the remote database. The remote is being asked to send a new upload that starts at the last ... [page 1168]
10014	Expecting at most '%1' parameter(s) in cursor, but found '%2' [page 1151]
10015	Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, uploaded timestamps can lose precision, defeating download filtering [page 1166]
10016	Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, downloaded timestamps can lose precision, resulting in inconsistent data [page 1166]
10017	The consolidated and remote databases have different timestamp precisions. Consolidated database timestamps are precise to '%1' digit(s) in the fractional second while the remote database timestamps are precise to '%2' digit(s) [page 1169]
10018	Resolve the timestamp precision mismatch by setting the SQL Anywhere DEFAULT_TIMESTAMP_INCREMENT option on the remote database to '%1' and TRUNCATE_TIMESTAMP_VALUES to 'On'. UltraLite remotes must set the TIMESTAMP_INCREMENT option to '%2' [page 1161]
10019	The remote database is not capable of matching the timestamp precision of the consolidated database. Your application, schema, and scripts must contain logic that copes with the precision mismatch [page 1172]
10020	The timestamp precision mismatch may affect upload conflict detection. Use the -zp option to cause the synchronization server to use the lowest timestamp precision for conflict detection purposes [page 1175]
10021	The remote and consolidated databases have different timestamp precisions, and a timestamp value with a precision higher than the lower-precision side was used for conflict detection purposes. Consider using the -zp option [page 1171]
10022	Publication '%1' is not referenced by any table [page 1160]
10023	The upload will be rolled back and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload [page 1176]
10032	Unable to open the file to store the client synchronization logs. The filename is '%1' [page 1181]
10033	An error occurred reading the remote client's synchronization log [page 1148]
10034	Unable to write to the local file that contains remote synchronization logs [page 1183]

Error code	Message text
10035	The remote client's synchronization log ended prematurely, and was probably truncated [page 1171]
10036	Client synchronization logs will be shown in the synchronization server message log file or the synchronization server messages window [page 1149]
10039	Error detected during multi-row operation, performing roll-back before retrying in single row mode [page 1150]
10040	'%1' row(s) were ignored in uploading data into table '%2' [page 1145]
10041	The upload will be committed and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload [page 1175]
10043	Unable to determine current timestamp from consolidated database [page 1180]
10045	Retrying the upload after deadlock in the consolidated database [page 1164]
10048	Retrying the begin_synchronization transaction after deadlock in the consolidated database [page 1162]
10049	Retrying the end_synchronization transaction after deadlock in the consolidated database [page 1163]
10050	%1 [page 1145]
10051	Unrecognized ODBC driver '%1'. The functionality and quality of ODBC drivers varies greatly. This driver may lack functionality required for successful synchronizations. Use at your own risk [page 1184]
10055	The client has provided '%1' authentication parameter(s), but no authenticate_parameters script exists [page 1167]
10064	Unknown users will be added automatically (when there is no authenticate_user script) [page 1183]
10068	'%1' [page 1146]
10073	Windows Firewall is enabled, and the synchronization server is not in the exception list. Clients on remote machines may not be able to connect to this server [page 1184]
10074	Unable to fetch the download timestamp from the consolidated database [page 1180]
10075	Unable to access ORACLE table 'gv\$transaction'. Access is needed to ensure no data is missed if using timestamp-based downloads [page 1179]
10078	Unable to access Microsoft SQL Server virtual table 'sys.dm_tran_active_transactions'. The synchronization server will not use snapshot isolation [page 1178]
10079	The command line option '%1' is ignored [page 1168]

Error code	Message text
10080	Retrying the upload after conflicting update in the consolidated database [page 1163]
10081	Unable to retrieve the column data types for table '%1' from the consolidated database [page 1182]
10082	The synchronization server has swapped data pages to disk out:%1 in: '%2' concurrently used pages: '%3' [page 1173]
10083	The synchronization server has suspended network reads on this synchronization due to a limit on concurrent synchronizations [page 1172]
10084	The synchronization server restarted network reads on this synchronization due to a drop in the number of concurrent synchronizations [page 1174]
10085	For table '%1', the number of entries in the ml_column table is greater than the number of columns in the remote table [page 1151]
10087	Unable to access ASE table 'master..systransactions'. The synchronization server will use system time for download [page 1178]
10088	The current SQL statement has been running for too long in the consolidated database. The connection ID is '%1' [page 1169]
10089	Performance warning -- database connections have been recycled at a rate of '%1'% [page 1159]
10091	A passthrough script failed at the remote client, run_order: '%1', script_id: '%2', error_code: '%3', error_text: '%4' [page 1147]
10092	Invalid log verbosity options: '%1' [page 1153]
10093	The synchronization server is currently running with -zf that will reduce its performance [page 1173]
10094	Minimum cache size is too small. Increasing from '%1' to '%2' bytes [page 1156]
10095	Maximum cache size is too small. Increasing from '%1' to '%2' bytes [page 1155]
10096	Initial cache size is too small. Increasing from '%1' to '%2' bytes [page 1152]
10097	Initial cache size is smaller than the minimum cache size. Increasing initial size to '%1' bytes [page 1152]
10098	Maximum cache size is smaller than the initial cache size. Increasing maximum size to '%1' bytes [page 1154]
10099	Unable to record the schema [page 1182]
10100	The synchronization server will record all synchronizations [page 1174]

Error code	Message text
10101	Synchronization request from client '%1' was rejected [page 1165]
10102	Spatial library warning: '%1' [page 1164]
10103	The Z/M values were dropped from the upload spatial data [page 1176]
10104	There are too many remote tasks to send to agent, '%1', at one time. The maximum number of remote tasks an agent can receive at one time is 255 [page 1177]
10105	No RTNotifier was started. Therefore, no remote tasks will be received by any agents [page 1157]
10106	Unable to lock the remote ID '%1', will try again [page 1181]
10107	<OE>: '%1' [page 1146]
10108	The following option has been deprecated: '%1' [page 1170]
10109	Loading a client Java VM [page 1154]
10110	Either '%1' does not exist or it does not contain any recorded protocol files (files with extension mlr) [page 1150]
10115	Performance warning: Column '%1' in the remote table '%2' has been remapped from '%3' to '%4' [page 1160]
10116	The earliest transaction has been running for '%1' seconds [page 1170]
10117	Connection ID '%1' is currently blocked by connection ID '%2' for '%3' seconds on '%4' [page 1149]
10118	Unable to authenticate the user '%1' against LDAP server [page 1179]
10119	Unable to fetch the UTC time from the database server [page 1181]
10120	Client network protocol version is too old [page 1148]
10121	Client network protocol version is too new [page 1148]
10122	ODBC tracing is currently enabled. This will significantly degrade performance [page 1159]
10123	Initial number of concurrent database worker threads greater than maximum specified. Decreasing initial number from '%1' to '%2' [page 1153]
10124	RETURN structure contained an warning [page 1164]
10125	This connection will be abandoned due to a first read error [page 1177]
10126	'%1' might not be a local address [page 1147]
10127	Unable to access SAP HANA Server system view 'SYS.M_TRANSACTIONS'. The synchronization server will not use snapshot isolation [page 1179]
10128	Generated too many Profiler phases [page 1152]

1.4.2 MobiLink Server Warning Messages Listed by Message Text

In this section:

[%1 \[page 1145\]](#)

['%1' row\(s\) were ignored in uploading data into table '%2' \[page 1145\]](#)

[<OE>: '%1' \[page 1146\]](#)

['%1' \[page 1146\]](#)

['%1' might not be a local address \[page 1147\]](#)

[A passthrough script failed at the remote client, run_order: '%1', script_id: '%2', error_code: '%3', error_text: '%4' \[page 1147\]](#)

[An error occurred reading the remote client's synchronization log \[page 1148\]](#)

[Client network protocol version is too new \[page 1148\]](#)

[Client network protocol version is too old \[page 1148\]](#)

[Client synchronization logs will be shown in the synchronization server message log file or the synchronization server messages window \[page 1149\]](#)

[Connection ID '%1' is currently blocked by connection ID '%2' for '%3' seconds on '%4' \[page 1149\]](#)

[Either '%1' does not exist or it does not contain any recorded protocol files \(files with extension mlr\) \[page 1150\]](#)

[Error detected during multi-row operation, performing rollback before retrying in single row mode \[page 1150\]](#)

[Expecting at most '%1' parameter\(s\) in cursor, but found '%2' \[page 1151\]](#)

[For table '%1', the number of entries in the ml_column table is greater than the number of columns in the remote table \[page 1151\]](#)

[Generated too many Profiler phases \[page 1152\]](#)

[Initial cache size is smaller than the minimum cache size. Increasing initial size to '%1' bytes \[page 1152\]](#)

[Initial cache size is too small. Increasing from '%1' to '%2' bytes \[page 1152\]](#)

[Initial number of concurrent database worker threads greater than maximum specified. Decreasing initial number from '%1' to '%2' \[page 1153\]](#)

[Invalid log verbosity options: '%1' \[page 1153\]](#)

[Loading a client Java VM \[page 1154\]](#)

[Maximum cache size is smaller than the initial cache size. Increasing maximum size to '%1' bytes \[page 1154\]](#)

[Maximum cache size is too small. Increasing from '%1' to '%2' bytes \[page 1155\]](#)

[Maximum number of database connections set to '%1' \(must be at least the number of database worker threads\) \[page 1155\]](#)

[Minimum cache size is too small. Increasing from '%1' to '%2' bytes \[page 1156\]](#)

[No handle_error script is defined. The default action code \(%1\) will decide the error behavior \[page 1156\]](#)

No RTNotifier was started. Therefore, no remote tasks will be received by any agents [page 1157]

ODBC function '%1' is not supported by the driver [page 1157]

ODBC Isolation level (%1) is not supported [page 1157]

ODBC statement option '%1' has changed from '%2' ('%3') to '%4' ('%5') [page 1158]

ODBC statement option '%1' has changed from '%2' to '%3' [page 1158]

ODBC tracing is currently enabled. This will significantly degrade performance [page 1159]

Performance warning -- database connections have been recycled at a rate of '%1%' [page 1159]

Performance warning: Column '%1' in the remote table '%2' has been remapped from '%3' to '%4' [page 1160]

Publication '%1' is not referenced by any table [page 1160]

Resolve the timestamp precision mismatch by setting the SQL Anywhere DEFAULT_TIMESTAMP_INCREMENT option on the remote database to '%1' and TRUNCATE_TIMESTAMP_VALUES to 'On'. UltraLite remotes must set the TIMESTAMP_INCREMENT option to '%2' [page 1161]

Retrying the begin_connection transaction after deadlock in the consolidated database [page 1162]

Retrying the begin_synchronization transaction after deadlock in the consolidated database [page 1162]

Retrying the end_synchronization transaction after deadlock in the consolidated database [page 1163]

Retrying the upload after conflicting update in the consolidated database [page 1163]

Retrying the upload after deadlock in the consolidated database [page 1164]

RETURN structure contained an warning [page 1164]

Spatial library warning: '%1' [page 1164]

Synchronization request from client '%1' was rejected [page 1165]

Synchronization server table '%1' is damaged [page 1165]

Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, downloaded timestamps can lose precision, resulting in inconsistent data [page 1166]

Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, uploaded timestamps can lose precision, defeating download filtering [page 1166]

The client has provided '%1' authentication parameter(s), but no authenticate_parameters script exists [page 1167]

The command line option '%1' is ignored [page 1168]

The consolidated and remote databases disagree on when the last synchronization took place, the progress offsets are '%1' in the consolidated database and '%2' in the remote database. The remote is being asked to send a new upload that starts at the last ... [page 1168]

The consolidated and remote databases have different timestamp precisions. Consolidated database timestamps are precise to '%1' digit(s) in the fractional second while the remote database timestamps are precise to '%2' digit(s) [page 1169]

The current SQL statement has been running for too long in the consolidated database. The connection ID is '%1' [page 1169]

The earliest transaction has been running for '%1' seconds [page 1170]

The following option has been deprecated: '%1' [page 1170]

The remote and consolidated databases have different timestamp precisions, and a timestamp value with a precision higher than the lower-precision side was used for conflict detection purposes. Consider using the -zp option [page 1171]

The remote client's synchronization log ended prematurely, and was probably truncated [page 1171]

The remote database is not capable of matching the timestamp precision of the consolidated database. Your application, schema, and scripts must contain logic that copes with the precision mismatch [page 1172]

The synchronization server has suspended network reads on this synchronization due to a limit on concurrent synchronizations [page 1172]

The synchronization server has swapped data pages to disk out:%1 in: '%2' concurrently used pages: '%3' [page 1173]

The synchronization server is currently running with -zf that will reduce its performance [page 1173]

The synchronization server restarted network reads on this synchronization due to a drop in the number of concurrent synchronizations [page 1174]

The synchronization server will record all synchronizations [page 1174]

The timestamp precision mismatch may affect upload conflict detection. Use the -zp option to cause the synchronization server to use the lowest timestamp precision for conflict detection purposes [page 1175]

The upload will be committed and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload [page 1175]

The upload will be rolled back and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload [page 1176]

The Z/M values were dropped from the upload spatial data [page 1176]

There are too many remote tasks to send to agent, '%1', at one time. The maximum number of remote tasks an agent can receive at one time is 255 [page 1177]

This connection will be abandoned due to a first read error [page 1177]

Unable to access ASE table 'master..systransactions'. The synchronization server will use system time for download [page 1178]

Unable to access Microsoft SQL Server virtual table 'sys.dm_tran_active_transactions'. The synchronization server will not use snapshot isolation [page 1178]

Unable to access ORACLE table 'gv\$transaction'. Access is needed to ensure no data is missed if using timestamp-based downloads [page 1179]

Unable to access SAP HANA Server system view 'SYS.M_TRANSACTIONS'. The synchronization server will not use snapshot isolation [page 1179]

Unable to authenticate the user '%1' against LDAP server [page 1179]

Unable to determine current timestamp from consolidated database [page 1180]

Unable to fetch the download timestamp from the consolidated database [page 1180]

Unable to fetch the UTC time from the database server [page 1181]

Unable to lock the remote ID '%1', will try again [page 1181]

Unable to open the file to store the client synchronization logs. The filename is '%1' [page 1181]

[Unable to record the schema \[page 1182\]](#)

[Unable to retrieve the column data types for table '%1' from the consolidated database \[page 1182\]](#)

[Unable to write to the local file that contains remote synchronization logs \[page 1183\]](#)

[Unknown users will be added automatically \(when there is no authenticate_user script\) \[page 1183\]](#)

[Unrecognized ODBC driver '%1'. The functionality and quality of ODBC drivers varies greatly. This driver may lack functionality required for successful synchronizations. Use at your own risk \[page 1184\]](#)

[Windows Firewall is enabled, and the synchronization server is not in the exception list. Clients on remote machines may not be able to connect to this server \[page 1184\]](#)

1.4.2.1 %1

Error code	10050
Parameter 1	A message from the ODBC driver.

Probable cause

The synchronization server made a successful ODBC call, but the ODBC driver displayed a warning message. Avoiding this message depends on the specific warning.

Related Information

[Character Set Conversion During Synchronization](#)
[ODBC Drivers for MobiLink](#)

1.4.2.2 '%1' row(s) were ignored in uploading data into table '%2'

Error code	10040
Parameter 1	The total number of ignored rows.
Parameter 2	Table name.

Probable cause

The synchronization server counts all the upload rows that were not applied to the consolidated database as ignored rows. This can happen if there are upload inserts/updates/deletes from the client, but there is no

upload_insert/upload_update/upload_delete script for the listed table in the consolidated database or errors occurred during uploading data into this table, but the handle_error/handle_odbc_error returned 1000.

Related Information

[Scripts to Upload Rows](#)

[Scripts to Handle Errors](#)

1.4.2.3 <OE>: '%1'

Error code	10107
Parameter 1	The warning.

Probable cause

The integrate outbound enabler had a warning.

Related Information

[The Outbound Enabler](#)

[-x mlsrv17 Option](#)

1.4.2.4 '%1'

Error code	10068
Parameter 1	A warning message.

Probable cause

Warning messages generated by .Net CLR.

Related Information

[Synchronization Scripts in Microsoft .NET](#)
[The CLR External Environment](#)
[-sl dnet mlsrv17 Option](#)

1.4.2.5 '%1' might not be a local address

Error code	10126
Parameter 1	The specified host

Probable cause

The synchronization server could not verify that a requested host uses a local IP address. This warning may be ignored if the host parameter specifies a local, virtual IP address.

1.4.2.6 A passthrough script failed at the remote client, run_order: '%1', script_id: '%2', error_code: '%3', error_text: ' '%4''

Error code	10091
Parameter 1	The run_order of the failed passthrough script.
Parameter 2	The script_id of the failed passthrough script.
Parameter 3	The error_code of the failed passthrough script.
Parameter 4	The error_text of the failed passthrough script.

Probable cause

Examine the error code and text and create a repair action for this script.

Related Information

[ml_add_passthrough_repair System Procedure](#)
[ml_delete_passthrough_repair System Procedure \(Deprecated\)](#)

[ml_add_passthrough](#) System Procedure
[ml_add_passthrough_script](#) System Procedure
[ml_delete_passthrough](#) System Procedure (Deprecated)
[ml_delete_passthrough_script](#) System Procedure (Deprecated)

1.4.2.7 An error occurred reading the remote client's synchronization log

Error code	10033
------------	-------

Probable cause

The synchronization server was unable to get the remote error log from the client. To avoid this warning, please do not kill the client when it is running and also make sure the network connection is okay.

Related Information

[-e mlsrv17 Option](#)
[-et mlsrv17 Option](#)
[ErrorLogSendLimit \(el\) Extended Option](#)

1.4.2.8 Client network protocol version is too new

Error code	10121
------------	-------

Probable cause

The synchronization server can not process this request because the server is too new. The client may be able to continue using an older network protocol. If further requests fail, please update your server.

1.4.2.9 Client network protocol version is too old

Error code	10120
------------	-------

Probable cause

The synchronization server can not process this request because the client is too old. Please update your client.

1.4.2.10 Client synchronization logs will be shown in the synchronization server message log file or the synchronization server messages window

Error code	10036
------------	-------

Probable cause

If an error occurs on the client side during synchronization, the client may send its output file to the server and the server will store this output file to a file specified using the server command line option -e or -et. However, if the synchronization server could not open this file for writing, it will show this warning message and will write the remote log into its message log file or messages window. To avoid this warning, please make sure the synchronization server has the privilege to write the file.

Related Information

[-e mlsrv17 Option](#)
[-et mlsrv17 Option](#)
[ErrorLogSendLimit \(el\) Extended Option](#)

1.4.2.11 Connection ID '%1' is currently blocked by connection ID ' '%2' for '%3' seconds on '%4'

Error code	10117
Parameter 1	A synchronization server database connection ID.
Parameter 2	Another database connection ID.
Parameter 3	Time in seconds.
Parameter 4	Table name or database operation that is currently blocked.

Probable cause

The synchronization server detects database operations that take longer than a given time and reports the database connection ID that is blocking the synchronization server connections.

1.4.2.12 Either '%1' does not exist or it does not contain any recorded protocol files (files with extension mlr)

Error code	10110
Parameter 1	The directory given with the rrp option.

Probable cause

Either use the '-rrp' option with a directory that contains recorded protocol files (files with extension mlr) or do not use the '-rrp' option.

Related Information

[-rrp mlsrv17 Option](#)

1.4.2.13 Error detected during multi-row operation, performing rollback before retrying in single row mode

Error code	10039
------------	-------

Probable cause

Errors were detected when the synchronization server applied the upload stream using multi-row mode. It will roll back the upload stream and retry the upload transaction in single-row mode.

1.4.2.14 Expecting at most '%1' parameter(s) in cursor, but found '%2'

Error code	10014
Parameter 1	The maximum number of parameter(s) expected.
Parameter 2	The number of parameter(s) found.

Probable cause

There is a maximum number of parameters for every cursor script in the synchronization server. If the number of parameters for the given cursor script is larger than the maximum number of parameters, the server will show this warning.

Related Information

[Scripts to Download Rows](#)

1.4.2.15 For table '%1', the number of entries in the ml_column table is greater than the number of columns in the remote table

Error code	10085
Parameter 1	Table name.

Probable cause

This warning tells you that you have extra column entries in the ml_column table for the given table. This is only a problem if (i) your synchronization scripts reference the column names via named parameters, and (ii) they reference a column name whose index is greater than the number of columns in the table. In this case, an error will be issued after this warning.

Related Information

[ml_add_column System Procedure \(Deprecated\)](#)

1.4.2.16 Generated too many Profiler phases

Error code	10128
------------	-------

Probable cause

The synchronization server generated too many Profiler phases. This indicates a bug in the synchronization server. Please contact tech support.

1.4.2.17 Initial cache size is smaller than the minimum cache size. Increasing initial size to '%1' bytes

Error code	10097
Parameter 1	The new initial cache size.

Probable cause

The -cinit option value is smaller than the -cmin option value.

Related Information

[-cinit mlsrv17 Option](#)

1.4.2.18 Initial cache size is too small. Increasing from '%1' to '%2' bytes

Error code	10096
Parameter 1	The given cache size.
Parameter 2	The new initial cache size.

Probable cause

The -cinit option value is too small.

Related Information

[-cinit mlsrv17 Option](#)

1.4.2.19 Initial number of concurrent database worker threads greater than maximum specified. Decreasing initial number from '%1' to '%2'

Error code	10123
Parameter 1	The given or default number of concurrent database worker threads.
Parameter 2	The new number of concurrent database worker threads.

Probable cause

The -w option value is smaller than the -wm option value.

Related Information

[-w mlsrv17 Option](#)
[-wm mlsrv17 Option](#)
[-wn mlsrv17 Option](#)
[-wu mlsrv17 Option](#)

1.4.2.20 Invalid log verbosity options: '%1'

Error code	10092
Parameter 1	Verbosity options.

Probable cause

The log verbosity options in the ml_property table are not valid. The valid verbosity options can be found from the synchronization server usage window.

Related Information

[ml_add_property System Procedure](#)
[-v mlsrv17 Option](#)

1.4.2.21 Loading a client Java VM

Error code	10109
------------	-------

Probable cause

The server could not find a server Java VM, so it loaded a client VM instead. Client VMs have significantly worse performance than server VMs. If you are intentionally using a client VM and want to suppress this warning, add -client to the -sl java options.

Related Information

[-sl java mlsrv17 Option](#)

1.4.2.22 Maximum cache size is smaller than the initial cache size. Increasing maximum size to '%1' bytes

Error code	10098
Parameter 1	The new maximum cache size.

Probable cause

The -cmax option value is smaller than the -cinit option value.

Related Information

[-cinit mlsrv17 Option](#)

1.4.2.23 Maximum cache size is too small. Increasing from '%1' to '%2' bytes

Error code	10095
Parameter 1	The given cache size.
Parameter 2	The new maximum cache size.

Probable cause

The -cmax option value is too small.

1.4.2.24 Maximum number of database connections set to '%1' (must be at least the number of database worker threads)

Error code	10001
Parameter 1	Maximum number of connections.

Probable cause

The synchronization server makes one connection for each database worker thread. Therefore, the maximum number of connections must be at least the number of database worker threads.

Related Information

[MobiLink Performance](#)

[MobiLink Tuning for Performance](#)

[-cn mlsrv17 Option](#)

[-w mlsrv17 Option](#)

[-wm mlsrv17 Option](#)

1.4.2.25 Minimum cache size is too small. Increasing from '%1' to '%2' bytes

Error code	10094
Parameter 1	The given cache size.
Parameter 2	The new minimum cache size.

Probable cause

The -cmin option value is too small.

1.4.2.26 No handle_error script is defined. The default action code (%1) will decide the error behavior

Error code	10010
Parameter 1	The error action code.

Probable cause

An error occurred in the synchronization server during synchronization. However there is no handle_error script defined in the consolidated database. The server will take the default action for the error. To avoid this warning, please define a handle_error script.

Related Information

[handle_error Connection Event](#)

1.4.2.27 No RTNotifier was started. Therefore, no remote tasks will be received by any agents

Error code	10105
------------	-------

Probable cause

No RTNotifier was started. Therefore, no remote tasks will be received by any agents. Make sure an RTNotifier is in the ml_property table.

Related Information

[Remote Task Notifier \(RTNotifier\)](#)
[ml_add_property System Procedure](#)

1.4.2.28 ODBC function '%1' is not supported by the driver

Error code	10004
Parameter 1	ODBC function name.

Probable cause

This function is required for the synchronization server to operate. Update your ODBC driver.

1.4.2.29 ODBC Isolation level (%1) is not supported

Error code	10003
Parameter 1	The required isolation level.

Probable cause

The required isolation level is not supported by the consolidated database. Determine if another level is suitable.

Related Information

[MobiLink Isolation Levels](#)

[Snapshot Isolation](#)

[How to Enable Snapshot Isolation](#)

1.4.2.30 ODBC statement option '%1' has changed from '%2' ('%3') to '%4' ('%5')

Error code	10005
Parameter 1	Name of the ODBC statement option.
Parameter 2	Original name of the setting.
Parameter 3	Original value of the setting.
Parameter 4	New name of the setting.
Parameter 5	New value of the setting.

Probable cause

The option has been changed by the ODBC driver. This may not be desirable.

1.4.2.31 ODBC statement option '%1' has changed from '%2' to '%3'

Error code	10006
Parameter 1	Name of the ODBC statement option.
Parameter 2	Original value of the setting.
Parameter 3	New value of the setting.

Probable cause

The option has been changed by the ODBC driver. This may not be desirable.

1.4.2.32 ODBC tracing is currently enabled. This will significantly degrade performance

Error code	10122
------------	-------

Probable cause

The synchronization server performance will be degraded when ODBC tracing is enabled. This warning will not be displayed when tracing has been enabled as a server option (-t or -tt).

Related Information

[Event Tracing](#)

1.4.2.33 Performance warning -- database connections have been recycled at a rate of '%1'%

Error code	10089
Parameter 1	Connection recycle rate.

Probable cause

The synchronization server maintains a pool of connections to the consolidated database to improve performance. Each pooled connection is associated with a script version. If the pool is full and there are no connection available for the requested version, then a pooled connection will be reconnected to get the required version. Please see the -cn switch for more information.

Related Information

[MobiLink Tuning for Performance](#)
[-cn mlsrv17 Option](#)

1.4.2.34 Performance warning: Column '%1' in the remote table '%2' has been remapped from '%3' to '%4'

Error code	10115
Parameter 1	Column index.
Parameter 2	Table name.
Parameter 3	Remote data type.
Parameter 4	Consolidated data type.

Probable cause

In order to properly complete the synchronization request, the synchronization server has remapped the column type. This remapping may decrease synchronization performance. See the documentation for information about data type mapping between consolidated and remote databases.

Related Information

[MobiLink Data Mappings Between Remote and Consolidated Databases](#)

1.4.2.35 Publication '%1' is not referenced by any table

Error code	10022
Parameter 1	Publication name.

Probable cause

The synchronization client sends an upload stream that includes upload data as well as upload tables, publications, and so on. All these publications must be referenced by at least one of the upload tables. If there are any publications that are not referenced by any upload table, the server will show this warning. If this happens, please contact technical support.

Related Information

[Publications](#)

[Publications for Scripted Upload](#)

[Adding Tables to Deployed SQL Anywhere Remote Databases](#)

[DROP PUBLICATION Statement \[MobiLink\] \[SQL Remote\]](#)

1.4.2.36 Resolve the timestamp precision mismatch by setting the SQL Anywhere DEFAULT_TIMESTAMP_INCREMENT option on the remote database to '%1' and TRUNCATE_TIMESTAMP_VALUES to 'On'. UltraLite remotes must set the TIMESTAMP_INCREMENT option to '%2'

Error code	10018
Parameter 1	Timestamp precision of the consolidated database in number of decimal digits in the fractional second.

Probable cause

This is an advisory on how to align timestamp precision by adjusting timestamp precision on the SQL Anywhere client database or the SQL Anywhere reference database for UltraLite clients. UltraLite clients need to be regenerated after the precision is adjusted.

Related Information

[default_timestamp_increment Option](#)

[truncate_timestamp_values Option](#)

[UltraLite timestamp_increment Creation Option](#)

[UltraLite Initialize Database Utility \(ulinit\)](#)

1.4.2.37 Retrying the begin_connection transaction after deadlock in the consolidated database

Error code	10007
------------	-------

Probable cause

Deadlock occurred in the transaction of begin_transaction in the consolidated database. To avoid this warning, please rewrite your begin_connection script to avoid deadlocks.

Related Information

[Overview of MobiLink Events](#)
[begin_connection Connection Event](#)

1.4.2.38 Retrying the begin_synchronization transaction after deadlock in the consolidated database

Error code	10048
------------	-------

Probable cause

Deadlock occurred when the synchronization server executed the begin_synchronization script. It will roll back the transaction and retry this script.

Related Information

[Overview of MobiLink Events](#)
[begin_synchronization Connection Event](#)

1.4.2.39 Retrying the end_synchronization transaction after deadlock in the consolidated database

Error code

10049

Probable cause

Deadlock occurred when the synchronization server executed the end_synchronization script. It will roll back the transaction and retry this script.

Related Information

[Overview of MobiLink Events](#)
[end_synchronization Connection Event](#)

1.4.2.40 Retrying the upload after conflicting update in the consolidated database

Error code

10080

Probable cause

A conflicting update occurred when the synchronization server was applying the upload stream with snapshot isolation. It will roll back the transaction and retry this script. To avoid this warning, please commit all the open transactions in all other applications that are connecting to this consolidated database.

Related Information

[Conflict Handling Overview](#)
[Snapshot Synchronization](#)

1.4.2.41 Retrying the upload after deadlock in the consolidated database

Error code	10045
------------	-------

Probable cause

Deadlock occurred when the synchronization server was applying the upload stream. It will roll back the transaction and retry this script. Avoid this warning by removing contention between synchronization scripts. There can also be contention between synchronization scripts and other applications.

Related Information

[Synchronization Scripts](#)

1.4.2.42 RETURN structure contained an warning

Error code	10124
------------	-------

Probable cause

details follow.

1.4.2.43 Spatial library warning: '%1'

Error code	10102
Parameter 1	The actual warning code generated by the spatial library.

Probable cause

Please look at the actual spatial library warning message to find the cause of the warning.

Related Information

[Synchronization of Spatial Data](#)

1.4.2.44 Synchronization request from client '%1' was rejected

Error code	10101
Parameter 1	Remote ID.

Probable cause

The synchronization server has rejected the synchronization request issued by the given client due to the number of concurrent synchronization requests being greater than the maximum number of concurrent active synchronizations allowed (specified by -sm).

Related Information

[MobiLink Performance](#)
[Concurrency During Synchronization](#)
[-sm mlsrv17 Option](#)

1.4.2.45 Synchronization server table '%1' is damaged

Error code	10009
Parameter 1	The synchronization server system table name.

Probable cause

The synchronization server was unable to get information from the listed table. Please make sure the table does exist and the database server is running.

Related Information

[MobiLink Server System Tables](#)

1.4.2.46 Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, downloaded timestamps can lose precision, resulting in inconsistent data

Error code	10016
Parameter 1	Table name.

Probable cause

A remote database is synchronizing a table with at least one timestamp column while the timestamp precision of the remote database is lower than that of the consolidated database. The downloaded value will lose precision after being stored into the remote database. This situation creates a virtual difference in the synchronized timestamp data between the consolidated database and the remote database. To avoid this data inconsistency problem, you should align timestamp precision across all databases involved in your synchronization system.

Related Information

[Ways to Send Dates and Times to the Database](#)

[TIMESTAMP Data Type](#)

[-zp mlsrv17 Option](#)

1.4.2.47 Table '%1' has at least one timestamp column. Due to a timestamp precision mismatch, uploaded timestamps can lose precision, defeating download filtering

Error code	10015
Parameter 1	Table name.

Probable cause

A remote database is synchronizing a table with at least one timestamp column while the timestamp precision on the remote database is higher than that of the consolidated database. The uploaded value will lose precision after being stored in the consolidated database. The synchronization server compares upload rows and download rows to filter away redundant download rows. The loss of precision may create a virtual difference that defeats the download filtering. This situation can affect download performance. To avoid this performance penalty, you should align timestamp precision across all databases involved in your synchronization system.

Related Information

[Ways to Send Dates and Times to the Database](#)
[TIMESTAMP Data Type](#)
[-zp mlsrv17 Option](#)

1.4.2.48 The client has provided '%1' authentication parameter(s), but no authenticate_parameters script exists

Error code	10055
Parameter 1	The number of authentication parameter(s).

Probable cause

The synchronization client sent the listed number of authentication parameters. However, there is no authentication parameter script defined in the consolidated database. To avoid this warning, please define the `authenticate_parameters` script in the consolidated database or do not send authentication parameter(s) from the client.

Related Information

[Authentication Parameters](#)
[authenticate_parameters Connection Event](#)

1.4.2.49 The command line option '%1' is ignored

Error code	10079
Parameter 1	Command line option.

Probable cause

The command line option is ignored by the synchronization server. Please make sure if the command line option can be applied.

Related Information

[MobiLink Server Options](#)

1.4.2.50 The consolidated and remote databases disagree on when the last synchronization took place, the progress offsets are '%1' in the consolidated database and '%2' in the remote database. The remote is being asked to send a new upload that starts at the last ...

Error code	10012
------------	-------

Probable cause

The synchronization server stores the remote ending log offsets in its system tables after every synchronization and it compares these ending log offsets with the remote beginning offsets when a new synchronization comes in. If the ending offsets do not match the beginning offsets, the server will show this warning and also inform the client about the mismatching offsets.

Related Information

[Log Translation Utility \(dbtran\)](#)

1.4.2.51 The consolidated and remote databases have different timestamp precisions. Consolidated database timestamps are precise to '%1' digit(s) in the fractional second while the remote database timestamps are precise to '%2' digit(s)

Error code	10017
Parameter 1	Timestamp precision of the consolidated database in number of decimal digits in the fractional second.
Parameter 2	Timestamp precision of the remote database in number of decimal digits in the fractional second.

Probable cause

Inconsistent timestamp precisions were found between the remote database and the consolidated database. Align the databases to the same precision to avoid a performance penalty or inconsistent data.

Related Information

[Ways to Send Dates and Times to the Database](#)

[TIMESTAMP Data Type](#)

[-zp mlsrv17 Option](#)

1.4.2.52 The current SQL statement has been running for too long in the consolidated database. The connection ID is '%1'

Error code	10088
------------	-------

Probable cause

The synchronization server has detected the SQL statement has been running for too long and the synchronization may be stuck. Please check the consolidated database server to see if the connection is still healthy

Related Information

[MobiLink Performance](#)

1.4.2.53 The earliest transaction has been running for '%1' seconds

Error code	10116
Parameter 1	The oldest transaction running time in seconds.

Probable cause

With snapshot isolation for download, an open transaction would prevent the synchronization server to advance the next last download time to the current timestamp and then it will generate lots redundant rows in the next download. To avoid this problem, try to reduce the transaction open time.

Related Information

[Snapshot Synchronization](#)

1.4.2.54 The following option has been deprecated: '%1'

Error code	10108
Parameter 1	The deprecated option.

Probable cause

The option specified has been deprecated. This option will be removed in a future version. Please consult the documentation to remove the usage of this option.

Related Information

[MobiLink Server Options](#)

1.4.2.55 The remote and consolidated databases have different timestamp precisions, and a timestamp value with a precision higher than the lower-precision side was used for conflict detection purposes. Consider using the -zp option

Error code

10021

Probable cause

An upload conflict is detected based on a tolerable timestamp difference while the -zp command line option is not used. If you decided not to align precision on the databases involved in your synchronization system, you may use the -zp switch to start the synchronization server. If the command line option is used, synchronization server will tolerate conflict caused by timestamp differences smaller than the lower precision among the two databases.

Related Information

[Conflict Handling Overview](#)

[Ways to Send Dates and Times to the Database](#)

[TIMESTAMP Data Type](#)

[-zp mlsrv17 Option](#)

1.4.2.56 The remote client's synchronization log ended prematurely, and was probably truncated

Error code

10035

Probable cause

The synchronization server was not able to completely get the remote error log from the client, so the remote error log may have been truncated. To avoid this warning, please do not kill the client when it is running and also make sure the network connection is okay.

Related Information

[-e mlsrv17 Option](#)
[-et mlsrv17 Option](#)
[ErrorLogSendLimit \(el\) Extended Option](#)

1.4.2.57 The remote database is not capable of matching the timestamp precision of the consolidated database. Your application, schema, and scripts must contain logic that copes with the precision mismatch

Error code	10019
------------	-------

Probable cause

Timestamp precision of the consolidated database is higher than attainable by the remote database. If possible you may lower the timestamp precision on the consolidated database to avoid inconsistent timestamp data between the remote and the consolidated database. Otherwise, you may need to avoid synchronizing timestamps in your synchronization schema; or you may need to have conflict detection scripts aware of the virtual difference; or you may need to use the `-zp` command line option to tolerate the conflict. Your application should also be able to deal with the inconsistency.

Related Information

[Ways to Send Dates and Times to the Database](#)
[TIMESTAMP Data Type](#)
[-zp mlsrv17 Option](#)

1.4.2.58 The synchronization server has suspended network reads on this synchronization due to a limit on concurrent synchronizations

Error code	10083
------------	-------

Probable cause

The synchronization server will suspend any new synchronization connections when the maximum number of concurrent synchronizations has been exceeded. This limit is set using the -sm option.

Related Information

[-sm mlsrv17 Option](#)

1.4.2.59 The synchronization server has swapped data pages to disk out:%1 in: '%2' concurrently used pages: '%3'

Error code	10082
Parameter 1	Total count of pages swapped out.
Parameter 2	Total count of pages swapped in.
Parameter 3	Count of concurrently used disk pages.

Probable cause

The synchronization server may write data out to disk that cannot fit in its cache memory. The server prints warning message to the log when this happens so that the user may determine if this is a performance problem. The -cm option controls the server cache memory size.

1.4.2.60 The synchronization server is currently running with -zf that will reduce its performance

Error code	10093
------------	-------

Probable cause

The synchronization server checks for script changes at the beginning of each synchronization, when it is started with -zf. This switch is intended to be used in a development environment where scripts may be changed after the synchronization server is started.

Related Information

[-zf mlsrv17 Option](#)

1.4.2.61 The synchronization server restarted network reads on this synchronization due to a drop in the number of concurrent synchronizations

Error code	10084
------------	-------

Probable cause

The synchronization server will restart reads on a synchronization that was stopped due to a limit on concurrent synchronizations. This limit is set using the -sm option.

Related Information

[-sm mlsrv17 Option](#)

1.4.2.62 The synchronization server will record all synchronizations

Error code	10100
------------	-------

Probable cause

The synchronization server will record all synchronizations.

Related Information

[Scripts and the Synchronization Process](#)

1.4.2.63 The timestamp precision mismatch may affect upload conflict detection. Use the -zp option to cause the synchronization server to use the lowest timestamp precision for conflict detection purposes

Error code

10020

Probable cause

Timestamp precision mismatch between the remote database and the consolidated database has been detected. The mismatch can affect upload conflict detection as the synchronization server will compare the rows for the two databases. If you decided not to align precision on the databases involved in your synchronization system, you may use the -zp switch to start the synchronization server. If this command line option is used, the synchronization server will tolerate conflict caused by timestamp differences smaller than the lower precision among the two databases.

Related Information

[Conflict Handling Overview](#)

[Ways to Send Dates and Times to the Database](#)

[TIMESTAMP Data Type](#)

[-zp mlsrv17 Option](#)

1.4.2.64 The upload will be committed and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload

Error code

10041

Probable cause

This is an internal warning that is primarily used for testing, but may also be seen as part of technical support engagements.

Related Information

[Scripts to Upload Rows](#)
[COMMIT Statement](#)

1.4.2.65 The upload will be rolled back and the synchronization aborted. The next time this remote synchronizes, it will ask what happened to the previous upload

Error code	10023
------------	-------

Probable cause

This is an internal warning that is primarily used for testing, but may also be seen as part of technical support engagements.

Related Information

[Scripts to Upload Rows](#)
[COMMIT Statement](#)

1.4.2.66 The Z/M values were dropped from the upload spatial data

Error code	10103
------------	-------

Probable cause

The synchronization server has dropped the Z/M values from the upload spatial data, because the consolidated database does not accept them in WKB.

Related Information

[Synchronization of Spatial Data](#)

1.4.2.67 There are too many remote tasks to send to agent, '%1', at one time. The maximum number of remote tasks an agent can receive at one time is 255

Error code	10104
Parameter 1	The agent name.

Probable cause

There are too many remote tasks to send to an agent at one time. The maximum number of remote tasks an agent can receive at one time is 255.

Related Information

[Server-initiated Remote Tasks \(SIRT\)](#)

1.4.2.68 This connection will be abandoned due to a first read error

Error code	10125
------------	-------

Probable cause

A connection was made to the socket on which the synchronization server was listening, but the first attempt to read data from the socket resulted in a failure.

1.4.2.69 Unable to access ASE table 'master..systransactions'. The synchronization server will use system time for download

Error code

10087

Probable cause

The synchronization server needs to access some tables in the master database to get transaction starting time during synchronization. Please make sure the userid used to connect the synchronization server to the Microsoft SQL Server has permission to access the 'master..systransactions' table.

Related Information

[Adaptive Server Enterprise Consolidated Database](#)

1.4.2.70 Unable to access Microsoft SQL Server virtual table 'sys.dm_tran_active_transactions'. The synchronization server will not use snapshot isolation

Error code

10078

Probable cause

The synchronization server needs to access some virtual tables to use snapshot isolation during synchronization. Please make sure the userid used to connect the synchronization server to the Microsoft SQL Server has permission to access the 'sys.dm_tran_active_transactions' table.

Related Information

[Snapshot Synchronization](#)
[Microsoft SQL Server and Microsoft Azure Consolidated Databases](#)

1.4.2.71 Unable to access ORACLE table 'gv\$transaction'. Access is needed to ensure no data is missed if using timestamp-based downloads

Error code

10075

Probable cause

The timestamp generated to filter the download may be incorrect due to ORACLE's non-blocking read feature. Please make sure the userid used to connect the synchronization server to the ORACLE database has permission to access the gv\$transaction table.

Related Information

[Oracle Consolidated Database](#)

1.4.2.72 Unable to access SAP HANA Server system view 'SYS.M_TRANSACTIONS'. The synchronization server will not use snapshot isolation

Error code

10127

Probable cause

The synchronization server needs to access some system tables or views to use snapshot isolation during synchronization. Please make sure the userid used to connect the synchronization server to the SAP HANA Server has permission to access the 'SYS.M_TRANSACTIONS' view.

1.4.2.73 Unable to authenticate the user '%1' against LDAP server

Error code

10118

Parameter 1

The user name.

Probable cause

The synchronization server was not able to authenticate the user against the LDAP servers. Please make sure the LDAP servers are up running or the user authentication policy is configurated properly.

1.4.2.74 Unable to determine current timestamp from consolidated database

Error code	10043
------------	-------

Probable cause

The synchronization server was not able to get the current timestamp from the consolidated database. Please make sure the database server is running and the network connection is okay.

Related Information

[CURRENT_TIMESTAMP Special Value](#)

1.4.2.75 Unable to fetch the download timestamp from the consolidated database

Error code	10074
------------	-------

Probable cause

The synchronization server was unable to get the download timestamp from the consolidated database. Please make sure the database server is running and the network connection is okay.

Related Information

[How Download Timestamps Are Generated and Used modify_last_download_timestamp Connection Event](#)

1.4.2.76 Unable to fetch the UTC time from the database server

Error code	10119
------------	-------

Probable cause

The synchronization server uses the database server UTC time to order sync requests. However, it was not able to fetch the UTC time from the database server within less than 1 second, so it will use the UTC time from local OS.

1.4.2.77 Unable to lock the remote ID '%1', will try again

Error code	10106
Parameter 1	Remote ID.

Probable cause

The synchronization server needs to lock the remote ID in order to detect concurrent synchronizations with the same remote ID. The server was not able to lock the given remote ID, but it will try to again.

1.4.2.78 Unable to open the file to store the client synchronization logs. The filename is '%1'

Error code	10032
Parameter 1	File name.

Probable cause

The synchronization server was unable to open the local remote log file given by option -e or -et. Please make sure the file name and path are valid and the file is writable.

Related Information

[-e mlsrv17 Option](#)
[-et mlsrv17 Option](#)
[ErrorLogSendLimit \(el\) Extended Option](#)

1.4.2.79 Unable to record the schema

Error code	10099
------------	-------

Probable cause

The synchronization server was unable to record the schema for the synchronization; which implies this synchronization cannot be replayed with different data.

1.4.2.80 Unable to retrieve the column data types for table '%1' from the consolidated database

Error code	10081
Parameter 1	Table name.

Probable cause

The synchronization server was not able to retrieve the column data types for the given table from the consolidated database using SQLDescribeParam. Therefore the server will assume that the data types for this table in the consolidated database are equivalent to those defined in the remote database.

Related Information

[64-bit ODBC Considerations](#)

1.4.2.81 Unable to write to the local file that contains remote synchronization logs

Error code

10034

Probable cause

The synchronization server was unable to write the remote error log to a local file. To avoid this warning, please make sure the file name and path given by option `-e` or `-et` are valid and the file is writable.

Related Information

[-e mlsrv17 Option](#)

[-et mlsrv17 Option](#)

[ErrorLogSendLimit \(el\) Extended Option](#)

1.4.2.82 Unknown users will be added automatically (when there is no `authenticate_user` script)

Error code

10064

Probable cause

This is a friendly warning message when the synchronization server command line option, `-zu+` is used.

Related Information

[-zu mlsrv17 Option](#)

[authenticate_user Connection Event](#)

1.4.2.83 Unrecognized ODBC driver '%1'. The functionality and quality of ODBC drivers varies greatly. This driver may lack functionality required for successful synchronizations. Use at your own risk

Error code	10051
Parameter 1	The file name of an ODBC driver.

Probable cause

The synchronization server is very well tested with a set of ODBC drivers. However, the ODBC driver you are currently using is not on the list. To avoid this warning, please run the synchronization server with a recommended ODBC driver.

1.4.2.84 Windows Firewall is enabled, and the synchronization server is not in the exception list. Clients on remote machines may not be able to connect to this server

Error code	10073
------------	-------

Probable cause

The Windows Firewall is enabled and either the synchronization server is not in the exception list or it is in the exception list but disabled. This configuration will prevent remote clients from connecting to the server.

1.5 MobiLink Communication Error Messages

The error messages are written to the MobiLink server message log and the MobiLink SQL Anywhere client message log. The error codes are returned to UltraLite clients in the `ss_error_code` member of the `stream_error` parameter.

Each error has a numeric error code. Both error and warning codes are positive. Warning codes are greater than 10000.

Many of the error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.

In this section:

[MobiLink Communication Error Messages Sorted by Error Code \[page 1185\]](#)

[MobiLink Communication Error Messages Listed by Message Text \[page 1191\]](#)

Related Information

[MobiLink Server Error Messages \[page 967\]](#)

[MobiLink Server Warning Messages \[page 1137\]](#)

1.5.1 MobiLink Communication Error Messages Sorted by Error Code

Error code	Message text
0	No error [page 1222]
1	Invalid parameter '%1' [page 1216]
2	Parameter value '%1' is not an unsigned integer [page 1227]
3	Parameter value '%1' is not an unsigned integer value or range. A range has the form NNN-NNN [page 1227]
4	Parameter value '%1' is not a valid boolean value. The value must be 0 or 1 [page 1226]
5	Parameter value '%1' is not a valid hexadecimal value [page 1226]
6	Unable to allocate sufficient memory [page 1240]
7	Unable to parse the parameter string '%1' [page 1254]
8	Unable to read %1 bytes [page 1255]
9	Unable to write %1 bytes [page 1270]
10	An end write failed [page 1201]
11	An end read failed [page 1200]
12	Feature not implemented [page 1209]
13	The operation would cause blocking [page 1235]
14	Unable to generate a random number [page 1249]
15	Unable to initialize the random number generator [page 1251]
16	Unable to seed the random number generator [page 1258]
17	Unable to create a random number object [page 1244]

Error code	Message text
18	An error occurred during shutdown [page 1201]
19	Unable to dequeue from the connection queue [page 1246]
20	Invalid root certificate [page 1217]
21	Unrecognized organization '%1' [page 1276]
24	Server certificate not trusted [page 1233]
25	Unable to duplicate security context [page 1247]
26	Unable to attach the network layer to the security layer [page 1241]
33	Unable to open certificate file '%1' [page 1253]
34	Unable to read certificates [page 1255]
35	Unable to read the private key [page 1257]
36	Unable to set the private key [page 1259]
37	Unable to fetch a certificate expiry date [page 1248]
38	Unable to copy a certificate [page 1244]
39	Unable to add a certificate to a certificate chain [page 1239]
40	Unable to find the trusted certificate file '%1' [page 1248]
41	Error reading from the trusted certificate file '%1' [page 1204]
42	No trusted certificates found in %1 [page 1224]
43	Unable to allocate a certificate [page 1240]
44	Unable to import a certificate [page 1251]
48	Unable to add a trusted certificate [page 1240]
49	Unable to create a private key object [page 1244]
50	A certificate has expired [page 1197]
51	Unrecognized organization unit '%1' [page 1276]
52	Unrecognized common name '%1' [page 1275]
53	Handshake error [page 1209]
54	Unsupported HTTP version: %1 [page 1278]
57	The host name '%1' could not be found [page 1234]
58	Unable to create a TCP/IP socket [page 1245]
59	Unable to create a UDP socket [page 1245]
60	Unable to bind a socket to port %1 [page 1241]
61	Unable to clean up the socket layer [page 1242]
62	Unable to close a socket [page 1242]
63	Unable to connect a socket [page 1242]

Error code	Message text
64	Unable to get a socket's local name [page 1249]
65	Unable to get socket option number %1 [page 1250]
66	Unable to set socket option number %1 [page 1258]
67	Unable to listen on a socket. The backlog is %1 [page 1252]
68	Unable to shut down a socket [page 1259]
69	Unable to select a socket status [page 1258]
70	Unable to initialize the sockets layer [page 1251]
71	Unable to determine localhost [page 1247]
72	Unable to get host by address [page 1250]
73	Unable to load the network interface library [page 1252]
74	Invalid port number %1. The value must be between zero and 65535 [page 1216]
75	ActiveSync synchronization cannot be initiated by an application [page 1200]
76	ActiveSync provider has not been installed [page 1199]
77	The content type '%1' is unknown [page 1234]
78	Client id is not available for use in HTTP header [page 1203]
79	The HTTP buffer size specified is out of the valid range [page 1235]
80	Extra data found in the HTTP body: %1 [page 1205]
81	Failed to read encoded CR LF [page 1208]
82	Failed to read CR LF [page 1208]
83	Timed out while waiting for the next HTTP request in this synchronization [page 1239]
84	Failed to read encoded chunk length [page 1208]
85	An unexpected character was read while parsing the chunk length. %1 [page 1202]
86	An error status was returned: '%1' [page 1202]
87	Unknown transfer encoding: '%1' [page 1275]
88	Unable to parse cookie: '%1' [page 1254]
89	Expected data from remote but current request is not a POST [page 1205]
200	Invalid liveness timeout value %1. The value must be between zero and 65535 [page 1215]
201	Timed out trying to read %1 bytes [page 1238]
202	Timed out trying to write %1 bytes [page 1238]

Error code	Message text
203	Automatic dialup is not supported on this machine [page 1202]
204	Failed dialing to %1 [page 1206]
205	No server certificate was provided [page 1224]
206	No server certificate password was provided [page 1223]
207	No trusted root certificates were provided [page 1224]
208	Password specified for an unencrypted server key [page 1228]
209	A userid and password are required for HTTP authentication [page 1198]
210	A userid and password are required for HTTP proxy authentication [page 1199]
211	HTTP Authentication failed [page 1210]
212	HTTP Proxy Authentication failed [page 1211]
213	No userid was supplied [page 1225]
214	No password was supplied [page 1222]
215	Unsupported http authentication algorithm: %1 [page 1277]
216	Error parsing HTTP header: %1 [page 1204]
217	HTTP server authentication failed [page 1211]
218	Operation interrupted [page 1225]
219	Invalid HTTP character [page 1214]
220	Internal error (%1) [page 1212]
221	Failed to open system certificate store [page 1207]
222	Failed to import a certificate from the system certificate store [page 1206]
223	No certificate found in system certificate store [page 1222]
224	Failed to load library %1 [page 1207]
225	Function %1 could not be found [page 1209]
226	Invalid synchronization protocol: %1 [page 1218]
227	Internal protocol not loaded: %1 [page 1212]
228	Server error %1 [page 1233]
229	Missing parameter: %1 [page 1220]
230	Could not open %1 for write [page 1203]
231	Protocol error [page 1228]
232	Invalid compression type: %1 [page 1213]
233	The value specified for %1 is out of range [page 1236]

Error code	Message text
234	Unexpected request type: %1 [page 1273]
235	Malformed session cookie (ML_SESSION_ID) value: %1 [page 1218]
236	Unexpected HTTP state %1 when decoding the header [page 1271]
237	Unexpected internal HTTP request type %1 [page 1271]
238	Internal error: %1 returned %2 [page 1212]
240	Unrecognized TLS type %1 [page 1277]
241	Connection attempt timed out [page 1203]
242	A secure stream has FIPS explicitly disabled, but the -fips option is in effect [page 1198]
243	Invalid destination path %1 for the downloaded file [page 1213]
244	The session key type '%1' is unknown [page 1236]
245	Invalid or corrupt network interface library: %1 [page 1215]
248	Network interface library version mismatch. Expecting version %1.%2, but found version %3.%4 [page 1221]
249	Synchronization server authentication failed [page 1233]
250	SACI implementation mismatch [page 1232]
251	Unknown public key end-to-end encryption type sent from client: %1 [page 1274]
252	Unexpected public key end-to-end encryption type. Expecting %1 but received %2 [page 1272]
253	Mismatched end-to-end encryption keys [page 1218]
254	Unexpected private key type. Expecting %1 but found %2 in the e2ee_private_key file '%3' [page 1272]
255	Unable to read the e2ee_private_key file '%1'. The error code is %2 [page 1256]
256	There is no private key in the e2ee_private_key file '%1' [page 1237]
257	Unable to decode the e2ee_private_key file '%1'. The error code is %2 [page 1246]
258	Unable to read the e2ee_private_key file '%1'. The error code is %2 [page 1257]
259	Missing e2ee_private_key_password for the e2ee_private_key file '%1' [page 1219]
260	Missing e2ee_private_key [page 1219]
261	Invalid e2ee_type '%1' [page 1214]
263	Unable to read the e2ee public key [page 1256]

Error code	Message text
264	Unable to open '%1' [page 1253]
265	Unable to continue unknown HTTP session [page 1243]
266	%1 [page 1197]
277	Failed reading an incomplete HTTP request [page 1206]
278	Unknown HTTP User-Agent or request type [page 1274]
279	This connection will be abandoned because of previous errors [page 1237]
280	Received non-HTTP traffic on port %1 [page 1230]
281	Received encrypted traffic instead of HTTP traffic on port %1 [page 1229]
282	Received end-to-end encrypted traffic instead of HTTP traffic on port %1 [page 1229]
283	Received unencrypted traffic on port %1 [page 1231]
284	Received unencrypted HTTP traffic on port %1 [page 1231]
285	Received end-to-end, but not transport layer security encrypted traffic on port %1 [page 1230]
286	Received out of order HTTP request on port %1 [page 1231]
287	Incorrect password for private key [page 1211]
288	Request headers too large [page 1232]
289	ml-session-id changed from %1 to %2 [page 1220]
290	Unable to validate peer certificate '%1': unable to find the issuer certificate [page 1267]
291	Unable to validate peer certificate '%1': unable to decrypt the certificate signature [page 1267]
292	Unable to validate peer certificate '%1': unable to decode the issuer public key [page 1266]
293	Unable to validate peer certificate '%1': unable to verify the certificate signature [page 1269]
294	Unable to validate peer certificate '%1': the certificate is not yet valid [page 1266]
295	Unable to validate peer certificate '%1': the certificate has expired [page 1265]
296	Unable to validate peer certificate '%1': format error in the certificate notBefore field [page 1262]
297	Unable to validate peer certificate '%1': format error in the certificate notAfter field [page 1261]
298	Unable to validate peer certificate '%1': self-signed certificate [page 1264]
299	Unable to validate peer certificate '%1': root certificate is not trusted [page 1265]

Error code	Message text
300	Unable to validate peer certificate '%1': unable to get local issuer certificate [page 1268]
301	Unable to validate peer certificate '%1': unable to verify the first certificate [page 1269]
302	Unable to validate peer certificate '%1': certificate chain too long [page 1260]
303	Unable to validate peer certificate '%1': invalid CA certificate [page 1263]
304	Unable to validate peer certificate '%1': path length constraint exceeded [page 1264]
305	Unable to validate peer certificate '%1': unsupported certificate purpose [page 1270]
306	Unable to validate peer certificate '%1': certificate not trusted [page 1260]
307	Unable to validate peer certificate '%1': certificate rejected [page 1261]
308	Unable to validate peer certificate '%1': general error [page 1262]
309	Unable to enable FIPS mode: %1 [page 1248]
310	An error occurred while writing to %1 [page 1201]
311	Invalid SAP passport: %1 [page 1217]
312	Unable to load MLSACIGetE2EEIface [page 1252]
313	Network communications failure: %1 [page 1221]
314	No peer certificate validation parameters were provided [page 1223]
315	The value for option '%1' is incompatible with the value for option '%2' [page 1236]
316	A request by a proxy server to do Basic HTTP authentication was rejected [page 1198]
317	Hostname '%1!s!' check against server identity failed [page 1210]
318	Invalid HTTP session ID received from the synchronization server [page 1215]
319	Unexpected response received [page 1273]

1.5.2 MobiLink Communication Error Messages Listed by Message Text

In this section:

%1 [page 1197]

A certificate has expired [page 1197]

A request by a proxy server to do Basic HTTP authentication was rejected [page 1198]

A secure stream has FIPS explicitly disabled, but the -fips option is in effect [page 1198]

A userid and password are required for HTTP authentication [page 1198]

A userid and password are required for HTTP proxy authentication [page 1199]

ActiveSync provider has not been installed [page 1199]

ActiveSync synchronization cannot be initiated by an application [page 1200]

An end read failed [page 1200]

An end write failed [page 1201]

An error occurred during shutdown [page 1201]

An error occurred while writing to %1 [page 1201]

An error status was returned: '%1' [page 1202]

An unexpected character was read while parsing the chunk length. %1 [page 1202]

Automatic dialup is not supported on this machine [page 1202]

Client id is not available for use in HTTP header [page 1203]

Connection attempt timed out [page 1203]

Could not open %1 for write [page 1203]

Error parsing HTTP header: %1 [page 1204]

Error reading from the trusted certificate file '%1' [page 1204]

Expected data from remote but current request is not a POST [page 1205]

Extra data found in the HTTP body: %1 [page 1205]

Failed dialing to %1 [page 1206]

Failed reading an incomplete HTTP request [page 1206]

Failed to import a certificate from the system certificate store [page 1206]

Failed to load library %1 [page 1207]

Failed to open system certificate store [page 1207]

Failed to read CR LF [page 1208]

Failed to read encoded chunk length [page 1208]

Failed to read encoded CR LF [page 1208]

Feature not implemented [page 1209]

Function %1 could not be found [page 1209]

Handshake error [page 1209]

Hostname '%1!s!' check against server identity failed [page 1210]

HTTP Authentication failed [page 1210]

HTTP Proxy Authentication failed [page 1211]

HTTP server authentication failed [page 1211]

Incorrect password for private key [page 1211]

Internal error (%1) [page 1212]

Internal error: %1 returned %2 [page 1212]

Internal protocol not loaded: %1 [page 1212]

Invalid compression type: %1 [page 1213]

Invalid destination path %1 for the downloaded file [page 1213]

Invalid e2ee_type '%1' [page 1214]

Invalid HTTP character [page 1214]

Invalid HTTP session ID received from the synchronization server [page 1215]

Invalid liveness timeout value %1. The value must be between zero and 65535 [page 1215]

Invalid or corrupt network interface library: %1 [page 1215]

Invalid parameter '%1' [page 1216]

Invalid port number %1. The value must be between zero and 65535 [page 1216]

Invalid root certificate [page 1217]

Invalid SAP passport: %1 [page 1217]

Invalid synchronization protocol: %1 [page 1218]

Malformed session cookie (ML_SESSION_ID) value: %1 [page 1218]

Mismatched end-to-end encryption keys [page 1218]

Missing e2ee_private_key [page 1219]

Missing e2ee_private_key_password for the e2ee_private_key file '%1' [page 1219]

Missing parameter: %1 [page 1220]

ml-session-id changed from %1 to %2 [page 1220]

Network communications failure: %1 [page 1221]

Network interface library version mismatch. Expecting version %1.%2, but found version %3.%4 [page 1221]

No certificate found in system certificate store [page 1222]

No error [page 1222]

No password was supplied [page 1222]

No peer certificate validation parameters were provided [page 1223]

No server certificate password was provided [page 1223]

No server certificate was provided [page 1224]

No trusted certificates found in %1 [page 1224]

No trusted root certificates were provided [page 1224]

No userid was supplied [page 1225]

Operation interrupted [page 1225]

Parameter value '%1' is not a valid boolean value. The value must be 0 or 1 [page 1226]

Parameter value '%1' is not a valid hexadecimal value [page 1226]

Parameter value '%1' is not an unsigned integer [page 1227]

Parameter value '%1' is not an unsigned integer value or range. A range has the form NNN-NNN [page 1227]

Password specified for an unencrypted server key [page 1228]

Protocol error [page 1228]

Received encrypted traffic instead of HTTP traffic on port %1 [page 1229]

Received end-to-end encrypted traffic instead of HTTP traffic on port %1 [page 1229]

Received end-to-end, but not transport layer security encrypted traffic on port %1 [page 1230]

Received non-HTTP traffic on port %1 [page 1230]

Received out of order HTTP request on port %1 [page 1231]

Received unencrypted HTTP traffic on port %1 [page 1231]

Received unencrypted traffic on port %1 [page 1231]

Request headers too large [page 1232]

SACI implementation mismatch [page 1232]

Server certificate not trusted [page 1233]

Server error %1 [page 1233]

Synchronization server authentication failed [page 1233]

The content type '%1' is unknown [page 1234]

The host name '%1' could not be found [page 1234]

The HTTP buffer size specified is out of the valid range [page 1235]

The operation would cause blocking [page 1235]

The session key type '%1' is unknown [page 1236]

The value for option '%1' is incompatible with the value for option '%2' [page 1236]

The value specified for %1 is out of range [page 1236]

There is no private key in the e2ee_private_key file '%1' [page 1237]

This connection will be abandoned because of previous errors [page 1237]

Timed out trying to read %1 bytes [page 1238]

Timed out trying to write %1 bytes [page 1238]

Timed out while waiting for the next HTTP request in this synchronization [page 1239]

Unable to add a certificate to a certificate chain [page 1239]

Unable to add a trusted certificate [page 1240]

Unable to allocate a certificate [page 1240]

Unable to allocate sufficient memory [page 1240]

Unable to attach the network layer to the security layer [page 1241]

Unable to bind a socket to port %1 [page 1241]

Unable to clean up the socket layer [page 1242]

Unable to close a socket [page 1242]

Unable to connect a socket [page 1242]

Unable to continue unknown HTTP session [page 1243]

Unable to copy a certificate [page 1244]

Unable to create a private key object [page 1244]

Unable to create a random number object [page 1244]

Unable to create a TCP/IP socket [page 1245]

Unable to create a UDP socket [page 1245]

Unable to decode the e2ee_private_key file '%1'. The error code is %2 [page 1246]

Unable to dequeue from the connection queue [page 1246]

Unable to determine localhost [page 1247]

Unable to duplicate security context [page 1247]

Unable to enable FIPS mode: %1 [page 1248]

Unable to fetch a certificate expiry date [page 1248]

Unable to find the trusted certificate file '%1' [page 1248]

Unable to generate a random number [page 1249]

Unable to get a socket's local name [page 1249]

Unable to get host by address [page 1250]

Unable to get socket option number %1 [page 1250]

Unable to import a certificate [page 1251]

Unable to initialize the random number generator [page 1251]

Unable to initialize the sockets layer [page 1251]

Unable to listen on a socket. The backlog is %1 [page 1252]

Unable to load MLSACIGetE2EEiface [page 1252]

Unable to load the network interface library [page 1252]

Unable to open '%1' [page 1253]

Unable to open certificate file '%1' [page 1253]

Unable to parse cookie: '%1' [page 1254]

Unable to parse the parameter string '%1' [page 1254]

Unable to read %1 bytes [page 1255]

Unable to read certificates [page 1255]

Unable to read the e2ee public key [page 1256]

Unable to read the e2ee_private_key file '%1'. The error code is %2 [page 1256]
Unable to read the e2ee_private_key file '%1'. The error code is %2 [page 1257]
Unable to read the private key [page 1257]
Unable to seed the random number generator [page 1258]
Unable to select a socket status [page 1258]
Unable to set socket option number %1 [page 1258]
Unable to set the private key [page 1259]
Unable to shut down a socket [page 1259]
Unable to validate peer certificate '%1': certificate chain too long [page 1260]
Unable to validate peer certificate '%1': certificate not trusted [page 1260]
Unable to validate peer certificate '%1': certificate rejected [page 1261]
Unable to validate peer certificate '%1': format error in the certificate notAfter field [page 1261]
Unable to validate peer certificate '%1': format error in the certificate notBefore field [page 1262]
Unable to validate peer certificate '%1': general error [page 1262]
Unable to validate peer certificate '%1': invalid CA certificate [page 1263]
Unable to validate peer certificate '%1': path length constraint exceeded [page 1264]
Unable to validate peer certificate '%1': self-signed certificate [page 1264]
Unable to validate peer certificate '%1': root certificate is not trusted [page 1265]
Unable to validate peer certificate '%1': the certificate has expired [page 1265]
Unable to validate peer certificate '%1': the certificate is not yet valid [page 1266]
Unable to validate peer certificate '%1': unable to decode the issuer public key [page 1266]
Unable to validate peer certificate '%1': unable to decrypt the certificate signature [page 1267]
Unable to validate peer certificate '%1': unable to find the issuer certificate [page 1267]
Unable to validate peer certificate '%1': unable to get local issuer certificate [page 1268]
Unable to validate peer certificate '%1': unable to verify the certificate signature [page 1269]
Unable to validate peer certificate '%1': unable to verify the first certificate [page 1269]
Unable to validate peer certificate '%1': unsupported certificate purpose [page 1270]
Unable to write %1 bytes [page 1270]
Unexpected HTTP state %1 when decoding the header [page 1271]
Unexpected internal HTTP request type %1 [page 1271]
Unexpected private key type. Expecting %1 but found %2 in the e2ee_private_key file '%3' [page 1272]
Unexpected public key end-to-end encryption type. Expecting %1 but received %2 [page 1272]
Unexpected request type: %1 [page 1273]
Unexpected response received [page 1273]
Unknown HTTP User-Agent or request type [page 1274]

[Unknown public key end-to-end encryption type sent from client: %1 \[page 1274\]](#)

[Unknown transfer encoding: '%1' \[page 1275\]](#)

[Unrecognized common name '%1' \[page 1275\]](#)

[Unrecognized organization '%1' \[page 1276\]](#)

[Unrecognized organization unit '%1' \[page 1276\]](#)

[Unrecognized TLS type %1 \[page 1277\]](#)

[Unsupported http authentication algorithm: %1 \[page 1277\]](#)

[Unsupported HTTP version: %1 \[page 1278\]](#)

1.5.2.1 %1

Error code	266
Error constant	SACI_ERROR
Parameter 1	The description of the SACI error.

Probable cause

The SACI encryption/decryption library is reporting an error. Refer to the provider of the SACI encryption/decryption library to resolve the problem.

1.5.2.2 A certificate has expired

Error code	50
Error constant	SECURE_CERTIFICATE_EXPIRED

Probable cause

A certificate in the certificate chain has expired. Obtain a new certificate with a later expiry date and retry the operation.

Related Information

[trusted_certificates MobiLink Client Network Protocol Option](#)

1.5.2.3 A request by a proxy server to do Basic HTTP authentication was rejected

Error code	316
Error constant	HTTP_BASIC_AUTH_DISALLOWED

Probable cause

A request by a proxy server to do Basic HTTP authentication was rejected to avoid sending plaintext credentials over the wire unencrypted. To allow this, use the `allow_unencrypted_basic_proxy_auth` option.

1.5.2.4 A secure stream has FIPS explicitly disabled, but the -fips option is in effect

Error code	242
Error constant	INCONSISTENT_FIPS

Probable cause

Use of the `-fips` switch on the synchronization server command line requires that all secure streams be FIPS-compliant. If a secure stream is not configured with the `fips` option, it will automatically be FIPS-compliant (for example, `fips=y`). Either remove the `fips` option from the secure stream, or enable it with `fips=y`.

Related Information

[FIPS-certified Encryption Technology](#)
[-fips mlsrv17 Option](#)
[-x mlsrv17 Option](#)

1.5.2.5 A userid and password are required for HTTP authentication

Error code	209
------------	-----

Error constant

HTTP_AUTHENTICATION_REQUIRED

Probable cause

An HTTP server or gateway requested HTTP authentication. Please supply a userid and password using the HTTP synchronization parameters `http_userid` and `http_password`.

Related Information

[http_userid](#) MobiLink Client Network Protocol Option

[http_password](#) MobiLink Client Network Protocol Option

1.5.2.6 A userid and password are required for HTTP proxy authentication

Error code

210

Error constant

HTTP_PROXY_AUTHENTICATION_REQUIRED

Probable cause

An HTTP proxy requested HTTP authentication. Please supply a userid and password using the HTTP synchronization parameters `http_proxy_userid` and `http_proxy_password`.

Related Information

[http_proxy_userid](#) MobiLink Client Network Protocol Option

[http_proxy_password](#) MobiLink Client Network Protocol Option

1.5.2.7 ActiveSync provider has not been installed

Error code

76

Error constant

ACTSYNC_NOT_INSTALLED

Probable cause

The Microsoft ActiveSync provider has not been installed. Run mlasinst to install it (see documentation for details).

1.5.2.8 ActiveSync synchronization cannot be initiated by an application

Error code	75
Error constant	ACTSYNC_NO_PORT

Probable cause

Microsoft ActiveSync synchronization can only be initiated by Microsoft ActiveSync itself, either by placing the device in its cradle or by selecting "Synchronize" from the Microsoft ActiveSync Manager. To initiate a synchronization from an application, use the TCP/IP socket synchronization stream.

1.5.2.9 An end read failed

Error code	11
Error constant	END_READ

Probable cause

Unable to finish a sequence of reads from the network. See also: READ

Related Information

[Unable to read %1 bytes \[page 1255\]](#)

1.5.2.10 An end write failed

Error code	10
Error constant	END_WRITE

Probable cause

Unable to finish a sequence of writes to the network. See also: WRITE

Related Information

[Unable to write %1 bytes \[page 1270\]](#)

1.5.2.11 An error occurred during shutdown

Error code	18
Error constant	SHUTTING_DOWN

Probable cause

The synchronization server encountered an error in the network layer during shutdown. Perhaps some network operations pending at the time of shutdown were affected.

1.5.2.12 An error occurred while writing to %1

Error code	310
Error constant	FILE_WRITE
Parameter 1	The name of the file.

Probable cause

An error occurred while trying to write to the specified file.

1.5.2.13 An error status was returned: '%1'

Error code	86
Error constant	HTTP_BAD_STATUS_CODE
Parameter 1	The status line read.

Probable cause

Examine the status line to determine the cause of the failure. The parameter of the error is a standard HTTP status code.

1.5.2.14 An unexpected character was read while parsing the chunk length. %1

Error code	85
Error constant	HTTP_CHUNK_LEN_BAD_CHARACTER
Parameter 1	The unexpected character.

Probable cause

Try using a fixed length HTTP body.

1.5.2.15 Automatic dialup is not supported on this machine

Error code	203
Error constant	DUN_NOT_SUPPORTED

Probable cause

An attempt to dialup has failed due to insufficient system support. On PocketPC you must use cellcore.dll and on Windows you must use wininet.dll from IE 4.0 or above. Dialup is not supported on other platforms.

1.5.2.16 Client id is not available for use in HTTP header

Error code	78
Error constant	HTTP_CLIENT_ID_NOT_SET

Probable cause

The client id was not passed into the HTTP client code. Contact technical support for a fix.

1.5.2.17 Connection attempt timed out

Error code	241
Error constant	CONNECT_TIMEOUT

Probable cause

The connection attempt timed out. Either the server is not running on the indicated host and port or the timeout value needs to be increased to allow more time to connect.

Related Information

[timeout MobiLink Client Network Protocol Option](#)
[MobiLink Client Network Protocol Options](#)

1.5.2.18 Could not open %1 for write

Error code	230
Error constant	COULD_NOT_OPEN_FILE_FOR_WRITE
Parameter 1	The name of the file.

Probable cause

The specified file could not be opened for write. Make sure that this is the correct file and that no other application is using it.

1.5.2.19 Error parsing HTTP header: %1

Error code	216
Error constant	HTTP_HEADER_PARSE_ERROR

Probable cause

An error occurred while trying to parse an HTTP header. The header may be malformed.

Related Information

[custom_header](#) [MobiLink Client Network Protocol Option](#)
[MobiLink Client Network Protocol Options](#)

1.5.2.20 Error reading from the trusted certificate file '%1'

Error code	41
Error constant	SECURE_TRUSTED_CERTIFICATE_READ
Parameter 1	The trusted certificate file name.

Probable cause

The secure network layer was unable to read the trusted certificate file. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s). 5) The program attempting to open the certificate file has sufficient privileges to see the file. This only applies to operating systems having user and/or file permissions.

Related Information

[trusted_certificates](#) MobiLink Client Network Protocol Option

1.5.2.21 Expected data from remote but current request is not a POST

Error code	89
Error constant	HTTP_EXPECTED_POST

Probable cause

The proxy you are using may not be compatible with the synchronization server. Please check your configuration.

1.5.2.22 Extra data found in the HTTP body: %1

Error code	80
Error constant	HTTP_EXTRA_DATA_END_READ
Parameter 1	First few characters in the extra data.

Probable cause

Extra data has been introduced into the HTTP body. This may have been added by a proxy agent. Try eliminating the proxy.

Related Information

[buffer_size](#) MobiLink Client Network Protocol Option

1.5.2.23 Failed dialing to %1

Error code	204
Error constant	DUN_DIAL_FAILED

Probable cause

Automatic dialup failed to establish connection to the specified dial up network.

1.5.2.24 Failed reading an incomplete HTTP request

Error code	277
Error constant	HTTP_FAILED_READING_HEADERS

Probable cause

The synchronization server received an incomplete set of HTTP headers.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.25 Failed to import a certificate from the system certificate store

Error code	222
Error constant	SECURE_IMPORT_CERT_FROM_SYSTEM_STORE

Probable cause

Failed to import a certificate from the system certificate store.

Related Information

[trusted_certificates MobiLink Client Network Protocol Option](#)

1.5.2.26 Failed to load library %1

Error code	224
Error constant	LOAD_LIBRARY_FAILURE

Probable cause

The indicated library could not be found in the path. If you are trying to use TLS encryption for synchronization, make sure you have acquired the proper license.

Related Information

[How to Set up Transport Layer Security](#)

1.5.2.27 Failed to open system certificate store

Error code	221
Error constant	SECURE_OPEN_SYSTEM_CERT_STORE

Probable cause

An attempt to open a system certificate store failed.

Related Information

[trusted_certificates MobiLink Client Network Protocol Option](#)

1.5.2.28 Failed to read CR LF

Error code	82
Error constant	HTTP_CRLF_MISSING

Probable cause

The proxy you are using may not be compatible with the synchronization server. Please check your configuration.

1.5.2.29 Failed to read encoded chunk length

Error code	84
Error constant	HTTP_CHUNK_LEN_ENCODED_MISSING

Probable cause

Try using a fixed length HTTP body.

Related Information

[CREATE FUNCTION Statement \[Web Service\]](#)
[CREATE PROCEDURE Statement \[Web Service\]](#)

1.5.2.30 Failed to read encoded CR LF

Error code	81
Error constant	HTTP_CRLF_ENCODED_MISSING

Probable cause

The proxy you are using may not be compatible with the synchronization server. Please check your configuration.

1.5.2.31 Feature not implemented

Error code	12
Error constant	NOT_IMPLEMENTED

Probable cause

An unimplemented internal feature was requested. Please contact technical support.

1.5.2.32 Function %1 could not be found

Error code	225
Error constant	LIBRARY_ENTRY_POINT_NOT_FOUND

Probable cause

The indicated library entry point could not be found.

1.5.2.33 Handshake error

Error code	53
Error constant	SECURE_HANDSHAKE

Probable cause

The secure handshake failed. Check the following: 1) On the client, the correct host machine and port number were specified. 2) On the server, the correct port number was specified. 3) The correct trusted certificate was specified on the client and the correct identity file was specified on the server.

Related Information

[certificate_company MobiLink Client Network Protocol Option](#)

[certificate_unit](#) MobiLink Client Network Protocol Option
[certificate_name](#) MobiLink Client Network Protocol Option
[trusted_certificates](#) MobiLink Client Network Protocol Option

1.5.2.34 Hostname '%1s!' check against server identity failed

Error code	317
Error constant	TLS_HOSTNAME_CHECK_FAILED

Probable cause

The hostname check against the valid names listed in the server's identity certificate failed. If the server identity is not expected to match the hostname, a custom check can be done by specifying the `certificate_name`, `certificate_company`, or `certificate_unit` options. Alternately, the check can be skipped entirely by setting the `skip_certificate_name_check` option.

1.5.2.35 HTTP Authentication failed

Error code	211
Error constant	HTTP_AUTHENTICATION_FAILED

Probable cause

The supplied userid and password were rejected. Check that they were entered correctly. If so, contact your systems administrator to ensure you have proper access.

Related Information

[http_userid](#) MobiLink Client Network Protocol Option
[http_password](#) MobiLink Client Network Protocol Option

1.5.2.36 HTTP Proxy Authentication failed

Error code	212
Error constant	HTTP_PROXY_AUTHENTICATION_FAILED

Probable cause

The supplied userid and password were rejected by the proxy server. Check that they were entered correctly. If so, contact your systems administrator to ensure you have proper access.

Related Information

[http_proxy_userid](#) MobiLink Client Network Protocol Option
[http_proxy_password](#) MobiLink Client Network Protocol Option

1.5.2.37 HTTP server authentication failed

Error code	217
Error constant	HTTP_SERVER_AUTH_FAILED

Probable cause

The Authentication-Info header sent from the server contained an incorrect value, causing authentication to fail. Make sure that you are connecting to a legitimate HTTP server.

1.5.2.38 Incorrect password for private key

Error code	287
Error constant	BAD_PRIVATE_KEY_PASSWORD

Probable cause

The provided password for the encrypted private key is incorrect.

Related Information

[End-to-end Encryption](#)

[-x mlsrv17 Option](#)

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.39 Internal error (%1)

Error code	220
Error constant	INTERNAL
Parameter 1	The internal error code.

Probable cause

An internal error has occurred in the network layer. Please contact technical support.

1.5.2.40 Internal error: %1 returned %2

Error code	238
Error constant	INTERNAL_API
Parameter 1	The name of the internal API.
Parameter 2	The internal error code.

Probable cause

An internal error has occurred in the network layer. Please contact technical support.

1.5.2.41 Internal protocol not loaded: %1

Error code	227
Error constant	INTERNAL_PROTOCOL_NOT_LOADED

Probable cause

A synchronization protocol could not be loaded. If you are using UltraLite, make sure you have called the proper ULEnable method.

Related Information

[Network Protocols for Clients](#)

1.5.2.42 Invalid compression type: %1

Error code	232
Error constant	INVALID_COMPRESSION_TYPE
Parameter 1	The invalid compression type

Probable cause

The specified compression type was not recognized.

Related Information

[compression MobiLink Client Network Protocol Option](#)

1.5.2.43 Invalid destination path %1 for the downloaded file

Error code	243
Error constant	INVALID_LOCAL_PATH
Parameter 1	The local path.

Probable cause

The destination path for the downloaded file is invalid. Consult the documentation for details.

Related Information

[MobiLink File Transfer Utility \(mfiletransfer\)](#)
[-ftr mlsrv17 Option](#)

1.5.2.44 Invalid e2ee_type '%1'

Error code	261
Error constant	E2EE_INVALID_TYPE
Parameter 1	The invalid end-to-end private key type

Probable cause

An invalid e2ee_type was specified. Please specify a valid value.

Related Information

[End-to-end Encryption](#)

1.5.2.45 Invalid HTTP character

Error code	219
Error constant	HTTP_INVALID_CHARACTER

Probable cause

An unexpected character was read in an HTTP header. The header may be malformed or the other side may not be sending HTTP at all.

Related Information

[custom_header](#) [MobiLink Client Network Protocol Option](#)
[MobiLink Client Network Protocol Options](#)

1.5.2.46 Invalid HTTP session ID received from the synchronization server

Error code	318
Error constant	HTTP_INVALID_SESSION_ID

Probable cause

The client received an ml-session-id value from the synchronization server that doesn't match the one it generated. It is possible this could occur if an intermediary erroneously sent a cached response from an earlier session or from a session involving a different client.

1.5.2.47 Invalid liveness timeout value %1. The value must be between zero and 65535

Error code	200
Error constant	SOCKET_LIVENESS_OUT_OF_RANGE
Parameter 1	The liveness timeout value.

Probable cause

An invalid liveness timeout value was specified. The liveness timeout value must be an integer between zero and 65535.

Related Information

[timeout MobiLink Client Network Protocol Option](#)

1.5.2.48 Invalid or corrupt network interface library: %1

Error code	245
Error constant	INVALID_NETWORK_LIBRARY

Parameter 1	The network library path.
-------------	---------------------------

Probable cause

The given network interface DLL or shared object could not be loaded, possibly because it is invalid or corrupt.

1.5.2.49 Invalid parameter '%1'

Error code	1
Error constant	PARAMETER
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". This code indicates an invalid parameter value. Consult the documentation for the corresponding parameter name, and correct the parameter value.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.50 Invalid port number %1. The value must be between zero and 65535

Error code	74
Error constant	SOCKET_PORT_OUT_OF_RANGE
Parameter 1	The port number.

Probable cause

An invalid port number was specified. The port number must be an integer between zero and 65535.

Related Information

[port MobiLink Client Network Protocol Option](#)
[-x mlsrv17 Option](#)

1.5.2.51 Invalid root certificate

Error code	20
Error constant	SECURE_CERTIFICATE_ROOT

Probable cause

The root certificate in the chain is invalid. At the time of publication, this error was defined but not used.

Related Information

[trusted_certificates MobiLink Client Network Protocol Option](#)

1.5.2.52 Invalid SAP passport: %1

Error code	311
Error constant	INVALID_SAP_PASSPORT
Parameter 1	The raw passport data received from the client via the SAP-PASSPORT HTTP header.

Probable cause

The SAP-PASSPORT HTTP header value received from the client could not be interpreted as an SAP passport. Make sure the client is set up to send a valid SAP passport in the SAP-PASSPORT header.

1.5.2.53 Invalid synchronization protocol: %1

Error code	226
Error constant	INVALID_SYNC_PROTOCOL

Probable cause

The specified protocol is not a valid synchronization protocol.

Related Information

[MobiLink Client Network Protocol Options](#)
-x mlsrv17 Option

1.5.2.54 Malformed session cookie (ML_SESSION_ID) value: %1

Error code	235
Error constant	HTTP_MALFORMED_SESSION_COOKIE
Parameter 1	The cookie value

Probable cause

The HTTP cookie used to manage the synchronization session is corrupt. Determine where the cookie is being corrupted. The most likely cause is a client error, or perhaps an HTTP intermediary misbehaving.

1.5.2.55 Mismatched end-to-end encryption keys

Error code	253
Error constant	E2EE_MISMATCHED_KEYS

Probable cause

The client and server are unable to communicate because the `e2ee_public_key` used for end-to-end encryption at the remote does not match the `e2ee_private_key` at the server.

Related Information

[End-to-end Encryption](#)

[e2ee_public_key MobiLink Client Network Protocol Option](#)

[Key Pair Generator Utility \(createkey\)](#)

[-x mlsrv17 Option](#)

1.5.2.56 Missing e2ee_private_key

Error code	260
Error constant	E2EE_MISSING_PRIVATE_KEY

Probable cause

Another end-to-end encryption option was specified, but not the `e2ee_private_key` option. Either specify all end-to-end encryption options or remove them all. Required end-to-end encryption options include: `e2ee_private_key`, `e2ee_private_key_password`.

Related Information

[End-to-end Encryption](#)

[e2ee_public_key MobiLink Client Network Protocol Option](#)

[Key Pair Generator Utility \(createkey\)](#)

[-x mlsrv17 Option](#)

1.5.2.57 Missing e2ee_private_key_password for the e2ee_private_key file '%1'

Error code	259
------------	-----

Error constant	E2EE_MISSING_PRIVATE_KEY_PASSWORD
Parameter 1	The private key file from the e2ee_private_key option.

Probable cause

The e2ee_private_key file cannot be read without an e2ee_private_key_password. Please provide the e2ee_private_key_password.

Related Information

[End-to-end Encryption](#)

[-x mlsrv17 Option](#)

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.58 Missing parameter: %1

Error code	229
Error constant	MISSING_PARAMETER
Parameter 1	The name of the missing parameter.

Probable cause

The specified parameter was expected but not supplied.

Related Information

[MobiLink Client Network Protocol Options](#)

[-x mlsrv17 Option](#)

1.5.2.59 ml-session-id changed from %1 to %2

Error code	289
------------	-----

Error constant	HTTP_SESSION_ID_CHANGED
Parameter 1	This connection's old ml-session-id value
Parameter 2	This connection's new ml-session-id value

Probable cause

The ml-session-id header value for this connection has changed. This is typically caused by an HTTP proxy that is reusing connections between unrelated syncs. Your proxy must be configured such that each connection to the proxy results in a new connection to the synchronization server and that these connections are never reused for new connections to the proxy.

1.5.2.60 Network communications failure: %1

Error code	313
Error constant	NETWORK_IO
Parameter 1	The failure description.

Probable cause

The network layer reported the given failure.

1.5.2.61 Network interface library version mismatch. Expecting version %1.%2, but found version %3.%4

Error code	248
Error constant	NETWORK_LIBRARY_VERSION_MISMATCH
Parameter 1	The major version expected.
Parameter 2	The minor version expected.
Parameter 3	The major version found.
Parameter 4	The minor version found.

Probable cause

A network interface DLL or shared object could not be loaded because it is the wrong version.

1.5.2.62 No certificate found in system certificate store

Error code	223
Error constant	SECURE_NO_CERTS_IN_SYS_STORE

Probable cause

No certificates were found in the system's certificate store.

Related Information

[trusted_certificates](#) MobiLink Client Network Protocol Option

1.5.2.63 No error

Error code	0
Error constant	NONE

Probable cause

This code indicates there was no network error.

1.5.2.64 No password was supplied

Error code	214
Error constant	HTTP_NO_PASSWORD

Probable cause

A userid was supplied for HTTP authentication but no password. Both are required for authentication.

Related Information

[http_userid](#) MobiLink Client Network Protocol Option

[http_password](#) MobiLink Client Network Protocol Option

1.5.2.65 No peer certificate validation parameters were provided

Error code	314
Error constant	SECURE_NO_CERTIFICATE_VALIDATION_PARAMETERS

Probable cause

No peer certificate validation parameters were provided. To ensure the peer is trusted, provide one or more of the `certificate_name`, `certificate_company`, or `certificate_unit` parameters.

1.5.2.66 No server certificate password was provided

Error code	206
Error constant	SECURE_NO_SERVER_CERTIFICATE_PASSWORD

Probable cause

No server certificate password was provided. This password is required to decrypt the server's encrypted private key.

1.5.2.67 No server certificate was provided

Error code	205
Error constant	SECURE_NO_SERVER_CERTIFICATE

Probable cause

No server certificate was provided. A server certificate is required for secure communications. The file provided must contain the full chain of certificates for the server as well as its private key.

1.5.2.68 No trusted certificates found in %1

Error code	42
Error constant	SECURE_CERTIFICATE_COUNT

Probable cause

The given file does not contain a certificate. Check the following: 1) The certificate file name was properly specified. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s).

Related Information

[trusted_certificates MobiLink Client Network Protocol Option](#)

1.5.2.69 No trusted root certificates were provided

Error code	207
Error constant	SECURE_NO_TRUSTED_ROOTS

Probable cause

No trusted root certificates were provided. At least one trusted root certificate is required for secure communications.

1.5.2.70 No userid was supplied

Error code	213
Error constant	HTTP_NO_USERID

Probable cause

A password was supplied for HTTP authentication but no userid. Both are required for authentication.

Related Information

[http_userid MobiLink Client Network Protocol Option](#)
[http_password MobiLink Client Network Protocol Option](#)

1.5.2.71 Operation interrupted

Error code	218
Error constant	INTERRUPTED

Probable cause

The current operation was interrupted by the caller.

1.5.2.72 Parameter value '%1' is not a valid boolean value. The value must be 0 or 1

Error code	4
Error constant	PARAMETER_NOT_BOOLEAN
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not a boolean value. Locate the offending parameter specification and change the value of the parameter to either 0 (for off or false) or 1 (for on or true).

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.73 Parameter value '%1' is not a valid hexadecimal value

Error code	5
Error constant	PARAMETER_NOT_HEX
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not a hexadecimal (base 16) value. Locate the offending parameter specification and change the value of the parameter to a hexadecimal value.

Related Information

[MobiLink Client Network Protocol Options](#)

1.5.2.74 Parameter value '%1' is not an unsigned integer

Error code	2
Error constant	PARAMETER_NOT_UINT32
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not an unsigned integer. Locate the offending parameter specification and change the value of the parameter to an unsigned integer.

Related Information

[MobiLink Client Network Protocol Options](#)

-x mlsrv17 Option

1.5.2.75 Parameter value '%1' is not an unsigned integer value or range. A range has the form NNN-NNN

Error code	3
Error constant	PARAMETER_NOT_UINT32_RANGE
Parameter 1	The invalid parameter value.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". The parameter value is not an unsigned integer value or range. Locate the offending parameter specification and change the value of the parameter to an unsigned integer or an unsigned range. An unsigned range has the form: NNN-NNN.

Related Information

[MobiLink Client Network Protocol Options](#)

[-x mlsrv17 Option](#)

1.5.2.76 Password specified for an unencrypted server key

Error code	208
Error constant	SECURE_REDUNDANT_SERVER_CERTIFICATE_PASSWORD

Probable cause

A password was specified when the server's private key wasn't encrypted by any password.

1.5.2.77 Protocol error

Error code	231
Error constant	PROTOCOL_ERROR

Probable cause

An unexpected value or token was read.

Related Information

[MobiLink Client Network Protocol Options](#)

[-x mlsrv17 Option](#)

1.5.2.78 Received encrypted traffic instead of HTTP traffic on port %1

Error code	281
Error constant	ENCRYPTED_INSTEAD_OF_HTTP
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received encrypted, non-HTTP traffic on a port that was servicing HTTP traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.79 Received end-to-end encrypted traffic instead of HTTP traffic on port %1

Error code	282
Error constant	E2EE_INSTEAD_OF_HTTP
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received end-to-end encrypted, non-HTTP traffic on a port that was servicing HTTP traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.80 Received end-to-end, but not transport layer security encrypted traffic on port %1

Error code	285
Error constant	E2EE_INSTEAD_OF_ENCR
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received non-TLS encrypted, but end-to-end encrypted traffic on a port that was servicing TLS encrypted traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.81 Received non-HTTP traffic on port %1

Error code	280
Error constant	TCP_INSTEAD_OF_HTTP
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received non-HTTP traffic on a port that was servicing HTTP traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.82 Received out of order HTTP request on port %1

Error code	286
Error constant	OUT_OF_ORDER_HTTP_REQUEST
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received an HTTP request that was sent by the client before another request the server has already processed.

1.5.2.83 Received unencrypted HTTP traffic on port %1

Error code	284
Error constant	HTTP_INSTEAD_OF_ENCR
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received non-encrypted HTTP traffic on a port that was servicing encrypted traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.84 Received unencrypted traffic on port %1

Error code	283
Error constant	TCP_INSTEAD_OF_ENCR
Parameter 1	The listening port.

Probable cause

The synchronization server aborted a request because it received non-encrypted traffic on a port that was servicing encrypted traffic. Ensure that the stream options used on the client match those on the server.

Related Information

[MobiLink Client Network Protocol Options](#)
-x mlsrv17 Option

1.5.2.85 Request headers too large

Error code	288
Error constant	HTTP_HEADERS_TOO_BIG

Probable cause

The headers for this HTTP header were too large. Consider increasing the header_limit HTTP option.

Related Information

-x mlsrv17 Option

1.5.2.86 SACI implementation mismatch

Error code	250
Error constant	SACI_IMPLEMENTATION_MISMATCH

Probable cause

The SACI implementation could not be loaded because it had an incompatible implementation ID.

1.5.2.87 Server certificate not trusted

Error code	24
Error constant	SECURE_CERTIFICATE_NOT_TRUSTED

Probable cause

The server's certificate was not signed by a trusted authority. Check the following: 1) The certificate file name was properly specified. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The client's list of trusted root certificates includes the server's root certificate.

Related Information

[trusted_certificates](#) MobiLink Client Network Protocol Option

1.5.2.88 Server error %1

Error code	228
Error constant	SERVER_ERROR
Parameter 1	The error reported by the server.

Probable cause

The server reported an error. Contact the synchronization server administrator to learn more.

1.5.2.89 Synchronization server authentication failed

Error code	249
Error constant	AUTHENTICATION_FAILED

Probable cause

The client failed to authenticate itself to the synchronization server.

Related Information

[Authentication Parameters](#)
[Authentication Process](#)
[Custom User Authentication](#)

1.5.2.90 The content type '%1' is unknown

Error code	77
Error constant	HTTP_CONTENT_TYPE_NOT_SPECIFIED
Parameter 1	The content type.

Probable cause

An unknown content type was specified. Refer to the documentation and change the content type to one of the supported types.

1.5.2.91 The host name '%1' could not be found

Error code	57
Error constant	SOCKET_HOST_NAME_NOT_FOUND
Parameter 1	The name of the host.

Probable cause

The given host name could not be found. Check the following: 1) The host name was correctly specified. 2) The host is accessible. Many systems include a "ping" utility that can be used to verify access to a named host. 3) The Domain Name Server (DNS), or its equivalent, is available. If the DNS is not available, try specifying the host's IP number (for example, NNN.NNN.NNN.NNN) instead of the host name. 4) The HOSTS file contains an entry that maps the host name to an IP number.

Related Information

[host](#) MobiLink Client Network Protocol Option
[proxy_host](#) MobiLink Client Network Protocol Option
[-x mlsrv17](#) Option

1.5.2.92 The HTTP buffer size specified is out of the valid range

Error code	79
Error constant	HTTP_BUFFER_SIZE_OUT_OF_RANGE

Probable cause

Fix the HTTP buffer size. A valid buffer size is positive and not overly large for the host platform.

Related Information

[buffer_size](#) MobiLink Client Network Protocol Option
[http_buffer_responses](#) MobiLink Client Network Protocol Option

1.5.2.93 The operation would cause blocking

Error code	13
Error constant	WOULD_BLOCK

Probable cause

A requested operation would block where blocking is undesirable or unexpected.

Related Information

[MobiLink Tuning for Performance](#)

1.5.2.94 The session key type '%1' is unknown

Error code	244
Error constant	HTTP_INVALID_SESSION_KEY
Parameter 1	The session key type.

Probable cause

An unknown session key type was specified. Refer to the documentation and change the session key type to one of the supported types.

Related Information

[-x mlsrv17 Option](#)

1.5.2.95 The value for option '%1' is incompatible with the value for option '%2'

Error code	315
Error constant	INCOMPATIBLE_OPTION_VALUES

Probable cause

The values for the two options are incompatible with each other. Review the documentation for each option.

1.5.2.96 The value specified for %1 is out of range

Error code	233
Error constant	VALUE_OUT_OF_RANGE

Parameter 1	The name of the parameter
-------------	---------------------------

Probable cause

The specified value was not in the range of acceptable values for that parameter. Check the documentation for the parameter to learn the acceptable range of values.

1.5.2.97 There is no private key in the e2ee_private_key file '%1'

Error code	256
Error constant	E2EE_NO_PRIVATE_KEY_IN_FILE
Parameter 1	The private key file from the e2ee_private_key option.

Probable cause

The given filename does not contain a private key.

Related Information

[End-to-end Encryption](#)
[-x mlsrv17 Option](#)
[Key Pair Generator Utility \(createkey\)](#)

1.5.2.98 This connection will be abandoned because of previous errors

Error code	279
Error constant	CONNECTION_ABANDONED

Probable cause

Some previous error forced the server to close this connection

1.5.2.99 Timed out trying to read %1 bytes

Error code	201
Error constant	READ_TIMEOUT
Parameter 1	The number of bytes that could not be read.

Probable cause

Unable to read the given number of bytes from the network layer in the given time. Check that the network is functioning correctly, and that the sending application is still running.

Related Information

[timeout MobiLink Client Network Protocol Option](#)
[-ct mlsrv17 Option](#)

1.5.2.100 Timed out trying to write %1 bytes

Error code	202
Error constant	WRITE_TIMEOUT
Parameter 1	The number of bytes that could not be written.

Probable cause

Unable to write the given number of bytes to the network layer in the given time. Check that the network is functioning correctly, and that the receiving application is still running.

Related Information

[timeout MobiLink Client Network Protocol Option](#)
[-ct mlsrv17 Option](#)

1.5.2.101 Timed out while waiting for the next HTTP request in this synchronization

Error code	83
Error constant	HTTP_NO_CONTD_CONNECTION

Probable cause

The server timed out while waiting for the next HTTP request from the remote site. Determine why this request failed to reach the server or try a persistent connection.

Related Information

[persistent MobiLink Client Network Protocol Option](#)

1.5.2.102 Unable to add a certificate to a certificate chain

Error code	39
Error constant	SECURE_ADD_CERTIFICATE

Probable cause

The secure network layer was unable to add a certificate to a certificate chain. Free up system resources and retry the operation.

Related Information

[Transport Layer Security](#)

1.5.2.103 Unable to add a trusted certificate

Error code	48
Error constant	SECURE_ADD_TRUSTED_CERTIFICATE

Probable cause

The secure network layer was unable to add a trusted certificate to a certificate chain. The most likely cause is a shortage of system resources. Free up system resources and retry the operation.

Related Information

[trusted_certificates](#) [MobiLink Client Network Protocol Option](#)

1.5.2.104 Unable to allocate a certificate

Error code	43
Error constant	SECURE_CREATE_CERTIFICATE

Probable cause

The secure network layer was unable to allocate storage for a certificate. Free up system resources and retry the operation.

Related Information

[trusted_certificates](#) [MobiLink Client Network Protocol Option](#)

1.5.2.105 Unable to allocate sufficient memory

Error code	6
------------	---

Probable cause

The network layer was unable to allocate enough bytes of storage. Free up system memory and retry the operation. The technique used to free up system memory depends on the operating system and how it is configured. The simplest technique is to reduce the number of active processes. Consult your operating system documentation for details.

1.5.2.106 Unable to attach the network layer to the security layer

Error code	26
Error constant	SECURE_SET_IO

Probable cause

The secure network layer was unable to attach to the network layer. Free up system resources and retry the operation.

1.5.2.107 Unable to bind a socket to port %1

Error code	60
Error constant	SOCKET_BIND
Parameter 1	The port number.

Probable cause

The network layer was unable to bind a socket to the given port. Check the following. 1) (Server only) Verify that the port isn't already in use. If the port is in use, either shut down the application listening on that port, or specify a different port. 2) (Server only) Verify that there are no firewall restrictions on the use of the port. 3) (Client only) If the client_port option was used, verify that the given port isn't already in use. If only one client port was specified, consider using a range (for example, NNN-NNN). If a range was specified, consider making it a wider range, or a different range. 4) (Client only) If the client_port option was used, verify that there are no firewall restrictions on the use of the port.

Related Information

[-x mlsrv17 Option](#)

[client_port MobiLink Client Network Protocol Option](#)

[port MobiLink Client Network Protocol Option](#)

1.5.2.108 Unable to clean up the socket layer

Error code	61
Error constant	SOCKET_CLEANUP

Probable cause

The network layer was unable to clean up the socket layer. This error should only occur after all connections are finished, so no current connections should be affected.

1.5.2.109 Unable to close a socket

Error code	62
Error constant	SOCKET_CLOSE

Probable cause

The network layer was unable to close a socket. The network session may or may not have terminated prematurely, due to pending writes that were not flushed. Check the following: 1) The other side of the network connection had any errors. 2) The other side of the connection is running normally. 3) The machine is still connected to the network, and the network is responsive.

1.5.2.110 Unable to connect a socket

Error code	63
Error constant	SOCKET_CONNECT

Probable cause

The network layer was unable to connect a socket. Check the following: 1) The machine is connected to the network. 2) The socket layer is properly initialized. 3) The correct host machine and port were specified. 4) The host server is running normally and listening on the correct port. 5) The host machine is listening for the proper socket type (TCP/IP vs. UDP). 6) If the `client_port` option was used, verify that there are no firewall restrictions on the use of the port. 7) If the device has a limit on the number of open sockets, verify that the limit has not been reached. 8) There are enough system resources available. Free up system resources if they are running low.

Related Information

[client_port MobiLink Client Network Protocol Option](#)
[-x mlsrv17 Option](#)

1.5.2.111 Unable to continue unknown HTTP session

Error code	265
Error constant	HTTP_UNKNOWN_SESSION

Probable cause

The HTTP cookie used to manage the synchronization session is not recognized. All HTTP requests for the same session must go to the same synchronization server instance. The most likely cause is an HTTP intermediary not sending all HTTP requests for the same session to the same synchronization server. This error can also occur when a server is quickly shut down and restarted between HTTP requests for the same session.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.112 Unable to copy a certificate

Error code	38
Error constant	SECURE_EXPORT_CERTIFICATE

Probable cause

The secure network layer was unable to copy a certificate. Free up system resources and retry the operation.

Related Information

[Transport Layer Security](#)

1.5.2.113 Unable to create a private key object

Error code	49
Error constant	SECURE_CREATE_PRIVATE_KEY_OBJECT

Probable cause

The secure network layer was unable to create a private key object before loading the private key. The most likely cause is a shortage of system resources. Free up system resources and retry the operation.

Related Information

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.114 Unable to create a random number object

Error code	17
Error constant	CREATE_RANDOM_OBJECT

Probable cause

The secure network layer could not create a random-number-generating object. Free up system resources, reconnect and retry the operation.

1.5.2.115 Unable to create a TCP/IP socket

Error code	58
Error constant	SOCKET_CREATE_TCPIP

Probable cause

The network layer was unable to create a TCP/IP socket. Check the following: 1) The machine is connected to the network. 2) The socket layer is properly initialized. 3) If the device has a limit on the number of open sockets, verify that the limit has not been reached. 4) There are enough system resources available. Free up system resources if they are running low.

Related Information

[-x mlsrv17 Option](#)
[port Mobilink Client Network Protocol Option](#)

1.5.2.116 Unable to create a UDP socket

Error code	59
Error constant	SOCKET_CREATE_UDP

Probable cause

The network layer was unable to create a UDP socket. Check the following: 1) The machine is connected to the network. 2) The socket layer is properly initialized. 3) If the client_port option was used, verify that the given port isn't already in use. If only one client port was specified, consider using a range (for example, NNN-NNN). If a range was specified, consider making it a wider range, or a different range. 4) If the client_port option was used, verify that there are no firewall restrictions on the use of the port. 5) If the device has a limit on the number of open sockets, verify that the limit has not been reached. 6) There are enough system resources available. Free up system resources if they are running low.

Related Information

[client_port MobiLink Client Network Protocol Option](#)

1.5.2.117 Unable to decode the e2ee_private_key file '%1'. The error code is %2

Error code	257
Error constant	E2EE_DECODING_PRIVATE_KEY_FILE
Parameter 1	The private key file from the e2ee_private_key option.
Parameter 2	The error code.

Probable cause

The file was found and its contents were read, but there was an error decoding the file. Please contact technical support and provide the error code.

Related Information

[End-to-end Encryption](#)

[-x mlsrv17 Option](#)

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.118 Unable to dequeue from the connection queue

Error code	19
Error constant	DEQUEUEING_CONNECTION

Probable cause

The synchronization server encountered an error while attempting to get a queued connection (synchronization) request. Free up system resources. If the problem persists, restart the synchronization server.

Related Information

[MobiLink Server](#)

1.5.2.119 Unable to determine localhost

Error code	71
Error constant	SOCKET_LOCALHOST_NAME_NOT_FOUND

Probable cause

The network layer was unable to determine the IP address of "localhost". Check the following: 1) The Domain Name Server (DNS), or its equivalent, is available. If the DNS is not available, try explicitly specifying the localhost IP number (usually 127.0.0.1) instead. 2) The HOSTS file contains an entry that maps the "localhost" name to an IP number. 3) There are enough system resources available. Free up system resources if they are running low.

Related Information

[host MobiLink Client Network Protocol Option
CommunicationAddress \(adr\) Extended Option
-x mlsrv17 Option](#)

1.5.2.120 Unable to duplicate security context

Error code	25
Error constant	SECURE_DUPLICATE_CONTEXT

Probable cause

The secure network layer was unable to duplicate a security context. Free up system resources and retry the operation.

1.5.2.121 Unable to enable FIPS mode: %1

Error code	309
Error constant	CANNOT_ENABLE_FIPS_MODE
Parameter 1	The reason why FIPS mode cannot be enabled.

Probable cause

The encryption layer was unable to enable FIPS mode.

1.5.2.122 Unable to fetch a certificate expiry date

Error code	37
Error constant	SECURE_CERTIFICATE_EXPIRY_DATE

Probable cause

A certificate's expiry date could not be read. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Related Information

[Server Authentication](#)

[trusted_certificates](#) MobiLink Client Network Protocol Option

[certificate_company](#) MobiLink Client Network Protocol Option

[certificate_name](#) MobiLink Client Network Protocol Option

[certificate_unit](#) MobiLink Client Network Protocol Option

1.5.2.123 Unable to find the trusted certificate file '%1'

Error code	40
Error constant	SECURE_TRUSTED_CERTIFICATE_FILE_NOT_FOUND

Parameter 1

The trusted certificate file name.

Probable cause

The certificate file could not be found. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s). 5) The program attempting to open the certificate file has sufficient privileges to see the file. This only applies to operating systems having user and/or file permissions.

Related Information

[trusted_certificates](#) [MobiLink Client Network Protocol Option](#)

1.5.2.124 Unable to generate a random number

Error code	14
Error constant	GENERATE_RANDOM

Probable cause

The secure network layer requires a random number but was unable to generate one. Free up system resources, reconnect and retry the operation.

1.5.2.125 Unable to get a socket's local name

Error code	64
Error constant	SOCKET_GET_NAME

Probable cause

The network layer was unable to determine a socket's local name. In a TCP/IP connection, each end of the connection has a socket exclusively attached to a port. A socket's local name includes this port number, which is assigned by the network at connection time. Check the following: 1) The machine is still connected to the

network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

1.5.2.126 Unable to get host by address

Error code	72
Error constant	SOCKET_GET_HOST_BY_ADDR

Probable cause

The network layer was unable to get the name of a host using its IP address. At the time of publication, this error was defined but not used.

Related Information

[host MobiLink Client Network Protocol Option CommunicationAddress \(adr\) Extended Option -x mlsrv17 Option](#)

1.5.2.127 Unable to get socket option number %1

Error code	65
Error constant	SOCKET_GET_OPTION
Parameter 1	The socket option being retrieved.

Probable cause

The network layer was unable to get a socket option. This error may be the first indication that a connection has been lost. Check the following: 1) The machine is still connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

1.5.2.128 Unable to import a certificate

Error code	44
Error constant	SECURE_IMPORT_CERTIFICATE

Probable cause

The secure network layer was unable to import a certificate. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s).

Related Information

[trusted_certificates MobiLink Client Network Protocol Option](#)

1.5.2.129 Unable to initialize the random number generator

Error code	15
Error constant	INIT_RANDOM

Probable cause

The secure network layer could not initialize its random number generator. Free up system resources, reconnect and retry the operation.

1.5.2.130 Unable to initialize the sockets layer

Error code	70
Error constant	SOCKET_STARTUP

Probable cause

The network layer was unable to initialize the socket layer. Check the following: 1) The sockets layer is properly installed. The correct network interface library must be present and accessible. 2) The machine is connected to

the network, and the network is responsive. 3) There are enough system resources available. Free up system resources if they are running low.

1.5.2.131 Unable to listen on a socket. The backlog is %1

Error code	67
Error constant	SOCKET_LISTEN
Parameter 1	The requested listener backlog.

Probable cause

The server is unable to listen on a socket. The backlog refers to the maximum number of queued connection requests that may be pending at any given time. Check the following: 1) The machine is still connected to the network, and the network is responsive. 2) There are no firewall or other restrictions preventing a socket listener from running on the current machine. 3) The backlog setting is within the limit, if any, on the machine. 4) There are enough system resources available. Free up system resources if they are running low.

1.5.2.132 Unable to load MLSACIGetE2EEIface

Error code	312
Error constant	E2EE_REQUESTED_BUT_MISSING

Probable cause

End-to-end encryption was requested, but the encryption library does not export MLSACIGetE2EEIface.

1.5.2.133 Unable to load the network interface library

Error code	73
Error constant	LOAD_NETWORK_LIBRARY

Probable cause

The network interface library could not be found and/or loaded. Please check the following: 1) The sockets layer is properly installed. The correct network interface library (or DLL or shared object) must be present and accessible. 2) There are enough system resources available. Free up system resources if they are running low.

Related Information

[Interface Library Communication Protocols](#)
[Troubleshooting: The Location of the Interface Library](#)

1.5.2.134 Unable to open '%1'

Error code	264
Error constant	COULD_NOT_OPEN_FILE
Parameter 1	The name of the file.

Probable cause

The specified file could not be opened.

1.5.2.135 Unable to open certificate file '%1'

Error code	33
Error constant	SECURE_CERTIFICATE_FILE_NOT_FOUND
Parameter 1	The certificate file name.

Probable cause

The certificate file could not be opened. Check the following: 1) The certificate file name was properly specified. 2) The certificate file exists. 3) The certificate file contains one or more certificates. 4) The certificate file contains the correct certificate(s). 5) The program attempting to open the certificate file has sufficient privileges to read the file. This only applies to operating systems having user and/or file permissions.

Related Information

[trusted_certificates MobiLink Client Network Protocol Option](#)

1.5.2.136 Unable to parse cookie: '%1'

Error code	88
Error constant	HTTP_UNABLE_TO_PARSE_COOKIE
Parameter 1	The set cookie header.

Probable cause

Determine where the set cookie header is being corrupted.

Related Information

[How to Use Cookies to Manage a Session](#)

1.5.2.137 Unable to parse the parameter string '%1'

Error code	7
Error constant	PARSE
Parameter 1	The parameter string that could not be parsed.

Probable cause

Network parameters are of the form "name=value;[name2=value2[;...]]". Optionally, the entire list of parameters may be enclosed in parentheses. The given string does not follow this convention. Inspect the string, fix any formatting problems, and retry the operation.

Related Information

[MobiLink Client Network Protocol Options](#)

1.5.2.138 Unable to read %1 bytes

Error code	8
Error constant	READ
Parameter 1	The number of bytes that could not be read.

Probable cause

Unable to read the given number of bytes from the network layer. Note that reads may occur as part of any larger network operation. For example, some network layers have sub-layers that perform several reads and writes as part of a basic operation in the upper layer. The cause of a read error is usually one of the following: 1) The network had a problem that caused the read to fail. Reconnect and retry the operation. 2) The connection timed out. Reconnect and retry the operation. 3) The other side of the connection cleanly terminated the connection. Consult the client and/or server logs for errors that indicate why the connection has been dropped. Consult the output-log errors and fix the cause, then retry the operation. 4) The process at the other side of the connection was aborted. Consult the client and/or server output logs for errors that indicate why the process was aborted. If the process was shut down by other than normal means, there may not be any errors in its output log. Reconnect and retry the operation. 5) The system is low on resources, and cannot perform the read. Free up system resources, reconnect and retry the operation. If subsequent retry attempts fail, consult your network administrator.

1.5.2.139 Unable to read certificates

Error code	34
Error constant	SECURE_READ_CERTIFICATE

Probable cause

The certificate file could not be read. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Related Information

[trusted_certificates](#) [MobiLink Client Network Protocol Option](#)

1.5.2.140 Unable to read the e2ee public key

Error code	263
Error constant	E2EE_PUBLIC_KEY

Probable cause

An error occurred while trying to read the end-to-end encryption public key.

Related Information

[End-to-end Encryption](#)
[e2ee_public_key](#) [MobiLink Client Network Protocol Option](#)
[Key Pair Generator Utility \(createkey\)](#)
[-x mlsrv17](#) [Option](#)

1.5.2.141 Unable to read the e2ee_private_key file '%1'. The error code is %2

Error code	255
Error constant	E2EE_READING_PRIVATE_KEY
Parameter 1	The private key file from the e2ee_private_key option.
Parameter 2	The error code.

Probable cause

An error occurred reading the e2ee_private_key file. Please contact technical support and provide the error code.

Related Information

[End-to-end Encryption](#)

[-x mlsrv17 Option](#)

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.142 Unable to read the e2ee_private_key file '%1'. The error code is %2

Error code	258
Error constant	E2EE_READING_PRIVATE_KEY_FILE
Parameter 1	The private key file from the e2ee_private_key option.
Parameter 2	The error code.

Probable cause

The given file could not be read. Please contact technical support and provide the error code.

Related Information

[End-to-end Encryption](#)

[-x mlsrv17 Option](#)

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.143 Unable to read the private key

Error code	35
Error constant	SECURE_READ_PRIVATE_KEY

Probable cause

The private key could not be read from the certificate file. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Related Information

[-x mlsrv17 Option](#)
[Key Pair Generator Utility \(createkey\)](#)
[identity MobiLink Client Network Protocol Option](#)
[identity_password MobiLink Client Network Protocol Option](#)

1.5.2.144 Unable to seed the random number generator

Error code	16
Error constant	SEED_RANDOM

Probable cause

The secure network layer could not seed its random number generator. Free up system resources, reconnect and retry the operation.

1.5.2.145 Unable to select a socket status

Error code	69
Error constant	SOCKET_SELECT

Probable cause

The network layer encountered an error attempting to wait for a socket to be ready for reading or writing. Check the following: 1) The machine is connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

1.5.2.146 Unable to set socket option number %1

Error code	66
Error constant	SOCKET_SET_OPTION

Parameter 1	The socket option being set.
-------------	------------------------------

Probable cause

The network layer was unable to set a socket option. This error may be the first indication that a connection has been lost. Check the following: 1) The machine is still connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

1.5.2.147 Unable to set the private key

Error code	36
Error constant	SECURE_SET_PRIVATE_KEY

Probable cause

The private key could not be used. Check the following: 1) The password was entered correctly. 2) The certificate file contains one or more certificates. 3) The certificate file contains the correct certificate(s). 4) The certificate file is undamaged.

Related Information

[-x mlsrv17 Option](#)
[Key Pair Generator Utility \(createkey\)](#)
[identity MobiLink Client Network Protocol Option](#)
[identity_password MobiLink Client Network Protocol Option](#)

1.5.2.148 Unable to shut down a socket

Error code	68
Error constant	SOCKET_SHUTDOWN

Probable cause

The network layer was unable to shut down a socket. Check the following: 1) The machine is connected to the network, and the network is responsive. 2) The other side of the connection is running normally. 3) There are enough system resources available. Free up system resources if they are running low.

1.5.2.149 Unable to validate peer certificate '%1': certificate chain too long

Error code	302
Error constant	PEER_VAL_CERT_CHAIN_TOO_LONG
Parameter 1	The peer certificate name.

Probable cause

The peer certificate chain length is greater than the maximum depth.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.150 Unable to validate peer certificate '%1': certificate not trusted

Error code	306
Error constant	PEER_VAL_CERT_UNTRUSTED
Parameter 1	The peer certificate name.

Probable cause

The root CA is not marked as trusted for the specified purpose.

Related Information

[ml_add_certificates_file System Procedure](#)
[trusted_certificates MobiLink Client Network Protocol Option](#)
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.151 Unable to validate peer certificate '%1': certificate rejected

Error code	307
Error constant	PEER_VAL_CERT_REJECTED
Parameter 1	The peer certificate name.

Probable cause

The root CA is marked to reject the specified purpose.

Related Information

[ml_add_certificates_file System Procedure](#)
[trusted_certificates MobiLink Client Network Protocol Option](#)
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.152 Unable to validate peer certificate '%1': format error in the certificate notAfter field

Error code	297
Error constant	PEER_VAL_ERROR_IN_CERT_NOT_AFTER_FIELD
Parameter 1	The peer certificate name.

Probable cause

The peer certificate's notAfter field contains an invalid time.

Related Information

[ml_add_certificates_file System Procedure](#)
[trusted_certificates MobiLink Client Network Protocol Option](#)
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.153 Unable to validate peer certificate '%1': format error in the certificate notBefore field

Error code	296
Error constant	PEER_VAL_ERROR_IN_CERT_NOT_BEFORE_FIELD
Parameter 1	The peer certificate name.

Probable cause

The peer certificate's notBefore field contains an invalid time.

Related Information

[ml_add_certificates_file System Procedure](#)
[trusted_certificates MobiLink Client Network Protocol Option](#)
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.154 Unable to validate peer certificate '%1': general error

Error code	308
------------	-----

Error constant	PEER_VAL_GENERAL
Parameter 1	The peer certificate name.

Probable cause

The peer certificate could not be validated due to an unspecified or unexpected general error.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.155 Unable to validate peer certificate '%1': invalid CA certificate

Error code	303
Error constant	PEER_VAL_INVALID_CA
Parameter 1	The peer certificate name.

Probable cause

A CA certificate is invalid. Either it is not a CA certificate or its extensions are not consistent with the supplied purpose.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.156 Unable to validate peer certificate '%1': path length constraint exceeded

Error code	304
Error constant	PEER_VAL_PATH_LENGTH_EXCEEDED
Parameter 1	The peer certificate name.

Probable cause

A path length has been exceeded while attempting to validate a peer certificate.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.157 Unable to validate peer certificate '%1': self-signed certificate

Error code	298
Error constant	PEER_VAL_DEPTH_ZERO_SELF_SIGNED_CERT
Parameter 1	The peer certificate name.

Probable cause

The peer certificate is self-signed and cannot be found in the list of trusted certificates.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)

1.5.2.158 Unable to validate peer certificate '%1': root certificate is not trusted

Error code	299
Error constant	PEER_VAL_SELF_SIGNED_CERT_IN_CHAIN
Parameter 1	The peer certificate name.

Probable cause

The certificate chain could be verified using the certificate chain the peer sent, but the root could not be found in the list of trusted certificate authorities.

Related Information

[ml_add_certificates_file System Procedure](#)
[trusted_certificates MobiLink Client Network Protocol Option](#)
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.159 Unable to validate peer certificate '%1': the certificate has expired

Error code	295
Error constant	PEER_VAL_CERT_HAS_EXPIRED
Parameter 1	The peer certificate name.

Probable cause

The peer certificate has expired.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.160 Unable to validate peer certificate '%1': the certificate is not yet valid

Error code	294
Error constant	PEER_VAL_CERT_NOT_YET_VALID
Parameter 1	The peer certificate name.

Probable cause

The peer certificate is being used too early. The current time is before the range of time the peer certificate can be used.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.161 Unable to validate peer certificate '%1': unable to decode the issuer public key

Error code	292
Error constant	PEER_VAL_UNABLE_TO_DECODE_ISSUER_PUBLIC_KEY
Parameter 1	The peer certificate name.

Probable cause

The public key of the peer certificate issuer could not be read.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.162 Unable to validate peer certificate '%1': unable to decrypt the certificate signature

Error code	291
Error constant	PEER_VAL_UNABLE_TO_DECRYPT_CERT_SIGNATURE
Parameter 1	The peer certificate name.

Probable cause

The signature of the peer certificate could not be decrypted. The certificate may be in an invalid or unexpected format.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.163 Unable to validate peer certificate '%1': unable to find the issuer certificate

Error code	290
------------	-----

Error constant	PEER_VAL_UNABLE_TO_GET_ISSUER_CERT
Parameter 1	The peer certificate name.

Probable cause

The issuer certificate of a looked up certificate could not be found. This normally means the list of trusted certificates is not complete.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.164 Unable to validate peer certificate '%1': unable to get local issuer certificate

Error code	300
Error constant	PEER_VAL_UNABLE_TO_GET_ISSUER_CERT_LOCALLY
Parameter 1	The peer certificate name.

Probable cause

The issuer certificate was not sent by the peer and can not be found in the list of trusted certificate authorities.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.165 Unable to validate peer certificate '%1': unable to verify the certificate signature

Error code	293
Error constant	PEER_VAL_CERT_SIGNATURE_FAILURE
Parameter 1	The peer certificate name.

Probable cause

The signature of the peer certificate is invalid. Verify the signature on the peer certificate.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.166 Unable to validate peer certificate '%1': unable to verify the first certificate

Error code	301
Error constant	PEER_VAL_UNABLE_TO_VERIFY_LEAF_SIGNATURE
Parameter 1	The peer certificate name.

Probable cause

The peer certificate chain contains only one certificate and it isn't self-signed.

Related Information

[ml_add_certificates_file](#) System Procedure
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Creation Utility \(createcert\)](#)

1.5.2.167 Unable to validate peer certificate '%1': unsupported certificate purpose

Error code	305
Error constant	PEER_VAL_INVALID_PURPOSE
Parameter 1	The peer certificate name.

Probable cause

The peer certificate cannot be used for the specified purpose. This usually means the peer certificate was not created for bi-directional encryption. Ensure the peer certificate is configured to allow bi-directional encryption.

Related Information

[ml_add_certificates_file System Procedure](#)
[trusted_certificates MobiLink Client Network Protocol Option](#)
[Certificate Creation Utility \(createcert\)](#)
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.168 Unable to write %1 bytes

Error code	9
Error constant	WRITE
Parameter 1	The number of bytes that could not be written.

Probable cause

Unable to write the given number of bytes to the network layer. Note that writes may occur as part of any larger network operation. For example, some network layers have sub-layers that perform several reads and writes as part of a basic operation in the upper layer. The cause of a write error is usually one of the following: 1) The network had a problem that caused the write to fail. Reconnect and retry the operation. 2) The connection timed out. Reconnect and retry the operation. 3) The other side of the connection cleanly terminated the

connection. Consult the client and/or server logs for errors that indicate why the connection has been dropped. Consult the output-log errors and fix the cause, then retry the operation. 4) The process at the other side of the connection was aborted. Consult the client and/or server output logs for errors that indicate why the process was aborted. If the process was shut down by other than normal means, there may not be any errors in its output log. Reconnect and retry the operation. 5) The system is low on resources, and cannot perform the write. Free up system resources, reconnect and retry the operation. If subsequent retry attempts fail, consult your network administrator.

1.5.2.169 Unexpected HTTP state %1 when decoding the header

Error code	236
Error constant	HTTP_INTERNAL_HEADER_STATE
Parameter 1	The internal header state

Probable cause

There was a problem decoding the HTTP header. This is an internal error that should never occur. Please contact technical support.

1.5.2.170 Unexpected internal HTTP request type %1

Error code	237
Error constant	HTTP_INTERNAL_REQUEST_TYPE
Parameter 1	The internal HTTP request type

Probable cause

There was a problem determining the HTTP request type. This is an internal error that should never occur. Please contact technical support.

1.5.2.171 Unexpected private key type. Expecting %1 but found %2 in the e2ee_private_key file '%3'

Error code	254
Error constant	E2EE_UNEXPECTED_PRIVATE_KEY_TYPE
Parameter 1	The end-to-end private key type from the e2ee_type option.
Parameter 2	The end-to-end private key type from the file.
Parameter 3	The private key file from the e2ee_private_key option.

Probable cause

The private key type found in the e2ee_private_key file does not match the type specified in the e2ee_type.

Related Information

[End-to-end Encryption](#)

[-x mlsrv17 Option](#)

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.172 Unexpected public key end-to-end encryption type. Expecting %1 but received %2

Error code	252
Error constant	E2EE_UNEXPECTED_PUBLIC_KEY_ENC_TYPE
Parameter 1	The end-to-end encryption type from the server.
Parameter 2	The end-to-end encryption type from the client.

Probable cause

The client sent an e2ee_type value that is different from the e2ee_type specified at the server. Please make sure these are the same.

Related Information

[End-to-end Encryption](#)

[e2ee_public_key MobiLink Client Network Protocol Option](#)

[Key Pair Generator Utility \(createkey\)](#)

1.5.2.173 Unexpected request type: %1

Error code	234
Error constant	UNEXPECTED_HTTP_REQUEST_TYPE
Parameter 1	The HTTP request type

Probable cause

The given HTTP request type was unexpected at this time. The most likely cause is an HTTP client that is not a synchronization server client.

Related Information

[MobiLink Clients](#)

1.5.2.174 Unexpected response received

Error code	319
Error constant	HTTP_UNEXPECTED_RESPONSE

Probable cause

The client received an HTTP response that was not from a synchronization server. This most often occurs when an intermediary web server or proxy server requires authentication and sends back an HTML login form. To resolve this, connect with an application that can display the form and complete the login and pass the cookies and any special headers received from the server to the client using the `set_cookie` and `custom_header` options.

1.5.2.175 Unknown HTTP User-Agent or request type

Error code	278
Error constant	HTTP_BAD_REQUEST

Probable cause

The synchronization server received an HTTP request with either an unknown User-Agent header, or an unknown request type.

Related Information

[MobiLink Client Network Protocol Options](#)
[-x mlsrv17 Option](#)

1.5.2.176 Unknown public key end-to-end encryption type sent from client: %1

Error code	251
Error constant	E2EE_UNKNOWN_PUBLIC_KEY_ENC_TYPE
Parameter 1	The end-to-end encryption type code

Probable cause

The client sent an e2ee_type value that is not recognized by the server. Please make sure the server version is equal to or greater than the version of the remote.

Related Information

[End-to-end Encryption](#)
[e2ee_public_key MobiLink Client Network Protocol Option](#)
[Key Pair Generator Utility \(createkey\)](#)

1.5.2.177 Unknown transfer encoding: '%1'

Error code	87
Error constant	HTTP_UNKNOWN_TRANSFER_ENCODING
Parameter 1	The unknown encoding.

Probable cause

Determine how the unknown transfer encoding is getting generated.

Related Information

[HTTP_RESPONSE_HEADER Function \[Web Service\]](#)

1.5.2.178 Unrecognized common name '%1'

Error code	52
Error constant	SECURE_CERTIFICATE_COMMON_NAME
Parameter 1	The common name.

Probable cause

The given common name is not in the certificate chain. Check the following: 1) The common name was properly entered. 2) The correct certificate file was specified. 3) The common name is in the certificate chain. You can verify this with the viewcert utility.

Related Information

[certificate_company](#) MobiLink Client Network Protocol Option
[certificate_unit](#) MobiLink Client Network Protocol Option
[certificate_name](#) MobiLink Client Network Protocol Option
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.179 Unrecognized organization '%1'

Error code	21
Error constant	SECURE_CERTIFICATE_COMPANY_NAME
Parameter 1	The organization name.

Probable cause

The given organization name is not in the certificate chain. Check the following: 1) The organization name was properly entered. 2) The correct certificate file was specified. 3) The organization name is in the certificate chain. You can verify this with the viewcert utility.

Related Information

[certificate_company](#) MobiLink Client Network Protocol Option
[trusted_certificates](#) MobiLink Client Network Protocol Option
[Certificate Viewer Utility \(viewcert\)](#)

1.5.2.180 Unrecognized organization unit '%1'

Error code	51
Error constant	SECURE_CERTIFICATE_COMPANY_UNIT
Parameter 1	The organization unit name.

Probable cause

The given organization unit is not in the certificate chain. Check the following: 1) The in company name was properly entered. 2) The correct certificate file was specified. 3) The company name is in the certificate chain. You can verify this with the viewcert utility.

Related Information

[certificate_company](#) MobiLink Client Network Protocol Option
[certificate_unit](#) MobiLink Client Network Protocol Option
[certificate_name](#) MobiLink Client Network Protocol Option

[trusted_certificates](#) MobiLink Client Network Protocol Option
Certificate Viewer Utility (viewcert)

1.5.2.181 Unrecognized TLS type %1

Error code	240
Error constant	UNRECOGNIZED_TLS_TYPE
Parameter 1	The TLS type

Probable cause

The TLS type is invalid. Consult the documentation for valid types.

Related Information

[Transport Layer Security](#)

1.5.2.182 Unsupported http authentication algorithm: %1

Error code	215
Error constant	HTTP_UNSUPPORTED_AUTH_ALGORITHM

Probable cause

The HTTP Digest authentication algorithm requested by the server is unsupported. Only "MD5" and "MD5-sess" are supported.

Related Information

[http_proxy_userid](#) MobiLink Client Network Protocol Option
[http_proxy_password](#) MobiLink Client Network Protocol Option

1.5.2.183 Unsupported HTTP version: %1

Error code	54
Error constant	HTTP_VERSION
Parameter 1	The requested HTTP version.

Probable cause

The requested HTTP version is unsupported. Consult the documentation and specify a supported HTTP version. At the time of publication the supported HTTP versions are 1.0 and 1.1.

Related Information

[version MobiLink Client Network Protocol Option
-x mlsvr17 Option](#)

1.6 MobiLink Replay Utility Error Messages

The MobiLink Replay utility error messages are written to the MobiLink Replay utility message log.

Each message has a numeric code. Many of the messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the message.

In this section:

[MobiLink Replay Utility Error Messages Sorted by Error Code \[page 1279\]](#)

[MobiLink Replay Utility Error Messages Listed by Message Text \[page 1282\]](#)

Related Information

[MobiLink Replay Utility Warning Messages \[page 1307\]](#)

1.6.1 MobiLink Replay Utility Error Messages Sorted by Error Code

Error code	Message text
0	No error or unknown error [page 1297]
-5001	The replay failed [page 1303]
-5002	MLReplay failed to initialize correctly [page 1288]
-5003	MLReplay was unable to connect to the MobiLink server for the following reason: '%1' [page 1292]
-5005	MLReplay was unable to open the recorded protocol file %1 [page 1297]
-5006	An error occurred while trying to read the recorded protocol [page 1286]
-5007	MLReplay is sending an unexpected amount of data to the MobiLink server [page 1290]
-5008	MLReplay could not generate a GUID for the remote ID [page 1287]
-5009	Memory allocation failed [page 1287]
-5010	The specified username is too long [page 1305]
-5011	The specified remote ID is too long [page 1305]
-5012	The specified password is too long [page 1304]
-5016	Unable to open the log file, %1 [page 1307]
-5017	Unable to initialize the log [page 1306]
-5018	MLReplay was unable to open the file %1 to get the simulated client information [page 1296]
-5019	The format of the specified simulated client information file does not match the expected format, which should consist of lines of the form '[username],[password],[remote ID],[last download time]' [page 1299]
-5020	A file I/O error occurred while MLReplay was accessing the specified simulated client information file [page 1285]
-5022	The Replay API Generator was unable to open the file, '%1' [page 1302]
-5023	The recorded protocol file is corrupted [page 1301]
-5024	The schema information could not be retrieved from the recorded protocol [page 1304]
-5026	The schema information read from the recorded protocol could not be parsed successfully [page 1304]
-5028	Unable to determine the transaction information from the recorded protocol [page 1306]

Error code	Message text
-5029	The Replay API Generator failed to initialize successfully [page 1302]
-5030	MLReplay timed out while waiting for the MobiLink server to respond [page 1291]
-5031	MLReplay failed to replay a download because MLReplay timed out while waiting for the MobiLink server [page 1289]
-5032	MLReplay was unable to close the specified simulated client information file [page 1292]
-5034	MLReplay was unable to close the recorded protocol file [page 1291]
-5035	An error occurred while accessing the recorded protocol [page 1285]
-5036	MLReplay was unable to load %1 [page 1292]
-5038	MLReplay was unable to load the CreateAndInitMLReplayUploadTransaction callback. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback [page 1293]
-5039	MLReplay was unable to load the IdentifySimulatedClient callback, which is a required callback [page 1296]
-5042	MLReplay failed to upload data to the MobiLink server [page 1290]
-5043	MLReplay received unexpected data from the MobiLink server [page 1291]
-5044	An unknown SQL domain type was found while determining the transaction information from the recorded protocol [page 1286]
-5045	The CreateAndInitMLReplayUploadTransaction callback failed. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback [page 1298]
-5046	The GetUploadTransaction callback failed [page 1299]
-5047	The IdentifySimulatedClient callback failed [page 1300]
-5048	MLReplay was unable to load the FinIdentifySimulatedClient callback, which is a required callback [page 1294]
-5050	MLReplay was unable to load the DestroyMLReplayUploadTransaction callback. The DestroyMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback [page 1293]
-5051	The Replay API Generator was unable to write to the file, %1 [page 1303]
-5052	The Replay API Generator was unable to close the file, '%1' [page 1302]

Error code	Message text
-5053	The Replay API Generator failed to generate the replay API [page 1301]
-5054	Column '%1' in table '%2' cannot be NULL [page 1286]
-5055	MLReplay was unable to load the FreeAllUploadRows callback. The FreeAllUploadRows callback is required to use the GetUploadTransaction callback [page 1294]
-5056	MLReplay was unable to load the GetNumUploadTables callback. The GetNumUploadTables callback is required to use the GetUploadTransaction callback [page 1295]
-5057	MLReplay was unable to load the GetUploadTable callback. The GetUploadTable callback is required to use the GetUploadTransaction callback [page 1296]
-5058	MLReplay was unable to load the GetNumRows callback. The GetNumRows callback is required to use the GetUploadTransaction callback [page 1294]
-5059	MLReplay was unable to load the GetRow callback. The GetRow callback is required to use the GetUploadTransaction callback [page 1295]
-5060	The ReportEndOfReplay callback returned false even though MLReplay determined that the simulated client was successful [page 1303]
-5061	The GlobalInit callback failed [page 1300]
-5062	Unable to determine whether or not the recorded protocol came from a DBMLSync client [page 1306]
-5064	MLReplay failed to initialize correctly for the following reason: '%1' [page 1288]
-5065	MLReplay failed due to the following network error: '%1' [page 1288]
-5066	Support for spatial is not available for this CPU [page 1298]
-5067	The number of simulated clients specified using the -n option is greater than the number of simulated clients specified in the simulated client information file [page 1300]
-5068	MLReplay failed to prepare repetition %1 [page 1289]
-5069	MLReplay failed to prepare repetition %1 for the following reason: '%2' [page 1289]
-5070	Spatial library error: '%1' [page 1298]
-5071	Replay API version '%1' is not valid [page 1297]
-5072	The specified script version is too long [page 1305]
-5073	Invalid liveness timeout value %1. The value must be between 0 and 65535 [page 1287]
-5074	MLReplay has received an unexpected progress offset mismatch warning from the MobiLink server [page 1290]

Error code	Message text
-5075	%1 is an incompatible recorded protocol version with this version of MLReplay [page 1284]
-5076	%1 is an incompatible recorded protocol version with this version of the Replay API Generator [page 1285]
-5077	The Replay API Generator failed to create %1 [page 1301]

1.6.2 MobiLink Replay Utility Error Messages Listed by Message Text

In this section:

[%1 is an incompatible recorded protocol version with this version of MLReplay \[page 1284\]](#)

[%1 is an incompatible recorded protocol version with this version of the Replay API Generator \[page 1285\]](#)

[A file I/O error occurred while MLReplay was accessing the specified simulated client information file \[page 1285\]](#)

[An error occurred while accessing the recorded protocol \[page 1285\]](#)

[An error occurred while trying to read the recorded protocol \[page 1286\]](#)

[An unknown SQL domain type was found while determining the transaction information from the recorded protocol \[page 1286\]](#)

[Column '%1' in table '%2' cannot be NULL \[page 1286\]](#)

[Invalid liveness timeout value %1. The value must be between 0 and 65535 \[page 1287\]](#)

[Memory allocation failed \[page 1287\]](#)

[MLReplay could not generate a GUID for the remote ID \[page 1287\]](#)

[MLReplay failed due to the following network error: '%1' \[page 1288\]](#)

[MLReplay failed to initialize correctly \[page 1288\]](#)

[MLReplay failed to initialize correctly for the following reason: '%1' \[page 1288\]](#)

[MLReplay failed to prepare repetition %1 \[page 1289\]](#)

[MLReplay failed to prepare repetition %1 for the following reason: '%2' \[page 1289\]](#)

[MLReplay failed to replay a download because MLReplay timed out while waiting for the MobiLink server \[page 1289\]](#)

[MLReplay failed to upload data to the MobiLink server \[page 1290\]](#)

[MLReplay has received an unexpected progress offset mismatch warning from the MobiLink server \[page 1290\]](#)

[MLReplay is sending an unexpected amount of data to the MobiLink server \[page 1290\]](#)

[MLReplay received unexpected data from the MobiLink server \[page 1291\]](#)

[MLReplay timed out while waiting for the MobiLink server to respond \[page 1291\]](#)

MLReplay was unable to close the recorded protocol file [page 1291]

MLReplay was unable to close the specified simulated client information file [page 1292]

MLReplay was unable to connect to the MobiLink server for the following reason: '%1' [page 1292]

MLReplay was unable to load %1 [page 1292]

MLReplay was unable to load the CreateAndInitMLReplayUploadTransaction callback. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback [page 1293]

MLReplay was unable to load the DestroyMLReplayUploadTransaction callback. The DestroyMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback [page 1293]

MLReplay was unable to load the FiniIdentifySimulatedClient callback, which is a required callback [page 1294]

MLReplay was unable to load the FreeAllUploadRows callback. The FreeAllUploadRows callback is required to use the GetUploadTransaction callback [page 1294]

MLReplay was unable to load the GetNumRows callback. The GetNumRows callback is required to use the GetUploadTransaction callback [page 1294]

MLReplay was unable to load the GetNumUploadTables callback. The GetNumUploadTables callback is required to use the GetUploadTransaction callback [page 1295]

MLReplay was unable to load the GetRow callback. The GetRow callback is required to use the GetUploadTransaction callback [page 1295]

MLReplay was unable to load the GetUploadTable callback. The GetUploadTable callback is required to use the GetUploadTransaction callback [page 1296]

MLReplay was unable to load the IdentifySimulatedClient callback, which is a required callback [page 1296]

MLReplay was unable to open the file %1 to get the simulated client information [page 1296]

MLReplay was unable to open the recorded protocol file %1 [page 1297]

No error or unknown error [page 1297]

Replay API version '%1' is not valid [page 1297]

Spatial library error: '%1' [page 1298]

Support for spatial is not available for this CPU [page 1298]

The CreateAndInitMLReplayUploadTransaction callback failed. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback [page 1298]

The format of the specified simulated client information file does not match the expected format, which should consist of lines of the form '[username],[password],[remote ID],[last download time]' [page 1299]

The GetUploadTransaction callback failed [page 1299]

The GlobalInit callback failed [page 1300]

The IdentifySimulatedClient callback failed [page 1300]

The number of simulated clients specified using the -n option is greater than the number of simulated clients specified in the simulated client information file [page 1300]

The recorded protocol file is corrupted [page 1301]

The Replay API Generator failed to create %1 [page 1301]

The Replay API Generator failed to generate the replay API [page 1301]

The Replay API Generator failed to initialize successfully [page 1302]

The Replay API Generator was unable to close the file, '%1' [page 1302]

The Replay API Generator was unable to open the file, '%1' [page 1302]

The Replay API Generator was unable to write to the file, %1 [page 1303]

The replay failed [page 1303]

The ReportEndOfReplay callback returned false even though MLReplay determined that the simulated client was successful [page 1303]

The schema information could not be retrieved from the recorded protocol [page 1304]

The schema information read from the recorded protocol could not be parsed successfully [page 1304]

The specified password is too long [page 1304]

The specified remote ID is too long [page 1305]

The specified script version is too long [page 1305]

The specified username is too long [page 1305]

Unable to determine the transaction information from the recorded protocol [page 1306]

Unable to determine whether or not the recorded protocol came from a DBMLSync client [page 1306]

Unable to initialize the log [page 1306]

Unable to open the log file, %1 [page 1307]

1.6.2.1 %1 is an incompatible recorded protocol version with this version of MLReplay

Error code	-5075
Error constant	MLREPLAY_INCOMPATIBLE_RECORDED_PROTOCOL_VERSION
Parameter 1	The recorded protocol version retrieved from the recorded protocol file

Probable cause

The recorded protocol version retrieved from the recorded protocol file was recorded by a MobiLink server that is newer than the version of MLReplay being used.

1.6.2.2 %1 is an incompatible recorded protocol version with this version of the Replay API Generator

Error code	-5076
Error constant	MLGENREPLAYAPI_INCOMPATIBLE_RECORDED_PROTOCOL_VERSION
Parameter 1	The recorded protocol version retrieved from the recorded protocol file

Probable cause

The recorded protocol version retrieved from the recorded protocol file was recorded by a MobiLink server that is newer than version of the Replay API Generator being used.

1.6.2.3 A file I/O error occurred while MLReplay was accessing the specified simulated client information file

Error code	-5020
Error constant	MLREPLAY_SIMULATED_CLIENT_INFO_FILE_IO_ERROR

Probable cause

A file I/O error occurred while MLReplay was accessing the specified simulated client information file.

1.6.2.4 An error occurred while accessing the recorded protocol

Error code	-5035
Error constant	MLREPLAY_RECORDED_PROTOCOL_ACCESS_ERROR

Probable cause

An error occurred while accessing the recorded protocol.

1.6.2.5 An error occurred while trying to read the recorded protocol

Error code	-5006
Error constant	MLREPLAY_READ_RECORDED_PROTOCOL_ERROR

Probable cause

An error occurred while trying to read the recorded protocol.

1.6.2.6 An unknown SQL domain type was found while determining the transaction information from the recorded protocol

Error code	-5044
Error constant	MLGENREPLAYAPI_UNKNOWN_DOMAIN

Probable cause

An unknown SQL domain type was found while determining the transaction information from the recorded protocol.

1.6.2.7 Column '%1' in table '%2' cannot be NULL

Error code	-5054
Error constant	MLREPLAY_NULL_VALUE
Parameter 1	column name
Parameter 2	table name

Probable cause

Cannot insert a NULL value into a non-nullable column.

1.6.2.8 Invalid liveness timeout value %1. The value must be between 0 and 65535

Error code	-5073
Error constant	MLREPLAY_TIMEOUT_OUT_OF_RANGE
Parameter 1	The timeout specified on the command line

Probable cause

An invalid liveness timeout value was specified. The liveness timeout value must be an integer between 0 and 65535.

1.6.2.9 Memory allocation failed

Error code	-5009
Error constant	MLREPLAY_OUT_OF_MEMORY

Probable cause

Your system is running out of memory. You may need to close some applications or add more memory to your system.

1.6.2.10 MLReplay could not generate a GUID for the remote ID

Error code	-5008
Error constant	MLREPLAY_COULD_NOT_GENERATE_GUID

Probable cause

MLReplay could not generate a GUID for the remote ID.

1.6.2.11 MLReplay failed due to the following network error: '%1'

Error code	-5065
Error constant	MLREPLAY_STREAM_ERROR
Parameter 1	Error message from the stream.

Probable cause

MLReplay failed due to the specified network error. Please check the network.

1.6.2.12 MLReplay failed to initialize correctly

Error code	-5002
Error constant	MLREPLAY_FAILED_INIT

Probable cause

MLReplay failed to initialize correctly.

1.6.2.13 MLReplay failed to initialize correctly for the following reason: '%1'

Error code	-5064
Error constant	MLREPLAY_FAILED_INIT_REASON
Parameter 1	Error message from the stream.

Probable cause

MLReplay failed to initialize correctly.

1.6.2.14 MLReplay failed to prepare repetition %1

Error code	-5068
Error constant	MLREPLAY_FAILED_PREPARING_REPETITION
Parameter 1	repetition number

Probable cause

MLReplay failed to prepare a repetition. The most likely cause of this error is a memory allocation error or one of the MLReplay callbacks failed. Check further up in the log to find the cause.

1.6.2.15 MLReplay failed to prepare repetition %1 for the following reason: '%2'

Error code	-5069
Error constant	MLREPLAY_FAILED_PREPARING_REPETITION_REASON
Parameter 1	repetition number
Parameter 2	Error message from the stream.

Probable cause

MLReplay failed to prepare a repetition for the given reason.

1.6.2.16 MLReplay failed to replay a download because MLReplay timed out while waiting for the MobiLink server

Error code	-5031
Error constant	MLREPLAY_REPLAY_DOWNLOAD_FAILED_TIMED_OUT

Probable cause

MLReplay failed to replay a download because MLReplay timed out while waiting for the MobiLink server.

1.6.2.17 MLReplay failed to upload data to the MobiLink server

Error code	-5042
Error constant	MLREPLAY_FAILED_UPLOAD

Probable cause

MLReplay failed to upload data to the MobiLink server.

1.6.2.18 MLReplay has received an unexpected progress offset mismatch warning from the MobiLink server

Error code	-5074
Error constant	MLREPLAY_RECEIVED_UNEXPECTED_SUB_MISMATCH

Probable cause

The most likely cause of this error is that the same recorded protocol file is being replayed more than once by the same client. To resolve the issue, run MLReplay with the -ap option.

1.6.2.19 MLReplay is sending an unexpected amount of data to the MobiLink server

Error code	-5007
Error constant	MLREPLAY_SENDING_UNEXPECTED_AMOUNT_OF_DATA

Probable cause

MLReplay is sending an unexpected amount of data to the MobiLink server.

1.6.2.20 MLReplay received unexpected data from the MobiLink server

Error code	-5043
Error constant	MLREPLAY_RECEIVED_UNEXPECTED_DATA

Probable cause

MLReplay received unexpected data from the MobiLink server.

1.6.2.21 MLReplay timed out while waiting for the MobiLink server to respond

Error code	-5030
Error constant	MLREPLAY_TIMED_OUT

Probable cause

MLReplay timed out while waiting for the MobiLink server to respond.

1.6.2.22 MLReplay was unable to close the recorded protocol file

Error code	-5034
Error constant	MLREPLAY_CLOSE_RECORDED_PROTOCOL_FILE_FAILED

Probable cause

MLReplay was unable to close the recorded protocol file.

1.6.2.23 MLReplay was unable to close the specified simulated client information file

Error code	-5032
Error constant	MLREPLAY_SIMULATED_CLIENT_INFO_FILE_CLOSE_ERROR

Probable cause

MLReplay was unable to close the specified simulated client information file.

1.6.2.24 MLReplay was unable to connect to the MobiLink server for the following reason: '%1'

Error code	-5003
Error constant	MLREPLAY_REPLAY_NEW_CONN_FAILED
Parameter 1	Error message from the stream.

Probable cause

MLReplay was unable to connect to the MobiLink server.

1.6.2.25 MLReplay was unable to load %1

Error code	-5036
Error constant	MLREPLAY_LOAD_DLL_FAILED

Probable cause

MLReplay was unable to load the specified replay DLL.

1.6.2.26 MLReplay was unable to load the CreateAndInitMLReplayUploadTransaction callback. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback

Error code	-5038
Error constant	MLREPLAY_LOAD_CREATE_UPLOAD_TRANS_FAILED

Probable cause

MLReplay was unable to load the CreateAndInitMLReplayUploadTransaction callback. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback. Make sure the CreateAndInitMLReplayUploadTransaction callback is defined in mlreplaycallbacks.cpp.

1.6.2.27 MLReplay was unable to load the DestroyMLReplayUploadTransaction callback. The DestroyMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback

Error code	-5050
Error constant	MLREPLAY_LOAD_DESTROY_MLREPLAY_UPLOAD_TRANS_FAILED

Probable cause

MLReplay was unable to load the DestroyMLReplayUploadTransaction callback. The DestroyMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback. Make sure the DestroyMLReplayUploadTransaction callback is defined in mlreplaycallbacks.cpp.

1.6.2.28 MLReplay was unable to load the FinIdentifySimulatedClient callback, which is a required callback

Error code	-5048
Error constant	MLREPLAY_LOAD_FINI_IDENTIFY_SIMULATED_CLIENT_FAILED

Probable cause

MLReplay was unable to load the FinIdentifySimulatedClient callback, which is a required callback. Make sure the FinIdentifySimulatedClient callback is defined in mlreplaycallbacks.cpp.

1.6.2.29 MLReplay was unable to load the FreeAllUploadRows callback. The FreeAllUploadRows callback is required to use the GetUploadTransaction callback

Error code	-5055
Error constant	MLREPLAY_LOAD_FREE_ALL_UPLOAD_ROWS_FAILED

Probable cause

MLReplay was unable to load the FreeAllUploadRows callback. The FreeAllUploadRows callback is required to use the GetUploadTransaction callback. Make sure the FreeAllUploadRows callback is defined in mlreplaycallbacks.cpp.

1.6.2.30 MLReplay was unable to load the GetNumRows callback. The GetNumRows callback is required to use the GetUploadTransaction callback

Error code	-5058
Error constant	MLREPLAY_LOAD_GET_NUM_ROWS_FAILED

Probable cause

MLReplay was unable to load the GetNumRows callback. The GetNumRows callback is required to use the GetUploadTransaction callback. Make sure the GetNumRows callback is defined in mlreplaycallbacks.cpp.

1.6.2.31 MLReplay was unable to load the GetNumUploadTables callback. The GetNumUploadTables callback is required to use the GetUploadTransaction callback

Error code	-5056
Error constant	MLREPLAY_LOAD_GET_NUM_UPLOAD_TABLES_FAILED

Probable cause

MLReplay was unable to load the GetNumUploadTables callback. The GetNumUploadTables callback is required to use the GetUploadTransaction callback. Make sure the GetNumUploadTables callback is defined in mlreplaycallbacks.cpp.

1.6.2.32 MLReplay was unable to load the GetRow callback. The GetRow callback is required to use the GetUploadTransaction callback

Error code	-5059
Error constant	MLREPLAY_LOAD_GET_ROW_FAILED

Probable cause

MLReplay was unable to load the GetRow callback. The GetRow callback is required to use the GetUploadTransaction callback. Make sure the GetRow callback is defined in mlreplaycallbacks.cpp.

1.6.2.33 MLReplay was unable to load the GetUploadTable callback. The GetUploadTable callback is required to use the GetUploadTransaction callback

Error code	-5057
Error constant	MLREPLAY_LOAD_GET_UPLOAD_TABLE_FAILED

Probable cause

MLReplay was unable to load the GetUploadTable callback. The GetUploadTable callback is required to use the GetUploadTransaction callback. Make sure the GetUploadTable callback is defined in mlreplaycallbacks.cpp.

1.6.2.34 MLReplay was unable to load the IdentifySimulatedClient callback, which is a required callback

Error code	-5039
Error constant	MLREPLAY_LOAD_IDENTIFY_SIMULATED_CLIENT_FAILED

Probable cause

MLReplay was unable to load the IdentifySimulatedClient callback, which is a required callback. Make sure the IdentifySimulatedClient callback is defined in mlreplaycallbacks.cpp.

1.6.2.35 MLReplay was unable to open the file %1 to get the simulated client information

Error code	-5018
Error constant	MLREPLAY_OPEN_SIMULATED_CLIENT_INFO_FAILED
Parameter 1	File name.

Probable cause

MLReplay was unable to open the file that contains the simulated client information.

1.6.2.36 MLReplay was unable to open the recorded protocol file %1

Error code	-5005
Error constant	MLREPLAY_OPEN_RECORDED_PROTOCOL_FILE_FAILED
Parameter 1	File name.

Probable cause

MLReplay was unable to open the recorded protocol file.

1.6.2.37 No error or unknown error

Error code	0
Error constant	MLREPLAY_NONE

Probable cause

This code indicates there was either no error or an unknown error.

1.6.2.38 Replay API version '%1' is not valid

Error code	-5071
Error constant	MLREPLAY_INVALID_API_VERSION
Parameter 1	The replay API version

Probable cause

The replay API version retrieved from the specified DLL or shared object is invalid. Regenerate the code using mlgenreplayapi.

1.6.2.39 Spatial library error: '%1'

Error code	-5070
Error constant	MLREPLAY_SPATIALLIB_ERROR
Parameter 1	The actual error code or error message generated by the spatial library.

Probable cause

Please look at the actual spatial library error message to find the cause of the error.

1.6.2.40 Support for spatial is not available for this CPU

Error code	-5066
Error constant	MLREPLAY_SPATIAL_SUPPORT_UNAVAILABLE

Probable cause

Spatial data support for 32-bit Windows and 32-bit Linux requires a CPU that supports the SSE2 instructions.

1.6.2.41 The CreateAndInitMLReplayUploadTransaction callback failed. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback

Error code	-5045
------------	-------

Error constant

MLREPLAY_CREATE_UPLOAD_TRANS_FAILED

Probable cause

The CreateAndInitMLReplayUploadTransaction callback failed. The CreateAndInitMLReplayUploadTransaction callback is required to use the GetUploadTransaction callback.

1.6.2.42 The format of the specified simulated client information file does not match the expected format, which should consist of lines of the form '[username],[password],[remote ID],[last download time]'

Error code

-5019

Error constant

MLREPLAY_WRONG_FORMAT_IN_SIMULATED_CLIENT_INFO_FILE

Probable cause

The format of the specified simulated client information file does not match the expected format, which should consist of lines of the form '[username],[password],[remote ID],[last download time]'

1.6.2.43 The GetUploadTransaction callback failed

Error code

-5046

Error constant

MLREPLAY_GET_UPLOAD_TRANS_FAILED

Probable cause

The GetUploadTransaction callback failed.

1.6.2.44 The Globalnit callback failed

Error code	-5061
Error constant	MLREPLAY_GLOBAL_INIT_FAILED

Probable cause

The Globalnit callback failed.

1.6.2.45 The IdentifySimulatedClient callback failed

Error code	-5047
Error constant	MLREPLAY_IDENTIFY_SIMULATED_CLIENT_FAILED

Probable cause

The IdentifySimulatedClient callback failed.

1.6.2.46 The number of simulated clients specified using the -n option is greater than the number of simulated clients specified in the simulated client information file

Error code	-5067
Error constant	MLREPLAY_INVALID_NUM_SIM_CLIENTS_SCI

Probable cause

If the -n <number of simulated clients> option is used with the -sci option, then the number of simulated clients specified by -n must be less than or equal to the number of simulated clients specified in the simulated client information file.

1.6.2.47 The recorded protocol file is corrupted

Error code	-5023
Error constant	MLREPLAY_CORRUPT_RECORDED_PROTOCOL_FILE

Probable cause

The recorded protocol file is corrupted. Make sure there were no errors on the MobiLink server while the file was being recorded.

1.6.2.48 The Replay API Generator failed to create %1

Error code	-5077
Error constant	MLGENREPLAYAPI_MKDIR_ERROR
Parameter 1	The directory in which to put the generated code

Probable cause

The Replay API Generator failed to create the directory in which to put the generated code. Try to create the directory manually and then re-try.

1.6.2.49 The Replay API Generator failed to generate the replay API

Error code	-5053
Error constant	MLGENREPLAYAPI_FAILED

Probable cause

The Replay API Generator failed to generate the replay API.

1.6.2.50 The Replay API Generator failed to initialize successfully

Error code	-5029
Error constant	MLGENREPLAYAPI_FAILED_INIT

Probable cause

The Replay API Generator failed to initialize successfully.

1.6.2.51 The Replay API Generator was unable to close the file, '%1'

Error code	-5052
Error constant	MLGENREPLAYAPI_FILE_CLOSE_FAILED
Parameter 1	filename

Probable cause

The Replay API Generator was unable to close a file.

1.6.2.52 The Replay API Generator was unable to open the file, '%1'

Error code	-5022
Error constant	MLGENREPLAYAPI_FILE_OPEN_FAILED
Parameter 1	filename

Probable cause

The Replay API Generator was unable to open a file.

1.6.2.53 The Replay API Generator was unable to write to the file, %1

Error code	-5051
Error constant	MLGENREPLAYAPI_FILE_WRITE_FAILED
Parameter 1	filename

Probable cause

The Replay API Generator was unable to write to a file.

1.6.2.54 The replay failed

Error code	-5001
Error constant	MLREPLAY_REPLAY_FAILED

Probable cause

MLReplay was unable to replay the recorded protocol successfully.

1.6.2.55 The ReportEndOfReplay callback returned false even though MLReplay determined that the simulated client was successful

Error code	-5060
Error constant	MLREPLAY_REPORT_END_OF_REPLAY_FAILED

Probable cause

The ReportEndOfReplay callback returned false even though MLReplay determined that the simulated client was successful.

1.6.2.56 The schema information could not be retrieved from the recorded protocol

Error code	-5024
Error constant	MLREPLAY_FAILED_TO_GET_SCHEMA

Probable cause

The schema information could not be retrieved from the recorded protocol. The schema information is necessary to generate part of the replay API.

1.6.2.57 The schema information read from the recorded protocol could not be parsed successfully

Error code	-5026
Error constant	MLREPLAY_FAILED_TO_PARSE_SCHEMA

Probable cause

The schema information read from the recorded protocol could not be parsed successfully.

1.6.2.58 The specified password is too long

Error code	-5012
Error constant	MLREPLAY_PASSWORD_TOO_LONG

Probable cause

The specified password is too long. The password must not be longer than 128 bytes.

1.6.2.59 The specified remote ID is too long

Error code	-5011
Error constant	MLREPLAY_REMOTE_ID_TO_LONG

Probable cause

The specified remote ID is too long. The remote ID must not be longer than 128 bytes.

1.6.2.60 The specified script version is too long

Error code	-5072
Error constant	MLREPLAY_SCRIPT_VERSION_TO_LONG

Probable cause

The specified script version is too long. The script version must not be longer than 128 bytes.

1.6.2.61 The specified username is too long

Error code	-5010
Error constant	MLREPLAY_USER_NAME_TO_LONG

Probable cause

The specified username is too long. The username must not be longer than 128 bytes.

1.6.2.62 Unable to determine the transaction information from the recorded protocol

Error code	-5028
Error constant	MLGENREPLAYAPI_FAILED_TO_LOAD_TRANS_INFO

Probable cause

Unable to determine the number of inserts, updates, and deletes per table, per transaction, per synchronization from the recorded protocol.

1.6.2.63 Unable to determine whether or not the recorded protocol came from a DBMLSync client

Error code	-5062
Error constant	MLGENREPLAYAPI_FAILED_TO_DETERMINE_CLIENT_TYPE

Probable cause

Unable to determine whether or not the recorded protocol came from a DBMLSync client. The most likely cause is a corrupt recorded protocol file.

1.6.2.64 Unable to initialize the log

Error code	-5017
Error constant	MLREPLAY_INIT_LOG_FAILED

Probable cause

MLReplay or the MLReplay API generator was unable to initialize the log file.

1.6.2.65 Unable to open the log file, %1

Error code	-5016
Error constant	MLREPLAY_OPEN_LOG_FAILED
Parameter 1	Log file name.

Probable cause

MLReplay or the MLReplay API generator was unable to open the log file.

1.7 MobiLink Replay Utility Warning Messages

The MobiLink Replay utility warning messages are written to the MobiLink Replay utility message log.

Each message has a numeric code. Many of the messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the message.

In this section:

[MobiLink Replay Utility Warning Messages Sorted by Error Code \[page 1307\]](#)

[MobiLink Replay Utility Warning Messages Listed by Message Text \[page 1308\]](#)

Related Information

[MobiLink Replay Utility Error Messages \[page 1278\]](#)

1.7.1 MobiLink Replay Utility Warning Messages Sorted by Error Code

Error code	Message text
5001	The recorded protocol being replayed is uploading schema information. Therefore, this recorded protocol cannot be replayed again without restarting the MobiLink server [page 1315]
5002	MLReplay was unable to load the ReportEndOfReplay callback [page 1312]

Error code	Message text
5003	MLReplay was unable to load the GetUploadTransaction callback [page 1311]
5004	MLReplay was unable to load the DelayCreationOfSimulatedClient callback [page 1309]
5005	MLReplay was unable to load the GetDownloadApplyTime callback [page 1310]
5006	MLReplay was unable to load the GlobalInit callback [page 1311]
5007	MLReplay was unable to load the GlobalFini callback [page 1311]
5009	There was no schema information in the recorded protocol which is necessary to generate some of the replay API [page 1315]
5010	Simulated client '%1' was not created because DelayCreationOfSimulatedClient returned false [page 1313]
5011	Repetition %1 of replaying the recorded protocol is being skipped because DelayStartOfReplay returned false [page 1312]
5012	MLReplay was unable to load the DelayStartOfReplay callback [page 1310]
5013	MLReplay was unable to load the DelayDestructionOfSimulatedClient callback [page 1309]
5014	The log file could not be renamed; continuing to append to the original log file [page 1314]
5015	Replay API version '%1' is not the latest version of the replay API [page 1312]
5016	Spatial library warning: '%1' [page 1313]
5017	The format of the simulated client information file being used does not match the latest format [page 1314]
5018	The directory, %1, does not exist; The Replay API Generator is creating it [page 1313]

1.7.2 MobiLink Replay Utility Warning Messages Listed by Message Text

In this section:

[MLReplay was unable to load the DelayCreationOfSimulatedClient callback \[page 1309\]](#)

[MLReplay was unable to load the DelayDestructionOfSimulatedClient callback \[page 1309\]](#)

[MLReplay was unable to load the DelayStartOfReplay callback \[page 1310\]](#)

[MLReplay was unable to load the GetDownloadApplyTime callback \[page 1310\]](#)

MLReplay was unable to load the GetUploadTransaction callback [page 1311]

MLReplay was unable to load the GlobalFini callback [page 1311]

MLReplay was unable to load the Globallnit callback [page 1311]

MLReplay was unable to load the ReportEndOfReplay callback [page 1312]

Repetition %1 of replaying the recorded protocol is being skipped because DelayStartOfReplay returned false [page 1312]

Replay API version '%1' is not the latest version of the replay API [page 1312]

Simulated client '%1' was not created because DelayCreationOfSimulatedClient returned false [page 1313]

Spatial library warning: '%1' [page 1313]

The directory, %1, does not exist; The Replay API Generator is creating it [page 1313]

The format of the simulated client information file being used does not match the latest format [page 1314]

The log file could not be renamed; continuing to append to the original log file [page 1314]

The recorded protocol being replayed is uploading schema information. Therefore, this recorded protocol cannot be replayed again without restarting the MobiLink server [page 1315]

There was no schema information in the recorded protocol which is necessary to generate some of the replay API [page 1315]

1.7.2.1 MLReplay was unable to load the DelayCreationOfSimulatedClient callback

Error code	5004
Error constant	MLREPLAY_LOAD_DELAY_CREATION_OF_SIMULATED_CLIENT_FAILED

Probable cause

MLReplay was unable to load the DelayCreationOfSimulatedClient callback. If you expected MLReplay to use the DelayCreationOfSimulatedClient callback, make sure it is defined in mlreplaycallbacks.cpp.

1.7.2.2 MLReplay was unable to load the DelayDestructionOfSimulatedClient callback

Error code	5013
------------	------

Error constant	MLREPLAY_LOAD_DELAY_DESTRUCTION_OF_SIMULATED_CLIENT_FAILED
----------------	--

Probable cause

MLReplay was unable to load the DelayDestructionOfSimulatedClient callback. If you expected MLReplay to use the DelayDestructionOfSimulatedClient callback, make sure it is defined in mlreplaycallbacks.cpp.

1.7.2.3 MLReplay was unable to load the DelayStartOfReplay callback

Error code	5012
Error constant	MLREPLAY_LOAD_DELAY_START_OF_REPLAY_FAILED

Probable cause

MLReplay was unable to load the DelayStartOfReplay callback. If you expected MLReplay to use the DelayStartOfReplay callback, make sure it is defined in mlreplaycallbacks.cpp.

1.7.2.4 MLReplay was unable to load the GetDownloadApplyTime callback

Error code	5005
Error constant	MLREPLAY_LOAD_GET_DOWNLOAD_APPLY_TIME_FAILED

Probable cause

MLReplay was unable to load the GetDownloadApplyTime callback. If you expected MLReplay to use the GetDownloadApplyTime callback, make sure it is defined in mlreplaycallbacks.cpp.

1.7.2.5 MLReplay was unable to load the GetUploadTransaction callback

Error code	5003
Error constant	MLREPLAY_LOAD_GET_UPLOAD_TRANS_FAILED

Probable cause

MLReplay was unable to load the GetUploadTransaction callback.

1.7.2.6 MLReplay was unable to load the GlobalFini callback

Error code	5007
Error constant	MLREPLAY_LOAD_GLOBAL_FINI_FAILED

Probable cause

MLReplay was unable to load the GlobalFini callback. If you expected MLReplay to use the GlobalFini callback, make sure it is defined in mlreplaycallbacks.cpp.

1.7.2.7 MLReplay was unable to load the GlobalInit callback

Error code	5006
Error constant	MLREPLAY_LOAD_GLOBAL_INIT_FAILED

Probable cause

MLReplay was unable to load the GlobalInit callback. If you expected MLReplay to use the GlobalInit callback, make sure it is defined in mlreplaycallbacks.cpp.

1.7.2.8 MLReplay was unable to load the ReportEndOfReplay callback

Error code	5002
Error constant	MLREPLAY_LOAD_REPORT_END_OF_REPLAY_FAILED

Probable cause

MLReplay was unable to load the ReportEndOfReplay callback. If you expected MLReplay to use the ReportEndOfReplay callback, make sure it is defined in mlreplaycallbacks.cpp.

1.7.2.9 Repetition %1 of replaying the recorded protocol is being skipped because DelayStartOfReplay returned false

Error code	5011
Error constant	MLREPLAY_SKIPPING_REPLAY
Parameter 1	repetition number

Probable cause

The specified repetition of replaying the recorded protocol is being skipped because DelayStartOfReplay returned false.

1.7.2.10 Replay API version '%1' is not the latest version of the replay API

Error code	5015
Error constant	MLREPLAY_OLD_API_VERSION
Parameter 1	The API version

Probable cause

The replay API being used is not the latest version. Regenerate the code with the latest mlgenreplayapi to get the latest replay API.

1.7.2.11 Simulated client '%1' was not created because DelayCreationOfSimulatedClient returned false

Error code	5010
Error constant	MLREPLAY_NOT_CREATING_SIMULATED_CLIENT
Parameter 1	Simulated client number

Probable cause

The specified simulated client was not created because DelayCreationOfSimulatedClient returned false.

1.7.2.12 Spatial library warning: '%1'

Error code	5016
Error constant	MLREPLAY_SPATIALLIB_WARNING
Parameter 1	The actual warning code generated by the spatial library.

Probable cause

Please look at the actual spatial library warning message to find the cause of the warning.

1.7.2.13 The directory, %1, does not exist; The Replay API Generator is creating it

Error code	5018
Error constant	MLGENREPLAYAPI_MKDIR_WARNING
Parameter 1	The directory in which the generated code will be put

Probable cause

The Replay API Generator is creating the directory in which to put the generated code because it does not exist. To avoid this warning, create the directory manually.

1.7.2.14 The format of the simulated client information file being used does not match the latest format

Error code	5017
Error constant	MLREPLAY_OLD_SCI_VERSION

Probable cause

The format of the simulated client information file does not match the latest format which is lines of the form <username>,<password>,<remote ID>,<last download time>,<script version>.

1.7.2.15 The log file could not be renamed; continuing to append to the original log file

Error code	5014
Error constant	MLREPLAY_CANNOT_RENAME_LOG

Probable cause

The log file could not be renamed to a file with filename like YYMMDDxx.rlg because all YYMMDDxx.rlg filename combinations have been used for the current day. To avoid this issue, make the size specified with the -os option larger.

1.7.2.16 The recorded protocol being replayed is uploading schema information. Therefore, this recorded protocol cannot be replayed again without restarting the MobiLink server

Error code	5001
Error constant	MLREPLAY_SCHEMA_INFO_SENT

Probable cause

The recorded protocol being replayed is uploading schema information. Therefore, this recorded protocol cannot be replayed again without restarting the MobiLink server.

1.7.2.17 There was no schema information in the recorded protocol which is necessary to generate some of the replay API

Error code	5009
Error constant	MLREPLAY_NO_SCHEMA

Probable cause

The recorded protocol did not contain schema information which is necessary to generate some of the replay API. Any part of the replay API that does not depend on the schema information will still be generated.

1.8 Relay Server Error Messages

Each Relay Server error has a numeric error code.

Many of the error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.

The text of each error message contains a prefix describing the type of error or warning:

RSE

A Relay Server error.

RSF

A Relay Server fatal error.

RSW

A Relay Server warning.

In this section:

[Relay Server Error Messages Sorted by Error Code \[page 1316\]](#)

[Relay Server Error Messages Listed by Message Text \[page 1323\]](#)

Related Information

[Relay Server Warning Messages \[page 1387\]](#)

1.8.1 Relay Server Error Messages Sorted by Error Code

Error code	Message text
0	RSE0: No error [page 1328]
1000	RSE1000: Client used a URL with no backend farm specified [page 1329]
1001	RSE1001: Client specified an unrecognized farm name '%1' in the URL [page 1329]
1002	RSE1002: Outbound enabler specified an unrecognized farm name '%1' [page 1329]
1003	RSE1003: Failed decoding session id '%1' from client request [page 1330]
1004	RSE1004: Outbound Enabler attempted to connect with invalid farm index: %1 [page 1330]
1005	RSE1005: Relay Server configuration request has been canceled [page 1331]
1006	RSE1006: Timed out waiting for SQL Anywhere Monitor commands [page 1331]
1007	RSE1007: The SQL Anywhere Monitor has disconnected prematurely [page 1331]
1008	RSE1008: Communication error [SYS%1: %2] occurred while reading SQL Anywhere Monitor request [page 1332]
1009	RSE1009: Communication error [SYS%1: %2] occurred while writing response back to SQL Anywhere Monitor [page 1333]

Error code	Message text
1010	RSE1010: Cannot update configuration concurrently [page 1333]
1011	RSE1011: Invalid or malformed session parameter in URL: '%1' [page 1334]
1012	RSE1012: Request from Outbound Enabler should not be chunked [page 1334]
1013	RSE1013: Request from Outbound Enabler cannot be smaller than minimum packet size [page 1334]
1014	RSE1014: Timed out waiting for the first packet from the Outbound Enabler [page 1335]
1015	RSE1015: Invalid first '%1' packet from the Outbound Enabler [page 1335]
1016	RSE1016: Timed out disconnecting up channel for server '%1' in farm '%2' [page 1336]
1017	RSE1017: Timed out waiting for down channels and clients to detach from shared memory during soft shutdown [page 1336]
2000	RSE2000: Backend farm '%1' is currently disabled [page 1337]
2001	RSE2001: Client security requirement is not satisfied in farm '%1' [page 1337]
2002	RSE2002: Failed to assign client request to any backend server in farm '%1' within %2 sec of application timeout [page 1338]
2003	RSE2003: Failed to use session id from client because backend server '%1' was not found in farm '%2' [page 1338]
2004	RSE2004: Backend security requirement is not satisfied in backend farm '%1' [page 1339]
2005	RSE2005: Backend server '%1' is not a recognized member of backend farm '%2' [page 1339]
2006	RSE2006: Outbound enabler is connecting a channel with invalid server index %1 in farm '%2' [page 1339]
3000	RSE3000: Incorrect MAC address(es) '%1' for backend server '%2' in backend farm '%3' [page 1340]
3001	RSE3001: Got token '%1' for backend server '%2' in farm '%3' but expecting '%4' [page 1340]
3002	RSE3002: Backend server '%1' in backend farm '%2' is using an unsupported outbound enabler [page 1341]
3003	RSE3003: Redundant outbound enabler connection for backend server '%1' in backend farm '%2' was ignored [page 1341]

Error code	Message text
3004	RSE3004: Communication error [SYS%1: %2] occurred while reading from down channel of backend server '%3' in backend farm '%4' [page 1342]
3005	RSE3005: Mismatched outbound enabler instance for backend server '%1' in backend farm '%2' [page 1342]
3006	RSE3006: Mismatched Relay Server instance for backend server '%1' in backend farm '%2' [page 1343]
3007	RSE3007: Timed out engaging reconnected up channel for backend server '%1' in backend farm '%2' after %3 seconds [page 1343]
3008	RSE3008: Backend server channel has been aborted because the backend server '%1' in backend farm '%2' has been removed or disabled from the Relay Server configuration [page 1344]
3009	RSE3009: Communication error [SYS%1: %2] occurred while writing to up channel of backend server '%3' in backend farm '%4' [page 1344]
3010	RSE3010: The outbound enabler of backend server '%1' in backend farm '%2' is using the -af switch which is longer supported. Please upgrade your outbound enabler [page 1345]
3011	RSE3011: Unknown event happened on backend server '%1' in backend farm '%2' [page 1345]
3012	RSE3012: Invalid packet from backend server '%1' in backend farm '%2' [page 1345]
3013	RSE3013: Timed out waiting for activity from outbound enabler for backend server '%1' in backend farm '%2' after %3 seconds [page 1346]
3014	RSE3014: The outbound enabler for backend server '%1' in backend farm '%2' disconnected prematurely [page 1346]
3015	RSE3015: Failed to lock urgent queue [page 1347]
3016	RSE3016: Failed to signal the Outbound Enabler for flow control purpose because %1 [page 1347]
3017	RSE3017: Request with missing '%1' header from malicious Outbound Enabler [page 1347]
3018	RSE3018: Request with incorrect header '%1: %2' from malicious Outbound Enabler [page 1348]
3019	RSE3019: Incompatible with Outbound Enabler protocol version %1 [page 1348]
3020	RSE3020: Ignored an add junction request [page 1349]
3021	RSE3021: There is no junction %1 [page 1349]
3022	RSE3022: Automatic configuration of backend server '%1' in backend farm '%2' failed with mismatched token [page 1349]

Error code	Message text
4000	RSE4000: Timed out waiting for up channel of backend server '%1' in backend farm '%2' after %3 seconds [page 1350]
4001	RSE4001: Timed out reading from client of backend server '%1' in backend farm '%2' after %3 seconds [page 1350]
4002	RSE4002: Communication error [SYS%1: %2] occurred while reading from client of backend server '%3' in backend farm '%4' [page 1351]
4003	RSE4003: Client of backend server '%1' in backend farm '%2' timed out waiting for backend server response after '%3' seconds [page 1351]
4004	RSE4004: Outbound enabler of backend server '%1' in backend farm '%2' reports session error '%7''%3' with parameters '%4', '%5', '%6' [page 1352]
4005	RSE4005: Aborting client request to backend server '%1' in backend farm '%2' due to backend server being unavailable [page 1352]
4006	RSE4006: Aborting client request to backend server '%1' in backend farm '%2' due to outbound enabler shutdown [page 1353]
4007	RSE4007: Aborting client request to backend server '%1' in backend farm '%2' due to unexpected down channel packet opcode %3 from the outbound enabler [page 1353]
4008	RSE4008: Communication error [SYS%1: %2] occurred while writing response to client of backend server '%3' in backend farm '%4' when '%5' [page 1354]
4009	RSE4009: Unexpected end of request while reading from client of backend server '%1' in backend farm '%2' [page 1354]
4010	RSE4010: Client of backend server '%1' in backend farm '%2' ignoring mis-routed OE_SERVER_RESPONSE packet with request index %3 [page 1355]
4011	RSE4011: Client of backend server '%1' in backend farm '%2' ignored mis-routed OE_SERVER_RESPONSE packet with session number %3 [page 1355]
4012	RSE4012: Client of backend server '%1' in backend farm '%2' ignored mis-routed OE_SERVER_RESPONSE packet with session fingerprint %3 while expecting %4 [page 1356]
4013	RSE4013: Forwarder certificate subject '%1' does not match pattern '%2' [page 1356]
4014	RSE4014: Forwarder certificate issuer '%1' does not match pattern '%2' [page 1357]
4015	RSE4015: Outbound enabler of backend server '%1' in backend farm '%2' reports session error %3 with parameters '%4', '%5', '%6' [page 1357]

Error code	Message text
4016	RSE4016: Failed to extract next header from response near '%1' [page 1358]
4017	RSE4017: The Outbound enabler reports error %1(%2) with parameters (%3) [page 1358]
11000	RSF11000: Relay Server list is too long. Outbound enabler connection aborted [page 1358]
11001	RSF11001: Shared memory exhausted when '%1' [page 1359]
11002	RSF11002: System error [SYS%1: %2] occurred while initializing resources for remote administration [page 1359]
11003	RSF11003: System error [SYS%1: %2] occurred while writing the entire configuration to file '%3' [page 1360]
11004	RSF11004: Out of memory while reading new configuration [page 1360]
11005	RSF11005: Protocol error when '%1' [page 1360]
11006	RSF11006: Failed to open '%1' to apply a configuration update [page 1361]
11007	RSF11007: System error [SYS%1: %2] occurred while updating configuration [page 1361]
11008	RSF11008: Timed out waiting for administration command after %1 seconds [page 1362]
11009	RSF11009: The remote administration tool disconnected prematurely [page 1362]
11010	RSF11010: Communication error [SYS%1: %2] occurred while reading from remote administration tool [page 1362]
11011	RSF11011: Cannot continue to process ADMIN_CMD_CONFIG_CONTINUE packet due to previous error [page 1363]
11012	RSF11012: Expecting section header at line %1 in configuration file '%2' [page 1363]
11013	RSF11013: System error [SYS%1: %2] occurred while archiving log file '%3' into '%4' [page 1364]
11014	RSF11014: Communication error [SYS%1: %2] occurred while writing response back to remote administration tool [page 1364]
11015	RSF11015: Invalid opcode in monitor command packet [page 1364]
11016	RSF11016: Freeing already freed memory block in shared memory [page 1365]
11017	RSE11017: Backend farm name '%1' not found while adding backend server '%2' [page 1336]
11018	RSF11018: Cannot add backend server '%1' as it is already defined in backend farm '%2' [page 1365]

Error code	Message text
11019	RSF11019: Failed initializing resource for accessing backend server '%1' in farm '%2' [page 1366]
11020	RSF11020: Missing required section '%1' in configuration file '%2' [page 1366]
11021	RSF11021: Failed preparing shared log [page 1367]
11022	RSF11022: Failed setting up data structure for all Relay Servers in the configuration [page 1367]
11023	RSF11023: Relay Server '%1' is previously defined in the configuration [page 1367]
11024	RSF11024: Failed preparing backend farms information [page 1368]
11025	RSF11025: Out of heap memory [page 1368]
11026	RSF11026: System error [SYS%1: %2] occurred while creating internal data structure on start up [page 1368]
11027	RSF11027: System error [SYS%1: %2] occurred while initializing internal data structures [page 1369]
11028	RSF11028: System error [SYS%1: %2] occurred while creating shared memory. Please shutdown any running rshost processes and restart the web server before retrying [page 1369]
11029	RSF11029: Failed to create semaphore manager [page 1370]
11030	RSF11030: System error [SYS%1: %2] occurred while initializing shared data structures [page 1370]
11031	RSF11031: Failed attaching to shared memory of Relay Server '%1' [page 1370]
11032	RSF11032: System error [SYS%1: %2] occurred while attaching to shared log '%3' [page 1371]
11033	RSF11033: Failed to update data structure for the list of Relay Servers in the configuration [page 1371]
11034	RSF11034: Failed to apply backend farm changes [page 1371]
11035	RSF11035: Failed to apply backend server changes [page 1372]
11036	RSF11036: Failed broadcasting to backend server '%1' in backend farm '%2' because up channel was too busy [page 1372]
11037	RSF11037: Farm '%1' is already defined [page 1373]
11038	RSF11038: System error [SYS%1: %2] occurred while renaming the log file '%3' [page 1373]
11039	RSF11039: Leaked a memory block in shared memory [page 1373]

Error code	Message text
11040	RSF11040: Cannot open Relay Server configuration file '%1' [page 1374]
11041	RSF11041: Cannot unhide Relay Server configuration file '%1' [page 1374]
11042	RSF11042: Bad syntax at line %1 in configuration file '%2' [page 1374]
11043	RSF11043: Invalid section name at line %1 in configuration file '%2' [page 1375]
11044	RSF11044: Invalid property name at line %1 in configuration file '%2' [page 1375]
11045	RSF11045: Invalid property value at line %1 in configuration file '%2' [page 1376]
11046	RSF11046: Duplicate '%1' section at line %2 in configuration file '%3' [page 1376]
11047	RSF11047: Missing required property '%1' at line %2 in configuration file '%3' [page 1376]
11048	RSF11048: An invalid change to '%1' has been detected on line %2 with %3 status. The problem needs to be corrected, otherwise, the Relay Server cannot be restarted [page 1377]
11049	RSF11049: Failed to initialize the Relay Server [page 1377]
11050	RSF11050: Giving up initializing the Relay Server after too long [page 1378]
12000	RSF12000: System error [SYS%1: %2] occurred while initializing resource for accessing backend farm '%3' [page 1378]
13000	RSF13000: System error [SYS%1: %2] occurred while generating acceptor uuid for backend server '%3' in backend farm '%4' [page 1379]
13001	RSF13001: System error [SYS%1: %2] occurred while initializing resource for accessing backend server '%3' in backend farm '%4' [page 1379]
13002	RSF13002: Failed to lock request list of backend server '%1' in backend farm '%2' for writing [page 1380]
13003	RSF13003: System error [SYS%1: %2] occurred while initializing request list for backend server '%3' in backend farm '%4' [page 1380]
13004	RSF13004: System error [SYS%1: %2] occurred while releasing up channel idle semaphore for backend server '%3' in backend farm '%4' [page 1381]
13005	RSF13005: The outbound enabler for backend server '%1' in backend farm '%2' is sending %3 bytes beyond channel limit [page 1381]
13006	RSF13006: Failed to lock request list of backend server '%1' in backend farm '%2' for reading [page 1382]

Error code	Message text
13007	RSF13007: Failed locking download packet queue of a client of backend server '%1' in backend farm '%2' for pushing a %3 packet [page 1382]
13008	RSF13008: System error [SYS%1: %2] occurred while initializing semaphore for download packet queue of backend server '%3' in backend farm '%4' while pushing a %5 packet [page 1383]
13009	RSF13009: Missing request list for backend server '%1' in backend farm '%2' [page 1383]
13010	RSF13010: Detected faulty request index recycling on backend server '%1' in backend farm '%2' [page 1384]
13011	RSF13011: Failed allocating shared memory block for client traffic statistic collector of backend server '%1' in backend farm '%2' [page 1384]
14000	RSF14000: System error [SYS%1: %2] occurred while initializing access to backend server '%3' in backend farm '%4' [page 1384]
14001	RSF14001: Failed to lock request list of backend server '%1' in backend farm '%2' for writing when '%3' [page 1385]
14002	RSF14002: Failed allocating shared memory block for client of backend server '%1' in backend farm '%2' when '%3' [page 1385]
14003	RSF14003: System error [SYS%1: %2] occurred while initializing request targeting backend server '%3' in backend farm '%4' [page 1386]
14004	RSF14004: Heap memory exhausted while client of backend server '%1' in backend farm '%2' is '%3' [page 1386]
14005	RSF14005: Removed unexpected request from request list of backend server '%1' in backend farm '%2' [page 1387]

1.8.2 Relay Server Error Messages Listed by Message Text

In this section:

[RSE0: No error \[page 1328\]](#)

[RSE1000: Client used a URL with no backend farm specified \[page 1329\]](#)

[RSE1001: Client specified an unrecognized farm name '%1' in the URL \[page 1329\]](#)

[RSE1002: Outbound enabler specified an unrecognized farm name '%1' \[page 1329\]](#)

[RSE1003: Failed decoding session id '%1' from client request \[page 1330\]](#)

[RSE1004: Outbound Enabler attempted to connect with invalid farm index: %1 \[page 1330\]](#)

[RSE1005: Relay Server configuration request has been canceled \[page 1331\]](#)

RSE1006: Timed out waiting for SQL Anywhere Monitor commands [page 1331]

RSE1007: The SQL Anywhere Monitor has disconnected prematurely [page 1331]

RSE1008: Communication error [SYS%1: %2] occurred while reading SQL Anywhere Monitor request [page 1332]

RSE1009: Communication error [SYS%1: %2] occurred while writing response back to SQL Anywhere Monitor [page 1333]

RSE1010: Cannot update configuration concurrently [page 1333]

RSE1011: Invalid or malformed session parameter in URL: '%1' [page 1334]

RSE1012: Request from Outbound Enabler should not be chunked [page 1334]

RSE1013: Request from Outbound Enabler cannot be smaller than minimum packet size [page 1334]

RSE1014: Timed out waiting for the first packet from the Outbound Enabler [page 1335]

RSE1015: Invalid first '%1' packet from the Outbound Enabler [page 1335]

RSE1016: Timed out disconnecting up channel for server '%1' in farm '%2' [page 1336]

RSE1017: Timed out waiting for down channels and clients to detach from shared memory during soft shutdown [page 1336]

RSE11017: Backend farm name '%1' not found while adding backend server '%2' [page 1336]

RSE2000: Backend farm '%1' is currently disabled [page 1337]

RSE2001: Client security requirement is not satisfied in farm '%1' [page 1337]

RSE2002: Failed to assign client request to any backend server in farm '%1' within %2 sec of application timeout [page 1338]

RSE2003: Failed to use session id from client because backend server '%1' was not found in farm '%2' [page 1338]

RSE2004: Backend security requirement is not satisfied in backend farm '%1' [page 1339]

RSE2005: Backend server '%1' is not a recognized member of backend farm '%2' [page 1339]

RSE2006: Outbound enabler is connecting a channel with invalid server index %1 in farm '%2' [page 1339]

RSE3000: Incorrect MAC address(es) '%1' for backend server '%2' in backend farm '%3' [page 1340]

RSE3001: Got token '%1' for backend server '%2' in farm '%3' but expecting '%4' [page 1340]

RSE3002: Backend server '%1' in backend farm '%2' is using an unsupported outbound enabler [page 1341]

RSE3003: Redundant outbound enabler connection for backend server '%1' in backend farm '%2' was ignored [page 1341]

RSE3004: Communication error [SYS%1: %2] occurred while reading from down channel of backend server '%3' in backend farm '%4' [page 1342]

RSE3005: Mismatched outbound enabler instance for backend server '%1' in backend farm '%2' [page 1342]

RSE3006: Mismatched Relay Server instance for backend server '%1' in backend farm '%2' [page 1343]

RSE3007: Timed out engaging reconnected up channel for backend server '%1' in backend farm '%2' after %3 seconds [page 1343]

RSE3008: Backend server channel has been aborted because the backend server '%1' in backend farm '%2' has been removed or disabled from the Relay Server configuration [page 1344]

RSE3009: Communication error [SYS%1: %2] occurred while writing to up channel of backend server '%3' in backend farm '%4' [page 1344]

RSE3010: The outbound enabler of backend server '%1' in backend farm '%2' is using the -af switch which is longer supported. Please upgrade your outbound enabler [page 1345]

RSE3011: Unknown event happened on backend server '%1' in backend farm '%2' [page 1345]

RSE3012: Invalid packet from backend server '%1' in backend farm '%2' [page 1345]

RSE3013: Timed out waiting for activity from outbound enabler for backend server '%1' in backend farm '%2' after %3 seconds [page 1346]

RSE3014: The outbound enabler for backend server '%1' in backend farm '%2' disconnected prematurely [page 1346]

RSE3015: Failed to lock urgent queue [page 1347]

RSE3016: Failed to signal the Outbound Enabler for flow control purpose because %1 [page 1347]

RSE3017: Request with missing '%1' header from malicious Outbound Enabler [page 1347]

RSE3018: Request with incorrect header '%1: %2' from malicious Outbound Enabler [page 1348]

RSE3019: Incompatible with Outbound Enabler protocol version %1 [page 1348]

RSE3020: Ignored an add junction request [page 1349]

RSE3021: There is no junction %1 [page 1349]

RSE3022: Automatic configuration of backend server '%1' in backend farm '%2' failed with mismatched token [page 1349]

RSE4000: Timed out waiting for up channel of backend server '%1' in backend farm '%2' after %3 seconds [page 1350]

RSE4001: Timed out reading from client of backend server '%1' in backend farm '%2' after %3 seconds [page 1350]

RSE4002: Communication error [SYS%1: %2] occurred while reading from client of backend server '%3' in backend farm '%4' [page 1351]

RSE4003: Client of backend server '%1' in backend farm '%2' timed out waiting for backend server response after '%3' seconds [page 1351]

RSE4004: Outbound enabler of backend server '%1' in backend farm '%2' reports session error '%7''%3' with parameters '%4', '%5', '%6' [page 1352]

RSE4005: Aborting client request to backend server '%1' in backend farm '%2' due to backend server being unavailable [page 1352]

RSE4006: Aborting client request to backend server '%1' in backend farm '%2' due to outbound enabler shutdown [page 1353]

RSE4007: Aborting client request to backend server '%1' in backend farm '%2' due to unexpected down channel packet opcode %3 from the outbound enabler [page 1353]

RSE4008: Communication error [SYS%1: %2] occurred while writing response to client of backend server '%3' in backend farm '%4' when '%5' [page 1354]

RSE4009: Unexpected end of request while reading from client of backend server '%1' in backend farm '%2' [page 1354]

RSE4010: Client of backend server '%1' in backend farm '%2' ignoring mis-routed OE_SERVER_RESPONSE packet with request index %3 [page 1355]

RSE4011: Client of backend server '%1' in backend farm '%2' ignored mis-routed OE_SERVER_RESPONSE packet with session number %3 [page 1355]

RSE4012: Client of backend server '%1' in backend farm '%2' ignored mis-routed OE_SERVER_RESPONSE packet with session fingerprint %3 while expecting %4 [page 1356]

RSE4013: Forwarder certificate subject '%1' does not match pattern '%2' [page 1356]

RSE4014: Forwarder certificate issuer '%1' does not match pattern '%2' [page 1357]

RSE4015: Outbound enabler of backend server '%1' in backend farm '%2' reports session error %3 with parameters '%4', '%5', '%6' [page 1357]

RSE4016: Failed to extract next header from response near '%1' [page 1358]

RSE4017: The Outbound enabler reports error %1(%2) with parameters (%3) [page 1358]

RSF11000: Relay Server list is too long. Outbound enabler connection aborted [page 1358]

RSF11001: Shared memory exhausted when '%1' [page 1359]

RSF11002: System error [SYS%1: %2] occurred while initializing resources for remote administration [page 1359]

RSF11003: System error [SYS%1: %2] occurred while writing the entire configuration to file '%3' [page 1360]

RSF11004: Out of memory while reading new configuration [page 1360]

RSF11005: Protocol error when '%1' [page 1360]

RSF11006: Failed to open '%1' to apply a configuration update [page 1361]

RSF11007: System error [SYS%1: %2] occurred while updating configuration [page 1361]

RSF11008: Timed out waiting for administration command after %1 seconds [page 1362]

RSF11009: The remote administration tool disconnected prematurely [page 1362]

RSF11010: Communication error [SYS%1: %2] occurred while reading from remote administration tool [page 1362]

RSF11011: Cannot continue to process ADMIN_CMD_CONFIG_CONTINUE packet due to previous error [page 1363]

RSF11012: Expecting section header at line %1 in configuration file '%2' [page 1363]

RSF11013: System error [SYS%1: %2] occurred while archiving log file '%3' into '%4' [page 1364]

RSF11014: Communication error [SYS%1: %2] occurred while writing response back to remote administration tool [page 1364]

RSF11015: Invalid opcode in monitor command packet [page 1364]

RSF11016: Freeing already freed memory block in shared memory [page 1365]

RSF11018: Cannot add backend server '%1' as it is already defined in backend farm '%2' [page 1365]

RSF11019: Failed initializing resource for accessing backend server '%1' in farm '%2' [page 1366]

RSF11020: Missing required section '%1' in configuration file '%2' [page 1366]

RSF11021: Failed preparing shared log [page 1367]

RSF11022: Failed setting up data structure for all Relay Servers in the configuration [page 1367]

RSF11023: Relay Server '%1' is previously defined in the configuration [page 1367]

RSF11024: Failed preparing backend farms information [page 1368]

RSF11025: Out of heap memory [page 1368]

RSF11026: System error [SYS%1: %2] occurred while creating internal data structure on start up [page 1368]

RSF11027: System error [SYS%1: %2] occurred while initializing internal data structures [page 1369]

RSF11028: System error [SYS%1: %2] occurred while creating shared memory. Please shutdown any running rshost processes and restart the web server before retrying [page 1369]

RSF11029: Failed to create semaphore manager [page 1370]

RSF11030: System error [SYS%1: %2] occurred while initializing shared data structures [page 1370]

RSF11031: Failed attaching to shared memory of Relay Server '%1' [page 1370]

RSF11032: System error [SYS%1: %2] occurred while attaching to shared log '%3' [page 1371]

RSF11033: Failed to update data structure for the list of Relay Servers in the configuration [page 1371]

RSF11034: Failed to apply backend farm changes [page 1371]

RSF11035: Failed to apply backend server changes [page 1372]

RSF11036: Failed broadcasting to backend server '%1' in backend farm '%2' because up channel was too busy [page 1372]

RSF11037: Farm '%1' is already defined [page 1373]

RSF11038: System error [SYS%1: %2] occurred while renaming the log file '%3' [page 1373]

RSF11039: Leaked a memory block in shared memory [page 1373]

RSF11040: Cannot open Relay Server configuration file '%1' [page 1374]

RSF11041: Cannot unhide Relay Server configuration file '%1' [page 1374]

RSF11042: Bad syntax at line %1 in configuration file '%2' [page 1374]

RSF11043: Invalid section name at line %1 in configuration file '%2' [page 1375]

RSF11044: Invalid property name at line %1 in configuration file '%2' [page 1375]

RSF11045: Invalid property value at line %1 in configuration file '%2' [page 1376]

RSF11046: Duplicate '%1' section at line %2 in configuration file '%3' [page 1376]

RSF11047: Missing required property '%1' at line %2 in configuration file '%3' [page 1376]

RSF11048: An invalid change to '%1' has been detected on line %2 with %3 status. The problem needs to be corrected, otherwise, the Relay Server cannot be restarted [page 1377]

RSF11049: Failed to initialize the Relay Server [page 1377]

RSF11050: Giving up initializing the Relay Server after too long [page 1378]

RSF12000: System error [SYS%1: %2] occurred while initializing resource for accessing backend farm '%3' [page 1378]

RSF13000: System error [SYS%1: %2] occurred while generating acceptor uuid for backend server '%3' in backend farm '%4' [page 1379]

RSF13001: System error [SYS%1: %2] occurred while initializing resource for accessing backend server '%3' in backend farm '%4' [page 1379]

RSF13002: Failed to lock request list of backend server '%1' in backend farm '%2' for writing [page 1380]

RSF13003: System error [SYS%1: %2] occurred while initializing request list for backend server '%3' in backend farm '%4' [page 1380]

RSF13004: System error [SYS%1: %2] occurred while releasing up channel idle semaphore for backend server '%3' in backend farm '%4' [page 1381]

RSF13005: The outbound enabler for backend server '%1' in backend farm '%2' is sending %3 bytes beyond channel limit [page 1381]

RSF13006: Failed to lock request list of backend server '%1' in backend farm '%2' for reading [page 1382]

RSF13007: Failed locking download packet queue of a client of backend server '%1' in backend farm '%2' for pushing a %3 packet [page 1382]

RSF13008: System error [SYS%1: %2] occurred while initializing semaphore for download packet queue of backend server '%3' in backend farm '%4' while pushing a %5 packet [page 1383]

RSF13009: Missing request list for backend server '%1' in backend farm '%2' [page 1383]

RSF13010: Detected faulty request index recycling on backend server '%1' in backend farm '%2' [page 1384]

RSF13011: Failed allocating shared memory block for client traffic statistic collector of backend server '%1' in backend farm '%2' [page 1384]

RSF14000: System error [SYS%1: %2] occurred while initializing access to backend server '%3' in backend farm '%4' [page 1384]

RSF14001: Failed to lock request list of backend server '%1' in backend farm '%2' for writing when '%3' [page 1385]

RSF14002: Failed allocating shared memory block for client of backend server '%1' in backend farm '%2' when '%3' [page 1385]

RSF14003: System error [SYS%1: %2] occurred while initializing request targeting backend server '%3' in backend farm '%4' [page 1386]

RSF14004: Heap memory exhausted while client of backend server '%1' in backend farm '%2' is '%3' [page 1386]

RSF14005: Removed unexpected request from request list of backend server '%1' in backend farm '%2' [page 1387]

1.8.2.1 RSE0: No error

Error code	0
Error constant	RSE_NO_ERROR

Probable cause

This code indicates there was no error.

1.8.2.2 RSE1000: Client used a URL with no backend farm specified

Error code	1000
Error constant	RSE_ROOT_NO_FARM_IN_URL

Probable cause

A client did not specify a backend farm in the URL. The request was aborted.

1.8.2.3 RSE1001: Client specified an unrecognized farm name '%1' in the URL

Error code	1001
Error constant	RSE_ROOT_FARM_NOT_FOUND_BY_CLIENT
Parameter 1	Backend farm name

Probable cause

The Relay Server is not configured with the given backend farm. The request was aborted. Please make sure the backend farm name sent from the client matches a configured backend farm name. Farm name comparison is case sensitive.

1.8.2.4 RSE1002: Outbound enabler specified an unrecognized farm name '%1'

Error code	1002
Error constant	RSE_ROOT_FARM_NOT_FOUND_BY_SERVER

Parameter 1

Backend farm name

Probable cause

The Relay Server is not configured with the given backend farm, so the connection was rejected. Please make sure the backend farm name specified by the outbound enabler matches a configured backend farm name. Farm name comparison is case sensitive.

1.8.2.5 RSE1003: Failed decoding session id '%1' from client request

Error code	1003
Error constant	RSE_ROOT_BAD_SESSION_ID
Parameter 1	Relay Server session id

Probable cause

The client sent an invalid session id. The request was aborted. Restarting the session at the client should resolve this error.

1.8.2.6 RSE1004: Outbound Enabler attempted to connect with invalid farm index: %1

Error code	1004
Error constant	RSE_ROOT_CHANNEL_CONNECT_WITH_INVALID_FARM_IDX
Parameter 1	Backend farm index

Probable cause

The backend farm was previously removed from the Relay Server configuration. The connection was rejected. Make sure the outbound enabler uses a configured backend farm name before restarting the outbound enabler.

1.8.2.7 RSE1005: Relay Server configuration request has been canceled

Error code	1005
Error constant	RSE_ROOT_ADMIN_CANCEL

Probable cause

A configuration request has been canceled. The previous configuration will remain in effect. If you still want the new Relay Server configuration, reapply it.

1.8.2.8 RSE1006: Timed out waiting for SQL Anywhere Monitor commands

Error code	1006
Error constant	RSE_ROOT_MON_READ_TIMEOUT

Probable cause

The SA monitor was not responding in a timely manner, so it was disconnected. The SA monitor should automatically reconnect some time after this error. If this error persists, make sure the machine running the SA monitor has enough resources.

i Note

Adobe will stop updating and distributing the Flash Player at the end of 2020. Because the SQL Anywhere Monitor is based on Flash, you cannot use it once Flash support ends. In many cases, tasks that were previously performed in the Monitor can be performed in the SQL Anywhere Cockpit. See [SQL Anywhere Monitor Non-GUI User Guide](#).

1.8.2.9 RSE1007: The SQL Anywhere Monitor has disconnected prematurely

Error code	1007
Error constant	RSE_ROOT_MON_DISCONNECT_EARLY

Probable cause

The SA monitor has disconnected prematurely. The SA monitor should automatically reconnect some time after this error.

i Note

Adobe will stop updating and distributing the Flash Player at the end of 2020. Because the SQL Anywhere Monitor is based on Flash, you cannot use it once Flash support ends. In many cases, tasks that were previously performed in the Monitor can be performed in the SQL Anywhere Cockpit. See [SQL Anywhere Monitor Non-GUI User Guide](#).

1.8.2.10 RSE1008: Communication error [SYS%1: %2] occurred while reading SQL Anywhere Monitor request

Error code	1008
Error constant	RSE_ROOT_MON_READ_FAIL
Parameter 1	System error code
Parameter 2	System error message

Probable cause

There was a communication error reading from the SA monitor, and the SA monitor connection was disconnected. If the SA monitor is still running properly, it should automatically reconnect some time after this error.

i Note

Adobe will stop updating and distributing the Flash Player at the end of 2020. Because the SQL Anywhere Monitor is based on Flash, you cannot use it once Flash support ends. In many cases, tasks that were previously performed in the Monitor can be performed in the SQL Anywhere Cockpit. See [SQL Anywhere Monitor Non-GUI User Guide](#).

1.8.2.11 RSE1009: Communication error [SYS%1: %2] occurred while writing response back to SQL Anywhere Monitor

Error code	1009
Error constant	RSE_ROOT_MON_WRITE_FAIL
Parameter 1	System error code
Parameter 2	System error message

Probable cause

There was a communication error writing to the SA monitor, and the SA monitor connection was disconnected. If the SA monitor is still running properly, it should automatically reconnect some time after this error.

i Note

Adobe will stop updating and distributing the Flash Player at the end of 2020. Because the SQL Anywhere Monitor is based on Flash, you cannot use it once Flash support ends. In many cases, tasks that were previously performed in the Monitor can be performed in the SQL Anywhere Cockpit. See [SQL Anywhere Monitor Non-GUI User Guide](#).

1.8.2.12 RSE1010: Cannot update configuration concurrently

Error code	1010
Error constant	RSE_ROOT_NO_CONCUR_CONFIG_UPDATE

Probable cause

A second configuration request was attempted while another was in progress. The second configuration request was aborted. Please wait until the current configuration update is complete before attempting another configuration update.

1.8.2.13 RSE1011: Invalid or malformed session parameter in URL: '%1'

Error code	1011
Error constant	RSE_ROOT_BAD_AFQ
Parameter 1	Value of IAS-RS-AFQ session parameter

Probable cause

The Relay Server was unable to interpret the session parameter in the URL sent up from the client. The request was aborted. There might be a compatibility issue between Relay Server and the client software or the backend server. Please consult the documentation, or technical support, for your client and/or backend server.

1.8.2.14 RSE1012: Request from Outbound Enabler should not be chunked

Error code	1012
Error constant	RSE_ROOT_INVALID_CHUNKED_OE_REQUEST

Probable cause

This was a bad request likely not issued by an outbound enabler. The request was ignored. Make sure only outbound enablers are accessing the server extension. If this error persists and prevents Relay Server access to your backend farm(s), please contact technical support.

1.8.2.15 RSE1013: Request from Outbound Enabler cannot be smaller than minimum packet size

Error code	1013
Error constant	RSE_ROOT_OE_REQUEST_TOO_SMALL

Probable cause

This was a bad request likely not issued by an outbound enabler. The request was ignored. Make sure only outbound enablers are accessing the server extension. If this error persists and prevents Relay Server access to your backend farm(s), please contact technical support.

1.8.2.16 RSE1014: Timed out waiting for the first packet from the Outbound Enabler

Error code	1014
Error constant	RSE_ROOT_OE_FIRST_READ_TIMEOUT

Probable cause

The outbound enabler has not responded in a timely manner, so the connection was aborted. The initial read timeout is 60 seconds before the channels are established.

1.8.2.17 RSE1015: Invalid first '%1' packet from the Outbound Enabler

Error code	1015
Error constant	RSE_ROOT_INVALID_FIRST_OE_PACKET
Parameter 1	Outbound enabler packet type

Probable cause

This was a bad request likely not issued by an outbound enabler. Make sure only outbound enablers are accessing the server extension. If this error persists and prevents Relay Server access to your backend farm(s), please contact technical support.

1.8.2.18 RSE1016: Timed out disconnecting up channel for server '%1' in farm '%2'

Error code	1016
Error constant	RSE_ROOT_TIMEOUT_DISCONNECT_CHANNEL

Probable cause

The outbound enabler was not responding to the Relay Server shutdown in a timely manner. Hard shutdown was initiated, and outstanding channels and client connections were all aborted abruptly.

1.8.2.19 RSE1017: Timed out waiting for down channels and clients to detach from shared memory during soft shutdown

Error code	1017
Error constant	RSE_ROOT_DETACH_TOO_LONG

Probable cause

All up channels were stopped but some client connection(s) or down channels were not responding to the Relay Server shutdown in a timely manner. Hard shutdown was initiated, and outstanding channels and client connections were all aborted abruptly.

1.8.2.20 RSE11017: Backend farm name '%1' not found while adding backend server '%2'

Error code	11017
Error constant	RSF_ROOT_FARM_NOT_FOUND_ADDING_SERVER
Parameter 1	Backend farm name
Parameter 2	Backend server name

Probable cause

Each backend farm must be added to the configuration before adding a backend server to it. Make sure your outbound enabler is configured with the correct backend farm name.

1.8.2.21 RSE2000: Backend farm '%1' is currently disabled

Error code	2000
Error constant	RSE_FARM_DISABLED
Parameter 1	Backend farm name

Probable cause

The backend farm was found in the Relay Server configuration but it was disabled. Either change the backend farm name sent from the client or the outbound enabler to an enabled name or enable the given backend farm.

1.8.2.22 RSE2001: Client security requirement is not satisfied in farm '%1'

Error code	2001
Error constant	RSE_FARM_CLIENT_SECURITY_DISALLOWED
Parameter 1	Backend farm name

Probable cause

The backend farm was set up to require specific client security using the client_security property but the client accessing the farm doesn't satisfy the requirement. The request was aborted.

1.8.2.23 RSE2002: Failed to assign client request to any backend server in farm '%1' within %2 sec of application timeout

Error code	2002
Error constant	RSE_FARM_SERVER_NOT_AVAILABLE
Parameter 1	Backend farm name
Parameter 2	Application timeout limit in seconds

Probable cause

Either there was no backend server available at the moment or the servers were extremely busy. The request was aborted. Retry the request later.

1.8.2.24 RSE2003: Failed to use session id from client because backend server '%1' was not found in farm '%2'

Error code	2003
Error constant	RSE_FARM_BAD_SERVER_NAME_IN_SESSION_ID
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The client request had a bad backend server name in the session id. The request was aborted. The backend server might have been removed or disabled from the Relay Server configuration. This error is usually temporary, due to a configuration change. Starting a new client session should succeed as long as there is at least one active backend server in the farm.

1.8.2.25 RSE2004: Backend security requirement is not satisfied in backend farm '%1'

Error code	2004
Error constant	RSE_FARM_SERVER_SECURITY_DISALLOWED
Parameter 1	Backend farm name

Probable cause

The backend farm was set up to require specific backend security using the `backend_security` property but the outbound enabler accessing the farm doesn't satisfy the requirement. The connection was aborted.

1.8.2.26 RSE2005: Backend server '%1' is not a recognized member of backend farm '%2'

Error code	2005
Error constant	RSE_FARM_SERVER_NOT_CONFIGURED
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The given backend server name is not a known member of the given backend farm. Make sure the backend server and backend farm names specified to the outbound enabler match the corresponding names in the Relay Server configuration. Farm and server name comparisons are case sensitive.

1.8.2.27 RSE2006: Outbound enabler is connecting a channel with invalid server index %1 in farm '%2'

Error code	2006
Error constant	RSE_FARM_CHANNEL_CONNECT_WITH_INVALID_SERVER_IDX
Parameter 1	Backend server index

Parameter 2

Backend farm name

Probable cause

The invalid server index usually occurs when a backend server was removed or disabled from the Relay Server configuration while a multi-request session was active. The connection was rejected. This error is usually temporary, due to a configuration change. Starting a new client session should succeed as long as there is at least one active backend server in the farm.

1.8.2.28 RSE3000: Incorrect MAC address(es) '%1' for backend server '%2' in backend farm '%3'

Error code	3000
Error constant	RSE_SERVER_UNAUTHORIZED_MAC
Parameter 1	Mac address(es) of the outbound enabler
Parameter 2	Backend server name
Parameter 3	Backend farm name

Probable cause

The Relay Server was configured to require MAC address verification when the outbound enabler connects for the named backend server, but the connecting outbound enabler failed to match the required MAC address. The connection was rejected. Make sure the configured MAC address is correct.

1.8.2.29 RSE3001: Got token '%1' for backend server '%2' in farm '%3' but expecting '%4'

Error code	3001
Error constant	RSE_SERVER_UNAUTHORIZED_TOKEN
Parameter 1	Received token
Parameter 2	Backend server name
Parameter 3	Backend farm name
Parameter 4	Expected token

Probable cause

The backend server was configured to require token verification when the outbound enabler connects for the named backend server, but the connecting outbound enabler failed to match the required token. The connection was rejected. Make sure the configured token is correct.

1.8.2.30 RSE3002: Backend server '%1' in backend farm '%2' is using an unsupported outbound enabler

Error code	3002
Error constant	RSE_SERVER_BETA_OE_NOT_SUPPORTED
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The outbound enabler must be upgraded to a newer, supported version.

1.8.2.31 RSE3003: Redundant outbound enabler connection for backend server '%1' in backend farm '%2' was ignored

Error code	3003
Error constant	RSE_SERVER_REDUNDANT_OE
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

A second outbound enabler connected using the same server id as an existing connected outbound enabler. The new instance was rejected. Make sure all outbound enablers are properly configured with unique server ids.

1.8.2.32 RSE3004: Communication error [SYS%1: %2] occurred while reading from down channel of backend server '%3' in backend farm '%4'

Error code	3004
Error constant	RSE_SERVER_READ_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

This error can be caused by a network problem between the Relay Server and the outbound enabler. The outbound enabler will normally try to reconnect some time after this error.

1.8.2.33 RSE3005: Mismatched outbound enabler instance for backend server '%1' in backend farm '%2'

Error code	3005
Error constant	RSE_SERVER_CONNECT_WITH_MISMATCH_OE_UUID
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

This error can happen if there are contending outbound enablers using the same server id. Each outbound enabler must have a unique server id. You should keep your backend server token confidential. Renew your backend server token with your Relay Server administrator if you suspect your token has been jeopardized.

1.8.2.34 RSE3006: Mismatched Relay Server instance for backend server '%1' in backend farm '%2'

Error code	3006
Error constant	RSE_SERVER_CONNECT_WITH_MISMATCH_RS_UUID
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

This error can happen if there are contending outbound enablers using the same server id. Each outbound enabler must have a unique server id. You should keep your backend server token confidential. Renew your backend server token with your Relay Server administrator if you suspect your token has been jeopardized.

1.8.2.35 RSE3007: Timed out engaging reconnected up channel for backend server '%1' in backend farm '%2' after %3 seconds

Error code	3007
Error constant	RSE_SERVER_FAIL_ENGAGE_UPCHANNEL
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Outbound enabler timeout limit

Probable cause

If this error occurs repeatedly, the Relay Server may need to be restarted.

1.8.2.36 RSE3008: Backend server channel has been aborted because the backend server '%1' in backend farm '%2' has been removed or disabled from the Relay Server configuration

Error code	3008
Error constant	RSE_SERVER_DISABLED
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

Existing requests to this backend server will be interrupted. This is normally a temporary error. Once the existing requests are aborted, the Relay Server will no longer redirect traffic to the given backend server.

1.8.2.37 RSE3009: Communication error [SYS%1: %2] occurred while writing to up channel of backend server '%3' in backend farm '%4'

Error code	3009
Error constant	RSE_SERVER_WRITE_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

A network communication error occurred when writing to the backend server. The outbound enabler will normally try to reconnect some time after this error.

1.8.2.38 RSE3010: The outbound enabler of backend server '%1' in backend farm '%2' is using the -af switch which is longer supported. Please upgrade your outbound enabler

Error code	3010
Error constant	RSE_SERVER_OLD_OE_WITH_DASH_AF
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The -af switch was introduced to the outbound enabler for Afaria server but the use of the switch is no longer supported in the current Relay Server. In the current Relay Server, there is no need to use the -af switch on the outbound enabler. Please upgrade the outbound enabler.

1.8.2.39 RSE3011: Unknown event happened on backend server '%1' in backend farm '%2'

Error code	3011
Error constant	RSE_SERVER_UNKNOWN_OE_EVENT
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

Make sure only outbound enablers are accessing the server extension. Please contact technical support if the problem persists.

1.8.2.40 RSE3012: Invalid packet from backend server '%1' in backend farm '%2'

Error code	3012
------------	------

Error constant	RSE_SERVER_PROTOCOL_ERROR
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

Make sure only outbound enablers are accessing the server extension. Please contact technical support if the problem persists.

1.8.2.41 RSE3013: Timed out waiting for activity from outbound enabler for backend server '%1' in backend farm '%2' after %3 seconds

Error code	3013
Error constant	RSE_SERVER_LIVENESS_TIMEOUT
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Outbound enabler timeout limit

Probable cause

The outbound enabler was not responding and the channels associated with it were aborted. It is likely that current multi-request sessions targeting the given backend server also failed. If the outbound enabler doesn't automatically reconnect, verify that it is functioning properly.

1.8.2.42 RSE3014: The outbound enabler for backend server '%1' in backend farm '%2' disconnected prematurely

Error code	3014
Error constant	RSE_SERVER_DISCONNECT_EARLY
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

This can be caused by a network problem or abrupt termination of the outbound enabler process. It is likely that current multi-request sessions targeting the given backend server failed. If the outbound enabler doesn't automatically reconnect, verify that it is functioning properly.

1.8.2.43 RSE3015: Failed to lock urgent queue

Error code	3015
Error constant	RSE_SERVER_LOCK_URGENT_QUEUE_FAIL

Probable cause

The Relay Server timeout locking the urgent queue for flow control. This may happen under stress. If this happens frequently, consider adding more Relay Servers to the farm.

1.8.2.44 RSE3016: Failed to signal the Outbound Enabler for flow control purpose because %1

Error code	3016
Error constant	RSE_SERVER_URGENT_SIGNAL_FAIL
Parameter 1	Reason of the failure (for technical support)

Probable cause

This may happen under extreme load and the Relay Server may run out of shared memory. If this happens frequently, consider adding more Relay Servers to the farm.

1.8.2.45 RSE3017: Request with missing '%1' header from malicious Outbound Enabler

Error code	3017
Error constant	RSE_SERVER_MISSING_HEADER

Parameter 1

Anticipated header name

Probable cause

A malicious request being refused by the Relay Server.

1.8.2.46 RSE3018: Request with incorrect header '%1: %2' from malicious Outbound Enabler

Error code	3018
Error constant	RSE_SERVER_INCORRECT_HEADER_VALUE
Parameter 1	Header name
Parameter 2	Header value

Probable cause

A malicious request being refused by the Relay Server.

1.8.2.47 RSE3019: Incompatible with Outbound Enabler protocol version %1

Error code	3019
Error constant	RSE_SERVER_INCOMPATIBLE
Parameter 1	Requested protocol version

Probable cause

Request from an incompatible Outbound Enabler has been ignored.

1.8.2.48 RSE3020: Ignored an add junction request

Error code	3020
Error constant	RSE_SERVER_CANNOT_ADD_JUNCTION

Probable cause

Cannot have more junction than what is specified in the max_junction property.

1.8.2.49 RSE3021: There is no junction %1

Error code	3021
Error constant	RSE_SERVER_NO_SUCH_JUNCTION
Parameter 1	Junction index

Probable cause

This may be caused by a Relay Server restart. The Outbound Enabler will automatically replenish the lost junction.

1.8.2.50 RSE3022: Automatic configuration of backend server '%1' in backend farm '%2' failed with mismatched token

Error code	3022
Error constant	RSE_SERVER_BAD_AUTO_CONFIG_TOKEN
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

Automatic configuration is enabled in your Relay Server configuration and an Outbound Enabler is connecting an unseen backend server name but the token provided didn't match the farm-wide token perviously established.

1.8.2.51 RSE4000: Timed out waiting for up channel of backend server '%1' in backend farm '%2' after %3 seconds

Error code	4000
Error constant	RSE_CLIENT_TIMEOUT_WAITING_FOR_UP_CHANNEL
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Application timeout limit

Probable cause

The backend server was not available due to the timeout. The request was aborted. If the outbound enabler doesn't automatically reconnect, verify that it is functioning properly.

1.8.2.52 RSE4001: Timed out reading from client of backend server '%1' in backend farm '%2' after %3 seconds

Error code	4001
Error constant	RSE_CLIENT_READ_TIMEOUT
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Application timeout limit

Probable cause

The Relay Server was expecting more bytes in the request but the client did not send any. The request was aborted. The client will likely see an error and should retry the request.

1.8.2.53 RSE4002: Communication error [SYS%1: %2] occurred while reading from client of backend server '%3' in backend farm '%4'

Error code	4002
Error constant	RSE_CLIENT_READ_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

This can be caused by a network communication issue between the Relay Server and the client. The request was aborted. The client will likely see an error and should retry the request.

1.8.2.54 RSE4003: Client of backend server '%1' in backend farm '%2' timed out waiting for backend server response after '%3' seconds

Error code	4003
Error constant	RSE_CLIENT_TIMEOUT_WAITING_FOR_RESPONSE
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Application timeout limit

Probable cause

The client was expecting a backend server response but the backend server did not send it on time. The request was aborted. The client will likely see an error and should retry the request.

1.8.2.55 RSE4004: Outbound enabler of backend server '%1' in backend farm '%2' reports session error '%7' '%3' with parameters '%4', '%5', '%6'

Error code	4004
Error constant	RSE_CLIENT_RSOE_REPORT_SESSION_ERROR
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Outbound enabler error code
Parameter 4	Outbound enabler error parameter number 1
Parameter 5	Outbound enabler error parameter number 2
Parameter 6	Outbound enabler error parameter number 3
Parameter 7	Qualifier for the class of error. OEF for fatal error or OEE for non-fatal error

Probable cause

The outbound enabler reported an error handling traffic for the client session. The session was aborted. The client will likely see an error and should retry the request.

1.8.2.56 RSE4005: Aborting client request to backend server '%1' in backend farm '%2' due to backend server being unavailable

Error code	4005
Error constant	RSE_CLIENT_ABORT_BY_BACKEND_DOWN
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The outbound enabler will continue to monitor the backend server and attempt to recover service automatically when the backend server is restored.

1.8.2.57 RSE4006: Aborting client request to backend server '%1' in backend farm '%2' due to outbound enabler shutdown

Error code	4006
Error constant	RSE_CLIENT_ABORT_BY_OE_SHUTDOWN
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

Service from this backend server will not be available unless the outbound enabler for the backend server is restarted.

1.8.2.58 RSE4007: Aborting client request to backend server '%1' in backend farm '%2' due to unexpected down channel packet opcode %3 from the outbound enabler

Error code	4007
Error constant	RSE_CLIENT_ABORT_BY_RSOE_PROTOCOL_ERROR
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Down channel packet opcode

Probable cause

Make sure only outbound enablers are accessing the server extension. If this error persists, please contact technical support.

1.8.2.59 RSE4008: Communication error [SYS%1: %2] occurred while writing response to client of backend server '%3' in backend farm '%4' when '%5'

Error code	4008
Error constant	RSE_CLIENT_WRITE_FAIL
Parameter 1	System error code if any, otherwise 0
Parameter 2	System error message if any, otherwise NULL
Parameter 3	Backend server name
Parameter 4	Backend farm name
Parameter 5	Internal context

Probable cause

The client request was aborted but the backend server should remain usable to other clients. If this error persists, please contact technical support.

1.8.2.60 RSE4009: Unexpected end of request while reading from client of backend server '%1' in backend farm '%2'

Error code	4009
Error constant	RSE_CLIENT_READ_NOT_ENOUGH_CONTENT
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

There was an error at the client or in an intermediary that caused the request to end prematurely. The client should retry the request. If this error persists, please contact technical support.

1.8.2.61 RSE4010: Client of backend server '%1' in backend farm '%2' ignoring mis-routed OE_SERVER_RESPONSE packet with request index %3

Error code	4010
Error constant	RSE_CLIENT_UNEXPECTED_REQUEST_INDEX
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Internal request index

Probable cause

The mis-routed packet was ignored and was not delivered to the client. The request from the intended client of the mis-routed packet will be aborted. If this error persists, please contact technical support.

1.8.2.62 RSE4011: Client of backend server '%1' in backend farm '%2' ignored mis-routed OE_SERVER_RESPONSE packet with session number %3

Error code	4011
Error constant	RSE_CLIENT_UNEXPECTED_SESSION_NUMBER
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Internal session number

Probable cause

The mis-routed packet was ignored and was not delivered to the client. The session from the intended client of the mis-routed packet will be aborted. If this error persists, please contact technical support.

1.8.2.63 RSE4012: Client of backend server '%1' in backend farm '%2' ignored mis-routed OE_SERVER_RESPONSE packet with session fingerprint %3 while expecting %4

Error code	4012
Error constant	RSE_CLIENT_UNEXPECTED_SESSION_FINGER_PRINT
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Internal session fingerprint of the received packet
Parameter 4	Internal session fingerprint of the request that received the packet

Probable cause

The mis-routed packet was ignored and was not delivered to the client. The session from the intended client of the mis-routed packet will be aborted. If this error persists, please contact technical support.

1.8.2.64 RSE4013: Forwarder certificate subject '%1' does not match pattern '%2'

Error code	4013
Error constant	RSE_CLIENT_MISMATCH_FORWARDER_SUBJECT
Parameter 1	Subject of forwarder certificate
Parameter 2	Required pattern

Probable cause

The forwarder certificate was issued with a subject not matching the required pattern specified in the forwarder_certificate_subject property of the backend farm in the Relay Server configuration. Make sure the forwarder has a valid certificate and the pattern is specified correctly.

1.8.2.65 RSE4014: Forwarder certificate issuer '%1' does not match pattern '%2'

Error code	4014
Error constant	RSE_CLIENT_MISMATCH_FORWARDER_ISSUER
Parameter 1	Issuer of forwarder certificate
Parameter 2	Required pattern

Probable cause

The forwarder certificate issuer does not match the required pattern specified in the forwarder_certificate_issuer property of the backend farm in the Relay Server configuration. Make sure the forwarder has a valid certificate and the pattern is specified correctly.

1.8.2.66 RSE4015: Outbound enabler of backend server '%1' in backend farm '%2' reports session error %3 with parameters '%4', '%5', '%6'

Error code	4015
Error constant	RSE_CLIENT_RSOE_REPORT_SESSION_ERR
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Outbound enabler error name and id
Parameter 4	Outbound enabler error parameter number 1
Parameter 5	Outbound enabler error parameter number 2
Parameter 6	Outbound enabler error parameter number 3

Probable cause

The outbound enabler reported an error handling traffic for the client session. The session was aborted. The client will likely see an error and should retry the request.

1.8.2.67 RSE4016: Failed to extract next header from response near '%1'

Error code	4016
Error constant	RSE_CLIENT_RESPONSE_HEADER_ERR
Parameter 1	Content of the malformed response near where the problem occurs

Probable cause

The Relay Server failed to process the server response while extracting HTTP headers. The server response may be malformed. Use verbosity level 5 to examine the server response to identify the source of the malformed data. Removing or correcting the malformed data depends on the backend deployment environment and is beyond the scope of this error description.

1.8.2.68 RSE4017: The Outbound enabler reports error %1(%2) with parameters (%3)

Error code	4017
Error constant	RSE_CLIENT_RSOE_REPORT_ABORTED
Parameter 1	Outbound enabler error name
Parameter 2	Outbound enabler error id
Parameter 3	List of Outbound enabler error parameters separated by #

Probable cause

The outbound enabler reported an abortion when relaying a client request.

1.8.2.69 RSF11000: Relay Server list is too long. Outbound enabler connection aborted

Error code	11000
Error constant	RSF_ROOT_RS_LIST_TOO_LONG

Probable cause

This error should be rare. The Relay Server has a limit on the total size of the configuration. The number of Relay Servers in the farm as well as the size of host names contribute to the total list size. Replacing host names with the dotted ip address, or removing domain names from configuration entries, or reducing the number of Relay Servers, can relieve the problem. These changes can be made with a Relay Server configuration update.

1.8.2.70 RSF11001: Shared memory exhausted when '%1'

Error code	11001
Error constant	RSF_ROOT_OUT_OF_SHM
Parameter 1	Internal context

Probable cause

The Relay Server failed to allocate a memory block from the pre-allocated shared memory, which has a fixed size determined on start up. The size is optionally specified using the `shared_mem` property in the options section in the Relay Server configuration file. The default value is 10M and changing this value requires restarting the Relay Server.

1.8.2.71 RSF11002: System error [SYS%1: %2] occurred while initializing resources for remote administration

Error code	11002
Error constant	RSF_ROOT_ADMIN_USE_FAIL
Parameter 1	System error code
Parameter 2	System error message

Probable cause

There was a resource problem preventing remote administration. Please fix the problem according to the system error.

1.8.2.72 RSF11003: System error [SYS%1: %2] occurred while writing the entire configuration to file '%3'

Error code	11003
Error constant	RSF_ROOT_WRITE_CONFIG_FILE_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Relay Server configuration file

Probable cause

The configuration was applied to the Relay Server and is in effect but the configuration file update failed. Restarting the Relay Server will revert to the last saved configuration. Please fix the problem according to the system error.

1.8.2.73 RSF11004: Out of memory while reading new configuration

Error code	11004
Error constant	RSF_ROOT_ADMIN_OUT_OF_MEM

Probable cause

The configuration update was aborted due to lack of memory. If this is an IIS based Relay Server, please check if the application pool setting is limiting memory usage of your Relay Server web server extensions. Increasing the maximum number of worker processes in the application pool on 32-bit IIS will help spread the load. Upgrading to a 64-bit Relay Server or adding another Relay Server to the Relay Server farm can also be valid solutions. Offloading other applications running on the Relay Server machine to other machines may also help.

1.8.2.74 RSF11005: Protocol error when '%1'

Error code	11005
Error constant	RSF_ROOT_ADMIN_PROTOCOL_ERROR
Parameter 1	Internal context

Probable cause

The administration request was invalid. Remote access of the administration extension should be secured with HTTP authentication and HTTPS so as to protect against invalid accesses.

1.8.2.75 RSF11006: Failed to open '%1' to apply a configuration update

Error code	11006
Error constant	RSF_ROOT_OPEN_CONFIG_FILE_FAIL
Parameter 1	Relay Server configuration file

Probable cause

The configuration was applied to the Relay Server and is in effect but the configuration file update failed. Restarting the Relay Server will revert to the last saved configuration. Make sure the Relay Server state manager process has sufficient permission to open the configuration for update.

1.8.2.76 RSF11007: System error [SYS%1: %2] occurred while updating configuration

Error code	11007
Error constant	RSF_ROOT_ADMIN_RECONFIG_FAIL
Parameter 1	System error code
Parameter 2	System error message

Probable cause

Reconfiguration of the Relay Server failed. The resulting configuration may be corrupted and may require fixing with a further configuration update. The original configuration file will not have been updated with the failed configuration. Please fix the problem according to the system error.

1.8.2.77 RSF11008: Timed out waiting for administration command after %1 seconds

Error code	11008
Error constant	RSF_ROOT_ADMIN_READ_TIMEOUT
Parameter 1	Administration timeout limit

Probable cause

The Relay Server was expecting more administration commands but the remote administration tool did not send them on time. The request was aborted. Please retry again. If this error persists, please contact technical support.

1.8.2.78 RSF11009: The remote administration tool disconnected prematurely

Error code	11009
Error constant	RSF_ROOT_ADMIN_DISCONNECT_EARLY

Probable cause

This can be caused by a network problem or abrupt termination of the remote administration tool. Please try again.

1.8.2.79 RSF11010: Communication error [SYS%1: %2] occurred while reading from remote administration tool

Error code	11010
Error constant	RSF_ROOT_ADMIN_READ_FAIL
Parameter 1	System error code
Parameter 2	System error message

Probable cause

This can be caused by a network communication issue between the Relay Server and the remote administration tool. The request was aborted. Please try again.

1.8.2.80 RSF11011: Cannot continue to process ADMIN_CMD_CONFIG_CONTINUE packet due to previous error

Error code	11011
Error constant	RSF_ROOT_ADMIN_CONTINUE_FAIL

Probable cause

Please refer to previous error with the same line label to inspect the cause of the problem.

1.8.2.81 RSF11012: Expecting section header at line %1 in configuration file '%2'

Error code	11012
Error constant	RSF_ROOT_CONFIG_EXPECT_SECTION_HEADER
Parameter 1	Line number
Parameter 2	Relay Server configuration file

Probable cause

The given Relay Server configuration file is missing a required section header entry at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.82 RSF11013: System error [SYS%1: %2] occurred while archiving log file '%3' into '%4'

Error code	11013
Error constant	RSF_ROOT_ADMIN_ARCHIVE_LOG_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Current log file name
Parameter 4	Archive log file name if available otherwise empty

Probable cause

Encountered a system error while creating an archive log, copying current log content over or truncating the current log. Please fix the problem according to the system error.

1.8.2.83 RSF11014: Communication error [SYS%1: %2] occurred while writing response back to remote administration tool

Error code	11014
Error constant	RSF_ROOT_ADMIN_WRITE_FAIL
Parameter 1	System error code
Parameter 2	System error message

Probable cause

There was a communication error reporting back to the remote administration tool. The request was aborted, after reconfiguration occurred. Please try again.

1.8.2.84 RSF11015: Invalid opcode in monitor command packet

Error code	11015
------------	-------

Probable cause

Please make sure only the SA monitor is accessing the monitor extension. If this error persists, please contact technical support.

i Note

Adobe will stop updating and distributing the Flash Player at the end of 2020. Because the SQL Anywhere Monitor is based on Flash, you cannot use it once Flash support ends. In many cases, tasks that were previously performed in the Monitor can be performed in the SQL Anywhere Cockpit. See [SQL Anywhere Monitor Non-GUI User Guide](#).

1.8.2.85 RSF11016: Freeing already freed memory block in shared memory

Error code	11016
Error constant	RSF_ROOT_MEMORY_ALREADY_FREED

Probable cause

This is an internal error. The shared memory manager inside the Relay Server is protected against this type of error and the Relay Server should remain stable without requiring a restart. If this error persists, please contact technical support.

1.8.2.86 RSF11018: Cannot add backend server '%1' as it is already defined in backend farm '%2'

Error code	11018
Error constant	RSF_ROOT_SERVER_PREVIOUSLY_DEFINED
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

This error occurs during Relay Server configuration and will not affect other parts of the configuration operation. However, the new configuration of the previously defined backend server was not applied to the Relay Server. You may need to reapply the Relay Server configuration. If this error persists, please contact technical support.

1.8.2.87 RSF11019: Failed initializing resource for accessing backend server '%1' in farm '%2'

Error code	11019
Error constant	RSF_ROOT_INIT_SERVER_FAIL
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

This may be caused by failing to allocate a memory block from the pre-allocated shared memory which has a fixed size determined on start up. The size is optionally specified using the `shared_mem` property in the options section in the Relay Server configuration file. The default value is 10M and changing this value requires restarting the Relay Server. This error can also be caused by other system resource limitations.

1.8.2.88 RSF11020: Missing required section '%1' in configuration file '%2'

Error code	11020
Error constant	RSF_ROOT_CONFIG_MISSING_SECTION
Parameter 1	Configuration section name
Parameter 2	Relay Server configuration file

Probable cause

The given Relay Server configuration file is missing a required section entry at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.89 RSF11021: Failed preparing shared log

Error code	11021
Error constant	RSF_ROOT_FAILED_PREPARE_SHARED_LOG

Probable cause

Make sure the state manager is running. If this error persists, please contact technical support.

1.8.2.90 RSF11022: Failed setting up data structure for all Relay Servers in the configuration

Error code	11022
Error constant	RSF_ROOT_FAILED_SETUP_RS_LIST

Probable cause

This can be caused by either having redundant Relay Servers in the configuration or the Relay Server running out of resources while creating the list of all Relay Servers. Make sure the configuration has uniquely-named Relay Servers and/or make sure there are sufficient resources on the machine running the Relay Server.

1.8.2.91 RSF11023: Relay Server '%1' is previously defined in the configuration

Error code	11023
Error constant	RSF_ROOT_RS_PREVIOUSLY_DEFINED
Parameter 1	Relay Server host name

Probable cause

No two Relay Servers can share the same host name. Make sure each Relay Server in the Relay Server farm has a unique name.

1.8.2.92 RSF11024: Failed preparing backend farms information

Error code	11024
Error constant	RSF_ROOT_FAILED_PREPARE_FARMS

Probable cause

Failed to prepare some of the backend farm(s). Errors with the same line label that come before this error in the log file may contain further details.

1.8.2.93 RSF11025: Out of heap memory

Error code	11025
Error constant	RSF_ROOT_OUT_OF_MEM

Probable cause

If this is an IIS based Relay Server, please check if the application pool setting is limiting memory usage of your Relay Server web server extensions. Increasing the maximum number of worker processes in the application pool on 32-bit IIS will help spread the load. Upgrading to a 64-bit Relay Server or adding Relay Server to the Relay Server farm can also be valid solutions. Offloading other applications running on the Relay Server computer to other computers may also help.

1.8.2.94 RSF11026: System error [SYS%1: %2] occurred while creating internal data structure on start up

Error code	11026
Error constant	RSF_ROOT_FAILED_CREATE_ROOT
Parameter 1	System error code
Parameter 2	System error message

Probable cause

Please fix the problem according to the system error.

1.8.2.95 RSF11027: System error [SYS%1: %2] occurred while initializing internal data structures

Error code	11027
Error constant	RSF_ROOT_FAILED_INIT_ROOT
Parameter 1	System error code
Parameter 2	System error message

Probable cause

Please fix the problem according to the system error.

1.8.2.96 RSF11028: System error [SYS%1: %2] occurred while creating shared memory. Please shutdown any running rshost processes and restart the web server before retrying

Error code	11028
Error constant	RSF_ROOT_FAILED_CRT_SHM
Parameter 1	System error code
Parameter 2	System error message

Probable cause

Shutdown any running rshost processes and restart the web server before retrying. If this error persists, please contact technical support.

1.8.2.97 RSF11029: Failed to create semaphore manager

Error code	11029
Error constant	RSF_ROOT_FAILED_CREATE_SEM_MGR

Probable cause

Please make sure your system is not running out of System V semaphores.

1.8.2.98 RSF11030: System error [SYS%1: %2] occurred while initializing shared data structures

Error code	11030
Error constant	RSF_ROOT_FAILED_INIT_ROOT_USE
Parameter 1	System error code
Parameter 2	System error message

Probable cause

Please fix the problem according to the system error.

1.8.2.99 RSF11031: Failed attaching to shared memory of Relay Server '%1'

Error code	11031
Error constant	RSF_ROOT_FAILED_ATTACH_SHM
Parameter 1	Internal name of the Relay Server

Probable cause

This error can occur for several reasons. Verify the following: 1) Your Relay Server configuration file is valid. A simple and quick way to check is to manually run rshost with your configuration file. Check the Relay Server configuration file documentation for more details. 2) The rshost process has successfully started. Check the

log file to make sure rshost is running successfully. 3) The attaching process has permissions to attach to the shared memory. Make sure the attaching process user has system privileges equivalent to the rshost process user that created the shared memory.

1.8.2.100 RSF11032: System error [SYS%1: %2] occurred while attaching to shared log '%3'

Error code	11032
Error constant	RSF_ROOT_FAILED_ATTACH_LOG
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Shared log file name

Probable cause

Please fix the problem according to the system error.

1.8.2.101 RSF11033: Failed to update data structure for the list of Relay Servers in the configuration

Error code	11033
Error constant	RSF_ROOT_FAILED_UPDATE_RS_LIST

Probable cause

Either there was an error broadcasting the update to some connected outbound enabler or there was a shared memory exhaustion during the update operation. Errors with the same line label that come before this error in the log file may contain more information. Increase the shared_mem property in the options section in the Relay Server configuration and restart the Relay Server.

1.8.2.102 RSF11034: Failed to apply backend farm changes

Error code	11034
------------	-------

Error constant

RSF_ROOT_FAILED_UPDATE_FARM

Probable cause

Failed to update configuration for some of the backend farm(s). The configuration update was only partially applied. Please retry again. Errors with the same line label that come before this error in the log file may contain more information.

1.8.2.103 RSF11035: Failed to apply backend server changes

Error code

11035

Error constant

RSF_ROOT_FAILED_UPDATE_SERVER

Probable cause

Failed to update configuration for some of the backend server(s). The configuration update was only partially applied. Please retry again. Errors with the same line label that come before this error in the log file may contain more information.

1.8.2.104 RSF11036: Failed broadcasting to backend server '%1' in backend farm '%2' because up channel was too busy

Error code

11036

Error constant

RSF_ROOT_BROADCAST_UPCH_TOO_BUSY

Parameter 1

Backend server name

Parameter 2

Backend farm name

Probable cause

The broadcast to this backend server has been skipped. Please retry updating the configuration.

1.8.2.105 RSF11037: Farm '%1' is already defined

Error code	11037
Error constant	RSF_ROOT_FARM_PREVIOUSLY_DEFINED
Parameter 1	Backend farm name

Probable cause

Relay Server configuration cannot contain redundant backend farm names. Make sure your backend farm names are unique.

1.8.2.106 RSF11038: System error [SYS%1: %2] occurred while renaming the log file '%3'

Error code	11038
Error constant	RSF_ROOT_RENAME_LOG_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Current log file name

Probable cause

Please fix the problem according to the system error.

1.8.2.107 RSF11039: Leaked a memory block in shared memory

Error code	11039
Error constant	RSF_ROOT_SHM_LEAK

Probable cause

This is an internal error. If this error persists, please contact technical support.

1.8.2.108 RSF11040: Cannot open Relay Server configuration file '%1'

Error code	11040
Error constant	RSF_ROOT_CONFIG_CANT_OPEN_FILE
Parameter 1	Relay Server configuration file

Probable cause

Make sure the Relay Server configuration file exists and is accessible to the rshost process.

1.8.2.109 RSF11041: Cannot unhide Relay Server configuration file '%1'

Error code	11041
Error constant	RSF_ROOT_CONFIG_CANT_UNHIDE
Parameter 1	Relay Server configuration file

Probable cause

The configuration file may be corrupted. A new hidden configuration file must be created using the dbfhide utility.

1.8.2.110 RSF11042: Bad syntax at line %1 in configuration file '%2'

Error code	11042
Error constant	RSF_ROOT_CONFIG_BAD_LINE_FMT
Parameter 1	Line number
Parameter 2	Relay Server configuration file

Probable cause

The given Relay Server configuration file contains bad syntax at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.111 RSF11043: Invalid section name at line %1 in configuration file '%2'

Error code	11043
Error constant	RSF_ROOT_CONFIG_BAD_SECTION_NAME
Parameter 1	Line number
Parameter 2	Relay Server configuration file

Probable cause

The given Relay Server configuration file contains an invalid section name at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.112 RSF11044: Invalid property name at line %1 in configuration file '%2'

Error code	11044
Error constant	RSF_ROOT_CONFIG_BAD_PROP_NAME
Parameter 1	Line number
Parameter 2	Relay Server configuration file

Probable cause

The given Relay Server configuration file contains an invalid property name at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.113 RSF11045: Invalid property value at line %1 in configuration file '%2'

Error code	11045
Error constant	RSF_ROOT_CONFIG_BAD_VALUE
Parameter 1	Line number
Parameter 2	Relay Server configuration file

Probable cause

The given Relay Server configuration file contains an invalid property value at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.114 RSF11046: Duplicate '%1' section at line %2 in configuration file '%3'

Error code	11046
Error constant	RSF_ROOT_CONFIG_CANT_REPEAT_SECTION
Parameter 1	Configuration section name
Parameter 2	Line number
Parameter 3	Relay Server configuration file

Probable cause

The given Relay Server configuration file contains a duplicate section at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.115 RSF11047: Missing required property '%1' at line %2 in configuration file '%3'

Error code	11047
------------	-------

Error constant	RSF_ROOT_CONFIG_MISSING_PROP
Parameter 1	Property name
Parameter 2	Line number
Parameter 3	Relay Server configuration file

Probable cause

The given Relay Server configuration file is missing a required property entry at the given line number. Either use the administration tool to generate the configuration file, or consult the configuration-file documentation and fix the file directly.

1.8.2.116 RSF11048: An invalid change to '%1' has been detected on line %2 with %3 status. The problem needs to be corrected, otherwise, the Relay Server cannot be restarted

Error code	11048
Error constant	RSF_ROOT_CONFIG_FILE_INVALID
Parameter 1	Relay Server configuration file
Parameter 2	Line number
Parameter 3	Status

Probable cause

The Relay Server configuration file has been modified in an invalid way. The problem needs to be corrected immediately, otherwise the Relay Server cannot be restarted.

1.8.2.117 RSF11049: Failed to initialize the Relay Server

Error code	11049
Error constant	RSF_ROOT_INIT_FAILED

Probable cause

This is an internal error. If this error persists, please contact technical support.

1.8.2.118 RSF11050: Giving up initializing the Relay Server after too long

Error code	11050
Error constant	RSF_ROOT_INIT_TOO_LONG

Probable cause

The Relay Server machine might be overload by other processes. Stop running them and try again.

1.8.2.119 RSF12000: System error [SYS%1: %2] occurred while initializing resource for accessing backend farm '%3'

Error code	12000
Error constant	RSF_FARM_FAIL_ACCESS
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend farm name

Probable cause

Please fix the problem according to the system error.

1.8.2.120 RSF13000: System error [SYS%1: %2] occurred while generating acceptor uuid for backend server '%3' in backend farm '%4'

Error code	13000
Error constant	RSF_SERVER_RS_UUID_GENERATION_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

Please fix the problem according to the system error.

1.8.2.121 RSF13001: System error [SYS%1: %2] occurred while initializing resource for accessing backend server '%3' in backend farm '%4'

Error code	13001
Error constant	RSF_SERVER_INIT_FAIL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

Please fix the problem according to the system error.

1.8.2.122 RSF13002: Failed to lock request list of backend server '%1' in backend farm '%2' for writing

Error code	13002
Error constant	RSF_SERVER_FAIL_WLOCK_REQUEST_LIST
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The backend server may become unusable until the outbound enabler is restarted. If this error persists, please contact technical support.

1.8.2.123 RSF13003: System error [SYS%1: %2] occurred while initializing request list for backend server '%3' in backend farm '%4'

Error code	13003
Error constant	RSF_SERVER_FAIL_INIT_REQUEST_LIST
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

Please fix the problem according to the system error. The outbound enabler should automatically recover the service.

1.8.2.124 RSF13004: System error [SYS%1: %2] occurred while releasing up channel idle semaphore for backend server '%3' in backend farm '%4'

Error code	13004
Error constant	RSF_SERVER_FAIL_SIGNIFYING_UPCHANNEL_IDLE
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

The backend server may become unstable until the Relay Server is restarted. If this error persists, please contact technical support.

1.8.2.125 RSF13005: The outbound enabler for backend server '%1' in backend farm '%2' is sending %3 bytes beyond channel limit

Error code	13005
Error constant	RSF_SERVER_CONTENT_OVERFLOW
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Number of extra bytes

Probable cause

This is an internal outbound enabler error. If this error persists, please contact technical support.

1.8.2.126 RSF13006: Failed to lock request list of backend server '%1' in backend farm '%2' for reading

Error code	13006
Error constant	RSF_SERVER_FAIL_RLOCK_REQUEST_LIST
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The backend server may become unusable until the outbound enabler is restarted. If this error persists, please contact technical support.

1.8.2.127 RSF13007: Failed locking download packet queue of a client of backend server '%1' in backend farm '%2' for pushing a %3 packet

Error code	13007
Error constant	RSF_SERVER_FAIL_LOCK_PUSH_DNQ
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Packet name

Probable cause

The response to a client request was not delivered but the backend server should remain usable to other clients. The client will likely receive an error and should retry again. If this error persists, please contact technical support.

1.8.2.128 RSF13008: System error [SYS%1: %2] occurred while initializing semaphore for download packet queue of backend server '%3' in backend farm '%4' while pushing a %5 packet

Error code	13008
Error constant	RSF_SERVER_FAIL_INIT_DNQ_SEMA
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name
Parameter 5	Packet name

Probable cause

Please fix the problem according to the system error.

1.8.2.129 RSF13009: Missing request list for backend server '%1' in backend farm '%2'

Error code	13009
Error constant	RSF_SERVER_MISSING_REQUEST_LIST
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The outbound enabler should automatically recover the service. If this error persists, please contact technical support.

1.8.2.130 RSF13010: Detected faulty request index recycling on backend server '%1' in backend farm '%2'

Error code	13010
Error constant	RSF_SERVER_FAULTY_REQUEST_IDX_RECYCLING
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

A client request and response may not have been routed properly but the backend server should remain usable for other clients. If this error persists, please contact technical support.

1.8.2.131 RSF13011: Failed allocating shared memory block for client traffic statistic collector of backend server '%1' in backend farm '%2'

Error code	13011
Error constant	RSF_SERVER_FAIL_NEWING_CLIENT_STATISTIC
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The client request was aborted but the backend server should remain usable. The low memory situation may be caused by temporarily high traffic volume. If this error persists, please consider increasing the shared memory limit and restart the Relay Server.

1.8.2.132 RSF14000: System error [SYS%1: %2] occurred while initializing access to backend server '%3' in backend farm '%4'

Error code	14000
------------	-------

Error constant	RSF_CLIENT_FAIL_INIT_SERVER_ACCESS
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

The client request was aborted. Please attempt to fix the problem according to the system error. If this error persists, please contact technical support.

1.8.2.133 RSF14001: Failed to lock request list of backend server '%1' in backend farm '%2' for writing when '%3'

Error code	14001
Error constant	RSF_CLIENT_FAIL_WLOCK_REQUEST_LIST
Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Internal context

Probable cause

The backend server was too busy. The client request was aborted. To handle the load, you may need to add more backend servers or more Relay Servers.

1.8.2.134 RSF14002: Failed allocating shared memory block for client of backend server '%1' in backend farm '%2' when '%3'

Error code	14002
Error constant	RSF_CLIENT_OUT_OF_SHM

Parameter 1	Backend server name
Parameter 2	Backend farm name
Parameter 3	Internal context

Probable cause

The client request was aborted but the backend server should remain usable for other clients. The low memory situation may be caused by temporary high traffic volume. If this error persists, please consider increasing the shared memory limit and restart the Relay Server.

1.8.2.135 RSF14003: System error [SYS%1: %2] occurred while initializing request targeting backend server '%3' in backend farm '%4'

Error code	14003
Error constant	RSF_CLIENT_FAIL_INIT_REQUEST
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Backend server name
Parameter 4	Backend farm name

Probable cause

The client request was aborted but the backend server should remain usable for other clients. Please fix the problem according to the system error.

1.8.2.136 RSF14004: Heap memory exhausted while client of backend server '%1' in backend farm '%2' is '%3'

Error code	14004
Error constant	RSF_CLIENT_OUT_OF_MEM
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The client request was aborted but the backend server should remain usable for other clients. The low memory situation may be caused by temporary high traffic volume. If this error persists on an IIS based Relay Server, please check if the application pool setting is limiting memory usage of your Relay Server web server extensions. Increasing the maximum number of worker processes in the application pool on a 32-bit IIS will help spread the load. Upgrading to a 64-bit Relay Server or adding Relay Servers to the Relay Server farm can also be valid solutions. Offloading other applications running on the Relay Server machine to other machines may also help.

1.8.2.137 RSF14005: Removed unexpected request from request list of backend server '%1' in backend farm '%2'

Error code	14005
Error constant	RSF_CLIENT_REMOVED_WRONG_REQUEST
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

The client request was aborted but the backend server should remain usable for other clients. If this error persists, please contact technical support.

1.9 Relay Server Warning Messages

The Relay Server warning messages are written to the Relay Server message log.

Each error has a numeric error code. Many of the error messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the error message.

The text of each error message contains a prefix describing the type of error or warning:

RSE

Relay Server error.

RSF

Relay Server fatal error.

RSW

Relay Server warning.

In this section:

[Relay Server Warning Messages Sorted by Error Code \[page 1388\]](#)

[Relay Server warning messages listed by message text \[page 1388\]](#)

Related Information

[Relay Server Error Messages \[page 1315\]](#)

1.9.1 Relay Server Warning Messages Sorted by Error Code

Error code	Message text
0	RSW0: No warning [page 1389]
100	RSW100: System error [SYS%1: %2] occurred while calling '%3' [page 1389]
101	RSW101: CPU monitoring is not available on this platform [page 1390]
102	RSW102: The backend connection was terminated before the entire chunked response body was received [page 1390]
103	RSW103: The backend connection was terminated before the entire content length response body was received. Remaining %1 of %2 bytes [page 1390]
104	RSW104: Ignoring invalid SAP Passport [page 1391]
105	RSW105: A change to '%1' has been detected and line %2 of the file is different from the configuration in use [page 1391]
106	RSW106: The '%1' property in the configuration is being ignored on this platform [page 1391]
107	RSW107: Too many type of clients has been accessing back-end server '%1' in backend farm '%2'. New metrics are no longer added [page 1392]

1.9.2 Relay Server warning messages listed by message text

In this section:

[RSW0: No warning \[page 1389\]](#)

[RSW100: System error \[SYS%1: %2\] occurred while calling '%3' \[page 1389\]](#)

[RSW101: CPU monitoring is not available on this platform \[page 1390\]](#)

[RSW102: The backend connection was terminated before the entire chunked response body was received \[page 1390\]](#)

[RSW103: The backend connection was terminated before the entire content length response body was received. Remaining %1 of %2 bytes \[page 1390\]](#)

[RSW104: Ignoring invalid SAP Passport \[page 1391\]](#)

[RSW105: A change to '%1' has been detected and line %2 of the file is different from the configuration in use \[page 1391\]](#)

[RSW106: The '%1' property in the configuration is being ignored on this platform \[page 1391\]](#)

[RSW107: Too many type of clients has been accessing backend server '%1' in backend farm '%2'. New metrics are no longer added \[page 1392\]](#)

1.9.2.1 RSW0: No warning

Error code	0
Error constant	RSW_NO_WARNING

Probable cause

There was no warning.

1.9.2.2 RSW100: System error [SYS%1: %2] occurred while calling '%3'

Error code	100
Error constant	RSW_SYS_CALL
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	Name of the system call

Probable cause

A non-fatal system call has failed. The Relay Server should remain operational.

1.9.2.3 RSW101: CPU monitoring is not available on this platform

Error code	101
Error constant	RSW_CPU_MON_NOT_AVAILABLE

Probable cause

The Relay Server cannot accurately report total CPU usage of all Relay Server related processes on this platform.

1.9.2.4 RSW102: The backend connection was terminated before the entire chunked response body was received

Error code	102
Error constant	RSW_CHUNKED_RESPONSE_NOT_COMPLETED

Probable cause

The result of this warning depends on the application protocol.

1.9.2.5 RSW103: The backend connection was terminated before the entire content length response body was received. Remaining %1 of %2 bytes

Error code	103
Error constant	RSW_CONTENT_LENGTH_RESPONSE_NOT_COMPLETED

Probable cause

The result of this warning depends on the application protocol.

1.9.2.6 RSW104: Ignoring invalid SAP Passport

Error code	104
Error constant	RSW_INVALID_SAP_PASSPORT

Probable cause

An invalid SAP-Passport header was found in the request and being ignored.

1.9.2.7 RSW105: A change to '%1' has been detected and line %2 of the file is different from the configuration in use

Error code	105
Error constant	RSW_CONFIG_OUT_OF_SYNC
Parameter 1	Configuration file
Parameter 2	Line number in the file

Probable cause

The configuration on disk is different from the in use copy. The difference is not in effect until either the Relay Server is restarted or the configuration file being applied using the online configuration tool.

1.9.2.8 RSW106: The '%1' property in the configuration is being ignored on this platform

Error code	106
Error constant	RSW_CONFIG_UNUSED_PROPERTY

Parameter 1

Property name

Probable cause

Setting this property on this Relay Server platform has no effect. Delete or unset the property can suppress this warning.

1.9.2.9 RSW107: Too many type of clients has been accessing backend server '%1' in backend farm '%2'. New metrics are no longer added

Error code	107
Error constant	RSW_TOO_MANY_TYPE_OF_CLIENTS
Parameter 1	Backend server name
Parameter 2	Backend farm name

Probable cause

Traffic statistics are kept per type of client and there is an internal limit of 1600 types. The limit has been reached and the Relay Server stop creating metrics for new type of client.

1.10 Outbound Enabler Error Messages

The Outbound Enabler messages are written to the Outbound Enabler message log.

Each message has a numeric code. Many of the messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the message.

In this section:

[Outbound Enabler Error Messages Sorted by Error Code \[page 1393\]](#)

[Outbound Enabler Error Messages Listed by Message Text \[page 1398\]](#)

Related Information

[Outbound Enabler Warning Messages \[page 1438\]](#)

1.10.1 Outbound Enabler Error Messages Sorted by Error Code

Error code	Message text
0	OEE0: No error [page 1401]
1000	OEE1000: Unable to write a GET request to ping the backend server using http://%1:%2/%3. Ping again [page 1402]
1001	OEE1001: Unable to read response headers from the backend server ping using http://%1:%2/%3. Pinging again [page 1402]
1002	OEE1002: Unexpected HTTP status code %1 from ping of backend server using http://%2:%3/%4. Pinging again [page 1403]
1003	OEE1003: Missing Content-Length header in response to backend server ping using http://%1:%2/%3. Pinging again [page 1403]
1004	OEE1004: Missing or malformed body found in response to backend server ping using http://%1:%2/%3. Pinging again [page 1404]
1005	OEE1005: Unable to find 'AVAILABLE=' in backend status ping response body from http://%1:%2/%3. Pinging again [page 1404]
1006	OEE1006: The Outbound Enabler does not recognize 'AVAILABLE=%1' in the response to the backend server status ping to http://%2:%3/%4. Valid values are 1, T, TRUE, ON, O, F, FALSE and OFF. Pinging again [page 1405]
1007	OEE1007: The Output Enabler backend server status ping to http://%1:%2/%3 reported service unavailable. Pinging again [page 1405]
1008	OEE1008: Unable to find nor shut down an Outbound Enabler for server '%1' of farm '%2' using relay server '%3%4' [page 1406]
1009	OEE1009: Unable to perform a network read from the Relay Server because of [MLC%1: %2] [page 1406]
1010	OEE1010: The Outbound Enabler cannot handle the WWW-Authenticate header in the response because of [MLC%1: %2] [page 1407]

Error code	Message text
1011	OEE1011: The Outbound Enabler cannot handle the Proxy-Authenticate header in the response because of [MLC%1: %2] [page 1407]
1012	OEE1012: The Outbound Enabler cannot handle the Authentication-Info header in the response because of [MLC%1: %2] [page 1408]
1013	OEE1013: The Outbound Enabler cannot handle the Proxy-Authentication-Info header in the response because of [MLC %1: %2] [page 1408]
1014	OEE1014: The length of an HTTP chunk length received from the Relay Server is too big [page 1409]
1015	OEE1015: An HTTP chunk length received from the Relay Server is malformed [page 1409]
1016	OEE1016: An HTTP chunk received from the Relay Server is missing a trailing CRLF [page 1409]
1017	OEE1017: The Outbound Enabler received an HTTP error status from the Relay Server:\r %1 [page 1410]
1018	OEE1018: Outbound Enabler connections to the Relay Server Web server require HTTP authentication, but no credentials were provided [page 1410]
1019	OEE1019: An Outbound Enabler connection to the Relay Server failed HTTP authentication [page 1411]
1020	OEE1020: Outbound Enabler connections to the Relay Server Web server are going through a proxy requiring proxy HTTP authentication, but no credentials were provided [page 1411]
1021	OEE1021: An Outbound Enabler connection to the Relay Server failed HTTP proxy authentication [page 1411]
1022	OEE1022: The Outbound Enabler received an unexpected HTTP error status:\r %1 [page 1412]
1023	OEE1023: The Outbound Enabler is missing the -cr http_password parameter [page 1412]
1024	OEE1024: The Outbound Enabler is missing the -cr http_proxy_password parameter [page 1412]
1025	OEE1025: The Outbound Enabler is missing the -cr http_userid parameter [page 1413]
1026	OEE1026: The Outbound Enabler is missing the -cr http_proxy_userid parameter [page 1413]
1027	OEE1027: The Outbound Enabler was unable to write an HTTP header to the Relay Server because of [MLC%1: %2] [page 1414]
1028	OEE1028: The Outbound Enabler was unable to write an HTTP body to the Relay Server because of [MLC%1: %2] [page 1414]

Error code	Message text
1029	OEE1029: The Outbound Enabler received an HTTP cookie or header from a client indicating the client cached it from a previous Relay Server configuration. The unexpected Relay Server index is: %1 [page 1415]
1030	OEE1030: The Outbound Enabler was unable to connect to the Relay Server using '%1' because of [MLC%2: %3]. Retrying [page 1415]
1031	OEE1031: The Outbound Enabler access was denied by the Relay Server [page 1416]
1032	OEE1032: Retry due to issue with the Relay Server [page 1416]
1033	OEE1033: The Outbound Enabler is unable to connect to the backend server at %1:%2 to ping it. Pinging again [page 1416]
1034	OEE1034: Communication error with backend server: '%1' [page 1417]
1035	OEE1035: Invalid tls_type %1 given to the Outbound Enabler's -cs switch. Only RSA is supported [page 1417]
1036	OEE1036: A network connection was closed by the Relay Server or an intermediary while the Outbound Enabler was reading from it [page 1418]
1037	OEE1037: The Outbound Enabler -cr switch is missing the %1 parameter [page 1418]
1038	OEE1038: Invalid Outbound Enabler command line near '%1' [page 1418]
1039	OEE1039: The Outbound Enabler connection to the Relay Server using '%1' failed because of [MLC%2: %3] [page 1419]
1040	OEE1040: The Outbound Enabler was unable to initialize secure communications to the backend server because of [MLC%1: %2] [page 1419]
1041	OEE1041: The Outbound Enabler -cr switch does not specify a valid Relay Server. The HTTP response from the server has the following headers: %1 [page 1420]
1042	OEE1042: The Relay Server needs to be upgraded in order to be compatible with this Outbound Enabler [page 1420]
1043	OEE1043: The Relay Server at host '%1' lacks a %2 entry in the Relay Server configuration [page 1420]
1044	OEE1044: The Outbound Enabler was unable to determine the MAC addresses of this machine [page 1421]
1045	OEE1045: System error [SYS%1: %2] while %3 with the backend server for sidx=%4 socket=%5 sfp=%6 [page 1421]

Error code	Message text
1046	OEE1046: Connecting to backend server at %1:%2 failed because of [MLC%3: %4] [page 1422]
1047	OEE1047: Error parsing the value of the Outbound Enabler - cs %1 parameter [page 1422]
1048	OEE1048: The communication between the Outbound Enabler and the backend server failed with [MLC%1: %2] while %3. sidx=%4 socket=%5 sfp=%6 [page 1423]
1049	OEE1049: The request URL is too long. Request with sidx=%1 sfp=%2 is aborted [page 1423]
1050	OEE1050: Failed to lookup a session that has just started with ridx=%1 snum=%2 sfp=%3 on a %4 packet [page 1424]
1051	OEE1051: The Outbound Enabler was unable to access the session with ridx=%1 sidx=%2 snum=%3 sfp=%4 on a %5 packet due to %6 [page 1424]
1052	OEE1052: The Outbound Enabler was unable to write a %1 packet to the Relay Server because of [MCL%2: %3] [page 1425]
1053	OEE1053: The Outbound Enabler was unable to flush a packet to the Relay Server because of [MLC%1: %2] [page 1425]
1054	OEE1054: The Outbound Enabler was unable to write a %5 packet with ridx=%1 sidx=%2 snum=%3 sfp=%4 failed because of [MLC%6: %7] [page 1426]
1055	OEE1055: The Outbound Enabler was unable to create a session error packet with ridx=%1 sidx=%2 snum=%3 sfp=%4 err=%5 for Relay Server index %6 as it cannot be found [page 1426]
1056	OEE1056: Failed to report shutdown to the Relay Server [page 1427]
1057	OEE1057: Failed connecting to backend server because of [MLC%1: %2] [page 1427]
1058	OEE1058: Failed writing to the backend server because of [MLC%1: %2] [page 1428]
1059	OEE1059: Failed reading from the backend server because of [MLC%1: %2] [page 1428]
1060	OEE1060: Lost idle backend connection sooner than max_junction_idle_sec expires. Configure the backend server or the Relay Server configuration to agree on the idle timeout [page 1429]
1061	OEE1061: Failed writing to the Relay Server because of [MLC %1: %2] [page 1429]
1062	OEE1062: Failed reading from the Relay Server because of [MLC%1: %2] [page 1429]

Error code	Message text
1603	OEE1603: Not compatible with the Relay Server due to unknown protocol version %1 [page 1430]
1604	OEE1604: The Relay Server response with %1 instead of %2 [page 1430]
1605	OEE1605: The response does not originate from the Relay Server server extension [page 1431]
10000	OEF10000: Failed to initialize socket library [MLC%1: %2] [page 1431]
10001	OEF10001: Out of memory [page 1431]
10002	OEF10002: The Outbound Enabler was unable to create shared memory directory for communicating shutdown [page 1432]
10003	OEF10003: The Outbound Enabler was unable to create shared memory for communicating shutdown [page 1432]
10004	OEF10004: The 'rsoe -s' command failed shutting down Outbound Enabler for server '%1' of farm '%2' using relay server '%3%4' [page 1433]
10005	OEF10005: Unable to load the Outbound Enabler support library: %1 -- %2 [page 1433]
10006	OEF10006: The Outbound Enabler was unable to load required functions from the '%1' library [page 1433]
10007	OEF10007: Failed to initialize an Outbound Enabler support library '%1' [page 1434]
10008	OEF10008: Protocol error while reading %1 packet [page 1434]
10009	OEF10009: Reduced to lowest supported protocol version but the Relay Server is still not compatible [page 1435]
10010	OEF10010: Invalid opcode received from the Relay Server [page 1435]
10011	OEF10011: The Outbound Enabler was unable to load the %1 encryption library because of [%2]. Make it is installed properly [page 1435]
10012	OEF10012: The Outbound Enabler was unable to load function %1 from encryption library %2 [page 1436]
10013	OEF10013: Encryption library version mismatch. Found version %1.%2 with implementation id %3 [page 1436]
10014	OEF10014: Internal error: %1 [page 1437]
10015	OEF10015: Internal error, RSOE configuration file location not specified. Contact technical support for assistance if the issue persists [page 1437]

Error code	Message text
10016	OEF10016: An error occurred while processing RSOE configuration parameters. Please make sure the RSOE configuration file exists and configuration parameters are specified correctly [page 1437]
10017	OEF10017: Protocol error [page 1438]

1.10.2 Outbound Enabler Error Messages Listed by Message Text

In this section:

OEE0: No error [page 1401]

OEE1000: Unable to write a GET request to ping the backend server using http://%1:%2/%3. Ping again [page 1402]

OEE1001: Unable to read response headers from the backend server ping using http://%1:%2/%3. Pinging again [page 1402]

OEE1002: Unexpected HTTP status code %1 from ping of backend server using http://%2:%3/%4. Pinging again [page 1403]

OEE1003: Missing Content-Length header in response to backend server ping using http://%1:%2/%3. Pinging again [page 1403]

OEE1004: Missing or malformed body found in response to backend server ping using http://%1:%2/%3. Pinging again [page 1404]

OEE1005: Unable to find 'AVAILABLE=' in backend status ping response body from http://%1:%2/%3. Pinging again [page 1404]

OEE1006: The Outbound Enabler does not recognize 'AVAILABLE=%1' in the response to the backend server status ping to http://%2:%3/%4. Valid values are 1, T, TRUE, ON, O, F, FALSE and OFF. Pinging again [page 1405]

OEE1007: The Output Enabler backend server status ping to http://%1:%2/%3 reported service unavailable. Pinging again [page 1405]

OEE1008: Unable to find nor shut down an Outbound Enabler for server '%1' of farm '%2' using relay server '%3%4' [page 1406]

OEE1009: Unable to perform a network read from the Relay Server because of [MLC%1: %2] [page 1406]

OEE1010: The Outbound Enabler cannot handle the WWW-Authenticate header in the response because of [MLC%1: %2] [page 1407]

OEE1011: The Outbound Enabler cannot handle the Proxy-Authenticate header in the response because of [MLC%1: %2] [page 1407]

OEE1012: The Outbound Enabler cannot handle the Authentication-Info header in the response because of [MLC%1: %2] [page 1408]

OOE1013: The Outbound Enabler cannot handle the Proxy-Authentication-Info header in the response because of [MLC%1: %2] [page 1408]

OOE1014: The length of an HTTP chunk length received from the Relay Server is too big [page 1409]

OOE1015: An HTTP chunk length received from the Relay Server is malformed [page 1409]

OOE1016: An HTTP chunk received from the Relay Server is missing a trailing CRLF [page 1409]

OOE1017: The Outbound Enabler received an HTTP error status from the Relay Server:\r %1 [page 1410]

OOE1018: Outbound Enabler connections to the Relay Server Web server require HTTP authentication, but no credentials were provided [page 1410]

OOE1019: An Outbound Enabler connection to the Relay Server failed HTTP authentication [page 1411]

OOE1020: Outbound Enabler connections to the Relay Server Web server are going through a proxy requiring proxy HTTP authentication, but no credentials were provided [page 1411]

OOE1021: An Outbound Enabler connection to the Relay Server failed HTTP proxy authentication [page 1411]

OOE1022: The Outbound Enabler received an unexpected HTTP error status:\r %1 [page 1412]

OOE1023: The Outbound Enabler is missing the -cr http_password parameter [page 1412]

OOE1024: The Outbound Enabler is missing the -cr http_proxy_password parameter [page 1412]

OOE1025: The Outbound Enabler is missing the -cr http_userid parameter [page 1413]

OOE1026: The Outbound Enabler is missing the -cr http_proxy_userid parameter [page 1413]

OOE1027: The Outbound Enabler was unable to write an HTTP header to the Relay Server because of [MLC %1: %2] [page 1414]

OOE1028: The Outbound Enabler was unable to write an HTTP body to the Relay Server because of [MLC %1: %2] [page 1414]

OOE1029: The Outbound Enabler received an HTTP cookie or header from a client indicating the client cached it from a previous Relay Server configuration. The unexpected Relay Server index is: %1 [page 1415]

OOE1030: The Outbound Enabler was unable to connect to the Relay Server using '%1' because of [MLC %2: %3]. Retrying [page 1415]

OOE1031: The Outbound Enabler access was denied by the Relay Server [page 1416]

OOE1032: Retry due to issue with the Relay Server [page 1416]

OOE1033: The Outbound Enabler is unable to connect to the backend server at %1:%2 to ping it. Pinging again [page 1416]

OOE1034: Communication error with backend server: '%1' [page 1417]

OOE1035: Invalid tls_type %1 given to the Outbound Enabler's -cs switch. Only RSA is supported [page 1417]

OOE1036: A network connection was closed by the Relay Server or an intermediary while the Outbound Enabler was reading from it [page 1418]

OOE1037: The Outbound Enabler -cr switch is missing the %1 parameter [page 1418]

OOE1038: Invalid Outbound Enabler command line near '%1' [page 1418]

OOE1039: The Outbound Enabler connection to the Relay Server using '%1' failed because of [MLC%2: %3] [page 1419]

OOE1040: The Outbound Enabler was unable to initialize secure communications to the backend server because of [MLC%1: %2] [page 1419]

OOE1041: The Outbound Enabler -cr switch does not specify a valid Relay Server. The HTTP response from the server has the following headers: %1 [page 1420]

OOE1042: The Relay Server needs to be upgraded in order to be compatible with this Outbound Enabler [page 1420]

OOE1043: The Relay Server at host '%1' lacks a %2 entry in the Relay Server configuration [page 1420]

OOE1044: The Outbound Enabler was unable to determine the MAC addresses of this machine [page 1421]

OOE1045: System error [SYS%1: %2] while %3 with the backend server for sidx=%4 socket=%5 sfp=%6 [page 1421]

OOE1046: Connecting to backend server at %1:%2 failed because of [MLC%3: %4] [page 1422]

OOE1047: Error parsing the value of the Outbound Enabler -cs %1 parameter [page 1422]

OOE1048: The communication between the Outbound Enabler and the backend server failed with [MLC%1: %2] while %3. sidx=%4 socket=%5 sfp=%6 [page 1423]

OOE1049: The request URL is too long. Request with sidx=%1 sfp=%2 is aborted [page 1423]

OOE1050: Failed to lookup a session that has just started with ridx=%1 snum=%2 sfp=%3 on a %4 packet [page 1424]

OOE1051: The Outbound Enabler was unable to access the session with ridx=%1 sidx=%2 snum=%3 sfp=%4 on a %5 packet due to %6 [page 1424]

OOE1052: The Outbound Enabler was unable to write a %1 packet to the Relay Server because of [MCL%2: %3] [page 1425]

OOE1053: The Outbound Enabler was unable to flush a packet to the Relay Server because of [MLC%1: %2] [page 1425]

OOE1054: The Outbound Enabler was unable to write a %5 packet with ridx=%1 sidx=%2 snum=%3 sfp=%4 failed because of [MLC%6: %7] [page 1426]

OOE1055: The Outbound Enabler was unable to create a session error packet with ridx=%1 sidx=%2 snum=%3 sfp=%4 err=%5 for Relay Server index %6 as it cannot be found [page 1426]

OOE1056: Failed to report shutdown to the Relay Server [page 1427]

OOE1057: Failed connecting to backend server because of [MLC%1: %2] [page 1427]

OOE1058: Failed writing to the backend server because of [MLC%1: %2] [page 1428]

OOE1059: Failed reading from the backend server because of [MLC%1: %2] [page 1428]

OOE1060: Lost idle backend connection sooner than max_junction_idle_sec expires. Configure the backend server or the Relay Server configuration to agree on the idle timeout [page 1429]

OOE1061: Failed writing to the Relay Server because of [MLC%1: %2] [page 1429]

OOE1062: Failed reading from the Relay Server because of [MLC%1: %2] [page 1429]

OOE1603: Not compatible with the Relay Server due to unknown protocol version %1 [page 1430]

- OEE1604: The Relay Server response with %1 instead of %2 [page 1430]
- OEE1605: The response does not originate from the Relay Server server extension [page 1431]
- OEF10000: Failed to initialize socket library [MLC%1: %2] [page 1431]
- OEF10001: Out of memory [page 1431]
- OEF10002: The Outbound Enabler was unable to create shared memory directory for communicating shutdown [page 1432]
- OEF10003: The Outbound Enabler was unable to create shared memory for communicating shutdown [page 1432]
- OEF10004: The 'rsoe -s' command failed shutting down Outbound Enabler for server '%1' of farm '%2' using relay server '%3%4' [page 1433]
- OEF10005: Unable to load the Outbound Enabler support library: %1 -- %2 [page 1433]
- OEF10006: The Outbound Enabler was unable to load required functions from the '%1' library [page 1433]
- OEF10007: Failed to initialize an Outbound Enabler support library '%1' [page 1434]
- OEF10008: Protocol error while reading %1 packet [page 1434]
- OEF10009: Reduced to lowest supported protocol version but the Relay Server is still not compatible [page 1435]
- OEF10010: Invalid opcode received from the Relay Server [page 1435]
- OEF10011: The Outbound Enabler was unable to load the %1 encryption library because of [%2]. Make it is installed properly [page 1435]
- OEF10012: The Outbound Enabler was unable to load function %1 from encryption library %2 [page 1436]
- OEF10013: Encryption library version mismatch. Found version %1.%2 with implementation id %3 [page 1436]
- OEF10014: Internal error: %1 [page 1437]
- OEF10015: Internal error, RSOE configuration file location not specified. Contact technical support for assistance if the issue persists [page 1437]
- OEF10016: An error occurred while processing RSOE configuration parameters. Please make sure the RSOE configuration file exists and configuration parameters are specified correctly [page 1437]
- OEF10017: Protocol error [page 1438]

1.10.2.1 OEE0: No error

Error code	0
Error constant	OEE_NO_ERROR

Probable cause

This code indicates there was no Outbound Enabler error.

1.10.2.2 OEE1000: Unable to write a GET request to ping the backend server using http://%1:%2/%3. Ping again

Error code	1000
Error constant	OEE_BE_STATUS_PING_FAILED_WRITE
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter
Parameter 3	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler was unable to write a GET request to the backend server during a status check. Make sure the -cs host and port parameter are pointing to the HTTP port of the backend server. Also make sure the backend server has not issue starting up.

1.10.2.3 OEE1001: Unable to read response headers from the backend server ping using http://%1:%2/%3. Pinging again

Error code	1001
Error constant	OEE_BE_STATUS_PING_FAILED_READ_HDR
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter
Parameter 3	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler was unable to read response headers from the backend server during a status check. Make sure the backend server is capable of serving HTTP requests of the status URL on the specified host and port.

1.10.2.4 OEE1002: Unexpected HTTP status code %1 from ping of backend server using http://%2:%3/%4. Pinging again

Error code	1002
Error constant	OEE_BE_STATUS_PING_FAILED_HTTP_OK
Parameter 1	HTTP status code of the ping response
Parameter 2	Backend server host specified by the -cs host parameter
Parameter 3	Backend server port specified by the -cs port parameter
Parameter 4	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler was unable to verify a ping of the backend server because of an unexpected HTTP status code. The HTTP status code is expected to be 200 regardless of the availability of the backend server. Make sure the given URL is correct, then make sure the response HTTP status code is always 200. If the URL is correct but this error persists, contact the backend server vendor's technical support team.

1.10.2.5 OEE1003: Missing Content-Length header in response to backend server ping using http://%1:%2/%3. Pinging again

Error code	1003
Error constant	OEE_BE_STATUS_PING_FAILED_CONTENT_LENGTH
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter
Parameter 3	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler was unable to verify a ping of the backend server because of the missing header in the response. The response must carry a Content-Length header regardless of the availability of the backend server. Make sure the given URL is correct. If the URL is correct but this error persists, contact the backend server vendor's technical support team.

1.10.2.6 OEE1004: Missing or malformed body found in response to backend server ping using http://%1:%2/%3. Pinging again

Error code	1004
Error constant	OEE_BE_STATUS_PING_FAILED_READ_BODY
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter
Parameter 3	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler was unable to verify a ping of the backend server because of a missing or malformed response body. The body of the response must match Content-Length header. Make sure the given URL is correct. If the URL is correct but this error persists, contact the backend server vendor's technical support team.

1.10.2.7 OEE1005: Unable to find 'AVAILABLE=' in backend status ping response body from http://%1:%2/%3. Pinging again

Error code	1005
Error constant	OEE_BE_STATUS_PING_AVAILABLE_NOT_FOUND
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter
Parameter 3	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler was unable to verify a ping of the backend server because the body did not contain 'AVAILABLE='. Make sure the given URL is correct. If the URL is correct but this error persists, contact the backend server vendor's technical support team.

1.10.2.8 OEE1006: The Outbound Enabler does not recognize 'AVAILABLE=%1' in the response to the backend server status ping to http://%2:%3/%4. Valid values are 1, T, TRUE, ON, 0, F, FALSE and OFF. Pinging again

Error code	1006
Error constant	OEE_BE_STATUS_PING_FAILED_PARSE_AVAILABLE_VAL
Parameter 1	The value taken from AVAILABLE=value
Parameter 2	Backend server host specified by the -cs host parameter
Parameter 3	Backend server port specified by the -cs port parameter
Parameter 4	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler was unable to verify a ping of the backend server because the body did not contain an expected 'AVAILABLE=' value. Make sure the given URL is correct. If the URL is correct but this error persists, contact the backend server vendor's technical support team.

1.10.2.9 OEE1007: The Output Enabler backend server status ping to http://%1:%2/%3 reported service unavailable. Pinging again

Error code	1007
Error constant	OEE_BE_STATUS_DOWN
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter
Parameter 3	Backend server status url specified by the -cs status_url parameter

Probable cause

The Outbound Enabler's ping of the backend server indicates the server is unavailable. There will be no relaying while the ping to the backend server continues to return the same status. To resume relaying to the backend server, configure it to return a status of available.

1.10.2.10 OEE1008: Unable to find nor shut down an Outbound Enabler for server '%1' of farm '%2' using relay server '%3%4'

Error code	1008
Error constant	OEE_SHUTDOWN_NOT_FOUND
Parameter 1	Backend server name provided by the -id switch
Parameter 2	Backend farm name provided by the -f switch
Parameter 3	Relay server host provided by the -cs host parameter
Parameter 4	Relay server url suffix provided by the -cs url_suffix parameter

Probable cause

The Outbound Enabler was unable to find nor shut down an already-running Outbound Enabler for the given backend server, farm, and relay server. If the Outbound Enabler is running, make sure the backend server, farm, relay server, and url suffix are specified correctly

1.10.2.11 OEE1009: Unable to perform a network read from the Relay Server because of [MLC%1: %2]

Error code	1009
Error constant	OEE_NET_READ_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler was unable to read bytes sent across the network from the Relay Server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.12 OEE1010: The Outbound Enabler cannot handle the WWW-Authenticate header in the response because of [MLC%1: %2]

Error code	1010
Error constant	OEE_PARSE_AUTH_HDR_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler cannot handle the value of a WWW-Authenticate header. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.13 OEE1011: The Outbound Enabler cannot handle the Proxy-Authenticate header in the response because of [MLC%1: %2]

Error code	1011
Error constant	OEE_PARSE_PROXY_AUTH_HDR_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler cannot handle the value of the Proxy-Authenticate header. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.14 OEE1012: The Outbound Enabler cannot handle the Authentication-Info header in the response because of [MLC%1: %2]

Error code	1012
Error constant	OEE_PARSE_AUTH_INFO_HDR_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler cannot handle the value of the Authentication-Info header. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.15 OEE1013: The Outbound Enabler cannot handle the Proxy-Authentication-Info header in the response because of [MLC%1: %2]

Error code	1013
Error constant	OEE_PARSE_PROXY_AUTH_INFO_HDR_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler cannot handle the value of the Authentication-Info header. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.16 OEE1014: The length of an HTTP chunk length received from the Relay Server is too big

Error code	1014
Error constant	OEE_CHUNK_LEN_TOO_LONG

Probable cause

The Outbound Enabler received an unexpectedly large HTTP chunk length in the response from the Relay Server. A legitimate Relay Server should not cause this problem. Check the -cr switch and make sure a Relay Server is running there by using a Web browser to fetch the status page from the Relay Server. A typical status page URL looks like <http://MyHost/rs/server/rs.dll> for IIS and <http://MyHost/srv/iarelayserver> for Apache.

1.10.2.17 OEE1015: An HTTP chunk length received from the Relay Server is malformed

Error code	1015
Error constant	OEE_MALFORMED_CHUNK_LEN

Probable cause

The Outbound Enabler received a malformed chunk length in the response from the Relay Server. A legitimate Relay Server should not cause this problem. Check the -cr switch and make sure a Relay Server is running there by using a Web browser to fetch the status page from the Relay Server. A typical status page URL looks like <http://MyHost/rs/server/rs.dll> for IIS and <http://MyHost/srv/iarelayserver> for Apache.

1.10.2.18 OEE1016: An HTTP chunk received from the Relay Server is missing a trailing CRLF

Error code	1016
Error constant	OEE_MALFORMED_CHUNK_END

Probable cause

The Outbound Enabler found a malformed chunk in the response from the Relay Server. A legitimate Relay Server should not cause this problem. Check the -cr switch and make sure a Relay Server is running there by using a Web browser to fetch the status page from the Relay Server. A typical status page URL looks like `http://MyHost/rs/server/rs.dll` for IIS and `http://MyHost/srv/iarelayserver` for Apache.

1.10.2.19 OEE1017: The Outbound Enabler received an HTTP error status from the Relay Server:\r %1

Error code	1017
Error constant	OEE_HTTP_ERR_FROM_RS
Parameter 1	Response headers from the Relay Server

Probable cause

Look up the meaning of the HTTP status and message and act accordingly. Check the -cr switch and make sure a Relay Server is running there using the status page. Ensure that no network intermediaries are improperly modifying the HTTP traffic between the Outbound Enabler and the Relay Server.

1.10.2.20 OEE1018: Outbound Enabler connections to the Relay Server Web server require HTTP authentication, but no credentials were provided

Error code	1018
Error constant	OEE_NO_CREDENTIAL

Probable cause

The Web server hosting the Relay Server is requiring HTTP authentication. Ensure the correct host and port are specified in the -cr switch. Restart the Outbound Enabler with -cr `http_userid` and `http_password`.

1.10.2.21 OEE1019: An Outbound Enabler connection to the Relay Server failed HTTP authentication

Error code	1019
Error constant	OEE_AUTH_FAILED

Probable cause

The Web server hosting the Relay Server is requiring HTTP authentication. Ensure the correct host and port are specified in the -cr switch. Check the -cr http_userid and http_password parameters.

1.10.2.22 OEE1020: Outbound Enabler connections to the Relay Server Web server are going through a proxy requiring proxy HTTP authentication, but no credentials were provided

Error code	1020
Error constant	OEE_NO_PROXY_CREDENTIAL

Probable cause

An HTTP intermediary is requiring proxy HTTP authentication. Ensure the correct proxy_host and proxy_port are specified in the -cr switch. Restart the Outbound Enabler with -cr http_proxy_userid and http_proxy_password.

1.10.2.23 OEE1021: An Outbound Enabler connection to the Relay Server failed HTTP proxy authentication

Error code	1021
Error constant	OEE_PROXY_AUTH_FAILED

Probable cause

An HTTP intermediary is requiring proxy HTTP authentication. Ensure the correct proxy_host and proxy_port are specified in the -cr switch. Check the -cr http_proxy_userid and http_proxy_password parameters.

1.10.2.24 OEE1022: The Outbound Enabler received an unexpected HTTP error status:\r %1

Error code	1022
Error constant	OEE_UNEXPECTED_HTTP_ERR
Parameter 1	Response headers

Probable cause

The Relay Server or intermediary unexpectedly responded with an HTTP errors status. Look up the meaning of the HTTP status and message and act accordingly.

1.10.2.25 OEE1023: The Outbound Enabler is missing the -cr http_password parameter

Error code	1023
Error constant	OEE_MISSING_HTTP_PWD

Probable cause

The parameter is required when -cr http_userid is used. Either add the http_password parameter or remove the http_userid parameter.

1.10.2.26 OEE1024: The Outbound Enabler is missing the -cr http_proxy_password parameter

Error code	1024
------------	------

Probable cause

The parameter is required when `-cr http_proxy_userid` is used. Either add the `http_proxy_password` parameter or remove the `http_proxy_userid` parameter.

1.10.2.27 OEE1025: The Outbound Enabler is missing the `-cr http_userid` parameter

Error code

1025

Error constant

OEE_MISSING_HTTP_UID

Probable cause

The parameter is required when `-cr http_password` is used. Either add the `http_userid` parameter or remove the `http_password` parameter.

1.10.2.28 OEE1026: The Outbound Enabler is missing the `-cr http_proxy_userid` parameter

Error code

1026

Error constant

OEE_MISSING_HTTP_PROXY_UID

Probable cause

The parameter is required when `-cr http_proxy_password` is used. Either add the `http_proxy_userid` parameter or remove the `http_proxy_password` parameter.

1.10.2.29 OEE1027: The Outbound Enabler was unable to write an HTTP header to the Relay Server because of [MLC%1: %2]

Error code	1027
Error constant	OEE_NET_WRITE_HDR_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler was unable to write an HTTP header to the Relay Server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.30 OEE1028: The Outbound Enabler was unable to write an HTTP body to the Relay Server because of [MLC%1: %2]

Error code	1028
Error constant	OEE_NET_WRITE_PKT_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler was unable to write an HTTP body to the Relay Server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.31 OEE1029: The Outbound Enabler received an HTTP cookie or header from a client indicating the client cached it from a previous Relay Server configuration. The unexpected Relay Server index is: %1

Error code	1029
Error constant	OEE_RS_IDX_NOT_FOUND
Parameter 1	Zero-based index of the Relay Server from the old Relay Server configuration file

Probable cause

The Outbound Enabler has determined that client has likely cached an HTTP cookie or header that is no longer valid after the Relay Server farm has reduced the number of Relay Servers. The Relay Server will automatically instruct the client software to expire the cached value upon receiving this error. There is no required user action for this error. It is only mentioned because the extra exchange to expire the cookie is inefficient. To prevent this error, disable cookie and/or header caching on the client.

1.10.2.32 OEE1030: The Outbound Enabler was unable to connect to the Relay Server using '%1' because of [MLC%2: %3]. Retrying

Error code	1030
Error constant	OEE_NET_CONNECT_FAILED
Parameter 1	Connect parameters
Parameter 2	MobiLink communication error code
Parameter 3	MobiLink communication error message

Probable cause

The Outbound Enabler could not connect to the Relay Server for the given reason, and will retry. Make sure the -cr switch correctly specifies the target Relay Server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.33 OEE1031: The Outbound Enabler access was denied by the Relay Server

Error code	1031
Error constant	OEE_RS_ERR_AUTH

Probable cause

Make sure the -f switch matches the backend farm id in the Relay Server configuration and the backend farm is enabled and the backend_security is compatible with the -cr https parameter. Make sure the -id switch matches the backend server id in the backend server is enabled. Make sure the -t switch matches the backend server token in the Relay Server configuration. Make sure the MAC address matches the backend server MAC in the Relay Server configuration. Also make sure the same authentication information is not shared by another instance of the Outbound Enabler.

1.10.2.34 OEE1032: Retry due to issue with the Relay Server

Error code	1032
Error constant	OEE_RS_ERR_SERVER_ERROR

Probable cause

The Relay Server is having internal issue and has notified the Outbound Enabler to reconnect both of the up and down channels. If this error persist, contact the Relay Server administrator to perform investigation on the Relay Server.

1.10.2.35 OEE1033: The Outbound Enabler is unable to connect to the backend server at %1:%2 to ping it. Pinging again

Error code	1033
Error constant	OEE_BE_STATUS_PING_CONNECT_FAILED
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter

Probable cause

Make sure the -cs host and port parameters are correct and the backend service is started up successfully.

1.10.2.36 OEE1034: Communication error with backend server: '%1'

Error code	1034
Error constant	OEE_BE_IO_FAILED
Parameter 1	Error message from the MobiLink server I/O subsystem

Probable cause

This error message only applies to the Outbound Enabler integrated with MobiLink server. The subsystem error code can be looked up in the MobiLink server error message documentation.

1.10.2.37 OEE1035: Invalid tls_type %1 given to the Outbound Enabler's -cs switch. Only RSA is supported

Error code	1035
Error constant	OEE_SACI_INVALID_TLS_TYPE
Parameter 1	The -cs tls_type parameter

Probable cause

The -cs tls_type parameter only supports RSA.

1.10.2.38 OEE1036: A network connection was closed by the Relay Server or an intermediary while the Outbound Enabler was reading from it

Error code	1036
Error constant	OEE_NET_READ_CLOSED

Probable cause

Make sure the connection timeout of the Web server is sufficient. Ensure that no intermediary has a timeout that is shorter than the Web server timeout.

1.10.2.39 OEE1037: The Outbound Enabler -cr switch is missing the %1 parameter

Error code	1037
Error constant	OEE_MISSING_RS_CONNECT_PARAM
Parameter 1	Name of the parameter

Probable cause

The given parameter is required and there is no default value. See the Outbound Enabler's usage by invoking rsoe without any arguments, or consult the documentation.

1.10.2.40 OEE1038: Invalid Outbound Enabler command line near '%1'

Error code	1038
Error constant	OEE_BAD_SWITCH
Parameter 1	The problematic switch

Probable cause

The Outbound Enabler cannot start up due an invalid command line. See the Outbound Enabler's usage by invoking rsoe without any arguments, or consult the documentation.

1.10.2.41 OEE1039: The Outbound Enabler connection to the Relay Server using '%1' failed because of [MLC%2: %3]

Error code	1039
Error constant	OEE_INIT_RS_COMMUNICATION_FAILED
Parameter 1	Communication parameters
Parameter 2	MobiLink communication error code
Parameter 3	MobiLink communication error message

Probable cause

The Outbound Enabler connection to the Relay Server failed for the given reason. Make sure the -cr switch correctly specifies the target Relay Server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.42 OEE1040: The Outbound Enabler was unable to initialize secure communications to the backend server because of [MLC%1: %2]

Error code	1040
Error constant	OEE_INIT_SECURED_BACKEND_COMMUNICATION_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler encountered an error initializing secure communications to the backend server. Ensure that your -cs switch is specified correctly. Further information regarding the probable cause and remedy of the

error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.43 OEE1041: The Outbound Enabler -cr switch does not specify a valid Relay Server. The HTTP response from the server has the following headers: %1

Error code	1041
Error constant	OEE_NON_RS
Parameter 1	HTTP response headers

Probable cause

Make sure the host and port parameters in the -cr switch are correct.

1.10.2.44 OEE1042: The Relay Server needs to be upgraded in order to be compatible with this Outbound Enabler

Error code	1042
Error constant	OEE_RS_TOO_OLD

Probable cause

The Relay Server versions does not support protocol version negotiation. Upgrade the Relay Server.

1.10.2.45 OEE1043: The Relay Server at host '%1' lacks a %2 entry in the Relay Server configuration

Error code	1043
Error constant	OEE_MISSING_RS_PORT
Parameter 1	The Relay Server host name

Parameter 2

The missing Relay Server configuration setting implied by the Outbound Enabler's -cr switch

Probable cause

The https parameter of the Outbound Enabler's -cr switch must correspond with the Relay Server configuration. Either add the given missing setting to the Relay Server configuration, or change the Outbound Enabler's -cr switch to correspond to the Relay Server configuration.

1.10.2.46 OEE1044: The Outbound Enabler was unable to determine the MAC addresses of this machine

Error code	1044
Error constant	OEE_GET_MAC_FAILED

Probable cause

Make sure the network interfaces are enabled.

1.10.2.47 OEE1045: System error [SYS%1: %2] while %3 with the backend server for sidx=%4 socket=%5 sfp=%6

Error code	1045
Error constant	OEE_BACKEND_IO_SYS_ERROR
Parameter 1	System error code
Parameter 2	System error message
Parameter 3	The Outbound Enabler context where the I/O error occurred (for technical support)
Parameter 4	Session index (for technical support)
Parameter 5	Socket handle (for technical support)
Parameter 6	Session fingerprint (for technical support)

Probable cause

Use the system error information to resolved the issue. Contact your network administrator or technical support if you need assistance.

1.10.2.48 OEE1046: Connecting to backend server at %1:%2 failed because of [MLC%3: %4]

Error code	1046
Error constant	OEE_BACKEND_CONNECT_TEST_FAILED
Parameter 1	Backend server host specified by the -cs host parameter
Parameter 2	Backend server port specified by the -cs port parameter
Parameter 3	MobiLink communication error code
Parameter 4	MobiLink communication error message

Probable cause

Make sure the backend server is running and the Outbound Enabler -cs port parameter is specified correctly if the backend server is listening on port other than 80 for HTTP. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.49 OEE1047: Error parsing the value of the Outbound Enabler -cs %1 parameter

Error code	1047
Error constant	OEE_PARSE_RS_CONNECT_PARAM_FAILED
Parameter 1	Connection parameter name

Probable cause

Make sure the specified value match the type of the parameter.

1.10.2.50 OEE1048: The communication between the Outbound Enabler and the backend server failed with [MLC%1: %2] while %3. sidx=%4 socket=%5 sfp=%6

Error code	1048
Error constant	OEE_BACKEND_IO_ERROR
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message
Parameter 3	The context where the I/O error occurs (for technical support)
Parameter 4	Session index (for technical support)
Parameter 5	Socket handle (for technical support)
Parameter 6	Session fingerprint (for technical support)

Probable cause

Make sure the backend server is running and the Outbound Enabler -cs port parameter is specified correctly if the backend server is listening on port other than 80 for HTTP. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.51 OEE1049: The request URL is too long. Request with sidx=%1 sfp=%2 is aborted

Error code	1049
Error constant	OEE_CANT_INJECT_AFQ_HDR
Parameter 1	Session index (for technical support)
Parameter 2	Session fingerprint (for technical support)

Probable cause

The Outbound Enabler cannot handle request header with first line longer than 64k. The problem might be workaround by reducing the size of the URL including query strings.

1.10.2.52 OEE1050: Failed to lookup a session that has just started with ridx=%1 snum=%2 sfp=%3 on a %4 packet

Error code	1050
Error constant	OEE_SESSION_NOT_FOUND
Parameter 1	Request index (for technical support)
Parameter 2	Session number (for technical support)
Parameter 3	Session fingerprint (for technical support)
Parameter 4	Packet name (for technical support)

Probable cause

The session might have been garbage collected due to timeout. The Relay Server will not assign a cookie to this failing session. This is an indication of slowness in delivering the request from the client to the Outbound Enabler. If the issue persists, report the issue to Relay Server administrators for further tracing.

1.10.2.53 OEE1051: The Outbound Enabler was unable to access the session with ridx=%1 sidx=%2 snum=%3 sfp=%4 on a %5 packet due to %6

Error code	1051
Error constant	OEE_SESSION_ACCESS_FAILED
Parameter 1	Request index (for technical support)
Parameter 2	Session index (for technical support)
Parameter 3	Session number (for technical support)
Parameter 4	Session fingerprint (for technical support)
Parameter 5	Packet name (for technical support)
Parameter 6	Reason of the failure (for technical support)

Probable cause

The session might have been garbage collected due to timeout or the client has cached an old cookie. The Relay Server will inform the client software to expire the cookie and the client should restart from a new session.

1.10.2.54 OEE1052: The Outbound Enabler was unable to write a %1 packet to the Relay Server because of [MCL%2: %3]

Error code	1052
Error constant	OEE_NOTIFICATION_PACKET_FAILED
Parameter 1	Packet name (for technical support)
Parameter 2	MobiLink communication error code
Parameter 3	MobiLink communication error message

Probable cause

There was a communication error between the Outbound Enabler and the Relay Server. The Outbound Enabler will automatically attempt to recover both the up and down channels to restore communication with the Relay Server. Abrupt service interruption is expected during this recovery period. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.55 OEE1053: The Outbound Enabler was unable to flush a packet to the Relay Server because of [MLC %1: %2]

Error code	1053
Error constant	OEE_NET_FLUSH_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

There was a communication error between the Outbound Enabler and the Relay Server. The Outbound Enabler will automatically attempt to recover both the up and down channels to restore communication with the Relay Server. Abrupt service interruption is expected during this recovery period. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.56 OEE1054: The Outbound Enabler was unable to write a %5 packet with ridx=%1 sidx=%2 snum=%3 sfp=%4 failed because of [MLC%6: %7]

Error code	1054
Error constant	OEE_NET_WRITE_RESPONSE_FAILED
Parameter 1	Request index (for technical support)
Parameter 2	Session index (for technical support)
Parameter 3	Session number (for technical support)
Parameter 4	Session fingerprint (for technical support)
Parameter 5	Packet name (for technical support)
Parameter 6	MobiLink communication error code
Parameter 7	MobiLink communication system error message

Probable cause

There was a communication error when the Outbound Enabler attempted to write a packet to the Relay Server. The Outbound Enabler will automatically attempt to recover both the up and down channels to restore communication with the Relay Server. Abrupt service interruption is expected during this recovery period. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.57 OEE1055: The Outbound Enabler was unable to create a session error packet with ridx=%1 sidx=%2 snum=%3 sfp=%4 err=%5 for Relay Server index %6 as it cannot be found

Error code	1055
Error constant	OEE_SESSION_ERROR_RS_IDX_NOT_FOUND
Parameter 1	Request index (for technical support)
Parameter 2	Session index (for technical support)
Parameter 3	Session number (for technical support)
Parameter 4	Session fingerprint (for technical support)
Parameter 5	Outbound Enabler error code

Parameter 6

Zero-based index of the Relay Server from the old Relay Server configuration file

Probable cause

The client might have cached a cookie that is no longer valid after the Relay Server farm has shrunk. The Relay Server will instruct the client software to expire the cookie cache upon receiving this error.

1.10.2.58 OEE1056: Failed to report shutdown to the Relay Server

Error code	1056
Error constant	OEE_REPORT_SHUTDOWN_FAILED

Probable cause

Failed to make a new connection or failed to send a notification to the Relay Server.

1.10.2.59 OEE1057: Failed connecting to backend server because of [MLC%1: %2]

Error code	1057
Error constant	OEE_BACKEND_CONNECT_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

Make sure the backend server is running and the Outbound Enabler -cs port parameter is specified correctly if the backend server is listening on port other than 80 for HTTP. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.60 OEE1058: Failed writing to the backend server because of [MLC%1: %2]

Error code	1058
Error constant	OEE_WRITE_BACKEND_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

There was a communication error when the Outbound Enabler attempted to write to the backend server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.61 OEE1059: Failed reading from the backend server because of [MLC%1: %2]

Error code	1059
Error constant	OEE_READ_BACKEND_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

There was a communication error when the Outbound Enabler attempted to read from the backend server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.62 OEE1060: Lost idle backend connection sooner than max_junction_idle_sec expires. Configure the backend server or the Relay Server configuration to agree on the idle timeout

Error code	1060
Error constant	OEE_LOST_BACKEND_CONNECTION

Probable cause

The Relay Server will expire idle junctions containing the backend connection in max_junction_idle_sec, which is specified as a backend server property in the Relay Server configuration file. Configuring the backend server to increase timeout tolerance or reduce max_junction_idle_sec in the Relay Server configuration may resolve this problem.

1.10.2.63 OEE1061: Failed writing to the Relay Server because of [MLC%1: %2]

Error code	1061
Error constant	OEE_WRITE_RS_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

There was a communication error when the Outbound Enabler attempted to write to the Relay Server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.64 OEE1062: Failed reading from the Relay Server because of [MLC%1: %2]

Error code	1062
Error constant	OEE_READ_RS_FAILED

Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

There was a communication error when the Outbound Enabler attempted to read from the Relay Server. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.65 OEE1603: Not compatible with the Relay Server due to unknown protocol version %1

Error code	1603
Error constant	OEE_PROTOCOL_VER_UNKNOWN
Parameter 1	Protocol version of the Relay Server

Probable cause

This Outbound Enabler is not compatible with the targeted Relay Server.

1.10.2.66 OEE1604: The Relay Server response with %1 instead of %2

Error code	1604
Error constant	OEE_UNEXPECTED_RS_RESPONSE_STATUS
Parameter 1	HTTP response status code from the Relay Server
Parameter 2	Expected HTTP response status code from the Relay Server

Probable cause

Report this error to the Relay Server administrator.

1.10.2.67 OEE1605: The response does not originate from the Relay Server server extension

Error code	1605
Error constant	OEE_NOT_RS

Probable cause

Make sure the value of the host, port, and url_suffix parameters in the -cr option of the Outbound Enabler are correct. If there is intermediary between the Outbound Enabler and the Relay Server, then make sure the destination targets the server extension of the Relay Server.

1.10.2.68 OEF10000: Failed to initialize socket library [MLC %1: %2]

Error code	10000
Error constant	OEF_SOCKET_LIB_INIT_FAILED
Parameter 1	MobiLink communication error code
Parameter 2	MobiLink communication error message

Probable cause

The Outbound Enabler was unable to initialize the socket (network) library. Further information regarding the probable cause and remedy of the error can be found in the "MobiLink Communication error messages" section of the SQL Anywhere documentation.

1.10.2.69 OEF10001: Out of memory

Error code	10001
Error constant	OEF_OUT_OF_MEMORY

Probable cause

The Outbound Enabler was unable to allocate enough memory to function. Consider increasing the amount of RAM, or increasing the swap file size, or reducing the number of applications running on the system.

1.10.2.70 OEF10002: The Outbound Enabler was unable to create shared memory directory for communicating shutdown

Error code	10002
Error constant	OEF_SHM_INIT_FAILED

Probable cause

In order to be able to shutdown the Outbound Enabler using the "rsoe -s" command locally, the Outbound Enabler is creating a directory on disk for holding a piece of shared memory to communicate the shutdown signal. However the create operation failed. Make sure to use an account with sufficient permission for running the Outbound Enabler.

1.10.2.71 OEF10003: The Outbound Enabler was unable to create shared memory for communicating shutdown

Error code	10003
Error constant	OEF_SHM_CREATE_FAILED

Probable cause

In order to be able to shutdown the Outbound Enabler using the "rsoe -s" command locally, the Outbound Enabler is creating a small memory mapped file for communicating the shutdown signal. However the creation of the memory mapped file failed. Make sure to use an account with sufficient permission for running the Outbound Enabler.

1.10.2.72 OEF10004: The 'rsoe -s' command failed shutting down Outbound Enabler for server '%1' of farm '%2' using relay server '%3%4'

Error code	10004
Error constant	OEF_SHUTDOWN_FAILED
Parameter 1	Backend server name provided by the -id switch
Parameter 2	Backend farm name provided by the -f switch
Parameter 3	Relay server host provided by the -cs host parameter
Parameter 4	Relay server url suffix provided by the -cs url_suffix parameter

Probable cause

The Outbound Enabler is not responding. Try terminating it with an OS utility.

1.10.2.73 OEF10005: Unable to load the Outbound Enabler support library: %1 -- %2

Error code	10005
Error constant	OEF_LOAD_DLL_FAILED
Parameter 1	Outbound Enabler support library name
Parameter 2	Reason of the failure (for technical support)

Probable cause

The support library needs to be loaded on startup but the operation failed. Use reason of the failure to resolve the issue.

1.10.2.74 OEF10006: The Outbound Enabler was unable to load required functions from the '%1' library

Error code	10006
------------	-------

Error constant	OEF_LOAD_DLL_FUNC_FAILED
Parameter 1	RSOE support library name

Probable cause

Make sure the version of the support library matches the Outbound Enabler.

1.10.2.75 OEF10007: Failed to initialize an Outbound Enabler support library '%1'

Error code	10007
Error constant	OEF_DLL_INIT_FAILED
Parameter 1	Outbound Enabler support library name

Probable cause

This can be caused by a problem with your command line or the Outbound Enabler could have run out of memory. Contact technical support for assistance if the issue persists.

1.10.2.76 OEF10008: Protocol error while reading %1 packet

Error code	10008
Error constant	OEF_INVALID_PACKET
Parameter 1	The name of the malformed packet

Probable cause

A legitimate Relay Server should not cause this problem. Check the -cr switch and make sure a Relay Server is running there by using a Web browser to fetch the status page from the Relay Server. A typical status page URL looks like <http://MyHost/rs/server/rs.dll> for IIS and <http://MyHost/srv/iarelayserver> for Apache.

1.10.2.77 OEF10009: Reduced to lowest supported protocol version but the Relay Server is still not compatible

Error code	10009
Error constant	OEF_LOWEST_PROTOCOL

Probable cause

The version of the Relay Server is too old and is thus incompatible. The Outbound Enabler has iteratively attempted to lower the protocol version but exhausted all supported versions without success. A Relay Server upgrade is required.

1.10.2.78 OEF10010: Invalid opcode received from the Relay Server

Error code	10010
Error constant	OEF_INVALID_OPCODE

Probable cause

A legitimate Relay Server should not cause this problem. Check the -cr switch and make sure a Relay Server is running there by using a Web browser to fetch the status page from the Relay Server. A typical status page URL looks like <http://MyHost/rs/server/rs.dll> for IIS and <http://MyHost/srv/iarelayserver> for Apache.

1.10.2.79 OEF10011: The Outbound Enabler was unable to load the %1 encryption library because of [%2]. Make it is installed properly

Error code	10011
Error constant	OEF_SACI_LOAD_FAILED
Parameter 1	The encryption library file name
Parameter 2	Reason of the failure

Probable cause

Make sure the library is installed within the search path and make use of the reason to resolve the issue.

1.10.2.80 OEF10012: The Outbound Enabler was unable to load function %1 from encryption library %2

Error code	10012
Error constant	OEF_SACI_LOAD_FUNC_FAILED
Parameter 1	The name of the function to be loaded
Parameter 2	The encryption library expected to contain the given function

Probable cause

Make sure the given encryption library has the same version as the Outbound Enabler.

1.10.2.81 OEF10013: Encryption library version mismatch. Found version %1.%2 with implementation id %3

Error code	10013
Error constant	OEF_SACI_VER_MISMATCH
Parameter 1	The major version of the encryption library
Parameter 2	The minor version of the encryption library
Parameter 3	The implementation id of the encryption library

Probable cause

Make sure the encryption library has the same version as the Outbound Enabler.

1.10.2.82 OEF10014: Internal error: %1

Error code	10014
Error constant	OEF_INTERNAL_ERROR
Parameter 1	Internal error description

Probable cause

Restart the Outbound Enabler. Contact technical support for assistance if the issue persists.

1.10.2.83 OEF10015: Internal error, RSOE configuration file location not specified. Contact technical support for assistance if the issue persists

Error code	10015
Error constant	OEF_OE_CONFIG_FILE_NOT_SPECIFIED

Probable cause

The RSOE configuration file was not specified. Contact Technical Support for assistance if the issue persists.

1.10.2.84 OEF10016: An error occurred while processing RSOE configuration parameters. Please make sure the RSOE configuration file exists and configuration parameters are specified correctly

Error code	10016
Error constant	OEF_ERR_PROCESSING_OE_CONFIG_PARAMS

Probable cause

The RSOE was unable to process the configuration parameters. Make sure the RSOE configuration file actually exists and that the configuration parameters are specified correctly.

1.10.2.85 OEF10017: Protocol error

Error code	10017
Error constant	OEF_PROTOCOL_ERROR

Probable cause

A legitimate Relay Server should not cause this problem.

1.11 Outbound Enabler Warning Messages

The Outbound Enabler messages are written to the Outbound Enabler message log.

Each message has a numeric code. Many of the messages contain the characters %1, %2, and so on. These characters are replaced by the parameters to the message.

In this section:

[Outbound Enabler Warning Messages Sorted by Error Code \[page 1438\]](#)

[Outbound Enabler Warning Messages Listed by Message Text \[page 1439\]](#)

Related Information

[Outbound Enabler Error Messages \[page 1392\]](#)

1.11.1 Outbound Enabler Warning Messages Sorted by Error Code

Error code	Message text
100	OEW0: Cannot disconnect backend session due to rid=%1 snum=%2 sfp=%3 not being found [page 1439]
101	OEW1: The proxy disallows passthrough to destination RS port. Reconfiguring the proxy to allow RS port as destination for CONNECT request is recommended [page 1439]

1.11.2 Outbound Enabler Warning Messages Listed by Message Text

In this section:

[OEWO: Cannot disconnect backend session due to rid=%1 snum=%2 sfp=%3 not being found \[page 1439\]](#)

[OEW1: The proxy disallows passthrough to destination RS port. Reconfiguring the proxy to allow RS port as destination for CONNECT request is recommended \[page 1439\]](#)

1.11.2.1 OEWO: Cannot disconnect backend session due to rid=%1 snum=%2 sfp=%3 not being found

Error code	100
Error constant	OEW_CANT_DISCONNECT_BE_NOT_FOUND
Parameter 1	Request index
Parameter 2	Session number
Parameter 3	Session fingerprint

Probable cause

The Relay Server has notified the outbound enabler to disconnect a backend connection before the session index was established by the first response in the session. However, the outbound enabler cannot lookup the session using other pieces of internal information reported in this warning.

1.11.2.2 OEW1: The proxy disallows passthrough to destination RS port. Reconfiguring the proxy to allow RS port as destination for CONNECT request is recommended

Error code	101
Error constant	OEW_PROXY_FORBID_PASSTHROUGH

Probable cause

If it is an Apache proxy, see `mod_proxy` documentation of the `AllowCONNECT` directive.

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon : You are leaving the documentation for that particular SAP product or service and are entering a SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

© 2022 SAP SE or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.

Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.

Please see <https://www.sap.com/about/legal/trademark.html> for additional trademark information and notices.